
Galaxy Code Documentation

Release

Galaxy Team

June 22, 2015

1	Contents	3
1.1	Galaxy API Documentation	3
1.2	lib	42
1.3	Releases	369
2	Indices and tables	377
	Python Module Index	379

Galaxy is an open, web-based platform for accessible, reproducible, and transparent computational biomedical research.

- *Accessible*: Users without programming experience can easily specify parameters and run tools and workflows.
- *Reproducible*: Galaxy captures information so that any user can repeat and understand a complete computational analysis.
- *Transparent*: Users share and publish analyses via the web and create Pages, interactive, web-based documents that describe a complete analysis.

Two copies of the Galaxy code documentation are published by the Galaxy Project

- **Galaxy-Dist**: This describes the code in the [most recent official release](#) of Galaxy.
- **Galaxy-Central**: Describes the [current code in the development branch](#) of Galaxy. This is the latest checkin, bleeding edge version of the code. The documentation should never be more than an hour behind the code.

Both copies are hosted at [ReadTheDocs](#), a publicly supported web site for hosting project documentation.

If you have your own copy of the Galaxy source code, you can also generate your own version of this documentation:

```
$ cd doc
$ make html
```

The generated documentation will be in `doc/build/html/` and can be viewed with a web browser. Note that you will need to install Sphinx and a fair number of module dependencies before this will produce output.

For more on the Galaxy Project, please visit the [project home page](#).

1.1 Galaxy API Documentation

1.1.1 Background

In addition to being accessible through a web interface, Galaxy can also be accessed programmatically, through shell scripts and other programs. The web interface is appropriate for things like exploratory analysis, visualization, construction of workflows, and rerunning workflows on new datasets.

The web interface is less suitable for things like

- Connecting a Galaxy instance directly to your sequencer and running workflows whenever data is ready.
- Running a workflow against multiple datasets (which can be done with the web interface, but is tedious).
- When the analysis involves complex control, such as looping and branching.

The Galaxy API addresses these and other situations by exposing Galaxy internals through an additional interface, known as an Application Programming Interface, or API.

1.1.2 Quickstart

Log in as your user, navigate to the API Keys page in the User menu, and generate a new API key. Make a note of the API key, and then pull up a terminal. Now we'll use the `display.py` script in your `galaxy/scripts/api` directory for a short example:

```
% ./display.py my_key http://localhost:4096/api/histories
Collection Members
-----
#1: /api/histories/8c49be448cfe29bc
    name: Unnamed history
    id: 8c49be448cfe29bc
#2: /api/histories/33b43b4e7093c91f
    name: output test
    id: 33b43b4e7093c91f
```

The result is a Collection of the histories of the user specified by the API key (you). To look at the details of a particular history, say #1 above, do the following:

```
% ./display.py my_key http://localhost:4096/api/histories/8c49be448cfe29bc
Member Information
-----
state_details: {'ok': 1, 'failed_metadata': 0, 'upload': 0, 'discarded': 0, 'running': 0, 'setting_m
```

```
state: ok
contents_url: /api/histories/8c49be448cfe29bc/contents
id: 8c49be448cfe29bc
name: Unnamed history
```

This gives detailed information about the specific member in question, in this case the History. To view history contents, do the following:

```
% ./display.py my_key http://localhost:4096/api/histories/8c49be448cfe29bc/contents
Collection Members
-----
#1: /api/histories/8c49be448cfe29bc/contents/6f91353f3eb0fa4a
    name: Pasted Entry
    type: file
    id: 6f91353f3eb0fa4a
```

What we have here is another Collection of items containing all of the datasets in this particular history. Finally, to view details of a particular dataset in this collection, execute the following:

```
% ./display.py my_key http://localhost:4096/api/histories/8c49be448cfe29bc/contents/6f91353f3eb0fa4a
Member Information
-----
misc_blurb: 1 line
name: Pasted Entry
data_type: txt
deleted: False
file_name: /Users/yoplait/work/galaxy-stock/database/files/000/dataset_82.dat
state: ok
download_url: /datasets/6f91353f3eb0fa4a/display?to_ext=txt
visible: True
genome_build: ?
model_class: HistoryDatasetAssociation
file_size: 17
metadata_data_lines: 1
id: 6f91353f3eb0fa4a
misc_info: uploaded txt file
metadata_dbkey: ?
```

And now you've successfully used the API to request and select a history, browse the contents of that history, and then look at detailed information about a particular dataset.

For a more comprehensive Data Library example, set the following option in your galaxy.ini as well, and restart galaxy again:

```
admin_users = you@example.org
library_import_dir = /path/to/some/directory
```

In the directory you specified for 'library_import_dir', create some subdirectories, and put (or symlink) files to import into Galaxy into those subdirectories.

In Galaxy, create an account that matches the address you put in 'admin_users', then browse to that user's preferences and generate a new API Key. Copy the key to your clipboard and then use these scripts:

```
% ./display.py my_key http://localhost:4096/api/libraries
Collection Members
-----

0 elements in collection

% ./library_create_library.py my_key http://localhost:4096/api/libraries api_test 'API Test Library'
```



```

Response
-----
/api/libraries/f3f73e481f432006
  name: api_test
  id: f3f73e481f432006

% ./display.py my_key http://localhost:4096/api/libraries
Collection Members
-----
/api/libraries/f3f73e481f432006
  name: api_test
  id: f3f73e481f432006

% ./display.py my_key http://localhost:4096/api/libraries/f3f73e481f432006
Member Information
-----
synopsis: None
contents_url: /api/libraries/f3f73e481f432006/contents
description: API Test Library
name: api_test

% ./display.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents
Collection Members
-----
/api/libraries/f3f73e481f432006/contents/28202595c0d2591f61ddda595d2c3670
  name: /
  type: folder
  id: 28202595c0d2591f61ddda595d2c3670

% ./library_create_folder.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents 28202595c0d2591f61ddda595d2c3670
Response
-----
/api/libraries/f3f73e481f432006/contents/28202595c0d2591fa4f9089d2303fd89
  name: api_test_folder1
  id: 28202595c0d2591fa4f9089d2303fd89

% ./library_upload_from_import_dir.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents 28202595c0d2591fa4f9089d2303fd89
Response
-----
/api/libraries/f3f73e481f432006/contents/e9ef7fdb2db87d7b
  name: 2.bed
  id: e9ef7fdb2db87d7b
/api/libraries/f3f73e481f432006/contents/3b7f6a31f80a5018
  name: 3.bed
  id: 3b7f6a31f80a5018

% ./display.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents
Collection Members
-----
/api/libraries/f3f73e481f432006/contents/28202595c0d2591f61ddda595d2c3670
  name: /
  type: folder
  id: 28202595c0d2591f61ddda595d2c3670
/api/libraries/f3f73e481f432006/contents/28202595c0d2591fa4f9089d2303fd89
  name: /api_test_folder1
  type: folder
  id: 28202595c0d2591fa4f9089d2303fd89
/api/libraries/f3f73e481f432006/contents/e9ef7fdb2db87d7b

```

```
name: /api_test_folder1/2.bed
type: file
id: e9ef7fdb2db87d7b
/api/libraries/f3f73e481f432006/contents/3b7f6a31f80a5018
name: /api_test_folder1/3.bed
type: file
id: 3b7f6a31f80a5018

% ./display.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents/e9ef7fdb2db87d7b
Member Information
-----
misc_blurb: 68 regions
metadata_endCol: 3
data_type: bed
metadata_columns: 6
metadata_nameCol: 4
uploaded_by: nate@...
metadata_strandCol: 6
name: 2.bed
genome_build: hg19
metadata_comment_lines: None
metadata_startCol: 2
metadata_chromCol: 1
file_size: 4272
metadata_data_lines: 68
message:
metadata_dbkey: hg19
misc_info: uploaded bed file
date_uploaded: 2010-06-22T17:01:51.266119
metadata_column_types: str, int, int, str, int, str
```

Other parameters are valid when uploading, they are the same parameters as are used in the web form, like 'link_data_only' and etc.

The request and response format should be considered alpha and are subject to change.

1.1.3 API Design Guidelines

The following section outlines guidelines related to extending and/or modifying the Galaxy API. The Galaxy API has grown in an ad-hoc fashion over time by many contributors and so clients SHOULD NOT expect the API will conform to these guidelines - but developers contributing to the Galaxy API SHOULD follow these guidelines.

- API functionality should include docstring documentation for consumption by readthedocs.org.
- Developers should familiarize themselves with the HTTP status code definitions <http://www.w3.org/Protocols/rfc2616/rfc2616-sec10.html>. The API responses should properly set the status code according to the result - in particular 2XX responses should be used for successful requests, 4XX for various kinds of client errors, and 5XX for the errors on the server side.
- If there is an error processing some part of request (one item in a list for instance), the status code should be set to reflect the error and the partial result may or may not be returned depending on the controller - this behavior should be documented.
- API methods should throw a finite number of exceptions (defined in [exceptions Package](#)) and these should subclass *MessageException* and not paste/wsgi HTTP exceptions. When possible, the framework itself should be responsible catching these exceptions, setting the status code, and building an error response.

- Error responses should not consist of plain text strings - they should be dictionaries describing the error and containing the following:

```
{
  "status_code": 400,
  "err_code": 400007,
  "err_msg": "Request contained invalid parameter, action could not be completed.",
  "type": "error",
  "extra_error_info": "Extra information."
}
```

Various error conditions (once a format has been chosen and framework to enforce it in place) should be spelled out in this document.

- Backward compatibility is important and should be maintained when possible. If changing behavior in a non-backward compatible way please ensure one of the following holds - there is a strong reason to believe no consumers depend on a behavior, the behavior is effectively broken, or the API method being modified has not been part of a tagged dist release.

The following bullet points represent good practices more than guidelines, please consider them when modifying the API.

- Functionality should not be copied and pasted between controllers - consider refactoring functionality into associated classes or short of that into Mixins (http://en.wikipedia.org/wiki/Composition_over_inheritance) or into Managers ([managers Package](#)).
- API additions are more permanent changes to Galaxy than many other potential changes and so a second opinion on API changes should be sought. (Consider a pull request!)
- New API functionality should include functional tests. These functional tests should be implemented in Python and placed in *test/functional/api*. (Once such a framework is in place - it is not right now).
- Changes to reflect modifications to the API should be pushed upstream to the BioBlend project if possible.

Longer term goals/notes.

- It would be advantageous to have a clearer separation of anonymous and admin handling functionality.
- If at some point in the future, functionality needs to be added that breaks backward compatibility in a significant way to a component used by the community - a “dev” variant of the API will be established and the community should be alerted and given a timeframe for when the old behavior will be replaced with the new behavior.
- Consistent standards for range-based requests, batch requests, filtered requests, etc... should be established and documented here.

1.1.4 API Controllers

Galaxy offers the following API controllers:

annotations Module

API operations on annotations.

```
class galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController(app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesStore
           galaxy.model.item_attrs.UsesAnnotations

    create (trans, *args, **kwargs)
    delete (trans, *args, **kwargs)
```

```
    index (trans, *args, **kwargs)
    undelele (trans, *args, **kwargs)

class galaxy.webapps.galaxy.api.annotations.HistoryAnnotationsController (app)
    Bases: galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController

    controller_name = 'history_annotations'
    tagged_item_id = 'history_id'

class galaxy.webapps.galaxy.api.annotations.HistoryContentAnnotationsController (app)
    Bases: galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController

    controller_name = 'history_content_annotations'
    tagged_item_id = 'history_content_id'

class galaxy.webapps.galaxy.api.annotations.WorkflowAnnotationsController (app)
    Bases: galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController

    controller_name = 'workflow_annotations'
    tagged_item_id = 'workflow_id'
```

authenticate Module

API key retrieval through BaseAuth Sample usage:

```
curl -user zipzap@foo.com:password http://localhost:8080/api/authenticate/baseauth
```

Returns:

```
{ "api_key": "baa4d6e3a156d3033f05736255f195f9"
}
```

```
class galaxy.webapps.galaxy.api.authenticate.AuthenticationController (app)
    Bases: galaxy.web.base.controller.BaseAPIController

    get_api_key (trans, *args, **kwargs)
        def get_api_key( self, trans, **kwd ) * GET /api/authenticate/baseauth
            returns an API key for authenticated user based on BaseAuth headers

            Returns api_key in json format
            Return type dict
            Raises ObjectNotFound, HTTPBadRequest
```

configuration Module

API operations allowing clients to determine Galaxy instance's capabilities and configuration settings.

```
class galaxy.webapps.galaxy.api.configuration.ConfigurationController (app)
    Bases: galaxy.web.base.controller.BaseAPIController

    dynamic_tool_confs (trans, *args, **kwargs)
```

get_config_dict (*trans*, *return_admin=False*, *view=None*, *keys=None*, *default_view='all'*)

Return a dictionary with (a subset of) current Galaxy settings.

If *return_admin* also include a subset of more sensitive keys. Pass in *view* (String) and comma separated list of keys to control which configuration settings are returned.

index (*trans*, **args*, ***kwargs*)

GET /api/configuration Return an object containing exposable configuration settings.

Note: a more complete list is returned if the user is an admin.

tool_lineages (*trans*, **args*, ***kwargs*)

version (*trans*, **args*, ***kwargs*)

GET /api/version Return a description of the major version of Galaxy (e.g. 15.03).

Return type dict

Returns dictionary with major version keyed on 'version_major'

dataset_collections Module

class `galaxy.webapps.galaxy.api.dataset_collections.DatasetCollectionsController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.UsesLibraries`

create (*trans*, **args*, ***kwargs*)

•**POST /api/dataset_collections:** create a new dataset collection instance.

Parameters **payload** (*dict*) – (optional) dictionary structure containing: * *collection_type*: dataset colltion type to create. * *instance_type*: Instance type - 'history' or 'library'. * *name*: the new dataset collections's name * *datasets*: object describing datasets for collection

Return type dict

Returns element view of new dataset collection

index (*trans*, **args*, ***kwargs*)

show (*trans*, **args*, ***kwargs*)

datasets Module

datatypes Module

API operations allowing clients to determine datatype supported by Galaxy.

class `galaxy.webapps.galaxy.api.datatypes.DatatypesController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`

converters (*trans*, **args*, ***kwargs*)

edam_formats (*trans*, **args*, ***kwargs*)

index (*trans*, **args*, ***kwargs*)

GET /api/datatypes Return an object containing upload datatypes.

mapping (*trans*, **args*, ***kwargs*)

GET /api/datatypes/mapping Return a dictionary of class to class mappings.

sniffers (*trans, *args, **kwargs*)
GET /api/datatypes/sniffers Return a list of sniffers.

extended_metadata Module

API operations on annotations.

class galaxy.webapps.galaxy.api.extended_metadata.**BaseExtendedMetadataController** (*app*)
Bases: *galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesExtendedMetadataController, galaxy.web.base.controller.UsesLibraryMixinItems, galaxy.web.base.controller.UsesStoredMetadataController*

create (*trans, *args, **kwargs*)
delete (*trans, *args, **kwargs*)
index (*trans, *args, **kwargs*)
undelete (*trans, *args, **kwargs*)

class galaxy.webapps.galaxy.api.extended_metadata.**HistoryDatasetExtendMetadataController** (*app*)
Bases: *galaxy.webapps.galaxy.api.extended_metadata.BaseExtendedMetadataController*

controller_name = 'history_dataset_extended_metadata'
exmeta_item_id = 'history_content_id'

class galaxy.webapps.galaxy.api.extended_metadata.**LibraryDatasetExtendMetadataController** (*app*)
Bases: *galaxy.webapps.galaxy.api.extended_metadata.BaseExtendedMetadataController*

controller_name = 'library_dataset_extended_metadata'
exmeta_item_id = 'library_content_id'

folder_contents Module

API operations on the contents of a library folder.

class galaxy.webapps.galaxy.api.folder_contents.**FolderContentsController** (*app*)
Bases: *galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesLibraryFolder, galaxy.web.base.controller.UsesLibraryMixinItems*

Class controls retrieval, creation and updating of folder contents.

build_path (*trans, folder*)
Search the path upwards recursively and load the whole route of names and ids for breadcrumb building purposes.

Parameters

- **folder** – current folder for navigating up
- **type** – Galaxy LibraryFolder

Returns list consisting of full path to the library

Type list

create (*self, trans, library_id, payload, **kwd*)

- **POST /api/folders/{encoded_id}/contents** create a new library file from an HDA

Parameters **payload** – dictionary structure containing:

Returns a dictionary containing the id, name, and ‘show’ url of the new item

Return type dict

Raises ObjectAttributeInvalidException, InsufficientPermissionsException, ItemAccessibilityException, InternalServerError

index (*trans*, **args*, ***kwargs*)

GET /api/folders/{encoded_folder_id}/contents

Displays a collection (list) of a folder’s contents (files and folders). Encoded folder ID is prepended with ‘F’ if it is a folder as opposed to a data set which does not have it. Full path is provided in response as a separate object providing data for breadcrumb path building.

Parameters

- **folder_id** (*encoded string*) – encoded ID of the folder which contents should be library_dataset_dict
- **kwd** (*dict*) – keyword dictionary with other params

Returns dictionary containing all items and metadata

Type dict

Raises MalformedId, InconsistentDatabase, ObjectNotFound, InternalServerError

show (*trans*, **args*, ***kwargs*)

GET /api/folders/{encoded_folder_id}/

update (*trans*, **args*, ***kwargs*)

PUT /api/folders/{encoded_folder_id}/contents

folders Module

API operations on library folders.

class galaxy.webapps.galaxy.api.folders.**FoldersController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesLibrary, galaxy.web.base.controller.UsesLibraryMixinItems*

create (*self*, *trans*, *encoded_parent_folder_id*, ***kwd*)

*POST /api/folders/{encoded_parent_folder_id}

Create a new folder object underneath the one specified in the parameters.

Parameters

- **encoded_parent_folder_id** (*an encoded id string (should be prefixed by ‘F’)*) – the parent folder’s id (required)
- **name** (*str*) – the name of the new folder (required)
- **description** (*str*) – the description of the new folder

Returns information about newly created folder, notably including ID

Return type dictionary

Raises RequestParameterMissingException

delete (*self*, *trans*, *id*, ***kwd*)

- **DELETE /api/folders/{id}** marks the folder with the given `id` as *deleted* (or removes the *deleted* mark if the *undelete* param is true)

Note: Currently, only admin users can un/delete folders.

Parameters

- **id** (*an encoded id string*) – the encoded id of the folder to un/delete
- **undelete** (*bool*) – (optional) flag specifying whether the item should be deleted or undeleted, defaults to false:

Returns detailed folder information

Return type dictionary

Raises ItemAccessibilityException, MalformedId, ObjectNotFound

get_permissions (*trans, *args, **kwargs*)

- GET /api/folders/{id}/permissions

Load all permissions for the given folder id and return it.

Parameters

- **encoded_folder_id** (*an encoded id string*) – the encoded id of the folder
- **scope** (*string*) – either ‘current’ or ‘available’

Returns dictionary with all applicable permissions’ values

Return type dictionary

Raises ObjectNotFound, InsufficientPermissionsException

index (*trans, *args, **kwargs*)

*GET /api/folders/ This would normally display a list of folders. However, that would be across multiple libraries, so it’s not implemented.

set_permissions (*trans, *args, **kwargs*)

def set_permissions(self, trans, encoded_folder_id, **kwd): *POST /api/folders/{encoded_folder_id}/permissions

Parameters

- **encoded_folder_id** (*an encoded id string*) – the encoded id of the folder to set the permissions of
- **action** (*string*) – (required) describes what action should be performed available actions: set_permissions
- **add_ids** [] (*string or list*) – list of Role.id defining roles that should have add item permission on the folder
- **manage_ids** [] (*string or list*) – list of Role.id defining roles that should have manage permission on the folder
- **modify_ids** [] (*string or list*) – list of Role.id defining roles that should have modify permission on the folder

Return type dictionary

Returns dict of current roles for all available permission types.

Raises RequestParameterInvalidException, ObjectNotFound, InsufficientPermissionsException, InternalServerError RequestParameterMissingException

show (*self*, *trans*, *id*, ***kwd*)

*GET /api/folders/{encoded_folder_id}

Displays information about a folder.

Parameters *id* (an encoded id string (has to be prefixed by 'F')) – the folder's encoded id (required)

Returns dictionary including details of the folder

Return type dict

update (*trans*, **args*, ***kwargs*)

PUT /api/folders/{encoded_folder_id}

forms Module

API operations on FormDefinition objects.

class galaxy.webapps.galaxy.api.forms.**FormDefinitionAPIController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

create (*trans*, **args*, ***kwargs*)

POST /api/forms Creates a new form.

index (*trans*, **args*, ***kwargs*)

GET /api/forms Displays a collection (list) of forms.

show (*trans*, **args*, ***kwargs*)

GET /api/forms/{encoded_form_id} Displays information about a form.

ftp_files Module

genomes Module

class galaxy.webapps.galaxy.api.genomes.**GenomesController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

RESTful controller for interactions with genome data.

index (*trans*, **args*, ***kwargs*)

GET /api/genomes: returns a list of installed genomes

show (*trans*, **args*, ***kwargs*)

GET /api/genomes/{id}

Returns information about build <id>

galaxy.webapps.galaxy.api.genomes.**get_id** (*base*, *format*)

group_roles Module

API operations on Group objects.

class galaxy.webapps.galaxy.api.group_roles.**GroupRolesAPIController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

delete (*trans*, *args, **kwargs)
DELETE /api/groups/{encoded_group_id}/roles/{encoded_role_id} Removes a role from a group

index (*trans*, *args, **kwargs)
GET /api/groups/{encoded_group_id}/roles Displays a collection (list) of groups.

show (*trans*, *args, **kwargs)
GET /api/groups/{encoded_group_id}/roles/{encoded_role_id} Displays information about a group role.

update (*trans*, *args, **kwargs)
PUT /api/groups/{encoded_group_id}/roles/{encoded_role_id} Adds a role to a group

group_users Module

API operations on Group objects.

class galaxy.webapps.galaxy.api.group_users.**GroupUsersAPIController** (*app*)
Bases: *galaxy.web.base.controller.BaseAPIController*

delete (*trans*, *args, **kwargs)
DELETE /api/groups/{encoded_group_id}/users/{encoded_user_id} Removes a user from a group

index (*trans*, *args, **kwargs)
GET /api/groups/{encoded_group_id}/users Displays a collection (list) of groups.

show (*trans*, *args, **kwargs)
GET /api/groups/{encoded_group_id}/users/{encoded_user_id} Displays information about a group user.

update (*trans*, *args, **kwargs)
PUT /api/groups/{encoded_group_id}/users/{encoded_user_id} Adds a user to a group

groups Module

API operations on Group objects.

class galaxy.webapps.galaxy.api.groups.**GroupAPIController** (*app*)
Bases: *galaxy.web.base.controller.BaseAPIController*

create (*trans*, *args, **kwargs)
POST /api/groups Creates a new group.

index (*trans*, *args, **kwargs)
GET /api/groups Displays a collection (list) of groups.

show (*trans*, *args, **kwargs)
GET /api/groups/{encoded_group_id} Displays information about a group.

update (*trans*, *args, **kwargs)
PUT /api/groups/{encoded_group_id} Modifies a group.

histories Module

API operations on a history.

See also:

galaxy.model.History

```
class galaxy.webapps.galaxy.api.histories.HistoriesController(app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.ExportsHis
    galaxy.web.base.controller.ImportsHistoryMixin
```

```
archive_download(trans, *args, **kwargs)
```

```
export_download( self, trans, id, jeha_id ) * GET /api/histories/{id}/exports/{jeha_id}:
```

If ready and available, return raw contents of exported history. Use/poll “PUT /api/histories/{id}/exports” to initiate the creation of such an export - when ready that route will return 200 status code (instead of 202) with a JSON dictionary containing a *download_url*.

```
archive_export(trans, *args, **kwargs)
```

```
export_archive( self, trans, id, payload ) * PUT /api/histories/{id}/exports:
```

start job (if needed) to create history export for corresponding history.

Parameters *id* (*str*) – the encoded id of the history to export

Return type dict

Returns object containing url to fetch export from.

```
citations(trans, *args, **kwargs)
```

```
create(trans, payload)
```

•**POST /api/histories:** create a new history

Parameters

- **payload** (*dict*) – (optional) dictionary structure containing: * *name*: the new history’s name * *history_id*: the id of the history to copy * *archive_source*: the url that will generate the archive to import * *archive_type*: ‘url’ (default)
- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type dict

Returns element view of new history

```
delete(self, trans, id, **kwd)
```

•**DELETE /api/histories/{id}** delete the history with the given *id*

Note: Stops all active jobs in the history if purge is set.

Parameters

- **id** (*str*) – the encoded id of the history to delete
- **kwd** (*dict*) – (optional) dictionary structure containing extra parameters

You can purge a history, removing all it’s datasets from disk (if unshared), by passing in *purge=True* in the url.

Parameters

- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type dict

Returns the deleted or purged history

index (*trans*, *deleted*='False')

- GET /api/histories:** return undeleted histories for the current user

- GET /api/histories/deleted:** return deleted histories for the current user

Note: Anonymous users are allowed to get their current history

Parameters **deleted** (*boolean*) – if True, show only deleted histories, if False, non-deleted

Return type *list*

Returns list of dictionaries containing summary history information

The following are optional parameters:

view: string, one of ('summary','detailed'), defaults to 'summary' controls which set of properties to return

keys: comma separated strings, unused by default keys/names of individual properties to return

If neither keys or views are sent, the default view (set of keys) is returned. If both a view and keys are sent, the key list and the view's keys are combined. If keys are sent and no view, only those properties in keys are returned.

For which properties are available see: galaxy/managers/histories/HistorySerializer

The list returned can be filtered by using two optional parameters:

q: string, generally a property name to filter by followed by an (often optional) hyphen and operator string.

qv: string, the value to filter by

..example: To filter the list to only those created after 2015-01-29, the query string would look like:

'?q=create_time-gt&qv=2015-01-29'

Multiple filters can be sent in using multiple q/qv pairs: '?q=create_time-gt&qv=2015-01-29&q=tag-has&qv=experiment-1'

The list returned can be paginated using two optional parameters:

limit: integer, defaults to no value and no limit (return all) how many items to return

offset: integer, defaults to 0 and starts at the beginning skip the first (offset - 1) items and begin returning at the Nth item

..example:

limit and offset can be combined. Skip the first two and return five: '?limit=5&offset=3'

show (*trans*, *id*, *deleted*='False')

- GET /api/histories/{id}:** return the history with *id*

- GET /api/histories/deleted/{id}:** return the deleted history with *id*

- GET /api/histories/most_recently_used:** return the most recently used history

Parameters

- **id** (*an encoded id string*) – the encoded id of the history to query or the string ‘most_recently_used’
- **deleted** (*boolean*) – if True, allow information on a deleted history to be shown.
- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type dictionary**Returns** detailed history information**undelelete** (*self, trans, id, **kwd*)

- **POST /api/histories/deleted/{id}/undelelete:** undelete history (that hasn’t been purged) with the given *id*

Parameters

- **id** (*str*) – the encoded id of the history to undelete
- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type str**Returns** ‘OK’ if the history was undeleted**update** (*self, trans, id, payload, **kwd*)

- **PUT /api/histories/{id}** updates the values for the history with the given *id*

Parameters

- **id** (*str*) – the encoded id of the history to update
- **payload** (*dict*) – a dictionary containing any or all the fields in `galaxy.model.History.to_dict()` and/or the following:
 - annotation: an annotation for the history
- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type dict**Returns** an error object if an error occurred or a dictionary containing any values that were different from the original and, therefore, updated**history_contents Module**

API operations on the contents of a history.

class `galaxy.webapps.galaxy.api.history_contents.HistoryContentsController` (*app*)Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.UsesLibraryMixin`, `galaxy.web.base.controller.UsesTagsMixin`**create** (*self, trans, history_id, payload, **kwd*)

- **POST** `/api/histories/{history_id}/contents/{type}` create a new HDA by copying an accessible LibraryDataset

Parameters

- **history_id** (*str*) – encoded id string of the new HDA’s History
- **type** (*str*) – Type of history content - ‘dataset’ (default) or ‘dataset_collection’.
- **payload** (*dict*) – dictionary structure containing:
 - copy from library (for type ‘dataset’):
‘source’ = ‘library’ ‘content’ = [the encoded id from the library dataset]
 - copy from history dataset (for type ‘dataset’): ‘source’ = ‘hda’ ‘content’ = [the encoded id from the HDA]
 - copy from history dataset collection (for type ‘dataset_collection’) ‘source’ = ‘hdca’ ‘content’ = [the encoded id from the HDCA]
 - create new history dataset collection (for type ‘dataset_collection’) ‘source’ = ‘new_collection’ (default ‘source’ if type is ‘dataset_collection’ - no need to specify this)
 - ‘collection_type’ = For example, “list”, “paired”, “list:paired”. ‘name’ = Name of new dataset collection. ‘element_identifiers’ = Recursive list structure defining collection.Each element must have ‘src’ which can be ‘hda’, ‘ldda’, ‘hdca’, or ‘new_collection’, as well as a ‘name’ which is the name of element (e.g. “forward” or “reverse” for paired datasets, or arbitrary sample names for instance for lists). For all src’s except ‘new_collection’ - a encoded ‘id’ attribute must be included with element as well. ‘new_collection’ sources must defined a ‘collection_type’ and their own list of (potentially) nested ‘element_identifiers’.

..note: Currently, a user can only copy an HDA from a history that the user owns.

Return type dict

Returns dictionary containing detailed information for the new HDA

delete (*self, trans, history_id, id, **kwd*)

- **DELETE** `/api/histories/{history_id}/contents/{id}` delete the HDA with the given id

Note: Currently does not stop any active jobs for which this dataset is an output.

Parameters

- **id** (*str*) – the encoded id of the history to delete
- **purge** (*bool*) – if True, purge the HDA
- **kwd** (*dict*) – (optional) dictionary structure containing:
 - **payload: a dictionary itself containing:**
 - * **purge:** if True, purge the HDA

Note: that payload optionally can be placed in the query string of the request. This allows clients that strip the request body to still purge the dataset.

Return type dict

Returns an error object if an error occurred or a dictionary containing: * `id`: the encoded id of the history, * `deleted`: if the history was marked as deleted, * `purged`: if the history was purged

index (*self*, *trans*, *history_id*, *ids=None*, ***kwd*)

• **GET /api/histories/{history_id}/contents** return a list of HDA data for the history with the given `id`

Note: Anonymous users are allowed to get their current history contents

If `Ids` is not given, `index` returns a list of *summary* objects for every HDA associated with the given *history_id*.

If `ids` is given, `index` returns a *more complete* json object for each HDA in the `ids` list.

Parameters

- **history_id** (*str*) – encoded id string of the HDA's History
- **ids** (*str*) – (optional) a comma separated list of encoded *HDA* ids
- **types** (*str*) – (optional) kinds of contents to index (currently just dataset, but `dataset_collection` will be added shortly).

Return type *list*

Returns dictionaries containing summary or detailed HDA information

show (*self*, *trans*, *id*, *history_id*, ***kwd*)

• **GET /api/histories/{history_id}/contents/{id}** return detailed information about an HDA within a history

Note: Anonymous users are allowed to get their current history contents

Parameters

- **ids** – the encoded id of the HDA to return
- **history_id** (*str*) – encoded id string of the HDA's History

Return type dict

Returns dictionary containing detailed HDA information

update (*self*, *trans*, *history_id*, *id*, *payload*, ***kwd*)

• **PUT /api/histories/{history_id}/contents/{id}** updates the values for the HDA with the given `id`

Parameters

- **history_id** (*str*) – encoded id string of the HDA's History
- **id** (*str*) – the encoded id of the history to undelete
- **payload** (*dict*) – a dictionary containing any or all the fields in `galaxy.model.HistoryDatasetAssociation.to_dict()` and/or the following:
 - `annotation`: an annotation for the HDA

Return type dict

Returns an error object if an error occurred or a dictionary containing any values that were different from the original and, therefore, updated

item_tags Module

API operations related to tagging items.

```
class galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController(app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesTagsM
```

```
    create(trans, *args, **kwargs)
```

```
    delete(trans, *args, **kwargs)
```

```
    index(trans, *args, **kwargs)
```

```
    show(trans, *args, **kwargs)
```

```
    update(trans, *args, **kwargs)
```

```
class galaxy.webapps.galaxy.api.item_tags.HistoryContentTagsController(app)
    Bases: galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController
```

```
    controller_name = 'history_content_tags'
```

```
    tagged_item_class = 'HistoryDatasetAssociation'
```

```
    tagged_item_id = 'history_content_id'
```

```
class galaxy.webapps.galaxy.api.item_tags.HistoryTagsController(app)
    Bases: galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController
```

```
    controller_name = 'history_tags'
```

```
    tagged_item_class = 'History'
```

```
    tagged_item_id = 'history_id'
```

```
class galaxy.webapps.galaxy.api.item_tags.WorkflowTagsController(app)
    Bases: galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController
```

```
    controller_name = 'workflow_tags'
```

```
    tagged_item_class = 'StoredWorkflow'
```

```
    tagged_item_id = 'workflow_id'
```

job_files Module

API for asynchronous job running mechanisms can use to fetch or put files related to running and queued jobs.

```
class galaxy.webapps.galaxy.api.job_files.JobFilesAPIController(app)
    Bases: galaxy.web.base.controller.BaseAPIController
```

This job files controller allows remote job running mechanisms to read and modify the current state of files for queued and running jobs. It is certainly not meant to represent part of Galaxy's stable, user facing API.

Furthermore, even if a user key corresponds to the user running the job, it should not be accepted for authorization - this API allows access to low-level unfiltered files and such authorization would break Galaxy's security model for tool execution.

create (*self, trans, job_id, payload, **kwargs*)

- **POST /api/jobs/{job_id}/files** Populate an output file (formal dataset, task split part, working directory file (such as those related to metadata)). This should be a multipart post with a 'file' parameter containing the contents of the actual file to create.

Parameters

- **job_id** (*str*) – encoded id string of the job
- **payload** (*dict*) – dictionary structure containing:: 'job_key' = Key authenticating
'path' = Path to file to create.

..note: This API method is intended only for consumption by job runners, not end users.

Return type dict

Returns an okay message

index (*self, trans, job_id, **kwargs*)

- **GET /api/jobs/{job_id}/files** Get a file required to staging a job (proper datasets, extra inputs, task-split inputs, working directory files).

Parameters

- **job_id** (*str*) – encoded id string of the job
- **path** (*str*) – Path to file.
- **job_key** (*str*) – A key used to authenticate this request as acting on behalf of a job runner for the specified job.

..note: This API method is intended only for consumption by job runners, not end users.

Return type *binary*

Returns contents of file

jobs Module

API operations on a jobs.

See also:

`galaxy.model.Jobs`

class `galaxy.webapps.galaxy.api.jobs.JobController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.UsesLibraries`

create (*trans, *args, **kwargs*)

See the create method in tools.py in order to submit a job.

index (*trans, state=None, tool_id=None, history_id=None, date_range_min=None, date_range_max=None, user_details=False*)

- **GET /api/jobs:** return jobs for current user

!! if user is admin and user_details is True, then return jobs for all galaxy users based on filtering - this is an extended service

Parameters **state** (*string or list*) – limit listing of jobs to those that match one of the included states. If none, all are returned.

Valid Galaxy job states include: ‘new’, ‘upload’, ‘waiting’, ‘queued’, ‘running’, ‘ok’, ‘error’, ‘paused’, ‘deleted’, ‘deleted_new’

Parameters

- **tool_id** (*string or list*) – limit listing of jobs to those that match one of the included tool_ids. If none, all are returned.
- **user_details** (*boolean*) – if true, and requestor is an admin, will return external job id and user email.
- **date_range_min** (*string ‘2014-01-01’*) – limit the listing of jobs to those updated on or after requested date
- **date_range_max** (*string ‘2014-12-31’*) – limit the listing of jobs to those updated on or before requested date
- **history_id** (*string*) – limit listing of jobs to those that match the history_id. If none, all are returned.

Return type *list*

Returns list of dictionaries containing summary job information

inputs (*trans, *args, **kwargs*)
show(trans, id) * GET /api/jobs/{job_id}/inputs
returns input datasets created by job

Parameters **id** (*string*) – Encoded job id

Return type dictionary

Returns dictionary containing input dataset associations

outputs (*trans, *args, **kwargs*)
show(trans, id) * GET /api/jobs/{job_id}/outputs
returns output datasets created by job

Parameters **id** (*string*) – Encoded job id

Return type dictionary

Returns dictionary containing output dataset associations

search (*trans, payload*)

• **POST /api/jobs/search:** return jobs for current user

Parameters **payload** (*dict*) – Dictionary containing description of requested job. This is in the same format as a request to POST /apt/tools would take to initiate a job

Return type *list*

Returns list of dictionaries containing summary job information of the jobs that match the requested job run

This method is designed to scan the list of previously run jobs and find records of jobs that had the exact same input parameters and datasets. This can be used to minimize the amount of repeated work, and simply recycle the old results.

show (*trans*, *id*)

• **GET /api/jobs/{job_id}**: return jobs for current user

Parameters

- **id** (*string*) – Specific job id
- **full** (*boolean*) – whether to return extra information

Return type dictionary

Returns dictionary containing full description of job data

lda_datasets Module

API operations on the library datasets.

class galaxy.webapps.galaxy.api.lda_datasets.**LibraryDatasetsController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesVisual*

delete (*trans*, **args*, ***kwargs*)

delete(self, trans, encoded_dataset_id, ***kwd*): * DELETE /api/libraries/datasets/{encoded_dataset_id}

Marks the dataset deleted or undeleted based on the value of the undelete flag. If the flag is not present it is considered False and the item is marked deleted.

Parameters **encoded_dataset_id** (*an encoded id string*) – the encoded id of the dataset to change

Returns dict containing information about the dataset

Return type dictionary

download (*self*, *trans*, *format*, ***kwd*)

• **GET /api/libraries/datasets/download/{format}**

• **POST /api/libraries/datasets/download/{format}** Downloads requested datasets (identified by encoded IDs) in requested format.

example: GET localhost:8080/api/libraries/datasets/download/tbz?ld_ids%255B%255D=a0d8

Note: supported format values are: 'zip', 'tgz', 'tbz', 'uncompressed'

Parameters

- **format** (*string*) – string representing requested archive format
- **ld_ids** [] (*an array*) – an array of encoded ids

Return type file

Returns either archive with the requested datasets packed inside or a single uncompressed dataset

Raises `MessageException`, `ItemDeletionException`, `ItemAccessibilityException`, `HTTP-BadRequest`, `OSError`, `IOError`, `ObjectNotFound`

load (*trans*, **args*, ***kwargs*)

`load(self, trans, **kwd)`: * `POST /api/libraries/datasets` Load dataset from the given source into the library. Source can be:

user directory - root folder specified in `galaxy.ini` as “`$user_library_import_dir`”

example path: `path/to/galaxy/$user_library_import_dir/user@example.com/{user can browse everything here}` the folder with the user login has to be created beforehand

(admin)import directory - root folder specified in `galaxy ini` as “`$library_import_dir`”

example path: `path/to/galaxy/$library_import_dir/{admin can browse everything here}`

(admin)any absolute or relative path - option allowed with “`allow_library_path_paste`” in `galaxy.ini`

Parameters

- **encoded_folder_id** (*an encoded id string*) – the encoded id of the folder to import dataset(s) to
- **source** (*str*) – source the datasets should be loaded form
- **link_data** (*bool*) – flag whether to link the dataset to data or copy it to Galaxy, defaults to copy while linking is set to True all symlinks will be resolved `_once_`
- **preserve_dirs** (*bool*) – flag whether to preserve the directory structure when importing dir if False only datasets will be imported
- **file_type** (*str*) – file type of the loaded datasets, defaults to ‘auto’ (autodetect)
- **dbkey** (*str*) – dbkey of the loaded genome, defaults to ‘?’ (unknown)

Returns dict containing information about the created upload job

Return type dictionary

show (*self*, *trans*, *id*, ***kwd*)

• **GET /api/libraries/datasets/{encoded_dataset_id}**: Displays information about the dataset identified by the encoded ID.

Parameters **id** (*an encoded id string*) – the encoded id of the dataset to query

Returns detailed dataset information from base controller

Return type dictionary

See also:

`galaxy.web.base.controller.UsesLibraryMixinItems.get_library_dataset`

show_roles (*trans*, **args*, ***kwargs*)

`show_roles(self, trans, id, **kwd)`: * `GET /api/libraries/datasets/{encoded_dataset_id}/permissions`

Displays information about current or available roles for a given dataset permission.

Parameters

- **encoded_dataset_id** (*an encoded id string*) – the encoded id of the dataset to query

- **scope** (*string*) – either ‘current’ or ‘available’

Return type dictionary

Returns either dict of current roles for all permission types or dict of available roles to choose from (is the same for any permission type)

show_version (*trans, *args, **kwargs*)

show_version(self, trans, encoded_dataset_id, encoded_ldda_id, ****kwd**): * GET
/api/libraries/datasets/:encoded_dataset_id/versions/:encoded_ldda_id

Displays information about specific version of the library_dataset (i.e. ldda).

Parameters

- **encoded_dataset_id** (*an encoded id string*) – the encoded id of the dataset to query
- **encoded_ldda_id** (*an encoded id string*) – the encoded id of the ldda to query

Return type dictionary

Returns dict of ldda’s details

update_permissions (*trans, *args, **kwargs*)

def update(self, trans, encoded_dataset_id, ****kwd**): *POST /api/libraries/datasets/{encoded_dataset_id}/permissions

Parameters

- **encoded_dataset_id** (*an encoded id string*) – the encoded id of the dataset to update permissions of
- **action** (*string*) – (required) describes what action should be performed available actions: make_private, remove_restrictions, set_permissions
- **access_ids** [] (*string or list*) – list of Role.name defining roles that should have access permission on the dataset
- **manage_ids** [] (*string or list*) – list of Role.name defining roles that should have manage permission on the dataset
- **modify_ids** [] (*string or list*) – list of Role.name defining roles that should have modify permission on the library dataset item

Return type dictionary

Returns dict of current roles for all available permission types

Raises RequestParameterInvalidException, ObjectNotFound, InsufficientPermissionsException, InternalServerError RequestParameterMissingException

libraries Module

API operations on a data library.

class galaxy.webapps.galaxy.api.libraries.**LibrariesController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

create (*self, trans, payload, **kwd*)

- **POST /api/libraries:** Creates a new library. Only name parameter is required.

Note: Currently, only admin users can create libraries.

Parameters **payload** (*dict*) – dictionary structure containing:: ‘name’: the new library’s name (required) ‘description’: the new library’s description (optional) ‘synopsis’: the new library’s synopsis (optional)

Returns detailed library information

Return type dict

Raises ItemAccessibilityException, RequestParameterMissingException

delete (*self, trans, id, **kwd*)

• **DELETE /api/libraries/{id}** marks the library with the given *id* as *deleted* (or removes the *deleted* mark if the *undelete* param is true)

Note: Currently, only admin users can un/delete libraries.

Parameters

- **id** (*an encoded id string*) – the encoded id of the library to un/delete
- **undelete** (*bool*) – (optional) flag specifying whether the item should be deleted or undeleted, defaults to false:

Returns detailed library information

Return type dictionary

See also:

galaxy.model.Library.dict_element_visible_keys

Raises ItemAccessibilityException, MalformedId, ObjectNotFound

get_permissions (*trans, *args, **kwargs*)

• **GET /api/libraries/{id}/permissions**

Load all permissions for the given library id and return it.

Parameters

- **encoded_library_id** (*an encoded id string*) – the encoded id of the library
- **scope** (*string*) – either ‘current’ or ‘available’
- **is_library_access** (*bool*) – indicates whether the roles available for the library access are requested

Returns dictionary with all applicable permissions’ values

Return type dictionary

Raises ObjectNotFound, InsufficientPermissionsException

index (*self, trans, **kwd*)

• **GET /api/libraries:** Returns a list of summary data for all libraries.

Parameters **deleted** (*boolean (optional)*) – if True, show only deleted libraries, if False show only non-deleted

Returns list of dictionaries containing library information

Return type *list*

See also:

galaxy.model.Library.dict_collection_visible_keys

set_permissions (*trans, *args, **kwargs*)

def set_permissions(self, trans, encoded_dataset_id, **kwd): *POST
/api/libraries/{encoded_library_id}/permissions

Parameters

- **encoded_library_id** (*an encoded id string*) – the encoded id of the library to set the permissions of
- **action** (*string*) – (required) describes what action should be performed available actions: remove_restrictions, set_permissions
- **access_ids** [] (*string or list*) – list of Role.id defining roles that should have access permission on the library
- **add_ids** [] (*string or list*) – list of Role.id defining roles that should have add item permission on the library
- **manage_ids** [] (*string or list*) – list of Role.id defining roles that should have manage permission on the library
- **modify_ids** [] (*string or list*) – list of Role.id defining roles that should have modify permission on the library

Return type dictionary

Returns dict of current roles for all available permission types

Raises RequestParameterInvalidException, ObjectNotFound, InsufficientPermissionsException, InternalServerError RequestParameterMissingException

set_permissions_old (*trans, library, payload, **kwd*)
* old implementation for backward compatibility *

POST /api/libraries/{encoded_library_id}/permissions Updates the library permissions.

show (*self, trans, id, deleted='False', **kwd*)

- **GET /api/libraries/{encoded_id}**: returns detailed information about a library
- **GET /api/libraries/deleted/{encoded_id}**: returns detailed information about a deleted library

Parameters

- **id** (*an encoded id string*) – the encoded id of the library
- **deleted** (*boolean*) – if True, allow information on a deleted library

Returns detailed library information

Return type dictionary

See also:

`galaxy.model.Library.dict_element_visible_keys`

Raises MalformedId, ObjectNotFound

update (*trans*, **args*, ***kwargs*)

• **PATCH /api/libraries/{encoded_id}** Updates the library defined by an `encoded_id` with the data in the payload.

Note: Currently, only admin users can update libraries. Also the library must not be *deleted*.

param id the encoded id of the library

type id an encoded id string

param payload (required) dictionary structure containing:: 'name': new library's name, cannot be empty 'description': new library's description 'synopsis': new library's synopsis

type payload dict

returns detailed library information

rtype dict

raises ItemAccessibilityException, MalformedId, ObjectNotFound, RequestParameterInvalidException, RequestParameterMissingException

library_contents Module

API operations on the contents of a data library.

class `galaxy.webapps.galaxy.api.library_contents.LibraryContentsController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.UsesLibraryMixin`, `galaxy.web.base.controller.UsesLibraryMixinItems`

create (*self*, *trans*, *library_id*, *payload*, ***kwd*)

• **POST /api/libraries/{library_id}/contents:** create a new library file or folder

To copy an HDA into a library send `create_type` of 'file' and the HDA's encoded id in `from_hda_id` (and optionally `ldda_message`).

Parameters

- **library_id** (*str*) – the encoded id of the library where to create the new item
- **payload** (*dict*) – dictionary structure containing:
 - `folder_id`: the encoded id of the parent folder of the new item
 - `create_type`: the type of item to create ('file', 'folder' or 'collection')
 - **from_hda_id**: (optional, only if `create_type` is 'file') the encoded id of an accessible HDA to copy into the library
 - `ldda_message`: (optional) the new message attribute of the LDDA created
 - **extended_metadata**: (optional) dub-dictionary containing any extended metadata to associate with the item

- **upload_option:** (optional) one of ‘upload_file’ (default), ‘upload_directory’ or ‘upload_paths’
- **server_dir:** (optional, only if upload_option is ‘upload_directory’) relative path of the subdirectory of Galaxy `library_import_dir` to upload. All and only the files (i.e. no subdirectories) contained in the specified directory will be uploaded.
- **filesystem_paths:** (optional, only if upload_option is ‘upload_paths’ and the user is an admin) file paths on the Galaxy server to upload to the library, one file per line
- **link_data_only:** (optional, only when upload_option is ‘upload_directory’ or ‘upload_paths’) either ‘copy_files’ (default) or ‘link_to_files’. Setting to ‘link_to_files’ symlinks instead of copying the files
- **name:** (optional, only if create_type is ‘folder’) name of the folder to create
- **description:** (optional, only if create_type is ‘folder’) description of the folder to create

Return type dict

Returns a dictionary containing the id, name, and ‘show’ url of the new item

delete (*self*, *trans*, *library_id*, *id*, ***kwd*)

•**DELETE /api/libraries/{library_id}/contents/{id}** delete the LibraryDataset with the given *id*

Parameters

- **id** (*str*) – the encoded id of the library dataset to delete
- **kwd** (*dict*) – (optional) dictionary structure containing:
 - **payload: a dictionary itself containing:**
 - * **purge:** if True, purge the LD

Return type dict

Returns an error object if an error occurred or a dictionary containing: * **id:** the encoded id of the library dataset, * **deleted:** if the library dataset was marked as deleted, * **purged:** if the library dataset was purged

index (*self*, *trans*, *library_id*, ***kwd*)

•**GET /api/libraries/{library_id}/contents:** Returns a list of library files and folders.

Note: May be slow! Returns all content traversing recursively through all folders.

See also:

`galaxy.webapps.galaxy.api.FolderContentsController.index` for a non-recursive solution

Parameters **library_id** (*str*) – the encoded id of the library

Returns

list of dictionaries of the form: * **id:** the encoded id of the library item * **name:** the ‘library path’

or relationship of the library item to the root

- type: ‘file’ or ‘folder’
- url: the url to get detailed information on the library item

Return type *list*

Raises `MalformedId`, `InconsistentDatabase`, `RequestParamerInvalidException`, `InternalServerError`

show (*self*, *trans*, *id*, *library_id*, ***kwd*)

•**GET /api/libraries/{library_id}/contents/{id}** Returns information about library file or folder.

Parameters

- **id** (*str*) – the encoded id of the library item to return
- **library_id** (*str*) – the encoded id of the library that contains this item

Returns detailed library item information

Return type *dict*

See also:

galaxy.model.LibraryDataset.to_dict() and *galaxy.model.LibraryFolder.dict_element_v*

update (*self*, *trans*, *id*, *library_id*, *payload*, ***kwd*)

•**PUT /api/libraries/{library_id}/contents/{id}** create a `ImplicitlyConvertedDatasetAssociation`

See also:

galaxy.model.ImplicitlyConvertedDatasetAssociation

Parameters

- **id** (*str*) – the encoded id of the library item to return
- **library_id** (*str*) – the encoded id of the library that contains this item
- **payload** (*dict*) – dictionary structure containing:: ‘converted_dataset_id’:

Return type *None*

Returns *None*

metrics Module

API operations for for querying and recording user metrics from some client (typically a user’s browser).

class `galaxy.webapps.galaxy.api.metrics.MetricsController` (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

create (*trans*, *payload*)

•**POST /api/metrics:** record any metrics sent and return some status object

Note: Anonymous users can post metrics

Parameters **payload** (*dict*) – (optional) dictionary structure containing: * metrics: a list containing dictionaries of the form:

** namespace: label indicating the source of the metric ** time: isoformat datetime when the metric was recorded ** level: an integer representing the metric’s log level ** args: a json string containing an array of extra data

Return type dict

Returns status object

debugging = None

set to true to send additional debugging info to the log

page_revisions Module

API for updating Galaxy Pages

class galaxy.webapps.galaxy.api.page_revisions.**PageRevisionsController** (*app*)
 Bases: *galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.SharableIt*
galaxy.model.item_attrs.UsesAnnotations, galaxy.web.base.controller.SharableMixin

create (*self, trans, page_id, payload **kwd*)

•**POST /api/pages/{page_id}/revisions** Create a new revision for a page

Parameters

- **page_id** – Add revision to Page with ID=page_id
- **payload** – A dictionary containing:: ‘title’ = New title of the page ‘content’ = New content of the page

Return type dictionary

Returns Dictionary with ‘success’ or ‘error’ element to indicate the result of the request

index (*self, trans, page_id, **kwd*)

•**GET /api/pages/{page_id}/revisions** return a list of Page revisions

Parameters **page_id** – Display the revisions of Page with ID=page_id

Return type *list*

Returns dictionaries containing different revisions of the page

pages Module

API for updating Galaxy Pages

class galaxy.webapps.galaxy.api.pages.**PagesController** (*app*)
 Bases: *galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.SharableIt*
galaxy.model.item_attrs.UsesAnnotations, galaxy.web.base.controller.SharableMixin

create (*self, trans, payload, **kwd*)

•**POST /api/pages** Create a page and return dictionary containing Page summary

Parameters **payload** – dictionary structure containing:: ‘slug’ = The title slug for the page URL, must be unique ‘title’ = Title of the page ‘content’ = HTML contents of the page ‘annotation’ = Annotation that will be attached to the page

Return type dict

Returns Dictionary return of the Page.to_dict call

delete (*self*, *trans*, *id*, ***kwd*)

•**DELETE /api/pages/{id}** Create a page and return dictionary containing Page summary

Parameters **id** – ID of page to be deleted

Return type dict

Returns Dictionary with ‘success’ or ‘error’ element to indicate the result of the request

index (*self*, *trans*, *deleted=False*, ***kwd*)

•**GET /api/pages** return a list of Pages viewable by the user

Parameters **deleted** – Display deleted pages

Return type *list*

Returns dictionaries containing summary or detailed Page information

show (*self*, *trans*, *id*, ***kwd*)

•**GET /api/pages/{id}** View a page summary and the content of the latest revision

Parameters **id** – ID of page to be displayed

Return type dict

Returns Dictionary return of the Page.to_dict call with the ‘content’ field populated by the most recent revision

provenance Module

API operations provenance

class galaxy.webapps.galaxy.api.provenance.**BaseProvenanceController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

create (*trans*, **args*, ***kwargs*)

delete (*trans*, **args*, ***kwargs*)

index (*trans*, **args*, ***kwargs*)

show (*trans*, **args*, ***kwargs*)

class galaxy.webapps.galaxy.api.provenance.**HDAProvenanceController** (*app*)

Bases: *galaxy.webapps.galaxy.api.provenance.BaseProvenanceController*

controller_name = ‘history_content_provenance’

provenance_item_class = ‘HistoryDatasetAssociation’

provenance_item_id = ‘history_content_id’

```
class galaxy.webapps.galaxy.api.provenance.LDDAProvenanceController(app)
    Bases: galaxy.webapps.galaxy.api.provenance.BaseProvenanceController

    controller_name = 'ldda_provenance'

    provenance_item_class = 'LibraryDatasetDatasetAssociation'

    provenance_item_id = 'library_content_id'
```

quotas Module

API operations on Quota objects.

```
class galaxy.webapps.galaxy.api.quotas.QuotaAPIController(app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controllers.admin.AdminActions, galaxy.actions.admin.AdminActions, galaxy.web.base.controller.UsesQuotaMixin, galaxy.web.params.QuotaParamParser

    create(trans, *args, **kwargs)
        POST /api/quotas Creates a new quota.

    delete(trans, *args, **kwargs)
        DELETE /api/quotas/{encoded_quota_id} Deletes a quota

    index(trans, *args, **kwargs)
        GET /api/quotas GET /api/quotas/deleted Displays a collection (list) of quotas.

    show(trans, *args, **kwargs)
        GET /api/quotas/{encoded_quota_id} GET /api/quotas/deleted/{encoded_quota_id} Displays information about a quota.

    undelete(trans, *args, **kwargs)
        POST /api/quotas/deleted/{encoded_quota_id}/undelete Undeletes a quota

    update(trans, *args, **kwargs)
        PUT /api/quotas/{encoded_quota_id} Modifies a quota.
```

request_types Module

API operations on RequestType objects.

```
class galaxy.webapps.galaxy.api.request_types.RequestTypeAPIController(app)
    Bases: galaxy.web.base.controller.BaseAPIController

    create(trans, *args, **kwargs)
        POST /api/request_types Creates a new request type (external_service configuration).

    index(trans, *args, **kwargs)
        GET /api/request_types Displays a collection (list) of request_types.

    show(trans, *args, **kwargs)
        GET /api/request_types/{encoded_request_type_id} Displays information about a request_type.
```

requests Module

API operations on a sample tracking system.

```
class galaxy.webapps.galaxy.api.requests.RequestsAPIController(app)
    Bases: galaxy.web.base.controller.BaseAPIController
```

```
index (trans, *args, **kwargs)  
    GET /api/requests Displays a collection (list) of sequencing requests.  
  
show (trans, *args, **kwargs)  
    GET /api/requests/{encoded_request_id} Displays details of a sequencing request.  
  
update (trans, *args, **kwargs)  
    PUT /api/requests/{encoded_request_id} Updates a request state, sample state or sample dataset transfer  
    status depending on the update_type  
  
v = ('REQUEST', 'request_state')
```

roles Module

API operations on Role objects.

```
class galaxy.webapps.galaxy.api.roles.RoleAPIController (app)  
    Bases: galaxy.web.base.controller.BaseAPIController  
  
    create (trans, *args, **kwargs)  
        POST /api/roles Creates a new role.  
  
    index (trans, *args, **kwargs)  
        GET /api/roles Displays a collection (list) of roles.  
  
    show (trans, *args, **kwargs)  
        GET /api/roles/{encoded_role_id} Displays information about a role.
```

samples Module

API operations for samples in the Galaxy sample tracking system.

```
class galaxy.webapps.galaxy.api.samples.SamplesAPIController (app)  
    Bases: galaxy.web.base.controller.BaseAPIController  
  
    index (trans, *args, **kwargs)  
        GET /api/requests/{encoded_request_id}/samples Displays a collection (list) of sample of a sequencing  
        request.  
  
    k = 'SAMPLE_DATASET'  
  
    update (trans, *args, **kwargs)  
        PUT /api/samples/{encoded_sample_id} Updates a sample or objects related ( mapped ) to a sample.  
  
    update_type_values = ['sample_state', 'run_details', 'sample_dataset_transfer_status']  
    update_types = <galaxy.util.bunch.Bunch object>  
    v = ['sample_dataset_transfer_status']
```

search Module

tool_data Module

```
class galaxy.webapps.galaxy.api.tool_data.ToolData (app)  
    Bases: galaxy.web.base.controller.BaseAPIController  
  
    RESTful controller for interactions with tool data
```

delete (*trans*, *args, **kwargs)

DELETE /api/tool_data/{id} Removes an item from a data table

Parameters

- **id** (*str*) – the id of the data table containing the item to delete
- **kwd** (*dict*) – (required) dictionary structure containing:
 - **payload: a dictionary itself containing:**
 - * values: <TAB> separated list of column contents, there must be a value for all the columns of the data table

download_field_file (*trans*, *args, **kwargs)

index (*trans*, *args, **kwargs)

GET /api/tool_data: returns a list tool_data tables:

reload (*trans*, *args, **kwargs)

GET /api/tool_data/{id}/reload

Reloads a tool_data table.

show (*trans*, *args, **kwargs)

show_field (*trans*, *args, **kwargs)

GET /api/tool_data/<id>/fields/<value>

Get information about a partiular field in a tool_data table

tool_shed_repositories Module

class galaxy.webapps.galaxy.api.tool_shed_repositories.**ToolShedRepositoriesController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

RESTful controller for interactions with tool shed repositories.

exported_workflows (*trans*, *args, **kwargs)

GET /api/tool_shed_repositories/{encoded_tool_shed_repository_id}/exported_workflows

Display a list of dictionaries containing information about this tool shed repository's exported workflows.

Parameters **id** – the encoded id of the ToolShedRepository object

get_latest_installable_revision (*trans*, *args, **kwargs)

POST /api/tool_shed_repositories/get_latest_installable_revision Get the latest installable revision of a specified repository from a specified Tool Shed.

Parameters **key** – the current Galaxy admin user's API key

The following parameters are included in the payload. :param tool_shed_url (required): the base URL of the Tool Shed from which to retrieve the Repository revision. :param name (required): the name of the Repository :param owner (required): the owner of the Repository

import_workflow (*trans*, *args, **kwargs)

POST /api/tool_shed_repositories/import_workflow

Import the specified exported workflow contained in the specified installed tool shed repository into Galaxy.

Parameters

- **key** – the API key of the Galaxy user with which the imported workflow will be associated.

- **id** – the encoded id of the ToolShedRepository object

The following parameters are included in the payload. :param index: the index location of the workflow tuple in the list of exported workflows stored in the metadata for the specified repository

import_workflows (*trans, *args, **kwargs*)

POST /api/tool_shed_repositories/import_workflows

Import all of the exported workflows contained in the specified installed tool shed repository into Galaxy.

Parameters

- **key** – the API key of the Galaxy user with which the imported workflows will be associated.
- **id** – the encoded id of the ToolShedRepository object

index (*trans, *args, **kwargs*)

GET /api/tool_shed_repositories Display a list of dictionaries containing information about installed tool shed repositories.

install_repository_revision (*trans, *args, **kwargs*)

POST /api/tool_shed_repositories/install_repository_revision Install a specified repository revision from a specified tool shed into Galaxy.

Parameters **key** – the current Galaxy admin user’s API key

The following parameters are included in the payload. :param tool_shed_url (required): the base URL of the Tool Shed from which to install the Repository :param name (required): the name of the Repository :param owner (required): the owner of the Repository :param changeset_revision (required): the changeset_revision of the RepositoryMetadata object associated with the Repository :param new_tool_panel_section_label (optional): label of a new section to be added to the Galaxy tool panel in which to load

tools contained in the Repository. Either this parameter must be an empty string or the tool_panel_section_id parameter must be an empty string or both must be an empty string (both cannot be used simultaneously).

Parameters

- **(optional)** (*shed_tool_conf*) – id of the Galaxy tool panel section in which to load tools contained in the Repository. If this parameter is an empty string and the above new_tool_panel_section_label parameter is an empty string, tools will be loaded outside of any sections in the tool panel. Either this parameter must be an empty string or the tool_panel_section_id parameter must be an empty string of both must be an empty string (both cannot be used simultaneously).
- **(optional)** – Set to True if you want to install repository dependencies defined for the specified repository being installed. The default setting is False.
- **(optional)** – Set to True if you want to install tool dependencies defined for the specified repository being installed. The default setting is False.
- **(optional)** – The shed-related tool panel configuration file configured in the “tool_config_file” setting in the Galaxy config file (e.g., galaxy.ini). At least one shed-related tool panel config file is required to be configured. Setting this parameter to a specific file enables you to choose where the specified repository will be installed because the tool_path attribute of the <toolbox> from the specified file is used as the installation location (e.g., <toolbox tool_path=”../shed_tools”>). If this parameter is not set, a shed-related tool panel configuration file will be selected automatically.

install_repository_revisions (*trans, *args, **kwargs*)

POST /api/tool_shed_repositories/install_repository_revisions Install one or more specified repository revisions from one or more specified tool sheds into Galaxy. The received parameters must be ordered lists so that positional values in tool_shed_urls, names, owners and changeset_revisions are associated.

It's questionable whether this method is needed as the above method for installing a single repository can probably cover all desired scenarios. We'll keep this one around just in case...

Parameters key – the current Galaxy admin user's API key

The following parameters are included in the payload. :param tool_shed_urls: the base URLs of the Tool Sheds from which to install a specified Repository :param names: the names of the Repositories to be installed :param owners: the owners of the Repositories to be installed :param changeset_revisions: the changeset_revisions of each RepositoryMetadata object associated with each Repository to be installed :param new_tool_panel_section_label: optional label of a new section to be added to the Galaxy tool panel in which to load

tools contained in the Repository. Either this parameter must be an empty string or the tool_panel_section_id parameter must be an empty string, as both cannot be used.

Parameters

- **tool_panel_section_id** – optional id of the Galaxy tool panel section in which to load tools contained in the Repository. If not set, tools will be loaded outside of any sections in the tool panel. Either this parameter must be an empty string or the tool_panel_section_id parameter must be an empty string, as both cannot be used.
- **(optional) (shed_tool_conf)** – Set to True if you want to install repository dependencies defined for the specified repository being installed. The default setting is False.
- **(optional)** – Set to True if you want to install tool dependencies defined for the specified repository being installed. The default setting is False.
- **(optional)** – The shed-related tool panel configuration file configured in the “tool_config_file” setting in the Galaxy config file (e.g., galaxy.ini). At least one shed-related tool panel config file is required to be configured. Setting this parameter to a specific file enables you to choose where the specified repository will be installed because the tool_path attribute of the <toolbox> from the specified file is used as the installation location (e.g., <toolbox tool_path=”../shed_tools”>). If this parameter is not set, a shed-related tool panel configuration file will be selected automatically.

repair_repository_revision (*trans, *args, **kwargs*)

POST /api/tool_shed_repositories/repair_repository_revision Repair a specified repository revision previously installed into Galaxy.

Parameters key – the current Galaxy admin user's API key

The following parameters are included in the payload. :param tool_shed_url (required): the base URL of the Tool Shed from which the Repository was installed :param name (required): the name of the Repository :param owner (required): the owner of the Repository :param changeset_revision (required): the changeset_revision of the RepositoryMetadata object associated with the Repository

reset_metadata_on_installed_repositories (*trans, *args, **kwargs*)

PUT /api/tool_shed_repositories/reset_metadata_on_installed_repositories

Resets all metadata on all repositories installed into Galaxy in an “orderly fashion”.

Parameters **key** – the API key of the Galaxy admin user.

show (*trans*, **args*, ***kwargs*)

GET /api/tool_shed_repositories/{encoded_tool_shed_repository_id} Display a dictionary containing information about a specified tool_shed_repository.

Parameters **id** – the encoded id of the ToolShedRepository object

`galaxy.webapps.galaxy.api.tool_shed_repositories.get_message_for_no_shed_tool_config()`

tools Module

users Module

API operations on User objects.

class `galaxy.webapps.galaxy.api.users.UserAPIController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.UsesTagsMixin`, `galaxy.web.base.controller.CreatesUsersMixin`, `galaxy.web.base.controller.CreatesApiKeysMixin`

anon_user_api_value (*trans*)

Returns data for an anonymous user, truncated to only usage and quota_percent

api_key (*trans*, **args*, ***kwargs*)

POST /api/users/{encoded_user_id}/api_key Creates a new API key for specified user.

create (*trans*, **args*, ***kwargs*)

POST /api/users Creates a new Galaxy user.

delete (*trans*, **args*, ***kwargs*)

index (*trans*, **args*, ***kwargs*)

GET /api/users GET /api/users/deleted Displays a collection (list) of users.

show (*trans*, **args*, ***kwargs*)

GET /api/users/{encoded_user_id} GET /api/users/deleted/{encoded_user_id} GET /api/users/current
Displays information about a user.

undelete (*trans*, **args*, ***kwargs*)

update (*trans*, **args*, ***kwargs*)

visualizations Module

Visualizations resource control over the API.

NOTE!: this is a work in progress and functionality and data structures may change often.

class `galaxy.webapps.galaxy.api.visualizations.VisualizationsController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.UsesVisualizationsMixin`, `galaxy.web.base.controller.SharableMixin`, `galaxy.model.item_attrs.UsesAnnotations`

RESTful controller for interactions with visualizations.

create (*trans*, **args*, ***kwargs*)

POST /api/visualizations creates a new visualization using the given payload

POST /api/visualizations?import_id={encoded_visualization_id} imports a copy of an existing visualization into the user's workspace

```

index (trans, *args, **kwargs)
    GET /api/visualizations:

show (trans, *args, **kwargs)
    GET /api/visualizations/{viz_id}

update (trans, *args, **kwargs)
    PUT /api/visualizations/{encoded_visualization_id}

```

workflows Module

API operations for Workflows

```

class galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController (app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesStore, galaxy.model.item_attrs.UsesAnnotations, galaxy.web.base.controller.SharableMixin

```

```

build_module (trans, *args, **kwargs)
    POST /api/workflows/build_module Builds module details including a tool model for the workflow editor.

cancel_invocation (trans, *args, **kwargs)
    DELETE /api/workflows/{workflow_id}/invocation/{invocation_id} Cancel the specified workflow invocation.

```

Parameters

- **workflow_id** (*str*) – the workflow id (required)
- **invocation_id** (*str*) – the usage id (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

```

create (trans, *args, **kwargs)
    POST /api/workflows

```

Run or create workflows from the api.

If `installed_repository_file` or `from_history_id` is specified a new workflow will be created for this user. Otherwise, `workflow_id` must be specified and this API method will cause a workflow to execute.

:param `installed_repository_file` The path of a workflow to import. Either `workflow_id`, `installed_repository_file` or `from_history_id` must be specified :type `installed_repository_file` str

Parameters

- **workflow_id** (*str*) – An existing workflow id. Either `workflow_id`, `installed_repository_file` or `from_history_id` must be specified
- **parameters** (*dict*) – If `workflow_id` is set - see `_update_step_parameters()`
- **ds_map** (*dict*) – If `workflow_id` is set - a dictionary mapping each input step id to a dictionary with 2 keys: ‘src’ (which can be ‘ldda’, ‘ld’ or ‘hda’) and ‘id’ (which should be the id of a LibraryDatasetDatasetAssociation, LibraryDataset or HistoryDatasetAssociation respectively)
- **no_add_to_history** (*str*) – If `workflow_id` is set - if present in the payload with any value, the input datasets will not be added to the selected history
- **history** (*str*) – If `workflow_id` is set - optional history where to run the workflow, either the name of a new history or “hist_id=HIST_ID” where HIST_ID is the id of an existing history. If not specified, the workflow will be run a new unnamed history

- **replacement_params** (*dict*) – If workflow_id is set - an optional dictionary used when renaming datasets
- **from_history_id** (*str*) – Id of history to extract a workflow from. Either workflow_id, installed_repository_file or from_history_id must be specified
- **job_ids** (*str*) – If from_history_id is set - optional list of jobs to include when extracting a workflow from history
- **dataset_ids** (*str*) – If from_history_id is set - optional list of HDA ‘hid’s corresponding to workflow inputs when extracting a workflow from history
- **dataset_collection_ids** (*str*) – If from_history_id is set - optional list of HDCA ‘hid’s corresponding to workflow inputs when extracting a workflow from history
- **workflow_name** (*str*) – If from_history_id is set - name of the workflow to create when extracting a workflow from history

delete (*trans*, **args*, ***kwargs*)

DELETE /api/workflows/{encoded_workflow_id} Deletes a specified workflow Author: rpark
copied from galaxy.web.controllers.workflows.py (delete)

import_new_workflow_deprecated (*trans*, **args*, ***kwargs*)

POST /api/workflows/upload Importing dynamic workflows from the api. Return newly generated workflow id. Author: rpark

currently assumes payload[‘workflow’] is a json representation of a workflow to be inserted into the database

Deprecated in favor of POST /api/workflows with encoded ‘workflow’ in payload the same way.

import_shared_workflow_deprecated (*trans*, **args*, ***kwargs*)

POST /api/workflows/import Import a workflow shared by other users.

Parameters **workflow_id** (*str*) – the workflow id (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

index (*trans*, **args*, ***kwargs*)

GET /api/workflows

Displays a collection of workflows.

Parameters **show_published** (*boolean*) – if True, show also published workflows

index_invocations (*trans*, **args*, ***kwargs*)

GET /api/workflows/{ workflow_id }/invocations

Get the list of the workflow invocations

Parameters **workflow_id** (*str*) – the workflow id (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

invocation_step (*trans*, **args*, ***kwargs*)

GET /api/workflows/{ workflow_id }/invocation/{ invocation_id }/steps/{ step_id }

Parameters

- **workflow_id** (*str*) – the workflow id (required)
- **invocation_id** (*str*) – the invocation id (required)
- **step_id** (*str*) – encoded id of the WorkflowInvocationStep (required)

- **payload** – payload containing update action information for running workflow.

Raises exceptions.MessageException, exceptions.ObjectNotFound

invoke (*trans*, **args*, ***kwargs*)

POST /api/workflows/{encoded_workflow_id}/invocations

Schedule the workflow specified by *workflow_id* to run.

show (*trans*, **args*, ***kwargs*)

GET /api/workflows/{encoded_workflow_id}

Displays information needed to run a workflow from the command line.

show_invocation (*trans*, **args*, ***kwargs*)

GET /api/workflows/{workflow_id}/invocation/{invocation_id} Get detailed description of workflow invocation

Parameters

- **workflow_id** (*str*) – the workflow id (required)
- **invocation_id** (*str*) – the invocation id (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

update (*trans*, **args*, ***kwargs*)

•PUT /api/workflows/{id} updates the workflow stored with *id*

Parameters

- **id** (*str*) – the encoded id of the workflow to update
- **payload** (*dict*) – a dictionary containing any or all the * workflow the json description of the workflow as would be

produced by GET workflows/<id>/download or given to *POST workflows*

The workflow contents will be updated to target this.

Return type dict

Returns serialized version of the workflow

update_invocation_step (*trans*, **args*, ***kwargs*)

PUT /api/workflows/{workflow_id}/invocation/{invocation_id}/steps/{step_id} Update state of running workflow step invocation - still very nebulous but this would be for stuff like confirming paused steps can proceed etc....

Parameters

- **workflow_id** (*str*) – the workflow id (required)
- **invocation_id** (*str*) – the usage id (required)
- **step_id** (*str*) – encoded id of the WorkflowInvocationStep (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

workflow_dict (*trans*, **args*, ***kwargs*)

GET /api/workflows/{encoded_workflow_id}/download Returns a selected workflow as a json dictionary.

1.2 lib

1.2.1 fpconst Module

1.2.2 galaxy Package

galaxy Package

Galaxy root package – this is a namespace package.

app Module

config Module

Universe configuration builder.

```
class galaxy.config.Configuration (**kwargs)
    Bases: object

    check()

    deprecated_options = ('database_file',)

    ensure_tempdir()

    get(key, default)

    get_bool(key, default)

    guess_galaxy_port()

    is_admin_user(user)
        Determine if the provided user is listed in admin_users.

        NOTE: This is temporary, admin users will likely be specified in the database in the future.

    resolve_path(path)
        Resolve a path relative to Galaxy's root.

    sentry_dsn_public
        Sentry URL with private key removed for use in client side scripts, sentry server will need to be configured
        to accept events

class galaxy.config.ConfiguresGalaxyMixin
    Shared code for configuring Galaxy-like app objects.

    reindex_tool_search()

galaxy.config.configure_logging(config)
    Allow some basic logging configuration to be read from ini file.

galaxy.config.get_database_engine_options(kwargs, model_prefix='')
    Allow options for the SQLAlchemy database engine to be passed by using the prefix "database_engine_option".

galaxy.config.resolve_path(path, root)
    If 'path' is relative make absolute by prepending 'root'
```

Subpackages

actions Package

admin Module	Contains administrative functions
---------------------	-----------------------------------

```
class galaxy.actions.admin.AdminActions
```

Bases: object

Mixin for controllers that provide administrative functionality.

datatypes Package

assembly Module velvet datatypes James E Johnson - University of Minnesota for velvet assembler tool in galaxy

```
class galaxy.datatypes.assembly.Amos (**kwd)
```

Bases: `galaxy.datatypes.data.Text`

Class describing the AMOS assembly file

```
edam_format = 'format_2561'
```

```
file_ext = 'afg'
```

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

sniff (*filename*)

Determines whether the file is an amos assembly file format Example:

[illegible]

```
class galaxy.datatypes.assembly.Roadmaps (**kwd)
```

Bases: `galaxy.datatypes.data.Text`

Class describing the Sequences file generated by velveth

```
edam_format = 'format_2561'
```

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

sniff (*filename*)

Determines whether the file is a velveth produced RoadMap:: 142858 21 1 ROADMAP 1
ROADMAP 2 ...

class galaxy.datatypes.assembly.**Sequences** (**kwd)

Bases: *galaxy.datatypes.sequence.Fasta*

Class describing the Sequences file generated by velveth

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

sniff (filename)

Determines whether the file is a velveth produced fasta format The id line has 3 fields separated by tabs:
sequence_name sequence_index category:

```
>SEQUENCE_0_length_35 1 1
GGATATAGGGCCAACCAACTCAACGGCCTGTCTT
>SEQUENCE_1_length_35 2 1
CGACGAATGACAGGTCACGAATTGGCGGGGATTA
```

class galaxy.datatypes.assembly.**Velvet** (**kwd)

Bases: *galaxy.datatypes.images.Html*

allow_datatype_change = False

composite_type = 'auto_primary_file'

file_ext = 'html'

generate_primary_file (dataset=None)

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

regenerate_primary_file (dataset)

cannot do this until we are setting metadata

set_meta (dataset, **kwd)

binary Module Binary classes

class galaxy.datatypes.binary.**Ab1** (**kwd)

Bases: *galaxy.datatypes.binary.Binary*

Class describing an ab1 binary sequence file

display_peek (dataset)

file_ext = 'ab1'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

set_peek (dataset, is_multi_byte=False)

class galaxy.datatypes.binary.**Bam** (**kwd)

Bases: *galaxy.datatypes.binary.Binary*

Class describing a BAM binary file

column_dataprovider (*args, **kwargs)

data_sources = {'index': 'bigwig', 'data': 'bai'}

dataproviders = {'chunk64': <function chunk64_dataprovider at 0x7f36a1a836e0>, 'id-seq-qual': <function id_seq_qual_dataprovider at 0x7f36a1a836e0>}

dataset_content_needs_grooming (file_name)

See if file_name is a sorted BAM file


```

dict_dataprovider (*args, **kwargs)

display_peek (dataset)

edam_format = 'format_2572'

file_ext = 'bam'

genomic_region_dataprovider (*args, **kwargs)

genomic_region_dict_dataprovider (*args, **kwargs)

groom_dataset_content (file_name)
    Ensures that the Bam file contents are sorted. This function is called on an output dataset after the content
    is initially generated.

header_dataprovider (*args, **kwargs)

id_seq_qual_dataprovider (*args, **kwargs)

init_meta (dataset, copy_from=None)

line_dataprovider (*args, **kwargs)

static merge (split_files, output_file)

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', bam_index (FileParameter): BAM Index

regex_line_dataprovider (*args, **kwargs)

samtools_dataprovider (*args, **kwargs)
    Generic samtools interface - all options available through settings.

set_meta (dataset, overwrite=True, **kwd)
    Creates the index for the BAM file.

set_peek (dataset, is_multi_byte=False)

sniff (filename)

track_type = 'ReadTrack'

class galaxy.datatypes.binary.Bcf (**kwd)
    Bases: galaxy.datatypes.binary.Binary
    Class describing a BCF file
    edam_format = 'format_3020'
    file_ext = 'bcf'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', bcf_index (FileParameter): BCF Index FI
    set_meta (dataset, overwrite=True, **kwd)
        Creates the index for the BCF file.
    sniff (filename)

class galaxy.datatypes.binary.BigBed (**kwd)
    Bases: galaxy.datatypes.binary.BigWig
    BigBed support from UCSC.
    data_sources = {'data_standalone': 'bigbed'}
    edam_format = 'format_3004'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

```

```
class galaxy.datatypes.binary.BigWig(**kwd)
    Bases: galaxy.datatypes.binary.Binary

    Accessing binary BigWig files from UCSC. The supplemental info in the paper has the binary details:
    http://bioinformatics.oxfordjournals.org/cgi/content/abstract/btq351v1

    data_sources = {'data_standalone': 'bigwig'}

    display_peek(dataset)

    edam_format = 'format_3006'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    set_peek(dataset, is_multi_byte=False)

    sniff(filename)

    track_type = 'LineTrack'

class galaxy.datatypes.binary.Binary(**kwd)
    Bases: galaxy.datatypes.data.Data

    Binary data

    display_data(trans, dataset, preview=False, filename=None, to_ext=None, size=None, off-
        set=None, **kwd)

    edam_format = 'format_2333'

    get_mime()
        Returns the mime type of the datatype

    static is_ext_unsniffable(ext)

    static is_sniffable_binary(filename)

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    static register_sniffable_binary_format(data_type, ext, type_class)

    static register_unsniffable_binary_ext(ext)

    set_peek(dataset, is_multi_byte=False)
        Set the peek and blurb text

    sniffable_binary_formats = [{'ext': 'idat', 'type': 'idat', 'class': <class 'galaxy.datatypes.binary.Idat'>}, {'ext': 'b
    unsniffable_binary_formats = ['ab1', 'compressed_archive', 'asn1-binary', 'h5', 'scf', 'hmmcompress']

class galaxy.datatypes.binary.CompressedArchive(**kwd)
    Bases: galaxy.datatypes.binary.Binary

    Class describing an compressed binary file This class can be subclass'ed to implement archive filetypes that will
    not be unpacked by upload.py.

    compressed = True

    display_peek(dataset)

    file_ext = 'compressed_archive'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    set_peek(dataset, is_multi_byte=False)
```

```

class galaxy.datatypes.binary.GeminiSQLite(**kwd)
    Bases: galaxy.datatypes.binary.SQLite
    Class describing a Gemini Sqlite database
    display_peek(dataset)
    file_ext = 'gemini.sqlite'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', tables (ListParameter): Database Tables,
    set_meta(dataset, overwrite=True, **kwd)
    set_peek(dataset, is_multi_byte=False)
    sniff(filename)

class galaxy.datatypes.binary.GenericAsn1Binary(**kwd)
    Bases: galaxy.datatypes.binary.Binary
    Class for generic ASN.1 binary format
    file_ext = 'asn1-binary'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

class galaxy.datatypes.binary.H5(**kwd)
    Bases: galaxy.datatypes.binary.Binary
    Class describing an HDF5 file
    display_peek(dataset)
    file_ext = 'h5'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
    set_peek(dataset, is_multi_byte=False)

class galaxy.datatypes.binary.Idat(**kwd)
    Bases: galaxy.datatypes.binary.Binary
    Binary data in idat format
    file_ext = 'idat'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
    sniff(filename)

class galaxy.datatypes.binary.RData(**kwd)
    Bases: galaxy.datatypes.binary.Binary
    Generic R Data file datatype implementation
    file_ext = 'rdata'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
    sniff(filename)

class galaxy.datatypes.binary.SQLite(**kwd)
    Bases: galaxy.datatypes.binary.Binary
    Class describing a Sqlite database
    dataproviders = {'chunk64': <function chunk64_dataprovider at 0x7f36a1a836e0>, 'chunk': <function chunk_dataprovider at 0x7f36a1a836e0>}
    display_peek(dataset)

```

```
file_ext = 'sqlite'
init_meta (dataset, copy_from=None)
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', tables (ListParameter): Database Tables,
set_meta (dataset, overwrite=True, **kwd)
set_peek (dataset, is_multi_byte=False)
sniff (filename)
sqlite_datadictprovider (*args, **kwargs)
sqlite_dataprovider (*args, **kwargs)
sqlite_datatableprovider (*args, **kwargs)
class galaxy.datatypes.binary.Scf (**kwd)
    Bases: galaxy.datatypes.binary.Binary
    Class describing an scf binary sequence file
    display_peek (dataset)
    edam_format = 'format_1632'
    file_ext = 'scf'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
    set_peek (dataset, is_multi_byte=False)
class galaxy.datatypes.binary.Sff (**kwd)
    Bases: galaxy.datatypes.binary.Binary
    Standard Flowgram Format (SFF)
    display_peek (dataset)
    edam_format = 'format_3284'
    file_ext = 'sff'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
    set_peek (dataset, is_multi_byte=False)
    sniff (filename)
class galaxy.datatypes.binary.Sra (**kwd)
    Bases: galaxy.datatypes.binary.Binary
    Sequence Read Archive (SRA) datatype originally from mdshw5/sra-tools-galaxy
    display_peek (dataset)
    file_ext = 'sra'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
    set_peek (dataset, is_multi_byte=False)
    sniff (filename)
    The first 8 bytes of any NCBI sra file is 'NCBI.sra', and the file is binary. For details about the format, see
    http://www.ncbi.nlm.nih.gov/books/n/helpsra/SRA\_Overview\_BK/#SRA\_Overview\_BK.4\_SRA\_Data\_Structure
```

```

class galaxy.datatypes.binary.TwoBit (**kwd)
    Bases: galaxy.datatypes.binary.Binary

    Class describing a TwoBit format nucleotide file

    display_peek (dataset)

    edam_format = 'format_3009'

    file_ext = 'twobit'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    set_peek (dataset, is_multi_byte=False)

    sniff (filename)

class galaxy.datatypes.binary.Xlsx (**kwd)
    Bases: galaxy.datatypes.binary.Binary

    Class for Excel 2007 (xlsx) files

    file_ext = 'xlsx'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename)

```

checkers Module

```

galaxy.datatypes.checkers.check_binary (name, file_path=True)
galaxy.datatypes.checkers.check_bz2 (file_path)
galaxy.datatypes.checkers.check_gzip (file_path)
galaxy.datatypes.checkers.check_html (file_path, chunk=None)
galaxy.datatypes.checkers.check_image (file_path)
galaxy.datatypes.checkers.check_zip (file_path)
galaxy.datatypes.checkers.is_bz2 (file_path)
galaxy.datatypes.checkers.is_gzip (file_path)

```

chrominfo Module

```

class galaxy.datatypes.chrominfo.ChromInfo (**kwd)
    Bases: galaxy.datatypes.tabular.Tabular

    file_ext = 'len'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

```

coverage Module Coverage datatypes

```

class galaxy.datatypes.coverage.LastzCoverage (**kwd)
    Bases: galaxy.datatypes.tabular.Tabular

    file_ext = 'coverage'

    get_track_resolution (dataset, start, end)

    get_track_window (dataset, data, start, end)
        Assumes we have a numpy file.

```

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

data Module

class galaxy.datatypes.data.Data (**kwd)

Bases: object

Base class for all datatypes. Implements basic interfaces as well as class methods for metadata.

```
>>> class DataTest( Data ):
...     MetadataElement( name="test" )
...
>>> DataTest.metadata_spec.test.name
'test'
>>> DataTest.metadata_spec.test.desc
'test'
>>> type( DataTest.metadata_spec.test.param )
<class 'galaxy.datatypes.metadata.MetadataParameter'>
```

CHUNKABLE = False

add_composite_file (name, **kws)

add_display_app (app_id, label, file_function, links_function)

Adds a display app to the datatype. app_id is a unique id label is the primary display label, e.g., display at 'UCSC' file_function is a string containing the name of the function that returns a properly formatted display links_function is a string containing the name of the function that returns a list of (link_name,link)

add_display_application (display_application)

New style display applications

after_setting_metadata (dataset)

This function is called on the dataset after metadata is set.

allow_datatype_change = True

as_display_type (dataset, type, **kwd)

Returns modified file contents for a particular display type

base_dataprovider (*args, **kwargs)

before_setting_metadata (dataset)

This function is called on the dataset before metadata is set.

chunk64_dataprovider (*args, **kwargs)

chunk_dataprovider (*args, **kwargs)

clear_display_apps ()

composite_files = {}

composite_type = None

convert_dataset (trans, original_dataset, target_type, return_output=False, visible=True, deps=None, set_output_history=True)

This function adds a job to the queue to convert a dataset to another type. Returns a message about success/failure.

copy_safe_peek = True

data_sources = {}

dataprovider (*dataset, data_format, **settings*)

Base dataprovider factory for all datatypes that returns the proper provider for the given *data_format* or raises a *NoProviderAvailable*.

dataproviders = {'chunk64': <function chunk64_dataprovider at 0x7f36a1a836e0>, 'base': <function base_dataprovider at 0x7f36a1a836e0>}

dataset_content_needs_grooming (*file_name*)

This function is called on an output dataset file after the content is initially generated.

display_data (*trans, data, preview=False, filename=None, to_ext=None, size=None, offset=None, **kwd*)

Old display method, for transition - though still used by API and test framework. Datatypes should be very careful if overriding this method and this interface between datatypes and Galaxy will likely change.

TOOD: Document alternatives to overriding this method (data providers?).

display_info (*dataset*)

Returns formatted html of dataset info

display_name (*dataset*)

Returns formatted html of dataset name

display_peek (*dataset*)

Create HTML table, used for displaying peek

edam_format = 'format_1915'

find_conversion_destination (*dataset, accepted_formats, datatypes_registry, **kwd*)

Returns (target_ext, existing converted dataset)

generate_auto_primary_file (*dataset=None*)

get_composite_files (*dataset=None*)

get_converter_types (*original_dataset, datatypes_registry*)

Returns available converters by type for this dataset

get_display_application (*key, default=None*)

get_display_applications_by_dataset (*dataset, trans*)

get_display_label (*type*)

Returns primary label for display app

get_display_links (*dataset, type, app, base_url, target_frame='_blank', **kwd*)

Returns a list of tuples of (name, link) for a particular display type. No check on 'access' permissions is done here - if you can view the dataset, you can also save it or send it to a destination outside of Galaxy, so Galaxy security restrictions do not apply anyway.

get_display_types ()

Returns display types available

get_max_optional_metadata_filesize ()

get_mime ()

Returns the mime type of the datatype

get_raw_data (*dataset*)

Returns the full data. To stream it open the file_name and read/write as needed

get_visualizations (*dataset*)

Returns a list of visualizations for datatype.

groom_dataset_content (*file_name*)

This function is called on an output dataset file if dataset_content_needs_grooming returns True.

has_dataprovider (*data_format*)
Returns True if *data_format* is available in *dataproviders*.

has_resolution

init_meta (*dataset*, *copy_from=None*)

is_binary = True

matches_any (*target_datatypes*)
Check if this datatype is of any of the *target_datatypes* or is a subtype thereof.

max_optional_metadata_filesize

static merge (*split_files*, *output_file*)
Merge files with `copy.copyfileobj()` will not hit the max argument limitation of `cat`. `gz` and `bz2` files are also working.

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
dictionary of metadata fields for this datatype:

missing_meta (*dataset*, *check=[]*, *skip=[]*)
Checks for empty metadata values, Returns True if non-optional metadata is missing Specifying a list of 'check' values will only check those names provided; when used, optionality is ignored Specifying a list of 'skip' items will return True even when a named metadata value is missing

primary_file_name = 'index'

remove_display_app (*app_id*)
Removes a display app from the datatype

repair_methods (*dataset*)
Unimplemented method, returns dict with method/option for repairing errors

set_max_optional_metadata_filesize (*max_value*)

set_meta (*dataset*, *overwrite=True*, ***kwd*)
Unimplemented method, allows guessing of metadata from contents of file

set_peek (*dataset*, *is_multi_byte=False*)
Set the peek and blurb text

set_raw_data (*dataset*, *data*)
Saves the data on the disc

supported_display_apps = {}

track_type = None

validate (*dataset*)
Unimplemented validate, return no exceptions

writable_files

write_from_stream (*dataset*, *stream*)
Writes data from a stream

class `galaxy.datatypes.data.DataMeta` (*name*, *bases*, *dict_*)
Bases: `type`

Metaclass for Data class. Sets up metadata spec.

class `galaxy.datatypes.data.GenericAsn1` (***kwd*)
Bases: `galaxy.datatypes.data.Text`

Class for generic ASN.1 text format


```

    file_ext = 'asn1'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

class galaxy.datatypes.data.LineCount (**kwd)
    Bases: galaxy.datatypes.data.Text

    Dataset contains a single line with a single integer that denotes the line count for a related dataset. Used for custom builds.

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

class galaxy.datatypes.data.Newick (**kwd)
    Bases: galaxy.datatypes.data.Text

    New Hampshire/Newick Format

    edam_format = 'format_1910'

    file_ext = 'nhx'

    get_visualizations (dataset)
        Returns a list of visualizations for datatype.

    init_meta (dataset, copy_from=None)

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

    sniff (filename)
        Returning false as the newick format is too general and cannot be sniffed.

class galaxy.datatypes.data.Nexus (**kwd)
    Bases: galaxy.datatypes.data.Text

    Nexus format as used By Paup, Mr Bayes, etc

    edam_format = 'format_1912'

    file_ext = 'nex'

    get_visualizations (dataset)
        Returns a list of visualizations for datatype.

    init_meta (dataset, copy_from=None)

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

    sniff (filename)
        All Nexus Files Simply puts a '#NEXUS' in its first line

class galaxy.datatypes.data.Text (**kwd)
    Bases: galaxy.datatypes.data.Data

    count_data_lines (dataset)
        Count the number of lines of data in dataset, skipping all blank lines and comments.

    dataproviders = {'chunk64': <function chunk64_dataprovider at 0x7f36a1a836e0>, 'base': <function base_dataprovider at 0x7f36a1a836e0>}

    edam_format = 'format_2330'

    estimate_file_lines (dataset)
        Perform a rough estimate by extrapolating number of lines from a small read.

    file_ext = 'txt'

    get_mime ()
        Returns the mime type of the datatype

```

```

line_class = 'line'

line_dataprovider (*args, **kwargs)
    Returns an iterator over the dataset's lines (that have been 'strip'ed) optionally excluding blank lines and
    lines that start with a comment character.

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of
    lines to read

regex_line_dataprovider (*args, **kwargs)
    Returns an iterator over the dataset's lines optionally including/excluding lines that match one or more
    regex filters.

set_meta (dataset, **kwd)
    Set the number of lines of data in dataset.

set_peek (dataset, line_count=None, is_multi_byte=False, WIDTH=256, skipchars=[])
    Set the peek. This method is used by various subclasses of Text.

set_raw_data (dataset, data)
    Saves the data on the disc

classmethod split (input_datasets, subdir_generator_function, split_params)
    Split the input files by line.

write_from_stream (dataset, stream)
    Writes data from a stream

galaxy.datatypes.data.get_file_peek (file_name, is_multi_byte=False, WIDTH=256,
                                     LINE_COUNT=5, skipchars=[])
    Returns the first LINE_COUNT lines wrapped to WIDTH

    ## >>> fname = get_test_fname('4.bed') ## >>> get_file_peek(fname) ## 'chr22 30128507
    31828507 uc003bnx.1_cds_2_0_chr22_29227_f0 +
    '

galaxy.datatypes.data.get_test_fname (fname)
    Returns test data filename

```

genetics Module rgenetics datatypes Use at your peril Ross Lazarus for the rgenetics and galaxy projects

genome graphs datatypes derived from Interval datatypes genome graphs datasets have a header row with appropriate columnnames The first column is always the marker - eg columnname = rs, first row= rs12345 if the rows are snps subsequent row values are all numeric ! Will fail if any non numeric (eg '+' or 'NA') values ross lazarus for rgenetics august 20 2007

```

class galaxy.datatypes.genetics.Affybatch (**kwd)
    Bases: galaxy.datatypes.genetics.RexpBase
    derived class for BioC data structures in Galaxy

    file_ext = 'affybatch'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of
        lines to read

class galaxy.datatypes.genetics.Eigenstratgeno (**kwd)
    Bases: galaxy.datatypes.genetics.Rgenetics
    Eigenstrat format - may be able to get rid of this if we move to shellfish Rgenetics data collections

    file_ext = 'eigenstratgeno'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of
        lines to read

```

```

class galaxy.datatypes.genetics.Eigenstratpca (**kwd)
    Bases: galaxy.datatypes.genetics.Rgenetics

    Eigenstrat PCA file for case control adjustment Rgenetics data collections

    file_ext = 'eigenstratpca'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

class galaxy.datatypes.genetics.Eset (**kwd)
    Bases: galaxy.datatypes.genetics.RexpBase

    derived class for BioC data structures in Galaxy

    file_ext = 'eset'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

class galaxy.datatypes.genetics.Fped (**kwd)
    Bases: galaxy.datatypes.genetics.Rgenetics

    FBAT pedigree format - single file, map is header row of rs numbers. Strange. Rgenetics data collections

    file_ext = 'fped'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

class galaxy.datatypes.genetics.Fphe (**kwd)
    Bases: galaxy.datatypes.genetics.Rgenetics

    fbat pedigree file - mad format with ! as first char on header row Rgenetics data collections

    file_ext = 'fphe'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

class galaxy.datatypes.genetics.GenomeGraphs (**kwd)
    Bases: galaxy.datatypes.tabular.Tabular

    Tab delimited data containing a marker id and any number of numeric values

    as_ucsc_display_file (dataset, **kwd)
        Returns file

    file_ext = 'gg'

    get_mime ()
        Returns the mime type of the datatype

    make_html_table (dataset, skipchars=[])
        Create HTML table, used for displaying peek

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

    set_meta (dataset, **kwd)

    sniff (filename)
        Determines whether the file is in gg format

    ucsc_links (dataset, type, app, base_url)
        from the ever-helpful angie hinrichs angie@soe.ucsc.edu a genome graphs call looks like this

        http://genome.ucsc.edu/cgi-bin/hgGenome?clade=mammal&org=Human&db=hg18&hgGenome\_dataSetName=dname&hgGenome\_dataSetDescription=test&hgGenome\_formatType=best%20guess&hgGenome\_markerType=best%20guess&hgGenome\_columnLabels=best%20guess&hgGenome\_maxVal=&hgGenome\_labelVals=&hgGenome\_maxGapToFill=25000000&hgGenome\_uploadFile=http://galaxy.esphealth.org/datasets/333/display/index&hgGenome\_doSubmitUpload=submit

```

Galaxy gives this for an interval file

http://genome.ucsc.edu/cgi-bin/hgTracks?db=hg18&position=chr1:1-1000&hgt.customText=http%3A%2F%2Fgalaxy.esphealth.org%2Fdisplay_as%3Fid%3D339%26display_app%3Ducsc

validate (*dataset*)

Validate a gg file - all numeric after header row

class `galaxy.datatypes.genetics.Lped` (***kwd*)

Bases: `galaxy.datatypes.genetics.Rgenetics`

linkage pedigree (ped,map) Rgenetics data collections

file_ext = 'lped'

metadata_spec = **dbkey** (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines

class `galaxy.datatypes.genetics.MAlist` (***kwd*)

Bases: `galaxy.datatypes.genetics.RexpBase`

derived class for BioC data structures in Galaxy

file_ext = 'malist'

metadata_spec = **dbkey** (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines

class `galaxy.datatypes.genetics.Pbed` (***kwd*)

Bases: `galaxy.datatypes.genetics.Rgenetics`

Plink Binary compressed 2bit/geno Rgenetics data collections

file_ext = 'pbed'

metadata_spec = **dbkey** (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines

class `galaxy.datatypes.genetics.Phe` (***kwd*)

Bases: `galaxy.datatypes.genetics.Rgenetics`

Phenotype file

file_ext = 'phe'

metadata_spec = **dbkey** (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines

class `galaxy.datatypes.genetics.Pheno` (***kwd*)

Bases: `galaxy.datatypes.tabular.Tabular`

base class for pheno files

file_ext = 'pheno'

metadata_spec = **dbkey** (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines

class `galaxy.datatypes.genetics.Pphe` (***kwd*)

Bases: `galaxy.datatypes.genetics.Rgenetics`

Plink phenotype file - header must have FID IID... Rgenetics data collections

file_ext = 'pphe'

metadata_spec = **dbkey** (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines

class `galaxy.datatypes.genetics.RexpBase` (***kwd*)

Bases: `galaxy.datatypes.images.Html`

base class for BioC data structures in Galaxy must be constructed with the pheno data in place since that goes into the metadata for each instance

```

allow_datatype_change = False

composite_type = 'auto_primary_file'

display_peek (dataset)
    Returns formatted html of peek

file_ext = 'rexpbase'

generate_primary_file (dataset=None)
    This is called only at upload to write the html file cannot rename the datasets here - they come with the
    default unfortunately

get_file_peek (filename)
    can't really peek at a filename - need the extra_files_path and such?

get_mime ()
    Returns the mime type of the datatype

get_peek (dataset)
    expects a .pheno file in the extra_files_dir - ugh

get_phecols (phenolist=[], maxConc=20)
    sept 2009: cannot use whitespace to split - make a more complex structure here and adjust the methods
    that rely on this structure return interesting phenotype column names for an rexpession eset or affybatch
    to use in array subsetting and so on. Returns a data structure for a dynamic Galaxy select parameter. A
    column with only 1 value doesn't change, so is not interesting for analysis. A column with a different
    value in every row is equivalent to a unique identifier so is also not interesting for anova or limma analysis
    - both these are removed after the concordance (count of unique terms) is constructed for each column.
    Then a complication - each remaining pair of columns is tested for redundancy - if two columns are always
    paired, then only one is needed :)

get_pheno (dataset)
    expects a .pheno file in the extra_files_dir - ugh note that R is wierd and adds the row.name in
    the header so the columns are all wrong - unless you tell it not to. A file can be written as
    write.table(file='foo.pheno',pData(foo),sep=' ',quote=F,row.names=F)

html_table = None

init_meta (dataset, copy_from=None)

is_binary = True

make_html_table (pp='nothing supplied from peek\n')
    Create HTML table, used for displaying peek

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

regenerate_primary_file (dataset)
    cannot do this until we are setting metadata

set_meta (dataset, **kwd)
    NOTE we apply the tabular machinery to the phenodata extracted from a BioC eSet or affybatch.

set_peek (dataset, **kwd)
    expects a .pheno file in the extra_files_dir - ugh note that R is weird and does not include the row.name in
    the header. why?

class galaxy.datatypes.genetics.Rgenetics (**kwd)
    Bases: galaxy.datatypes.images.Html

    base class to use for rgenetics datatypes derived from html - composite datatype elements stored in extra files
    path

```

```
allow_datatype_change = False
composite_type = 'auto_primary_file'
file_ext = 'rgenetics'
generate_primary_file (dataset=None)
get_mime ()
    Returns the mime type of the datatype
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number
regenerate_primary_file (dataset)
    cannot do this until we are setting metadata
set_meta (dataset, **kwd)
    for lped/pbed eg
```

class galaxy.datatypes.genetics.**SNPMatrix** (**kwd)
Bases: *galaxy.datatypes.genetics.Rgenetics*
BioC SNPMatrix Rgenetics data collections

```
file_ext = 'snpmatrix'
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number
set_peek (dataset, **kwd)
sniff (filename)
    need to check the file header hex code
```

class galaxy.datatypes.genetics.**Snptest** (**kwd)
Bases: *galaxy.datatypes.genetics.Rgenetics*
BioC snptest Rgenetics data collections

```
file_ext = 'snptest'
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number
```

class galaxy.datatypes.genetics.**ldIndep** (**kwd)
Bases: *galaxy.datatypes.genetics.Rgenetics*
LD (a good measure of redundancy of information) depleted Plink Binary compressed 2bit/geno This is really a plink binary, but some tools work better with less redundancy so are constrained to these files

```
file_ext = 'ldreduced'
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number
```

class galaxy.datatypes.genetics.**rgFeatureList** (**kwd)
Bases: *galaxy.datatypes.genetics.rgTabList*
for featureid lists of exclusions or inclusions in the clean tool output from QC eg low maf, high missingness, bad hwe in controls, excess mendel errors,... featureid subsets on statistical criteria -> specialized display such as gg same infrastructure for expression?

```
file_ext = 'rgFList'
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number
```

class galaxy.datatypes.genetics.**rgSampleList** (**kwd)
Bases: *galaxy.datatypes.genetics.rgTabList*

for sampleid exclusions or inclusions in the clean tool output from QC eg excess het, gender error, ibd pair member, eigen outlier, excess mendel errors,... since they can be uploaded, should be flexible but they are persistent at least same infrastructure for expression?

file_ext = 'rgSList'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

sniff (filename)

class galaxy.datatypes.genetics.**rgTabList** (**kwd)

Bases: *galaxy.datatypes.tabular.Tabular*

for sampleid and for featureid lists of exclusions or inclusions in the clean tool featureid subsets on statistical criteria -> specialized display such as gg

display_peek (dataset)

Returns formatted html of peek

file_ext = 'rgTList'

get_mime ()

Returns the mime type of the datatype

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

images Module Image classes

class galaxy.datatypes.images.**Bmp** (**kwd)

Bases: *galaxy.datatypes.images.Image*

file_ext = 'bmp'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

sniff (filename, image=None)

Determine if the file is in bmp format.

class galaxy.datatypes.images.**Eps** (**kwd)

Bases: *galaxy.datatypes.images.Image*

edam_format = 'format_3466'

file_ext = 'eps'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

sniff (filename, image=None)

Determine if the file is in eps format.

class galaxy.datatypes.images.**Gif** (**kwd)

Bases: *galaxy.datatypes.images.Image*

edam_format = 'format_3467'

file_ext = 'gif'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

sniff (filename, image=None)

Determine if the file is in gif format.

class galaxy.datatypes.images.**Gmaj** (**kwd)

Bases: *galaxy.datatypes.data.Data*

Class describing a GMAJ Applet

```
copy_safe_peek = False
```

```
display_peek (dataset)
```

```
edam_format = 'format_3547'
```

```
file_ext = 'gmaj.zip'
```

```
get_mime ()
```

Returns the mime type of the datatype

```
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
```

```
set_peek (dataset, is_multi_byte=False)
```

```
sniff (filename)
```

NOTE: the sniff.convert_newlines() call in the upload utility will keep Gmaj data types from being correctly sniffed, but the files can be uploaded (they'll be sniffed as 'txt'). This sniff function is here to provide an example of a sniffer for a zip file.

```
class galaxy.datatypes.images.Html (**kwd)
```

Bases: *galaxy.datatypes.data.Text*

Class describing an html file

```
edam_format = 'format_2331'
```

```
file_ext = 'html'
```

```
get_mime ()
```

Returns the mime type of the datatype

```
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to peek
```

```
set_peek (dataset, is_multi_byte=False)
```

```
sniff (filename)
```

Determines whether the file is in html format

```
>>> fname = get_test_fname( 'complete.bed' )
>>> Html().sniff( fname )
False
>>> fname = get_test_fname( 'file.html' )
>>> Html().sniff( fname )
True
```

```
class galaxy.datatypes.images.Im (**kwd)
```

Bases: *galaxy.datatypes.images.Image*

```
file_ext = 'im'
```

```
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
```

```
sniff (filename, image=None)
```

Determine if the file is in im format.

```
class galaxy.datatypes.images.Image (**kwd)
```

Bases: *galaxy.datatypes.data.Data*

Class describing an image

```
edam_format = 'format_3547'
```

```
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
```

```
set_peek (dataset, is_multi_byte=False)
```



```

    sniff (filename)

class galaxy.datatypes.images.Jpg (**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'jpg'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in jpg format.

class galaxy.datatypes.images.Laj (**kwd)
    Bases: galaxy.datatypes.data.Text

    Class describing a LAJ Applet

    copy_safe_peek = False

    display_peek (dataset)

    file_ext = 'laj'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to peek

    set_peek (dataset, is_multi_byte=False)

class galaxy.datatypes.images.Pbm (**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'pbm'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in PBM format

class galaxy.datatypes.images.Pcd (**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'pcd'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in pcd format.

class galaxy.datatypes.images.Pcx (**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'pcx'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in pcx format.

class galaxy.datatypes.images.Pdf (**kwd)
    Bases: galaxy.datatypes.images.Image

    edam_format = 'format_3508'

    file_ext = 'pdf'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename)
        Determine if the file is in pdf format.

```

```
class galaxy.datatypes.images.Pgm(**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'pgm'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in PGM format

class galaxy.datatypes.images.Png(**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'png'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in png format.

class galaxy.datatypes.images.Ppm(**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'ppm'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in ppm format.

class galaxy.datatypes.images.Psd(**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'psd'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in psd format.

class galaxy.datatypes.images.Rast(**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'rast'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in rast format

class galaxy.datatypes.images.Rgb(**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'rgb'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

    sniff (filename, image=None)
        Determine if the file is in RGB format.

class galaxy.datatypes.images.Tiff(**kwd)
    Bases: galaxy.datatypes.images.Image

    file_ext = 'tiff'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
```

sniff (*filename*, *image=None*)
Determine if the file is in tiff format.

class `galaxy.datatypes.images.Xbm` (***kwd*)
Bases: `galaxy.datatypes.images.Image`

file_ext = 'xbm'

metadata_spec = **dbkey** (**DBKeyParameter**): Database/Build, defaults to '?'

sniff (*filename*, *image=None*)
Determine if the file is in XBM format.

class `galaxy.datatypes.images.Xpm` (***kwd*)
Bases: `galaxy.datatypes.images.Image`

file_ext = 'xpm'

metadata_spec = **dbkey** (**DBKeyParameter**): Database/Build, defaults to '?'

sniff (*filename*, *image=None*)
Determine if the file is in XPM format.

`galaxy.datatypes.images.create_applet_tag_peek` (*class_name*, *archive*, *params*)

interval Module Interval datatypes

class `galaxy.datatypes.interval.Bed` (***kwd*)
Bases: `galaxy.datatypes.interval.Interval`

Tab delimited data in BED format

as_ucsc_display_file (*dataset*, ***kwd*)
Returns file contents with only the bed data. If bed 6+, treat as interval.

data_sources = {'index': 'bigwig', 'data': 'tabix', 'feature_search': 'fli'}

edam_format = 'format_3003'

file_ext = 'bed'

metadata_spec = **dbkey** (**DBKeyParameter**): Database/Build, defaults to '?', **data_lines** (**MetadataParameter**): Number of lines

set_meta (*dataset*, *overwrite=True*, ***kwd*)
Sets the metadata information for datasets previously determined to be in bed format.

sniff (*filename*)
Checks for 'bedness'

BED lines have three required fields and nine additional optional fields. The number of fields per line must be consistent throughout any single set of data in an annotation track. The order of the optional fields is binding: lower-numbered fields must always be populated if higher-numbered fields are used. The data type of all 12 columns is: 1-str, 2-int, 3-int, 4-str, 5-int, 6-str, 7-int, 8-int, 9-int or list, 10-int, 11-list, 12-list

For complete details see <http://genome.ucsc.edu/FAQ/FAQformat#format1>

```
>>> fname = get_test_fname( 'test_tab.bed' )
>>> Bed().sniff( fname )
True
>>> fname = get_test_fname( 'intervall.bed' )
>>> Bed().sniff( fname )
True
>>> fname = get_test_fname( 'complete.bed' )
```

```
>>> Bed().sniff( fname )
True
```

```
track_type = 'FeatureTrack'
```

```
    Add metadata elements
```

```
class galaxy.datatypes.interval.Bed12 (**kwd)
```

```
    Bases: galaxy.datatypes.interval.BedStrict
```

```
    Tab delimited data in strict BED format - no non-standard columns allowed; column count forced to 12
```

```
file_ext = 'bed12'
```

```
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines
```

```
class galaxy.datatypes.interval.Bed6 (**kwd)
```

```
    Bases: galaxy.datatypes.interval.BedStrict
```

```
    Tab delimited data in strict BED format - no non-standard columns allowed; column count forced to 6
```

```
file_ext = 'bed6'
```

```
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines
```

```
class galaxy.datatypes.interval.BedGraph (**kwd)
```

```
    Bases: galaxy.datatypes.interval.Interval
```

```
    Tab delimited chrom/start/end/datavalue dataset
```

```
as_ucsc_display_file (dataset, **kwd)
```

```
    Returns file contents as is with no modifications. TODO: this is a functional stub and will need to be enhanced moving forward to provide additional support for bedgraph.
```

```
data_sources = {'index': 'bigwig', 'data': 'bigwig'}
```

```
file_ext = 'bedgraph'
```

```
get_estimated_display_viewport (dataset, chrom_col=0, start_col=1, end_col=2)
```

```
    Set viewport based on dataset's first 100 lines.
```

```
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines
```

```
track_type = 'LineTrack'
```

```
class galaxy.datatypes.interval.BedStrict (**kwd)
```

```
    Bases: galaxy.datatypes.interval.Bed
```

```
    Tab delimited data in strict BED format - no non-standard columns allowed
```

```
allow_datatype_change = False
```

```
file_ext = 'bedstrict'
```

```
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines
```

```
set_meta (dataset, overwrite=True, **kwd)
```

```
sniff (filename)
```

```
class galaxy.datatypes.interval.ChromatinInteractions (**kwd)
```

```
    Bases: galaxy.datatypes.interval.Interval
```

```
    Chromatin interactions obtained from 3C/5C/Hi-C experiments.
```

```
column_names = ['Chrom1', 'Start1', 'End1', 'Chrom2', 'Start2', 'End2', 'Value']
```

```
    Add metadata elements
```

```

data_sources = {'index': 'bigwig', 'data': 'tabix'}
file_ext = 'chrint'
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read
sniff (filename)
track_type = 'DiagonalHeatmapTrack'

```

class `galaxy.datatypes.interval.CustomTrack` (***kwd*)
 Bases: `galaxy.datatypes.tabular.Tabular`
 UCSC CustomTrack

display_peek (*dataset*)
 Returns formatted html of peek

file_ext = 'customtrack'

get_estimated_display_viewport (*dataset*, *chrom_col=None*, *start_col=None*, *end_col=None*)
 Return a chrom, start, stop tuple for viewing a file.

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read

set_meta (*dataset*, *overwrite=True*, ***kwd*)

sniff (*filename*)
 Determines whether the file is in customtrack format.

CustomTrack files are built within Galaxy and are basically bed or interval files with the first line looking something like this.

track name="User Track" description="User Supplied Track (from Galaxy)" color=0,0,0 visibility=1

```

>>> fname = get_test_fname( 'complete.bed' )
>>> CustomTrack().sniff( fname )
False
>>> fname = get_test_fname( 'ucsc.customtrack' )
>>> CustomTrack().sniff( fname )
True

```

ucsc_links (*dataset*, *type*, *app*, *base_url*)

class `galaxy.datatypes.interval.ENCODEPeak` (***kwd*)
 Bases: `galaxy.datatypes.interval.Interval`

Human ENCODE peak format. There are both broad and narrow peak formats. Formats are very similar; narrow peak has an additional column, though.

Broad peak (<http://genome.ucsc.edu/FAQ/FAQformat#format13>): This format is used to provide called regions of signal enrichment based on pooled, normalized (interpreted) data. It is a BED 6+3 format.

Narrow peak <http://genome.ucsc.edu/FAQ/FAQformat#format12> and : This format is used to provide called peaks of signal enrichment based on pooled, normalized (interpreted) data. It is a BED6+4 format.

column_names = ['Chrom', 'Start', 'End', 'Name', 'Score', 'Strand', 'SignalValue', 'pValue', 'qValue', 'Peak']

data_sources = {'index': 'bigwig', 'data': 'tabix'}
 Add metadata elements

file_ext = 'encodepeak'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read

sniff (*filename*)

```

class galaxy.datatypes.interval.Gff (**kwd)
    Bases: galaxy.datatypes.tabular.Tabular, galaxy.datatypes.interval._RemoteCallMixin
    Tab delimited data in Gff format

    column_names = ['Seqname', 'Source', 'Feature', 'Start', 'End', 'Score', 'Strand', 'Frame', 'Group']
    data_sources = {'index': 'bigwig', 'data': 'interval_index', 'feature_search': 'fli'}
    dataproviders = {'dataset-column': <function dataset_column_dataprovider at 0x7f36a247fc80>, 'chunk64': <function
    display_peek (dataset)
        Returns formatted html of peek

    edam_format = 'format_2305'

    file_ext = 'gff'

    gbrowse_links (dataset, type, app, base_url)

    genomic_region_dataprovider (*args, **kwargs)

    genomic_region_dict_dataprovider (*args, **kwargs)

    get_estimated_display_viewport (dataset)
        Return a chrom, start, stop tuple for viewing a file. There are slight differences between gff 2 and gff 3
        formats. This function should correctly handle both...

    interval_dataprovider (*args, **kwargs)

    interval_dict_dataprovider (*args, **kwargs)

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number
    set_attribute_metadata (dataset)
        Sets metadata elements for dataset's attributes.

    set_meta (dataset, overwrite=True, **kwd)

    sniff (filename)
        Determines whether the file is in gff format

        GFF lines have nine required fields that must be tab-separated.

        For complete details see http://genome.ucsc.edu/FAQ/FAQformat#format3

    track_type = 'FeatureTrack'
        Add metadata elements

    ucsc_links (dataset, type, app, base_url)

class galaxy.datatypes.interval.Gff3 (**kwd)
    Bases: galaxy.datatypes.interval.Gff
    Tab delimited data in Gff3 format

    column_names = ['Seqid', 'Source', 'Type', 'Start', 'End', 'Score', 'Strand', 'Phase', 'Attributes']
    edam_format = 'format_1975'

    file_ext = 'gff3'

```

```

>>> fname = get_test_fname( 'gff_version_3.gff' )
>>> Gff().sniff( fname )
False
>>> fname = get_test_fname( 'test.gff' )
>>> Gff().sniff( fname )
True

```

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

set_meta (*dataset*, *overwrite=True*, ***kwd*)

sniff (*filename*)

Determines whether the file is in gff version 3 format

GFF 3 format:

- 1.adds a mechanism for representing more than one level of hierarchical grouping of features and subfeatures.
- 2.separates the ideas of group membership and feature name/id
- 3.constrains the feature type field to be taken from a controlled vocabulary.
- 4.allows a single feature, such as an exon, to belong to more than one group at a time.
- 5.provides an explicit convention for pairwise alignments
- 6.provides an explicit convention for features that occupy disjunct regions

The format consists of 9 columns, separated by tabs (NOT spaces).

Undefined fields are replaced with the "." character, as described in the original GFF spec.

For complete details see <http://song.sourceforge.net/gff3.shtml>

```
>>> fname = get_test_fname( 'test.gff' )
>>> Gff3().sniff( fname )
False
>>> fname = get_test_fname('gff_version_3.gff')
>>> Gff3().sniff( fname )
True
```

track_type = 'FeatureTrack'

Add metadata elements

valid_gff3_phase = ['.', '0', '1', '2']

valid_gff3_strand = ['+', '-', '?', '?']

class galaxy.datatypes.interval.**Gtf** (***kwd*)

Bases: *galaxy.datatypes.interval.Gff*

Tab delimited data in Gtf format

column_names = ['Seqname', 'Source', 'Feature', 'Start', 'End', 'Score', 'Strand', 'Frame', 'Attributes']

edam_format = 'format_2306'

file_ext = 'gtf'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

sniff (*filename*)

Determines whether the file is in gtf format

GTF lines have nine required fields that must be tab-separated. The first eight GTF fields are the same as GFF. The group field has been expanded into a list of attributes. Each attribute consists of a type/value pair. Attributes must end in a semi-colon, and be separated from any following attribute by exactly one space. The attribute list must begin with the two mandatory attributes:

- gene_id value - A globally unique identifier for the genomic source of the sequence. transcript_id value - A globally unique identifier for the predicted transcript.

For complete details see <http://genome.ucsc.edu/FAQ/FAQformat#format4>

```
>>> fname = get_test_fname( '1.bed' )
>>> Gtf().sniff( fname )
False
>>> fname = get_test_fname( 'test.gff' )
>>> Gtf().sniff( fname )
False
>>> fname = get_test_fname( 'test.gtf' )
>>> Gtf().sniff( fname )
True
```

track_type = 'FeatureTrack'

Add metadata elements

class galaxy.datatypes.interval.**Interval** (**kwd)

Bases: *galaxy.datatypes.tabular.Tabular*

Tab delimited data containing interval information

as_ucsc_display_file (dataset, **kwd)

Returns file contents with only the bed data

data_sources = {'index': 'bigwig', 'data': 'tabix'}

Add metadata elements

dataproviders = {'dataset-column': <function dataset_column_dataprovider at 0x7f36a247fc80>, 'chunk64': <function

display_peek (dataset)

Returns formatted html of peek

displayable (dataset)

edam_format = 'format_3475'

file_ext = 'interval'

genomic_region_dataprovider (*args, **kwargs)

genomic_region_dict_dataprovider (*args, **kwargs)

get_estimated_display_viewport (dataset, chrom_col=None, start_col=None, end_col=None)

Return a chrom, start, stop tuple for viewing a file.

get_track_resolution (dataset, start, end)

get_track_window (dataset, data, start, end)

Assumes the incoming track data is sorted already.

init_meta (dataset, copy_from=None)

interval_dataprovider (*args, **kwargs)

interval_dict_dataprovider (*args, **kwargs)

line_class = 'region'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

repair_methods (dataset)

Return options for removing errors along with a description

set_meta (dataset, overwrite=True, first_line_is_header=False, **kwd)

Tries to guess from the line the location number of the column for the chromosome, region start-end and strand

sniff (*filename*)

Checks for 'intervalness'

This format is mostly used by galaxy itself. Valid interval files should include a valid header comment, but this seems to be loosely regulated.

```
>>> fname = get_test_fname( 'test_space.txt' )
>>> Interval().sniff( fname )
False
>>> fname = get_test_fname( 'interval.interval' )
>>> Interval().sniff( fname )
True
```

track_type = 'FeatureTrack'

ucsc_links (*dataset, type, app, base_url*)

Generate links to UCSC genome browser sites based on the dbkey and content of dataset.

validate (*dataset*)

Validate an interval file using the bx GenomicIntervalReader

class galaxy.datatypes.interval.**Wiggle** (***kwd*)

Bases: *galaxy.datatypes.tabular.Tabular*, *galaxy.datatypes.interval._RemoteCallMixin*

Tab delimited data in wiggle format

data_sources = {'index': 'bigwig', 'data': 'bigwig'}

dataproviders = {'dataset-column': <function dataset_column_dataprovider at 0x7f36a247fc80>, 'chunk64': <function

display_peek (*dataset*)

Returns formatted html of peek

edam_format = 'format_3005'

file_ext = 'wig'

gbrowse_links (*dataset, type, app, base_url*)

get_estimated_display_viewport (*dataset*)

Return a chrom, start, stop tuple for viewing a file.

get_track_resolution (*dataset, start, end*)

get_track_window (*dataset, data, start, end*)

Assumes we have a numpy file.

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

set_meta (*dataset, overwrite=True, **kwd*)

sniff (*filename*)

Determines whether the file is in wiggle format

The .wig format is line-oriented. Wiggle data is preceded by a track definition line, which adds a number of options for controlling the default display of this track. Following the track definition line is the track data, which can be entered in several different formats.

The track definition line begins with the word 'track' followed by the track type. The track type with version is REQUIRED, and it currently must be wiggle_0. For example, track type=wiggle_0...

For complete details see <http://genome.ucsc.edu/goldenPath/help/wiggle.html>

```
>>> fname = get_test_fname( 'intervall.bed' )
>>> Wiggle().sniff( fname )
False
>>> fname = get_test_fname( 'wiggle.wig' )
>>> Wiggle().sniff( fname )
True
```

track_type = 'LineTrack'

ucsc_links (dataset, type, app, base_url)

wiggle_dataprovider (*args, **kwargs)

wiggle_dict_dataprovider (*args, **kwargs)

metadata Module Galaxy Metadata

class galaxy.datatypes.metadata.**ColumnParameter** (spec)

Bases: *galaxy.datatypes.metadata.RangeParameter*

get_html (value, context=None, other_values=None, values=None, **kwd)

get_html_field (value=None, context=None, other_values=None, values=None, **kwd)

class galaxy.datatypes.metadata.**ColumnTypesParameter** (spec)

Bases: *galaxy.datatypes.metadata.MetadataParameter*

to_string (value)

class galaxy.datatypes.metadata.**DBKeyParameter** (spec)

Bases: *galaxy.datatypes.metadata.SelectParameter*

get_html (value=None, context=None, other_values=None, values=None, **kwd)

get_html_field (value=None, context=None, other_values=None, values=None, **kwd)

class galaxy.datatypes.metadata.**DictParameter** (spec)

Bases: *galaxy.datatypes.metadata.MetadataParameter*

to_safe_string (value)

to_string (value)

class galaxy.datatypes.metadata.**FileParameter** (spec)

Bases: *galaxy.datatypes.metadata.MetadataParameter*

from_external_value (value, parent, path_rewriter=None)

Turns a value read from a external dict into its value to be pushed directly into the metadata dict.

get_html (value=None, context=None, other_values=None, **kwd)

get_html_field (value=None, context=None, other_values=None, **kwd)

make_copy (value, target_context, source_context)

classmethod marshal (value)

new_file (dataset=None, **kws)

to_external_value (value)

Turns a value read from a metadata into its value to be pushed directly into the external dict.

to_safe_string (value)

to_string (value)

wrap (*value, session*)

class `galaxy.datatypes.metadata.JobExternalOutputMetadataWrapper` (*job*)

Bases: `object`

Class with methods allowing `set_meta()` to be called externally to the Galaxy head. This class allows access to external metadata filenames for all outputs associated with a job. We will use JSON as the medium of exchange of information, except for the `DatasetInstance` object which will use pickle (in the future this could be JSONified as well)

cleanup_external_metadata (*sa_session*)

external_metadata_set_successfully (*dataset, sa_session*)

get_dataset_metadata_key (*dataset*)

get_output_filenames_by_dataset (*dataset, sa_session*)

invalidate_external_metadata (*datasets, sa_session*)

set_job_runner_external_pid (*pid, sa_session*)

setup_external_metadata (*datasets, sa_session, exec_dir=None, tmp_dir=None, dataset_files_path=None, output_fnames=None, config_root=None, config_file=None, datatypes_config=None, job_metadata=None, compute_tmp_dir=None, include_command=True, kwds=None*)

class `galaxy.datatypes.metadata.ListParameter` (*spec*)

Bases: `galaxy.datatypes.metadata.MetadataParameter`

to_string (*value*)

class `galaxy.datatypes.metadata.MetadataCollection` (*parent*)

Bases: `object`

`MetadataCollection` is not a collection at all, but rather a proxy to the real metadata which is stored as a Dictionary. This class handles processing the metadata elements when they are set and retrieved, returning default values in cases when metadata is not set.

element_is_set (*name*)

from_JSON_dict (*filename=None, path_rewriter=None, json_dict=None*)

get (*key, default=None*)

get_html_by_name (*name, **kwd*)

get_parent ()

items ()

make_dict_copy (*to_copy*)

Makes a deep copy of input iterable *to_copy* according to *self.spec*

parent

set_parent (*parent*)

spec

to_JSON_dict (*filename=None*)

`galaxy.datatypes.metadata.MetadataElement` = `<galaxy.datatypes.metadata.Statement object>`
`MetadataParameter` sub-classes.

```
class galaxy.datatypes.metadata.MetadataElementSpec (datatype, name=None,
                                                    desc=None, param=<class
                                                    'galaxy.datatypes.metadata.MetadataParameter'>,
                                                    default=None, no_value=None, vis-
                                                    ible=True, set_in_upload=False,
                                                    **kwargs)
```

Bases: object

Defines a metadata element and adds it to the metadata_spec (which is a MetadataSpecCollection) of datatype.

get (name, default=None)

unwrap (value)

Turns an incoming value into its storable form.

wrap (value, session)

Turns a stored value into its usable form.

```
class galaxy.datatypes.metadata.MetadataParameter (spec)
```

Bases: object

from_external_value (value, parent)

Turns a value read from an external dict into its value to be pushed directly into the metadata dict.

get_html (value, context=None, other_values=None, **kwd)

The “context” is simply the metadata collection/bunch holding this piece of metadata. This is passed in to allow for metadata to validate against each other (note: this could turn into a huge, recursive mess if not done with care). For example, a column assignment should validate against the number of columns in the dataset.

get_html_field (value=None, context=None, other_values=None, **kwd)

make_copy (value, target_context=None, source_context=None)

classmethod marshal (value)

This method should/can be overridden to convert the incoming value to whatever type it is supposed to be.

to_external_value (value)

Turns a value read from a metadata into its value to be pushed directly into the external dict.

to_safe_string (value)

to_string (value)

unwrap (form_value)

Turns a value into its storable form.

validate (value)

Throw an exception if the value is invalid.

wrap (value, session)

Turns a value into its usable form.

```
class galaxy.datatypes.metadata.MetadataSpecCollection (dict=None)
```

Bases: *galaxy.util.odict.odict*

A simple extension of dict which allows cleaner access to items and allows the values to be iterated over directly as if it were a list. `append()` is also implemented for simplicity and does not “append”.

append (item)

iter ()

```
class galaxy.datatypes.metadata.MetadataTempFile (**kws)
    Bases: object
```

```
    classmethod cleanup_from_JSON_dict_filename (filename)
```

```
    file_name
```

```
    classmethod from_JSON (json_dict)
```

```
    classmethod is_JSONified_value (value)
```

```
    tmp_dir = 'database/tmp'
```

```
    to_JSON ()
```

```
class galaxy.datatypes.metadata.PythonObjectParameter (spec)
    Bases: galaxy.datatypes.metadata.MetadataParameter
```

```
    get_html (value=None, context=None, other_values=None, **kwd)
```

```
    get_html_field (value=None, context=None, other_values=None, **kwd)
```

```
    classmethod marshal (value)
```

```
    to_string (value)
```

```
class galaxy.datatypes.metadata.RangeParameter (spec)
    Bases: galaxy.datatypes.metadata.SelectParameter
```

```
    get_html (value, context=None, other_values=None, values=None, **kwd)
```

```
    get_html_field (value=None, context=None, other_values=None, values=None, **kwd)
```

```
    classmethod marshal (value)
```

```
class galaxy.datatypes.metadata.SelectParameter (spec)
    Bases: galaxy.datatypes.metadata.MetadataParameter
```

```
    get_html (value, context=None, other_values=None, values=None, **kwd)
```

```
    get_html_field (value=None, context=None, other_values=None, values=None, **kwd)
```

```
    classmethod marshal (value)
```

```
    to_string (value)
```

```
    wrap (value, session)
```

```
class galaxy.datatypes.metadata.Statement (target)
    Bases: object
```

This class inserts its target into a list in the surrounding class. the data.Data class has a metaclass which executes these statements. This is how we shove the metadata element spec into the class.

```
    classmethod process (element)
```

ngsindex Module NGS indexes

```
class galaxy.datatypes.ngsindex.BowtieBaseIndex (**kwd)
    Bases: galaxy.datatypes.ngsindex.BowtieIndex
```

Bowtie base space index

```
    file_ext = 'bowtie_base_index'
```

```
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number
```

```
class galaxy.datatypes.ngsindex.BowtieColorIndex(**kwd)
    Bases: galaxy.datatypes.ngsindex.BowtieIndex
    Bowtie color space index
    file_ext = 'bowtie_color_index'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

class galaxy.datatypes.ngsindex.BowtieIndex(**kwd)
    Bases: galaxy.datatypes.images.Html
    base class for BowtieIndex is subclassed by BowtieColorIndex and BowtieBaseIndex
    allow_datatype_change = False
    composite_type = 'auto_primary_file'
    display_peek (dataset)
    file_ext = 'bowtie_index'
    generate_primary_file (dataset=None)
        This is called only at upload to write the html file cannot rename the datasets here - they come with the
        default unfortunately
    is_binary = True
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines
    regenerate_primary_file (dataset)
        cannot do this until we are setting metadata
    set_peek (dataset, is_multi_byte=False)
    sniff (filename)
```

qualityscore Module Qualityscore class

```
class galaxy.datatypes.qualityscore.QualityScore(**kwd)
    Bases: galaxy.datatypes.data.Text
    until we know more about quality score formats
    file_ext = 'qual'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

class galaxy.datatypes.qualityscore.QualityScore454(**kwd)
    Bases: galaxy.datatypes.qualityscore.QualityScore
    until we know more about quality score formats
    file_ext = 'qual454'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines
    sniff (filename)
```

```
>>> fname = get_test_fname( 'sequence.fasta' )
>>> QualityScore454().sniff( fname )
False
>>> fname = get_test_fname( 'sequence.qual454' )
>>> QualityScore454().sniff( fname )
True
```

```

class galaxy.datatypes.qualityscore.QualityScoreIllumina (**kwd)
    Bases: galaxy.datatypes.qualityscore.QualityScore

    until we know more about quality score formats

    file_ext = 'qualillumina'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

class galaxy.datatypes.qualityscore.QualityScoreSOLiD (**kwd)
    Bases: galaxy.datatypes.qualityscore.QualityScore

    until we know more about quality score formats

    file_ext = 'qualsolid'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

    set_meta (dataset, **kwd)

    sniff (filename)

```

```

>>> fname = get_test_fname( 'sequence.fasta' )
>>> QualityScoreSOLiD().sniff( fname )
False
>>> fname = get_test_fname( 'sequence.qualsolid' )
>>> QualityScoreSOLiD().sniff( fname )
True

```

```

class galaxy.datatypes.qualityscore.QualityScoreSolexa (**kwd)
    Bases: galaxy.datatypes.qualityscore.QualityScore

    until we know more about quality score formats

    file_ext = 'qualsolexa'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

```

registry Module Provides mapping between extensions and datatypes, mime-types, etc.

```

exception galaxy.datatypes.registry.ConfigurationError
    Bases: exceptions.Exception

```

```

class galaxy.datatypes.registry.Registry
    Bases: object

    change_datatype (data, ext)

    edam_formats

    find_conversion_destination_for_dataset_by_extensions (dataset, accepted_formats, converter_safe=True)

        Returns ( target_ext, existing converted dataset )

    get_available_tracks ()

    get_composite_extensions ()

    get_converter_by_target_type (source_ext, target_ext)
        Returns a converter based on source and target datatypes

    get_converters_by_datatype (ext)
        Returns available converters by source type

```

get_datatype_by_extension (*ext*)

Returns a datatype based on an extension

get_datatype_class_by_name (*name*)

Return the datatype class where the datatype's *type* attribute (as defined in the *datatype_conf.xml* file) contains *name*.

get_display_sites (*site_type*)

get_legacy_sites_by_build (*site_type*, *build*)

get_mimetype_by_extension (*ext*, *default*='application/octet-stream')

Returns a mimetype based on an extension

get_upload_metadata_params (*context*, *group*, *tool*)

Returns dict of case value:inputs for metadata conditional for upload tool

integrated_datatypes_configs

load_build_sites (*root*)

load_datatype_converters (*toolbox*, *installed_repository_dict*=None, *deactivate*=False)

If deactivate is False, add datatype converters from *self.converters* or *self.proprietary_converters* to the calling app's toolbox. If deactivate is True, eliminates relevant converters from the calling app's toolbox.

load_datatype_sniffers (*root*, *deactivate*=False, *handling_proprietary_datatypes*=False, *override*=False)

Process the sniffers element from a parsed a datatypes XML file located at *root_dir/config* (if processing the Galaxy distributed config) or contained within an installed Tool Shed repository. If deactivate is True, an installed Tool Shed repository that includes custom sniffers is being deactivated or uninstalled, so appropriate loaded sniffers will be removed from the registry. The value of override will be False when a Tool Shed repository is being installed. Since installation is occurring after the datatypes registry has been initialized at server startup, its contents cannot be overridden by newly introduced conflicting sniffers.

load_datatypes (*root_dir*=None, *config*=None, *deactivate*=False, *override*=True)

Parse a datatypes XML file located at *root_dir/config* (if processing the Galaxy distributed config) or contained within an installed Tool Shed repository. If deactivate is True, an installed Tool Shed repository that includes custom datatypes is being deactivated or uninstalled, so appropriate loaded datatypes will be removed from the registry. The value of override will be False when a Tool Shed repository is being installed. Since installation is occurring after the datatypes registry has been initialized at server startup, its contents cannot be overridden by newly introduced conflicting data types.

load_display_applications (*app*, *installed_repository_dict*=None, *deactivate*=False)

If deactivate is False, add display applications from *self.display_app_containers* or *self.proprietary_display_app_containers* to appropriate datatypes. If deactivate is True, eliminates relevant display applications from appropriate datatypes.

load_external_metadata_tool (*toolbox*)

Adds a tool which is used to set external metadata

reload_display_applications (*display_application_ids*=None)

Reloads display applications: by id, or all if no ids provided Returns tuple([reloaded_ids], [failed_ids])

set_default_values ()

to_xml_file ()

sequence Module Sequence classes

class galaxy.datatypes.sequence.**Alignment** (***kwd*)

Bases: *galaxy.datatypes.data.Text*

Class describing an alignment

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

split (*input_datasets, subdir_generator_function, split_params*)

Split a generic alignment file (not sensible or possible, see subclasses).

class galaxy.datatypes.sequence.**Axt** (**kwd)

Bases: *galaxy.datatypes.data.Text*

Class describing an axt alignment

file_ext = 'axt'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

sniff (*filename*)

Determines whether the file is in axt format

axt alignment files are produced from Blastz, an alignment tool available from Webb Miller's lab at Penn State University.

Each alignment block in an axt file contains three lines: a summary line and 2 sequence lines. Blocks are separated from one another by blank lines.

The summary line contains chromosomal position and size information about the alignment. It consists of 9 required fields.

The sequence lines contain the sequence of the primary assembly (line 2) and aligning assembly (line 3) with inserts. Repeats are indicated by lower-case letters.

For complete details see <http://genome.ucsc.edu/goldenPath/help/axt.html>

```
>>> fname = get_test_fname( 'alignment.axt' )
>>> Axt().sniff( fname )
True
>>> fname = get_test_fname( 'alignment.lav' )
>>> Axt().sniff( fname )
False
```

class galaxy.datatypes.sequence.**Fasta** (**kwd)

Bases: *galaxy.datatypes.sequence.Sequence*

Class representing a FASTA sequence

edam_format = 'format_1929'

file_ext = 'fasta'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines

sniff (*filename*)

Determines whether the file is in fasta format

A sequence in FASTA format consists of a single-line description, followed by lines of sequence data. The first character of the description line is a greater-than (">") symbol in the first column. All lines should be shorter than 80 characters

For complete details see <http://www.ncbi.nlm.nih.gov/blast/fasta.shtml>

Rules for sniffing as True:

We don't care about line length (other than empty lines).

The first non-empty line must start with '>' and the Very Next line.strip() must have sequence data and not be a header.

‘sequence data’ here is loosely defined as non-empty lines which do not start with ‘>’

This will cause Color Space FASTA (csfasta) to be detected as True (they are, after all, still FASTA files - they have a header line followed by sequence data)

Previously this method did some checking to determine if the sequence data had integers (presumably to differentiate between fasta and csfasta)

This should be done through sniff order, where csfasta (currently has a null sniff function) is detected for first (stricter definition) followed sometime after by fasta

We will only check that the first purported sequence is correctly formatted.

```
>>> fname = get_test_fname( 'sequence.maf' )
>>> Fasta().sniff( fname )
False
>>> fname = get_test_fname( 'sequence.fasta' )
>>> Fasta().sniff( fname )
True
```

classmethod `split` (*input_datasets*, *subdir_generator_function*, *split_params*)

Split a FASTA file sequence by sequence.

Note that even if `split_mode="number_of_parts"`, the actual number of sub-files produced may not match that requested by `split_size`.

If `split_mode="to_size"` then `split_size` is treated as the number of FASTA records to put in each sub-file (not size in bytes).

class `galaxy.datatypes.sequence.Fastq` (**kwd)

Bases: `galaxy.datatypes.sequence.Sequence`

Class representing a generic FASTQ sequence

edam_format = ‘format_1930’

file_ext = ‘fastq’

metadata_spec = `dbkey` (DBKeyParameter): Database/Build, defaults to ‘?’, `data_lines` (MetadataParameter): Number of data lines

static process_split_file (*data*)

This is called in the context of an external process launched by a Task (possibly not on the Galaxy machine) to create the input files for the Task. The parameters: *data* - a dict containing the contents of the split file

set_meta (*dataset*, **kwd)

Set the number of sequences and the number of data lines in dataset. FIXME: This does not properly handle line wrapping

sniff (*filename*)

Determines whether the file is in generic fastq format For details, see <http://maq.sourceforge.net/fastq.shtml>

Note: There are three kinds of FASTQ files, known as “Sanger” (sometimes called “Standard”), Solexa, and Illumina
These differ in the representation of the quality scores

```
>>> fname = get_test_fname( '1.fastqsanger' )
>>> Fastq().sniff( fname )
True
>>> fname = get_test_fname( '2.fastqsanger' )
```

```
>>> Fastq().sniff( fname )
True
```

classmethod `split` (*input_datasets, subdir_generator_function, split_params*)

FASTQ files are split on cluster boundaries, in increments of 4 lines

class `galaxy.datatypes.sequence.FastqCSSanger` (***kwd*)

Bases: `galaxy.datatypes.sequence.Fastq`

Class representing a Color Space FASTQ sequence (e.g a SOLiD variant)

file_ext = 'fastqcssanger'

metadata_spec = `dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number`

class `galaxy.datatypes.sequence.FastqIllumina` (***kwd*)

Bases: `galaxy.datatypes.sequence.Fastq`

Class representing a FASTQ sequence (the Illumina 1.3+ variant)

edam_format = 'format_1931'

file_ext = 'fastqillumina'

metadata_spec = `dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number`

class `galaxy.datatypes.sequence.FastqSanger` (***kwd*)

Bases: `galaxy.datatypes.sequence.Fastq`

Class representing a FASTQ sequence (the Sanger variant)

edam_format = 'format_1932'

file_ext = 'fastqsanger'

metadata_spec = `dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number`

class `galaxy.datatypes.sequence.FastqSolexa` (***kwd*)

Bases: `galaxy.datatypes.sequence.Fastq`

Class representing a FASTQ sequence (the Solexa variant)

edam_format = 'format_1933'

file_ext = 'fastqsolexa'

metadata_spec = `dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number`

class `galaxy.datatypes.sequence.Lav` (***kwd*)

Bases: `galaxy.datatypes.data.Text`

Class describing a LAV alignment

edam_format = 'format_3014'

file_ext = 'lav'

metadata_spec = `dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number`

sniff (*filename*)

Determines whether the file is in lav format

LAV is an alignment format developed by Webb Miller's group. It is the primary output format for BLASTZ. The first line of a .lav file begins with #:lav.

For complete details see http://www.bioperl.org/wiki/LAV_alignment_format

```

>>> fname = get_test_fname( 'alignment.lav' )
>>> Lav().sniff( fname )
True
>>> fname = get_test_fname( 'alignment.axt' )
>>> Lav().sniff( fname )
False

```

```

class galaxy.datatypes.sequence.Maf(**kwd)
    Bases: galaxy.datatypes.sequence.Alignment

```

Class describing a Maf alignment

display_peek (dataset)

Returns formatted html of peek

edam_format = 'format_3008'

file_ext = 'maf'

init_meta (dataset, copy_from=None)

make_html_table (dataset, skipchars=[])

Create HTML table, used for displaying peek

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to display

set_meta (dataset, overwrite=True, **kwd)

Parses and sets species, chromosomes, index from MAF file.

set_peek (dataset, is_multi_byte=False)

sniff (filename)

Determines whether the file is in maf format

The .maf format is line-oriented. Each multiple alignment ends with a blank line. Each sequence in an alignment is on a single line, which can get quite long, but there is no length limit. Words in a line are delimited by any white space. Lines starting with # are considered to be comments. Lines starting with ## can be ignored by most programs, but contain meta-data of one form or another.

The first line of a .maf file begins with ##maf. This word is followed by white-space-separated variable=value pairs. There should be no white space surrounding the “=”.

For complete details see <http://genome.ucsc.edu/FAQ/FAQformat#format5>

```

>>> fname = get_test_fname( 'sequence.maf' )
>>> Maf().sniff( fname )
True
>>> fname = get_test_fname( 'sequence.fasta' )
>>> Maf().sniff( fname )
False

```

```

class galaxy.datatypes.sequence.MafCustomTrack(**kwd)

```

Bases: galaxy.datatypes.data.Text

file_ext = 'mafcustomtrack'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to display

set_meta (dataset, overwrite=True, **kwd)

Parses and sets viewport metadata from MAF file.

```

class galaxy.datatypes.sequence.RNADotPlotMatrix(**kwd)

```

Bases: galaxy.datatypes.data.Data

```

edam_format = 'format_3466'

file_ext = 'rna_eps'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'

set_peek (dataset, is_multi_byte=False)

sniff (filename)
    Determine if the file is in RNA dot plot format.

class galaxy.datatypes.sequence.Sequence (**kwd)
    Bases: galaxy.datatypes.data.Text

    Class describing a sequence

    classmethod do_fast_split (input_datasets, toc_file_datasets, subdir_generator_function,
                               split_params)

    classmethod do_slow_split (input_datasets, subdir_generator_function, split_params)

    static get_sequences_per_file (total_sequences, split_params)

    static get_split_commands_sequential (is_compressed, input_name, output_name,
                                          start_sequence, sequence_count)
        Does a brain-dead sequential scan & extract of certain sequences >>> Se-
        quence.get_split_commands_sequential(True, './input.gz', './output.gz', start_sequence=0, se-
        quence_count=10) ['zcat './input.gz' | ( tail -n +1 2> /dev/null) | head -40 | gzip -c > './output.gz'"]
        >>> Sequence.get_split_commands_sequential(False, './input.fastq', './output.fastq', start_sequence=10,
        sequence_count=10) ['tail -n +41 './input.fastq' 2> /dev/null | head -40 > './output.fastq'"]

    static get_split_commands_with_toc (input_name, output_name, toc_file, start_sequence, se-
                                       quence_count)
        Uses a Table of Contents dict, parsed from an FQTOC file, to come up with a set of shell commands
        that will extract the parts necessary >>> three_sections=[dict(start=0, end=74, sequences=10),
        dict(start=74, end=148, sequences=10), dict(start=148, end=148+76, sequences=10)] >>> Se-
        quence.get_split_commands_with_toc('./input.gz', './output.gz', dict(sections=three_sections),
        start_sequence=0, sequence_count=10) ['dd bs=1 skip=0 count=74 if=./input.gz 2> /dev/null
        >> ./output.gz'] >>> Sequence.get_split_commands_with_toc('./input.gz', './output.gz',
        dict(sections=three_sections), start_sequence=1, sequence_count=5) ['(dd bs=1 skip=0 count=74
        if=./input.gz 2> /dev/null) | zcat | ( tail -n +5 2> /dev/null) | head -20 | gzip -c >> ./output.gz'] >>>
        Sequence.get_split_commands_with_toc('./input.gz', './output.gz', dict(sections=three_sections),
        start_sequence=0, sequence_count=20) ['dd bs=1 skip=0 count=148 if=./input.gz 2> /dev/null
        >> ./output.gz'] >>> Sequence.get_split_commands_with_toc('./input.gz', './output.gz',
        dict(sections=three_sections), start_sequence=5, sequence_count=10) ['(dd bs=1 skip=0 count=74
        if=./input.gz 2> /dev/null) | zcat | ( tail -n +21 2> /dev/null) | head -20 | gzip -c >> ./output.gz',
        '(dd bs=1 skip=74 count=74 if=./input.gz 2> /dev/null) | zcat | ( tail -n +1 2> /dev/null) | head -20
        | gzip -c >> ./output.gz'] >>> Sequence.get_split_commands_with_toc('./input.gz', './output.gz',
        dict(sections=three_sections), start_sequence=10, sequence_count=10) ['dd bs=1 skip=74 count=74
        if=./input.gz 2> /dev/null >> ./output.gz'] >>> Sequence.get_split_commands_with_toc('./input.gz',
        './output.gz', dict(sections=three_sections), start_sequence=5, sequence_count=20) ['(dd bs=1 skip=0
        count=74 if=./input.gz 2> /dev/null) | zcat | ( tail -n +21 2> /dev/null) | head -20 | gzip -c >> ./output.gz',
        'dd bs=1 skip=74 count=74 if=./input.gz 2> /dev/null >> ./output.gz', '(dd bs=1 skip=148 count=76
        if=./input.gz 2> /dev/null) | zcat | ( tail -n +1 2> /dev/null) | head -20 | gzip -c >> ./output.gz']

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number
set_meta (dataset, **kwd)
    Set the number of sequences and the number of data lines in dataset.

set_peek (dataset, is_multi_byte=False)

```

split (*input_datasets, subdir_generator_function, split_params*)
Split a generic sequence file (not sensible or possible, see subclasses).

classmethod write_split_files (*input_datasets, toc_file_datasets, subdir_generator_function, sequences_per_file*)

class `galaxy.datatypes.sequence.SequenceSplitLocations` (**kwd)
Bases: `galaxy.datatypes.data.Text`

Class storing information about a sequence file composed of multiple gzip files concatenated as one OR an uncompressed file. In the GZIP case, each sub-file's location is stored in start and end.

The format of the file is JSON:

```
{ "sections" : [  
    { "start" : "x", "end" : "y", "sequences" : "z" },  
    ...  
]}
```

file_ext = 'fqtoc'

metadata_spec = `dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines`

set_peek (*dataset, is_multi_byte=False*)

sniff (*filename*)

class `galaxy.datatypes.sequence.csFasta` (**kwd)
Bases: `galaxy.datatypes.sequence.Sequence`

Class representing the SOLID Color-Space sequence (csfasta)

edam_format = 'format_1929'

file_ext = 'csfasta'

metadata_spec = `dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines`

set_meta (*dataset, **kwd*)

sniff (*filename*)

Color-space sequence: >2_15_85_F3 T213021013012303002332212012112221222112212222

```
>>> fname = get_test_fname( 'sequence.fasta' )  
>>> csFasta().sniff( fname )  
False  
>>> fname = get_test_fname( 'sequence.csfasta' )  
>>> csFasta().sniff( fname )  
True
```

sniff Module File format detector

exception `galaxy.datatypes.sniff.InappropriateDatasetContentError`
Bases: `exceptions.Exception`

`galaxy.datatypes.sniff.check_newlines` (*fname, bytes_to_read=52428800*)
Determines if there are any non-POSIX newlines in the first number_of_bytes (by default, 50MB) of the file.

`galaxy.datatypes.sniff.convert_newlines` (*fname, in_place=True, tmp_dir=None, tmp_prefix=None*)
Converts in place a file from universal line endings to Posix line endings.


```

>>> guess_ext(fname)
'gff'
>>> fname = get_test_fname('gff_version_3.gff')
>>> guess_ext(fname)
'gff3'
>>> fname = get_test_fname('temp.txt')
>>> file(fname, 'wt').write("a\t2\nc\t1\nd\t0")
>>> guess_ext(fname)
'tabular'
>>> fname = get_test_fname('temp.txt')
>>> file(fname, 'wt').write("a 1 2 x\nb 3 4 y\nc 5 6 z")
>>> guess_ext(fname)
'txt'
>>> fname = get_test_fname('test_tab1.tabular')
>>> guess_ext(fname)
'tabular'
>>> fname = get_test_fname('alignment.lav')
>>> guess_ext(fname)
'lav'
>>> fname = get_test_fname('1.sff')
>>> guess_ext(fname)
'sff'
>>> fname = get_test_fname('1.bam')
>>> guess_ext(fname)
'bam'
>>> fname = get_test_fname('3unsorted.bam')
>>> guess_ext(fname)
'bam'

```

galaxy.datatypes.sniff.**handle_compressed_file**(filename, datatypes_registry, ext='auto')

galaxy.datatypes.sniff.**handle_uploaded_dataset_file**(filename, datatypes_registry,
ext='auto',
is_multi_byte=False)

galaxy.datatypes.sniff.**is_column_based**(fname, sep='\t', skip=0, is_multi_byte=False)

Checks whether the file is column based with respect to a separator (defaults to tab separator).

```

>>> fname = get_test_fname('test.gff')
>>> is_column_based(fname)
True
>>> fname = get_test_fname('test_tab.bed')
>>> is_column_based(fname)
True
>>> is_column_based(fname, sep=' ')
False
>>> fname = get_test_fname('test_space.txt')
>>> is_column_based(fname)
False
>>> is_column_based(fname, sep=' ')
True
>>> fname = get_test_fname('test_ensembl.tab')
>>> is_column_based(fname)
True
>>> fname = get_test_fname('test_tab1.tabular')
>>> is_column_based(fname, sep=' ', skip=0)
False
>>> fname = get_test_fname('test_tab1.tabular')

```



```
>>> is_column_based(fname)
True
```

`galaxy.datatypes.sniff.sep2tabs(fname, in_place=True, patt='\s+')`
 Transforms in place a 'sep' separated file to a tab separated one

```
>>> fname = get_test_fname('temp.txt')
>>> file(fname, 'wt').write("1 2\n3 4\n")
>>> sep2tabs(fname)
(2, None)
>>> file(fname).read()
'1\t2\n3\t4\n'
```

`galaxy.datatypes.sniff.stream_to_file(stream, suffix='', prefix='', dir=None, text=False, **kwd)`

Writes a stream to a temporary file, returns the temporary file's name

`galaxy.datatypes.sniff.stream_to_open_named_file(stream, fd, filename, source_encoding=None, source_error='strict', get_encoding=None, get_error='strict', tar-)`

Writes a stream to the provided file descriptor, returns the file's name and `bool(is_multi_byte)`. Closes file descriptor

tabular Module Tabular datatype

class `galaxy.datatypes.tabular.CSV(**kwd)`

Bases: `galaxy.datatypes.tabular.TabularData`

Delimiter-separated table data. This includes CSV, TSV and other dialects understood by the Python 'csv' module <https://docs.python.org/2/library/csv.html>

dataproviders = {'dataset-column': <function dataset_column_dataprovider at 0x7f36a247fc80>, 'chunk64': <function chunk64_dataprovider at 0x7f36a247fc80>}

delimiter = ','

file_ext = 'csv'

guess_type (text)

is_float (column_text)

is_int (column_text)

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read

peek_size = 1024

set_meta (dataset, **kwd)

sniff (filename)

Return True if it recognizes dialect and header.

class `galaxy.datatypes.tabular.Eland(**kwd)`

Bases: `galaxy.datatypes.tabular.Tabular`

Support for the export.txt.gz file used by Illumina's ELANDv2e aligner

file_ext = '_export.txt.gz'

make_html_table (*dataset*, *skipchars=None*)

Create HTML table, used for displaying peek

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines to display

set_meta (*dataset*, *overwrite=True*, *skip=None*, *max_data_lines=5*, ***kwd*)

sniff (*filename*)

Determines whether the file is in ELAND export format

A file in ELAND export format consists of lines of tab-separated data. There is no header.

Rules for sniffing as True:

- There must be 22 columns on each line
- LANE, TILEm X, Y, INDEX, READ_NO, SEQ, QUAL, POSITION, *STRAND, FILT must be correct
- We will only check that up to the first 5 alignments are correctly formatted.

class galaxy.datatypes.tabular.**ElandMulti** (***kwd*)

Bases: *galaxy.datatypes.tabular.Tabular*

file_ext = 'elandmulti'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines to display

sniff (*filename*)

class galaxy.datatypes.tabular.**FeatureLocationIndex** (***kwd*)

Bases: *galaxy.datatypes.tabular.Tabular*

An index that stores feature locations in tabular format.

file_ext = 'fli'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines to display

class galaxy.datatypes.tabular.**Pileup** (***kwd*)

Bases: *galaxy.datatypes.tabular.Tabular*

Tab delimited data in pileup (6- or 10-column) format

data_sources = {'data': 'tabix'}

Add metadata elements

dataproviders = {'dataset-column': <function dataset_column_dataprovider at 0x7f36a247fc80>, 'chunk64': <function chunk64_dataprovider at 0x7f36a247fc80>}

display_peek (*dataset*)

Returns formatted html of peek

edam_format = 'format_3015'

file_ext = 'pileup'

genomic_region_dataprovider (**args*, ***kwargs*)

genomic_region_dict_dataprovider (**args*, ***kwargs*)

init_meta (*dataset*, *copy_from=None*)

line_class = 'genomic coordinate'

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', **data_lines** (MetadataParameter): Number of lines to display

repair_methods (*dataset*)

Return options for removing errors along with a description

sniff (*filename*)

Checks for ‘pileup-ness’

There are two main types of pileup: 6-column and 10-column. For both, the first three and last two columns are the same. We only check the first three to allow for some personalization of the format.

```
>>> fname = get_test_fname( 'interval.interval' )
>>> Pileup().sniff( fname )
False
>>> fname = get_test_fname( '6col.pileup' )
>>> Pileup().sniff( fname )
True
>>> fname = get_test_fname( '10col.pileup' )
>>> Pileup().sniff( fname )
True
```

class galaxy.datatypes.tabular.**Sam** (***kwd*)

Bases: *galaxy.datatypes.tabular.Tabular*

column_dataprovider (**args, **kwargs*)

data_sources = {'index': 'bigwig', 'data': 'bam'}

dataproviders = {'dataset-column': <function dataset_column_dataprovider at 0x7f36a2497a28>, 'chunk64': <function

dataset_column_dataprovider (**args, **kwargs*)

dataset_dict_dataprovider (**args, **kwargs*)

dict_dataprovider (**args, **kwargs*)

display_peek (*dataset*)

Returns formatted html of peek

edam_format = 'format_2573'

file_ext = 'sam'

genomic_region_dataprovider (**args, **kwargs*)

genomic_region_dict_dataprovider (**args, **kwargs*)

header_dataprovider (**args, **kwargs*)

id_seq_qual_dataprovider (**args, **kwargs*)

line_dataprovider (**args, **kwargs*)

static merge (*split_files, output_file*)

Multiple SAM files may each have headers. Since the headers should all be the same, remove the headers from files 1-n, keeping them in the first file only

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

regex_line_dataprovider (**args, **kwargs*)

set_meta (*dataset, overwrite=True, skip=None, max_data_lines=5, **kwd*)

sniff (*filename*)

Determines whether the file is in SAM format

A file in SAM format consists of lines of tab-separated data. The following header line may be the first line:

@QNAME	FLAG	RNAME	POS	MAPQ	CIGAR	MRNM	MPOS	ISIZE	SEQ	QUAL	
or											
@QNAME	FLAG	RNAME	POS	MAPQ	CIGAR	MRNM	MPOS	ISIZE	SEQ	QUAL	OPT

Data in the OPT column is optional and can consist of tab-separated data

For complete details see <http://samtools.sourceforge.net/SAM1.pdf>

Rules for sniffing as True:

There must be 11 or more columns of data on each line
Columns 2 (FLAG), 4(POS), 5 (MAPQ), 8 (MPOS), and 9 (ISIZE) must be numbers (9 can be negat
We will only check that up to the first 5 alignments are correctly formatted.

```
>>> fname = get_test_fname( 'sequence.maf' )
>>> Sam().sniff( fname )
False
>>> fname = get_test_fname( '1.sam' )
>>> Sam().sniff( fname )
True
```

track_type = 'ReadTrack'

class galaxy.datatypes.tabular.**Tabular** (**kwd)

Bases: *galaxy.datatypes.tabular.TabularData*

Tab delimited data

as_gbrowse_display_file (dataset, **kwd)

as_ucsc_display_file (dataset, **kwd)

dataproviders = {'dataset-column': <function dataset_column_dataprovider at 0x7f36a247fc80>, 'chunk64': <function

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

set_meta (dataset, overwrite=True, skip=None, max_data_lines=100000, max_guess_type_data_lines=None, **kwd)

Tries to determine the number of columns as well as those columns that contain numerical values in the dataset. A skip parameter is used because various tabular data types reuse this function, and their data type classes are responsible to determine how many invalid comment lines should be skipped. Using None for skip will cause skip to be zero, but the first line will be processed as a header. A max_data_lines parameter is used because various tabular data types reuse this function, and their data type classes are responsible to determine how many data lines should be processed to ensure that the non-optional metadata parameters are properly set; if used, optional metadata parameters will be set to None, unless the entire file has already been read. Using None for max_data_lines will process all data lines.

Items of interest:

- 1.We treat 'overwrite' as always True (we always want to set tabular metadata when called).
- 2.If a tabular file has no data, it will have one column of type 'str'.
- 3.We used to check only the first 100 lines when setting metadata and this class's set_peek() method read the entire file to determine the number of lines in the file. Since metadata can now be processed on cluster nodes, we've merged the line count portion of the set_peek() processing here, and we now check the entire contents of the file.

class galaxy.datatypes.tabular.**TabularData** (**kwd)

Bases: *galaxy.datatypes.data.Text*

Generic tabular data

```

CHUNKABLE = True
    Add metadata elements

column_dataprovider (*args, **kwargs)
    Uses column settings that are passed in

dataproviders = {'dataset-column': <function dataset_column_dataprovider at 0x7f36a247fc80>, 'chunk64': <function
dataset_column_dataprovider (*args, **kwargs)
    Attempts to get column settings from dataset.metadata

dataset_dict_dataprovider (*args, **kwargs)
    Attempts to get column settings from dataset.metadata

dict_dataprovider (*args, **kwargs)
    Uses column settings that are passed in

display_data (trans, dataset, preview=False, filename=None, to_ext=None, chunk=None, **kwd)

display_peek (dataset)
    Returns formatted html of peek

displayable (dataset)

edam_format = 'format_3475'

get_chunk (trans, dataset, chunk)

make_html_peek_header (dataset, skipchars=None, column_names=None, col-
                        umn_number_format='%s', column_parameter_alias=None,
                        **kwargs)

make_html_peek_rows (dataset, skipchars=None, **kwargs)

make_html_table (dataset, **kwargs)
    Create HTML table, used for displaying peek

metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number
set_peek (dataset, line_count=None, is_multi_byte=False)

class galaxy.datatypes.tabular.Taxonomy (**kwd)
    Bases: galaxy.datatypes.tabular.Tabular

    display_peek (dataset)
        Returns formatted html of peek

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number

class galaxy.datatypes.tabular.Vcf (**kwd)
    Bases: galaxy.datatypes.tabular.Tabular

    Variant Call Format for describing SNPs and other simple genome variations.

    column_names = ['Chrom', 'Pos', 'ID', 'Ref', 'Alt', 'Qual', 'Filter', 'Info', 'Format', 'data']

    data_sources = {'index': 'bigwig', 'data': 'tabix'}

    dataproviders = {'dataset-column': <function dataset_column_dataprovider at 0x7f36a247fc80>, 'chunk64': <function
    display_peek (dataset)
        Returns formatted html of peek

    edam_format = 'format_3016'

    file_ext = 'vcf'

    genomic_region_dataprovider (*args, **kwargs)

```

```
genomic_region_dict_dataprovider (*args, **kwargs)
metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read
set_meta (dataset, **kwd)
sniff (filename)
track_type = 'VariantTrack'
```

tracks Module Datatype classes for tracks/track views within galaxy.

```
class galaxy.datatypes.tracks.GeneTrack (**kwargs)
    Bases: galaxy.datatypes.binary.Binary
    edam_format = 'format_2919'
    file_ext = 'genetrack'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?'
```

xml Module XML format classes

```
class galaxy.datatypes.xml.CisML (**kwd)
    Bases: galaxy.datatypes.xml.GenericXml
    CisML XML data
    file_ext = 'cismml'
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read
    set_peek (dataset, is_multi_byte=False)
        Set the peek and blurb text
    sniff (filename)

class galaxy.datatypes.xml.GenericXml (**kwd)
    Bases: galaxy.datatypes.data.Text
    Base format class for any XML file.
    dataproviders = {'xml': <function xml_dataprovider at 0x7f36a20b5320>, 'chunk64': <function chunk64_dataprovider at 0x7f36a20b5320>}
    edam_format = 'format_2332'
    file_ext = 'xml'
    static merge (split_files, output_file)
        Merging multiple XML files is non-trivial and must be done in subclasses.
    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read
    set_peek (dataset, is_multi_byte=False)
        Set the peek and blurb text
    sniff (filename)
        Determines whether the file is XML or not
```

```
>>> fname = get_test_fname( 'megablast_xml_parser_test1.blastxml' )
>>> GenericXml().sniff( fname )
True
>>> fname = get_test_fname( 'interval.interval' )
>>> GenericXml().sniff( fname )
False
```

```

    xml_dataprovider (*args, **kwargs)

class galaxy.datatypes.xml.MEMEXml (**kwd)
    Bases: galaxy.datatypes.xml.GenericXml

    MEME XML Output data

    file_ext = 'memexml'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read from the database

    set_peek (dataset, is_multi_byte=False)
        Set the peek and blurb text

    sniff (filename)

class galaxy.datatypes.xml.Owl (**kwd)
    Bases: galaxy.datatypes.xml.GenericXml

    Web Ontology Language OWL format description http://www.w3.org/TR/owl-ref/

    edam_format = 'format_3262'

    file_ext = 'owl'

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read from the database

    set_peek (dataset, is_multi_byte=False)

    sniff (filename)
        Checking for keyword - '<owl' in the first 200 lines.

class galaxy.datatypes.xml.Phyloxml (**kwd)
    Bases: galaxy.datatypes.xml.GenericXml

    Format for defining phyloxml data http://www.phyloxml.org/

    file_ext = 'phyloxml'

    get_visualizations (dataset)
        Returns a list of visualizations for datatype.

    metadata_spec = dbkey (DBKeyParameter): Database/Build, defaults to '?', data_lines (MetadataParameter): Number of lines to read from the database

    set_peek (dataset, is_multi_byte=False)
        Set the peek and blurb text

    sniff (filename)
        "Checking for keyword - 'phyloxml' always in lowercase in the first few lines

```

Subpackages

converters Package

bed_to_genetrack_converter Module

bed_to_gff_converter Module

bedgraph_to_array_tree_converter Module

bgzip Module Uses pysam to bgzip a file

usage: %prog in_file out_file

```
galaxy.datatypes.converters.bgzip.main()
```

fasta_to_len Module Input: fasta, int Output: tabular Return titles with lengths of corresponding seq

```
galaxy.datatypes.converters.fasta_to_len.compute_fasta_length(fasta_file,
                                                                out_file,
                                                                keep_first_char,
                                                                keep_first_word=False)
```

fasta_to_tabular_converter Module Input: fasta Output: tabular

fastq_to_fqtoc Module

```
galaxy.datatypes.converters.fastq_to_fqtoc.main()
```

The format of the file is JSON:

```
{ "sections" : [
    { "start" : "x", "end" : "y", "sequences" : "z" },
    ...
  ] }
```

This works only for UNCOMPRESSED fastq files. The Python GzipFile does not provide seekable offsets via tell(), so clients just have to split the slow way

fastqsolexa_to_fasta_converter Module convert fastqsolexa file to separated sequence and quality files.

assume each sequence and quality score are contained in one line the order should be: 1st line: @title_of_seq 2nd line: nucleotides 3rd line: +title_of_qualityscore (might be skipped) 4th line: quality scores (in three forms: a. digits, b. ASCII codes, the first char as the coding base, c. ASCII codes without the first char.)

Usage: %python fastqsolexa_to_fasta_converter.py <your_fastqsolexa_filename> <output_seq_filename> <output_score_filename>

```
galaxy.datatypes.converters.fastqsolexa_to_fasta_converter.stop_err(msg)
```

fastqsolexa_to_qual_converter Module convert fastqsolexa file to separated sequence and quality files.

assume each sequence and quality score are contained in one line the order should be: 1st line: @title_of_seq 2nd line: nucleotides 3rd line: +title_of_qualityscore (might be skipped) 4th line: quality scores (in three forms: a. digits, b. ASCII codes, the first char as the coding base, c. ASCII codes without the first char.)

Usage: %python fastqsolexa_to_qual_converter.py <your_fastqsolexa_filename> <output_seq_filename> <output_score_filename>

```
galaxy.datatypes.converters.fastqsolexa_to_qual_converter.stop_err(msg)
```

gff_to_bed_converter Module

gff_to_interval_index_converter Module Convert from GFF file to interval index file.

usage: python gff_to_interval_index_converter.py [input] [output]

```
galaxy.datatypes.converters.gff_to_interval_index_converter.main()
```

interval_to_bed_converter Module

```
galaxy.datatypes.converters.interval_to_bed_converter.stop_err(msg)
```

interval_to_bedstrict_converter Module

```
galaxy.datatypes.converters.interval_to_bedstrict_converter.force_bed_field_count(fields,
re-
gion_count,
force_num_c

galaxy.datatypes.converters.interval_to_bedstrict_converter.stop_err(msg)
```

interval_to_coverage Module Converter to generate 3 (or 4) column base-pair coverage from an interval file.

usage: %prog bed_file out_file -1, -cols1=N,N,N,N: Columns for chrom, start, end, strand in interval file -2, -cols2=N,N,N,N: Columns for chrom, start, end, strand in coverage file

```
class galaxy.datatypes.converters.interval_to_coverage.CoverageWriter(out_stream=None,
chrom-
Col=0,
position-
Col=1,
forward-
Col=2,
rever-
seCol=3)
```

Bases: object

```
close()
```

```
write(**kwargs)
```

```
galaxy.datatypes.converters.interval_to_coverage.main(interval, coverage)
```

Uses a sliding window of partitions to count coverages. Every interval record adds its start and end to the partitions. The result is a list of partitions, or every position that has a (maybe) different number of basepairs covered. We don't worry about merging because we pop as the sorted intervals are read in. As the input start positions exceed the partition positions in partitions, coverages are kicked out in bulk.

interval_to_fli Module Creates a feature location index (FLI) for a given BED/GFF file. FLI index has the form:

```
[line_length]
<symbol1_in_lowercase><tab><symbol1><tab><location>
<symbol2_in_lowercase><tab><symbol2><tab><location>
...
```

where location is formatted as:

```
contig:start-end
```

and symbols are sorted in lexicographical order.

```
galaxy.datatypes.converters.interval_to_fli.main()
```

interval_to_interval_index_converter Module Convert from interval file to interval index file.

usage: %prog <options> in_file out_file -c, --chr-col: chromosome column, default=1 -s, --start-col: start column, default=2 -e, --end-col: end column, default=3

```
galaxy.datatypes.converters.interval_to_interval_index_converter.main()
```

interval_to_summary_tree_converter Module

interval_to_tabix_converter Module Uses pysam to index a bgzipped interval file with tabix Supported presets: bed, gff, vcf

usage: %prog in_file out_file

```
galaxy.datatypes.converters.interval_to_tabix_converter.main()
```

lped_to_fped_converter Module

```
galaxy.datatypes.converters.lped_to_fped_converter.main()
```

call fbat need to work with rgenetics composite datatypes so in and out are html files with data in extrafiles path
<command interpreter="python">rg_convert_lped_fped.py '\$input1/\$input1.metadata.base_name' '\$output1' '\$output1.extra_files_path' </command>

```
galaxy.datatypes.converters.lped_to_fped_converter.rgConv (inpedfilepath, outhtml-  
name, outfilepath)
```

convert linkage ped/map to fbat

```
galaxy.datatypes.converters.lped_to_fped_converter.timenow()
```

return current time as a string

lped_to_pbed_converter Module

```
galaxy.datatypes.converters.lped_to_pbed_converter.getMissval (inped='')
```

read some lines...ugly hack - try to guess missing value should be N or 0 but might be . or -

```
galaxy.datatypes.converters.lped_to_pbed_converter.main()
```

need to work with rgenetics composite datatypes so in and out are html files with data in extrafiles path
<command interpreter="python">lped_to_pbed_converter.py '\$input1/\$input1.metadata.base_name' '\$output1' '\$output1.extra_files_path' '\${GALAXY_DATA_INDEX_DIR}/rg/bin/plink' </command>

```
galaxy.datatypes.converters.lped_to_pbed_converter.rgConv (inpedfilepath, out-  
htmlname, outfilepath,  
plink)
```

```
galaxy.datatypes.converters.lped_to_pbed_converter.timenow()
```

return current time as a string

maf_to_fasta_converter Module

maf_to_interval_converter Module

pbed_ldreduced_converter Module

```
galaxy.datatypes.converters.pbed_ldreduced_converter.main()
    need to work with rgenetics composite datatypes so in and out are html files with data in extrafiles path
galaxy.datatypes.converters.pbed_ldreduced_converter.makeLDreduced(basename,
                                                                    inf-
                                                                    path=None,
                                                                    outf-
                                                                    path=None,
                                                                    plinke='plink',
                                                                    forcere-
                                                                    build=False,
                                                                    returnF-
                                                                    name=False,
                                                                    win-
                                                                    size='60',
                                                                    win-
                                                                    move='40',
                                                                    r2thresh='0.1')
    not there so make and leave in output dir for post job hook to copy back into input extra files path for next time
galaxy.datatypes.converters.pbed_ldreduced_converter.pruneLD(plinktasks=[],
                                                                cd='./',
                                                                vclbase=[])
galaxy.datatypes.converters.pbed_ldreduced_converter.timenow()
    return current time as a string
```

pbed_to_lped_converter Module

```
galaxy.datatypes.converters.pbed_to_lped_converter.main()
    need to work with rgenetics composite datatypes so in and out are html files with data in extrafiles path
    <command interpreter="python">pbed_to_lped_converter.py '$input1/$input1.metadata.base_name' '$out-
    put1' '$output1.extra_files_path' '${GALAXY_DATA_INDEX_DIR}/rg/bin/plink' </command>
galaxy.datatypes.converters.pbed_to_lped_converter.rgConv(inpedfilepath,      out-
                                                            htmlname,  outfilepath,
                                                            plink)
galaxy.datatypes.converters.pbed_to_lped_converter.timenow()
    return current time as a string
```

picard_interval_list_to_bed6_converter Module**sam_or_bam_to_summary_tree_converter Module**

sam_to_bam Module A wrapper script for converting SAM to BAM, with sorting. %prog input_filename.sam
output_filename.bam

```
galaxy.datatypes.converters.sam_to_bam.cleanup_before_exit(tmp_dir)
```

vcf_to_interval_index_converter Module Convert from VCF file to interval index file.

```
galaxy.datatypes.converters.vcf_to_interval_index_converter.main()
```

vcf_to_summary_tree_converter Module

vcf_to_vcf_bgzip Module Uses pysam to bgzip a vcf file as-is. Headers, which are important, are kept. Original ordering, which may be specifically needed by tools or external display applications, is also maintained.

usage: %prog in_file out_file

```
galaxy.datatypes.converters.vcf_to_vcf_bgzip.main()
```

wiggle_to_array_tree_converter Module

```
galaxy.datatypes.converters.wiggle_to_array_tree_converter.main()
```

wiggle_to_simple_converter Module Read a wiggle track and print out a series of lines containing “chrom position score”. Ignores track lines, handles bed, variableStep and fixedStep wiggle lines.

```
galaxy.datatypes.converters.wiggle_to_simple_converter.main()
```

```
galaxy.datatypes.converters.wiggle_to_simple_converter.stop_err(msg)
```

display_applications Package

application Module

```
class galaxy.datatypes.display_applications.application.DisplayApplication(display_id,  
                                                                           name,  
                                                                           app,  
                                                                           ver-  
                                                                           sion=None,  
                                                                           file-  
                                                                           name=None,  
                                                                           elem=None)
```

Bases: object

```
add_data_table_watch(table_name, version=None)
```

```
filter_by_dataset(data, trans)
```

```
classmethod from_elem(elem, app, filename=None)
```

```
classmethod from_file(filename, app)
```

```
get_link(link_name, data, dataset_hash, user_hash, trans, app_kwds)
```

```
reload()
```

```
class galaxy.datatypes.display_applications.application.DisplayApplicationLink(display_application,
```

Bases: object

```
build_parameter_dict(data, dataset_hash, user_hash, trans, app_kwds)
```

```
filter_by_dataset(data, trans)
```

```
classmethod from_elem(elem, display_application, other_values=None)
```

```
get_display_url(data, trans)
```

```
get_initail_values(data, trans)
```

```
class galaxy.datatypes.display_applications.application.DynamicDisplayApplicationBuilder(elem,
```

Bases: object

```
dis-  
play_  
build,
```

```
class galaxy.datatypes.display_applications.application.PopulatedDisplayApplicationLink (display
data,
dataset,
user_hash,
trans,
app_kv)
```

Bases: object

```
display_ready()
display_url()
get_param_name_by_url(url)
get_param_value(name)
get_prepare_steps(datasets_only=True)
prepare_display()
preparing_display()
```

parameters Module

```
class galaxy.datatypes.display_applications.parameters.DisplayApplicationDataParameter (elem,
link)
```

Bases: *galaxy.datatypes.display_applications.parameters.DisplayApplicationParameter*

Parameter that returns a file_name containing the requested content

```
formats
get_value(other_values, dataset_hash, user_hash, trans)
is_preparing(other_values)
prepare(other_values, dataset_hash, user_hash, trans)
ready(other_values)
type = 'data'
```

```
class galaxy.datatypes.display_applications.parameters.DisplayApplicationParameter (elem,
link)
```

Bases: object

Abstract Class for Display Application Parameters

```
build_url(other_values)
classmethod from_elem(elem, link)
get_value(other_values, dataset_hash, user_hash, trans)
is_preparing(other_values)
prepare(other_values, dataset_hash, user_hash, trans)
ready(other_values)
type = None
```

```
class galaxy.datatypes.display_applications.parameters.DisplayApplicationTemplateParameter (elem,
link)
```

Bases: *galaxy.datatypes.display_applications.parameters.DisplayApplicationParameter*

Parameter that returns a string containing the requested content

```
get_value(other_values, dataset_hash, user_hash, trans)
```

type = 'template'

```
class galaxy.datatypes.display_applications.parameters.DisplayDataValueWrapper (value,
                                                                                   pa-
                                                                                   ram-
                                                                                   e-
                                                                                   ter,
                                                                                   other_values,
                                                                                   dataset_hash,
                                                                                   user_hash,
                                                                                   trans)

Bases: galaxy.datatypes.display_applications.parameters.DisplayParameterValueWrapper
```

ACTION_NAME = 'data'

action_name

mime_type (action_param_extra=None)

qp

```
class galaxy.datatypes.display_applications.parameters.DisplayParameterValueWrapper (value,
                                                                                   pa-
                                                                                   ram-
                                                                                   e-
                                                                                   ter,
                                                                                   other_values,
                                                                                   dataset_hash,
                                                                                   user_hash,
                                                                                   trans)
```

Bases: object

ACTION_NAME = 'param'

action_name

mime_type (action_param_extra=None)

qp

url

util Module

```
galaxy.datatypes.display_applications.util.decode_dataset_user (trans,
                                                                    dataset_hash,
                                                                    user_hash)
galaxy.datatypes.display_applications.util.encode_dataset_user (trans, dataset,
                                                                    user)
```

util Package

util Package Utilities for Galaxy datatypes.

gff_util Module Provides utilities for working with GFF files.

```
class galaxy.datatypes.util.gff_util.GFFFeature(reader, chrom_col=0, feature_col=2,
                                              start_col=3, end_col=4, strand_col=6,
                                              score_col=5, default_strand='.',
                                              fix_strand=False, intervals=[],
                                              raw_size=0)
```

Bases: `galaxy.datatypes.util.gff_util.GFFInterval`

A GFF feature, which can include multiple intervals.

copy()

lines()

name()

Returns feature's name.

```
class galaxy.datatypes.util.gff_util.GFFInterval(reader, fields, chrom_col=0, fea-
                                              ture_col=2, start_col=3, end_col=4,
                                              strand_col=6, score_col=5, de-
                                              fault_strand='.', fix_strand=False)
```

Bases: `bx.intervals.io.GenomicInterval`

A GFF interval, including attributes. If file is strictly a GFF file, only attribute is 'group.'

copy()

```
class galaxy.datatypes.util.gff_util.GFFIntervalToBEDReaderWrapper(reader,
                                                                    **kwargs)
```

Bases: `bx.intervals.io.NiceReaderWrapper`

Reader wrapper that reads GFF intervals/lines and automatically converts them to BED format.

parse_row(line)

```
class galaxy.datatypes.util.gff_util.GFFReaderWrapper(reader, chrom_col=0, fea-
                                              ture_col=2, start_col=3,
                                              end_col=4, strand_col=6,
                                              score_col=5, fix_strand=False,
                                              convert_to_bed_coord=False,
                                              **kwargs)
```

Bases: `bx.intervals.io.NiceReaderWrapper`

Reader wrapper for GFF files.

Wrapper has two major functions:

- 1.group entries for GFF file (via group column), GFF3 (via id attribute), or GTF (via gene_id/transcript id);
- 2.convert coordinates from GFF format—starting and ending coordinates are 1-based, closed—to the 'traditional'/BED interval format—0 based, half-open. This is useful when using GFF files as inputs to tools that expect traditional interval format.

next()

Returns next GFFFeature.

parse_row(line)

```
galaxy.datatypes.util.gff_util.convert_bed_coords_to_gff(interval)
```

Converts an interval object's coordinates from BED format to GFF format. Accepted object types include `GenomicInterval` and list (where the first element in the list is the interval's start, and the second element is the interval's end).

```
galaxy.datatypes.util.gff_util.convert_gff_coords_to_bed(interval)
```

Converts an interval object's coordinates from GFF format to BED format. Accepted object types include `GFFFeature`, `GenomicInterval`, and list (where the first element in the list is the interval's start, and the second element is the interval's end).

`galaxy.datatypes.util.gff_util.gff_attributes_to_str(attrs, gff_format)`

Convert GFF attributes to string. Supported formats are GFF3, GTF.

`galaxy.datatypes.util.gff_util.parse_gff_attributes(attr_str)`

Parses a GFF/GTF attribute string and returns a dictionary of name-value pairs. The general format for a GFF3 attributes string is

name1=value1;name2=value2

The general format for a GTF attribute string is

name1 "value1" ; name2 "value2"

The general format for a GFF attribute string is a single string that denotes the interval's group; in this case, method returns a dictionary with a single key-value pair, and key name is 'group'

`galaxy.datatypes.util.gff_util.read_unordered_gtf(iterator, strict=False)`

Returns GTF features found in an iterator. GTF lines need not be ordered or clustered for reader to work. Reader returns GFFFeature objects sorted by transcript_id, chrom, and start position.

image_util Module Provides utilities for working with image files.

`galaxy.datatypes.util.image_util.check_image_type(filename, types, image=None)`

`galaxy.datatypes.util.image_util.get_image_ext(file_path, image)`

`galaxy.datatypes.util.image_util.image_type(filename, image=None)`

eggs Package

eggs Package Manage Galaxy eggs

class `galaxy.eggs.CaseSensitiveConfigParser` (*defaults=None, dict_type=<class 'collections.OrderedDict'>, allow_no_value=False*)

Bases: `ConfigParser.SafeConfigParser`

optionxform (*optionstr*)

class `galaxy.eggs.Crate` (*galaxy_config_file=None, platform=None*)

Bases: `object`

Reads the eggs.ini file for use with checking and fetching.

all_eggs

Return a list of all eggs in the crate.

all_missing

Return true if any eggs in the eggs config file are missing.

all_names

Return a list of names of all eggs in the crate.

config_eggs

Return a list of all eggs in the crate that are needed based on the options set in the Galaxy config file.

config_file = `'/var/build/user_builds/galaxy/checkouts/latest/eggs.ini'`

config_missing

Return true if any eggs are missing, conditional on options set in the Galaxy config file.

config_names

Return a list of names of all eggs in the crate that are needed based on the options set in the Galaxy config file.

parse ()


```

parse_egg_section (eggs, tags, full_platform=False, egg_class=<class 'galaxy.eggs.Egg'>)
resolve (all=False)
    Try to resolve (e.g. fetch) all eggs in the crate.
class galaxy.eggs.Egg (name=None, version=None, tag=None, url=None, platform=None, crate=None)
    Bases: object

    Contains information about locating and downloading eggs.

    fetch () serves as the install method to pkg_resources.working_set.resolve()

    path
        Return the path of the egg, if it exists, or None

    remove_doppelgangers ()

    require ()

    resolve ()

    set_dir ()

    set_distribution ()
        Stores a pkg_resources Distribution object for reference later

    unpack_if_needed ()

    version_conflict (conflict_dist, conflict_req)
exception galaxy.eggs.EggNotFetchable (eggs)
    Bases: exceptions.Exception

class galaxy.eggs.GalaxyConfig (config_file)
    Bases: object

    always_conditional = ('pysam', 'ctypes', 'python_daemon')

    check_conditional (egg_name)

class galaxy.eggs.URLRetriever (*args, **kwargs)
    Bases: urllib.FancyURLopener

    http_error_default (*args)

galaxy.eggs.get_env ()

galaxy.eggs.remove_file_or_path (f)

galaxy.eggs.require (req_str)

galaxy.eggs.string_as_bool (string)

galaxy.eggs.unpack_zipfile (filename, extract_dir, ignores=[])

```

dist Module Manage Galaxy eggs

```

class galaxy.eggs.dist.DistScrambleCrate (galaxy_config_file, build_on='all')
    Bases: galaxy.eggs.scramble.ScrambleCrate

    Holds eggs with info on how to build them for distribution.

    dist_config_file = '/var/build/user_builds/galaxy/checkouts/latest/dist-eggs.ini'

    get_platforms (wanted)

    parse ()

```

```
    parse_egg_section (eggs, tags, full_platform=False)

class galaxy.eggs.dist.DistScrambleEgg (*args, **kwargs)
    Bases: galaxy.eggs.scramble.ScrambleEgg

    path

    run_scramble_script ()

    set_dir ()

    unpack_if_needed ()


scramble Module  Manage Galaxy eggs

class galaxy.eggs.scramble.ScrambleCrate (galaxy_config_file=None, platform=None)
    Bases: galaxy.eggs.__init__.Crate

    Reads the eggs.ini file for use with scrambling eggs.

    parse ()

    parse_egg_section (*args, **kwargs)

    scramble (all=False)

class galaxy.eggs.scramble.ScrambleEgg (*args, **kwargs)
    Bases: galaxy.eggs.__init__.Egg

    Contains information about scrambling eggs.

    archive_dir = '/var/build/user_builds/galaxy/checkouts/latest/scripts/scramble/archives'
    build_dir = '/var/build/user_builds/galaxy/checkouts/latest/scripts/scramble/build'
    copy_build_script ()
    ez_setup = '/var/build/user_builds/galaxy/checkouts/latest/scripts/scramble/lib/ez_setup.py'
    ez_setup_url = 'http://peak.telecommunity.com/dist/ez_setup.py'
    fetch_one (urls)
        Fetches the first available archive out of a list.
    fetch_source ()
        Get egg (and dependent) source
    get_tld (names)
    run_scramble_script ()
    scramble ()
    scramble_dir = '/var/build/user_builds/galaxy/checkouts/latest/scripts/scramble'
    script_dir = '/var/build/user_builds/galaxy/checkouts/latest/scripts/scramble/scripts'
    unpack_source ()
    unpack_tar ()
    unpack_zip ()

exception galaxy.eggs.scramble.ScrambleFailure (eggs, msg=None)
    Bases: exceptions.Exception
```

exceptions Package**exceptions Package** Custom exceptions for Galaxy**exception** `galaxy.exceptions.ActionInputError` (*err_msg*, *type*='error')Bases: `galaxy.exceptions.MessageException`**err_code** = <galaxy.exceptions.error_codes.ErrorCode object>**status_code** = 400**exception** `galaxy.exceptions.AdminRequiredException` (*err_msg*=None, *type*='info', ****extra_error_info**)Bases: `galaxy.exceptions.MessageException`**err_code** = <galaxy.exceptions.error_codes.ErrorCode object>**status_code** = 403**exception** `galaxy.exceptions.AuthenticationFailed` (*err_msg*=None, *type*='info', ****extra_error_info**)Bases: `galaxy.exceptions.MessageException`**err_code** = <galaxy.exceptions.error_codes.ErrorCode object>**status_code** = 401**exception** `galaxy.exceptions.AuthenticationRequired` (*err_msg*=None, *type*='info', ****extra_error_info**)Bases: `galaxy.exceptions.MessageException`**err_code** = <galaxy.exceptions.error_codes.ErrorCode object>**status_code** = 403**exception** `galaxy.exceptions.ConfigDoesNotAllowException` (*err_msg*=None, *type*='info', ****extra_error_info**)Bases: `galaxy.exceptions.MessageException`**err_code** = <galaxy.exceptions.error_codes.ErrorCode object>**status_code** = 403**exception** `galaxy.exceptions.ConfigurationError`Bases: `exceptions.Exception`**err_code** = <galaxy.exceptions.error_codes.ErrorCode object>**status_code** = 500**exception** `galaxy.exceptions.Conflict` (*err_msg*=None, *type*='info', ****extra_error_info**)Bases: `galaxy.exceptions.MessageException`**err_code** = <galaxy.exceptions.error_codes.ErrorCode object>**status_code** = 409**exception** `galaxy.exceptions.DeprecatedMethod` (*err_msg*=None, *type*='info', ****extra_error_info**)Bases: `galaxy.exceptions.MessageException`

Method (or a particular form/arg signature) has been removed and won't be available later

err_code = <galaxy.exceptions.error_codes.ErrorCode object>**status_code** = 404

```
exception galaxy.exceptions.DuplicatedIdentifierException (err_msg=None,
                                                         type='info',      **extra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 400

exception galaxy.exceptions.DuplicatedSlugException (err_msg=None, type='info', **extra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 400

exception galaxy.exceptions.InconsistentDatabase (err_msg=None, type='info', **extra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 500

exception galaxy.exceptions.InsufficientPermissionsException (err_msg=None,
                                                             type='info',      **extra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 403

exception galaxy.exceptions.InternalServerError (err_msg=None, type='info', **extra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 500

exception galaxy.exceptions.ItemAccessibilityException (err_msg=None, type='info', **extra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 403

exception galaxy.exceptions.ItemDeletionException (err_msg=None, type='info', **extra_error_info)

Bases: galaxy.exceptions.MessageException

exception galaxy.exceptions.ItemOwnershipException (err_msg=None, type='info', **extra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 403

exception galaxy.exceptions.MalformedId (err_msg=None, type='info', **extra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>
```

```

    status_code = 400

exception galaxy.exceptions.MessageException (err_msg=None,          type='info',          **ex-
                                             tra_error_info)

Bases: exceptions.Exception

Exception to make throwing errors from deep in controllers easier.

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 400

exception galaxy.exceptions.NotImplemented (err_msg=None, type='info', **extra_error_info)
Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 501

exception galaxy.exceptions.ObjectAttributeInvalidException (err_msg=None,
                                                            type='info',          **ex-
                                                            tra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 400

exception galaxy.exceptions.ObjectAttributeMissingException (err_msg=None,
                                                            type='info',          **ex-
                                                            tra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 400

exception galaxy.exceptions.ObjectInvalid
Bases: exceptions.Exception

Accessed object store ID is invalid

exception galaxy.exceptions.ObjectNotFound (err_msg=None, type='info', **extra_error_info)
Bases: galaxy.exceptions.MessageException

Accessed object was not found

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 404

exception galaxy.exceptions.RequestParameterInvalidException (err_msg=None,
                                                             type='info',          **ex-
                                                             tra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

status_code = 400

exception galaxy.exceptions.RequestParameterMissingException (err_msg=None,
                                                             type='info',          **ex-
                                                             tra_error_info)

Bases: galaxy.exceptions.MessageException

err_code = <galaxy.exceptions.error_codes.ErrorCode object>

```

```
status_code = 400
```

```
exception galaxy.exceptions.ToolMetaParameterException (err_msg=None, type='info',
                                                         **extra_error_info)
```

```
Bases: galaxy.exceptions.MessageException
```

```
err_code = <galaxy.exceptions.error_codes.ErrorCode object>
```

```
status_code = 400
```

```
exception galaxy.exceptions.UnknownContentsType (err_msg=None, type='info', **ex-
                                                  tra_error_info)
```

```
Bases: galaxy.exceptions.MessageException
```

```
err_code = <galaxy.exceptions.error_codes.ErrorCode object>
```

```
status_code = 400
```

external_services Package

actions Module

```
class galaxy.external_services.actions.ExternalServiceAction (elem, parent)
```

```
Bases: object
```

```
Abstract Class for External Service Actions
```

```
classmethod from_elem (elem, parent)
```

```
get_action_access_link (trans, param_dict)
```

```
handle_action (completed_action, param_dict, trans)
```

```
perform_action (param_dict)
```

```
populate_action (param_dict)
```

```
type = None
```

```
class galaxy.external_services.actions.ExternalServiceResult (name, param_dict)
```

```
Bases: object
```

```
content
```

```
class galaxy.external_services.actions.ExternalServiceTemplateAction (elem, par-
                                                                      ent)
```

```
Bases: galaxy.external_services.actions.ExternalServiceAction
```

```
Action that redirects to an external URL
```

```
perform_action (param_dict)
```

```
type = 'template'
```

```
class galaxy.external_services.actions.ExternalServiceValueResult (name,
                                                                    param_dict,
                                                                    value)
```

```
Bases: galaxy.external_services.actions.ExternalServiceResult
```

```
content
```

```
class galaxy.external_services.actions.ExternalServiceWebAPIAction (elem, parent)
```

```
Bases: galaxy.external_services.actions.ExternalServiceAction
```

```
Action that accesses an external Web API and provides handlers for the requested content
```

```

class ExternalServiceWebAPIActionRequest (elem, parent)
    Bases: object

    get_web_api_action (param_dict)

    ExternalServiceWebAPIAction.perform_action (param_dict)

    ExternalServiceWebAPIAction.type = 'web_api'
class galaxy.external_services.actions.ExternalServiceWebAPIActionResult (name,
                                                                              param_dict,
                                                                              url,
                                                                              method,
                                                                              tar-
                                                                              get)

    Bases: galaxy.external_services.actions.ExternalServiceResult

    content

class galaxy.external_services.actions.ExternalServiceWebAction (elem, parent)
    Bases: galaxy.external_services.actions.ExternalServiceAction

    Action that accesses an external web application

    get_action_access_link (trans, param_dict)

    type = 'web'
class galaxy.external_services.actions.PopulatedExternalServiceAction (action,
                                                                           param_dict)

    Bases: object

    get_action_access_link (trans)

    handle_results (trans)

    perform_action ()
class galaxy.external_services.actions.Template (elem, parent)
    Bases: object

    build_template (param_dict)

parameters Module
class galaxy.external_services.parameters.ExternalServiceParameter (elem, parent)
    Bases: object

    Abstract Class for External Service Parameters

    classmethod from_elem (elem, parent)

    get_value (param_dict)

    requires_user_input = False

    type = None
class galaxy.external_services.parameters.ExternalServiceTemplateParameter (elem,
                                                                               par-
                                                                               ent)

    Bases: galaxy.external_services.parameters.ExternalServiceParameter

    Parameter that returns a string containing the requested content

    get_value (param_dict)

```

```
type = 'template'
```

service Module

```
class galaxy.external_services.service.ActionSection (name, label)
    Bases: list

    has_action ()

class galaxy.external_services.service.BooleanExternalServiceActionsGroupWhen (parent,
                                                                                   name,
                                                                                   value,
                                                                                   la-
                                                                                   bel=None)

    Bases: galaxy.external_services.service.ExternalServiceActionsGroupWhen

    classmethod from_elem (parent, elem)
        Returns an instance of this when

    is_case (param_dict)

    type = 'boolean'

class galaxy.external_services.service.ExternalServiceActionsConditional (elem,
                                                                           par-
                                                                           ent)

    Bases: object

    get_current_cases (param_dict)

    type = 'conditional'

class galaxy.external_services.service.ExternalServiceActionsGroup (parent, name,
                                                                      label=None)

    Bases: object

    add_item (item)

    classmethod from_elem (elem, parent=None)
        Return ExternalServiceActionsGroup created from an xml element.

    load_sub_elems (elem)

    populate (service_instance, item=None, param_dict=None)

    prepare_actions (param_dict, parent_dict, parent_section)

class galaxy.external_services.service.ExternalServiceActionsGroupWhen (parent,
                                                                           name,
                                                                           la-
                                                                           bel=None)

    Bases: galaxy.external_services.service.ExternalServiceActionsGroup

    classmethod from_elem (parent, elem)
        Loads the proper when by attributes of elem

    get_ref (param_dict)

    is_case (param_dict)

    type = 'when'
```



```

class galaxy.external_services.service.ItemIsInstanceExternalServiceActionsGroupWhen (parent,
                                                                                       name,
                                                                                       value,
                                                                                       la-
                                                                                       bel=None)

    Bases: galaxy.external_services.service.ExternalServiceActionsGroupWhen

    classmethod from_elem (parent, elem)
        Returns an instance of this when

    is_case (param_dict)

    type = 'item_type'

class galaxy.external_services.service.PopulatedExternalService (service_group,
                                                                 service_instance,
                                                                 item,
                                                                 param_dict=None)

    Bases: object

    get_action_by_name (actions_list)

    perform_action_by_name (actions_list)

    populate ()

class galaxy.external_services.service.ValueExternalServiceActionsGroupWhen (parent,
                                                                                   name,
                                                                                   value,
                                                                                   la-
                                                                                   bel=None)

    Bases: galaxy.external_services.service.ExternalServiceActionsGroupWhen

    classmethod from_elem (parent, elem)
        Returns an instance of this when

    is_case (param_dict)

    type = 'value'

galaxy.external_services.service.class_type
    alias of ItemIsInstanceExternalServiceActionsGroupWhen

```

Subpackages

result_handlers Package

basic Module

```

class galaxy.external_services.result_handlers.basic.ExternalServiceActionJQueryGridResultHan

    Bases: galaxy.external_services.result_handlers.basic.ExternalServiceActionResultHandler

    Class for External Service Actions JQuery Result Handler

    handle_result (result, param_dict, trans)

    type = 'jquery_grid'

```

```
class galaxy.external_services.result_handlers.basic.ExternalServiceActionJSONResultHandler (elem, parent)

    Bases: galaxy.external_services.result_handlers.basic.ExternalServiceActionResultHandler

    Class for External Service Actions JQuery Result Handler

    handle_result (result, param_dict, trans)

    type = 'json_display'

class galaxy.external_services.result_handlers.basic.ExternalServiceActionResultHandler (elem, parent)

    Bases: object

    Basic Class for External Service Actions Result Handlers

    classmethod from_elem (elem, parent)

    handle_result (result, param_dict, trans)

    type = 'display'

class galaxy.external_services.result_handlers.basic.ExternalServiceActionURLRedirectResultHandler (elem, parent)

    Bases: galaxy.external_services.result_handlers.basic.ExternalServiceActionResultHandler

    Basic Class for External Service Actions Result Handlers

    classmethod from_elem (elem, parent)

    handle_result (result, param_dict, trans)

    type = 'web_redirect'

galaxy.external_services.result_handlers.basic.handler_class
    alias of ExternalServiceActionJSONResultHandler
```

forms Package

forms Module FormDefinition and field factories

```
class galaxy.forms.forms.FormDefinitionAddressFieldFactory

    Bases: galaxy.forms.forms.FormDefinitionFieldFactory

    from_elem (elem, layout=None)
        Return FormDefinition field created from an xml element.

    new (name=None, label=None, required=False, helptext=None, default=None, visible=True, layout=None)
        Return new FormDefinition field.

    type = 'address'

class galaxy.forms.forms.FormDefinitionFactory (form_types, field_type_factories)

    Bases: object

    from_elem (elem, form_definition_current=None)
        Return FormDefinition created from an xml element.

    new (form_type, name, description=None, fields=None, layout=None, form_definition_current=None)
        Return new FormDefinition.
```

```

class galaxy.forms.forms.FormDefinitionFieldFactory
    Bases: object

    from_elem (elem, layout=None)
        Return FormDefinition created from an xml element.

    new (name=None, label=None, required=False, helptext=None, default=None, visible=True, layout=None)
        Return new FormDefinition field.

    type = None

class galaxy.forms.forms.FormDefinitionHistoryFieldFactory
    Bases: galaxy.forms.forms.FormDefinitionFieldFactory

    from_elem (elem, layout=None)
        Return FormDefinition field created from an xml element.

    new (name=None, label=None, required=False, helptext=None, default=None, visible=True, layout=None)
        Return new FormDefinition field.

    type = 'history'

class galaxy.forms.forms.FormDefinitionPasswordFieldFactory
    Bases: galaxy.forms.forms.FormDefinitionFieldFactory

    from_elem (elem, layout=None)
        Return FormDefinition field created from an xml element.

    new (name=None, label=None, required=False, helptext=None, default=None, visible=True, layout=None, area=False)
        Return new FormDefinition field.

    type = 'password'

class galaxy.forms.forms.FormDefinitionSelectFieldFactory
    Bases: galaxy.forms.forms.FormDefinitionFieldFactory

    from_elem (elem, layout=None)
        Return FormDefinition field created from an xml element.

    new (name=None, label=None, required=False, helptext=None, default=None, visible=True, layout=None, options=[], checkboxes=False)
        Return new FormDefinition field.

    type = 'select'

class galaxy.forms.forms.FormDefinitionTextFieldFactory
    Bases: galaxy.forms.forms.FormDefinitionFieldFactory

    from_elem (elem, layout=None)
        Return FormDefinition field created from an xml element.

    new (name=None, label=None, required=False, helptext=None, default=None, visible=True, layout=None, area=False)
        Return new FormDefinition field.

    type = 'text'

class galaxy.forms.forms.FormDefinitionWorkflowFieldFactory
    Bases: galaxy.forms.forms.FormDefinitionFieldFactory

    from_elem (elem, layout=None)
        Return FormDefinition field created from an xml element.

```

new (*name=None, label=None, required=False, helptext=None, default=None, visible=True, layout=None*)
Return new FormDefinition field.

type = 'workflow'

class galaxy.forms.forms.**FormDefinitionWorkflowMappingFieldFactory**

Bases: *galaxy.forms.forms.FormDefinitionFieldFactory*

from_elem (*elem, layout=None*)

Return FormDefinition field created from an xml element.

new (*name=None, label=None, required=False, helptext=None, default=None, visible=True, layout=None*)
Return new FormDefinition field.

type = 'workflowmapping'

galaxy.forms.forms.**field**

alias of *FormDefinitionHistoryFieldFactory*

jobs Package

jobs Package Support for running a tool in Galaxy via an internal job management system

class galaxy.jobs.**ComputeEnvironment**

Bases: object

Definition of the job as it will be run on the (potentially) remote compute server.

config_directory ()

Directory containing config files (potentially remote)

input_paths ()

Input DatasetPaths defined by job.

new_file_path ()

Absolute path to dump new files for this job on compute server.

output_paths ()

Output DatasetPaths defined by job.

sep ()

os.path.sep for the platform this job will execute in.

tool_directory ()

Absolute path to tool files for this job on compute server.

unstructured_path_rewriter ()

Return a function that takes in a value, determines if it is path to be rewritten (will be passed non-path values as well - onus is on this function to determine both if its input is a path and if it should be rewritten.)

version_path ()

Location of the version file for the underlying tool.

working_directory ()

Job working directory (potentially remote)

class galaxy.jobs.**JobConfiguration** (*app*)

Bases: object

A parser and interface to advanced job management features.

These features are configured in the job configuration, by default, `job_conf.xml`

DEFAULT_NWORKERS = 4

convert_legacy_destinations (*job_runners*)

Converts legacy (from a URL) destinations to contain the appropriate runner params defined in the URL.

Parameters *job_runners* (*list of job runner plugins*) – All loaded job runner plugins.

default_job_tool_configuration

The default JobToolConfiguration, used if a tool does not have an explicit definition in the configuration. It consists of a reference to the default handler and default destination.

Returns JobToolConfiguration – a representation of a <tool> element that uses the default handler and destination

get_destination (*id_or_tag*)

Given a destination ID or tag, return the JobDestination matching the provided ID or tag

Parameters *id_or_tag* (*str*) – A destination ID or tag.

Returns JobDestination – A valid destination

Destinations are deepcopied as they are expected to be passed in to job runners, which will modify them for persisting params set at runtime.

get_destinations (*id_or_tag*)

Given a destination ID or tag, return all JobDestinations matching the provided ID or tag

Parameters *id_or_tag* (*str*) – A destination ID or tag.

Returns list or tuple of JobDestinations

Destinations are not deepcopied, so they should not be passed to anything which might modify them.

get_handler (*id_or_tag*)

Given a handler ID or tag, return the provided ID or an ID matching the provided tag

Parameters *id_or_tag* (*str*) – A handler ID or tag.

Returns str – A valid job handler ID.

get_job_runner_plugins (*handler_id*)

Load all configured job runner plugins

Returns list of job runner plugins

get_job_tool_configurations (*ids*)

Get all configured JobToolConfigurations for a tool ID, or, if given a list of IDs, the JobToolConfigurations for the first id in *ids* matching a tool definition.

Note: You should not mix tool shed tool IDs, versionless tool shed IDs, and tool config tool IDs that refer to the same tool.

Parameters *ids* (*list or str*) – Tool ID or IDs to fetch the JobToolConfiguration of.

Returns list – JobToolConfiguration Bunches representing <tool> elements matching the specified ID(s).

Example tool ID strings include:

- Full tool shed id: `toolshed.example.org/repos/nate/filter_tool_repo/filter_tool/1.0.0`
- Tool shed id less version: `toolshed.example.org/repos/nate/filter_tool_repo/filter_tool`
- Tool config tool id: `filter_tool`

get_tool_resource_parameters (*tool_id*)

Given a tool id, return XML elements describing parameters to insert into job resources.

Tool id A tool ID (a string)

Returns List of parameter elements.

is_handler (*server_name*)

Given a server name, indicate whether the server is a job handler

Parameters **server_name** (*str*) – The name to check

Returns bool

is_id (*collection*)

Given a collection of handlers or destinations, indicate whether the collection represents a tag or a real ID

Parameters **collection** (*tuple or list*) – A representation of a destination or handler

Returns bool

is_tag (*collection*)

Given a collection of handlers or destinations, indicate whether the collection represents a tag or a real ID

Parameters **collection** (*tuple or list*) – A representation of a destination or handler

Returns bool

class `galaxy.jobs.JobDestination` (***kws*)

Bases: `galaxy.util.bunch.Bunch`

Provides details about where a job runs

class `galaxy.jobs.JobToolConfiguration` (***kws*)

Bases: `galaxy.util.bunch.Bunch`

Provides details on what handler and destination a tool should use

A JobToolConfiguration will have the required attribute ‘id’ and optional attributes ‘handler’, ‘destination’, and ‘params’

get_resource_group ()

class `galaxy.jobs.JobWrapper` (*job, queue, use_persisted_destination=False*)

Bases: `object`

Wraps a ‘model.Job’ with convenience methods for running processes and state management.

can_split ()

change_ownership_for_run ()

change_state (*state, info=False*)

check_limits (*runtime=None*)

check_tool_output (*stdout, stderr, tool_exit_code, job*)

cleanup (*delete_files=True*)

clear_working_directory ()

commands_in_new_shell

compute_outputs ()

create_working_directory ()

default_compute_environment (*job=None*)

fail (*message*, *exception=False*, *stdout=''*, *stderr=''*, *exit_code=None*)

Indicate job failure by setting state and message on all output datasets.

finish (*stdout*, *stderr*, *tool_exit_code=None*, *remote_working_directory=None*)

Called to indicate that the associated command has been run. Updates the output datasets based on stderr and stdout from the command, and the contents of the output files.

galaxy_lib_dir

galaxy_system_pwent

get_command_line ()

get_dataset_finish_context (*job_context*, *dataset*)

get_env_setup_clause ()

get_id_tag ()

get_input_dataset_fnames (*ds*)

get_input_fnames ()

get_input_paths (*job=None*)

get_job ()

get_job_runner ()

get_job_runner_url ()

get_mutable_output_fnames ()

get_output_destination (*output_path*)

Destination for outputs marked as from_work_dir. This is the normal case, just copy these files directly to the ultimate destination.

get_output_file_id (*file*)

get_output_fnames ()

get_output_hdas_and_fnames ()

get_output_sizes ()

get_parallelism ()

get_param_dict ()

Restore the dictionary of parameters from the database.

get_session_id ()

get_state ()

get_tool_provided_job_metadata ()

get_version_string_path ()

has_limits ()

invalidate_external_metadata ()

job_destination

Return the JobDestination that this job will use to run. This will either be a configured destination, a randomly selected destination if the configured destination was a tag, or a dynamically generated destination from the dynamic runner.

Calling this method for the first time causes the dynamic runner to do its calculation, if any.

Returns JobDestination

mark_as_resubmitted (*info=None*)

pause (*job=None, message=None*)

prepare (*compute_environment=None*)

Prepare the job to run by creating the working directory and the config files.

reclaim_ownership ()

requires_setting_metadata

set_job_destination (*job_destination, external_id=None*)

Persist job destination params in the database for recovery.

self.job_destination is not used because a runner may choose to rewrite parts of the destination (e.g. the params).

set_runner (*runner_url, external_id*)

setup_external_metadata (*exec_dir=None, tmp_dir=None, dataset_files_path=None, config_root=None, config_file=None, datatypes_config=None, set_extension=True, **kwargs*)

user

user_system_pwent

class galaxy.jobs.NoopQueue

Bases: object

Implements the JobQueue / JobStopQueue interface but does nothing

put (**args, **kwargs*)

put_stop (**args*)

shutdown ()

class galaxy.jobs.ParallelismInfo (*tag*)

Bases: object

Stores the information (if any) for running multiple instances of the tool in parallel on the same set of inputs.

class galaxy.jobs.SharedComputeEnvironment (*job_wrapper, job*)

Bases: *galaxy.jobs.SimpleComputeEnvironment*

Default ComputeEnvironment for job and task wrapper to pass to ToolEvaluator - valid when Galaxy and compute share all the relevant file systems.

input_paths ()

new_file_path ()

output_paths ()

tool_directory ()

version_path ()

working_directory ()

class galaxy.jobs.SimpleComputeEnvironment

Bases: object

config_directory ()

sep ()


```

unstructured_path_rewriter ()

class galaxy.jobs.TaskWrapper (task, queue)
    Bases: galaxy.jobs.JobWrapper

    Extension of JobWrapper intended for running tasks. Should be refactored into a generalized executable unit
    wrapper parent, then jobs and tasks.

    can_split ()

    change_state (state, info=False)

    cleanup (delete_files=True)

    fail (message, exception=False)

    finish (stdout, stderr, tool_exit_code=None)
        Called to indicate that the associated command has been run. Updates the output datasets based on stderr
        and stdout from the command, and the contents of the output files.

    get_command_line ()

    get_dataset_finish_context (job_context, dataset)

    get_exit_code ()

    get_id_tag ()

    get_job ()

    get_output_destination (output_path)
        Destination for outputs marked as from_work_dir. These must be copied with the same basenme as the
        path for the ultimate output destination. This is required in the task case so they can be merged.

    get_output_file_id (file)

    get_param_dict ()
        Restore the dictionary of parameters from the database.

    get_session_id ()

    get_state ()

    get_task ()

    get_tool_provided_job_metadata ()

    prepare (compute_environment=None)
        Prepare the job to run by creating the working directory and the config files.

    set_runner (runner_url, external_id)

    setup_external_metadata (exec_dir=None, tmp_dir=None, dataset_files_path=None, con-
        fig_root=None, config_file=None, datatypes_config=None,
        set_extension=True, **kws)

galaxy.jobs.config_exception (e, file)

```

handler Module Galaxy job handler, prepares, runs, tracks, and finishes Galaxy jobs

```

class galaxy.jobs.handler.DefaultJobDispatcher (app)
    Bases: object

    put (job_wrapper)

    recover (job, job_wrapper)

```

shutdown()

stop(*job*)

Stop the given job. The input variable *job* may be either a Job or a Task.

url_to_destination(*url*)

This is used by the runner mapper (a.k.a. dynamic runner) and recovery methods to have runners convert URLs to destinations.

New-style runner plugin IDs must match the URL's scheme for this to work.

class `galaxy.jobs.handler.JobHandler(app)`

Bases: `object`

Handle the preparation, running, tracking, and finishing of jobs

shutdown()

start()

class `galaxy.jobs.handler.JobHandlerQueue(app, dispatcher)`

Bases: `object`

Job Handler's Internal Queue, this is what actually implements waiting for jobs to be runnable and dispatching to a JobRunner.

STOP_SIGNAL = <object object>

get_total_job_count_per_destination()

get_user_job_count(*user_id*)

get_user_job_count_per_destination(*user_id*)

increase_running_job_count(*user_id*, *destination_id*)

job_pair_for_id(*id*)

job_wrapper(*job*, *use_persisted_destination=False*)

put(*job_id*, *tool_id*)

Add a job to the queue (by job identifier)

shutdown()

Attempts to gracefully shut down the worker thread

start()

Starts the JobHandler's thread after checking for any unhandled jobs.

class `galaxy.jobs.handler.JobHandlerStopQueue(app, dispatcher)`

Bases: `object`

A queue for jobs which need to be terminated prematurely.

STOP_SIGNAL = <object object>

monitor()

Continually iterate the waiting jobs, stop any that are found.

monitor_step()

Called repeatedly by *monitor* to stop jobs.

put(*job_id*, *error_msg=None*)

shutdown()

Attempts to gracefully shut down the worker thread

manager Module Top-level Galaxy job manager, moves jobs to handler(s)

class `galaxy.jobs.manager.JobManager` (*app*)

Bases: `object`

Highest level interface to job management.

TODO: Currently the app accesses “job_queue” and “job_stop_queue” directly. This should be decoupled.

shutdown ()

start ()

class `galaxy.jobs.manager.NoopHandler` (**args, **kwargs*)

Bases: `object`

shutdown (**args*)

start ()

mapper Module

exception `galaxy.jobs.mapper.JobMappingException` (*failure_message*)

Bases: `exceptions.Exception`

exception `galaxy.jobs.mapper.JobNotReadyException` (*job_state=None, message=None*)

Bases: `exceptions.Exception`

class `galaxy.jobs.mapper.JobRunnerMapper` (*job_wrapper, url_to_destination, job_config*)

Bases: `object`

This class is responsible to managing the mapping of jobs (in the form of *job_wrappers*) to job runner url strings.

cache_job_destination (*raw_job_destination*)

get_job_destination (*params*)

Cache the *job_destination* to avoid recalculation.

transfer_manager Module Manage transfers from arbitrary URLs to temporary files. Socket interface for IPC with multiple process configurations.

class `galaxy.jobs.transfer_manager.Sleeper`

Bases: `object`

Provides a ‘sleep’ method that sleeps for a number of seconds *unless* the notify method is called (from a different thread).

sleep (*seconds*)

wake ()

class `galaxy.jobs.transfer_manager.TransferManager` (*app*)

Bases: `object`

Manage simple data transfers from URLs to temporary locations.

get_state (*transfer_jobs, via_socket=False*)

new (*path=None, **kwd*)

run (*transfer_jobs*)

This method blocks, so if invoking the transfer manager ever starts taking too long, we should move it to a thread. However, the *transfer_manager* will either daemonize or return after submitting to a running daemon, so it should be fairly quick to return.

```
shutdown()
```

Subpackages

actions Package

actions Package This package contains job action classes.

post Module Actions to be run at job completion (or output hda creation, as in the case of immediate_actions listed below. Currently only used in workflows.

```
class galaxy.jobs.actions.post.ActionBox
    Bases: object

    actions = {'ChangeDatatypeAction': <class 'galaxy.jobs.actions.post.ChangeDatatypeAction'>, 'RenameDatasetAction'
    classmethod execute (app, sa_session, pja, job, replacement_dict=None)
    classmethod get_add_list ()
    classmethod get_forms (trans)
    classmethod get_short_str (action)
    classmethod handle_incoming (incoming)
    immediate_actions = ['ChangeDatatypeAction', 'RenameDatasetAction', 'TagDatasetAction']
    public_actions = ['RenameDatasetAction', 'ChangeDatatypeAction', 'ColumnSetAction', 'EmailAction', 'DeleteInte

class galaxy.jobs.actions.post.ChangeDatatypeAction
    Bases: galaxy.jobs.actions.post.DefaultJobAction

    classmethod execute (app, sa_session, action, job, replacement_dict)
    classmethod get_config_form (trans)
    classmethod get_short_str (pja)
    name = 'ChangeDatatypeAction'
    verbose_name = 'Change Datatype'

class galaxy.jobs.actions.post.ColumnSetAction
    Bases: galaxy.jobs.actions.post.DefaultJobAction

    classmethod execute (app, sa_session, action, job, replacement_dict)
    classmethod get_config_form (trans)
    classmethod get_short_str (pja)
    name = 'ColumnSetAction'
    verbose_name = 'Assign Columns'

class galaxy.jobs.actions.post.DefaultJobAction
    Bases: object

    Base job action.

    classmethod execute (app, sa_session, action, job, replacement_dict=None)
    classmethod get_config_form (trans)
```

```

    classmethod get_short_str (pja)
    name = 'DefaultJobAction'
    verbose_name = 'Default Job'
class galaxy.jobs.actions.post.DeleteDatasetAction
    Bases: galaxy.jobs.actions.post.DefaultJobAction
    classmethod execute (app, sa_session, action, job, replacement_dict)
    classmethod get_config_form (trans)
    classmethod get_short_str (pja)
    name = 'DeleteDatasetAction'
    verbose_name = 'Delete Dataset'
class galaxy.jobs.actions.post.DeleteIntermediatesAction
    Bases: galaxy.jobs.actions.post.DefaultJobAction
    classmethod execute (app, sa_session, action, job, replacement_dict)
    classmethod get_config_form (trans)
    classmethod get_short_str (pja)
    name = 'DeleteIntermediatesAction'
    verbose_name = 'Delete Non-Output Completed Intermediate Steps'
class galaxy.jobs.actions.post.EmailAction
    Bases: galaxy.jobs.actions.post.DefaultJobAction
    This action sends an email to the galaxy user responsible for a job.
    classmethod execute (app, sa_session, action, job, replacement_dict)
    classmethod get_config_form (trans)
    classmethod get_short_str (pja)
    name = 'EmailAction'
    verbose_name = 'Email Notification'
class galaxy.jobs.actions.post.HideDatasetAction
    Bases: galaxy.jobs.actions.post.DefaultJobAction
    classmethod execute (app, sa_session, action, job, replacement_dict)
    classmethod get_config_form (trans)
    classmethod get_short_str (pja)
    name = 'HideDatasetAction'
    verbose_name = 'Hide Dataset'
class galaxy.jobs.actions.post.RenameDatasetAction
    Bases: galaxy.jobs.actions.post.DefaultJobAction
    classmethod execute (app, sa_session, action, job, replacement_dict)
    classmethod get_config_form (trans)
    classmethod get_short_str (pja)
    name = 'RenameDatasetAction'

```

```
    verbose_name = 'Rename Dataset'

class galaxy.jobs.actions.post.SetMetadataAction
    Bases: galaxy.jobs.actions.post.DefaultJobAction

    classmethod execute (app, sa_session, action, job, replacement_dict)

    classmethod get_config_form (trans)

    name = 'SetMetadataAction'

class galaxy.jobs.actions.post.TagDatasetAction
    Bases: galaxy.jobs.actions.post.DefaultJobAction

    classmethod execute (app, sa_session, action, job, replacement_dict)

    classmethod get_config_form (trans)

    classmethod get_short_str (pja)

    name = 'TagDatasetAction'

    verbose_name = 'Add tag to dataset'

galaxy.jobs.actions.post.get_form_template (action_type, title, content, help,
                                           on_output=True)
```

deferred Package

deferred Package Queue for running deferred code via plugins.

```
class galaxy.jobs.deferred.DeferredJobQueue (app)
    Bases: object

    job_states = <galaxy.util.bunch.Bunch object>

    shutdown ()

class galaxy.jobs.deferred.FakeTrans (app, history=None, user=None)
    Bases: object

    A fake trans for calling the external set metadata tool

    db_dataset_for (dbkey)

    get_current_user_roles ()

    get_galaxy_session ()

    log_event (message, tool_id=None)

class galaxy.jobs.deferred.Sleeper
    Bases: object

    Provides a 'sleep' method that sleeps for a number of seconds unless the notify method is called (from a different thread).

    sleep (seconds)

    wake ()
```

data_transfer Module Module for managing data transfer jobs.

```
class galaxy.jobs.deferred.data_transfer.DataTransfer (app)
    Bases: object

    check_interval = 15

    check_job (job)

    create_job (trans, **kwd)

    dataset_datatype_re = <_sre.SRE_Pattern object>

    dataset_name_re = <_sre.SRE_Pattern object>

    run_job (job)
```

genome_index Module

genome_transfer Module

liftover_transfer Module

manual_data_transfer Module Generic module for managing manual data transfer jobs using Galaxy's built-in file browser. This module can be used by various external services that are configured to transfer data manually.

```
class galaxy.jobs.deferred.manual_data_transfer.ManualDataTransferPlugin (app)
    Bases: galaxy.jobs.deferred.data_transfer.DataTransfer

    check_job (job)

    create_job (trans, **kwd)
```

pacific_biosciences_smrt_portal Module Module for managing jobs in Pacific Bioscience's SMRT Portal and automatically transferring files produced by SMRT Portal.

```
class galaxy.jobs.deferred.pacific_biosciences_smrt_portal.SMRTPortalPlugin (app)
    Bases: galaxy.jobs.deferred.data_transfer.DataTransfer

    api_path = '/smrtportal/api'

    check_job (job)

    create_job (trans, **kwd)
```

runners Package

runners Package Base classes for job runner plugins.

```
class galaxy.jobs.runners.AsynchronousJobRunner (app, nworkers, **kwargs)
    Bases: galaxy.jobs.runners.BaseJobRunner

    Parent class for any job runner that runs jobs asynchronously (e.g. via a distributed resource manager). Provides
    general methods for having a thread to monitor the state of asynchronous jobs and submitting those jobs to the
    correct methods (queue, finish, cleanup) at appropriate times..

    check_watched_item (job_state)
```

check_watched_items()

This method is responsible for iterating over `self.watched` and handling state changes and updating `self.watched` with a new list of watched job states. Subclasses can opt to override this directly (as older job runners will initially) or just override `check_watched_item` and allow the list processing to reuse the logic here.

fail_job(job_state)

finish_job(job_state)

Get the output/error for a finished job, pass to `job_wrapper.finish` and cleanup all the job's temporary files.

handle_stop()

mark_as_failed(job_state)

mark_as_finished(job_state)

monitor()

Watches jobs currently in the monitor queue and deals with state changes (queued to running) and job completion.

monitor_job(job_state)

shutdown()

Attempts to gracefully shut down the monitor thread

```
class galaxy.jobs.runners.AsynchronousJobState(files_dir=None, job_wrapper=None,
                                              job_id=None, job_file=None, out-
                                              put_file=None, error_file=None,
                                              exit_code_file=None, job_name=None,
                                              job_destination=None)
```

Bases: `galaxy.jobs.runners.JobState`

Encapsulate the state of an asynchronous job, this should be subclassed as needed for various job runners to capture additional information needed to communicate with distributed resource manager.

check_limits(runtime=None)

cleanup()

register_cleanup_file_attribute(attribute)

running

```
class galaxy.jobs.runners.BaseJobRunner(app, nworkers, **kwargs)
```

Bases: `object`

DEFAULT_SPECS = {'recheck_missing_job_retries': {'default': 0, 'map': <type 'int'>, 'valid': <function <lambda> at 0x...

build_command_line(job_wrapper, include_metadata=False, include_work_dir_outputs=True)

get_job_file(job_wrapper, **kws)

get_work_dir_outputs(job_wrapper, job_working_directory=None)

Returns list of pairs (source_file, destination) describing path to work_dir output file and ultimate destination.

mark_as_queued(job_wrapper)

mark_as_resubmitted(job_state, info=None)

parse_destination_params(params)

Parse the JobDestination `params` dict and return the runner's native representation of those params.

prepare_job(job_wrapper, include_metadata=False, include_work_dir_outputs=True)

Some sanity checks that all runners' `queue_job()` methods are likely to want to do

put (*job_wrapper*)

Add a job to the queue (by job identifier), indicate that the job is ready to run.

queue_job (*job_wrapper*)

recover (*job, job_wrapper*)

run_next ()

Run the next item in the work queue (a job waiting to run)

shutdown ()

Attempts to gracefully shut down the worker threads

stop_job (*job*)

url_to_destination (*url*)

Convert a legacy URL to a JobDestination.

Job runner URLs are deprecated, JobDestinations should be used instead. This base class method converts from a URL to a very basic JobDestination without destination params.

class `galaxy.jobs.runners.JobState`

Bases: `object`

Encapsulate state of jobs.

static default_exit_code_file (*files_dir, id_tag*)

static default_job_file (*files_dir, id_tag*)

runner_states = `<galaxy.util.bunch.Bunch object>`

set_defaults (*files_dir*)

class `galaxy.jobs.runners.RunnerParams` (*specs=None, params=None*)

Bases: `galaxy.util.ParamsWithSpecs`

cli Module Job control via a command line interface (e.g. qsub/qstat), possibly over a remote connection (e.g. ssh).

class `galaxy.jobs.runners.cli.ShellJobRunner` (*app, nworkers*)

Bases: `galaxy.jobs.runners.AsynchronousJobRunner`

Job runner backed by a finite pool of worker threads. FIFO scheduling

check_watched_items ()

Called by the monitor thread to look at each watched job and deal with state changes.

finish_job (*job_state*)

For recovery of jobs started prior to standardizing the naming of files in the AsynchronousJobState object

get_cli_plugins (*shell_params, job_params*)

parse_destination_params (*params*)

queue_job (*job_wrapper*)

Create job script and submit it to the DRM

recover (*job, job_wrapper*)

Recovers jobs stuck in the queued/running state when Galaxy started

runner_name = `'ShellRunner'`

stop_job (*job*)

Attempts to delete a dispatched job

url_to_destination (*url*)

condor Module Job control via the Condor DRM.

class `galaxy.jobs.runners.condor.CondorJobRunner` (*app, nworkers*)

Bases: `galaxy.jobs.runners.AsynchronousJobRunner`

Job runner backed by a finite pool of worker threads. FIFO scheduling

check_watched_items ()

Called by the monitor thread to look at each watched job and deal with state changes.

queue_job (*job_wrapper*)

Create job script and submit it to the DRM

recover (*job, job_wrapper*)

Recovers jobs stuck in the queued/running state when Galaxy started

runner_name = 'CondorRunner'

stop_job (*job*)

Attempts to delete a job from the DRM queue

drmaa Module Job control via the DRMAA API.

class `galaxy.jobs.runners.drmaa.DRMAAJobRunner` (*app, nworkers, **kwargs*)

Bases: `galaxy.jobs.runners.AsynchronousJobRunner`

Job runner backed by a finite pool of worker threads. FIFO scheduling

check_watched_items ()

Called by the monitor thread to look at each watched job and deal with state changes.

external_runjob (*jobtemplate_filename, username*)

runs an external script the will QSUB a new job. The external script will be run with sudo, and will setuid() to the specified user. Effectively, will QSUB as a different user (then the one used by Galaxy).

get_native_spec (*url*)

Get any native DRM arguments specified by the site configuration

queue_job (*job_wrapper*)

Create job script and submit it to the DRM

recover (*job, job_wrapper*)

Recovers jobs stuck in the queued/running state when Galaxy started

runner_name = 'DRMAARunner'

stop_job (*job*)

Attempts to delete a job from the DRM queue

store_jobtemplate (*job_wrapper, jt*)

Stores the content of a DRMAA JobTemplate object in a file as a JSON string. Path is hard-coded, but it's no worse than other path in this module. Uses Galaxy's JobID, so file is expected to be unique.

url_to_destination (*url*)

Convert a legacy URL to a job destination

local Module Job runner plugin for executing jobs on the local system via the command line.

```
class galaxy.jobs.runners.local.LocalJobRunner (app, nworkers)
```

Bases: *galaxy.jobs.runners.BaseJobRunner*

Job runner backed by a finite pool of worker threads. FIFO scheduling

queue_job (*job_wrapper*)

recover (*job, job_wrapper*)

runner_name = 'LocalRunner'

stop_job (*job*)

lwr Module

```
class galaxy.jobs.runners.lwr.LwrJobRunner (app, nworkers, **kws)
```

Bases: *galaxy.jobs.runners.AsynchronousJobRunner*

LWR Job Runner

check_pid (*pid*)

check_watched_item (*job_state*)

fail_job (*job_state*)

Seperated out so we can use the worker threads for it.

finish_job (*job_state*)

get_client (*job_destination_params, job_id, env=[]*)

get_client_from_state (*job_state*)

get_client_from_wrapper (*job_wrapper*)

get_input_files (*job_wrapper*)

get_output_files (*job_wrapper*)

queue_job (*job_wrapper*)

recover (*job, job_wrapper*)

Recovers jobs stuck in the queued/running state when Galaxy started

runner_name = 'LWRRunner'

shutdown ()

stop_job (*job*)

url_to_destination (*url*)

Convert a legacy URL to a job destination

pbs Module

tasks Module

```
class galaxy.jobs.runners.tasks.TaskedJobRunner (app, nworkers)
```

Bases: *galaxy.jobs.runners.BaseJobRunner*

Job runner backed by a finite pool of worker threads. FIFO scheduling

queue_job (*job_wrapper*)

```
recover (job, job_wrapper)  
runner_name = 'TaskRunner'  
stop_job (job)
```

Subpackages

cli_job Package

cli_job Package

torque Module

cli_shell Package

cli_shell Package

rsh Module

splitters Package

basic Module

```
galaxy.jobs.splitters.basic.do_merge (job_wrapper, task_wrappers)  
galaxy.jobs.splitters.basic.do_split (job_wrapper)  
galaxy.jobs.splitters.basic.set_basic_defaults (job_wrapper)
```

multi Module

```
galaxy.jobs.splitters.multi.do_merge (job_wrapper, task_wrappers)  
galaxy.jobs.splitters.multi.do_split (job_wrapper)
```

model Package

model Package Galaxy data model classes

Naming: try to use class names that have a distinct plural form so that the relationship cardinalities are obvious (e.g. prefer Dataset to Data)

```
class galaxy.model.APIKeys (id=None, user_id=None, key=None)  
    Bases: object
```

```
class galaxy.model.BaseJobMetric (plugin, metric_name, metric_value)  
    Bases: object
```

```
exception galaxy.model.ConverterDependencyException (value)  
    Bases: exceptions.Exception
```

```
class galaxy.model.DataManagerHistoryAssociation (id=None, history=None, user=None)  
    Bases: object
```

```

class galaxy.model.DataManagerJobAssociation (id=None,                                     job=None,
                                             data_manager_id=None)
    Bases: object

class galaxy.model.Dataset (id=None, state=None, external_filename=None, extra_files_path=None,
                             file_size=None, purgable=True, uuid=None)
    Bases: object

    conversion_messages = <galaxy.util.bunch.Bunch object>
    engine = None
    extra_files_path
    file_name
    file_path = '/tmp/'
    full_delete ()
        Remove the file and extra files, marks deleted and purged
    get_access_roles (trans)
    get_extra_files_path ()
    get_file_name ()
    get_manage_permissions_roles (trans)
    get_size (nice_size=False)
        Returns the size of the data on disk
    get_total_size ()
    has_data ()
        Detects whether there is any data
    has_manage_permissions_roles (trans)
    in_ready_state ()
    is_multi_byte ()
    mark_deleted (include_children=True)
    non_ready_states = ('upload', 'queued', 'running', 'setting_metadata')
    object_store = None
    permitted_actions = <galaxy.util.bunch.Bunch object>
    ready_states = ('discarded', 'ok', 'failed_metadata', 'paused', 'error', 'new', 'empty')
    set_extra_files_path (extra_files_path)
    set_file_name (filename)
    set_size ()
        Returns the size of the data on disk
    set_total_size ()
    states = <galaxy.util.bunch.Bunch object>
    user_can_purge

class galaxy.model.DatasetCollection (id=None, collection_type=None, populated=True)
    Bases: object, galaxy.model.item_attrs.Dictifiable, galaxy.model.item_attrs.UsesAnnotations

```

```
copy (destination=None, element_destination=None)
dataset_elements
dataset_instances
dict_collection_visible_keys = ('id', 'collection_type')
dict_element_visible_keys = ('id', 'collection_type')
handle_population_failed (message)
mark_as_populated ()
populated
populated_states = <galaxy.util.bunch.Bunch object>
set_from_dict (new_data)
state
validate ()
waiting_for_elements
```

class galaxy.model.**DatasetCollectionElement** (*id=None, collection=None, element=None, element_index=None, element_identifier=None*)

Bases: object, [galaxy.model.item_attrs.Dictifiable](#)

Associates a DatasetInstance (hda or ldda) with a DatasetCollection.

```
copy_to_collection (collection, destination=None, element_destination=None)
dataset
dataset_instance
dict_collection_visible_keys = ('id', 'element_type', 'element_index', 'element_identifier')
dict_element_visible_keys = ('id', 'element_type', 'element_index', 'element_identifier')
element_object
element_type
first_dataset_instance ()
is_collection
```

class galaxy.model.**DatasetCollectionInstance** (*collection=None, deleted=False*)

Bases: object, [galaxy.model.HasName](#)

```
display_name ()
set_from_dict (new_data)
    Set object attributes to the values in dictionary new_data limiting to only those keys in
    dict_element_visible_keys.

    Returns a dictionary of the keys, values that have been changed.
state
```

```

class galaxy.model.DatasetInstance (id=None, hid=None, name=None, info=None, blurb=None,
                                     peek=None, tool_version=None, extension=None,
                                     dbkey=None, metadata=None, history=None, dataset=None,
                                     deleted=False, designation=None, parent_id=None, vali-
                                     dation_errors=None, visible=True, create_dataset=False,
                                     sa_session=None, extended_metadata=None)

Bases: object

A base class for all 'dataset instances', HDAs, LDAs, etc

add_validation_error (validation_error)

as_display_type (type, **kwd)

can_convert_to (format)

change_datatype (new_ext)

clear_associated_files (metadata_safe=False, purge=False)

conversion_messages = <galaxy.util.bunch.Bunch object>

convert_dataset (trans, target_type)
    Converts a dataset to the target_type and returns a message indicating status of the conversion. None is
    returned to indicate that dataset was converted successfully.

creating_job

datatype

dbkey

display_info ()

display_name ()

display_peek ()

ext

extend_validation_errors (validation_errors)

extra_files_path

file_name

find_conversion_destination (accepted_formats, **kwd)
    Returns ( target_ext, existing converted dataset )

get_child_by_designation (designation)

get_converted_dataset (trans, target_ext)
    Return converted dataset(s) if they exist, along with a dict of dependencies. If not converted yet, do so
    and return None (the first time). If unconvertible, raise exception.

get_converted_dataset_deps (trans, target_ext)
    Returns dict of { "dependency" => HDA }

get_converted_files_by_type (file_type)

get_converter_types ()

get_dataset_state ()

get_datasources (trans)
    Returns datasources for dataset; if datasources are not available due to indexing, indexing is started.

```

Return value is a dictionary with entries of type (<datasource_type> : {<datasource_name>, <indexing_message>}).

get_dbkey ()

get_display_applications (*trans*)

get_file_name ()

get_metadata ()

get_metadata_dataset (*dataset_ext*)

Returns an HDA that points to a metadata file which contains a converted data with the requested extension.

get_mime ()

Returns the mime type of the data

get_raw_data ()

Returns the full data. To stream it open the file_name and read/write as needed

get_size (*nice_size=False*)

Returns the size of the data on disk

get_total_size ()

get_visualizations ()

has_data ()

Detects whether there is any data

init_meta (*copy_from=None*)

is_multi_byte ()

Data consists of multi-byte characters

is_pending

Return true if the dataset is neither ready nor in error

mark_deleted (*include_children=True*)

mark_undeleted (*include_children=True*)

mark_unhidden (*include_children=True*)

metadata

missing_meta (***kwd*)

permitted_actions = <galaxy.util.bunch.Bunch object>

set_dataset_state (*state*)

set_dbkey (*value*)

set_file_name (*filename*)

set_meta (***kwd*)

set_metadata (*bunch*)

set_peek (*is_multi_byte=False*)

set_raw_data (*data*)

Saves the data on the disc

set_size ()

Returns the size of the data on disk


```

    set_total_size()
    source_dataset_chain
    source_library_dataset
    state
    states = <galaxy.util.bunch.Bunch object>
    undeletable()
    write_from_stream(stream)
        Writes data from a stream
class galaxy.model.DatasetPermissions(action, dataset, role)
    Bases: object
class galaxy.model.DatasetTagAssociation(id=None, user=None, item_id=None, tag_id=None,
                                         user_tname=None, value=None)
    Bases: galaxy.model.ItemTagAssociation
class galaxy.model.DatasetToValidationErrorAssociation(dataset, validation_error)
    Bases: object
class galaxy.model.DefaultHistoryPermissions(history, action, role)
    Bases: object
class galaxy.model.DefaultQuotaAssociation(type, quota)
    Bases: galaxy.model.Quota, galaxy.model.item_attrs.Dictifiable
    dict_element_visible_keys = ('type',)
    types = <galaxy.util.bunch.Bunch object>
class galaxy.model.DefaultUserPermissions(user, action, role)
    Bases: object
class galaxy.model.DeferredJob(state=None, plugin=None, params=None)
    Bases: object
    check_interval
    get_check_interval()
    get_last_check()
    is_check_time
    last_check
    set_check_interval(seconds)
    set_last_check(seconds)
    states = <galaxy.util.bunch.Bunch object>
class galaxy.model.Event(message=None, history=None, user=None, galaxy_session=None)
    Bases: object
class galaxy.model.ExtendedMetadata(data)
    Bases: object
class galaxy.model.ExtendedMetadataIndex(extended_metadata, path, value)
    Bases: object

```

```
class galaxy.model.ExternalService (name=None, description=None, external_service_type_id=None, version=None, form_definition_id=None, form_values_id=None, deleted=None)

Bases: object

data_transfer_protocol = <galaxy.util.bunch.Bunch object>

get_external_service_type (trans)

load_data_transfer_settings (trans)

populate_actions (trans, item, param_dict=None)

class galaxy.model.FormDefinition (name=None, desc=None, fields=[], form_definition_current=None, form_type=None, layout=None)

Bases: object, galaxy.model.item_attrs.Dictifiable

dict_collection_visible_keys = ('id', 'name')

dict_element_visible_keys = ('id', 'name', 'desc', 'form_definition_current_id', 'fields', 'layout')

field_as_html (field)
    Generates disabled html for a field

get_widgets (user, contents={}, **kwd)
    Return the list of widgets that comprise a form definition, including field contents if any.

grid_fields (grid_index)

supported_field_types = [<class 'galaxy.web.form_builder.AddressField'>, <class 'galaxy.web.form_builder.CheckboxField'>]

types = <galaxy.util.bunch.Bunch object>

class galaxy.model.FormDefinitionCurrent (form_definition=None)

Bases: object

class galaxy.model.FormValues (form_def=None, content=None)

Bases: object

class galaxy.model.GalaxySession (id=None, user=None, remote_host=None, remote_addr=None, referer=None, current_history=None, session_key=None, is_valid=False, prev_session_id=None, last_action=None)

Bases: object

add_history (history, association=None)

get_disk_usage ()

set_disk_usage (bytes)

total_disk_usage

class galaxy.model.GalaxySessionToHistoryAssociation (galaxy_session, history)

Bases: object

class galaxy.model.GenomeIndexToolData (job=None, params=None, dataset=None, deferred_job=None, transfer_job=None, fasta_path=None, created_time=None, modified_time=None, dbkey=None, user=None, index=None)

Bases: object

class galaxy.model.Group (name=None)

Bases: object, galaxy.model.item_attrs.Dictifiable
```

```

    dict_collection_visible_keys = ('id', 'name')
    dict_element_visible_keys = ('id', 'name')
class galaxy.model.GroupQuotaAssociation(group, quota)
    Bases: object, galaxy.model.item_attrs.Dictifiable
    dict_element_visible_keys = ('group',)
class galaxy.model.GroupRoleAssociation(group, role)
    Bases: object
class galaxy.model.HasJobMetrics

    add_metric(plugin, metric_name, metric_value)

    metrics

class galaxy.model.HasName

    get_display_name()
        These objects have a name attribute can be either a string or a unicode object. If string, convert to unicode
        object assuming 'utf-8' format.
class galaxy.model.History(id=None, name=None, user=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable, galaxy.model.item_attrs.UsesAnnotations,
    galaxy.model.HasName
    activatable_datasets
    active_contents
        Return all active contents ordered by hid.
    active_datasets_children_and_roles
    add_dataset(dataset, parent_id=None, genome_build=None, set_hid=True, quota=True)
    add_dataset_collection(history_dataset_collection, set_hid=True)
    add_galaxy_session(galaxy_session, association=None)
    contents_iter(**kws)
        Fetch filtered list of contents of history.
    copy(name=None, target_user=None, activatable=False, all_datasets=False)
        Return a copy of this history using the given name and target_user. If activatable, copy only non-deleted
        datasets. If all_datasets, copy non-deleted, deleted, and purged datasets.
    copy_tags_from(target_user, source_history)
    default_name = 'Unnamed history'
    dict_collection_visible_keys = ('id', 'name', 'published', 'deleted')
    dict_element_visible_keys = ('id', 'name', 'genome_build', 'deleted', 'purged', 'update_time', 'published', 'impor
    empty
    get_disk_size(nice_size=False)
    get_disk_size_bytes
    latest_export
    resume_paused_jobs()

```

```
to_dict (view='collection', value_mapper=None)

unhide_datasets ()

class galaxy.model.HistoryAnnotationAssociation
    Bases: object

class galaxy.model.HistoryDatasetAssociation (hid=None, history=None,
                                             copied_from_history_dataset_association=None,
                                             copied_from_library_dataset_association=None,
                                             sa_session=None, **kwd)
    Bases: galaxy.model.DatasetInstance, galaxy.model.item_attrs.Dictifiable,
          galaxy.model.item_attrs.UsesAnnotations, galaxy.model.HasName

    Resource class that creates a relation between a dataset and a user history.

clear_associated_files (metadata_safe=False, purge=False)

copy (copy_children=False, parent_id=None)
    Create a copy of this HDA.

get_access_roles (trans)
    Return The access roles associated with this HDA's dataset.

history_content_type

quota_amount (user)
    Return the disk space used for this HDA relevant to user quotas.

    If the user has multiple instances of this dataset, it will not affect their disk usage statistic.

to_dict (view='collection', expose_dataset_path=False)
    Return attributes of this HDA that are exposed using the API.

to_library_dataset_dataset_association (trans, target_folder, replace_dataset=None,
                                          parent_id=None, user=None, roles=None,
                                          llda_message='')
    Copy this HDA to a library optionally replacing an existing LDDA.

class galaxy.model.HistoryDatasetAssociationAnnotationAssociation
    Bases: object

class galaxy.model.HistoryDatasetAssociationDisplayAtAuthorization (hda=None,
                                                                      user=None,
                                                                      site=None)
    Bases: object

class galaxy.model.HistoryDatasetAssociationRatingAssociation (id=None,
                                                                user=None,
                                                                item=None, rating=0)
    Bases: galaxy.model.ItemRatingAssociation

set_item (history_dataset_association)

class galaxy.model.HistoryDatasetAssociationSubset (hda, subset, location)
    Bases: object

class galaxy.model.HistoryDatasetAssociationTagAssociation (id=None, user=None,
                                                            item_id=None,
                                                            tag_id=None,
                                                            user_tname=None,
                                                            value=None)
    Bases: galaxy.model.ItemTagAssociation
```

```

class galaxy.model.HistoryDatasetCollectionAnnotationAssociation
    Bases: object

class galaxy.model.HistoryDatasetCollectionAssociation (id=None,          hid=None,
                                                         collection=None,      his-
                                                         tory=None,          name=None,
                                                         deleted=False,     visible=True,
                                                         copied_from_history_dataset_collection_association=None,
                                                         implicit_output_name=None,
                                                         implicit_input_collections=[])

    Bases: galaxy.model.DatasetCollectionInstance, galaxy.model.item_attrs.Dictifiable

    Associates a DatasetCollection with a History.

    add_implicit_input_collection (name, history_dataset_collection)

    copy (element_destination=None)
        Create a copy of this history dataset collection association. Copy underlying collection.

    editable_keys = ('name', 'deleted', 'visible')

    find_implicit_input_collection (name)

    history_content_type

    to_dict (view='collection')

class galaxy.model.HistoryDatasetCollectionRatingAssociation (id=None, user=None,
                                                              item=None, rating=0)

    Bases: galaxy.model.ItemRatingAssociation

    set_item (dataset_collection)

class galaxy.model.HistoryDatasetCollectionTagAssociation (id=None,      user=None,
                                                           item_id=None,
                                                           tag_id=None,
                                                           user_tname=None,
                                                           value=None)

    Bases: galaxy.model.ItemTagAssociation

class galaxy.model.HistoryRatingAssociation (id=None, user=None, item=None, rating=0)
    Bases: galaxy.model.ItemRatingAssociation

    set_item (history)

class galaxy.model.HistoryTagAssociation (id=None, user=None, item_id=None, tag_id=None,
                                          user_tname=None, value=None)
    Bases: galaxy.model.ItemTagAssociation

class galaxy.model.HistoryUserShareAssociation
    Bases: object

class galaxy.model.ImplicitlyConvertedDatasetAssociation (id=None,          par-
                                                         ent=None,    dataset=None,
                                                         file_type=None,
                                                         deleted=False,
                                                         purged=False,          meta-
                                                         data_safe=True)

    Bases: object

    clear (purge=False, delete_dataset=True)

```

```
class galaxy.model.ImplicitlyCreatedDatasetCollectionInput (name, input_dataset_collection)
    Bases: object

class galaxy.model.ItemRatingAssociation (id=None, user=None, item=None, rating=0)
    Bases: object
    set_item (item)
        Set association's item.

class galaxy.model.ItemTagAssociation (id=None, user=None, item_id=None, tag_id=None,
                                       user_tname=None, value=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable
    copy ()
    dict_collection_visible_keys = ('id', 'user_tname', 'user_value')
    dict_element_visible_keys = ('id', 'user_tname', 'user_value')

class galaxy.model.Job
    Bases: object, galaxy.model.HasJobMetrics, galaxy.model.item_attrs.Dictifiable
    add_implicit_output_dataset_collection (name, dataset_collection)
    add_input_dataset (name, dataset)
    add_input_dataset_collection (name, dataset)
    add_input_library_dataset (name, dataset)
    add_output_dataset (name, dataset)
    add_output_dataset_collection (name, dataset_collection_instance)
    add_output_library_dataset (name, dataset)
    add_parameter (name, value)
    add_post_job_action (pja)
    check_if_output_datasets_deleted ()
        Return true if all of the output datasets associated with this job are in the deleted state
    dict_collection_visible_keys = ['id', 'state', 'exit_code', 'update_time', 'create_time']
    dict_element_visible_keys = ['id', 'state', 'exit_code', 'update_time', 'create_time']
        A job represents a request to run a tool given input datasets, tool parameters, and output datasets.
    finished
    get_command_line ()
    get_external_output_metadata ()
        The external_output_metadata is currently a reference from Job to JobExternalOutputMetadata. It exists
        for a job but not a task.
    get_handler ()
    get_id ()
    get_id_tag ()
        Return a tag that can be useful in identifying a Job. This returns the Job's get_id
    get_imported ()
    get_info ()
```

```

get_input_datasets ()
get_input_library_datasets ()
get_job ()
get_job_runner_external_id ()
get_job_runner_name ()
get_output_datasets ()
get_output_library_datasets ()
get_param_filename ()
get_param_values (app, ignore_errors=False)
    Read encoded parameter values from the database and turn back into a dict of tool parameter values.
get_parameters ()
get_params ()
get_post_job_actions ()
get_session_id ()
get_state ()
get_tasks ()
get_tool_id ()
get_tool_version ()
get_user ()
get_user_id ()
mark_deleted (track_jobs_in_database=False)
    Mark this job as deleted, and mark any output datasets as discarded.
raw_param_dict ()
set_command_line (command_line)
set_final_state (final_state)
set_handler (handler)
set_imported (imported)
set_info (info)
set_input_datasets (input_datasets)
set_input_library_datasets (input_library_datasets)
set_output_datasets (output_datasets)
set_output_library_datasets (output_library_datasets)
set_param_filename (param_filename)
set_parameters (parameters)
set_params (params)
set_post_job_actions (post_job_actions)
set_runner_external_id (job_runner_external_id)

```

```
    set_runner_name (job_runner_name)
    set_session_id (session_id)
    set_state (state)
        Save state history
    set_tool_id (tool_id)
    set_tool_version (tool_version)
    set_user_id (user_id)
    states = <galaxy.util.bunch.Bunch object>
    to_dict (view='collection', system_details=False)

class galaxy.model.JobExportHistoryArchive (job=None, history=None, dataset=None, compressed=False, history_attrs_filename=None, datasets_attrs_filename=None, jobs_attrs_filename=None)

    Bases: object

    export_name
    preparing
    ready
    up_to_date
        Return False, if a new export should be generated for corresponding history.

class galaxy.model.JobExternalOutputMetadata (job=None, dataset=None)
    Bases: object

    dataset

class galaxy.model.JobImportHistoryArchive (job=None, history=None, archive_dir=None)
    Bases: object

class galaxy.model.JobMetricNumeric (plugin, metric_name, metric_value)
    Bases: galaxy.model.BaseJobMetric

class galaxy.model.JobMetricText (plugin, metric_name, metric_value)
    Bases: galaxy.model.BaseJobMetric

class galaxy.model.JobParameter (name, value)
    Bases: object

class galaxy.model.JobStateHistory (job)
    Bases: object

class galaxy.model.JobToImplicitOutputDatasetCollectionAssociation (name, dataset_collection)
    Bases: object

class galaxy.model.JobToInputDatasetAssociation (name, dataset)
    Bases: object

class galaxy.model.JobToInputDatasetCollectionAssociation (name, dataset)
    Bases: object

class galaxy.model.JobToInputLibraryDatasetAssociation (name, dataset)
    Bases: object
```

```

class galaxy.model.JobToOutputDatasetAssociation(name, dataset)
    Bases: object

class galaxy.model.JobToOutputDatasetCollectionAssociation(name,
                                                         dataset_collection_instance)
    Bases: object

class galaxy.model.JobToOutputLibraryDatasetAssociation(name, dataset)
    Bases: object

class galaxy.model.Library(name=None, description=None, synopsis=None, root_folder=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable, galaxy.model.HasName
    dict_collection_visible_keys = ('id', 'name')
    dict_element_visible_keys = ('id', 'deleted', 'name', 'description', 'synopsis', 'root_folder_id')
    get_access_roles(trans)
    get_active_folders(folder, folders=None)
    get_info_association(restrict=False, inherited=False)
    get_template_widgets(trans, get_contents=True)
    permitted_actions = <galaxy.util.bunch.Bunch object>
    to_dict(view='collection', value_mapper=None)
        We prepend an F to folders.

class galaxy.model.LibraryDataset(folder=None, order_id=None, name=None, info=None, li-
                                brary_dataset_dataset_association=None, **kwd)
    Bases: object
    display_name()
    get_info()
    get_name()
    info
    name
    set_info(info)
    set_library_dataset_dataset_association(ldda)
    set_name(name)
    to_dict(view='collection')
    upload_options = [('upload_file', 'Upload files'), ('upload_directory', 'Upload directory of files'), ('upload_paths', 'U

class galaxy.model.LibraryDatasetCollectionAnnotationAssociation
    Bases: object

class galaxy.model.LibraryDatasetCollectionAssociation(id=None, collection=None,
                                                         name=None, deleted=False,
                                                         folder=None)
    Bases: galaxy.model.DatasetCollectionInstance, galaxy.model.item_attrs.Dictifiable
    Associates a DatasetCollection with a library folder.
    editable_keys = ('name', 'deleted')
    to_dict(view='collection')

```

```
class galaxy.model.LibraryDatasetCollectionRatingAssociation (id=None, user=None,
                                                             item=None, rating=0)
    Bases: galaxy.model.ItemRatingAssociation
    set_item (dataset_collection)

class galaxy.model.LibraryDatasetCollectionTagAssociation (id=None, user=None,
                                                          item_id=None,
                                                          tag_id=None,
                                                          user_tname=None,
                                                          value=None)
    Bases: galaxy.model.ItemTagAssociation

class galaxy.model.LibraryDatasetDatasetAssociation (copied_from_history_dataset_association=None,
                                                     copied_from_library_dataset_dataset_association=None,
                                                     library_dataset=None, user=None,
                                                     sa_session=None, **kwd)
    Bases: galaxy.model.DatasetInstance, galaxy.model.HasName
    clear_associated_files (metadata_safe=False, purge=False)
    copy (copy_children=False, parent_id=None, target_folder=None)
    get_access_roles (trans)
    get_info_association (restrict=False, inherited=False)
    get_manage_permissions_roles (trans)
    get_template_widgets (trans, get_contents=True)
    has_manage_permissions_roles (trans)
    templates_dict (use_name=False)
        Returns a dict of template info
    templates_json (use_name=False)
    to_dict (view='collection')
    to_history_dataset_association (target_history, parent_id=None, add_to_history=False)

class galaxy.model.LibraryDatasetDatasetAssociationPermissions (action, library_item, role)
    Bases: object

class galaxy.model.LibraryDatasetDatasetInfoAssociation (library_dataset_dataset_association,
                                                         form_definition, info)
    Bases: object
    inheritable

class galaxy.model.LibraryDatasetPermissions (action, library_item, role)
    Bases: object

class galaxy.model.LibraryFolder (name=None, description=None, item_count=0, order_id=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable, galaxy.model.HasName
    activatable_library_datasets
    add_folder (folder)
    add_library_dataset (library_dataset, genome_build=None)
    dict_element_visible_keys = ('id', 'parent_id', 'name', 'description', 'item_count', 'genome_build', 'update_time')
```

```

    get_info_association (restrict=False, inherited=False)
    get_template_widgets (trans, get_contents=True)
    library_path
    parent_library
    to_dict (view='collection', value_mapper=None)
class galaxy.model.LibraryFolderInfoAssociation (folder, form_definition, info, inheritable=False)
    Bases: object
class galaxy.model.LibraryFolderPermissions (action, library_item, role)
    Bases: object
class galaxy.model.LibraryInfoAssociation (library, form_definition, info, inheritable=False)
    Bases: object
class galaxy.model.LibraryPermissions (action, library_item, role)
    Bases: object
class galaxy.model.MetadataFile (dataset=None, name=None)
    Bases: object
    file_name
exception galaxy.model.NoConverterException (value)
    Bases: exceptions.Exception
class galaxy.model.Page
    Bases: object, galaxy.model.item_attrs.Dictifiable
    dict_element_visible_keys = ['id', 'title', 'latest_revision_id', 'slug', 'published', 'importable', 'deleted']
    to_dict (view='element')
class galaxy.model.PageAnnotationAssociation
    Bases: object
class galaxy.model.PageRatingAssociation (id=None, user=None, item=None, rating=0)
    Bases: galaxy.model.ItemRatingAssociation
    set_item (page)
class galaxy.model.PageRevision
    Bases: object, galaxy.model.item_attrs.Dictifiable
    dict_element_visible_keys = ['id', 'page_id', 'title', 'content']
    to_dict (view='element')
class galaxy.model.PageTagAssociation (id=None, user=None, item_id=None, tag_id=None,
                                         user_tname=None, value=None)
    Bases: galaxy.model.ItemTagAssociation
class galaxy.model.PageUserShareAssociation
    Bases: object
class galaxy.model.PasswordResetToken (user, token=None)
    Bases: object
class galaxy.model.PostJobAction (action_type, workflow_step, output_name=None, action_arguments=None)
    Bases: object

```

```
class galaxy.model.PostJobActionAssociation (pja, job)
    Bases: object

class galaxy.model.Quota (name='', description='', amount=0, operation='')
    Bases: object, galaxy.model.item_attrs.Dictifiable

    amount
    dict_collection_visible_keys = ('id', 'name')
    dict_element_visible_keys = ('id', 'name', 'description', 'bytes', 'operation', 'display_amount', 'default', 'users')
    display_amount
    get_amount ()
    set_amount (amount)
    valid_operations = ('+', '-', '=')

class galaxy.model.Request (name=None, desc=None, request_type=None, user=None,
                             form_values=None, notification=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable

    dict_collection_visible_keys = ('id', 'name', 'state')
    get_sample (sample_name)
    is_complete
    is_new
    is_rejected
    is_submitted
    is_unsubmitted
    last_comment
    latest_event
    samples_have_common_state
        Returns the state of this request's samples when they are all in one common state. Otherwise returns False.
    samples_with_bar_code
    samples_without_library_destinations
    send_email_notification (trans, common_state, final_state=False)
    state
    states = <galaxy.util.bunch.Bunch object>

class galaxy.model.RequestEvent (request=None, request_state=None, comment='')
    Bases: object

class galaxy.model.RequestType (name=None, desc=None, request_form=None, sam-
                                ple_form=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable

    add_external_service_association (trans, external_service)
    delete_external_service_associations (trans)
        Deletes all external service associations.
    dict_collection_visible_keys = ('id', 'name', 'desc')
```

```

dict_element_visible_keys = ('id', 'name', 'desc', 'request_form_id', 'sample_form_id')
external_services
final_sample_state
get_external_service(external_service_type_id)
get_external_services_for_manual_data_transfer(trans)
    Returns all external services that use manual data transfer
get_template_widgets(trans, get_contents=True)
permitted_actions = <galaxy.util.bunch.Bunch object>
rename_dataset_options = <galaxy.util.bunch.Bunch object>
run_details
class galaxy.model.RequestTypeExternalServiceAssociation(request_type, external_service)
    Bases: object
class galaxy.model.RequestTypePermissions(action, request_type, role)
    Bases: object
class galaxy.model.RequestTypeRunAssociation(request_type, run)
    Bases: object
class galaxy.model.Role(name='', description='', type='system', deleted=False)
    Bases: object, galaxy.model.item_attrs.Dictifiable
    dict_collection_visible_keys = ('id', 'name')
    dict_element_visible_keys = ('id', 'name', 'description', 'type')
    private_id = None
    types = <galaxy.util.bunch.Bunch object>
class galaxy.model.Run(form_definition, form_values, subindex=None)
    Bases: object
class galaxy.model.Sample(name=None, desc=None, request=None, form_values=None,
                        bar_code=None, library=None, folder=None, workflow=None, history=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable
    adding_to_library_dataset_files
    bulk_operations = <galaxy.util.bunch.Bunch object>
    dict_collection_visible_keys = ('id', 'name')
    get_template_widgets(trans, get_contents=True)
    get_untransferred_dataset_size(filepath, scp_configs)
    inprogress_dataset_files
    latest_event
    populate_external_services(param_dict=None, trans=None)
    queued_dataset_files
    run_details
    state

```

```
supported_field_types = [<class 'galaxy.web.form_builder.CheckboxField'>, <class 'galaxy.web.form_builder.SelectField'>]
transfer_error_dataset_files
transferred_dataset_files
transferring_dataset_files
untransferred_dataset_files

class galaxy.model.SampleDataset (sample=None, name=None, file_path=None, status=None, error_msg=None, size=None, external_service=None)
    Bases: object
    transfer_status = <galaxy.util.bunch.Bunch object>

class galaxy.model.SampleEvent (sample=None, sample_state=None, comment='')
    Bases: object

class galaxy.model.SampleRunAssociation (sample, run)
    Bases: object

class galaxy.model.SampleState (name=None, desc=None, request_type=None)
    Bases: object

class galaxy.model.StoredWorkflow
    Bases: object, galaxy.model.item_attrs.Dictifiable
    copy_tags_from (target_user, source_workflow)
    dict_collection_visible_keys = ('id', 'name', 'published', 'deleted')
    dict_element_visible_keys = ('id', 'name', 'published', 'deleted')
    to_dict (view='collection', value_mapper=None)

class galaxy.model.StoredWorkflowAnnotationAssociation
    Bases: object

class galaxy.model.StoredWorkflowMenuEntry
    Bases: object

class galaxy.model.StoredWorkflowRatingAssociation (id=None, user=None, item=None, rating=0)
    Bases: galaxy.model.ItemRatingAssociation
    set_item (stored_workflow)

class galaxy.model.StoredWorkflowTagAssociation (id=None, user=None, item_id=None, tag_id=None, user_tname=None, value=None)
    Bases: galaxy.model.ItemTagAssociation

class galaxy.model.StoredWorkflowUserShareAssociation
    Bases: object

class galaxy.model.Tag (id=None, type=None, parent_id=None, name=None)
    Bases: object

class galaxy.model.Task (job, working_directory, prepare_files_cmd)
    Bases: object, galaxy.model.HasJobMetrics
    A task represents a single component of a job.
    get_command_line ()
```

get_external_output_metadata()

The `external_output_metadata` is currently a backref to `JobExternalOutputMetadata`. It exists for a job but not a task, and when a task is cancelled its corresponding parent Job will be cancelled. So `None` is returned now, but that could be changed to `self.get_job().get_external_output_metadata()`.

get_id()

get_id_tag()

Return an id tag suitable for identifying the task. This combines the task's job id and the task's own id.

get_info()

get_job()

get_job_runner_external_id()

Runners will use the same methods to get information about the Task class as they will about the Job class, so this method just returns the task's external id.

get_job_runner_name()

Since runners currently access Tasks the same way they access Jobs, this method just refers to *this* instance's runner.

get_param_values(app)

Read encoded parameter values from the database and turn back into a dict of tool parameter values.

get_parameters()

get_prepare_input_files_cmd()

get_session_id()

get_state()

get_stderr()

get_stdout()

get_task_runner_external_id()

get_task_runner_name()

get_working_directory()

set_command_line(command_line)

set_id(id)

set_info(info)

set_job(job)

set_job_runner_external_id(task_runner_external_id)

set_parameters(parameters)

set_prepare_input_files_cmd(prepare_input_files_cmd)

set_state(state)

set_stderr(stderr)

set_stdout(stdout)

set_task_runner_external_id(task_runner_external_id)

set_task_runner_name(task_runner_name)

set_working_directory(working_directory)

```
states = <galaxy.util.bunch.Bunch object>

class galaxy.model.TaskMetricNumeric(plugin, metric_name, metric_value)
    Bases: galaxy.model.BaseJobMetric

class galaxy.model.TaskMetricText(plugin, metric_name, metric_value)
    Bases: galaxy.model.BaseJobMetric

class galaxy.model.ToolTagAssociation(id=None, user=None, tool_id=None, tag_id=None,
    user_tname=None, value=None)
    Bases: galaxy.model.ItemTagAssociation

class galaxy.model.TransferJob(state=None, path=None, info=None, pid=None, socket=None,
    params=None)
    Bases: object

states = <galaxy.util.bunch.Bunch object>

terminal_states = ['error', 'done']

class galaxy.model.UCI
    Bases: object

class galaxy.model.User(email=None, password=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable

all_roles()
    Return a unique list of Roles associated with this user or any of their groups.

calculate_disk_usage()
    Return byte count total of disk space used by all non-purged, non-library HDAs in non-purged histories.

check_password(cleartext)
    Check if cleartext matches user password when hashed.

dict_collection_visible_keys = ('id', 'email', 'username')

dict_element_visible_keys = ('id', 'email', 'username', 'total_disk_usage', 'nice_total_disk_usage')

static expand_user_properties(user, in_string)

get_disk_usage(nice_size=False)
    Return byte count of disk space used by user or a human-readable string if nice_size is True.

nice_total_disk_usage
    Return byte count of disk space used in a human-readable string.

set_disk_usage(bytes)
    Manually set the disk space used by a user to bytes.

set_password_cleartext(cleartext)
    Set user password to the digest of cleartext.

total_disk_usage
    Return byte count of disk space used by user or a human-readable string if nice_size is True.

use_pbkdf2 = True
    Data for a Galaxy user or admin and relations to their histories, credentials, and roles.

static user_template_environment(user)
```

```
>>> env = User.user_template_environment(None)
>>> env['__user_email__']
'Anonymous'
```



```

>>> env['__user_id__']
'Anonymous'
>>> user = User('foo@example.com')
>>> user.id = 6
>>> user.username = 'foo2'
>>> env = User.user_template_environment(user)
>>> env['__user_id__']
'6'
>>> env['__user_name__']
'foo2'

```

```

class galaxy.model.UserAction (id=None, create_time=None, user_id=None, session_id=None, action=None, params=None, context=None)

```

Bases: object

```

class galaxy.model.UserAddress (user=None, desc=None, name=None, institution=None, address=None, city=None, state=None, postal_code=None, country=None, phone=None)

```

Bases: object

get_html ()

```

class galaxy.model.UserGroupAssociation (user, group)

```

Bases: object

```

class galaxy.model.UserOpenID (user=None, session=None, openid=None)

```

Bases: object

```

class galaxy.model.UserPreference (name=None, value=None)

```

Bases: object

```

class galaxy.model.UserQuotaAssociation (user, quota)

```

Bases: object, *galaxy.model.item_attrs.Dictifiable*

dict_element_visible_keys = ('user',)

```

class galaxy.model.UserRoleAssociation (user, role)

```

Bases: object

```

class galaxy.model.ValidationError (message=None, err_type=None, attributes=None)

```

Bases: object

```

class galaxy.model.Visualization (id=None, user=None, type=None, title=None, dbkey=None, slug=None, latest_revision=None)

```

Bases: object

copy (user=None, title=None)

Provide copy of visualization with only its latest revision.

```

class galaxy.model.VisualizationAnnotationAssociation

```

Bases: object

```

class galaxy.model.VisualizationRatingAssociation (id=None, user=None, item=None, rating=0)

```

Bases: *galaxy.model.ItemRatingAssociation*

set_item (visualization)

```

class galaxy.model.VisualizationRevision (visualization=None, title=None, dbkey=None, config=None)

```

Bases: object

copy (visualization=None)

Returns a copy of this object.

```
class galaxy.model.VisualizationTagAssociation (id=None, user=None, item_id=None,
                                              tag_id=None, user_tname=None,
                                              value=None)
    Bases: galaxy.model.ItemTagAssociation

class galaxy.model.VisualizationUserShareAssociation
    Bases: object

class galaxy.model.WorkRequestTagAssociation (id=None, user=None, work-
                                              flow_request_id=None, tag_id=None,
                                              user_tname=None, value=None)
    Bases: galaxy.model.ItemTagAssociation

class galaxy.model.Workflow (uuid=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable

    dict_collection_visible_keys = ('name', 'has_cycles', 'has_errors')
    dict_element_visible_keys = ('name', 'has_cycles', 'has_errors')
    has_outputs_defined ()
        Returns true or false indicating whether or not a workflow has outputs defined.
    to_dict (view='collection', value_mapper=None)

class galaxy.model.WorkflowInvocation
    Bases: object, galaxy.model.item_attrs.Dictifiable

    active
        Indicates the workflow invocation is somehow active - and in particular valid actions may be performed
        on its "WorkflowInvocationStep"s.
    add_input (content, step_id)
    cancel ()
    dict_collection_visible_keys = ('id', 'update_time', 'workflow_id', 'history_id', 'uuid', 'state')
    dict_element_visible_keys = ('id', 'update_time', 'workflow_id', 'history_id', 'uuid', 'state')
    fail ()
    has_input_for_step (step_id)
    static poll_active_workflow_ids (sa_session, scheduler=None, handler=None)
    states = <galaxy.util.bunch.Bunch object>
    step_invocations_by_step_id ()
    step_invocations_for_step_id (step_id)
    step_states_by_step_id ()
    to_dict (view='collection', value_mapper=None, step_details=False)
    update ()

class galaxy.model.WorkflowInvocationStep
    Bases: object, galaxy.model.item_attrs.Dictifiable

    dict_collection_visible_keys = ('id', 'update_time', 'job_id', 'workflow_step_id', 'action')
    dict_element_visible_keys = ('id', 'update_time', 'job_id', 'workflow_step_id', 'action')
    to_dict (view='collection', value_mapper=None)
    update ()
```

```

class galaxy.model.WorkflowOutput (workflow_step, output_name)
    Bases: object

class galaxy.model.WorkflowRequest
    Bases: object, galaxy.model.item_attrs.Dictifiable

    dict_collection_visible_keys = ['id', 'name', 'type', 'state', 'history_id', 'workflow_id']
    dict_element_visible_keys = ['id', 'name', 'type', 'state', 'history_id', 'workflow_id']
    to_dict (view='collection', value_mapper=None)

class galaxy.model.WorkflowRequestInputParameter (name=None, value=None, type=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable

    Workflow-related parameters not tied to steps or inputs.

    dict_collection_visible_keys = ['id', 'name', 'value', 'type']
    types = <galaxy.util.bunch.Bunch object>

class galaxy.model.WorkflowRequestStepState (workflow_step=None, name=None, value=None)
    Bases: object, galaxy.model.item_attrs.Dictifiable

    Workflow step value parameters.

    dict_collection_visible_keys = ['id', 'name', 'value', 'workflow_step_id']

class galaxy.model.WorkflowRequestToInputDatasetAssociation
    Bases: object, galaxy.model.item_attrs.Dictifiable

    Workflow step input dataset parameters.

    dict_collection_visible_keys = ['id', 'workflow_invocation_id', 'workflow_step_id', 'dataset_id', 'name']

class galaxy.model.WorkflowRequestToInputDatasetCollectionAssociation
    Bases: object, galaxy.model.item_attrs.Dictifiable

    Workflow step input dataset collection parameters.

    dict_collection_visible_keys = ['id', 'workflow_invocation_id', 'workflow_step_id', 'dataset_collection_id', 'name']

class galaxy.model.WorkflowStep
    Bases: object

class galaxy.model.WorkflowStepAnnotationAssociation
    Bases: object

class galaxy.model.WorkflowStepConnection
    Bases: object

    NON_DATA_CONNECTION = '__NO_INPUT_OUTPUT_NAME__'
    non_data_connection
    set_non_data_connection()

class galaxy.model.WorkflowStepTagAssociation (id=None, user=None, item_id=None, tag_id=None, user_tname=None, value=None)
    Bases: galaxy.model.ItemTagAssociation

galaxy.model.set_datatypes_registry (d_registry)
    Set up datatypes_registry

```

custom_types Module

item_attrs Module

class galaxy.model.item_attrs.Dictifiable

Mixin that enables objects to be converted to dictionaries. This is useful when for sharing objects across boundaries, such as the API, tool scripts, and JavaScript code.

to_dict (view='collection', value_mapper=None)

Return item dictionary.

exception galaxy.model.item_attrs.RuntimeException

Bases: exceptions.Exception

class galaxy.model.item_attrs.UsesAnnotations

Mixin for getting and setting item annotations.

add_item_annotation (db_session, user, item, annotation)

Add or update an item's annotation; a user can only have a single annotation for an item.

copy_item_annotation (db_session, source_user, source_item, target_user, target_item)

Copy an annotation from a user/item source to a user/item target.

delete_item_annotation (db_session, user, item)

get_item_annotation_obj (db_session, user, item)

Returns a user's annotation object for an item.

get_item_annotation_str (db_session, user, item)

Returns a user's annotation string for an item.

class galaxy.model.item_attrs.UsesItemRatings

Mixin for getting and setting item ratings.

Class makes two assumptions: (1) item-rating association table is named <item_class>RatingAssociation (2) item-rating association table has a column with a foreign key referencing item table that contains the item's id.

get_ave_item_rating_data (db_session, item, webapp_model=None)

Returns the average rating for an item.

get_user_item_rating (db_session, user, item, webapp_model=None)

Returns user's rating for an item. Return type is <item_class>RatingAssociation.

rate_item (db_session, user, item, rating, webapp_model=None)

Rate an item. Return type is <item_class>RatingAssociation.

mapping Module

mapping_tests Module

Subpackages

migrate Package

check Module

```
galaxy.model.migrate.check.create_or_verify_database(url, galaxy_config_file, engine_options={}, app=None)
```

Check that the database is use-able, possibly creating it if empty (this is the only time we automatically create tables, otherwise we force the user to do it using the management script so they can create backups).

1. Empty database -> initialize with latest version and return
2. Database older than migration support -> fail and require manual update
3. Database at state where migrate support introduced -> add version control information but make no changes (might still require manual update)
4. Database versioned but out of date -> fail with informative message, user must run “sh manage_db.sh upgrade”

```
galaxy.model.migrate.check.migrate_to_current_version(engine, schema)
```

orm Package**orm Package**

```
galaxy.model.orm.load_egg_for_url(url)
```

logging_connection_proxy Module

```
class galaxy.model.orm.logging_connection_proxy.LoggingProxy
```

Bases: sqlalchemy.interfaces.ConnectionProxy

Logs SQL statements using standard logging module

```
begin(conn, begin)
```

```
commit(conn, commit)
```

```
cursor_execute(execute, cursor, statement, parameters, context, executemany)
```

```
rollback(conn, rollback)
```

```
class galaxy.model.orm.logging_connection_proxy.TraceLoggerProxy(trace_logger)
```

Bases: sqlalchemy.interfaces.ConnectionProxy

Logs SQL statements using a metlog client

```
cursor_execute(execute, cursor, statement, parameters, context, executemany)
```

```
galaxy.model.orm.logging_connection_proxy.pretty_stack()
```

```
galaxy.model.orm.logging_connection_proxy.stripwd(s)
```

Subpackages**ext Package****ext Package****assignmapper Module**

managers Package

managers Package Classes that manage resources (models, tools, etc.) by using the current Transaction.

Encapsulates the intersection of trans (or trans.sa_session), models, and Controllers.

Responsibilities: model operations that involve the trans/sa_session (CRUD) security:

ownership, accessibility

common aspect-oriented operations via new mixins: sharable, annotatable, tagable, ratable

Not responsible for: encoding/decoding ids any http gobblygook formatting of returned data (always python structures) formatting of raised errors

The goal is to have Controllers only handle: query-string/payload parsing and encoding/decoding ids http return formatting

and: control, improve namespacing in Controllers DRY for Controller ops (define here - use in both UI/API Controllers)

In other words, 'Business logic' independent of web transactions/user context (trans) should be pushed into models - but logic that requires the context trans should be placed under this module.

api_keys Module

```
class galaxy.managers.api_keys.ApiKeyManager (app)
```

Bases: object

```
create_api_key (user)
```

```
get_or_create_api_key (user)
```

base Module Keeps the older BaseController security and fetching methods and also defines a base ModelManager, ModelSerializer, and ModelDeserializer.

ModelManagers are used for operations on models that occur outside the scope of a single model object, such as:

- object creation
- object lookup
- interactions between 2+ objects of different model classes

(Since these were to replace model Mixins from web/framework/base/controller.py the rule of thumb used there also generally has been applied here: if it uses the trans or sa_session, put it in a manager and not the model.)

ModelSerializers allow flexible conversion of model objects to dictionaries. They control what keys are sent, how values are simplified, can remap keys, and allow both predefined and user controlled key sets.

ModelDeserializers control how a model validates and process an incoming attribute change to a model object.

```
class galaxy.managers.base.ModelDeserializer (app)
```

Bases: object

An object that converts an incoming serialized dict into values that can be directly assigned to an item's attributes and assigns them.

```
add_deserializers ()
```

Register a map of attribute keys -> functions that will deserialize data into attributes to be assigned to the item.

```
default_deserializer (item, key, val, **context)
```

If the incoming val is different than the item value change it and, in either case, return the value.

deserialize (*item*, *data*, *flush=True*, ***context*)
 Convert an incoming serialized dict into values that can be directly assigned to an item's attributes and assign them

deserialize_basestring (*item*, *key*, *val*, *convert_none_to_empty=False*, ***context*)

deserialize_bool (*item*, *key*, *val*, ***context*)

deserialize_genome_build (*item*, *key*, *val*, ***context*)
 Make sure *val* is a valid dbkey and assign it.

deserialize_int (*item*, *key*, *val*, *min=None*, *max=None*, ***context*)

model_manager_class = None
 the class used to create this deserializer's generically accessible model_manager

exception galaxy.managers.base.**ModelDeserializingError** (*err_msg=None*, *type='info'*, ***extra_error_info*)
 Bases: *galaxy.exceptions.ObjectAttributeInvalidException*
 Thrown when an incoming value isn't usable by the model (bad type, out of range, etc.)

class galaxy.managers.base.**ModelFilterParser** (*app*)
 Bases: object

Converts string tuples (partially converted query string params) of attr, op, val into either:
 •ORM based filters (filters that can be applied by the ORM at the SQL level) or - functional filters (filters that use derived values or values not within the SQL tables)
 These filters can then be applied to queries.

This abstraction allows 'smarter' application of limit and offset at either the SQL level or the generator/list level based on the presence of functional filters. In other words, if no functional filters are present, limit and offset may be applied at the SQL level. If functional filters are present, limit and offset need to be applied at the list level.

These might be safely be replaced in the future by creating SQLAlchemy hybrid properties or more thoroughly mapping derived values.

UNDERSCORED_OPS = ('lt', 'le', 'eq', 'ne', 'ge', 'gt')
 these are the easier/shorter string equivalents to the python operator fn names that need '__' around them

fn_filter_parsers = None
 dictionary containing parsing data for functional filters - applied after a query is made

model_class = None
 model class

orm_filter_parsers = None
 dictionary containing parsing data for ORM/SQLAlchemy-based filters over potentially expensive queries

parse_bool (*bool_string*)
 Parse a boolean from a string.

parse_filter (*attr*, *op*, *val*)
 Attempt to parse filter as a custom/fn filter, then an orm filter, and if neither work - raise an error.
 Raises **exceptions.RequestParameterInvalidException** if no functional or orm filter can be parsed.

parse_filters (*filter_tuple_list*)
 Parse string 3-tuples (attr, op, val) into orm or functional filters.

parse_id_list (*id_list_string*, *sep*=' , ')
Split *id_list_string* at *sep*.

string_standard_ops (*key*)

class `galaxy.managers.base.ModelManager` (*app*)
Bases: `object`

Base class for all model/resource managers.

Provides common queries and CRUD operations as a (hopefully) light layer over the ORM.

associate (*associate_with*, *item*, *foreign_key_name*=None)
Generically associate *item* with *associate_with* based on *foreign_key_name*.

by_id (*id*, ***kwargs*)
Gets a model by primary id.

by_ids (*ids*, *filters*=None, ***kwargs*)
Returns an in-order list of models with the matching ids in *ids*.

copy (*item*, ***kwargs*)
Clone or copy an item.

create (*flush*=True, **args*, ***kwargs*)
Generically create a new model.

foreign_key_name = None

list (*filters*=None, *order_by*=None, *limit*=None, *offset*=None, ***kwargs*)
Returns all objects matching the given filters

model_class
alias of `object`

one (***kwargs*)
Sends *kwargs* to build the query and returns one and only one model.

query (*eagerloads*=True, *filters*=None, *order_by*=None, *limit*=None, *offset*=None, ***kwargs*)
Return a basic query from *model_class*, *filters*, *order_by*, and *limit* and *offset*.

Set *eagerloads* to False to disable them for this query.

query_associated (*associated_model_class*, *item*, *foreign_key_name*=None)
Generically query other items that have been associated with this *item*.

session ()

update (*item*, *new_values*, *flush*=True, ***kwargs*)
Given a dictionary of new values, update *item* and return it.

..note: NO validation or deserialization occurs here.

class `galaxy.managers.base.ModelSerializer` (*app*)
Bases: `object`

Turns models into JSONable dicts.

Maintains a map of requestable keys and the `Callable()` serializer functions that should be called for those keys.
E.g. { 'x': lambda item, key: item.x, ... }

Note: if a key to serialize is not listed in the `Serializer.serializable_keyset` or `serializers`, it will not be returned.

To serialize call: `my_serializer = MySerializer(app) ... keys_to_serialize = ['id', 'name', 'attr1', 'attr2', ...]`
`item_dict = MySerializer.serialize(my_item, keys_to_serialize)`

add_serializers ()

Register a map of attribute keys -> serializing functions that will serialize the attribute.

add_view (*view_name*, *key_list*, *include_keys_from=None*)

Add the list of serializable attributes *key_list* to the serializer's view dictionary under the key *view_name*.

If *include_keys_from* is a proper view name, extend *key_list* by the list in that view.

default_serializer (*item*, *key*, ***context*)

Serialize the *item*'s attribute named *key*.

serialize (*item*, *keys*, ***context*)

Serialize the model *item* to a dictionary.

Given model *item* and the list *keys*, create and return a dictionary built from each key in *keys* that also exists in *serializers* and values of calling the keyed/named serializers on item.

serialize_date (*item*, *key*, ***context*)

Serialize a date attribute of *item*.

serialize_id (*item*, *key*, ***context*)

Serialize an id attribute of *item*.

serialize_to_view (*item*, *view=None*, *keys=None*, *default_view=None*, ***context*)

Use a predefined list of keys (the string *view*) and any additional keys listed in *keys*.

The combinations can be: *view* only: return those keys listed in the named view *keys* only: return those keys listed no *view* or *keys*: use the *default_view* if any *view* and *keys*: combine both into one list of keys

skip (*msg='skipped'*)

To be called from inside a serializer to skip it.

Handy for config checks, information hiding, etc.

static url_for (**args*, ***kwargs*)

'service' to use for getting urls - use class var to allow overriding when testing

exception `galaxy.managers.base.ModelSerializerError` (*err_msg=None*, *type='info'*, ***extra_error_info*)

Bases: `galaxy.exceptions.InternalServerError`

Thrown when request model values can't be serialized

class `galaxy.managers.base.ModelValidator` (*app*, **args*, ***kwargs*)

Bases: `object`

An object that inspects a dictionary (generally meant to be a set of new/updated values for the model) and raises an error if a value is not acceptable.

basestring (*key*, *val*)

basestring_list (*key*, *val*)

Must be a list of basestrings.

bool (*key*, *val*)

genome_build (*key*, *val*)

Must be a valid base_string.

Note: no checking against installation's ref list is done as many data sources consider this an open field.

int (*key*, *val*)

int_range (*key*, *val*, *min=None*, *max=None*)

Must be a int between min and max.

nullable_basestring (*key, val*)

Must be a basestring or None.

type (*key, val, types*)

Check *val* against the type (or tuple of types) in *types*.

Raises exceptions.`RequestParameterInvalidException` if not an instance.

exception `galaxy.managers.base.SkipAttribute`

Bases: `exceptions.Exception`

Raise this inside a serializer to prevent the returned dictionary from having a the associated key or value for this attribute.

`galaxy.managers.base.get_class` (*class_name*)

Returns the class object that a string denotes. Without this method, we'd have to do `eval(<class_name>)`.

`galaxy.managers.base.get_object` (*trans, id, class_name, check_ownership=False, check_accessible=False, deleted=None*)

Convenience method to get a model object with the specified checks. This is a generic method for dealing with objects uniformly from the older controller mixin code - however whenever possible the managers for a particular model should be used to load objects.

`galaxy.managers.base.security_check` (*trans, item, check_ownership=False, check_accessible=False*)

Security checks for an item: checks if (a) user owns item or (b) item is accessible to user. This is a generic method for dealing with objects uniformly from the older controller mixin code - however whenever possible the managers for a particular model should be used to perform security checks.

citations Module

class `galaxy.managers.citations.BaseCitation`

Bases: `object`

equals (*other_citation*)

has_doi ()

to_dict (*citation_format*)

class `galaxy.managers.citations.BibtexCitation` (*elem, directory, citation_manager*)

Bases: `galaxy.managers.citations.BaseCitation`

to_bibtex ()

class `galaxy.managers.citations.CitationCollection`

Bases: `object`

add (*new_citation*)

class `galaxy.managers.citations.CitationsManager` (*app*)

Bases: `object`

citations_for_tool (*tool*)

citations_for_tool_ids (*tool_ids*)

parse_citation (*citation_elem, tool_directory*)

class `galaxy.managers.citations.DoiCache` (*config*)

Bases: `object`

get_bibtex (*doi*)

class `galaxy.managers.citations.DoiCitation` (*elem, directory, citation_manager*)

Bases: `galaxy.managers.citations.BaseCitation`

BIBTEX_UNSET = <object object>

doi ()

has_doi ()

to_bibtex ()

`galaxy.managers.citations.parse_citation` (*elem, directory, citation_manager*)

Parse an abstract citation entry from the specified XML element. The directory parameter should be used to find external files for this citation.

collections Module

class `galaxy.managers.collections.DatasetCollectionManager` (*app*)

Bases: `object`

Abstraction for interfacing with dataset collections instance - ideally abstracts out model and plugin details.

ELEMENTS_UNINITIALIZED = <object object>

copy (*trans, parent, source, encoded_source_id*)

create (*trans, parent, name, collection_type, element_identifiers=None, elements=None, implicit_collection_info=None*)

create_dataset_collection (*trans, collection_type, elements=None*)

delete (*trans, instance_type, id*)

get_dataset_collection (*trans, encoded_id*)

get_dataset_collection_instance (*trans, instance_type, id, **kwds*)

history_dataset_collections (*history, query*)

match_collections (*collections_to_match*)

May seem odd to place it here, but planning to grow sophistication and get plugin types involved so it will likely make sense in the future.

set_collection_elements (*dataset_collection, dataset_instances*)

update (*trans, instance_type, id, payload*)

collections_util Module

`galaxy.managers.collections_util.api_payload_to_create_params` (*payload*)

Cleanup API payload to pass into `dataset_collections`.

`galaxy.managers.collections_util.dictify_dataset_collection_instance` (*dataset_collection_instance, parent, security, view='element'*)

`galaxy.managers.collections_util.dictify_element` (*element*)

`galaxy.managers.collections_util.validate_input_element_identifiers` (*element_identifiers*)

Scan through the list of element identifiers supplied by the API consumer and verify the structure is valid.

context Module Mixins for transaction-like objects.

class `galaxy.managers.context.ProvidesAppContext`

Bases: `object`

For transaction-like objects to provide Galaxy convenience layer for database and event handling.

Mixed in class must provide *app* property.

expunge_all()

get_toolbox()

Returns the application toolbox

install_model

log_action (*user=None, action=None, context=None, params=None*)

Application-level logging of user actions.

log_event (*message, tool_id=None, **kwargs*)

Application level logging. Still needs fleshing out (log levels and such) Logging events is a config setting - if False, do not log.

model

request_types()

sa_session

Returns a SQLAlchemy session – currently just gets the current session from the threadlocal session context, but this is provided to allow migration toward a more SQLAlchemy 0.4 style of use.

class galaxy.managers.context.**ProvidesHistoryContext**

Bases: object

For transaction-like objects to provide Galaxy convenience layer for reasoning about histories.

Mixed in class must provide *user*, *history*, and *app* properties.

db_builds

Returns the builds defined by galaxy and the builds defined by the user (chromInfo in history).

db_dataset_for (*dbkey*)

Returns the db_file dataset associated/needed by *dataset*, or *None*.

class galaxy.managers.context.**ProvidesUserContext**

Bases: object

For transaction-like objects to provide Galaxy convenience layer for reasoning about users.

Mixed in class must provide *user*, *api_inherit_admin*, and *app* properties.

anonymous

get_current_user_roles()

user_can_do_run_as()

user_ftp_dir

user_is_admin()

folders Module Manager and Serializer for Library Folders.

class galaxy.managers.folders.**FolderManager**

Bases: object

Interface/service object for interacting with folders.

can_add_item (*trans, folder*)

Return true if the user has permissions to add item to the given folder.

check_accessible (*trans, folder*)

Check whether the folder is accessible to current user. By default every folder is accessible (contents have their own permissions).

check_manageable (*trans, folder*)

Check whether the user can manage the folder.

Returns the original folder

Return type *LibraryFolder*

Raises AuthenticationRequired, InsufficientPermissionsException

create (*trans, parent_folder_id, new_folder_name, new_folder_description=''*)

Create a new folder under the given folder.

Parameters

- **parent_folder_id** (*int*) – decoded id
- **new_folder_name** (*str*) – name of the new folder
- **new_folder_description** (*str*) – description of the folder (optional, defaults to empty string)

Returns the new folder

Return type *LibraryFolder*

Raises InsufficientPermissionsException

cut_and_decode (*trans, encoded_folder_id*)

Cuts the folder prefix (the prepended 'F') and returns the decoded id.

Parameters **encoded_folder_id** (*string*) – encoded id of the Folder object

Returns decoded Folder id

Return type *int*

cut_the_prefix (*encoded_folder_id*)

Remove the prefix from the encoded folder id.

Parameters **encoded_folder_id** (*string*) – encoded id of the Folder object with 'F' prepended

Returns encoded Folder id without the 'F' prefix

Return type *string*

Raises MalformedId

decode_folder_id (*trans, encoded_folder_id*)

Decode the folder id given that it has already lost the prefixed 'F'.

Parameters **encoded_folder_id** (*string*) – encoded id of the Folder object

Returns decoded Folder id

Return type *int*

Raises MalformedId

delete (*trans, folder, undelete=False*)

Mark given folder deleted/undeleted based on the flag.

Parameters

- **folder** ([LibraryFolder](#)) – the model object
- **undelete** (*Bool*) – flag whether to delete (when False) or undelete

Returns the folder

Return type [LibraryFolder](#)

Raises ItemAccessibilityException

get (*trans, decoded_folder_id, check_manageable=False, check_accessible=True*)
Get the folder from the DB.

Parameters

- **decoded_folder_id** (*int*) – decoded folder id
- **check_manageable** (*bool*) – flag whether the check that user can manage item
- **check_accessible** (*bool*) – flag whether to check that user can access item

Returns the requested folder

Return type [LibraryFolder](#)

Raises InconsistentDatabase, RequestParameterInvalidException, InternalServerError

get_current_roles (*trans, folder*)
Find all roles currently connected to relevant permissions on the folder.

Parameters **folder** ([LibraryFolder](#)) – the model object

Returns dict of current roles for all available permission types

Return type dictionary

get_folder_dict (*trans, folder*)
Return folder data in the form of a dictionary.

Parameters **folder** ([LibraryFolder](#)) – folder item

Returns dict with data about the folder

Return type dictionary

secure (*trans, folder, check_manageable=True, check_accessible=True*)
Check if (a) user can manage folder or (b) folder is accessible to user.

Parameters

- **folder** ([LibraryFolder](#)) – folder item
- **check_manageable** (*bool*) – flag whether to check that user can manage item
- **check_accessible** (*bool*) – flag whether to check that user can access item

Returns the original folder

Return type [LibraryFolder](#)

hdas Module Manager and Serializer for HDAs.

HistoryDatasetAssociations (HDAs) are datasets contained or created in a history.

class `galaxy.managers.hdas.HDADeserializer` (*app*)

Bases: `galaxy.managers.datasets.DatasetAssociationDeserializer`,
`galaxy.managers.taggable.TaggableDeserializerMixin`, `galaxy.managers.annotatable.Annotatable`

Interface/service object for validating and deserializing dictionaries into histories.

add_deserializers ()

model_manager_class

alias of *HDAManager*

class `galaxy.managers.hdas.HDAFilterParser` (*app*)

Bases: `galaxy.managers.datasets.DatasetAssociationFilterParser`,

`galaxy.managers.taggable.TaggableFilterMixin`, `galaxy.managers.annotatable.AnnotatableFi`

model_class

alias of `HistoryDatasetAssociation`

class `galaxy.managers.hdas.HDAManager` (*app*)

Bases: `galaxy.managers.datasets.DatasetAssociationManager`,

`galaxy.managers.secured.OwnableManagerMixin`, `galaxy.managers.taggable.TaggableManagerMi`

`galaxy.managers.annotatable.AnnotatableManagerMixin`

Interface/service object for interacting with HDAs.

annotation_assoc

alias of `HistoryDatasetAssociationAnnotationAssociation`

copy (*hda*, *history=None*, ***kwargs*)

Copy and return the given HDA.

copy_ldda (*history*, *ldda*, ***kwargs*)

Copy this HDA as a LDDA and return.

create (*history=None*, *dataset=None*, *flush=True*, ***kwargs*)

Create a new hda optionally passing in it's history and dataset.

..note: to explicitly set hid to *None* you must pass in *hid=None*, otherwise it will be automatically set.

data_conversion_status (*hda*)

Returns a message if an hda is not ready to be used in visualization.

error_if_uploading (*hda*)

Raise error if HDA is still uploading.

foreign_key_name = 'history_dataset_association'

has_been_resubmitted (*hda*)

Return True if the hda's job was resubmitted at any point.

is_accessible (*hda*, *user*, ***kwargs*)

Override to allow owners (those that own the associated history).

is_owner (*hda*, *user*, *current_history=None*, ***kwargs*)

Use history to see if current user owns HDA.

model_class

alias of `HistoryDatasetAssociation`

purge (*hda*, *current_user=None*, *flush=True*)

Purge this HDA and the dataset underlying it.

tag_assoc

alias of `HistoryDatasetAssociationTagAssociation`

text_data (*hda*, *preview=True*)

Get data from text file, truncating if necessary.

```
class galaxy.managers.hdas.HDASerializer(app)
    Bases:
        galaxy.managers.datasets.DatasetAssociationSerializer,
        galaxy.managers.taggable.TaggableSerializerMixin, galaxy.managers.annotatable.Annotatable

    add_serializers()

    serialize_display_apps(hda, key, trans=None, **context)
        Return dictionary containing new-style display app urls.

    serialize_old_display_applications(hda, key, trans=None, **context)
        Return dictionary containing old-style display app urls.

    serialize_type_id(hda, key, **context)

    serialize_urls(hda, key, **context)
        Return web controller urls useful for this HDA.

    serialize_visualization_links(hda, key, trans=None, **context)
        Return a list of dictionaries with links to visualization pages for those visualizations that apply to this hda.
```

histories Module Manager and Serializer for histories.

Histories are containers for datasets or dataset collections created (or copied) by users over the course of an analysis.

```
class galaxy.managers.histories.HistoryDeserializer(app)
    Bases:
        galaxy.managers.sharable.SharableModelDeserializer,
        galaxy.managers.deletable.PurgableDeserializerMixin

    Interface/service object for validating and deserializing dictionaries into histories.

    add_deserializers()

    model_manager_class
        alias of HistoryManager

class galaxy.managers.histories.HistoryFilters(app)
    Bases:
        galaxy.managers.sharable.SharableModelFilters,
        galaxy.managers.deletable.PurgableFiltersMixin

    model_class
        alias of History

class galaxy.managers.histories.HistoryManager(app, *args, **kwargs)
    Bases:
        galaxy.managers.sharable.SharableModelManager,
        galaxy.managers.deletable.PurgableManagerMixin

    annotation_assoc
        alias of HistoryAnnotationAssociation

    by_user(user, current_history=None, **kwargs)
        Get all the histories for a given user (allowing anon users' theirs) ordered by update time.

    copy(history, user, **kwargs)
        Copy and return the given history.

    foreign_key_name = 'history'

    get_current(trans)
        Return the current history.

    is_owner(history, user, current_history=None, **kwargs)
        True if the current user is the owner of the given history.
```



```

model_class
    alias of History

most_recent (user, filters=None, current_history=None, **kwargs)
    Return the most recently update history for the user.

    If user is anonymous, return the current history. If the user is anonymous and the current history is deleted,
    return None.

purge (history, flush=True, **kwargs)
    Purge this history and all HDAs, Collections, and Datasets inside this history.

rating_assoc
    alias of HistoryRatingAssociation

set_current (trans, history)
    Set the current history.

set_current_by_id (trans, history_id)
    Set the current history by an id.

tag_assoc
    alias of HistoryTagAssociation

user_share_model
    alias of HistoryUserShareAssociation

class galaxy.managers.histories.HistorySerializer (app)
    Bases: galaxy.managers.sharable.SharableModelSerializer,
    galaxy.managers.deletable.PurgableSerializerMixin

    Interface/service object for serializing histories into dictionaries.

    SINGLE_CHAR_ABBR = 'h'

    add_serializers ()

    serialize_contents (history, *args, **context)

    serialize_history_state (history, key, **context)
        Returns the history state based on the states of the HDAs it contains.

    serialize_state_counts (history, key, exclude_deleted=True, exclude_hidden=False, **con-
                           text)
        Return a dictionary keyed to possible dataset states and valued with the number of datasets in this history
        that have those states.

    serialize_state_ids (history, key, **context)
        Return a dictionary keyed to possible dataset states and valued with lists containing the ids of each HDA
        in that state.

```

lddas Module

```

class galaxy.managers.lddas.LDDAManager (app)
    Bases: object

    A fairly sparse manager for LDDAs.

    get (trans, id, check_accessible=True)

```

libraries Module Manager and Serializer for libraries.

class `galaxy.managers.libraries.LibraryManager` (*args, **kwargs)

Bases: `object`

Interface/service object for interacting with libraries.

check_accessible (*trans*, *library*)

Check whether the library is accessible to current user.

create (*trans*, *name*, *description*='', *synopsis*='')

Create a new library.

delete (*trans*, *library*, *undele*=False)

Mark given library deleted/undeleted based on the flag.

get (*trans*, *decoded_library_id*, *check_accessible*=True)

Get the library from the DB.

Parameters

- **decoded_library_id** (`int`) – decoded library id
- **check_accessible** (`bool`) – flag whether to check that user can access item

Returns the requested library

Return type `Library`

get_access_roles (*trans*, *library*)

Load access roles for all library permissions

get_add_roles (*trans*, *library*)

Load add roles for all library permissions

get_current_roles (*trans*, *library*)

Load all permissions currently related to the given library.

Parameters **library** (`Library`) – the model object

Return type dictionary

Returns dict of current roles for all available permission types

get_library_dict (*trans*, *library*)

Return library data in the form of a dictionary.

Parameters **library** (`Library`) – library

Returns dict with data about the library

Return type dictionary

get_manage_roles (*trans*, *library*)

Load manage roles for all library permissions

get_modify_roles (*trans*, *library*)

Load modify roles for all library permissions

is_public (*trans*, *library*)

Return true if lib is public.

list (*trans*, *deleted*=False)

Return a list of libraries from the DB.

Parameters **deleted** (*boolean (optional)*) – if True, show only deleted libraries, if False show only non-deleted

Returns query that will emit all accessible libraries

Return type sqlalchemy query

make_public (*trans, library*)

Makes the given library public (removes all access roles)

secure (*trans, library, check_accessible=True*)

Check if library is accessible to user.

Parameters

- **folder** ([Library](#)) – library
- **check_accessible** ([bool](#)) – flag whether to check that user can access library

Returns the original folder

Return type [LibraryFolder](#)

set_permission_roles (*trans, library, access_roles, modify_roles, manage_roles, add_roles*)

Set permissions on the given library.

update (*trans, library, name=None, description=None, synopsis=None*)

Update the given library

roles Module Manager and Serializer for Roles.

class `galaxy.managers.roles.RoleManager` (*app*)

Bases: `galaxy.managers.base.ModelManager`

Business logic for roles.

foreign_key_name = 'role'

get (*trans, decoded_role_id*)

Method loads the role from the DB based on the given role id.

Parameters **decoded_role_id** ([int](#)) – id of the role to load from the DB

Returns the loaded Role object

Return type [Role](#)

Raises [InconsistentDatabase](#), [RequestParameterInvalidException](#), [InternalServerError](#)

group_assoc

alias of [GroupRoleAssociation](#)

model_class

alias of [Role](#)

user_assoc

alias of [UserRoleAssociation](#)

tags Module

class `galaxy.managers.tags.CommunityTagManager` (*app*)

Bases: `galaxy.managers.tags.TagManager`

class `galaxy.managers.tags.GalaxyTagManager` (*app*)

Bases: `galaxy.managers.tags.TagManager`

class `galaxy.managers.tags.ItemTagAssocInfo` (*item_class, tag_assoc_class, item_id_col*)

Bases: [object](#)

```
class galaxy.managers.tags.TagManager (app)
    Bases: object

    Manages CRUD operations related to tagging objects.

    apply_item_tag (user, item, name, value=None)

    apply_item_tags (user, item, tags_str)
        Apply tags to an item.

    delete_item_tags (user, item)
        Delete tags from an item.

    get_community_tags (item=None, limit=None)
        Returns community tags for an item.

    get_id_col_in_item_tag_assoc_table (item_class)
        Returns item id column in class' item-tag association table.

    get_tag_assoc_class (item_class)
        Returns tag association class for item class.

    get_tag_by_id (tag_id)
        Get a Tag object from a tag id.

    get_tag_by_name (tag_name)
        Get a Tag object from a tag name (string).

    get_tags_str (tags)
        Build a string from an item's tags.

    get_tool_tags ()

    item_has_tag (user, item, tag)
        Returns true if item is has a given tag.

    parse_tags (tag_str)
        Returns a list of raw (tag-name, value) pairs derived from a string; method scrubs tag names and values
        as well. Return value is a dictionary where tag-names are keys.

    remove_item_tag (user, item, tag_name)
        Remove a tag from an item.

    set_tags_from_list (user, item, new_tags_list)
```

workflows Module

```
class galaxy.managers.workflows.CreatedWorkflow (stored_workflow, missing_tools)
    Bases: tuple

    missing_tools
        Alias for field number 1

    stored_workflow
        Alias for field number 0

class galaxy.managers.workflows.MissingToolsException (workflow, errors)
    Bases: object

class galaxy.managers.workflows.WorkflowContentsManager
    Bases: galaxy.model.item_attrs.UsesAnnotations

    build_workflow_from_dict (trans, data, source=None, add_to_menu=False, publish=False)

    update_workflow_from_dict (trans, stored_workflow, workflow_data, from_editor=False)
```

workflow_to_dict (*trans, stored, style='export'*)

Export the workflow contents to a dictionary ready for JSON-ification and to be sent out via API for instance. There are three styles of export allowed 'export', 'instance', and 'editor'. The Galaxy team will do it best to preserve the backward compatibility of the 'export' style - this is the export method meant to be portable across Galaxy instances and over time. The 'editor' style is subject to rapid and unannounced changes. The 'instance' export option describes the workflow in a context more tied to the current Galaxy instance and includes fields like 'url' and 'url' and actual unencoded step ids instead of 'order_index'.

class `galaxy.managers.workflows.WorkflowsManager` (*app*)

Bases: `object`

Handle CRUD type operations related to workflows. More interesting stuff regarding workflow execution, step sorting, etc... can be found in the `galaxy.workflow` module.

build_invocations_query (*trans, decoded_stored_workflow_id*)

cancel_invocation (*trans, decoded_invocation_id*)

check_security (*trans, has_workflow, check_ownership=True, check_accessible=True*)

check accessibility or ownership of workflows, stored workflows, and workflow invocations. Throw an exception or returns True if user has needed level of access.

get_invocation (*trans, decoded_invocation_id*)

get_invocation_step (*trans, decoded_workflow_invocation_step_id*)

update_invocation_step (*trans, decoded_workflow_invocation_step_id, action*)

objectstore Package

objectstore Package objectstore package, abstraction for storing blobs of data for use in Galaxy, all providers ensure that data can be accessed on the filesystem for running tools

class `galaxy.objectstore.CachingObjectStore` (*path, backend*)

Bases: `galaxy.objectstore.ObjectStore`

Object store that uses a directory for caching files, but defers and writes back to another object store.

class `galaxy.objectstore.DiskObjectStore` (*config, config_xml=None, file_path=None, extra_dirs=None*)

Bases: `galaxy.objectstore.ObjectStore`

Standard Galaxy object store, stores objects in files under a specific directory on disk.

```
>>> from galaxy.util.bunch import Bunch
>>> import tempfile
>>> file_path=tempfile.mkdtemp()
>>> obj = Bunch(id=1)
>>> s = DiskObjectStore(Bunch(umask=077, job_working_directory=file_path, new_file_path=file_path))
>>> s.create(obj)
>>> s.exists(obj)
True
>>> assert s.get_filename(obj) == file_path + '/000/dataset_1.dat'
```

create (*obj, **kwargs*)

delete (*obj, entire_dir=False, **kwargs*)

empty (*obj, **kwargs*)

exists (*obj, **kwargs*)

get_data (*obj*, *start=0*, *count=-1*, ***kwargs*)

get_filename (*obj*, ***kwargs*)

get_object_url (*obj*, ***kwargs*)

get_store_usage_percent ()

size (*obj*, ***kwargs*)

update_from_file (*obj*, *file_name=None*, *create=False*, ***kwargs*)
create parameter is not used in this implementation

class `galaxy.objectstore.DistributedObjectStore` (*config*, *config_xml=None*, *fsmon=False*)
Bases: `galaxy.objectstore.NestedObjectStore`

ObjectStore that defers to a list of backends, for getting objects the first store where the object exists is used, objects are created in a store selected randomly, but with weighting.

create (*obj*, ***kwargs*)
create() is the only method in which *obj.object_store_id* may be *None*

shutdown ()

class `galaxy.objectstore.HierarchicalObjectStore` (*config*, *config_xml=None*, *fsmon=False*)
Bases: `galaxy.objectstore.NestedObjectStore`

ObjectStore that defers to a list of backends, for getting objects the first store where the object exists is used, objects are always created in the first store.

create (*obj*, ***kwargs*)
Create will always be called by the primary *object_store*

exists (*obj*, ***kwargs*)
Exists must check all child object stores

class `galaxy.objectstore.NestedObjectStore` (*config*, *config_xml=None*)
Bases: `galaxy.objectstore.ObjectStore`

Base for ObjectStores that use other ObjectStores (*DistributedObjectStore*, *HierarchicalObjectStore*)

create (*obj*, ***kwargs*)

delete (*obj*, ***kwargs*)

empty (*obj*, ***kwargs*)

exists (*obj*, ***kwargs*)

file_ready (*obj*, ***kwargs*)

get_data (*obj*, ***kwargs*)

get_filename (*obj*, ***kwargs*)

get_object_url (*obj*, ***kwargs*)

shutdown ()

size (*obj*, ***kwargs*)

update_from_file (*obj*, ***kwargs*)

class `galaxy.objectstore.ObjectStore` (*config*, *config_xml=None*, ***kwargs*)
Bases: `object`

ObjectStore abstract interface

create (*obj*, *base_dir=None*, *dir_only=False*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*, *obj_dir=False*)

Mark the object identified by *obj* as existing in the store, but with no content. This method will create a proper directory structure for the file if the directory does not already exist. See *exists* method for the description of other fields.

delete (*obj*, *entire_dir=False*, *base_dir=None*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*, *obj_dir=False*)

Deletes the object identified by *obj*. See *exists* method for the description of other fields.

Parameters *entire_dir* (*bool*) – If True, delete the entire directory pointed to by *extra_dir*. For safety reasons, this option applies only for and in conjunction with the *extra_dir* or *obj_dir* options.

empty (*obj*, *base_dir=None*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*, *obj_dir=False*)

Test if the object identified by *obj* has content. If the object does not exist raises *ObjectNotFound*. See *exists* method for the description of the fields.

exists (*obj*, *base_dir=None*, *dir_only=False*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*)

Returns True if the object identified by *obj* exists in this file store, False otherwise.

FIELD DESCRIPTIONS (these apply to all the methods in this class):

Parameters

- **obj** (*object*) – A Galaxy object with an assigned database ID accessible via the *.id* attribute.
- **base_dir** (*string*) – A key in *self.extra_dirs* corresponding to the base directory in which this object should be created, or None to specify the default directory.
- **dir_only** (*bool*) – If True, check only the path where the file identified by *obj* should be located, not the dataset itself. This option applies to *extra_dir* argument as well.
- **extra_dir** (*string*) – Append *extra_dir* to the directory structure where the dataset identified by *obj* should be located. (e.g., 000/*extra_dir*/*obj.id*)
- **extra_dir_at_root** (*bool*) – Applicable only if *extra_dir* is set. If True, the *extra_dir* argument is placed at root of the created directory structure rather than at the end (e.g., *extra_dir*/000/*obj.id* vs. 000/*extra_dir*/*obj.id*)
- **alt_name** (*string*) – Use this name as the alternative name for the created dataset rather than the default.
- **obj_dir** (*bool*) – Append a subdirectory named with the object's ID (e.g. 000/*obj.id*)

file_ready (*obj*, *base_dir=None*, *dir_only=False*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*, *obj_dir=False*)

A helper method that checks if a file corresponding to a dataset is ready and available to be used. Return True if so, False otherwise.

get_data (*obj*, *start=0*, *count=-1*, *base_dir=None*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*, *obj_dir=False*)

Fetch *count* bytes of data starting at offset *start* from the object identified uniquely by *obj*. If the object does not exist raises *ObjectNotFound*. See *exists* method for the description of other fields.

Parameters

- **start** (*int*) – Set the position to start reading the dataset file

- **count** (*int*) – Read at most *count* bytes from the dataset

get_filename (*obj*, *base_dir=None*, *dir_only=False*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*, *obj_dir=False*)

Get the expected filename (including the absolute path) which can be used to access the contents of the object uniquely identified by *obj*. See *exists* method for the description of the fields.

get_object_url (*obj*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*, *obj_dir=False*)

If the store supports direct URL access, return a URL. Otherwise return None. Note: need to be careful to to bypass dataset security with this. See *exists* method for the description of the fields.

get_store_usage_percent ()

Return the percentage indicating how full the store is

shutdown ()

size (*obj*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*, *obj_dir=False*)

Return size of the object identified by *obj*. If the object does not exist, return 0. See *exists* method for the description of the fields.

update_from_file (*obj*, *base_dir=None*, *extra_dir=None*, *extra_dir_at_root=False*, *alt_name=None*, *obj_dir=False*, *file_name=None*, *create=False*)

Inform the store that the file associated with the object has been updated. If *file_name* is provided, update from that file instead of the default. If the object does not exist raises *ObjectNotFound*. See *exists* method for the description of other fields.

Parameters

- **file_name** (*string*) – Use file pointed to by *file_name* as the source for updating the dataset identified by *obj*
- **create** (*bool*) – If True and the default dataset does not exist, create it first.

`galaxy.objectstore.build_object_store_from_config` (*config*, *fsmon=False*, *con-*
fig_xml=None)

Depending on the configuration setting, invoke the appropriate object store

`galaxy.objectstore.convert_bytes` (*bytes*)

A helper function used for pretty printing disk usage

`galaxy.objectstore.create_object_in_session` (*obj*)

`galaxy.objectstore.local_extra_dirs` (*func*)

A decorator for non-local plugins to utilize local directories for their *extra_dirs* (*job_working_directory* and *temp*).

s3_multipart_upload Module Split large file into multiple pieces for upload to S3. This parallelizes the task over available cores using multiprocessing. Code mostly taken from CloudBioLinux.

`galaxy.objectstore.s3_multipart_upload.map_wrap` (*f*)

`galaxy.objectstore.s3_multipart_upload.mp_from_ids` (*s3server*, *mp_id*, *mp_keyname*,
mp_bucketname)

Get the multipart upload from the bucket and multipart IDs.

This allows us to reconstitute a connection to the upload from within multiprocessing functions.

`galaxy.objectstore.s3_multipart_upload.multimap` (**args*, ***kws*)

Provide multiprocessing imap like function.

The context manager handles setting up the pool, worked around interrupt issues and terminating the pool on completion.


```
galaxy.objectstore.s3_multipart_upload.multipart_upload(s3server,      bucket,
                                                         s3_key_name,    tarball,
                                                         mb_size)
```

Upload large files using Amazon's multipart upload functionality.

```
galaxy.objectstore.s3_multipart_upload.transfer_part(*args, **kwargs)
```

Transfer a part of a multipart upload. Designed to be run in parallel.

openid Package

openid Package OpenID functionality

providers Module Contains OpenID provider functionality

```
class galaxy.openid.providers.OpenIDProvider(id,          name,          op_endpoint_url,
                                              sreg_required=None, sreg_optional=None,
                                              use_for=None,  store_user_preference=None,
                                              never_associate_with_user=None)
```

Bases: object

An OpenID Provider object.

```
classmethod from_elem(xml_root)
```

```
classmethod from_file(filename)
```

```
has_post_authentication_actions()
```

```
post_authentication(trans, openid_manager, info)
```

```
class galaxy.openid.providers.OpenIDProviders(providers=None)
```

Bases: object

Collection of OpenID Providers

```
NO_PROVIDER_ID = 'None'
```

```
classmethod from_elem(xml_root)
```

```
classmethod from_file(filename)
```

```
get(name, default=None)
```

```
new_provider_from_identifier(identifier)
```

quota Package

quota Package Galaxy Quotas

```
class galaxy.quota.NoQuotaAgent(model)
```

Bases: object

Base quota agent, always returns no quota

```
default_quota
```

```
get_percent(trans=None, user=False, history=False, usage=False, quota=False)
```

```
get_quota(user, nice_size=False)
```

```
get_usage(trans=None, user=False, history=False)
```

```
    get_user_quotas (user)
class galaxy.quota.QuotaAgent (model)
    Bases: galaxy.quota.NoQuotaAgent
    Class that handles galaxy quotas
    default_registered_quota
    default_unregistered_quota
    get_percent (trans=None, user=False, history=False, usage=False, quota=False)
        Return the percentage of any storage quota applicable to the user/transaction.
    get_quota (user, nice_size=False)
        Calculated like so:
        1. Anonymous users get the default quota.
        2. Logged in users start with the highest of their associated '=' quotas or the default quota, if there are
           no associated '=' quotas. If an '=' unlimited (-1 in the database) quota is found during this process,
           the user has no quota (aka unlimited).
        3. Quota is increased or decreased by any corresponding '+' or '-' quotas.
    get_user_quotas (user)
    set_default_quota (default_type, quota)
    set_entity_quota_associations (quotas=[], users=[], groups=[],
                                  delete_existing_assocs=True)
```

sample_tracking Package

data_transfer Module

```
class galaxy.sample_tracking.data_transfer.DataTransferFactory
    Bases: object
    parse ()
    type = None
class galaxy.sample_tracking.data_transfer.FtpDataTransferFactory
    Bases: galaxy.sample_tracking.data_transfer.DataTransferFactory
    parse (elem)
    type = 'ftp'
class galaxy.sample_tracking.data_transfer.HttpDataTransferFactory
    Bases: galaxy.sample_tracking.data_transfer.DataTransferFactory
    parse (config_file, elem)
    type = 'http'
class galaxy.sample_tracking.data_transfer.ScpDataTransferFactory
    Bases: galaxy.sample_tracking.data_transfer.DataTransferFactory
    parse (config_file, elem)
    type = 'scp'
galaxy.sample_tracking.data_transfer.data_transfer
    alias of FtpDataTransferFactory
```

external_service_types Module

```
class galaxy.sample_tracking.external_service_types.ExternalServiceType (external_service_type_xml_con-  

root,  

visi-  

ble=True)
```

Bases: object

parse (*root*)

parse_data_transfer_settings (*root*)

parse_run_details (*root*)

parse_run_details_results (*root*)

```
exception galaxy.sample_tracking.external_service_types.ExternalServiceTypeNotFoundException
```

Bases: exceptions.Exception

```
class galaxy.sample_tracking.external_service_types.ExternalServiceTypesCollection (config_filename,  

root_dir,  

app)
```

Bases: object

load_all (*config_filename*)

load_external_service_type (*config_file, visible=True*)

reload (*external_service_type_id*)

Attempt to reload the external_service_type identified by 'external_service_type_id', if successful replace the old external_service_type.

request_types Module RequestType

```
class galaxy.sample_tracking.request_types.RequestTypeFactory (sample_state_factory,  

re-  

name_dataset_options)
```

Bases: object

from_elem (*elem, request_form, sample_form, external_service*)

Return RequestType created from an xml string.

new (*name, request_form, sample_form, external_service, description=None, sample_states=None*)

Return new RequestType.

sample Module Sample

```
class galaxy.sample_tracking.sample.SampleStateFactory
```

Bases: object

from_elem (*request_type, elem*)

Return SampleState created from an xml string.

new (*request_type, name, description=None*)

Return new SampleState.

security Package**security Package** Galaxy Security

```
class galaxy.security.Action (action, description, model)
```

Bases: object

```
class galaxy.security.GalaxyRBACAgent (model, permitted_actions=None)
    Bases: galaxy.security.RBACAgent

    allow_action (roles, action, item)
        Method for checking a permission for the current user ( based on roles ) to perform a specific action on an
        item, which must be one of: Dataset, Library, LibraryFolder, LibraryDataset, LibraryDatasetDatasetAs-
        sociation

    allow_action_on_libitems (trans, user_roles, action, items)
        This should be the equivalent of allow_action defined on multiple items. It is meant to specifically replace
        allow_action for multiple LibraryDatasets, but it could be reproduced or modified for allow_action's per-
        mitted classes - Dataset, Library, LibraryFolder, and LDDAs.

    associate_action_dataset_role (action, dataset, role)

    associate_components ( **kwd )

    associate_group_role (group, role)

    associate_user_group (user, group)

    associate_user_role (user, role)

    can_access_dataset (user_roles, dataset)

    can_access_library (roles, library)

    can_access_library_item (roles, item, user)

    can_access_request_type (roles, request_type)

    can_add_library_item (roles, item)

    can_manage_dataset (roles, dataset)

    can_manage_library_item (roles, item)

    can_modify_library_item (roles, item)

    check_folder_contents (user, roles, folder, hidden_folder_ids='')
        This method must always be sent an instance of LibraryFolder(). Recursive execution produces a comma-
        separated string of folder ids whose folders do NOT meet the criteria for showing. Along with the string,
        True is returned if the current user has permission to access folder. Otherwise, cycle through all sub-
        folders in folder until one is found that meets this criteria, if it exists. This method does not necessarily
        scan the entire library as it returns when it finds the first folder that is accessible to user.

    copy_dataset_permissions (src, dst)

    copy_library_permissions (trans, source_library_item, target_library_item, user=None)

    create_private_user_role (user)

    dataset_access_mapping (trans, user_roles, datasets)
        For the given list of datasets, return a mapping of the datasets' ids to whether they can be accessed by the
        user or not. The datasets input is expected to be a simple list of Dataset objects.

    dataset_is_private_to_user (trans, dataset)
        If the LibraryDataset object has exactly one access role and that is the current user's private role then we
        consider the dataset private.

    dataset_is_public (dataset)
        A dataset is considered public if there are no "access" actions associated with it. Any other actions (
        'manage permissions', 'edit metadata' ) are irrelevant. Accessing dataset.actions will cause a query to be
        emitted.
```

dataset_is_unrestricted (*trans, dataset*)

Different implementation of the method above with signature: `def dataset_is_public(self, dataset)`

dataset_permission_map_for_access (*trans, user_roles, libitems*)

For a given list of library items (e.g., Datasets), return a map of the datasets' ids to whether they can have permission to use that action (e.g., "access" or "modify") on the dataset. The libitems input is expected to be a simple list of library items, such as Datasets or LibraryDatasets. NB: This is currently only usable for Datasets; it was intended to be used for any library item.

datasets_are_public (*trans, datasets*)

Given a transaction object and a list of Datasets, return a mapping from Dataset ids to whether the Dataset is public or not. All Dataset ids should be returned in the mapping's keys.

derive_roles_from_access (*trans, item_id, cntrller, library=False, **kwd*)

folder_is_public (*folder*)

folder_is_unrestricted (*folder*)

get_accessible_libraries (*trans, user*)

Return all data libraries that the received user can access

get_accessible_request_types (*trans, user*)

Return all RequestTypes that the received user has permission to access.

get_actions_for_items (*trans, action, permission_items*)

get_all_roles (*trans, cntrller*)

get_component_associations (***kwd*)

get_item_actions (*action, item*)

get_legitimate_roles (*trans, item, cntrller*)

Return a sorted list of legitimate roles that can be associated with a permission on item where item is a Library or a Dataset. The cntrller param is the controller from which the request is sent. We cannot use `trans.user_is_admin()` because the controller is what is important since admin users do not necessarily have permission to do things on items outside of the admin view.

If cntrller is from the admin side (e.g., `library_admin`):

- if item is public, all roles, including private roles, are legitimate.
- if item is restricted, legitimate roles are derived from the users and groups associated with each role that is associated with the access permission (i.e., `DATASET_MANAGE_PERMISSIONS` or `LIBRARY_MANAGE`) on item. Legitimate roles will include private roles.

If cntrller is not from the admin side (e.g., `root`, `library`):

- if item is public, all non-private roles, except for the current user's private role, are legitimate.
- if item is restricted, legitimate roles are derived from the users and groups associated with each role that is associated with the access permission on item. Private roles, except for the current user's private role, will be excluded.

get_permissions (*item*)

Return a dictionary containing the actions and associated roles on item where item is one of Library, LibraryFolder, LibraryDatasetDatasetAssociation, LibraryDataset, Dataset. The dictionary looks like: { Action : [Role, Role] }.

get_permitted_libraries (*trans, user, actions*)

This method is historical (it is not currently used), but may be useful again at some point. It returns a dictionary whose keys are library objects and whose values are a comma-separated string of folder ids. This method works with the `show_library_item()` method below, and it returns libraries for which the

received user has permission to perform the received actions. Here is an example call to this method to return all libraries for which the received user has LIBRARY_ADD permission:

```
libraries = trans.app.security_agent.get_permitted_libraries( trans, user,
    [ trans.app.security_agent.permitted_actions.LIBRARY_ADD ] )
```

get_private_user_role (*user*, *auto_create=False*)

get_roles_for_action (*item*, *action*)

Return a list containing the roles associated with given action on given item where item is one of Library, LibraryFolder, LibraryDatasetDatasetAssociation, LibraryDataset, Dataset.

get_sharing_roles (*user*)

get_showable_folders (*user*, *roles*, *library_item*, *actions_to_check*, *hidden_folder_ids=[]*, *showable_folders=[]*)

This method must be sent an instance of Library(), all the folders of which are scanned to determine if user is allowed to perform any action in actions_to_check. The param hidden_folder_ids, if passed, should contain a list of folder IDs which was generated when the library was previously scanned using the same actions_to_check. A list of showable folders is generated. This method scans the entire library.

get_valid_roles (*trans*, *item*, *query=None*, *page=None*, *page_limit=None*, *is_library_access=False*)

This method retrieves the list of possible roles that user can select in the item permissions form. Admins can select any role so the results are paginated in order to save the bandwidth and to speed things up. Standard users can select their own private role, any of their sharing roles and any public role (not private and not sharing).

guess_derived_permissions_for_datasets (*datasets=[]*)

Returns a dict of { action : [role, role, ...] } for the output dataset based upon provided datasets

has_accessible_folders (*trans*, *folder*, *user*, *roles*, *search_downward=True*)

has_accessible_library_datasets (*trans*, *folder*, *user*, *roles*, *search_downward=True*)

history_get_default_permissions (*history*)

history_set_default_permissions (*history*, *permissions={}*, *dataset=False*, *by-pass_manage_permission=False*)

item_permission_map_for_add (*trans*, *user_roles*, *libitems*)

item_permission_map_for_manage (*trans*, *user_roles*, *libitems*)

item_permission_map_for_modify (*trans*, *user_roles*, *libitems*)

library_is_public (*library*, *contents=False*)

library_is_unrestricted (*library*)

make_dataset_public (*dataset*)

make_folder_public (*folder*)

make_library_public (*library*, *contents=False*)

ok_to_display (*user*, *role*)

Method for checking if: - a role is private and is the current user's private role - a role is a sharing role and belongs to the current user

privately_share_dataset (*dataset*, *users=[]*)

sa_session

Returns a SQLAlchemy session

```

set_all_dataset_permissions (dataset, permissions={})
    Set new full permissions on a dataset, eliminating all current permissions. Permission looks like: { Action
    : [ Role, Role ] }

set_all_library_permissions (trans, library_item, permissions={})

set_dataset_permission (dataset, permission={})
    Set a specific permission on a dataset, leaving all other current permissions on the dataset alone. Permis-
    sion looks like: { Action.action : [ Role, Role ] }

set_entity_group_associations (groups=[], users=[], roles=[],
                                delete_existing_assocs=True)

set_entity_role_associations (roles=[], users=[], groups=[],
                                delete_existing_assocs=True)

set_entity_user_associations (users=[], roles=[], groups=[],
                                delete_existing_assocs=True)

set_library_item_permission (library_item, permission={})
    Set a specific permission on a library item, leaving all other current permissions on the item alone. Per-
    mission looks like: { Action.action : [ Role, Role ] }

set_request_type_permissions (request_type, permissions={})

show_library_item (user, roles, library_item, actions_to_check, hidden_folder_ids='')
    This method must be sent an instance of Library() or LibraryFolder(). Recursive execution produces a
    comma-separated string of folder ids whose folders do NOT meet the criteria for showing. Along with
    the string, True is returned if the current user has permission to perform any 1 of actions_to_check on
    library_item. Otherwise, cycle through all sub-folders in library_item until one is found that meets this
    criteria, if it exists. This method does not necessarily scan the entire library as it returns when it finds the
    first library_item that allows user to perform any one action in actions_to_check.

sort_by_attr (seq, attr)
    Sort the sequence of objects by object's attribute Arguments: seq - the list or any sequence (including
    immutable one) of objects to sort. attr - the name of attribute to sort by

user_get_default_permissions (user)

user_set_default_permissions (user, permissions={}, history=False, dataset=False,
                                bypass_manage_permission=False, de-
                                fault_access_private=False)

class galaxy.security.HostAgent (model, permitted_actions=None)
    Bases: galaxy.security.RBACAgent

    A simple security agent which allows access to datasets based on host. This exists so that external sites such as
    UCSC can gain access to datasets which have permissions which would normally prevent such access.

    allow_action (addr, action, **kwd)

    sa_session
        Returns a SQLAlchemy session

    set_dataset_permissions (hda, user, site)

    sites = <galaxy.util.bunch.Bunch object>

class galaxy.security.RBACAgent
    Class that handles galaxy security

    associate_components (**kwd)

    can_access_dataset (roles, dataset)

```

can_access_library (*roles, library*)

can_add_library_item (*roles, item*)

can_manage_dataset (*roles, dataset*)

can_manage_library_item (*roles, item*)

can_modify_library_item (*roles, item*)

components_are_associated (***kwd*)

convert_permitted_action_strings (*permitted_action_strings*)
When getting permitted actions from an untrusted source like a form, ensure that they match our actual permitted actions.

create_private_user_role (*user*)

dataset_is_public (*dataset*)

derive_roles_from_access (*trans, item_id, cntrller, library=False, **kwd*)

folder_is_public (*library*)

get_accessible_libraries (*trans, user*)

get_accessible_request_types (*trans, user*)

get_action (*name, default=None*)
Get a permitted action by its dict key or action name

get_actions ()
Get all permitted actions as a list of Action objects

get_all_roles (*trans, cntrller*)

get_component_associations (***kwd*)

get_item_actions (*action, item*)

get_legitimate_roles (*trans, item, cntrller*)

get_permissions (*library_dataset*)

get_permitted_libraries (*trans, user, actions*)

get_private_user_role (*user*)

guess_derived_permissions_for_datasets (*datasets=[]*)

history_set_default_permissions (*history, permissions=None, dataset=False, by-pass_manage_permission=False*)

library_is_public (*library*)

make_dataset_public (*dataset*)

make_folder_public (*folder, count=0*)

make_library_public (*library*)

permitted_actions = <galaxy.util.bunch.Bunch object>

set_all_dataset_permissions (*dataset, permissions*)

set_all_library_permissions (*trans, dataset, permissions*)

set_dataset_permission (*dataset, permission*)

set_library_item_permission (*library_item, permission*)

user_set_default_permissions (*user*, *permissions*={}, *history*=False, *dataset*=False)

`galaxy.security.get_permitted_actions` (*filter*=None)

Utility method to return a subset of RBACAgent's permitted actions

validate_user_input Module Utilities for validating inputs related to user objects.

The `validate_*` methods in this file return simple messages that do not contain user inputs - so these methods do not need to be escaped.

`galaxy.security.validate_user_input.transform_publicname` (*trans*, *publicname*,
user=None)

`galaxy.security.validate_user_input.validate_email` (*trans*, *email*, *user*=None,
check_dup=True)

Validates the email format, also checks whether the domain is blacklisted in the disposable domains configuration.

`galaxy.security.validate_user_input.validate_password` (*trans*, *password*, *confirm*)

`galaxy.security.validate_user_input.validate_publicname` (*trans*, *publicname*,
user=None)

tags Package

tags Package Galaxy tagging classes and methods.

tag_handler Module

tool_shed Package

tool_shed Package

common_util Module

encoding_util Module

install_manager Module

tool_shed_registry Module

update_manager Module

Subpackages

migrate Package

check Module

common Module

tool_dependencies Package

common_util Module

fabric_util Module

install_util Module

tools Package

tools Package Classes encapsulating galaxy tools and tool configuration.

```
class galaxy.tools.AsyncDataSourceTool (config_file, tool_source, app, guid=None, repository_id=None, allow_code_files=True)
```

Bases: *galaxy.tools.DataSourceTool*

tool_type = 'data_source_async'

```
class galaxy.tools.BadValue (value)
```

Bases: object

```
class galaxy.tools.DataDestinationTool (config_file, tool_source, app, guid=None, repository_id=None, allow_code_files=True)
```

Bases: *galaxy.tools.Tool*

tool_type = 'data_destination'

```
class galaxy.tools.DataManagerTool (config_file, root, app, guid=None, data_manager_id=None, **kws)
```

Bases: *galaxy.tools.OutputParameterJSONTool*

allow_user_access (user, attempting_access=True)

Parameters

- **user** (*galaxy.model.User*) – model object representing user.
- **attempting_access** (bool) – is the user attempting to do something with the tool (set false for incidental checks like toolbox listing)

Returns bool – Whether the user is allowed to access the tool.

Data Manager tools are only accessible to admins.

default_tool_action

alias of *DataManagerToolAction*

exec_after_process (app, inp_data, out_data, param_dict, job=None, **kws)

get_default_history_by_trans (trans, create=False)

tool_type = 'manage_data'

```
class galaxy.tools.DataSourceTool (config_file, tool_source, app, guid=None, repository_id=None, allow_code_files=True)
```

Bases: *galaxy.tools.OutputParameterJSONTool*

Alternate implementation of Tool for data_source tools – those that allow the user to query and extract data from another web site.

default_tool_action

alias of DataSourceToolAction

exec_before_job (*app, inp_data, out_data, param_dict=None*)

parse_inputs (*tool_source*)

tool_type = 'data_source'

class galaxy.tools.**DefaultToolState**

Bases: object

Keeps track of the state of a users interaction with a tool between requests. The default tool state keeps track of the current page (for multipage “wizard” tools) and the values of all

copy ()

WARNING! Makes a shallow copy, *SHOULD* rework to have it make a deep copy.

decode (*value, tool, app, secure=True*)

Restore the state from a string

encode (*tool, app, secure=True*)

Convert the data to a string

class galaxy.tools.**ExportHistoryTool** (*config_file, tool_source, app, guid=None, repository_id=None, allow_code_files=True*)

Bases: *galaxy.tools.Tool*

tool_type = 'export_history'

class galaxy.tools.**GenomeIndexTool** (*config_file, tool_source, app, guid=None, repository_id=None, allow_code_files=True*)

Bases: *galaxy.tools.Tool*

tool_type = 'index_genome'

class galaxy.tools.**ImportHistoryTool** (*config_file, tool_source, app, guid=None, repository_id=None, allow_code_files=True*)

Bases: *galaxy.tools.Tool*

tool_type = 'import_history'

exception galaxy.tools.**InterruptedUpload**

Bases: exceptions.Exception

class galaxy.tools.**OutputParameterJSONTool** (*config_file, tool_source, app, guid=None, repository_id=None, allow_code_files=True*)

Bases: *galaxy.tools.Tool*

Alternate implementation of Tool that provides parameters and other values JSONified within the contents of an output dataset

exec_before_job (*app, inp_data, out_data, param_dict=None*)

tool_type = 'output_parameter_json'

class galaxy.tools.**SetMetadataTool** (*config_file, tool_source, app, guid=None, repository_id=None, allow_code_files=True*)

Bases: *galaxy.tools.Tool*

Tool implementation for special tool that sets metadata on an existing dataset.

exec_after_process (*app, inp_data, out_data, param_dict, job=None*)

```
job_failed(job_wrapper, message, exception=False)

requires_setting_metadata = False

tool_type = 'set_metadata'

class galaxy.tools.SetParamAction(name, output_name)
    Set parameter action.

    static parse(elt)
        Parse action from element.

class galaxy.tools.Tool(config_file, tool_source, app, guid=None, repository_id=None, allow_code_files=True)
    Bases: object, galaxy.model.item_attrs.Dictifiable
    Represents a computational tool that can be executed through Galaxy.

    allow_user_access(user, attempting_access=True)

        Returns bool – Whether the user is allowed to access the tool.

    build_dependency_shell_commands()
        Return a list of commands to be run to populate the current environment to include this tools requirements.

    build_redirect_url_params(param_dict)
        Substitute parameter values into self.redirect_url_params

    call_hook(hook_name, *args, **kwargs)
        Call the custom code hook function identified by 'hook_name' if any, and return the results

    check_and_update_param_values(values, trans, update_values=True, allow_workflow_parameters=False)
        Check that all parameters have values, and fill in with default values where necessary. This could be called after loading values from a database in case new parameters have been added.

    check_and_update_param_values_helper(inputs, values, trans, messages, context=None, prefix=', update_values=True, allow_workflow_parameters=False)
        Recursive helper for check_and_update_param_values_helper

    check_workflow_compatible(tool_source)
        Determine if a tool can be used in workflows. External tools and the upload tool are currently not supported by workflows.

    collect_child_datasets(output, job_working_directory)
        Look for child dataset files, create HDA and attach to parent.

    collect_dynamic_collections(output, **kwds)
        Find files corresponding to dynamically structured collections.

    collect_primary_datasets(output, job_working_directory, input_ext)
        Find any additional datasets generated by a tool and attach (for cases where number of outputs is not known in advance).

    default_template = 'tool_form.mako'

    default_tool_action
        alias of DefaultToolAction

    dict_collection_visible_keys = ('id', 'name', 'version', 'description')

    exec_after_process(app, inp_data, out_data, param_dict, job=None)

    exec_before_job(app, inp_data, out_data, param_dict={})
```

execute (*trans*, *incoming*={}, *set_output_hid*=True, *history*=None, ***kwargs*)

Execute the tool using parameter values in *incoming*. This just dispatches to the *ToolAction* instance specified by *self.tool_action*. In general this will create a *Job* that when run will build the tool's outputs, e.g. *DefaultToolAction*.

fill_in_new_state (*trans*, *inputs*, *state*, *context*=None, *history*=None)

Fill in a tool state dictionary with default values for all parameters in the dictionary *inputs*. Grouping elements are filled in recursively.

find_fieldstorage (*x*)

find_output_def (*name*)

get_default_history_by_trans (*trans*, *create*=False)

classmethod get_externally_referenced_paths (*path*)

Return relative paths to externally referenced files by the tool described by file at *path*. External components should not assume things about the structure of tool xml files (this is the tool's responsibility).

get_hook (*name*)

Returns an object from the code file referenced by *code_namespace* (this will normally be a callable object)

get_job_destination (*job_params*=None)

Returns galaxy.jobs.JobDestination – The destination definition and runner parameters.

get_job_handler (*job_params*=None)

Get a suitable job handler for this *Tool* given the provided *job_params*. If multiple handlers are valid for combination of *Tool* and *job_params* (e.g. the defined handler is a handler tag), one will be selected at random.

Parameters *job_params* (*dict* or *None*) – Any params specific to this job (e.g. the job source)

Returns str – The id of a job handler for a job run of this *Tool*

get_panel_section ()

get_param (*key*)

Returns the parameter named *key* or None if there is no such parameter.

get_param_html_map (*trans*, *page*=0, *other_values*={})

Return a dictionary containing the HTML representation of each parameter. This is used for rendering display elements. It is currently not compatible with grouping constructs.

NOTE: This should be considered deprecated, it is only used for tools with *display* elements. These should be eliminated.

get_static_param_values (*trans*)

Returns a map of parameter names and values if the tool does not require any user input. Will raise an exception if any parameter does require input.

handle_input (*trans*, *incoming*, *history*=None, *old_errors*=None, *process_state*='update', *source*='html')

Process incoming parameters for this tool from the dict *incoming*, update the tool state (or create if none existed), and either return to the form or execute the tool (only if 'execute' was clicked and there were no errors).

process_state can be either 'update' (to incrementally build up the state over several calls - one repeat per handle for instance) or 'populate' force a complete build of the state and submission all at once (like from API). May want an incremental version of the API also at some point, that is why this is not just called for_api.

handle_interrupted (*trans, inputs*)

Upon handling inputs, if it appears that we have received an incomplete form, do some cleanup or anything else deemed necessary. Currently this is only likely during file uploads, but this method could be generalized and a method standardized for handling other tools.

handle_job_failure_exception (*e*)

Called by `job.fail` when an exception is generated to allow generation of a better error message (returning `None` yields the default behavior)

handle_single_execution (*trans, rerun_remap_job_id, params, history, mapping_over_collection*)

Return a pair with whether execution is successful as well as either resulting output data or an error message indicating the problem.

handle_unvalidated_param_values (*input_values, app*)

Find any instances of *UnvalidatedValue* within *input_values* and validate them (by calling *ToolParameter.from_html* and *ToolParameter.validate*).

handle_unvalidated_param_values_helper (*inputs, input_values, app, context=None, prefix=''*)

Recursive helper for *handle_unvalidated_param_values*

help**help_by_page****installed_tool_dependencies****job_failed** (*job_wrapper, message, exception=False*)

Called when a job has failed

new_state (*trans, all_pages=False, history=None*)

Create a new *DefaultToolState* for this tool. It will be initialized with default values for inputs.

Only inputs on the first page will be initialized unless *all_pages* is `True`, in which case all inputs regardless of page are initialized.

params_from_strings (*params, app, ignore_errors=False*)**params_to_strings** (*params, app*)**params_with_missing_data_table_entry**

Return all parameters that are dynamically generated select lists whose options require an entry not currently in the *tool_data_table_conf.xml* file.

params_with_missing_index_file

Return all parameters that are dynamically generated select lists whose options refer to a missing *.loc* file.

parse (*tool_source, guid=None*)

Read tool configuration from the element *root* and fill in *self*.

parse_help (*tool_source*)

Parse the help text for the tool. Formatted in reStructuredText, but stored as Mako to allow for dynamic image paths. This implementation supports multiple pages.

parse_input_elem (*page_source, enttypes, context=None*)

Parse a parent element whose children are inputs – these could be groups (repeat, conditional) or parameter elements. Groups will be parsed recursively.

parse_input_page (*page_source, enttypes*)

Parse a page of inputs. This basically just calls ‘*parse_input_elem*’, but it also deals with possible ‘display’ elements which are supported only at the top/page level (not in groups).

parse_inputs (*tool_source*)

Parse the “<inputs>” element and create appropriate `ToolParameter`’s. This implementation supports multiple pages and grouping constructs.

parse_outputs (*tool_source*)

Parse <outputs> elements and fill in `self.outputs` (keyed by name)

parse_param_elem (*input_source, entypes, context*)

Parse a single “<param>” element and return a `ToolParameter` instance. Also, if the parameter has a ‘required_entype’ add it to the set entypes.

parse_redirect_url (*data, param_dict*)

Parse the REDIRECT_URL tool param. Tools that send data to an external application via a redirect must include the following 3 tool params:

1. REDIRECT_URL - the url to which the data is being sent
2. DATA_URL - the url to which the receiving application will send an http post to retrieve the Galaxy data
3. GALAXY_URL - the url to which the external application may post data as a response

parse_stdio (*tool_source*)

Parse <stdio> element(s) and fill in `self.return_codes`, `self.stderr_rules`, and `self.stdout_rules`. Return codes have a range and an error type (fault or warning). Stderr and stdout rules have a regular expression and an error level (fault or warning).

populate_state (*trans, inputs, state, incoming, history=None, source='html', prefix='', context=None*)**populate_tool_shed_info** ()**produces_collections_of_unknown_type****requires_setting_metadata** = True**sa_session**

Returns a SQLAlchemy session

tests**to_dict** (*trans, link_details=False, io_details=False*)

Returns dict of tool.

to_json (*trans, kwd={}, is_workflow=False*)

Recursively creates a tool dictionary containing repeats, dynamic options and updated states.

tool_shed_repository**tool_type** = ‘default’**tool_version**

Return a `ToolVersion` if one exists for our id

tool_versions**update_state** (*trans, inputs, state, incoming, source='html', prefix='', context=None, update_only=False, old_errors={}, item_callback=None*)

Update the tool state in *state* using the user input in *incoming*. This is designed to be called recursively: *inputs* contains the set of inputs being processed, and *prefix* specifies a prefix to add to the name of each input to extract its value from *incoming*.

If *update_only* is True, values that are not in *incoming* will not be modified. In this case *old_errors* can be provided, and any errors for parameters which were *not* updated will be preserved.

visit_inputs (*value, callback*)

Call the function *callback* on each parameter of this tool. Visits grouping parameters recursively and constructs unique prefixes for each nested set of The callback method is then called as:

callback(level_prefix, parameter, parameter_value)

class `galaxy.tools.ToolBox` (*config_filenames, tool_root_dir, app*)

Bases: `galaxy.tools.toolbox.base.AbstractToolBox`

A derivative of `AbstractToolBox` with knowledge about Tool internals - how to construct them, action types, dependency management, etc....

create_tool (*config_file, repository_id=None, guid=None, **kwds*)

handle_datatypes_changed ()

Refresh upload tools when new datatypes are added.

tools_by_id

class `galaxy.tools.ToolErrorLog`

add_error (*file, phase, exception*)

exception `galaxy.tools.ToolNotFoundException`

Bases: `exceptions.Exception`

class `galaxy.tools.ToolOutput` (*name, format=None, format_source=None, metadata_source=None, parent=None, label=None, filters=None, actions=None, hidden=False, implicit=False*)

Bases: `galaxy.tools.ToolOutputBase`

Represents an output datasets produced by a tool. For backward compatibility this behaves as if it were the tuple:

(*format, metadata_source, parent*)

dict_collection_visible_keys = ('name', 'format', 'label', 'hidden')

to_dict (*view='collection', value_mapper=None, app=None*)

class `galaxy.tools.ToolOutputBase` (*name, label=None, filters=None, hidden=False*)

Bases: `object, galaxy.model.item_attrs.Dictifiable`

class `galaxy.tools.ToolOutputCollection` (*name, structure, label=None, filters=None, hidden=False, default_format='data', default_format_source=None, default_metadata_source=None, inherit_format=False, inherit_metadata=False*)

Bases: `galaxy.tools.ToolOutputBase`

Represents a `HistoryDatasetCollectionAssociation` of output datasets produced by a tool. <outputs>

```
<dataset_collection type="list" label="{tool.name} on ${on_string} fasta">
  <discover_datasets pattern="__name__" ext="fasta" visible="True" directory="outputFiles"
  />
```

```
</dataset_collection> <dataset_collection type="paired" label="{tool.name} on ${on_string}
paired reads">
```

```
  <data name="forward" format="fastqsanger" /> <data name="reverse" for-
  mat="fastqsanger"/>
```

```
</dataset_collection>
```



```

    <outputs>
    dataset_collectors
    dynamic_structure
    known_outputs (inputs, type_registry)
class galaxy.tools.ToolOutputCollectionPart (output_collection_def, element_identifier, out-
                                         put_def)
    Bases: object
    effective_output_name
    static is_named_collection_part_name (name)
    static split_output_name (name)
class galaxy.tools.ToolOutputCollectionStructure (collection_type,          structured_like,
                                                dataset_collectors)
    Bases: object
class galaxy.tools.TracksterConfig (actions)
    Trackster configuration encapsulation.
    static parse (root)
galaxy.tools.check_param_from_incoming (trans, state, input, incoming, key, context, source)
    Unlike “update” state, this preserves default if no incoming value found. This lets API user specify just a subset
    of params and allow defaults to be used when available.
galaxy.tools.get_incoming_value (incoming, key, default)
    Fetch value from incoming dict directly or check special nginx upload created variants of this key.
galaxy.tools.json_fix (val)
galaxy.tools.tool_class
    alias of DataDestinationTool

exception_handling Module Exceptions and handlers for tools.
FIXME: These are used by tool scripts, not the framework, and should not live in this package.
exception galaxy.tools.exception_handling.UCSCLimitException
    Bases: exceptions.Exception
class galaxy.tools.exception_handling.UCSOutWrapper (other)
    Bases: object
    File-like object that throws an exception if it encounters the UCSC limit error lines
    next ()
    readline ()

test Module
class galaxy.tools.test.ParamContext (name, index=None, parent_context=None)
    Bases: object
    extract_value (raw_inputs)
    for_state ()
    param_names ()

```

```
class galaxy.tools.test.RootParamContext
```

Bases: object

```
    for_state()
```

```
    get_index()
```

```
    param_names()
```

```
class galaxy.tools.test.ToolTestBuilder(tool, test_dict, i, default_interactor)
```

Bases: object

Encapsulates information about a tool test, and allows creation of a dynamic TestCase class (the unittest framework is very class oriented, doing dynamic tests in this way allows better integration)

```
    test_data()
```

Iterator over metadata representing the required files for upload.

```
galaxy.tools.test.nottest(x)
```

```
galaxy.tools.test.parse_tests(tool, tests_source)
```

Build ToolTestBuilder objects for each “<test>” elements and return default interactor (if any).

```
galaxy.tools.test.require_file(name, value, extra, required_files)
```

```
galaxy.tools.test.test_data_iter(required_files)
```

Subpackages

actions Package

actions Package

```
class galaxy.tools.actions.DefaultToolAction
```

Bases: object

Default tool action is to run an external command

```
    collect_input_dataset_collections(tool, param_values)
```

```
    collect_input_datasets(tool, param_values, trans)
```

Collect any dataset inputs from incoming. Returns a mapping from parameter name to Dataset instance for each tool parameter that is of the DataToolParameter type.

```
    execute(tool, trans, incoming={}, return_job=False, set_output_hid=True, set_output_history=True,
            history=None, job_params=None, rerun_remap_job_id=None, mapping_over_collection=False)
```

Executes a tool, creating job and tool outputs, associating them, and submitting the job to the job queue. If history is not specified, use trans.history as destination for tool’s output datasets.

```
    get_output_name(output, dataset, tool, on_text, trans, incoming, history, params, job_params)
```

```
class galaxy.tools.actions.ObjectStorePopulator(app)
```

Bases: object

Small helper for interacting with the object store and making sure all datasets from a job end up with the same object_store_id.

```
    set_object_store_id(data)
```

```
class galaxy.tools.actions.ToolAction
```

Bases: object

The actions to be taken when a tool is run (after parameters have been converted and validated).

execute (*tool, trans, incoming={}*, *set_output_hid=True*)

`galaxy.tools.actions.determine_output_format` (*output, parameter_context, input_datasets,*
random_input_ext)

Determines the output format for a dataset based on an abstract description of the output (`galaxy.tools.ToolOutput`), the parameter wrappers, a map of the input datasets (`name => HDA`), and the last input extensions in the tool form.

TODO: Don't deal with XML here - move this logic into `ToolOutput`. TODO: Make the input extension used deterministic instead of random.

`galaxy.tools.actions.filter_output` (*output, incoming*)

`galaxy.tools.actions.on_text_for_names` (*input_names*)

history_imp_exp Module

class `galaxy.tools.actions.history_imp_exp.ExportHistoryToolAction`

Bases: `galaxy.tools.actions.ToolAction`

Tool action used for exporting a history to an archive.

execute (*tool, trans, incoming={}*, *set_output_hid=False*, *overwrite=True*, *history=None*, ***kwargs*)

class `galaxy.tools.actions.history_imp_exp.ImportHistoryToolAction`

Bases: `galaxy.tools.actions.ToolAction`

Tool action used for importing a history to an archive.

execute (*tool, trans, incoming={}*, *set_output_hid=False*, *overwrite=True*, *history=None*, ***kwargs*)

index_genome Module

metadata Module

class `galaxy.tools.actions.metadata.SetMetadataToolAction`

Bases: `galaxy.tools.actions.__init__.ToolAction`

Tool action used for setting external metadata on an existing dataset

execute (*tool, trans, incoming={}*, *set_output_hid=False*, *overwrite=True*, *history=None*,
job_params=None, ***kwargs*)
Execute using a web transaction.

execute_via_app (*tool, app, session_id, history_id, user=None, incoming={}*,
set_output_hid=False, *overwrite=True*, *history=None*, *job_params=None*)
Execute using application.

upload Module

class `galaxy.tools.actions.upload.UploadToolAction`

Bases: `galaxy.tools.actions.__init__.ToolAction`

execute (*tool, trans, incoming={}*, *set_output_hid=True*, *history=None*, ***kwargs*)

upload_common Module

`galaxy.tools.actions.upload_common.active_folders` (*trans, folder*)

`galaxy.tools.actions.upload_common.cleanup_unused_precreated_datasets` (*precreated_datasets*)

`galaxy.tools.actions.upload_common.create_job` (*trans, params, tool, json_file_path,*
data_list, folder=None, history=None)

Create the upload job.

```
galaxy.tools.actions.upload_common.create_paramfile(trans, uploaded_datasets)
```

Create the upload tool's JSON "param" file.

```
galaxy.tools.actions.upload_common.get_precreated_dataset(precreated_datasets,  
                                                           name)
```

Return a dataset matching a name from the list of precreated (via async upload) datasets. If there's more than one upload with the exact same name, we need to pop one (the first) so it isn't chosen next time.

```
galaxy.tools.actions.upload_common.get_precreated_datasets(trans,          params,  
                                                           data_obj,          con-  
                                                           troller='root')
```

Get any precreated datasets (when using asynchronous uploads).

```
galaxy.tools.actions.upload_common.get_uploaded_datasets(trans, cntrller, params,  
                                                         precreated_datasets,  
                                                         dataset_upload_inputs,  
                                                         library_bunch=None,  
                                                         history=None)
```

```
galaxy.tools.actions.upload_common.handle_library_params(trans, params, folder_id,  
                                                         replace_dataset=None)
```

```
galaxy.tools.actions.upload_common.new_upload(trans, cntrller, uploaded_dataset, li-  
                                              brary_bunch=None,          history=None,  
                                              state=None)
```

```
galaxy.tools.actions.upload_common.persist_uploads(params)
```

Turn any uploads in the submitted form to persisted files.

data Package

data Package Manage tool data tables, which store (at the application level) data that is used by tools, for example in the generation of dynamic options. Tables are loaded and stored by names which tools use to refer to them. This allows users to configure data tables for a local Galaxy instance without needing to modify the tool configurations.

```
class galaxy.tools.data.TabularToolDataField(data)
```

Bases: *galaxy.model.item_attrs.Dictifiable*, object

```
clean_base_dir(path)
```

```
dict_collection_visible_keys = []
```

```
get_base_dir()
```

```
get_base_path()
```

```
get_files()
```

```
get_filesize_map(rm_base_dir=False)
```

```
get_fingerprint()
```

```
to_dict()
```

```
class galaxy.tools.data.TabularToolDataTable(config_element,          tool_data_path,  
                                              from_shed_config=False, filename=None)
```

Bases: *galaxy.tools.data.ToolDataTable*, *galaxy.model.item_attrs.Dictifiable*

Data stored in a tabular / separated value format on disk, allows multiple files to be merged but all must have the same column definitions:

```
<table type="tabular" name="test">
  <column name='...' index = '...' />
  <file path="..." />
  <file path="..." />
</table>
```

configure_and_load (*config_element*, *tool_data_path*, *from_shed_config=False*, *url_timeout=10*)
Configure and load table from an XML element.

dict_collection_visible_keys = ['name']

extend_data_with (*filename*, *errors=None*)

filter_file_fields (*loc_file*, *values*)

Reads separated lines from file and print back only the lines that pass a filter.

get_column_name_list ()

get_entries (*query_attr*, *query_val*, *return_attr*, *default=None*, *limit=None*)

Returns table entry associated with a col/val pair.

get_entry (*query_attr*, *query_val*, *return_attr*, *default=None*)

Returns table entry associated with a col/val pair.

get_field (*value*)

get_fields ()

get_filename_for_source (*source*, *default=None*)

get_named_fields_list ()

get_version_fields ()

handle_found_index_file (*filename*)

merge_tool_data_table (*other_table*, *allow_duplicates=True*, *persist=False*, *persist_on_error=False*, *entry_source=None*, ***kwd*)

parse_column_spec (*config_element*)

Parse column definitions, which can either be a set of 'column' elements with a name and index (as in dynamic options config), or a shorthand comma separated list of names in order as the text of a 'column_names' element.

A column named 'value' is required.

parse_file_fields (*reader*, *errors=None*, *here='__HERE__'*)

Parse separated lines from file and return a list of tuples.

TODO: Allow named access to fields using the column names.

to_dict (*view='collection'*)

type_key = 'tabular'

xml_string

class galaxy.tools.data.**ToolDataTable** (*config_element*, *tool_data_path*, *from_shed_config=False*, *filename=None*)

Bases: object

add_entries (*entries*, *allow_duplicates=True*, *persist=False*, *persist_on_error=False*, *entry_source=None*, ***kwd*)

add_entry (*entry*, *allow_duplicates=True*, *persist=False*, *persist_on_error=False*, *entry_source=None*, ***kwd*)

```

classmethod from_elem (table_elem, tool_data_path, from_shed_config, filename)

get_empty_field_by_name (name)

is_current_version (other_version)

merge_tool_data_table (other_table, allow_duplicates=True, persist=False, per-
                        sist_on_error=False, entry_source=None, **kwd)

reload_from_files ()

remove_entry (values)

```

```
class galaxy.tools.data.ToolDataTableManager (tool_data_path, config_filename=None)
```

Bases: object

Manages a collection of tool data tables

```

add_new_entries_from_config_file (config_filename, tool_data_path,
                                   shed_tool_data_table_config, persist=False)

```

This method is called when a tool shed repository that includes a `tool_data_table_conf.xml.sample` file is being installed into a local galaxy instance. We have 2 cases to handle, files whose root tag is `<tables>`, for example:

```

<tables>
  <!-- Location of Tmap files -->
  <table name="tmap_indexes" comment_char="#">
    <columns>value, dbkey, name, path</columns>
    <file path="tool-data/tmap_index.loc" />
  </table>
</tables>

```

and files whose root tag is `<table>`, for example:

```

<!-- Location of Tmap files -->
<table name="tmap_indexes" comment_char="#">
  <columns>value, dbkey, name, path</columns>
  <file path="tool-data/tmap_index.loc" />
</table>

```

```
get (name, default=None)
```

```
get_tables ()
```

```
load_from_config_file (config_filename, tool_data_path, from_shed_config=False)
```

This method is called under 3 conditions:

1. When the ToolDataTableManager is initialized (see `__init__` above).
2. Just after the ToolDataTableManager is initialized and the additional entries defined by `shed_tool_data_table_conf.xml` are being loaded into the ToolDataTableManager.data_tables.
3. When a tool shed repository that includes a `tool_data_table_conf.xml.sample` file is being installed into a local Galaxy instance. In this case, we have 2 entry types to handle, files whose root tag is `<tables>`, for example:

```
reload_tables (table_names=None)
```

```
set (name, value)
```

```
to_xml_file (shed_tool_data_table_config, new_elems=None, remove_elems=None)
```

Write the current in-memory version of the `shed_tool_data_table_conf.xml` file to disk. `remove_elems` are removed before `new_elems` are added.

```
galaxy.tools.data.cls
    alias of TabularToolDataTable

galaxy.tools.data.expand_here_template(content, here=None)
```

deps Package

deps Package Dependency management for tools.

```
class galaxy.tools.deps.DependencyManager(default_base_path, conf_file=None)
    Bases: object
```

A DependencyManager attempts to resolve named and versioned dependencies by searching for them under a list of directories. Directories should be of the form:

\$BASE/name/version/...

and should each contain a file 'env.sh' which can be sourced to make the dependency available in the current shell environment.

dependency_shell_commands (*requirements, **kwds*)

find_dep (*name, version=None, type='package', **kwds*)

uses_tool_shed_dependencies ()

```
class galaxy.tools.deps.NullDependencyManager
    Bases: object
```

dependency_shell_commands (*requirements, **kwds*)

find_dep (*name, version=None, type='package', **kwds*)

uses_tool_shed_dependencies ()

```
galaxy.tools.deps.build_dependency_manager(config)
```

tests Module

genome_index Package

genome_index Package

index_genome Module

imp_exp Package

imp_exp Package

```
class galaxy.tools.imp_exp.JobExportHistoryArchiveWrapper(job_id)
    Bases: object, galaxy.model.item_attrs.UsesAnnotations
```

Class provides support for performing jobs that export a history to an archive.

cleanup_after_job (*db_session*)

Remove temporary directory and attribute files generated during setup for this job.

get_history_datasets (*trans, history*)

Returns history's datasets.

setup_job (*trans, jeha, include_hidden=False, include_deleted=False*)

Perform setup for job to export a history into an archive. Method generates attribute files for export, sets the corresponding attributes in the *jeha* object, and returns a command line for running the job. The command line includes the command, inputs, and options; it does not include the output file because it must be set at runtime.

class `galaxy.tools.imp_exp.JobImportHistoryArchiveWrapper` (*app, job_id*)

Bases: object, *galaxy.model.item_attrs.UsesAnnotations*

Class provides support for performing jobs that import a history from an archive.

cleanup_after_job ()

Set history, datasets, and jobs' attributes and clean up archive directory.

`galaxy.tools.imp_exp.load_history_imp_exp_tools` (*toolbox*)

Adds tools for importing/exporting histories to archives.

export_history Module Export a history to an archive file using attribute files.

usage: `%prog history_attrs dataset_attrs job_attrs out_file -G, -gzip: gzip archive file`

`galaxy.tools.imp_exp.export_history.create_archive` (*history_attrs_file,*
datasets_attrs_file, jobs_attrs_file,
out_file, gzip=False)

Create archive from the given attribute/metadata files and save it to *out_file*.

`galaxy.tools.imp_exp.export_history.get_dataset_filename` (*name, ext*)

Builds a filename for a dataset using its name and extension.

`galaxy.tools.imp_exp.export_history.main` ()

unpack_tar_gz_archive Module Unpack a tar or tar.gz archive into a directory.

usage: `%prog archive_source dest_dir -[urlfile] source type, either a URL or a file.`

`galaxy.tools.imp_exp.unpack_tar_gz_archive.unpack_archive` (*archive_file, dest_dir*)

Unpack a tar and/or gzipped archive into a destination directory.

`galaxy.tools.imp_exp.unpack_tar_gz_archive.url_to_file` (*url, dest_file*)

Transfer a file from a remote URL to a temporary file.

parameters Package

parameters Package Classes encapsulating Galaxy tool parameters.

`galaxy.tools.parameters.check_param` (*trans, param, incoming_value, param_values,*
source='html', history=None)

Check the value of a single parameter *param*. The value in *incoming_value* is converted from its HTML encoding and validated. The *param_values* argument contains the processed values of previous parameters (this may actually be an ExpressionContext when dealing with grouping scenarios).

`galaxy.tools.parameters.params_from_strings` (*params, param_values, app, ignore_errors=False*)

Convert a dictionary of strings as produced by *params_to_strings* back into parameter values (decode the json representation and then allow each parameter to convert the basic types into the parameters preferred form).

`galaxy.tools.parameters.params_to_incoming` (*incoming, inputs, input_values, app,*
name_prefix='', to_html=True)

Given a tool's parameter definition (*inputs*) and a specific set of parameter *input_values* objects, populate *incoming* with the html values.

Useful for e.g. the rerun function.

`galaxy.tools.parameters.params_to_strings` (*params*, *param_values*, *app*)

Convert a dictionary of parameter values to a dictionary of strings suitable for persisting. The *value_to_basic* method of each parameter is called to convert its value to basic types, the result of which is then json encoded (this allowing complex nested parameters and such).

`galaxy.tools.parameters.visit_input_values` (*inputs*, *input_values*, *callback*, *name_prefix*='', *label_prefix*='')

Given a tools parameter definition (*inputs*) and a specific set of parameter *values*, call *callback* for each non-grouping parameter, passing the parameter object, value, a constructed unique name, and a display label.

If the callback returns a value, it will be replace the old value.

FIXME: There is redundancy between this and the visit_inputs methods of Repeat and Group. This tracks labels and those do not. It would be nice to unify all the places that recursively visit inputs.

basic Module Basic tool parameters.

class `galaxy.tools.parameters.basic.BaseDataToolParameter` (*tool*, *input_source*, *trans*)

Bases: `galaxy.tools.parameters.basic.ToolParameter`

class `galaxy.tools.parameters.basic.BaseURLToolParameter` (*tool*, *input_source*)

Bases: `galaxy.tools.parameters.basic.HiddenToolParameter`

Returns a parameter that contains its value prepended by the current server base url. Used in all redirects.

from_html (*value*=None, *trans*=None, *context*={})

get_html_field (*trans*=None, *value*=None, *other_values*={})

get_initial_value (*trans*, *context*, *history*=None)

to_dict (*trans*, *view*='collection', *value_mapper*=None, *other_values*={})

class `galaxy.tools.parameters.basic.BooleanToolParameter` (*tool*, *input_source*)

Bases: `galaxy.tools.parameters.basic.ToolParameter`

Parameter that takes one of two values.

```
>>> p = BooleanToolParameter( None, XML( '<param name="blah" type="boolean" checked="yes" truevalue="bulletproof vests" falsevalue="cellophane chests"' ) )
>>> print p.name
blah
>>> print p.get_html()
<input type="checkbox" id="blah" name="blah" value="true" checked="checked"><input type="hidden" name="blah" value="false" />
>>> print p.from_html( ["true", "true"] )
True
>>> print p.to_param_dict_string( True )
bulletproof vests
>>> print p.from_html( ["true"] )
False
>>> print p.to_param_dict_string( False )
cellophane chests
```

from_html (*value*, *trans*=None, *other_values*={})

from_json (*value*, *trans*=None, *other_values*={})

get_html_field (*trans*=None, *value*=None, *other_values*={})

get_initial_value (*trans*, *context*, *history*=None)

legal_values

```
to_dict (trans, view='collection', value_mapper=None, other_values={})
```

```
to_html_value (value, app)
```

```
to_param_dict_string (value, other_values={})
```

```
to_python (value, app)
```

```
class galaxy.tools.parameters.basic.ColorToolParameter (tool, input_source)
```

Bases: `galaxy.tools.parameters.basic.ToolParameter`

Parameter that stores a color.

```
>>> p = ColorToolParameter( None, XML( '<param name="blah" type="color" value="#ffffff"/>' ) )
>>> print p.name
blah
```

```
get_html_field (trans=None, value=None, other_values={})
```

```
get_initial_value (trans, context, history=None)
```

```
class galaxy.tools.parameters.basic.ColumnListParameter (tool, input_source)
```

Bases: `galaxy.tools.parameters.basic.SelectToolParameter`

Select list that consists of either the total number of columns or only those columns that contain numerical values in the associated DataToolParameter.

TODO: we need better testing here, but not sure how to associate a DatatoolParameter with a ColumnListParameter # from a twill perspective...

```
>>> # Mock up a history (not connected to database)
>>> from galaxy.model import History, HistoryDatasetAssociation
>>> from galaxy.util.bunch import Bunch
>>> from galaxy.model.mapping import init
>>> sa_session = init( "/tmp", "sqlite:///memory:", create_tables=True ).session
>>> hist = History()
>>> sa_session.add( hist )
>>> sa_session.flush()
>>> hda = hist.add_dataset( HistoryDatasetAssociation( id=1, extension='interval', create_dataset=True ) )
>>> dtp = DataToolParameter( None, XML( '<param name="blah" type="data" format="interval"/>' ) )
>>> print dtp.name
blah
>>> clp = ColumnListParameter ( None, XML( '<param name="numerical_column" type="data_column" data_format="interval"/>' ) )
>>> print clp.name
numerical_column
```

```
from_html (value, trans=None, context={})
```

Label convention prepends column number with a 'c', but tool uses the integer. This removes the 'c' when entered into a workflow.

```
get_column_list (trans, other_values)
```

Generate a select list containing the columns of the associated dataset (if found).

```
get_dependencies ()
```

```
get_initial_value (trans, context, history=None)
```

```
get_legal_values (trans, other_values)
```

```
get_options (trans, other_values)
```

show column labels rather than c1..cn if use_header_names=True

```

    to_dict (trans, view='collection', value_mapper=None, other_values={})
galaxy.tools.parameters.basic.DEFAULT_VALUE_MAP (x)
class galaxy.tools.parameters.basic.DataCollectionToolParameter (tool, input_source, trans=None)
    Bases: galaxy.tools.parameters.basic.BaseDataToolParameter
    collection_type
    from_html (value, trans, other_values={})
    get_html_field (trans=None, value=None, other_values={})
    match_collections (trans, history, dataset_matcher)
    match_multirun_collections (trans, history, dataset_matcher)
    to_dict (trans, view='collection', value_mapper=None, other_values=None)
    to_python (value, app)
    to_string (value, app)
    validate (value, history=None)
    value_to_display_text (value, app)
class galaxy.tools.parameters.basic.DataToolParameter (tool, input_source, trans=None)
    Bases: galaxy.tools.parameters.basic.BaseDataToolParameter
    Parameter that takes on one (or many) or a specific set of values.
    TODO: There should be an alternate display that allows single selects to be displayed as radio buttons and
    multiple selects as a set of checkboxes
    TODO: The following must be fixed to test correctly for the new security_check tag in the DataToolParameter (
    the last test below is broken ) Nate's next pass at the dataset security stuff will dramatically alter this anyway.
    converter_safe (other_values, trans)
    from_html (value, trans, other_values={})
    get_dependencies ()
        Get the names of the other params this param depends on.
    get_html_field (trans=None, value=None, other_values={})
    get_initial_value (trans, context, history=None)
    get_initial_value_from_history_prevent_repeats (trans, context, already_used, history=None)
    NOTE: This is wasteful since dynamic options and dataset collection happens twice (here and when
    generating HTML).
    match_collections (history, dataset_matcher, reduction=True)
    match_datasets (history, dataset_matcher)
    to_dict (trans, view='collection', value_mapper=None, other_values=None)
    to_param_dict_string (value, other_values={})
    to_python (value, app)
    to_string (value, app)
    validate (value, history=None)

```

value_to_display_text (*value*, *app*)

class galaxy.tools.parameters.basic.**DrillDownSelectToolParameter** (*tool*, *input_source*, *context=None*)

Bases: *galaxy.tools.parameters.basic.SelectToolParameter*

Parameter that takes on one (or many) of a specific set of values. Creating a hierarchical select menu, which allows users to ‘drill down’ a tree-like set of options.

```
>>> p = DrillDownSelectToolParameter( None, XML(
... '''
... <param name="some_name" type="drill_down" display="checkbox" hierarchy="recurse" multiple="t
... <options>
... <option name="Heading 1" value="heading1">
... <option name="Option 1" value="option1"/>
... <option name="Option 2" value="option2"/>
... <option name="Heading 1" value="heading1">
... <option name="Option 3" value="option3"/>
... <option name="Option 4" value="option4"/>
... </option>
... </option>
... <option name="Option 5" value="option5"/>
... </options>
... </param>
... ''' ) )
>>> print p.get_html()
<div class="form-row drilldown-container" id="drilldown--736f6d655f6e616d65">
<div class="form-row-input">
<div><span class="form-toggle icon-button toggle-expand" id="drilldown--736f6d655f6e616d65-68656
<input type="checkbox" name="some_name" value="heading1" >Heading 1
</div><div class="form-row" id="drilldown--736f6d655f6e616d65-68656164696e6731-container" style=
<div class="form-row-input">
<input type="checkbox" name="some_name" value="option1" >Option 1
</div>
<div class="form-row-input">
<input type="checkbox" name="some_name" value="option2" >Option 2
</div>
<div class="form-row-input">
<div><span class="form-toggle icon-button toggle-expand" id="drilldown--736f6d655f6e616d65-68656
<input type="checkbox" name="some_name" value="heading1" >Heading 1
</div><div class="form-row" id="drilldown--736f6d655f6e616d65-68656164696e6731-68656164696e6731-
<div class="form-row-input">
<input type="checkbox" name="some_name" value="option3" >Option 3
</div>
<div class="form-row-input">
<input type="checkbox" name="some_name" value="option4" >Option 4
</div>
</div>
</div>
</div>
<div class="form-row-input">
<input type="checkbox" name="some_name" value="option5" >Option 5
</div>
</div>
>>> p = DrillDownSelectToolParameter( None, XML(
... '''
... <param name="some_name" type="drill_down" display="radio" hierarchy="recurse" multiple="false">
```

```

...     <options>
...         <option name="Heading 1" value="heading1">
...             <option name="Option 1" value="option1"/>
...             <option name="Option 2" value="option2"/>
...             <option name="Heading 1" value="heading1">
...                 <option name="Option 3" value="option3"/>
...                 <option name="Option 4" value="option4"/>
...             </option>
...         </option>
...         <option name="Option 5" value="option5"/>
...     </options>
... </param>
... ''' ) )
>>> print p.get_html()
<div class="form-row drilldown-container" id="drilldown--736f6d655f6e616d65">
<div class="form-row-input">
<div><span class="form-toggle icon-button toggle-expand" id="drilldown--736f6d655f6e616d65-68656"
<input type="radio" name="some_name" value="heading1" >Heading 1
</div><div class="form-row" id="drilldown--736f6d655f6e616d65-68656164696e6731-container" style=
<div class="form-row-input">
<input type="radio" name="some_name" value="option1" >Option 1
</div>
<div class="form-row-input">
<input type="radio" name="some_name" value="option2" >Option 2
</div>
<div class="form-row-input">
<div><span class="form-toggle icon-button toggle-expand" id="drilldown--736f6d655f6e616d65-68656"
<input type="radio" name="some_name" value="heading1" >Heading 1
</div><div class="form-row" id="drilldown--736f6d655f6e616d65-68656164696e6731-68656164696e6731-
<div class="form-row-input">
<input type="radio" name="some_name" value="option3" >Option 3
</div>
<div class="form-row-input">
<input type="radio" name="some_name" value="option4" >Option 4
</div>
</div>
</div>
</div>
</div>
<div class="form-row-input">
<input type="radio" name="some_name" value="option5" >Option 5
</div>
</div>
>>> print sorted(p.options[1].items())
[('name', 'Option 5'), ('options', []), ('selected', False), ('value', 'option5')]
>>> p.options[0]["name"]
'Heading 1'
>>> p.options[0]["selected"]
False

```

from_html (value, trans=None, other_values={})

get_dependencies ()

Get the *names* of the other params this param depends on.

get_html (trans=None, value=None, other_values={})

Returns the html widget corresponding to the paramter. Optionally attempt to retain the current value specific by 'value'

```

get_html_field (trans=None, value=None, other_values={})
get_initial_value (trans, context, history=None)
get_legal_values (trans, other_values)
get_options (trans=None, value=None, other_values={})
to_dict (trans, view='collection', value_mapper=None, other_values={})
to_param_dict_string (value, other_values={}, value_map=<function <lambda>>())
value_to_display_text (value, app)

```

```
class galaxy.tools.parameters.basic.DummyDataset
```

Bases: object

```
class galaxy.tools.parameters.basic.FTPFileToolParameter (tool, input_source)
```

Bases: *galaxy.tools.parameters.basic.ToolParameter*

Parameter that takes a file uploaded via FTP as a value.

```

from_html (value, trans=None, other_values={})
get_html_field (trans=None, value=None, other_values={})
get_initial_value (trans, context, history=None)
to_dict (trans, view='collection', value_mapper=None, other_values=None)
to_param_dict_string (value, other_values={})
to_python (value, app, validate=False)
to_string (value, app)
visible

```

```
class galaxy.tools.parameters.basic.FileToolParameter (tool, input_source)
```

Bases: *galaxy.tools.parameters.basic.ToolParameter*

Parameter that takes an uploaded file as a value.

```

>>> p = FileToolParameter( None, XML( '<param name="blah" type="file"/>' ) )
>>> print p.name
blah
>>> print p.get_html()
<input type="file" name="blah">
>>> p = FileToolParameter( None, XML( '<param name="blah" type="file" ajax-upload="true"/>' ) )
>>> print p.get_html()
<input type="file" name="blah" galaxy-ajax-upload="true">

```

```

from_html (value, trans=None, other_values={})
get_html_field (trans=None, value=None, other_values={})
get_initial_value (trans, context, history=None)
get_required enctype ()
    File upload elements require the multipart/form-data encoding
to_python (value, app)
to_string (value, app)

```

```
class galaxy.tools.parameters.basic.FloatToolParameter(tool, input_source)
    Bases: galaxy.tools.parameters.basic.TextToolParameter
```

Parameter that takes a real number value.

```
>>> p = FloatToolParameter( None, XML( '<param name="blah" type="float" size="4" value="3.141592'
>>> print p.name
blah
>>> print p.get_html()
<input type="text" name="blah" size="4" value="3.141592">
>>> type( p.from_html( "36.1" ) )
<type 'float'>
>>> type( p.from_html( "bleh" ) )
Traceback (most recent call last):
...
ValueError: A real number is required
```

```
dict_collection_visible_keys = ('name', 'argument', 'type', 'label', 'help', 'min', 'max')
```

```
from_html (value, trans=None, other_values={})
```

```
get_html_field (trans=None, value=None, other_values={})
```

```
get_initial_value (trans, context, history=None)
```

```
to_python (value, app)
```

```
class galaxy.tools.parameters.basic.GenomeBuildParameter(*args, **kwargs)
    Bases: galaxy.tools.parameters.basic.SelectToolParameter
```

Select list that sets the last used genome build for the current history as “selected”.

```
>>> # Create a mock transaction with 'hg17' as the current build
>>> from galaxy.util.bunch import Bunch
>>> trans = Bunch( history=Bunch( genome_build='hg17' ), db_builds=util.read_dbnames( None ) )
```

```
>>> p = GenomeBuildParameter( None, XML(
... '''
... <param name="blah" type="genomebuild" />
... ''' ) )
>>> print p.name
blah
```

```
>>> # hg17 should be selected by default
>>> print p.get_html( trans )
<select name="blah" last_selected_value="hg17">
<option value="?">unspecified (?)</option>
...
<option value="hg18">Human Mar. 2006 (NCBI36/hg18) (hg18)</option>
<option value="hg17" selected>Human May 2004 (NCBI35/hg17) (hg17)</option>
...
</select>
```

```
>>> # If the user selected something else already, that should be used
>>> # instead
>>> print p.get_html( trans, value='hg18' )
<select name="blah" last_selected_value="hg18">
```

```
<option value="?">unspecified (?)</option>
...
<option value="hg18" selected>Human Mar. 2006 (NCBI36/hg18) (hg18)</option>
<option value="hg17">Human May 2004 (NCBI35/hg17) (hg17)</option>
...
</select>
```

```
>>> print p.filter_value( "hg17" )
hg17
```

```
get_legal_values (trans, other_values)
```

```
get_options (trans, other_values)
```

```
to_dict (trans, view='collection', value_mapper=None, other_values={})
```

```
class galaxy.tools.parameters.basic.HiddenDataToolParameter (tool, elem)
```

Bases: *galaxy.tools.parameters.basic.HiddenToolParameter*,
galaxy.tools.parameters.basic.DataToolParameter

Hidden parameter that behaves as a DataToolParameter. As with all hidden parameters, this is a HACK.

```
get_html_field (trans=None, value=None, other_values={})
```

```
get_initial_value (trans, context, history=None)
```

```
class galaxy.tools.parameters.basic.HiddenToolParameter (tool, input_source)
```

Bases: *galaxy.tools.parameters.basic.ToolParameter*

Parameter that takes one of two values.

FIXME: This seems hacky, parameters should only describe things the user might change. It is used for 'initializing' the UCSC proxy tool

```
>>> p = HiddenToolParameter( None, XML( '<param name="blah" type="hidden" value="wax so rockin"/>' ) )
>>> print p.name
blah
>>> print p.get_html()
<input type="hidden" name="blah" value="wax so rockin">
```

```
get_html_field (trans=None, value=None, other_values={})
```

```
get_initial_value (trans, context, history=None)
```

```
get_label()
```

```
class galaxy.tools.parameters.basic.IntegerToolParameter (tool, input_source)
```

Bases: *galaxy.tools.parameters.basic.TextToolParameter*

Parameter that takes an integer value.

```
>>> p = IntegerToolParameter( None, XML( '<param name="blah" type="integer" size="4" value="10"/>' ) )
>>> print p.name
blah
>>> print p.get_html()
<input type="text" name="blah" size="4" value="10">
>>> type( p.from_html( "10" ) )
<type 'int'>
>>> type( p.from_html( "bleh" ) )
Traceback (most recent call last):
```



```
...
ValueError: An integer is required
```

```
dict_collection_visible_keys = ('name', 'argument', 'type', 'label', 'help', 'min', 'max')
from_html (value, trans=None, other_values={})
get_html_field (trans=None, value=None, other_values={})
get_initial_value (trans, context, history=None)
to_python (value, app)
```

```
class galaxy.tools.parameters.basic.LibraryDatasetToolParameter (tool, input_source,
                                                                context=None)
```

Bases: *galaxy.tools.parameters.basic.ToolParameter*

Parameter that lets users select a LDDA from a modal window, then use it within the wrapper.

```
from_html (value, trans, other_values={})
get_html_field (trans=None, value=None, other_values={})
get_initial_value (trans, context, history=None)
to_dict (trans, view='collection', value_mapper=None, other_values=None)
to_param_dict_string (value, other_values={})
to_python (value, app, other_values={}, validate=False)
to_string (value, app)
```

```
class galaxy.tools.parameters.basic.RuntimeValue
Bases: object
```

Wrapper to note a value that is not yet set, but will be required at runtime.

```
class galaxy.tools.parameters.basic.SelectToolParameter (tool, input_source, context=None)
```

Bases: *galaxy.tools.parameters.basic.ToolParameter*

Parameter that takes on one (or many) or a specific set of values.

```
>>> p = SelectToolParameter( None, XML(
...     '''
...     <param name="blah" type="select">
...         <option value="x">I am X</option>
...         <option value="y" selected="true">I am Y</option>
...         <option value="z">I am Z</option>
...     </param>
...     ''' ) )
>>> print p.name
blah
>>> print p.get_html()
<select name="blah" last_selected_value="y">
<option value="x">I am X</option>
<option value="y" selected>I am Y</option>
<option value="z">I am Z</option>
</select>
>>> print p.get_html( value="z" )
<select name="blah" last_selected_value="z">
<option value="x">I am X</option>
```

```

<option value="y">I am Y</option>
<option value="z" selected>I am Z</option>
</select>
>>> print p.filter_value( "y" )
y

```

```

>>> p = SelectToolParameter( None, XML(
...     '''
...     <param name="blah" type="select" multiple="true">
...         <option value="x">I am X</option>
...         <option value="y" selected="true">I am Y</option>
...         <option value="z" selected="true">I am Z</option>
...     </param>
...     ''' ) )
>>> print p.name
blah
>>> print p.get_html()
<select name="blah" multiple last_selected_value="z">
<option value="x">I am X</option>
<option value="y" selected>I am Y</option>
<option value="z" selected>I am Z</option>
</select>
>>> print p.get_html( value=["x","y"])
<select name="blah" multiple last_selected_value="y">
<option value="x" selected>I am X</option>
<option value="y" selected>I am Y</option>
<option value="z">I am Z</option>
</select>
>>> print p.to_param_dict_string( ["y", "z"] )
y,z

```

```

>>> p = SelectToolParameter( None, XML(
...     '''
...     <param name="blah" type="select" multiple="true" display="checkboxes">
...         <option value="x">I am X</option>
...         <option value="y" selected="true">I am Y</option>
...         <option value="z" selected="true">I am Z</option>
...     </param>
...     ''' ) )
>>> print p.name
blah
>>> print p.get_html()
<div class="checkUncheckAllPlaceholder" checkbox_name="blah"></div>
<div><input type="checkbox" name="blah" value="x" id="blah|x"><label class="inline" for="blah|x">
<div class="odd_row"><input type="checkbox" name="blah" value="y" id="blah|y" checked='checked'>
<div><input type="checkbox" name="blah" value="z" id="blah|z" checked='checked'><label class="inline" for="blah|z">
>>> print p.get_html( value=["x","y"])
<div class="checkUncheckAllPlaceholder" checkbox_name="blah"></div>
<div><input type="checkbox" name="blah" value="x" id="blah|x" checked='checked'><label class="inline" for="blah|x">
<div class="odd_row"><input type="checkbox" name="blah" value="y" id="blah|y" checked='checked'>
<div><input type="checkbox" name="blah" value="z" id="blah|z"><label class="inline" for="blah|z">
>>> print p.to_param_dict_string( ["y", "z"] )
y,z

```

from_html (value, trans=None, context={})

```

get_dependencies ()
    Get the names of the other params this param depends on.

get_html_field (trans=None, value=None, context={})

get_initial_value (trans, context, history=None)

get_legal_values (trans, other_values)

get_options (trans, other_values)

to_dict (trans, view='collection', value_mapper=None, other_values={})

to_html_value (value, app)

to_param_dict_string (value, other_values={}, value_map=<function <lambda>>>)

value_from_basic (value, app, ignore_errors=False)

value_to_basic (value, app)

value_to_display_text (value, app)

```

class galaxy.tools.parameters.basic.**TextToolParameter** (tool, input_source)

Bases: *galaxy.tools.parameters.basic.ToolParameter*

Parameter that can take on any text value.

```

>>> p = TextToolParameter( None, XML( '<param name="blah" type="text" size="4" value="default" /
>>> print p.name
blah
>>> print p.get_html()
<input type="text" name="blah" size="4" value="default">
>>> print p.get_html( value="meh" )
<input type="text" name="blah" size="4" value="meh">

```

```

get_html_field (trans=None, value=None, other_values={})

get_initial_value (trans, context, history=None)

to_dict (trans, view='collection', value_mapper=None, other_values={})

to_html_value (value, app)

to_string (value, app)

```

Convert a value to a string representation suitable for persisting

class galaxy.tools.parameters.basic.**ToolParameter** (tool, input_source, context=None)

Bases: object, *galaxy.model.item_attrs.Dictifiable*

Describes a parameter accepted by a tool. This is just a simple stub at the moment but in the future should encapsulate more complex parameters (lists of valid choices, validation logic, ...)

classmethod **build** (tool, param)

Factory method to create parameter of correct type

dict_collection_visible_keys = ('name', 'argument', 'type', 'label', 'help')

filter_value (value, trans=None, other_values={})

Parse the value returned by the view into a form usable by the tool OR raise a ValueError.

from_html (value, trans=None, other_values={})

Convert a value from an HTML POST into the parameters preferred value format.

from_json (value, trans=None, other_values={})

get_dependencies ()

Return the names of any other parameters this parameter depends on

get_html (*trans=None, value=None, other_values={}*)

Returns the html widget corresponding to the parameter. Optionally attempt to retain the current value specific by 'value'

get_html_field (*trans=None, value=None, other_values={}*)

get_initial_value (*trans, context, history=None*)

Return the starting value of the parameter

get_initial_value_from_history_prevent_repeats (*trans, context, already_used, history=None*)

Get the starting value for the parameter, but if fetching from the history, try to find a value that has not yet been used. *already_used* is a list of objects that tools must manipulate (by adding to it) to store a memento that they can use to detect if a value has already been chosen from the history. This is to support the capability to choose each dataset once

get_label ()

Return user friendly name for the parameter

get_required_encoding ()

If this parameter needs the form to have a specific encoding return it, otherwise return None (indicating compatibility with any encoding)

classmethod parse_name (*input_source*)

to_dict (*trans, view='collection', value_mapper=None, other_values={}*)

to_dict tool parameter. This can be overridden by subclasses.

to_html_value (*value, app*)

Convert an object value to the value expected from an html post

to_param_dict_string (*value, other_values={}*)

Called via `__str__` when used in the Cheetah template

to_python (*value, app*)

Convert a value created with `to_string` back to an object representation

to_string (*value, app*)

Convert a value to a string representation suitable for persisting

validate (*value, history=None*)

value_from_basic (*value, app, ignore_errors=False*)

value_to_basic (*value, app*)

value_to_display_text (*value, app*)

Convert a value to a text representation suitable for displaying to the user

visible

Return true if the parameter should be rendered on the form

class `galaxy.tools.parameters.basic.UnvalidatedValue` (*value*)

Bases: `object`

Wrapper to mark a value that has not been validated

dynamic_options Module Support for generating the options for a `SelectToolParameter` dynamically (based on the values of other parameters or other aspects of the current state)

```

class galaxy.tools.parameters.dynamic_options.AdditionalValueFilter (d_option,
                                                                    elem)
    Bases: galaxy.tools.parameters.dynamic_options.Filter
    Adds a single static value to an options list.
    Type: add_value
    Required Attributes: value: value to appear in select list
    Optional Attributes: name: Display name to appear in select list (value) index: Index of option list to add
        value (APPEND)
    filter_options (options, trans, other_values)

class galaxy.tools.parameters.dynamic_options.AttributeValueSplitterFilter (d_option,
                                                                    elem)
    Bases: galaxy.tools.parameters.dynamic_options.Filter
    Filters a list of attribute-value pairs to be unique attribute names.
    Type: attribute_value_splitter
    Required Attributes: column: column in options to compare with
    Optional Attributes: pair_separator: Split column by this (,) name_val_separator: Split name-value pair by
        this ( whitespace )
    filter_options (options, trans, other_values)

class galaxy.tools.parameters.dynamic_options.DataMetaFilter (d_option, elem)
    Bases: galaxy.tools.parameters.dynamic_options.Filter
    Filters a list of options on a column by a dataset metadata value.
    Type: data_meta

    When no 'from' source has been specified in the <options> tag, this will populate the options list with
    (meta_value, meta_value, False). Otherwise, options which do not match the metadata value in the column
    are discarded.

    Required Attributes:
    •ref: Name of input dataset
    •key: Metadata key to use for comparison
    •column: column in options to compare with (not required when not associated with input options)
    Optional Attributes:
    •multiple: Option values are multiple, split column by separator (True)
    •separator: When multiple split by this (,)
    filter_options (options, trans, other_values)
    get_dependency_name ()

class galaxy.tools.parameters.dynamic_options.DynamicOptions (elem, tool_param)
    Bases: object
    Handles dynamically generated SelectToolParameter options

    column_spec_to_index (column_spec)
        Convert a column specification (as read from the config file), to an index. A column specification can just
        be a number, a column name, or a column alias.

    get_dependency_names ()
        Return the names of parameters these options depend on – both data and other param types.

    get_field_by_name_for_value (field_name, value, trans, other_values)
        Get contents of field by name for specified value.

    get_fields (trans, other_values)

```

get_fields_by_value (*value, trans, other_values*)
Return a list of fields with column 'value' matching provided value.

get_options (*trans, other_values*)

parse_column_definitions (*elem*)

parse_file_fields (*reader*)

class `galaxy.tools.parameters.dynamic_options.Filter` (*d_option, elem*)

Bases: `object`

A filter takes the current options list and modifies it.

filter_options (*options, trans, other_values*)
Returns a list of options after the filter is applied

classmethod from_element (*d_option, elem*)
Loads the proper filter by the type attribute of elem

get_dependency_name ()
Returns the name of any dependencies, otherwise None

class `galaxy.tools.parameters.dynamic_options.MultipleSplitterFilter` (*d_option, elem*)

Bases: `galaxy.tools.parameters.dynamic_options.Filter`

Turns a single line of options into multiple lines, by splitting a column and creating a line for each item.

Type: `multiple_splitter`

Required Attributes: column: column in options to compare with

Optional Attributes: separator: Split column by this (,)

filter_options (*options, trans, other_values*)

class `galaxy.tools.parameters.dynamic_options.ParamValueFilter` (*d_option, elem*)

Bases: `galaxy.tools.parameters.dynamic_options.Filter`

Filters a list of options on a column by the value of another input.

Type: `param_value`

Required Attributes:

- ref:** Name of input value
- column:** column in options to compare with

Optional Attributes:

- keep: Keep columns matching value (True)** Discard columns matching value (False)
- ref_attribute:** Period (.) separated attribute chain of input (ref) to use as value for filter

filter_options (*options, trans, other_values*)

get_dependency_name ()

class `galaxy.tools.parameters.dynamic_options.RemoveValueFilter` (*d_option, elem*)

Bases: `galaxy.tools.parameters.dynamic_options.Filter`

Removes a value from an options list.

Type: `remove_value`

Required Attributes:

value: value to remove from select list
or
ref: param to refer to
or

```
meta_ref: dataset to refer to
key: metadata key to compare to
```

filter_options (*options, trans, other_values*)

class galaxy.tools.parameters.dynamic_options.**SortByColumnFilter** (*d_option, elem*)

Bases: *galaxy.tools.parameters.dynamic_options.Filter*

Sorts an options list by a column

Type: sort_by

Required Attributes: column: column to sort by

filter_options (*options, trans, other_values*)

class galaxy.tools.parameters.dynamic_options.**StaticValueFilter** (*d_option, elem*)

Bases: *galaxy.tools.parameters.dynamic_options.Filter*

Filters a list of options on a column by a static value.

Type: static_value

Required Attributes: value: static value to compare to column: column in options to compare with

Optional Attributes:

keep: Keep columns matching value (True) Discard columns matching value (False)

filter_options (*options, trans, other_values*)

class galaxy.tools.parameters.dynamic_options.**UniqueValueFilter** (*d_option, elem*)

Bases: *galaxy.tools.parameters.dynamic_options.Filter*

Filters a list of options to be unique by a column value.

Type: unique_value

Required Attributes: column: column in options to compare with

filter_options (*options, trans, other_values*)

get_dependency_name ()

grouping Module Constructs for grouping tool parameters

class galaxy.tools.parameters.grouping.**Conditional**

Bases: *galaxy.tools.parameters.grouping.Group*

get_current_case (*value, trans*)

get_initial_value (*trans, context, history=None*)

is_job_resource_conditional

label

to_dict (*trans, view='collection', value_mapper=None*)

type = 'conditional'

value_from_basic (*value, app, ignore_errors=False*)

value_to_basic (*value, app*)

visit_inputs (*prefix, value, callback*)

class galaxy.tools.parameters.grouping.**ConditionalWhen**

Bases: object, *galaxy.model.item_attrs.Dictifiable*

dict_collection_visible_keys = ('value',)

```
    to_dict (trans, view='collection', value_mapper=None)

class galaxy.tools.parameters.grouping.Group
    Bases: object, galaxy.model.item_attrs.Dictifiable

    dict_collection_visible_keys = ('name', 'type')

    get_initial_value (trans, context, history=None)
        Return the initial state/value for this group

    to_dict (trans, view='collection', value_mapper=None)

    value_from_basic (value, app, ignore_errors=False)
        Convert a basic representation as produced by value_to_basic back into the preferred value form.

    value_to_basic (value, app)
        Convert value to a (possibly nested) representation using only basic types (dict, list, tuple, str, unicode,
        int, long, float, bool, None)

    visible

class galaxy.tools.parameters.grouping.Repeat
    Bases: galaxy.tools.parameters.grouping.Group

    dict_collection_visible_keys = ('name', 'type', 'title', 'help', 'default', 'min', 'max')

    get_initial_value (trans, context, history=None)

    label ()

    title_plural

    to_dict (trans, view='collection', value_mapper=None)

    type = 'repeat'

    value_from_basic (value, app, ignore_errors=False)

    value_to_basic (value, app)

    visit_inputs (prefix, value, callback)

class galaxy.tools.parameters.grouping.Section
    Bases: galaxy.tools.parameters.grouping.Group

    dict_collection_visible_keys = ('name', 'type', 'title', 'help', 'expanded')

    get_initial_value (trans, context, history=None)

    label ()

    title_plural

    to_dict (trans, view='collection', value_mapper=None)

    type = 'section'

    value_from_basic (value, app, ignore_errors=False)

    value_to_basic (value, app)

    visit_inputs (prefix, value, callback)

class galaxy.tools.parameters.grouping.UploadDataset
    Bases: galaxy.tools.parameters.grouping.Group

    get_composite_dataset_name (context)

    get_datatype (trans, context)
```



```

get_datatype_ext (trans, context)
get_file_base_name (context)
get_file_type (context)
get_initial_value (trans, context, history=None)
get_uploaded_datasets (trans, context, override_name=None, override_info=None)
group_title (context)
title_by_index (trans, index, context)
title_plural
type = 'upload_dataset'
value_from_basic (value, app, ignore_errors=False)
value_to_basic (value, app)
visit_inputs (prefix, value, callback)

```

input_translation Module Tool Input Translation.

class galaxy.tools.parameters.input_translation.**ToolInputTranslator**

Bases: object

Handles Tool input translation. This is used for data source tools

```

>>> from galaxy.util import Params
>>> from xml.etree.ElementTree import XML
>>> translator = ToolInputTranslator.from_element( XML(
...     '''
...     <request_param_translation>
...     <request_param galaxy_name="URL_method" remote_name="URL_method" missing="post" />
...     <request_param galaxy_name="URL" remote_name="URL" missing="" >
...         <append_param separator="&" first_separator="?" join="=">
...             <value name="_export" missing="1" />
...             <value name="GALAXY_URL" missing="0" />
...         </append_param>
...     </request_param>
...     <request_param galaxy_name="dbkey" remote_name="db" missing="?" />
...     <request_param galaxy_name="organism" remote_name="org" missing="unknown species" />
...     <request_param galaxy_name="table" remote_name="hgta_table" missing="unknown table" />
...     <request_param galaxy_name="description" remote_name="hgta_regionType" missing="no description" />
...     <request_param galaxy_name="data_type" remote_name="hgta_outputType" missing="tabular" >
...         <value_translation>
...             <value galaxy_value="tabular" remote_value="primaryTable" />
...             <value galaxy_value="tabular" remote_value="selectedFields" />
...             <value galaxy_value="wig" remote_value="wigData" />
...             <value galaxy_value="interval" remote_value="tab" />
...             <value galaxy_value="html" remote_value="hyperlinks" />
...             <value galaxy_value="fasta" remote_value="sequence" />
...         </value_translation>
...     </request_param>
... </request_param_translation>
...     ''' ) )
>>> params = Params( { 'db':'hg17', 'URL':'URL_value', 'org':'Human', 'hgta_outputType':'primaryTable' } )
>>> translator.translate( params )
>>> print sorted(list(params.__dict__.keys()))

```

```
[ 'URL', 'URL_method', 'data_type', 'db', 'dbkey', 'description', 'hgta_outputType', 'org', 'orga
>>> params.get('URL', None) in ['URL_value?GALAXY_URL=0&_export=1', 'URL_value?_export=1&GALAXY_
True
```

classmethod from_element (*elem*)

Loads the proper filter by the type attribute of elem

translate (*params*)

update params in-place

output Module Support for dynamically modifying output attributes.

class `galaxy.tools.parameters.output.BooleanFilter` (*parent, elem*)

Bases: `galaxy.tools.parameters.output.ToolOutputActionOptionFilter`

filter_options (*options, other_values*)

tag = 'boolean'

class `galaxy.tools.parameters.output.ColumnReplaceFilter` (*parent, elem*)

Bases: `galaxy.tools.parameters.output.ToolOutputActionOptionFilter`

filter_options (*options, other_values*)

tag = 'column_replace'

class `galaxy.tools.parameters.output.ColumnStripFilter` (*parent, elem*)

Bases: `galaxy.tools.parameters.output.ToolOutputActionOptionFilter`

filter_options (*options, other_values*)

tag = 'column_strip'

class `galaxy.tools.parameters.output.DatatypeIsInstanceToolOutputActionConditionalWhen` (*parent, con-fig_elem, value*)

Bases: `galaxy.tools.parameters.output.ToolOutputActionConditionalWhen`

is_case (*output_dataset, other_values*)

tag = 'when datatype_isinstance'

class `galaxy.tools.parameters.output.FormatToolOutputAction` (*parent, elem*)

Bases: `galaxy.tools.parameters.output.ToolOutputAction`

apply_action (*output_dataset, other_values*)

tag = 'format'

class `galaxy.tools.parameters.output.FromDataTableOutputActionOption` (*parent, elem*)

Bases: `galaxy.tools.parameters.output.ToolOutputActionOption`

get_value (*other_values*)

tag = 'from_data_table'

class `galaxy.tools.parameters.output.FromFileToolOutputActionOption` (*parent, elem*)

Bases: `galaxy.tools.parameters.output.ToolOutputActionOption`

get_value (*other_values*)

tag = 'from_file'

```

class galaxy.tools.parameters.output.FromParamToolOutputActionOption (parent,
                                                                    elem)
    Bases: galaxy.tools.parameters.output.ToolOutputActionOption
    get_value (other_values)
    tag = 'from_param'

class galaxy.tools.parameters.output.InsertColumnToolOutputActionOptionFilter (parent,
                                                                    elem)
    Bases: galaxy.tools.parameters.output.ToolOutputActionOptionFilter
    filter_options (options, other_values)
    tag = 'insert_column'

class galaxy.tools.parameters.output.MetadataToolOutputAction (parent, elem)
    Bases: galaxy.tools.parameters.output.ToolOutputAction
    apply_action (output_dataset, other_values)
    tag = 'metadata'

class galaxy.tools.parameters.output.MetadataValueFilter (parent, elem)
    Bases: galaxy.tools.parameters.output.ToolOutputActionOptionFilter
    filter_options (options, other_values)
    tag = 'metadata_value'

class galaxy.tools.parameters.output.MultipleSplitterFilter (parent, elem)
    Bases: galaxy.tools.parameters.output.ToolOutputActionOptionFilter
    filter_options (options, other_values)
    tag = 'multiple_splitter'

class galaxy.tools.parameters.output.NullToolOutputActionOption (parent, elem)
    Bases: galaxy.tools.parameters.output.ToolOutputActionOption
    get_value (other_values)
    tag = 'null_option'

class galaxy.tools.parameters.output.ParamValueToolOutputActionOptionFilter (parent,
                                                                    elem)
    Bases: galaxy.tools.parameters.output.ToolOutputActionOptionFilter
    filter_options (options, other_values)
    tag = 'param_value'

class galaxy.tools.parameters.output.StringFunctionFilter (parent, elem)
    Bases: galaxy.tools.parameters.output.ToolOutputActionOptionFilter
    filter_options (options, other_values)
    tag = 'string_function'

class galaxy.tools.parameters.output.ToolOutputAction (parent, elem)
    Bases: object
    apply_action (output_dataset, other_values)
    classmethod from_elem (parent, elem)
        Loads the proper action by the type attribute of elem
    tag = 'action'

```

tool

```
class galaxy.tools.parameters.output.ToolOutputActionConditional (parent,      con-  
                                                                fig_elem)
```

Bases: object

apply_action (output_dataset, other_values)

tag = 'conditional'

tool

```
class galaxy.tools.parameters.output.ToolOutputActionConditionalWhen (parent,  
                                                                con-  
                                                                fig_elem,  
                                                                value)
```

Bases: *galaxy.tools.parameters.output.ToolOutputActionGroup*

apply_action (output_dataset, other_values)

classmethod from_elem (parent, when_elem)

Loads the proper when by attributes of elem

get_ref (output_dataset, other_values)

is_case (output_dataset, other_values)

tag = 'when'

```
class galaxy.tools.parameters.output.ToolOutputActionGroup (parent, config_elem)  
Bases: object
```

Manages a set of tool output dataset actions directives

apply_action (output_dataset, other_values)

tag = 'group'

tool

```
class galaxy.tools.parameters.output.ToolOutputActionOption (parent, elem)  
Bases: object
```

classmethod from_elem (parent, elem)

Loads the proper action by the type attribute of elem

get_value (other_values)

tag = 'object'

tool

```
class galaxy.tools.parameters.output.ToolOutputActionOptionFilter (parent, elem)  
Bases: object
```

filter_options (options, other_values)

classmethod from_elem (parent, elem)

Loads the proper action by the type attribute of elem

tag = 'filter'

tool

```

class galaxy.tools.parameters.output.ValueToolOutputActionConditionalWhen (parent,
                                                                    con-
                                                                    fig_elem,
                                                                    value)

    Bases: galaxy.tools.parameters.output.ToolOutputActionConditionalWhen

    is_case (output_dataset, other_values)

    tag = 'when value'

galaxy.tools.parameters.output.action_type
    alias of FormatToolOutputAction

galaxy.tools.parameters.output.compare_endswith (value1, value2)
galaxy.tools.parameters.output.compare_eq (value1, value2)
galaxy.tools.parameters.output.compare_gt (value1, value2)
galaxy.tools.parameters.output.compare_gte (value1, value2)
galaxy.tools.parameters.output.compare_in (value1, value2)
galaxy.tools.parameters.output.compare_lt (value1, value2)
galaxy.tools.parameters.output.compare_lte (value1, value2)
galaxy.tools.parameters.output.compare_neq (value1, value2)
galaxy.tools.parameters.output.compare_re_search (value1, value2)
galaxy.tools.parameters.output.compare_startswith (value1, value2)
galaxy.tools.parameters.output.filter_type
    alias of ColumnReplaceFilter

galaxy.tools.parameters.output.option_type
    alias of FromDataTableOutputActionOption

galaxy.tools.parameters.output.parse_cast_attribute (cast)
galaxy.tools.parameters.output.parse_compare_type (compare)

```

sanitize Module Tool Parameter specific sanitizing.

```
class galaxy.tools.parameters.sanitize.ToolParameterSanitizer
```

Bases: object

Handles tool parameter specific sanitizing.

```

>>> from xml.etree.ElementTree import XML
>>> sanitizer = ToolParameterSanitizer.from_element( XML(
...     '''
...     <sanitizer invalid_char="">
...     <valid initial="string.letters"/>
...     </sanitizer>
...     ''' ) )
>>> sanitizer.sanitize_param( ''.join( sorted( [ c for c in string.printable ] ) ) ) == ''.join(
True
>>> slash = chr( 92 )
>>> sanitizer = ToolParameterSanitizer.from_element( XML(
...     '''
...     <sanitizer>
...     <valid initial="none">

```

```
...     <add preset="string.printable"/>
...     <remove value="&quot;"/>
...     <remove value="%s"/>
... </valid>
... <mapping initial="none">
...     <add source="&quot;" target="%s&quot;"/>
...     <add source="%s" target="%s%s"/>
... </mapping>
... </sanitizer>
... ''' % ( slash, slash, slash, slash, slash ) )
>>> text = '%s"%$rm&#!' % slash
>>> [ c for c in sanitizer.sanitize_param( text ) ] == [ slash, slash, slash, '!', '$', 'r', 'm' ]
True
```

```
DEFAULT_INVALID_CHAR = 'X'
```

```
MAPPING_PRESET = {'default': {'@': '__at__', '\t': '__tc__', '\n': '__cn__', '\r': '__cr__', '[': '__ob__', ']': '__cb__', '#'}
```

```
VALID_PRESET = {'default': 'ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789 -_.()
```

classmethod **from_element** (*elem*)

Loads the proper filter by the type attribute of elem

```
classmethod get_mapping_by_name (name)
```

```
classmethod get_valid_by_name (name)
```

```
restore_param(value)
```

```
restore_text (text)
```

Restores sanitized text

sanitize_param (*value*)

Clean incoming parameters (strings or lists)

```
sanitize_text(text)
```

Restricts the characters that are allowed in a text

validation Module Classes related to parameter validation.

```
class galaxy.tools.parameters.validation.DatasetOkValidator (message=None)
```

Bases: `galaxy.tools.parameters.validation.Validator`

Validator that checks if a dataset is in an 'ok' state

classmethod **from_element** (*param*, *elem*)**validate** (*value*, *history=None*)

```
class galaxy.tools.parameters.validation.EmptyTextfieldValidator (message=None)
```

Bases: `galaxy.tools.parameters.validation.Validator`

Validator that checks for empty text field

classmethod **from_element** (*param, elem*)**validate** (*value*, *history=None*)[illegible]

Bases: `galaxy.tools.parameters.validation.Validator`

Validator that evaluates a python expression using the value

```

>>> from xml.etree.ElementTree import XML
>>> from galaxy.tools.parameters.basic import ToolParameter
>>> p = ToolParameter.build( None, XML( '''
... <param name="blah" type="text" size="10" value="10">
...   <validator type="expression" message="Not gonna happen">value.lower() == "foo"</validator>
... </param>
... ''' ) )
>>> t = p.validate( "Foo" )
>>> t = p.validate( "foo" )
>>> t = p.validate( "Fop" )
Traceback (most recent call last):
...
ValueError: Not gonna happen

```

classmethod `from_element` (*param, elem*)

validate (*value, history=None*)

class `galaxy.tools.parameters.validation.InRangeValidator` (*message, range_min, range_max, exclude_min=False, exclude_max=False*)

Bases: `galaxy.tools.parameters.validation.Validator`

Validator that ensures a number is in a specific range

```

>>> from xml.etree.ElementTree import XML
>>> from galaxy.tools.parameters.basic import ToolParameter
>>> p = ToolParameter.build( None, XML( '''
... <param name="blah" type="integer" size="10" value="10">
...   <validator type="in_range" message="Not gonna happen" min="10" exclude_min="true" max="20">
... </param>
... ''' ) )
>>> t = p.validate( 10 )
Traceback (most recent call last):
...
ValueError: Not gonna happen
>>> t = p.validate( 15 )
>>> t = p.validate( 20 )
>>> t = p.validate( 21 )
Traceback (most recent call last):
...
ValueError: Not gonna happen

```

classmethod `from_element` (*param, elem*)

validate (*value, history=None*)

exception `galaxy.tools.parameters.validation.LateValidationError` (*message*)

Bases: `exceptions.Exception`

class `galaxy.tools.parameters.validation.LengthValidator` (*message, length_min, length_max*)

Bases: `galaxy.tools.parameters.validation.Validator`

Validator that ensures the length of the provided string (value) is in a specific range

```

>>> from xml.etree.ElementTree import XML
>>> from galaxy.tools.parameters.basic import ToolParameter

```

```

>>> p = ToolParameter.build( None, XML( '''
... <param name="blah" type="text" size="10" value="foobar">
...     <validator type="length" min="2" max="8"/>
... </param>
... ''' ) )
>>> t = p.validate( "foo" )
>>> t = p.validate( "bar" )
>>> t = p.validate( "f" )
Traceback (most recent call last):
...
ValueError: Must have length of at least 2
>>> t = p.validate( "foobarbaz" )
Traceback (most recent call last):
...
ValueError: Must have length no more than 8

```

classmethod `from_element` (*param, elem*)

validate (*value, history=None*)

```

class galaxy.tools.parameters.validation.MetadataInDataTableColumnValidator(tool_data_table,
                                                                           meta-
                                                                           data_name,
                                                                           meta-
                                                                           data_column,
                                                                           mes-
                                                                           sage='Value
                                                                           for
                                                                           meta-
                                                                           data
                                                                           not
                                                                           found.',
                                                                           line_startswith=None)

```

Bases: `galaxy.tools.parameters.validation.Validator`

Validator that checks if the value for a dataset's metadata item exists in a file.

classmethod `from_element` (*param, elem*)

validate (*value, history=None*)

```

class galaxy.tools.parameters.validation.MetadataInFileColumnValidator(filename,
                                                                           meta-
                                                                           data_name,
                                                                           meta-
                                                                           data_column,
                                                                           mes-
                                                                           sage='Value
                                                                           for
                                                                           meta-
                                                                           data
                                                                           not
                                                                           found.',
                                                                           line_startswith=None)

```

Bases: `galaxy.tools.parameters.validation.Validator`

Validator that checks if the value for a dataset's metadata item exists in a file.

classmethod `from_element` (*param, elem*)

validate (*value*, *history*=None)

class galaxy.tools.parameters.validation.**MetadataValidator** (*message*=None,
check='', skip='')
Bases: *galaxy.tools.parameters.validation.Validator*

Validator that checks for missing metadata

classmethod **from_element** (*param*, *elem*)

validate (*value*, *history*=None)

class galaxy.tools.parameters.validation.**NoOptionsValidator** (*message*=None)
Bases: *galaxy.tools.parameters.validation.Validator*

Validator that checks for empty select list

classmethod **from_element** (*param*, *elem*)

validate (*value*, *history*=None)

class galaxy.tools.parameters.validation.**RegexValidator** (*message*, *expression*)
Bases: *galaxy.tools.parameters.validation.Validator*

Validator that evaluates a regular expression

```
>>> from xml.etree.ElementTree import XML
>>> from galaxy.tools.parameters.basic import ToolParameter
>>> p = ToolParameter.build( None, XML( '''
... <param name="blah" type="text" size="10" value="10">
...   <validator type="regex" message="Not gonna happen">[Ff]oo</validator>
... </param>
... ''' ) )
>>> t = p.validate( "Foo" )
>>> t = p.validate( "foo" )
>>> t = p.validate( "Fop" )
Traceback (most recent call last):
...
ValueError: Not gonna happen
```

classmethod **from_element** (*param*, *elem*)

validate (*value*, *history*=None)

class galaxy.tools.parameters.validation.**UnspecifiedBuildValidator** (*message*=None)
Bases: *galaxy.tools.parameters.validation.Validator*

Validator that checks for dbkey not equal to '?'

classmethod **from_element** (*param*, *elem*)

validate (*value*, *history*=None)

class galaxy.tools.parameters.validation.**Validator**
Bases: object

A validator checks that a value meets some conditions OR raises ValueError

classmethod **from_element** (*param*, *elem*)

validate (*value*, *history*=None)

galaxy.tools.parameters.validation.**get_suite** ()
Get unittest suite for this module

search Package

search Package Module for building and searching the index of tools installed within this Galaxy.

```
class galaxy.tools.search.ToolBoxSearch(toolbox, index_help=True)
```

Bases: object

Support searching tools in a toolbox. This implementation uses the Whoosh search library.

```
build_index(index_help=True)
```

```
search(q, tool_name_boost, tool_section_boost, tool_description_boost, tool_help_boost,
        tool_search_limit)
```

Perform search on the in-memory index. Weight in the given boosts.

util Package

util Package Utilities used by various Galaxy tools

FIXME: These are used by tool scripts, not the framework, and should not live in this package.

maf_utilities Module Provides wrappers and utilities for working with MAF files and alignments.

```
class galaxy.tools.util.maf_utilities.GenomicRegionAlignment(start, end, species=[],
                                                             temp_file_handler=None)
```

Bases: *galaxy.tools.util.maf_utilities.RegionAlignment*

```
class galaxy.tools.util.maf_utilities.RegionAlignment(size, species=[],
                                                       temp_file_handler=None)
```

Bases: object

```
DNA_COMPLEMENT = '\x00\x01\x02\x03\x04\x05\x06\x07\x08\t\n\x0b\x0c\r\x0e\x0f\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\x1f\x20\x21\x22\x23\x24\x25\x26\x27\x28\x29\x2a\x2b\x2c\x2d\x2e\x2f\x30\x31\x32\x33\x34\x35\x36\x37\x38\x39\x3a\x3b\x3c\x3d\x3e\x3f\x40\x41\x42\x43\x44\x45\x46\x47\x48\x49\x4a\x4b\x4c\x4d\x4e\x4f\x50\x51\x52\x53\x54\x55\x56\x57\x58\x59\x5a\x5b\x5c\x5d\x5e\x5f\x60\x61\x62\x63\x64\x65\x66\x67\x68\x69\x6a\x6b\x6c\x6d\x6e\x6f\x70\x71\x72\x73\x74\x75\x76\x77\x78\x79\x7a\x7b\x7c\x7d\x7e\x7f\x80\x81\x82\x83\x84\x85\x86\x87\x88\x89\x8a\x8b\x8c\x8d\x8e\x8f\x90\x91\x92\x93\x94\x95\x96\x97\x98\x99\x9a\x9b\x9c\x9d\x9e\x9f\xa0\xa1\xa2\xa3\xa4\xa5\xa6\xa7\xa8\xa9\xaa\xab\xac\xad\xae\xaf\xb0\xb1\xb2\xb3\xb4\xb5\xb6\xb7\xb8\xb9\xba\xbb\xbc\xbd\xbe\xbf\xc0\xc1\xc2\xc3\xc4\xc5\xc6\xc7\xc8\xc9\xca\xcb\xcc\xcd\xce\xcf\x1000'
```

```
MAX_SEQUENCE_SIZE = 9223372036854775807
```

```
add_species(species)
```

```
flush(species=None)
```

```
get_sequence(species)
```

```
get_sequence_reverse_complement(species)
```

```
get_species_names(skip=[])
```

```
set_position(index, species, base)
```

```
set_range(index, species, bases)
```

```
class galaxy.tools.util.maf_utilities.SplicedAlignment(exon_starts, exon_ends, species=[],
                                                         temp_file_handler=None)
```

Bases: object

```
DNA_COMPLEMENT = '\x00\x01\x02\x03\x04\x05\x06\x07\x08\t\n\x0b\x0c\r\x0e\x0f\x10\x11\x12\x13\x14\x15\x16\x17\x18\x19\x1a\x1b\x1c\x1d\x1e\x1f\x20\x21\x22\x23\x24\x25\x26\x27\x28\x29\x2a\x2b\x2c\x2d\x2e\x2f\x30\x31\x32\x33\x34\x35\x36\x37\x38\x39\x3a\x3b\x3c\x3d\x3e\x3f\x40\x41\x42\x43\x44\x45\x46\x47\x48\x49\x4a\x4b\x4c\x4d\x4e\x4f\x50\x51\x52\x53\x54\x55\x56\x57\x58\x59\x5a\x5b\x5c\x5d\x5e\x5f\x60\x61\x62\x63\x64\x65\x66\x67\x68\x69\x6a\x6b\x6c\x6d\x6e\x6f\x70\x71\x72\x73\x74\x75\x76\x77\x78\x79\x7a\x7b\x7c\x7d\x7e\x7f\x80\x81\x82\x83\x84\x85\x86\x87\x88\x89\x8a\x8b\x8c\x8d\x8e\x8f\x90\x91\x92\x93\x94\x95\x96\x97\x98\x99\x9a\x9b\x9c\x9d\x9e\x9f\xa0\xa1\xa2\xa3\xa4\xa5\xa6\xa7\xa8\xa9\xaa\xab\xac\xad\xae\xaf\xb0\xb1\xb2\xb3\xb4\xb5\xb6\xb7\xb8\xb9\xba\xbb\xbc\xbd\xbe\xbf\xc0\xc1\xc2\xc3\xc4\xc5\xc6\xc7\xc8\xc9\xca\xcb\xcc\xcd\xce\xcf\x1000'
```

```
end
```

```
get_sequence(species)
```

```
get_sequence_reverse_complement(species)
```

```
get_species_names(skip=[])
```

start

class galaxy.tools.util.maf_utilities.**TempFileHandler** (*max_open_files=None, **kws*)
 Bases: object

Handles creating, opening, closing, and deleting of Temp files, with a maximum number of files open at one time.

DEFAULT_MAX_OPEN_FILES = 512

close (*index, delete=False*)

flush (*index*)

get_open_tempfile (*index=None, **kws*)

galaxy.tools.util.maf_utilities.**build_maf_index** (*maf_file, species=None*)

galaxy.tools.util.maf_utilities.**build_maf_index_species_chromosomes** (*filename, in-
dex_species=None*)

galaxy.tools.util.maf_utilities.**chop_block_by_region** (*block, src, region, species=None, mincols=0*)

galaxy.tools.util.maf_utilities.**component_overlaps_region** (*c, region*)

galaxy.tools.util.maf_utilities.**fill_region_alignment** (*alignment, index, primary_species, chrom, start, end, strand='+', species=None, mincols=0, overwrite_with_gaps=True*)

galaxy.tools.util.maf_utilities.**get_attributes_from_fasta_header** (*header*)

galaxy.tools.util.maf_utilities.**get_chopped_blocks_for_region** (*index, src, region, species=None, mincols=0*)

galaxy.tools.util.maf_utilities.**get_chopped_blocks_with_index_offset_for_region** (*index, src, re-
gion, species=None, min-
cols=0*)

galaxy.tools.util.maf_utilities.**get_components_by_src** (*block, src*)

galaxy.tools.util.maf_utilities.**get_components_by_src_start** (*block, src*)

galaxy.tools.util.maf_utilities.**get_fasta_header** (*component, attributes={}, suffix=None*)

galaxy.tools.util.maf_utilities.**get_oriented_chopped_blocks_for_region** (*index, src, re-
gion, species=None, min-
cols=0, force_strand=None*)

```
galaxy.tools.util.maf_utilities.get_oriented_chopped_blocks_with_index_offset_for_region(in
sn
re
gi
sp
m.
co
fo

galaxy.tools.util.maf_utilities.get_region_alignment(index, primary_species,
chrom, start, end, strand='+',
species=None, mincols=0,
overwrite_with_gaps=True,
temp_file_handler=None)

galaxy.tools.util.maf_utilities.get_species_in_block(block)

galaxy.tools.util.maf_utilities.get_species_in_maf(maf_filename)

galaxy.tools.util.maf_utilities.get_spliced_region_alignment(index, pri-
mary_species,
chrom, starts,
ends, strand='+',
species=None,
mincols=0, over-
write_with_gaps=True,
temp_file_handler=None)

galaxy.tools.util.maf_utilities.get_starts_ends_fields_from_gene_bed(line)

galaxy.tools.util.maf_utilities.iter_blocks_split_by_species(block,
species=None)

galaxy.tools.util.maf_utilities.iter_blocks_split_by_src(block, src)

galaxy.tools.util.maf_utilities.iter_components_by_src(block, src)

galaxy.tools.util.maf_utilities.iter_components_by_src_start(block, src)

galaxy.tools.util.maf_utilities.iter_fasta_alignment(filename)

galaxy.tools.util.maf_utilities.line_enumerator(lines, comment_start='#')

galaxy.tools.util.maf_utilities.maf_index_by_uid(maf_uid, index_location_file)

galaxy.tools.util.maf_utilities.open_or_build_maf_index(maf_file, index_filename,
species=None)

galaxy.tools.util.maf_utilities.orient_block_by_region(block, src, region,
force_strand=None)

galaxy.tools.util.maf_utilities.parse_species_option(species)

galaxy.tools.util.maf_utilities.reduce_block_by_primary_genome(block, species,
chromosome,
region_start)

galaxy.tools.util.maf_utilities.remove_temp_index_file(index_filename)

galaxy.tools.util.maf_utilities.sort_block_components_by_block(block1, block2)

galaxy.tools.util.maf_utilities.src_merge(spec, chrom, contig=None)

galaxy.tools.util.maf_utilities.src_split(src)

galaxy.tools.util.maf_utilities.tool_fail(msg='Unknown Error')
```

Subpackages

galaxyops Package

galaxyops Package Utility functions for galaxyops

`galaxy.tools.util.galaxyops.default_printer` (*stream, exc, obj*)

`galaxy.tools.util.galaxyops.fail` (*msg*)

`galaxy.tools.util.galaxyops.parse_cols_arg` (*cols*)

Parse a columns command line argument into a four-tuple

`galaxy.tools.util.galaxyops.skipped` (*reader, filedesc=''*)

`galaxy.tools.util.galaxyops.warn` (*msg*)

util Package

util Package Utility functions used systemwide.

class `galaxy.util.ExecutionTimer`

Bases: `object`

class `galaxy.util.Params` (*params, sanitize=True*)

Bases: `object`

Stores and ‘sanitizes’ parameters. Alphanumeric characters and the non-alphanumeric ones that are deemed safe are let to pass through (see `L{valid_chars}`). Some non-safe characters are escaped to safe forms for example `C{>}` becomes `C{__lt__}` (see `L{mapped_chars}`). All other characters are replaced with `C{X}`.

Operates on string or list values only (HTTP parameters).

```
>>> values = { 'status':'on', 'symbols':[ 'alpha', '<>', '$rm&#!' ] }
>>> par = Params(values)
>>> par.status
'on'
>>> par.value == None      # missing attributes return None
True
>>> par.get('price', 0)
0
>>> par.symbols            # replaces unknown symbols with X
['alpha', '__lt__gt__', 'XrmX__pd__!']
>>> sorted(par.flatten())  # flattening to a list
[('status', 'on'), ('symbols', 'XrmX__pd__!'), ('symbols', '__lt__gt__'), ('symbols', 'alpha')]
```

NEVER_SANITIZE = ['file_data', 'url_paste', 'URL', 'filesystem_paths']

flatten ()

Creates a tuple list from a dict with a tuple/value pair for every value that is a list

get (*key, default*)

update (*values*)

class `galaxy.util.ParamsWithSpecs` (*specs=None, params=None*)

Bases: `collections.defaultdict`

`galaxy.util.asbool` (*obj*)

`galaxy.util.commaify` (*amount*)

`galaxy.util.compare_urls` (*url1*, *url2*, *compare_scheme=True*, *compare_hostname=True*, *compare_path=True*)

`galaxy.util.docstring_trim` (*docstring*)

Trimming python doc strings. Taken from: <http://www.python.org/dev/peps/pep-0257/>

`galaxy.util.file_iter` (*fname*, *sep=None*)

This generator iterates over a file and yields its lines splitted via the C{sep} parameter. Skips empty lines and lines starting with the C{#} character.

```
>>> lines = [ line for line in file_iter(__file__) ]
>>> len(lines) != 0
True
```

`galaxy.util.file_reader` (*fp*, *chunk_size=65536*)

This generator yields the open fileobject in chunks (default 64k). Closes the file at the end

`galaxy.util.force_symlink` (*source*, *link_name*)

`galaxy.util.galaxy_directory` ()

`galaxy.util.get_charset_from_http_headers` (*headers*, *default=None*)

`galaxy.util.get_file_size` (*value*, *default=None*)

`galaxy.util.in_directory` (*file*, *directory*, *local_path_module=<module 'posixpath' from*

'/home/docs/checkouts/readthedocs.org/user_builds/galaxy/envs/latest/lib/python2.7/posixpath.py'

Return true, if the common prefix of both is equal to directory e.g. /a/b/c/d.rst and directory is /a/b, the common prefix is /a/b

`galaxy.util.is_binary` (*value*, *binary_chars=None*)

File is binary if it contains a null-byte by default (e.g. behavior of grep, etc.). This may fail for utf-16 files, but so would ASCII encoding. >>> is_binary(string.printable) False >>> is_binary('xcex94') False >>> is_binary('000') True

`galaxy.util.is_multi_byte` (*chars*)

`galaxy.util.is_uuid` (*value*)

This method returns True if value is a UUID, otherwise False. >>> is_uuid("123e4567-e89b-12d3-a456-426655440000") True >>> is_uuid("0x3242340298902834") False

`galaxy.util.listify` (*item*, *do_strip=False*)

Make a single item a single item list, or return a list if passed a list. Passing a None returns an empty list.

`galaxy.util.mask_password_from_url` (*url*)

Masks out passwords from connection urls like the database connection in galaxy.ini

```
>>> mask_password_from_url( 'sqlite+postgresql://user:password@localhost/' )
'sqlite+postgresql://user:*****@localhost/'
>>> mask_password_from_url( 'amqp://user:amqp@localhost' )
'amqp://user:*****@localhost'
>>> mask_password_from_url( 'amqp://localhost')
'amqp://localhost'
```

`galaxy.util.merge_sorted_iterables` (*operator*, **iterables*)

```
>>> operator = lambda x: x
>>> list( merge_sorted_iterables( operator, [1,2,3], [4,5] ) )
[1, 2, 3, 4, 5]
>>> list( merge_sorted_iterables( operator, [4, 5], [1,2,3] ) )
[1, 2, 3, 4, 5]
>>> list( merge_sorted_iterables( operator, [1, 4, 5], [2], [3] ) )
[1, 2, 3, 4, 5]
```

`galaxy.util.mkstemp_ln` (*src*, *prefix*=*'mkstemp_ln_'*)

From `tempfile.mkstemp_inner`, generate a hard link in the same dir with a random name. Created so we can persist the underlying file of a `NamedTemporaryFile` upon its closure.

`galaxy.util.move_merge` (*source*, *target*)

`galaxy.util.nice_size` (*size*)

Returns a readably formatted string with the size

```
>>> nice_size(100)
'100 bytes'
>>> nice_size(10000)
'9.8 KB'
>>> nice_size(1000000)
'976.6 KB'
>>> nice_size(100000000)
'95.4 MB'
```

`galaxy.util.object_to_string` (*obj*)

`galaxy.util.parse_xml` (*fname*)

Returns a parsed xml tree

`galaxy.util.parse_xml_string` (*xml_string*)

`galaxy.util.pretty_print_json` (*json_data*, *is_json_string*=*False*)

`galaxy.util.pretty_print_time_interval` (*time*=*False*, *precise*=*False*)

Get a datetime object or a int() Epoch timestamp and return a pretty string like ‘an hour ago’, ‘Yesterday’, ‘3 months ago’, ‘just now’, etc credit: <http://stackoverflow.com/questions/1551382/user-friendly-time-format-in-python>

`galaxy.util.pretty_print_xml` (*elem*, *level*=0)

`galaxy.util.read_build_sites` (*filename*, *check_builds*=*True*)

read db names to ucsc mappings from file, this file should probably be merged with the one above

`galaxy.util.read_dbnames` (*filename*)

Read build names from file

`galaxy.util.ready_name_for_url` (*raw_name*)

General method to convert a string (i.e. object name) to a URL-ready slug.

```
>>> ready_name_for_url( "My Cool Object" )
'My-Cool-Object'
>>> ready_name_for_url( "!My Cool Object!" )
'My-Cool-Object'
>>> ready_name_for_url( "HelloW" )
'Hello'
```

`galaxy.util.recursively_stringify_dictionary_keys` (*d*)

`galaxy.util.relative_symlinks` (*path*, *start=None*, *followlinks=False*)

`galaxy.util.restore_text` (*text*, *character_map*={'@': '__at__', '\t': '__tc__', '\n': '__cn__', '\r': '__cr__', '[': '__ob__', ']' : '__cb__', '#': '__pd__', '\"': '__dq__', '\"': '__sq__', '{': '__oc__', '}' : '__cc__', '<': '__lt__', '>': '__gt__'})

Restores sanitized text

`galaxy.util.roundify` (*amount*, *sfs=2*)

Take a number in string form and truncate to 'sfs' significant figures.

`galaxy.util.rst_to_html` (*s*)

Convert a blob of reStructuredText to HTML

`galaxy.util.safe_str_cmp` (*a*, *b*)

safely compare two strings in a timing-attack-resistant manner

`galaxy.util.sanitize_for_filename` (*text*, *default=None*)

Restricts the characters that are allowed in a filename portion; Returns default value or a unique id string if result is not a valid name. Method is overly aggressive to minimize possible complications, but a maximum length is not considered.

`galaxy.util.sanitize_lists_to_string` (*values*, *valid_characters*=set(['!', ' ', ')', '(', '+', '*', '-', ' ', '/', ':', 'I', 'O', '3', '2', '5', '4', '7', '6', '9', '8', ':', '=', '?', 'A', 'C', 'B', 'E', 'D', 'G', 'F', 'T', 'H', 'K', 'J', 'M', 'L', 'O', 'N', 'Q', 'P', 'S', 'R', 'U', 'T', 'W', 'V', 'Y', 'X', 'Z', '_', '^', 'a', 'c', 'b', 'e', 'd', 'g', 'f', 'i', 'h', 'k', 'j', 'm', 'l', 'o', 'n', 'q', 'p', 's', 'r', 'u', 't', 'w', 'v', 'y', 'x', 'z']), *character_map*={'@': '__at__', '\t': '__tc__', '\n': '__cn__', '\r': '__cr__', '[': '__ob__', ']' : '__cb__', '#': '__pd__', '\"': '__dq__', '\"': '__sq__', '{': '__oc__', '}' : '__cc__', '<': '__lt__', '>': '__gt__'}, *invalid_character*='X')

`galaxy.util.sanitize_param` (*value*, *valid_characters*=set(['!', ' ', ')', '(', '+', '*', '-', ' ', '/', ':', 'I', 'O', '3', '2', '5', '4', '7', '6', '9', '8', ':', '=', '?', 'A', 'C', 'B', 'E', 'D', 'G', 'F', 'T', 'H', 'K', 'J', 'M', 'L', 'O', 'N', 'Q', 'P', 'S', 'R', 'U', 'T', 'W', 'V', 'Y', 'X', 'Z', '_', '^', 'a', 'c', 'b', 'e', 'd', 'g', 'f', 'i', 'h', 'k', 'j', 'm', 'l', 'o', 'n', 'q', 'p', 's', 'r', 'u', 't', 'w', 'v', 'y', 'x', 'z']), *character_map*={'@': '__at__', '\t': '__tc__', '\n': '__cn__', '\r': '__cr__', '[': '__ob__', ']' : '__cb__', '#': '__pd__', '\"': '__dq__', '\"': '__sq__', '{': '__oc__', '}' : '__cc__', '<': '__lt__', '>': '__gt__'}, *invalid_character*='X')

Clean incoming parameters (strings or lists)

`galaxy.util.sanitize_text` (*text*, *valid_characters*=set(['!', ' ', ')', '(', '+', '*', '-', ' ', '/', ':', 'I', 'O', '3', '2', '5', '4', '7', '6', '9', '8', ':', '=', '?', 'A', 'C', 'B', 'E', 'D', 'G', 'F', 'T', 'H', 'K', 'J', 'M', 'L', 'O', 'N', 'Q', 'P', 'S', 'R', 'U', 'T', 'W', 'V', 'Y', 'X', 'Z', '_', '^', 'a', 'c', 'b', 'e', 'd', 'g', 'f', 'i', 'h', 'k', 'j', 'm', 'l', 'o', 'n', 'q', 'p', 's', 'r', 'u', 't', 'w', 'v', 'y', 'x', 'z']), *character_map*={'@': '__at__', '\t': '__tc__', '\n': '__cn__', '\r': '__cr__', '[': '__ob__', ']' : '__cb__', '#': '__pd__', '\"': '__dq__', '\"': '__sq__', '{': '__oc__', '}' : '__cc__', '<': '__lt__', '>': '__gt__'}, *invalid_character*='X')

Restricts the characters that are allowed in text; accepts both strings and lists of strings; non-string entities will be cast to strings.

`galaxy.util.send_mail` (*frm*, *to*, *subject*, *body*, *config*)

Sends an email.

`galaxy.util.shrink_stream_by_size` (*value*, *size*, *join_by*='..', *left_larger*=True, *beginning_on_size_error*=False, *end_on_size_error*=False)

`galaxy.util.shrink_string_by_size` (*value*, *size*, *join_by*='..', *left_larger*=True, *beginning_on_size_error*=False, *end_on_size_error*=False)

`galaxy.util.size_to_bytes` (*size*)

Returns a number of bytes if given a reasonably formatted string with the size

`galaxy.util.smart_str` (*s*, *encoding*='utf-8', *strings_only*=False, *errors*='strict')

Returns a bytestring version of 's', encoded as specified in 'encoding'.

If *strings_only* is True, don't convert (some) non-string-like objects.

Adapted from an older, simpler version of `django.utils.encoding.smart_str`.

`galaxy.util.string_as_bool` (*string*)

`galaxy.util.string_as_bool_or_none` (*string*)

Returns True, None or False based on the argument: True if passed True, 'True', 'Yes', or 'On' None if passed None or 'None' False otherwise

Note: string comparison is case-insensitive so lowercase versions of those function equivalently.

`galaxy.util.string_to_object` (*s*)

`galaxy.util.stringify_dictionary_keys` (*in_dict*)

`galaxy.util.synchronized` (*func*)

This wrapper will serialize access to 'func' to a single thread. Use it as a decorator.

`galaxy.util.umask_fix_perms` (*path*, *umask*, *unmasked_perms*, *gid*=None)

umask-friendly permissions fixing

`galaxy.util.unicodify` (*value*, *encoding*='utf-8', *error*='replace', *default*=None)

Returns a unicode string or None

`galaxy.util.unique_id` (*KEY_SIZE*=128)

Generates an unique id

```
>>> ids = [ unique_id() for i in range(1000) ]
>>> len(set(ids))
1000
```

`galaxy.util.xml_element_compare` (*elem1*, *elem2*)

`galaxy.util.xml_element_list_compare` (*elem_list1*, *elem_list2*)

`galaxy.util.xml_element_to_dict` (*elem*)

`galaxy.util.xml_text` (*root*, *name*=None)

Returns the text inside an element

`galaxy.util.xml_to_string` (*elem*, *pretty*=False)

Returns a string from an xml tree

aliaspickler Module

`class galaxy.util.aliaspickler.AliasPickleModule` (*aliases*)

Bases: object

dump (*obj*, *fileobj*, *protocol*=0)

dumps (*obj*, *protocol*=0)

load (*fileobj*)

```
loads (string)
class galaxy.util.aliaspickler.AliasUnpickler (aliases, *args, **kw)
    Bases: pickle.Unpickler

    find_class (module, name)
```

bunch Module

```
class galaxy.util.bunch.Bunch (**kws)
    Bases: object
```

<http://aspn.activestate.com/ASPN/Cookbook/Python/Recipe/52308>

Often we want to just collect a bunch of stuff together, naming each item of the bunch; a dictionary's OK for that, but a small do-nothing class is even handier, and prettier to use.

```
get (key, default=None)

items ()

keys ()

values ()
```

debugging Module

```
class galaxy.util.debugging.SimpleProfiler (log=None)
    Bases: object
```

Simple profiler that captures the duration between calls to *report* and stores the results in a list.

```
REPORT_FORMAT = '%20f: %s'
```

```
get_reports ()

report (msg)
```

```
start (msg=None)
```

```
galaxy.util.debugging.stack_trace_string (max_depth=None,
                                             line_format='{index}:{file}:{function}:{line}')
```

Returns a string representation of the current stack.

Parameters *depth* – positive integer to control how many levels of the stack are returned. *max_depth=None* returns the entire stack (default).

expressions Module

 Expression evaluation support.

For the moment this depends on python's eval. In the future it should be replaced with a "safe" parser.

```
class galaxy.util.expressions.ExpressionContext (dict, parent=None)
    Bases: object, UserDict.DictMixin
```

hash_util Module

 Utility functions for bi-directional Python version compatibility. Python 2.5 introduced hash-lib which replaced sha in Python 2.4 and previous versions.

```
galaxy.util.hash_util.hmac_new (key, value)
```

```
galaxy.util.hash_util.is_hashable (value)
```

```
galaxy.util.hash_util.new_secure_hash (text_type=None)
```

Returns either a sha1 hash object (if called with no arguments), or a hexdigest of the sha1 hash of the argument *text_type*.

heartbeat Module

class galaxy.util.heartbeat.**Heartbeat** (*name='Heartbeat Thread', period=20, fname='heartbeat.log'*)

Bases: threading.Thread

Thread that periodically dumps the state of all threads to a file

get_interesting_stack_frame (*stack_frames*)

Scans a given backtrace stack frames, returns a single quadruple of [filename, line, function-name, text] of the single, deepest, most interesting frame.

Interesting being:

```
inside the galaxy source code ("/lib/galaxy"),
preferably not an egg.
```

print_nonsleeping (*threads_object_dict*)

run ()

shutdown ()

thread_is_sleeping (*last_stack_frame*)

Returns True if the given stack-frame represents a known sleeper function (at least in python 2.5)

galaxy.util.heartbeat.**get_current_thread_object_dict** ()

Get a dictionary of all 'Thread' objects created via the threading module keyed by thread_id. Note that not all interpreter threads have a thread objects, only the main thread and any created via the 'threading' module. Threads created via the low level 'thread' module will not be in the returned dictionary.

HACK: This mucks with the internals of the threading module since that module does not expose any way to match 'Thread' objects with interpreter thread identifiers (though it should).

inflection Module

class galaxy.util.inflection.**Base**

Locale inflectors must inherit from this base class in order to provide the basic Inflector functionality

camelize (*word*)

Returns given word as CamelCased Converts a word like "send_email" to "SendEmail". It will remove non alphanumeric character from the word, so "who's online" will be converted to "WhoSOnline"

classify (*table_name*)

Converts a table name to its class name according to rails naming conventions. Example: Converts "people" to "Person"

cond_plural (*number_of_records, word*)

Returns the plural form of a word if first parameter is greater than 1

demodulize (*module_name*)

foreignKey (*class_name, separate_class_name_and_id_with_underscore=1*)

Returns class_name in underscored form, with "_id" tacked on at the end. This is for use in dealing with the database.

humanize (*word, uppercase=''*)

Returns a human-readable string from word Returns a human-readable string from word, by replacing underscores with a space, and by upper-casing the initial character by default. If you need to uppercase all the words you just have to pass 'all' as a second parameter.

modulize (*module_description*)

ordinalize (*number*)

Converts number to its ordinal English form. This method converts 13 to 13th, 2 to 2nd ...

string_replace (*word, find, replace*)

This function returns a copy of word, translating all occurrences of each character in find to the corresponding character in replace

tableize (*class_name*)

Converts a class name to its table name according to rails naming conventions. Example. Converts “Person” to “people”

titleize (*word, uppercase=''*)

Converts an underscored or CamelCase word into a English sentence. The titleize function converts text like “WelcomePage”, “welcome_page” or “welcome page” to this “Welcome Page”. If second parameter is set to ‘first’ it will only capitalize the first character of the title.

unaccent (*text*)

Transforms a string to its unaccented version. This might be useful for generating “friendly” URLs

underscore (*word*)

Converts a word “into_it_s_underscored_version” Convert any “CamelCased” or “ordinary Word” into an “underscored_word”. This can be really useful for creating friendly URLs.

urlize (*text*)

Transform a string its unaccented and underscored version ready to be inserted in friendly URLs

variablize (*word*)

Same as camelize but first char is lowercased Converts a word like “send_email” to “sendEmail”. It will remove non alphanumeric character from the word, so “who’s online” will be converted to “whoSONline”

class `galaxy.util.inflection.English`

Bases: `galaxy.util.inflection.Base`

Inflector for pluralize and singularize English nouns.

This is the default Inflector for the Inflector obj

pluralize (*word*)

Pluralizes English nouns.

singularize (*word*)

Singularizes English nouns.

class `galaxy.util.inflection.Inflector` (*Inflector=<class galaxy.util.inflection.English>*)

Inflector for pluralizing and singularizing nouns.

It provides methods for helping on creating programs based on naming conventions like on Ruby on Rails.

camelize (*word*)

Returns given word as CamelCased Converts a word like “send_email” to “SendEmail”. It will remove non alphanumeric character from the word, so “who’s online” will be converted to “WhoSONline”

classify (*table_name*)

Converts a table name to its class name according to rails naming conventions. Example: Converts “people” to “Person”

cond_plural (*number_of_records, word*)

Returns the plural form of a word if first parameter is greater than 1

demodulize (*module_name*)

foreignKey (*class_name, separate_class_name_and_id_with_underscore=1*)

Returns class_name in underscored form, with “_id” tacked on at the end. This is for use in dealing with the database.

humanize (*word, uppercase=''*)

Returns a human-readable string from word Returns a human-readable string from word, by replacing

underscores with a space, and by upper-casing the initial character by default. If you need to uppcase all the words you just have to pass ‘all’ as a second parameter.

modulize (*module_description*)

ordinalize (*number*)

Converts number to its ordinal form. This method converts 13 to 13th, 2 to 2nd ...

pluralize (*word*)

Pluralizes nouns.

singularize (*word*)

Singularizes nouns.

tableize (*class_name*)

Converts a class name to its table name according to rails naming conventions. Example. Converts “Person” to “people”

titleize (*word*, *uppercase*=’')

Converts an underscored or CamelCase word into a sentence. The titleize function converts text like “WelcomePage”, “welcome_page” or “welcome page” to this “Welcome Page”. If the “uppercase” parameter is set to ‘first’ it will only capitalize the first character of the title.

unaccent (*text*)

Transforms a string to its unaccented version. This might be useful for generating “friendly” URLs

underscore (*word*)

Converts a word “into_it_s_underscored_version” Convert any “CamelCased” or “ordinary Word” into an “underscored_word”. This can be really useful for creating friendly URLs.

urlize (*text*)

Transform a string to its unaccented and underscored version ready to be inserted in friendly URLs

variablize (*word*)

Same as camelize but first char is lowercased Converts a word like “send_email” to “sendEmail”. It will remove non alphanumeric character from the word, so “who’s online” will be converted to “whoSONline”

json Module

`galaxy.util.json.dumps` (*obj*, *skipkeys*=False, *ensure_ascii*=True, *check_circular*=True, *allow_nan*=True, *cls*=None, *indent*=None, *separators*=None, *encoding*=’utf-8’, *default*=None, *sort_keys*=False, ***kw*)

Serialize *obj* to a JSON formatted *str*.

If *skipkeys* is false then dict keys that are not basic types (*str*, *unicode*, *int*, *long*, *float*, *bool*, *None*) will be skipped instead of raising a *TypeError*.

If *ensure_ascii* is false, all non-ASCII characters are not escaped, and the return value may be a *unicode* instance. See *dump* for details.

If *check_circular* is false, then the circular reference check for container types will be skipped and a circular reference will result in an *OverflowError* (or worse).

If *allow_nan* is false, then it will be a *ValueError* to serialize out of range float values (*nan*, *inf*, *-inf*) in strict compliance of the JSON specification, instead of using the JavaScript equivalents (*NaN*, *Infinity*, *-Infinity*).

If *indent* is a non-negative integer, then JSON array elements and object members will be pretty-printed with that indent level. An indent level of 0 will only insert newlines. *None* is the most compact representation. Since the default item separator is ‘, ’, the output might include trailing whitespace when *indent* is specified. You can use *separators*=(' ', ': ') to avoid this.

If `separators` is an `(item_separator, dict_separator)` tuple then it will be used instead of the default `(' ', ' ', ': ')` separators. `('', '', ':')` is the most compact JSON representation.

`encoding` is the character encoding for str instances, default is UTF-8.

`default(obj)` is a function that should return a serializable version of `obj` or raise `TypeError`. The default simply raises `TypeError`.

If `sort_keys` is `True` (default: `False`), then the output of dictionaries will be sorted by key.

To use a custom `JSONEncoder` subclass (e.g. one that overrides the `.default()` method to serialize additional types), specify it with the `cls` kwarg; otherwise `JSONEncoder` is used.

`galaxy.util.json.loads(s, encoding=None, cls=None, object_hook=None, parse_float=None, parse_int=None, parse_constant=None, object_pairs_hook=None, **kw)`

Deserialize `s` (a str or unicode instance containing a JSON document) to a Python object.

If `s` is a str instance and is encoded with an ASCII based encoding other than utf-8 (e.g. latin-1) then an appropriate encoding name must be specified. Encodings that are not ASCII based (such as UCS-2) are not allowed and should be decoded to unicode first.

`object_hook` is an optional function that will be called with the result of any object literal decode (a dict). The return value of `object_hook` will be used instead of the dict. This feature can be used to implement custom decoders (e.g. JSON-RPC class hinting).

`object_pairs_hook` is an optional function that will be called with the result of any object literal decoded with an ordered list of pairs. The return value of `object_pairs_hook` will be used instead of the dict. This feature can be used to implement custom decoders that rely on the order that the key and value pairs are decoded (for example, collections.OrderedDict will remember the order of insertion). If `object_hook` is also defined, the `object_pairs_hook` takes priority.

`parse_float`, if specified, will be called with the string of every JSON float to be decoded. By default this is equivalent to `float(num_str)`. This can be used to use another datatype or parser for JSON floats (e.g. decimal.Decimal).

`parse_int`, if specified, will be called with the string of every JSON int to be decoded. By default this is equivalent to `int(num_str)`. This can be used to use another datatype or parser for JSON integers (e.g. float).

`parse_constant`, if specified, will be called with one of the following strings: `-Infinity`, `Infinity`, `NaN`, `null`, `true`, `false`. This can be used to raise an exception if invalid JSON numbers are encountered.

To use a custom `JSONDecoder` subclass, specify it with the `cls` kwarg; otherwise `JSONDecoder` is used.

`galaxy.util.json.safe_dumps(*args, **kwargs)`

This is a wrapper around `dumps` that encodes `Infinity` and `NaN` values. It's a fairly rare case (which will be low in request volume). Basically, we tell `json.dumps` to blow up if it encounters `Infinity/NaN`, and we 'fix' it before re-encoding.

`galaxy.util.json.json_fix(val)`

`galaxy.util.json.validate_jsonrpc_request(request, regular_methods, notification_methods)`

`galaxy.util.json.validate_jsonrpc_response(response, id=None)`

`galaxy.util.json.jsonrpc_request(method, params=None, id=None, jsonrpc='2.0')`

`galaxy.util.json.jsonrpc_response(request=None, id=None, result=None, error=None, jsonrpc='2.0')`

lru Module Kanwei Li, 03/2010

Simple LRU cache that uses a dictionary to store a specified number of objects at a time.

```
class galaxy.util.lrucache.LRUCache (num_elements)
```

```
    clear()
        Clears/initiates storage variables
```

memdump Module

none_like Module Objects with No values

```
class galaxy.util.none_like.NoneDataset (datatypes_registry=None, ext='data', dbkey='??')
    Bases: galaxy.util.none_like.RecursiveNone
```

```
    missing_meta()
```

```
class galaxy.util.none_like.RecursiveNone
```

odict Module Ordered dictionary implementation.

```
class galaxy.util.odict.odict (dict=None)
```

```
    Bases: UserDict.UserDict
```

<http://aspn.activestate.com/ASPN/Cookbook/Python/Recipe/107747>

This dictionary class extends UserDict to record the order in which items are added. Calling keys(), values(), items(), etc. will return results in this order.

```
    clear()
    copy()
    insert (index, key, item)
    items()
    iteritems()
    iterkeys()
    itervalues()
    keys()
    popitem()
    reverse()
    setdefault (key, failobj=None)
    update (dict)
    values()
```

sanitize_html Module HTML Sanitizer (ripped from feedparser)

```
galaxy.util.sanitize_html.sanitize_html (htmlSource, encoding='utf-8', type='text/html')
```

shed_util Module

shed_util_common Module

streamball Module A simple wrapper for writing tarballs as a stream.

```
class galaxy.util.streamball.StreamBall(mode, members=None)
    Bases: object

    add(file, relpath, check_file=False)

    stream(envIRON, start_response)

class galaxy.util.streamball.ZipBall(tmpf, tmpd)
    Bases: object

    stream(envIRON, start_response)
```

template Module

```
galaxy.util.template.fill_template(template_text, context=None, **kwargs)
```

topsort Module Topological sort.

From Tim Peters, see: <http://mail.python.org/pipermail/python-list/1999-July/006660.html>

topsort takes a list of pairs, where each pair (x, y) is taken to mean that $x \leq y$ wrt some abstract partial ordering. The return value is a list, representing a total ordering that respects all the input constraints. E.g.,

```
topsort([(1,2), (3,3)])
```

Valid topological sorts would be any of (but nothing other than)

```
[3, 1, 2] [1, 3, 2] [1, 2, 3]
```

... however this variant ensures that ‘key’ order (first element of tuple) is preserved so the following will be result returned:

```
[1, 3, 2]
```

because those are the permutations of the input elements that respect the “1 precedes 2” and “3 precedes 3” input constraints. Note that a constraint of the form (x, x) is really just a trick to make sure x appears *somewhere* in the output list.

If there’s a cycle in the constraints, say

```
topsort([(1,2), (2,1)])
```

then CycleError is raised, and the exception object supports many methods to help analyze and break the cycles. This requires a good deal more code than topsort itself!

```
exception galaxy.util.topsort.CycleError(sofar, numpreds, succs)
    Bases: exceptions.Exception

    get_elements()
    get_pairlist()
    get_partial()
    get_pred_counts()
    get_preds()
    get_succs()
    pick_a_cycle()

galaxy.util.topsort.topsort(pairlist)
galaxy.util.topsort.topsort_levels(pairlist)
```


Subpackages

backports Package

backports Package Modules for providing backward compatibility with future versions of Python

Subpackages

importlib Package

importlib Package Backport of importlib.import_module from 3.x.

`galaxy.util.backports.importlib.import_module(name, package=None)`
 Import a module.

The ‘package’ argument is required when performing a relative import. It specifies the package to use as the anchor point from which to resolve the relative import to an absolute import.

visualization Package

visualization Package Package for Galaxy visualization plugins.

genomes Module

class `galaxy.visualization.genomes.Genome(key, description, len_file=None, twobit_file=None)`
 Bases: object

Encapsulates information about a known genome/dbkey.

to_dict (*num=None, chrom=None, low=None*)
 Returns representation of self as a dictionary.

class `galaxy.visualization.genomes.GenomeRegion(chrom=None, start=0, end=0, sequence=None)`
 Bases: object

A genomic region on an individual chromosome.

static from_dict (*obj_dict*)

static from_str (*obj_str*)

class `galaxy.visualization.genomes.Genomes(app)`
 Bases: object

Provides information about available genome data and methods for manipulating that data.

check_and_reload ()

chroms (*trans, dbkey=None, num=None, chrom=None, low=None*)

Returns a naturally sorted list of chroms/contigs for a given dbkey. Use either chrom or low to specify the starting chrom in the return list.

get_build (*dbkey*)

Returns build for the given key.

get_dbkeys (*trans, chrom_info=False, **kwd*)

Returns all known dbkeys. If chrom_info is True, only dbkeys with chromosome lengths are returned.

has_reference_data (*dbkey, dbkey_owner=None*)

Returns true if there is reference data for the specified dbkey. If dbkey is custom, dbkey_owner is needed to determine if there is reference data.

reference (*trans, dbkey, chrom, low, high*)

Return reference data for a build.

reload_genomes ()

`galaxy.visualization.genomes.decode_dbkey` (*dbkey*)

Decodes dbkey and returns tuple (username, dbkey)

Subpackages

data_providers Package

data_providers Package Galaxy visualization/visual analysis data providers.

basic Module

class `galaxy.visualization.data_providers.basic.BaseDataProvider` (*converted_dataset=None, original_dataset=None, dependencies=None, error_max_vals='Only the first %i values are returned.'*)

Bases: `object`

Base class for data providers. Data providers (a) read and package data from datasets; and (b) write subsets of data to new datasets.

get_data (*chrom, start, end, start_val=0, max_vals=9223372036854775807, **kwargs*)

Returns data as specified by kwargs. start_val is the first element to return and max_vals indicates the number of values to return.

Return value must be a dictionary with the following attributes: dataset_type, data

get_iterator (***kwargs*)

Returns an iterator that provides data in the region chrom:start-end

has_data (***kwargs*)

Returns true if dataset has data in the specified genome window, false otherwise.

process_data (*iterator, start_val=0, max_vals=None, **kwargs*)

Process data from an iterator to a format that can be provided to client.

write_data_to_file (*filename, **kwargs*)

Write data in region defined by chrom, start, and end to a file.

class `galaxy.visualization.data_providers.basic.ColumnDataProvider` (*original_dataset, max_lines_returned=30000*)

Bases: `galaxy.visualization.data_providers.basic.BaseDataProvider`

Data provider for columnar data

MAX_LINES_RETURNED = 30000

get_data (*columns=None, start_val=0, max_vals=None, skip_comments=True, **kwargs*)
Returns data from specified columns in dataset. Format is list of lists where each list is a line of data.

genome Module

registry Module

Subpackages

phyloviz Package

phyloviz Package Data providers code for PhyloViz

class `galaxy.visualization.data_providers.phyloviz.PhylovizDataProvider` (*original_dataset=None*)
Bases: `galaxy.visualization.data_providers.basic.BaseDataProvider`

dataset_type = 'phylo'

get_data (*tree_index=0*)
Returns trees. Trees are actually an array of JsonDicts. It's usually one tree, except in the case of Nexus

baseparser Module

class `galaxy.visualization.data_providers.phyloviz.baseparser.Base_Parser`
Bases: object

Base parsers contain all the methods to handle phylogeny tree creation and converting the data to json that all parsers should have

parseFile (*filePath*)
Base method that all phylogeny file parser should have

toJson (*jsonDict*)
Convenience method to get a json string from a python json dict

class `galaxy.visualization.data_providers.phyloviz.baseparser.Node` (*nodeName, **kwargs*)

Bases: object

Node class of PhyloTree, which represents a CLAUDE in a phylogenetic tree

addChildNode (*child*)
Adds a child node to the current node

addChildrentoJson (*jsonDict*)
Needs a special method to addChildren, such that the key does not appear in the Jsdict when the children is empty this requirement is due to the layout algorithm used by d3 layout for hiding subtree

addMiscToJson (*jsonDict*)
Adds other misc attributes to json if they are present

toJson ()
Converts the data in the node to a dict representation of json

class `galaxy.visualization.data_providers.phyloviz.baseparser.PhyloTree`
Bases: object

Standardized python based class to represent the phylogenetic tree parsed from different phylogenetic file formats.

addAttributesToRoot (*attrDict*)

Adds attributes to root, but first we put it in a temp store and bind it with root when .toJson is called

addRoot (*root*)

Creates a root for phyloTree

generateJsonableDict ()

Changes itself into a dictionary by recursively calling the toJson on all its nodes. Think of it as a dict in an array of dict in an array of dict and so on...

makeNode (*nodeName*, ***kwargs*)

Called to make a node within PhyloTree, arbitrary kwargs can be passed to annotate nodes Tracks the number of nodes via internally incremented id

newickparser Module

class galaxy.visualization.data_providers.phyloviz.newickparser.**Newick_Parser**

Bases: *galaxy.visualization.data_providers.phyloviz.baseparser.Base_Parser*

For parsing trees stored in the newick format (.nhx) It is necessarily more complex because this parser is later extended by Nexus for parsing newick as well..

cleanNewickString (*rawNewick*)

removing semi colon, and illegal json characters (',') and white spaces

parseData (*newickString*)

To be called on a newickString directly to parse it. Returns: jsonableDict

parseFile (*filePath*)

Parses a newick file to obtain the string inside. Returns: jsonableDict

parseNode (*string*, *depth*)

Recursive method for parsing newick string, works by stripping down the string into substring of newick contained with brackets, which is used to call itself.

Eg ... (A, B, (D, E)C, F, G) ...

We will make the preceding nodes first A, B, then the internal node C, its children D, E, and finally the succeeding nodes F, G

nexusparser Module

class galaxy.visualization.data_providers.phyloviz.nexusparser.**Nexus_Parser**

Bases: *galaxy.visualization.data_providers.phyloviz.newickparser.Newick_Parser*

checkComments (*line*)

Check to see if the line/lines is a comment.

parseFile (*filePath*)

passes a file and extracts its Nexus content.

parseNexus (*filename*)

Nexus data is stored in blocks between a line starting with begin and another line starting with end; Comments inside square brackets are to be ignored, For more information: http://wiki.christophchamp.com/index.php/NEXUS_file_format Nexus can store multiple trees

splitLinebyWhitespaces (*line*)

replace tabs and write spaces to a single write space, so we can properly split it.

phyloxmlparser Module

class `galaxy.visualization.data_providers.phyloviz.phyloxmlparser.Phyloxml_Parser`
 Bases: `galaxy.visualization.data_providers.phyloviz.baseparser.Base_Parser`

Parses a phyloxml file into a json file that will be passed to PhyloViz for display

cleanTag (*tagString*)

parseFile (*filePath*)

passes a file and extracts its Phylogeny Tree content.

parseNode (*node, depth*)

Parses any node within a phyloxml tree and looks out for claude, which signals the creation of nodes - internal OR leaf

genome Package

genome Package Code for Galaxy genome visualizations.

visual_analytics Module**tracks Package**

tracks Package Summary.py required to be in this module due to pickling.

summary Module**web Package**

web Package The Galaxy web application framework

buildapp Module

form_builder Module Classes for generating HTML forms

class `galaxy.web.form_builder.AddressField` (*name, user=None, value=None, params=None*)
 Bases: `galaxy.web.form_builder.BaseField`

static fields ()

get_html (*disabled=False*)

class `galaxy.web.form_builder.BaseField`

Bases: `object`

get_disabled_str (*disabled=False*)

get_html (*prefix=''*)

Returns the html widget corresponding to the parameter

```
class galaxy.web.form_builder.CheckboxField(name, checked=None, re-
                                           fresh_on_change=False, re-
                                           fresh_on_change_values=None)
```

Bases: `galaxy.web.form_builder.BaseField`

A checkbox (boolean input)

```
>>> print CheckboxField( "foo" ).get_html()
<input type="checkbox" id="foo" name="foo" value="true"><input type="hidden" name="foo" value="t
>>> print CheckboxField( "bar", checked="yes" ).get_html()
<input type="checkbox" id="bar" name="bar" value="true" checked="checked"><input type="hidden" n
```

get_html (prefix=',', disabled=False)

static is_checked (value)

set_checked (value)

```
class galaxy.web.form_builder.DrillDownField(name, multiple=None, display=None, re-
                                           fresh_on_change=False, options=[], value=[],
                                           refresh_on_change_values=[])
```

Bases: `galaxy.web.form_builder.BaseField`

A hierarchical select field, which allows users to ‘drill down’ a tree-like set of options.

```
>>> t = DrillDownField( "foo", multiple=True, display="checkbox", options=[{'name': 'Heading 1',
>>> print t.get_html()
<div class="form-row drilldown-container" id="drilldown--666f6f">
<div class="form-row-input">
<div><span class="form-toggle icon-button toggle-expand" id="drilldown--666f6f-68656164696e6731-
<input type="checkbox" name="foo" value="heading1" >Heading 1
</div><div class="form-row" id="drilldown--666f6f-68656164696e6731-container" style="float: left
<div class="form-row-input">
<input type="checkbox" name="foo" value="option1" >Option 1
</div>
<div class="form-row-input">
<input type="checkbox" name="foo" value="option2" >Option 2
</div>
<div class="form-row-input">
<div><span class="form-toggle icon-button toggle-expand" id="drilldown--666f6f-68656164696e6731-
<input type="checkbox" name="foo" value="heading1" >Heading 1
</div><div class="form-row" id="drilldown--666f6f-68656164696e6731-68656164696e6731-container" s
<div class="form-row-input">
<input type="checkbox" name="foo" value="option3" >Option 3
</div>
<div class="form-row-input">
<input type="checkbox" name="foo" value="option4" >Option 4
</div>
</div>
</div>
</div>
</div>
<div class="form-row-input">
<input type="checkbox" name="foo" value="option5" >Option 5
</div>
</div>
>>> t = DrillDownField( "foo", multiple=False, display="radio", options=[{'name': 'Heading 1',
>>> print t.get_html()
<div class="form-row drilldown-container" id="drilldown--666f6f">
```

```
class galaxy.web.form_builder.FTPFileField(name, dir, ftp_site, value=None)
```

An FTP file upload input.

```
tfoot = '\n </tbody>\n </table>\n '
```

```
trow = '\n <tr>\n <td><input type="checkbox" name="%s%s" value="%s"/></td>\n <td>%s</td>\n <td>%s</td>\n <t
```

```
class galaxy.web.form_builder.FileField(name, value=None, ajax=False)
```

A file upload input.

```
class galaxy.web.form_builder.HiddenField (name, value=None)
```

A hidden field.

```
>>> print HiddenField( "foo", 100 ).get_html()
<input type="hidden" name="foo" value="100">
```

```
get_html (prefix='')
```

```
class galaxy.web.form_builder.HistoryField(name, user=None, value=None, params=None)
Bases: galaxy.web.form_builder.BaseField
```

```
get_display_text ()
```

```
get_html (disabled=False)
```

```
class galaxy.web.form_builder.LibraryField(name, value=None, trans=None)
Bases: galaxy.web.form_builder.BaseField
```

```
get_display_text ()
```

```
get_html (prefix='', disabled=False)
```

```
class galaxy.web.form_builder.PasswordField(name, size=None, value=None)
Bases: galaxy.web.form_builder.BaseField
```

A password input box. text appears as “***”

```
>>> print PasswordField( "foo" ).get_html()
<input type="password" name="foo" size="10" value="">
>>> print PasswordField( "bins", size=4, value="default" ).get_html()
<input type="password" name="bins" size="4" value="default">
```

```
get_html (prefix='', disabled=False)
```

```
set_size (size)
```

```
class galaxy.web.form_builder.SelectField(name, multiple=None, display=None,
refresh_on_change=False, re-
fresh_on_change_values=None, size=None)
Bases: galaxy.web.form_builder.BaseField
```

A select field.

```
>>> t = SelectField( "foo", multiple=True )
>>> t.add_option( "tuti", 1 )
>>> t.add_option( "fruity", "x" )
>>> print t.get_html()
<select name="foo" multiple>
<option value="1">tuti</option>
<option value="x">fruity</option>
</select>
```

```
>>> t = SelectField( "bar" )
>>> t.add_option( "automatic", 3 )
>>> t.add_option( "bazooty", 4, selected=True )
>>> print t.get_html()
<select name="bar" last_selected_value="4">
<option value="3">automatic</option>
<option value="4" selected>bazooty</option>
</select>
```



```
>>> t = SelectField( "foo", display="radio" )
>>> t.add_option( "tuti", 1 )
>>> t.add_option( "fruity", "x" )
>>> print t.get_html()
<div><input type="radio" name="foo" value="1" id="foo|1"><label class="inline" for="foo|1">tuti</div>
<div><input type="radio" name="foo" value="x" id="foo|x"><label class="inline" for="foo|x">fruit</div>
```

```
>>> t = SelectField( "bar", multiple=True, display="checkboxes" )
>>> t.add_option( "automatic", 3 )
>>> t.add_option( "bazooty", 4, selected=True )
>>> print t.get_html()
<div class="checkUncheckAllPlaceholder" checkbox_name="bar"></div>
<div><input type="checkbox" name="bar" value="3" id="bar|3"><label class="inline" for="bar|3">au</div>
<div><input type="checkbox" name="bar" value="4" id="bar|4" checked='checked'><label class="inli</div>
```

add_option (*text, value, selected=False*)

get_html (*prefix='', disabled=False*)

get_html_checkboxes (*prefix='', disabled=False*)

get_html_default (*prefix='', disabled=False*)

get_html_radio (*prefix='', disabled=False*)

get_selected (*return_label=False, return_value=False, multi=False*)

Return the currently selected option's label, value or both as a tuple. For multi-select lists, a list is returned.

to_dict ()

class galaxy.web.form_builder.**SwitchingSelectField** (*delegate_fields, default_field=None*)

Bases: *galaxy.web.form_builder.BaseField*

get_html (*prefix='', disabled=False*)

primary_field

class galaxy.web.form_builder.**TextArea** (*name, size=None, value=None*)

Bases: *galaxy.web.form_builder.BaseField*

A standard text area box.

```
>>> print TextArea( "foo" ).get_html()
<textarea name="foo" rows="5" cols="25"></textarea>
>>> print TextArea( "bins", size="4x5", value="default" ).get_html()
<textarea name="bins" rows="4" cols="5">default</textarea>
```

get_html (*prefix='', disabled=False*)

set_size (*rows, cols*)

class galaxy.web.form_builder.**TextField** (*name, size=None, value=None*)

Bases: *galaxy.web.form_builder.BaseField*

A standard text input box.

```
>>> print TextField( "foo" ).get_html()
<input type="text" name="foo" size="10" value="">
>>> print TextField( "bins", size=4, value="default" ).get_html()
<input type="text" name="bins" size="4" value="default">
```

```
    get_html (prefix='', disabled=False)
    set_size (size)
class galaxy.web.form_builder.WorkflowField (name, user=None, value=None, params=None)
    Bases: galaxy.web.form_builder.BaseField
    get_html (disabled=False)
class galaxy.web.form_builder.WorkflowMappingField (name, user=None, value=None,
                                                    params=None, **kwd)
    Bases: galaxy.web.form_builder.BaseField
    get_display_text ()
    get_html (disabled=False)
galaxy.web.form_builder.build_select_field (trans, objs, label_attr, select_field_name, initial_value='none',
                                            selected_value='none', refresh_on_change=False, multiple=False, display=None, size=None)
    Build a SelectField given a set of objects. The received params are:
        •objs: the set of objects used to populate the option list
        •label_attr: the attribute of each obj (e.g., name, email, etc ) whose value is used to populate each option label.
            -If the string 'self' is passed as label_attr, each obj in objs is assumed to be a string, so the obj itself is used
        •select_field_name: the name of the SelectField
        •initial_value: the value of the first option in the SelectField - allows for an option telling the user to select something
        •selected_value: the value of the currently selected option
        •refresh_on_change: True if the SelectField should perform a refresh_on_change
galaxy.web.form_builder.get_suite ()
    Get unittest suite for this module
```

params Module Mixins for parsing web form and API parameters

```
class galaxy.web.params.BaseParamParser
    Bases: object
    get_params (kwargs)
class galaxy.web.params.QuotaParamParser
    Bases: galaxy.web.params.BaseParamParser
    get_quota_params (kwargs)
```

Subpackages

base Package

controller Module Contains functionality needed in every web interface

```
class galaxy.web.base.controller.BaseAPIController (app)
    Bases: galaxy.web.base.controller.BaseController
    get_object (trans, id, class_name, check_ownership=False, check_accessible=False,
                deleted=None)
```

```

not_implemented (trans, **kwd)

validate_in_users_and_groups (trans, payload)
    For convenience, in_users and in_groups can be encoded IDs or emails/group names in the API.

class galaxy.web.base.controller.BaseController (app)
    Bases: object

    Base class for Galaxy web application controllers.

    decode_id (id)

    encode_all_ids (trans, rval, recursive=False)
        Encodes all integer values in the dict rval whose keys are 'id' or end with '_id'

        It might be useful to turn this in to a decorator

    get_class (class_name)
        Returns the class object that a string denotes. Without this method, we'd have to do eval(<class_name>).

    get_group (trans, id, check_ownership=False, check_accessible=False, deleted=None)

    get_object (trans, id, class_name, check_ownership=False, check_accessible=False,
                deleted=None)
        Convenience method to get a model object with the specified checks.

    get_role (trans, id, check_ownership=False, check_accessible=False, deleted=None)

    get_toolbox ()
        Returns the application toolbox

    get_user (trans, id, check_ownership=False, check_accessible=False, deleted=None)

    parse_filter_params (qdict, filter_attr_key='q', filter_value_key='qv', attr_op_split_char='-')

    parse_limit_offset (qdict)

class galaxy.web.base.controller.BaseUIController (app)
    Bases: galaxy.web.base.controller.BaseController

    get_object (trans, id, class_name, check_ownership=False, check_accessible=False,
                deleted=None)

exception galaxy.web.base.controller.ControllerUnavailable
    Bases: exceptions.Exception

    Deprecated: BaseController used to be available under the name Root

class galaxy.web.base.controller.CreatesApiKeysMixin
    Mixing centralizing logic for creating API keys for user objects.

    Deprecated - please use api_keys.ApiKeyManager for new development.

    create_api_key (trans, user)

class galaxy.web.base.controller.CreatesUsersMixin
    Mixin centralizing logic for user creation between web and API controller.

    Web controller handles additional features such e-mail subscription, activation, user forms, etc.... API created
    users are much more vanilla for the time being.

    create_user (trans, email, username, password)

class galaxy.web.base.controller.Datatype (extension, dtype, type_extension, mimetype, display_in_upload)
    Bases: object

    Used for storing in-memory list of datatypes currently in the datatypes registry.

```

class `galaxy.web.base.controller.ExportsHistoryMixin`

queue_history_export (*trans*, *history*, *gzip=True*, *include_hidden=False*, *include_deleted=False*)

serve_ready_history_export (*trans*, *jeha*)

class `galaxy.web.base.controller.ImportsHistoryMixin`

queue_history_import (*trans*, *archive_type*, *archive_source*)

`galaxy.web.base.controller.Root`

alias of `BaseController`

class `galaxy.web.base.controller.SharableItemSecurityMixin`

Mixin for handling security for sharable items.

security_check (*trans*, *item*, *check_ownership=False*, *check_accessible=False*)

Security checks for an item: checks if (a) user owns item or (b) item is accessible to user.

class `galaxy.web.base.controller.SharableMixin`

Mixin for a controller that manages an item that can be shared.

create_item_slug (*sa_session*, *item*)

Create/set item slug. Slug is unique among user's importable items for item's class. Returns true if item's slug was set/changed; false otherwise.

display_by_username_and_slug (*trans*, *username*, *slug*)

Display item by username and slug.

get_item (*trans*, *id*)

Return item based on id.

get_item_content_async (*trans*, **args*, ***kwargs*)

Returns item content in HTML format.

get_name_and_link_async (*trans*, **args*, ***kwargs*)

Returns item's name and link.

set_public_username (*trans*, **args*, ***kwargs*)

Set user's public username and delegate to sharing()

set_slug_async (*trans*, **args*, ***kwargs*)

share (*trans*, **args*, ***kwargs*)

Handle sharing an item with a particular user.

sharing (*trans*, **args*, ***kwargs*)

Handle item sharing.

class `galaxy.web.base.controller.UsesExtendedMetadataMixin`

Bases: `galaxy.web.base.controller.SharableItemSecurityMixin`

Mixin for getting and setting item extended metadata.

create_extended_metadata (*trans*, *extmeta*)

Create/index an extended metadata object. The returned object is not associated with any items

delete_extended_metadata (*trans*, *item*)

get_item_extended_metadata_obj (*trans*, *item*)

Given an item object (such as a LibraryDatasetDatasetAssociation), find the object of the associated extended metadata

```

    set_item_extended_metadata_obj (trans, item, extmeta_obj, check_writable=False)
    unset_item_extended_metadata_obj (trans, item, check_writable=False)

class galaxy.web.base.controller.UsesFormDefinitionsMixin
    Mixin for controllers that use Galaxy form objects.

    add_template (trans, cntrller, item_type, form_type, **kwd)
    build_form_id_select_field (trans, forms, selected_value='none')
    clean_field_contents (widgets, **kwd)
    delete_template (trans, cntrller, item_type, form_type, **kwd)
    edit_template (trans, cntrller, item_type, form_type, **kwd)
    edit_template_info (trans, cntrller, item_type, form_type, **kwd)
    field_param_values_ok (widget_name, widget_type, **kwd)
    get_all_forms (trans, all_versions=False, filter=None, form_type='All')
        Return all the latest forms from the form_definition_current table if all_versions is set to True. Otherwise
        return all the versions of all the forms from the form_definition table.
    get_all_forms_by_type (trans, cntrller, form_type)
    get_form_values (trans, user, form_definition, **kwd)
        Returns the name:value dictionary containing all the form values
    get_item_and_stuff (trans, item_type, **kwd)
    populate_widgets_from_kwd (trans, widgets, **kwd)
    save_widget_field (trans, field_obj, widget_name, **kwd)
    widget_fields_have_contents (widgets)

class galaxy.web.base.controller.UsesLibraryMixin

    get_library (trans, id, check_ownership=False, check_accessible=True)

class galaxy.web.base.controller.UsesLibraryMixinItems
    Bases: galaxy.web.base.controller.SharableItemSecurityMixin

    can_current_user_add_to_library_item (trans, item)
    check_user_can_add_to_library_item (trans, item, check_accessible=True)
        Raise exception if user cannot add to the specified library item (i.e. Folder). Can set check_accessible to
        False if folder was loaded with this check.
    copy_hda_to_library_folder (trans, hda, library_folder, roles=None, ldda_message='')
    get_library_dataset (trans, id, check_ownership=False, check_accessible=True)
    get_library_dataset_dataset_association (trans, id, check_ownership=False, check_accessible=True)
    get_library_folder (trans, id, check_ownership=False, check_accessible=True)

class galaxy.web.base.controller.UsesQuotaMixin
    Bases: object

    get_quota (trans, id, check_ownership=False, check_accessible=False, deleted=None)

```

```
class galaxy.web.base.controller.UsesStoredWorkflowMixin
    Bases: galaxy.web.base.controller.SharableItemSecurityMixin,
           galaxy.model.item_attrs.UsesAnnotations
    Mixin for controllers that use StoredWorkflow objects.

    get_stored_workflow(trans, id, check_ownership=True, check_accessible=False)
        Get a StoredWorkflow from the database by id, verifying ownership.

    get_stored_workflow_steps(trans, stored_workflow)
        Restores states for a stored workflow's steps.

class galaxy.web.base.controller.UsesTagsMixin
    Bases: galaxy.web.base.controller.SharableItemSecurityMixin

    get_tag_handler(trans)

    get_user_tags_used(trans, user=None)
        Return a list of distinct 'user_tname:user_value' strings that the given user has used.

        user defaults to trans.user. Returns an empty list if no user is given and trans.user is anonymous.

    set_tags_from_list(trans, item, new_tags_list, user=None)

class galaxy.web.base.controller.UsesVisualizationMixin
    Bases: galaxy.web.base.controller.UsesLibraryMixinItems
    Mixin for controllers that use Visualization objects.

    add_visualization_revision(trans, visualization, config, title, dbkey)
        Adds a new VisualizationRevision to the given visualization with the given parameters and set its parent
        visualization's latest_revision to the new revision.

    create_visualization(trans, type, title='Untitled Visualization', slug=None, dbkey=None, an-
                        notation=None, config={}, save=True)
        Create visualiation and first revision.

    get_hda(trans, dataset_id, check_ownership=True, check_accessible=False, check_state=True)
        Get an HDA object by id performing security checks using the current transaction.

    get_hda_or_ldda(trans, hda_ldda, dataset_id)
        Returns either HDA or LDDA for hda/ldda and id combination.

    get_new_track_config(trans, dataset)
        Returns track configuration dict for a dataset.

    get_published_visualizations(trans, exclude_user=None, order_by=None,
                                query_only=False)
        Return query or query results for published visualizations optionally excluding the user in exclude_user.

        Set order_by to a column or list of columns to change the order returned. Defaults to DE-
        FAULT_ORDER_BY. Set query_only to return just the query for further filtering or processing.

    get_tool_def(trans, hda)
        Returns definition of an interactive tool for an HDA.

    get_visualization(trans, id, check_ownership=True, check_accessible=False)
        Get a Visualization from the database by id, verifying ownership.

    get_visualization_config(trans, visualization)
        Returns a visualization's configuration. Only works for trackster visualizations right now.

    get_visualization_dict(visualization)
        Return a set of detailed attributes for a visualization in dictionary form. The visualization's latest_revision
```

is returned in its own sub-dictionary. NOTE: that encoding ids isn't done here should happen at the caller level.

get_visualization_revision_dict (*revision*)

Return a set of detailed attributes for a visualization in dictionary form. NOTE: that encoding ids isn't done here should happen at the caller level.

get_visualization_summary_dict (*visualization*)

Return a set of summary attributes for a visualization in dictionary form. NOTE: that encoding ids isn't done here should happen at the caller level.

get_visualizations_by_user (*trans, user, order_by=None, query_only=False*)

Return query or query results of visualizations filtered by a user.

Set *order_by* to a column or list of columns to change the order returned. Defaults to *DEFAULT_ORDER_BY*. Set *query_only* to return just the query for further filtering or processing.

get_visualizations_shared_with_user (*trans, user, order_by=None, query_only=False*)

Return query or query results for visualizations shared with the given user.

Set *order_by* to a column or list of columns to change the order returned. Defaults to *DEFAULT_ORDER_BY*. Set *query_only* to return just the query for further filtering or processing.

import_visualization (*trans, id, user=None*)

Copy the visualization with the given id and associate the copy with the given user (defaults to *trans.user*).

Raises *ItemAccessibilityException* if *user* is not passed and the current user is anonymous, and if the visualization is not *importable*. Raises *ItemDeletionException* if the visualization has been deleted.

save_visualization (*trans, config, type, id=None, title=None, dbkey=None, slug=None, annotation=None*)

viz_types = ['trackster']

`galaxy.web.base.controller.sort_by_attr(seq, attr)`

Sort the sequence of objects by object's attribute Arguments: seq - the list or any sequence (including immutable one) of objects to sort. attr - the name of attribute to sort by

Subpackages

controllers Package

admin Module

class `galaxy.web.base.controllers.admin.Admin`

Bases: `object`

center (*trans, *args, **kwargs*)

create_group (*trans, *args, **kwargs*)

create_new_user (*trans, *args, **kwargs*)

create_role (*trans, *args, **kwargs*)

delete_operation = `None`

group_list_grid = `None`

groups (*trans, *args, **kwargs*)

index (*trans, *args, **kwargs*)

```
job_info (trans, *args, **kwargs)
jobs (trans, *args, **kwargs)
manage_roles_and_groups_for_user (trans, *args, **kwargs)
manage_users_and_groups_for_role (trans, *args, **kwargs)
manage_users_and_roles_for_group (trans, *args, **kwargs)
mark_group_deleted (trans, *args, **kwargs)
mark_role_deleted (trans, *args, **kwargs)
mark_user_deleted (trans, *args, **kwargs)
name_autocomplete_data (trans, *args, **kwargs)
    Return autocomplete data for user emails
package_tool (trans, *args, **kwargs)
purge_group (trans, *args, **kwargs)
purge_operation = None
purge_role (trans, *args, **kwargs)
purge_user (trans, *args, **kwargs)
quota_list_grid = None
reload_tool (trans, *args, **kwargs)
rename_group (trans, *args, **kwargs)
rename_role (trans, *args, **kwargs)
repository_list_grid = None
reset_user_password (trans, *args, **kwargs)
role_list_grid = None
roles (trans, *args, **kwargs)
tool_version_list_grid = None
tool_versions (trans, *args, **kwargs)
undelete_group (trans, *args, **kwargs)
undelete_operation = None
undelete_role (trans, *args, **kwargs)
undelete_user (trans, *args, **kwargs)
user_list_grid = None
users (trans, *args, **kwargs)
galaxy.web.base.controllers.admin.get_group (trans, id)
    Get a Group from the database by id.
galaxy.web.base.controllers.admin.get_quota (trans, id)
    Get a Quota from the database by id.
galaxy.web.base.controllers.admin.get_role (trans, id)
    Get a Role from the database by id.
```



```
galaxy.web.base.controllers.admin.get_user(trans, user_id)
```

Get a User from the database by id.

```
galaxy.web.base.controllers.admin.get_user_by_username(trans, username)
```

Get a user from the database by username

framework Package

framework Package Galaxy web application framework

base Module A simple WSGI application/framework.

```
class galaxy.web.framework.base.DefaultWebTransaction( environ)
```

Bases: object

Wraps the state of a single web transaction (request/response cycle).

TODO: Provide hooks to allow application specific state to be included in here.

session

Property that replaces itself with a calculated value the first time it is used.

```
class galaxy.web.framework.base.FieldStorage (fp=None, headers=None,
outerboundary='', environ={ 'CELERY_LOG_REDIRECT_LEVEL':
'WARNING', '_MP_FORK_LOGFILE_':
'/home/docs/log/celery_proc.log',
'NEW_RELIC_CONFIG_FILE':
'/home/docs/newrelic.ini', 'CEL-
ERY_LOG_REDIRECT': '1', 'LOG-
NAME': 'docs', 'USER': 'docs', 'PATH':
'/home/docs/bin:/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin',
'HOME': '/home/docs', 'PS1':
'(docs)', 'TERM': 'linux', 'SHELL':
'/bin/bash', 'TZ': 'America/Chicago',
'_MP_FORK_LOGFORMAT_': "[% (asc-
time)s: %(levelname)s/% (processName)s]
%(message)s", 'SHLVL': '1', 'SUPER-
VISOR_ENABLED': '1', 'EDITOR':
'vim', 'DJANGO_PROJECT_DIR':
'/home/docs/checkouts/readthedocs.org/readthedocs',
'SUDO_USER': 'root',
'CELERY_LOG_FILE':
'/home/docs/log/celery_proc.log',
'USERNAME': 'docs', 'READTHE-
DOCS': 'True', 'SUDO_UID': '0',
'VIRTUAL_ENV': '/home/docs', 'SU-
PERVISOR_PROCESS_NAME': 'cel-
ery', 'SUPERVISOR_SERVER_URL':
'unix:///home/docs/run/supervisord-
docs.sock', '_': '/home/docs/bin/supervisord',
'SUDO_COMMAND': '/bin/bash -c
/home/docs/bin/supervisord -nodaemon',
'SUDO_GID': '0', 'CELERY_LOADER':
'djcelery.loaders.DjangoLoader',
'OLDPWD': '/home/docs', 'PWD':
'/home/docs/checkouts/readthedocs.org/readthedocs',
'_MP_FORK_LOGLEVEL_': '20', 'MAIL':
'/var/mail/docs', 'CELERY_LOG_LEVEL':
'20', 'SUPERVISOR_GROUP_NAME':
'celery'}, keep_blank_values=0,
strict_parsing=0)
```

Bases: `cgi.FieldStorage`

make_file (*binary=None*)

read_lines ()

```
class galaxy.web.framework.base.LazyProperty (func)
```

Bases: `object`

Property that replaces itself with a calculated value the first time it is used.

```
class galaxy.web.framework.base.Request (environ)
```

Bases: `webob.Request`

Encapsulates an HTTP request.

base

Property that replaces itself with a calculated value the first time it is used.

browser_url

Property that replaces itself with a calculated value the first time it is used.

cookies

Property that replaces itself with a calculated value the first time it is used.

path

Property that replaces itself with a calculated value the first time it is used.

protocol

Descriptor that delegates a property to a key in the environ member of the associated object (provides property style access to keys in the WSGI environment)

remote_host

Property that replaces itself with a calculated value the first time it is used.

remote_hostname

Property that replaces itself with a calculated value the first time it is used.

remote_port

Descriptor that delegates a property to a key in the environ member of the associated object (provides property style access to keys in the WSGI environment)

class `galaxy.web.framework.base.Response`

Bases: `object`

Describes an HTTP response. Currently very simple since the actual body of the request is handled separately.

get_content_type ()

send_redirect (*url*)

Send an HTTP redirect response to (target *url*)

set_content_type (*type*)

Sets the Content-Type header

wsgi_headeritems ()

Return headers in format appropriate for WSGI *start_response*

wsgi_status ()

Return status line in format appropriate for WSGI *start_response*

class `galaxy.web.framework.base.WSGIEnvironmentProperty` (*key*, *default*='')

Bases: `object`

Descriptor that delegates a property to a key in the environ member of the associated object (provides property style access to keys in the WSGI environment)

class `galaxy.web.framework.base.WebApplication`

Bases: `object`

A simple web application which maps requests to objects using routes, and to methods on those objects in the CherryPy style. Thus simple argument mapping in the CherryPy style occurs automatically, but more complicated encoding of arguments in the PATH_INFO can be performed with routes.

add_api_controller (*controller_name*, *controller*)

add_route (*route*, ***kwargs*)

Add a route to match a URL with a method. Accepts all keyword arguments of *routes.Mapper.connect*. Every route should result in at least a controller value which corresponds to one of the objects added with *add_controller*. It optionally may yield an *action* argument which will be used to locate the method to call on the controller. Additional arguments will be passed to the method as keyword args.

add_ui_controller (*controller_name, controller*)

Add a controller class to this application. A controller class has methods which handle web requests. To connect a URL to a controller's method use *add_route*.

finalize_config ()

Call when application is completely configured and ready to serve requests

handle_controller_exception (*e, trans, **kwargs*)

Allow handling of exceptions raised in controller methods.

handle_request (*environ, start_response*)

make_body_iterable (*trans, body*)

set_transaction_factory (*transaction_factory*)

Use the callable *transaction_factory* to create the transaction which will be passed to requests.

trace (***fields*)

`galaxy.web.framework.base.flatten` (*seq*)

Flatten a possible nested set of iterables

`galaxy.web.framework.base.iterate_file` (*file*)

Progressively return chunks from *file*.

`galaxy.web.framework.base.lazy_property`

alias of *LazyProperty*

`galaxy.web.framework.base.send_file` (*start_response, trans, body*)

openid_manager Module Manage the OpenID consumer and related data stores.

class `galaxy.web.framework.openid_manager.OpenIDManager` (*cache_path*)

Bases: object

CANCEL = 'cancel'

FAILURE = 'failure'

SETUP_NEEDED = 'setup_needed'

SUCCESS = 'success'

add_sreg (*trans, request, required=None, optional=None*)

get_consumer (*trans*)

get_session (*trans*)

get_sreg (*info*)

persist_session (*trans, oidconsumer*)

`galaxy.web.framework.openid_manager.oidlog` (*message, level=0*)

Subpackages

helpers Package

helpers Package Galaxy web framework helpers

`galaxy.web.framework.helpers.css(*args)`

Take a list of stylesheet names (no extension) and return appropriate string of link tags.

Cache-bust with time that server started running on

`galaxy.web.framework.helpers.iff(a, b, c)`

Ternary shortcut

`galaxy.web.framework.helpers.is_true(val)`

Returns true if input is a boolean and true or is a string and looks like a true value.

`galaxy.web.framework.helpers.js(*args)`

Take a prefix and list of javascript names and return appropriate string of script tags.

`galaxy.web.framework.helpers.js_helper(prefix, *args)`

Take a prefix and list of javascript names and return appropriate string of script tags.

Cache-bust with time that server started running on

`galaxy.web.framework.helpers.md5(s)`

Return hex encoded md5 hash of string s

`galaxy.web.framework.helpers.templates(*args)`

Take a list of template names (no extension) and return appropriate string of script tags.

`galaxy.web.framework.helpers.time_ago(x)`

Convert a datetime to a string.

`galaxy.web.framework.helpers.to_unicode(a_string)`

Convert a string to unicode in utf-8 format; if string is already unicode, does nothing because string's encoding cannot be determined by introspection.

`galaxy.web.framework.helpers.truncate(content, length=100, suffix='...')`

Smart string truncation

grids Module

```
class galaxy.web.framework.helpers.grids.BooleanColumn(label,
                                                         key=None,
                                                         model_class=None,
                                                         method=None,
                                                         format=None,
                                                         link=None,
                                                         attach_popup=False,
                                                         visible=True,
                                                         nowrap=False,
                                                         filterable=None,
                                                         sortable=True,
                                                         label_id_prefix=None,
                                                         inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.TextColumn`

`get_single_filter(user, a_filter)`

`sort(trans, query, ascending, column_name=None)`

Sort query using this column.

```
class galaxy.web.framework.helpers.grid CommunityRatingColumn (label, key=None,
                                                                model_class=None,
                                                                method=None,
                                                                format=None,
                                                                link=None, attach_popup=False,
                                                                visible=True,
                                                                nowrap=False,
                                                                filterable=None,
                                                                sortable=True, label_id_prefix=None,
                                                                inbound=False)
```

Bases: `galaxy.web.framework.helpers.grid.GridColumn`,
`galaxy.model.item_attrs.UsesItemRatings`

Column that displays community ratings for an item.

get_value (*trans, grid, item*)

sort (*trans, query, ascending, column_name=None*)

```
class galaxy.web.framework.helpers.grid CommunityTagsColumn (col_name, key,
                                                             model_class=None,
                                                             model_tag_association_class=None,
                                                             filterable=None,
                                                             grid_name=None)
```

Bases: `galaxy.web.framework.helpers.grid.TextColumn`

Column that supports community tags.

filter (*trans, user, query, column_filter*)

Modify query to filter model_class by tag. Multiple filters are ANDed.

get_filter (*trans, user, column_filter*)

get_value (*trans, grid, item*)

```
class galaxy.web.framework.helpers.grid DateTimeColumn (label, key=None,
                                                         model_class=None,
                                                         method=None,
                                                         format=None, link=None,
                                                         attach_popup=False, visible=True,
                                                         nowrap=False, filterable=None,
                                                         sortable=True, label_id_prefix=None,
                                                         inbound=False)
```

Bases: `galaxy.web.framework.helpers.grid.TextColumn`

sort (*trans, query, ascending, column_name=None*)

Sort query using this column.

```
class galaxy.web.framework.helpers.grid DeletedColumn (label, key=None,
                                                        model_class=None,
                                                        method=None,
                                                        format=None, link=None,
                                                        attach_popup=False, visible=True,
                                                        nowrap=False, filterable=None,
                                                        sortable=True, label_id_prefix=None,
                                                        inbound=False)
```

Bases: *galaxy.web.framework.helpers.grid.GridColumn*

Column that tracks and filters for items with deleted attribute.

filter (*trans, user, query, column_filter*)

Modify query to filter self.model_class by state.

get_accepted_filters ()

Returns a list of accepted filters for this column.

class *galaxy.web.framework.helpers.grid.DisplayByUsernameAndSlugGridOperation* (*label,*
key=None,
con-
di-
tion=None,
al-
low_multiple=True,
al-
low_popup=True,
tar-
get=None,
url_args=None,
async_compatible=1,
con-
firm=None,
global_operation=None,
in-
bound=False)

Bases: *galaxy.web.framework.helpers.grid.GridOperation*

Operation to display an item by username and slug.

get_url_args (*item*)

class *galaxy.web.framework.helpers.grid.Grid*

Bases: object

Specifies the content and format of a grid (data table).

apply_query_filter (*trans, query, **kwargs*)

async_template = 'grid_base_async.mako'

build_initial_query (*trans, **kwargs*)

columns = []

cur_filter_pref_name = '.filter'

cur_sort_key_pref_name = '.sort_key'

default_filter = {}

default_sort_key = None

exposed = True

get_current_item (*trans, **kwargs*)

get_ids (***kwargs*)

global_actions = []

handle_operation (*trans, operation, ids, **kwargs*)

```
info_text = None
legend = None
model_class = None
num_page_links = 10
num_rows_per_page = 25
operations = []
pass_through_operations = {}
preserve_state = False
show_item_checkboxes = False
standard_filters = []
template = 'grid_base.mako'
title = ''
use_async = False
use_hide_message = True
use_paging = False
```

```
class galaxy.web.framework.helpers.grids.GridAction(label=None, url_args=None, in-
                                                    bound=False)
```

Bases: object

```
class galaxy.web.framework.helpers.grids.GridColumn(label,                                key=None,
                                                    model_class=None, method=None,
                                                    format=None,          link=None,
                                                    attach_popup=False,        visi-
                                                    ble=True,    nowrap=False,  fil-
                                                    terable=None,    sortable=True,
                                                    label_id_prefix=None,      in-
                                                    bound=False)
```

Bases: object

```
filter (trans, user, query, column_filter)
    Modify query to reflect the column filter.
```

```
get_accepted_filters ()
    Returns a list of accepted filters for this column.
```

```
get_link (trans, grid, item)
```

```
get_value (trans, grid, item)
```

```
sort (trans, query, ascending, column_name=None)
    Sort query using this column.
```

```
class galaxy.web.framework.helpers.grids.GridColumnFilter(label, args=None)
```

Bases: object

```
get_url_args ()
```



```
class galaxy.web.framework.helpers.grids.GridOperation(label,      key=None,      con-
                                                         dition=None,      al-
                                                         low_multiple=True,      al-
                                                         low_popup=True,      tar-
                                                         get=None,      url_args=None,
                                                         async_compatible=False,
                                                         confirm=None,
                                                         global_operation=None,
                                                         inbound=False)
```

Bases: object

allowed(item)

get_url_args(item)

```
class galaxy.web.framework.helpers.grids.IndividualTagsColumn(col_name,      key,
                                                         model_class=None,
                                                         model_tag_association_class=None,
                                                         filterable=None,
                                                         grid_name=None)
```

Bases: *galaxy.web.framework.helpers.grids.CommunityTagsColumn*

Column that supports individual tags.

get_filter(trans, user, column_filter)

get_value(trans, grid, item)

```
class galaxy.web.framework.helpers.grids.IntegerColumn(label,      key=None,
                                                         model_class=None,
                                                         method=None,      for-
                                                         mat=None,      link=None,
                                                         attach_popup=False,      visi-
                                                         ble=True,      nowrap=False,      fil-
                                                         terable=None,      sortable=True,
                                                         label_id_prefix=None,      in-
                                                         bound=False)
```

Bases: *galaxy.web.framework.helpers.grids.TextColumn*

Integer column that employs freetext, but checks that the text is an integer, so support filtering on integer values.

IMPORTANT NOTE: grids that use this column type should not include the column in the cols_to_filter list of MulticolFilterColumn (i.e., searching on this column type should not be performed in the grid's standard search - it won't throw exceptions, but it also will not find what you're looking for). Grids that search on this column should use 'filterable="advanced"' so that searching is only performed in the advanced search component, restricting the search to the specific column.

This is useful for searching on object ids or other integer columns. See the JobIdColumn column in the SpecifiedDateListGrid class in the jobs controller of the reports webapp for an example.

get_single_filter(user, a_filter)

sort(trans, query, ascending, column_name=None)

Sort query using this column.

```
class galaxy.web.framework.helpers.grids.MulticolFilterColumn(col_name,
                                                         cols_to_filter,
                                                         key,      visible,      fil-
                                                         terable='default')
```

Bases: *galaxy.web.framework.helpers.grids.TextColumn*

Column that performs multicolumn filtering.

filter (*trans, user, query, column_filter*)

Modify query to filter model_class by tag. Multiple filters are ANDed.

```
class galaxy.web.framework.helpers.grids.OwnerAnnotationColumn (col_name,      key,
                                                                model_class=None,
                                                                model_annotation_association_class=None,
                                                                filterable=None)
```

Bases: *galaxy.web.framework.helpers.grids.TextColumn*,
galaxy.model.item_attrs.UsesAnnotations

Column that displays and filters item owner's annotations.

get_single_filter (*user, a_filter*)

Filter by annotation and annotation owner.

get_value (*trans, grid, item*)

Returns first 150 characters of annotation.

```
class galaxy.web.framework.helpers.grids.OwnerColumn (label,                      key=None,
                                                         model_class=None,
                                                         method=None,      format=None,
                                                         link=None,  attach_popup=False,
                                                         visible=True,  nowrap=False,  filterable=None,
                                                         sortable=True,
                                                         label_id_prefix=None,      in-bound=False)
```

Bases: *galaxy.web.framework.helpers.grids.TextColumn*

Column that lists item's owner.

get_value (*trans, grid, item*)

sort (*trans, query, ascending, column_name=None*)

Sort column using case-insensitive alphabetical sorting on item's username.

```
class galaxy.web.framework.helpers.grids.PublicURLColumn (label,                      key=None,
                                                         model_class=None,
                                                         method=None,      format=None,
                                                         link=None,  attach_popup=False,
                                                         visible=True,  nowrap=False,
                                                         filterable=None,
                                                         sortable=True,      label_id_prefix=None,
                                                         in-bound=False)
```

Bases: *galaxy.web.framework.helpers.grids.TextColumn*

Column displays item's public URL based on username and slug.

get_link (*trans, grid, item*)

```
class galaxy.web.framework.helpers.grids.ReverseSortColumn(label, key=None,
                                                            model_class=None,
                                                            method=None, format=None, link=None,
                                                            attach_popup=False,
                                                            visible=True,
                                                            nowrap=False,
                                                            filterable=None,
                                                            sortable=True, label_id_prefix=None,
                                                            inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.GridColumn`

Column that reverses sorting; this is useful when the natural sort is descending.

sort (*trans, query, ascending, column_name=None*)

```
class galaxy.web.framework.helpers.grids.SharingStatusColumn(label, key=None,
                                                            model_class=None,
                                                            method=None,
                                                            format=None,
                                                            link=None, attach_popup=False,
                                                            visible=True,
                                                            nowrap=False,
                                                            filterable=None,
                                                            sortable=True, label_id_prefix=None,
                                                            inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.GridColumn`

Grid column to indicate sharing status.

filter (*trans, user, query, column_filter*)
 Modify query to filter histories by sharing status.

get_accepted_filters ()
 Returns a list of accepted filters for this column.

get_link (*trans, grid, item*)

get_value (*trans, grid, item*)

```
class galaxy.web.framework.helpers.grids.StateColumn(label, key=None,
                                                       model_class=None,
                                                       method=None, format=None,
                                                       link=None, attach_popup=False,
                                                       visible=True, nowrap=False, filterable=None,
                                                       sortable=True, label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.GridColumn`

Column that tracks and filters for items with state attribute.

IMPORTANT NOTE: self.model_class must have a states Bunch or dict if this column type is used in the grid.

filter (*trans, user, query, column_filter*)
 Modify query to filter self.model_class by state.

get_accepted_filters()

Returns a list of accepted filters for this column.

get_value(*trans, grid, item*)

```
class galaxy.web.framework.helpers.grids.TextColumn(label,
                                                    key=None,
                                                    model_class=None, method=None,
                                                    format=None,      link=None,
                                                    attach_popup=False,    visi-
                                                    ble=True,    nowrap=False,    fil-
                                                    terable=None,    sortable=True,
                                                    label_id_prefix=None,    in-
                                                    bound=False)
```

Bases: *galaxy.web.framework.helpers.grids.GridColumn*

Generic column that employs freetext and, hence, supports freetext, case-independent filtering.

filter(*trans, user, query, column_filter*)

Modify query to filter using free text, case independence.

get_filter(*trans, user, column_filter*)

Returns a SQLAlchemy criterion derived from *column_filter*.

get_single_filter(*user, a_filter*)

Returns a SQLAlchemy criterion derived for a single filter. Single filter is the most basic filter—usually a string—and cannot be a list.

sort(*trans, query, ascending, column_name=None*)

Sort column using case-insensitive alphabetical sorting.

middleware Package

middleware Package WSGI Middleware.

profile Module Middleware that profiles the request with cProfile and displays profiling information at the bottom of each page.

```
class galaxy.web.framework.middleware.profile.ProfileMiddleware(app,
                                                                global_conf=None,
                                                                limit=40)
```

Bases: object

Middleware that profiles all requests.

All HTML pages will have profiling information appended to them. The data is isolated to that single request, and does not include data from previous requests.

galaxy.web.framework.middleware.profile.func_std_string(*func_name*)

Match what old profile produced

galaxy.web.framework.middleware.profile.get_func_list(*stats, sel_list*)

Use 'sel_list' to select a list of functions to display.

galaxy.web.framework.middleware.profile.pstats_as_html(*stats, *sel_list*)

Return an HTML representation of a *pstats.Stats* object.

remoteuser Module Middleware for handling \$REMOTE_USER if use_remote_user is enabled.

```
class galaxy.web.framework.middleware.remoteuser.RemoteUser (app, maildomain=None,
                                                             display_servers=None,
                                                             admin_users=None, re-
                                                             mote_user_header=None, re-
                                                             mote_user_secret_header=None)

Bases: object

error (start_response, title='Access denied', message='Please contact your local Galaxy administra-
tor:')
```

static Module

```
class galaxy.web.framework.middleware.static.CacheableStaticURLParser (directory,
                                                                       cache_seconds=None)

Bases: paste.urlparser.StaticURLParser
galaxy.web.framework.middleware.static.make_static (global_conf, document_root,
                                                    cache_seconds=None)
```

translogger Module Middleware for logging requests, using Apache combined log format

```
class galaxy.web.framework.middleware.translogger.TransLogger (application, logger=None, for-
                                                                mat=None, log-
                                                                ging_level=20, log-
                                                                ger_name='wsgi',
                                                                setup_console_handler=True,
                                                                set_logger_level=10)

Bases: object
```

This logging middleware will log all requests as they go through. They are, by default, sent to a logger named 'wsgi' at the INFO level.

If setup_console_handler is true, then messages for the named logger will be sent to the console.

```
format = '%(REMOTE_ADDR)s - %(REMOTE_USER)s [%(time)s] “%(REQUEST_METHOD)s %(REQUEST_URI)s”
write_log (environ, method, req_uri, start, status, bytes)
```

```
galaxy.web.framework.middleware.translogger.make_filter (app, global_conf, logger_name='wsgi',
                                                         format=None, log-
                                                         ging_level=20,
                                                         setup_console_handler=True,
                                                         set_logger_level=10)
```

This logging middleware will log all requests as they go through. They are, by default, sent to a logger named 'wsgi' at the INFO level.

If setup_console_handler is true, then messages for the named logger will be sent to the console.

xforwardedhost Module

```
class galaxy.web.framework.middleware.xforwardedhost.XForwardedHostMiddleware (app,
                                                                                global_conf=None)

Bases: object
```

A WSGI middleware that changes the HTTP host header in the WSGI environ based on the X-Forwarded-Host header IF found

security Package

security Package

class galaxy.web.security.**SecurityHelper** (***config*)

Bases: object

decode_guid (*session_key*)

decode_id (*obj_id*, *kind=None*)

encode_all_ids (*rval*, *recursive=False*)

Encodes all integer values in the dict *rval* whose keys are ‘id’ or end with ‘_id’ excluding *tool_id* which are consumed and produced as is via the API.

encode_dict_ids (*a_dict*, *kind=None*)

Encode all ids in dictionary. Ids are identified by (a) an ‘id’ key or (b) a key that ends with ‘_id’

encode_guid (*session_key*)

encode_id (*obj_id*, *kind=None*)

get_new_guid ()

galaxy.web.security.**get_random_bytes** (*nbytes*)

webapps Package

webapps Package Galaxy webapps root package – this is a namespace package.

Subpackages

community Package

community Package

app Module

buildapp Module

config Module

Subpackages

controllers Package

controllers Package

admin Module

common Module

hg Module

repository Module

repository_review Module

upload Module

user Module

framework Package

framework Package

Subpackages

middleware Package

middleware Package

hg Module

remoteuser Module

model Package

model Package

mapping Module

Subpackages

migrate Package

check Module

security Package

security Package

util Package

container_util Module

hgweb_config Module

shed_statistics Module

workflow_util Module

galaxy Package

buildapp Module

Subpackages

Galaxy API Documentation

Background In addition to being accessible through a web interface, Galaxy can also be accessed programmatically, through shell scripts and other programs. The web interface is appropriate for things like exploratory analysis, visualization, construction of workflows, and rerunning workflows on new datasets.

The web interface is less suitable for things like

- Connecting a Galaxy instance directly to your sequencer and running workflows whenever data is ready.
- Running a workflow against multiple datasets (which can be done with the web interface, but is tedious).
- When the analysis involves complex control, such as looping and branching.

The Galaxy API addresses these and other situations by exposing Galaxy internals through an additional interface, known as an Application Programming Interface, or API.

Quickstart Log in as your user, navigate to the API Keys page in the User menu, and generate a new API key. Make a note of the API key, and then pull up a terminal. Now we'll use the `display.py` script in your `galaxy/scripts/api` directory for a short example:

```
% ./display.py my_key http://localhost:4096/api/histories
Collection Members
-----
#1: /api/histories/8c49be448cfe29bc
    name: Unnamed history
    id: 8c49be448cfe29bc
#2: /api/histories/33b43b4e7093c91f
    name: output test
    id: 33b43b4e7093c91f
```

The result is a Collection of the histories of the user specified by the API key (you). To look at the details of a particular history, say #1 above, do the following:


```
% ./display.py my_key http://localhost:4096/api/histories/8c49be448cfe29bc
Member Information
-----
state_details: {'ok': 1, 'failed_metadata': 0, 'upload': 0, 'discarded': 0, 'running': 0, 'setting_m
state: ok
contents_url: /api/histories/8c49be448cfe29bc/contents
id: 8c49be448cfe29bc
name: Unnamed history
```

This gives detailed information about the specific member in question, in this case the History. To view history contents, do the following:

```
% ./display.py my_key http://localhost:4096/api/histories/8c49be448cfe29bc/contents
Collection Members
-----
#1: /api/histories/8c49be448cfe29bc/contents/6f91353f3eb0fa4a
    name: Pasted Entry
    type: file
    id: 6f91353f3eb0fa4a
```

What we have here is another Collection of items containing all of the datasets in this particular history. Finally, to view details of a particular dataset in this collection, execute the following:

```
% ./display.py my_key http://localhost:4096/api/histories/8c49be448cfe29bc/contents/6f91353f3eb0fa4a
Member Information
-----
misc_blurb: 1 line
name: Pasted Entry
data_type: txt
deleted: False
file_name: /Users/yoplait/work/galaxy-stock/database/files/000/dataset_82.dat
state: ok
download_url: /datasets/6f91353f3eb0fa4a/display?to_ext=txt
visible: True
genome_build: ?
model_class: HistoryDatasetAssociation
file_size: 17
metadata_data_lines: 1
id: 6f91353f3eb0fa4a
misc_info: uploaded txt file
metadata_dbkey: ?
```

And now you've successfully used the API to request and select a history, browse the contents of that history, and then look at detailed information about a particular dataset.

For a more comprehensive Data Library example, set the following option in your galaxy.ini as well, and restart galaxy again:

```
admin_users = you@example.org
library_import_dir = /path/to/some/directory
```

In the directory you specified for 'library_import_dir', create some subdirectories, and put (or symlink) files to import into Galaxy into those subdirectories.

In Galaxy, create an account that matches the address you put in 'admin_users', then browse to that user's preferences and generate a new API Key. Copy the key to your clipboard and then use these scripts:

```
% ./display.py my_key http://localhost:4096/api/libraries
Collection Members
-----

0 elements in collection

% ./library_create_library.py my_key http://localhost:4096/api/libraries api_test 'API Test Library'
Response
-----
/api/libraries/f3f73e481f432006
  name: api_test
  id: f3f73e481f432006

% ./display.py my_key http://localhost:4096/api/libraries
Collection Members
-----
/api/libraries/f3f73e481f432006
  name: api_test
  id: f3f73e481f432006

% ./display.py my_key http://localhost:4096/api/libraries/f3f73e481f432006
Member Information
-----
synopsis: None
contents_url: /api/libraries/f3f73e481f432006/contents
description: API Test Library
name: api_test

% ./display.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents
Collection Members
-----
/api/libraries/f3f73e481f432006/contents/28202595c0d2591f61ddda595d2c3670
  name: /
  type: folder
  id: 28202595c0d2591f61ddda595d2c3670

% ./library_create_folder.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents 28202595c0d2591f61ddda595d2c3670
Response
-----
/api/libraries/f3f73e481f432006/contents/28202595c0d2591fa4f9089d2303fd89
  name: api_test_folder1
  id: 28202595c0d2591fa4f9089d2303fd89

% ./library_upload_from_import_dir.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents/28202595c0d2591fa4f9089d2303fd89
Response
-----
/api/libraries/f3f73e481f432006/contents/e9ef7fdb2db87d7b
  name: 2.bed
  id: e9ef7fdb2db87d7b
/api/libraries/f3f73e481f432006/contents/3b7f6a31f80a5018
  name: 3.bed
  id: 3b7f6a31f80a5018

% ./display.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents
Collection Members
-----
/api/libraries/f3f73e481f432006/contents/28202595c0d2591f61ddda595d2c3670
  name: /
```

```

    type: folder
    id: 28202595c0d2591f61ddda595d2c3670
/api/libraries/f3f73e481f432006/contents/28202595c0d2591fa4f9089d2303fd89
    name: /api_test_folder1
    type: folder
    id: 28202595c0d2591fa4f9089d2303fd89
/api/libraries/f3f73e481f432006/contents/e9ef7fdb2db87d7b
    name: /api_test_folder1/2.bed
    type: file
    id: e9ef7fdb2db87d7b
/api/libraries/f3f73e481f432006/contents/3b7f6a31f80a5018
    name: /api_test_folder1/3.bed
    type: file
    id: 3b7f6a31f80a5018

% ./display.py my_key http://localhost:4096/api/libraries/f3f73e481f432006/contents/e9ef7fdb2db87d7b
Member Information
-----
misc_blurb: 68 regions
metadata_endCol: 3
data_type: bed
metadata_columns: 6
metadata_nameCol: 4
uploaded_by: nate@...
metadata_strandCol: 6
name: 2.bed
genome_build: hg19
metadata_comment_lines: None
metadata_startCol: 2
metadata_chromCol: 1
file_size: 4272
metadata_data_lines: 68
message:
metadata_dbkey: hg19
misc_info: uploaded bed file
date_uploaded: 2010-06-22T17:01:51.266119
metadata_column_types: str, int, int, str, int, str

```

Other parameters are valid when uploading, they are the same parameters as are used in the web form, like 'link_data_only' and etc.

The request and response format should be considered alpha and are subject to change.

API Design Guidelines The following section outlines guidelines related to extending and/or modifying the Galaxy API. The Galaxy API has grown in an ad-hoc fashion over time by many contributors and so clients SHOULD NOT expect the API will conform to these guidelines - but developers contributing to the Galaxy API SHOULD follow these guidelines.

- API functionality should include docstring documentation for consumption by readthedocs.org.
- Developers should familiarize themselves with the HTTP status code definitions <http://www.w3.org/Protocols/rfc2616/rfc2616-sec10.html>. The API responses should properly set the status code according to the result - in particular 2XX responses should be used for successful requests, 4XX for various kinds of client errors, and 5XX for the errors on the server side.
- If there is an error processing some part of request (one item in a list for instance), the status code should be set to reflect the error and the partial result may or may not be returned depending on the controller - this behavior should be documented.

- API methods should throw a finite number of exceptions (defined in [exceptions Package](#)) and these should subclass *MessageException* and not paste/wsgi HTTP exceptions. When possible, the framework itself should be responsible catching these exceptions, setting the status code, and building an error response.
- Error responses should not consist of plain text strings - they should be dictionaries describing the error and containing the following:

```
{
  "status_code": 400,
  "err_code": 400007,
  "err_msg": "Request contained invalid parameter, action could not be completed.",
  "type": "error",
  "extra_error_info": "Extra information."
}
```

Various error conditions (once a format has been chosen and framework to enforce it in place) should be spelled out in this document.

- Backward compatibility is important and should be maintained when possible. If changing behavior in a non-backward compatible way please ensure one of the following holds - there is a strong reason to believe no consumers depend on a behavior, the behavior is effectively broken, or the API method being modified has not been part of a tagged dist release.

The following bullet points represent good practices more than guidelines, please consider them when modifying the API.

- Functionality should not be copied and pasted between controllers - consider refactoring functionality into associated classes or short of that into Mixins (http://en.wikipedia.org/wiki/Composition_over_inheritance) or into Managers ([managers Package](#)).
- API additions are more permanent changes to Galaxy than many other potential changes and so a second opinion on API changes should be sought. (Consider a pull request!)
- New API functionality should include functional tests. These functional tests should be implemented in Python and placed in *test/functional/api*. (Once such a framework is in place - it is not right now).
- Changes to reflect modifications to the API should be pushed upstream to the BioBlend project if possible.

Longer term goals/notes.

- It would be advantageous to have a clearer separation of anonymous and admin handling functionality.
- If at some point in the future, functionality needs to be added that breaks backward compatibility in a significant way to a component used by the community - a “dev” variant of the API will be established and the community should be alerted and given a timeframe for when the old behavior will be replaced with the new behavior.
- Consistent standards for range-based requests, batch requests, filtered requests, etc... should be established and documented here.

API Controllers Galaxy offers the following API controllers:

annotations Module API operations on annotations.

```
class galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController(app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesStore, galaxy.model.item_attrs.UsesAnnotations

    create (trans, *args, **kwargs)
    delete (trans, *args, **kwargs)
```

```

    index (trans, *args, **kwargs)
    undelele (trans, *args, **kwargs)
class galaxy.webapps.galaxy.api.annotations.HistoryAnnotationsController (app)
    Bases: galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController

    controller_name = 'history_annotations'
    tagged_item_id = 'history_id'
class galaxy.webapps.galaxy.api.annotations.HistoryContentAnnotationsController (app)
    Bases: galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController

    controller_name = 'history_content_annotations'
    tagged_item_id = 'history_content_id'
class galaxy.webapps.galaxy.api.annotations.WorkflowAnnotationsController (app)
    Bases: galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController

    controller_name = 'workflow_annotations'
    tagged_item_id = 'workflow_id'

```

authenticate Module API key retrieval through BaseAuth Sample usage:

```
curl -user zipzap@foo.com:password http://localhost:8080/api/authenticate/baseauth
```

Returns:

```
{ "api_key": "baa4d6e3a156d3033f05736255f195f9"
}
```

```

class galaxy.webapps.galaxy.api.authenticate.AuthenticationController (app)
    Bases: galaxy.web.base.controller.BaseAPIController

    get_api_key (trans, *args, **kwargs)
        def get_api_key( self, trans, **kwd ) * GET /api/authenticate/baseauth
            returns an API key for authenticated user based on BaseAuth headers

            Returns api_key in json format
            Return type dict
            Raises ObjectNotFound, HTTPBadRequest

```

configuration Module API operations allowing clients to determine Galaxy instance's capabilities and configuration settings.

```

class galaxy.webapps.galaxy.api.configuration.ConfigurationController (app)
    Bases: galaxy.web.base.controller.BaseAPIController

    dynamic_tool_confs (trans, *args, **kwargs)

    get_config_dict (trans, return_admin=False, view=None, keys=None, default_view='all')
        Return a dictionary with (a subset of) current Galaxy settings.

        If return_admin also include a subset of more sensitive keys. Pass in view (String) and comma seperated
        list of keys to control which configuration settings are returned.

```

index (*trans*, **args*, ***kwargs*)

GET /api/configuration Return an object containing exposable configuration settings.

Note: a more complete list is returned if the user is an admin.

tool_lineages (*trans*, **args*, ***kwargs*)

version (*trans*, **args*, ***kwargs*)

GET /api/version Return a description of the major version of Galaxy (e.g. 15.03).

Return type dict

Returns dictionary with major version keyed on 'version_major'

dataset_collections Module

class galaxy.webapps.galaxy.api.dataset_collections.**DatasetCollectionsController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*, *galaxy.web.base.controller.UsesLibraries*

create (*trans*, **args*, ***kwargs*)

•**POST /api/dataset_collections:** create a new dataset collection instance.

Parameters **payload** (*dict*) – (optional) dictionary structure containing: * *collection_type*: dataset colltion type to create. * *instance_type*: Instance type - 'history' or 'library'. * *name*: the new dataset collections's name * *datasets*: object describing datasets for collection

Return type dict

Returns element view of new dataset collection

index (*trans*, **args*, ***kwargs*)

show (*trans*, **args*, ***kwargs*)

datasets Module

datatypes Module API operations allowing clients to determine datatype supported by Galaxy.

class galaxy.webapps.galaxy.api.datatypes.**DatatypesController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

converters (*trans*, **args*, ***kwargs*)

edam_formats (*trans*, **args*, ***kwargs*)

index (*trans*, **args*, ***kwargs*)

GET /api/datatypes Return an object containing upload datatypes.

mapping (*trans*, **args*, ***kwargs*)

GET /api/datatypes/mapping Return a dictionary of class to class mappings.

sniffers (*trans*, **args*, ***kwargs*)

GET /api/datatypes/sniffers Return a list of sniffers.

extended_metadata Module API operations on annotations.

```
class galaxy.webapps.galaxy.api.extended_metadata.BaseExtendedMetadataController (app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesExtendedMetadata, galaxy.web.base.controller.UsesLibraryMixinItems, galaxy.web.base.controller.UsesStoredMetadata
```

```
    create (trans, *args, **kwargs)
```

```
    delete (trans, *args, **kwargs)
```

```
    index (trans, *args, **kwargs)
```

```
    undelele (trans, *args, **kwargs)
```

```
class galaxy.webapps.galaxy.api.extended_metadata.HistoryDatasetExtendMetadataController (app)
    Bases: galaxy.webapps.galaxy.api.extended_metadata.BaseExtendedMetadataController
```

```
    controller_name = 'history_dataset_extended_metadata'
```

```
    exmeta_item_id = 'history_content_id'
```

```
class galaxy.webapps.galaxy.api.extended_metadata.LibraryDatasetExtendMetadataController (app)
    Bases: galaxy.webapps.galaxy.api.extended_metadata.BaseExtendedMetadataController
```

```
    controller_name = 'library_dataset_extended_metadata'
```

```
    exmeta_item_id = 'library_content_id'
```

folder_contents Module API operations on the contents of a library folder.

```
class galaxy.webapps.galaxy.api.folder_contents.FolderContentsController (app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesLibraryFolder, galaxy.web.base.controller.UsesLibraryMixinItems
```

Class controls retrieval, creation and updating of folder contents.

```
build_path (trans, folder)
```

Search the path upwards recursively and load the whole route of names and ids for breadcrumb building purposes.

Parameters

- **folder** – current folder for navigating up
- **type** – Galaxy LibraryFolder

Returns list consisting of full path to the library

Type list

```
create (self, trans, library_id, payload, **kwd)
```

• **POST /api/folders/{encoded_id}/contents** create a new library file from an HDA

Parameters **payload** – dictionary structure containing:

Returns a dictionary containing the id, name, and ‘show’ url of the new item

Return type dict

Raises `ObjectAttributeInvalidException`, `InsufficientPermissionsException`, `ItemAccessibilityException`, `InternalServerError`

index (*trans*, *args, **kwargs)

GET /api/folders/{encoded_folder_id}/contents

Displays a collection (list) of a folder's contents (files and folders). Encoded folder ID is prepended with 'F' if it is a folder as opposed to a data set which does not have it. Full path is provided in response as a separate object providing data for breadcrumb path building.

Parameters

- **folder_id** (*encoded string*) – encoded ID of the folder which contents should be library_dataset_dict
- **kwd** (*dict*) – keyword dictionary with other params

Returns dictionary containing all items and metadata

Type dict

Raises MalformedId, InconsistentDatabase, ObjectNotFound, InternalServerError

show (*trans*, *args, **kwargs)

GET /api/folders/{encoded_folder_id}/

update (*trans*, *args, **kwargs)

PUT /api/folders/{encoded_folder_id}/contents

folders Module API operations on library folders.

class galaxy.webapps.galaxy.api.folders.**FoldersController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesLibraryMixinItems*

create (*self*, *trans*, *encoded_parent_folder_id*, **kwd)

*POST /api/folders/{encoded_parent_folder_id}

Create a new folder object underneath the one specified in the parameters.

Parameters

- **encoded_parent_folder_id** (*an encoded id string (should be prefixed by 'F')*) – the parent folder's id (required)
- **name** (*str*) – the name of the new folder (required)
- **description** (*str*) – the description of the new folder

Returns information about newly created folder, notably including ID

Return type dictionary

Raises RequestParameterMissingException

delete (*self*, *trans*, *id*, **kwd)

- **DELETE /api/folders/{id}** marks the folder with the given *id* as *deleted* (or removes the *deleted* mark if the *undelete* param is true)

Note: Currently, only admin users can un/delete folders.

Parameters

- **id** (*an encoded id string*) – the encoded id of the folder to un/delete

- **undelete** (*bool*) – (optional) flag specifying whether the item should be deleted or undeleted, defaults to false:

Returns detailed folder information

Return type dictionary

Raises ItemAccessibilityException, MalformedId, ObjectNotFound

get_permissions (*trans, *args, **kwargs*)

- GET /api/folders/{id}/permissions

Load all permissions for the given folder id and return it.

Parameters

- **encoded_folder_id** (*an encoded id string*) – the encoded id of the folder
- **scope** (*string*) – either ‘current’ or ‘available’

Returns dictionary with all applicable permissions’ values

Return type dictionary

Raises ObjectNotFound, InsufficientPermissionsException

index (*trans, *args, **kwargs*)

*GET /api/folders/ This would normally display a list of folders. However, that would be across multiple libraries, so it’s not implemented.

set_permissions (*trans, *args, **kwargs*)

def set_permissions(self, trans, encoded_folder_id, **kwd): *POST
/api/folders/{encoded_folder_id}/permissions

Parameters

- **encoded_folder_id** (*an encoded id string*) – the encoded id of the folder to set the permissions of
- **action** (*string*) – (required) describes what action should be performed available actions: set_permissions
- **add_ids** [] (*string or list*) – list of Role.id defining roles that should have add item permission on the folder
- **manage_ids** [] (*string or list*) – list of Role.id defining roles that should have manage permission on the folder
- **modify_ids** [] (*string or list*) – list of Role.id defining roles that should have modify permission on the folder

Return type dictionary

Returns dict of current roles for all available permission types.

Raises RequestParameterInvalidException, ObjectNotFound, InsufficientPermissionsException, InternalServerError RequestParameterMissingException

show (*self, trans, id, **kwd*)

*GET /api/folders/{encoded_folder_id}

Displays information about a folder.

Parameters `id` (an encoded id string (has to be prefixed by 'F')) – the folder's encoded id (required)

Returns dictionary including details of the folder

Return type dict

update (*trans*, *args, **kwargs)
PUT /api/folders/{encoded_folder_id}

forms Module API operations on FormDefinition objects.

class `galaxy.webapps.galaxy.api.forms.FormDefinitionAPIController` (*app*)
Bases: `galaxy.web.base.controller.BaseAPIController`

create (*trans*, *args, **kwargs)
POST /api/forms Creates a new form.

index (*trans*, *args, **kwargs)
GET /api/forms Displays a collection (list) of forms.

show (*trans*, *args, **kwargs)
GET /api/forms/{encoded_form_id} Displays information about a form.

ftp_files Module

genomes Module

class `galaxy.webapps.galaxy.api.genomes.GenomesController` (*app*)
Bases: `galaxy.web.base.controller.BaseAPIController`

RESTful controller for interactions with genome data.

index (*trans*, *args, **kwargs)
GET /api/genomes: returns a list of installed genomes

show (*trans*, *args, **kwargs)
GET /api/genomes/{id}

Returns information about build <id>

`galaxy.webapps.galaxy.api.genomes.get_id` (*base*, *format*)

group_roles Module API operations on Group objects.

class `galaxy.webapps.galaxy.api.group_roles.GroupRolesAPIController` (*app*)
Bases: `galaxy.web.base.controller.BaseAPIController`

delete (*trans*, *args, **kwargs)
DELETE /api/groups/{encoded_group_id}/roles/{encoded_role_id} Removes a role from a group

index (*trans*, *args, **kwargs)
GET /api/groups/{encoded_group_id}/roles Displays a collection (list) of groups.

show (*trans*, *args, **kwargs)
GET /api/groups/{encoded_group_id}/roles/{encoded_role_id} Displays information about a group role.

update (*trans*, *args, **kwargs)
PUT /api/groups/{encoded_group_id}/roles/{encoded_role_id} Adds a role to a group

group_users Module API operations on Group objects.

```
class galaxy.webapps.galaxy.api.group_users.GroupUsersAPIController (app)
    Bases: galaxy.web.base.controller.BaseAPIController

    delete (trans, *args, **kwargs)
        DELETE /api/groups/{encoded_group_id}/users/{encoded_user_id} Removes a user from a group

    index (trans, *args, **kwargs)
        GET /api/groups/{encoded_group_id}/users Displays a collection (list) of groups.

    show (trans, *args, **kwargs)
        GET /api/groups/{encoded_group_id}/users/{encoded_user_id} Displays information about a group user.

    update (trans, *args, **kwargs)
        PUT /api/groups/{encoded_group_id}/users/{encoded_user_id} Adds a user to a group
```

groups Module API operations on Group objects.

```
class galaxy.webapps.galaxy.api.groups.GroupAPIController (app)
    Bases: galaxy.web.base.controller.BaseAPIController

    create (trans, *args, **kwargs)
        POST /api/groups Creates a new group.

    index (trans, *args, **kwargs)
        GET /api/groups Displays a collection (list) of groups.

    show (trans, *args, **kwargs)
        GET /api/groups/{encoded_group_id} Displays information about a group.

    update (trans, *args, **kwargs)
        PUT /api/groups/{encoded_group_id} Modifies a group.
```

histories Module API operations on a history.

See also:

galaxy.model.History

```
class galaxy.webapps.galaxy.api.histories.HistoriesController (app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.ExportsHistoryMixin, galaxy.web.base.controller.ImportsHistoryMixin

    archive_download (trans, *args, **kwargs)
        export_download( self, trans, id, jeha_id ) * GET /api/histories/{id}/exports/{jeha_id}:

            If ready and available, return raw contents of exported history. Use/poll “PUT
            /api/histories/{id}/exports” to initiate the creation of such an export - when ready that route
            will return 200 status code (instead of 202) with a JSON dictionary containing a download_url.

    archive_export (trans, *args, **kwargs)
        export_archive( self, trans, id, payload ) * PUT /api/histories/{id}/exports:

            start job (if needed) to create history export for corresponding history.

    Parameters id (str) – the encoded id of the history to export

    Return type dict

    Returns object containing url to fetch export from.
```

citations (*trans*, *args, **kwargs)

create (*trans*, *payload*)

•**POST /api/histories:** create a new history

Parameters

- **payload** (*dict*) – (optional) dictionary structure containing: * **name**: the new history's name * **history_id**: the id of the history to copy * **archive_source**: the url that will generate the archive to import * **archive_type**: 'url' (default)
- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type dict

Returns element view of new history

delete (*self*, *trans*, *id*, **kwd)

•**DELETE /api/histories/{id}** delete the history with the given *id*

Note: Stops all active jobs in the history if purge is set.

Parameters

- **id** (*str*) – the encoded id of the history to delete
- **kwd** (*dict*) – (optional) dictionary structure containing extra parameters

You can purge a history, removing all it's datasets from disk (if unshared), by passing in `purge=True` in the url.

Parameters

- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type dict

Returns the deleted or purged history

index (*trans*, *deleted*=*False*)

•**GET /api/histories:** return undeleted histories for the current user

•**GET /api/histories/deleted:** return deleted histories for the current user

Note: Anonymous users are allowed to get their current history

Parameters **deleted** (*boolean*) – if True, show only deleted histories, if False, non-deleted

Return type *list*

Returns list of dictionaries containing summary history information

The following are optional parameters:

view: string, one of ('summary','detailed'), defaults to 'summary' controls which set of properties to return

keys: comma separated strings, unused by default keys/names of individual properties to return

If neither keys or views are sent, the default view (set of keys) is returned. If both a view and keys are sent, the key list and the view's keys are combined. If keys are sent and no view, only those properties in keys are returned.

For which properties are available see: galaxy/managers/histories/HistorySerializer

The list returned can be filtered by using two optional parameters:

q: string, generally a property name to filter by followed by an (often optional) hyphen and operator string.

qv: string, the value to filter by

..example: To filter the list to only those created after 2015-01-29, the query string would look like:

'?q=create_time-gt&qv=2015-01-29'

Multiple filters can be sent in using multiple q/qv pairs: '?q=create_time-gt&qv=2015-01-29&q=tag-has&qv=experiment-1'

The list returned can be paginated using two optional parameters:

limit: integer, defaults to no value and no limit (return all) how many items to return

offset: integer, defaults to 0 and starts at the beginning skip the first (offset - 1) items and begin returning at the Nth item

..example:

limit and offset can be combined. Skip the first two and return five: '?limit=5&offset=3'

show (*trans*, *id*, *deleted*='False')

- **GET /api/histories/{id}:** return the history with *id*
- **GET /api/histories/deleted/{id}:** return the deleted history with *id*
- **GET /api/histories/most_recently_used:** return the most recently used history

Parameters

- **id** (*an encoded id string*) – the encoded id of the history to query or the string 'most_recently_used'
- **deleted** (*boolean*) – if True, allow information on a deleted history to be shown.
- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type dictionary

Returns detailed history information

undelete (*self*, *trans*, *id*, ***kwd*)

- **POST /api/histories/deleted/{id}/undelete:** undelete history (that hasn't been purged) with the given *id*

Parameters

- **id** (*str*) – the encoded id of the history to undelete

- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type str

Returns 'OK' if the history was undeleted

update (*self*, *trans*, *id*, *payload*, ***kwd*)

• **PUT /api/histories/{id}** updates the values for the history with the given *id*

Parameters

- **id** (*str*) – the encoded id of the history to update
- **payload** (*dict*) – a dictionary containing any or all the fields in `galaxy.model.History.to_dict()` and/or the following:
 - annotation: an annotation for the history
- **keys** – same as the use of *keys* in the *index* function above
- **view** – same as the use of *view* in the *index* function above

Return type dict

Returns an error object if an error occurred or a dictionary containing any values that were different from the original and, therefore, updated

history_contents Module API operations on the contents of a history.

class `galaxy.webapps.galaxy.api.history_contents.HistoryContentsController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.UsesLibraryMixin`, `galaxy.web.base.controller.UsesLibraryMixinItems`, `galaxy.web.base.controller.UsesTagsMixin`

create (*self*, *trans*, *history_id*, *payload*, ***kwd*)

• **POST /api/histories/{history_id}/contents/{type}** create a new HDA by copying an accessible LibraryDataset

Parameters

- **history_id** (*str*) – encoded id string of the new HDA's History
- **type** (*str*) – Type of history content - 'dataset' (default) or 'dataset_collection'.
- **payload** (*dict*) – dictionary structure containing:
 - copy from library (for type 'dataset'): 'source' = 'library' 'content' = [the encoded id from the library dataset]
 - copy from history dataset (for type 'dataset'): 'source' = 'hda' 'content' = [the encoded id from the HDA]
 - copy from history dataset collection (for type 'dataset_collection') 'source' = 'hdca' 'content' = [the encoded id from the HDCA]
 - create new history dataset collection (for type 'dataset_collection') 'source' = 'new_collection' (default 'source' if type is 'dataset_collection' - no need to specify this)

‘collection_type’ = For example, “list”, “paired”, “list:paired”. ‘name’ = Name of new dataset collection. ‘element_identifiers’ = Recursive list structure defining collection.

Each element must have ‘src’ which can be ‘hda’, ‘ldda’, ‘hdca’, or ‘new_collection’, as well as a ‘name’ which is the name of element (e.g. “forward” or “reverse” for paired datasets, or arbitrary sample names for instance for lists). For all src’s except ‘new_collection’ - a encoded ‘id’ attribute must be included with element as well. ‘new_collection’ sources must defined a ‘collection_type’ and their own list of (potentially) nested ‘element_identifiers’.

..note: Currently, a user can only copy an HDA from a history that the user owns.

Return type dict

Returns dictionary containing detailed information for the new HDA

delete (*self*, *trans*, *history_id*, *id*, ***kwd*)

• **DELETE /api/histories/{history_id}/contents/{id}** delete the HDA with the given *id*

Note: Currently does not stop any active jobs for which this dataset is an output.

Parameters

- **id** (*str*) – the encoded id of the history to delete
- **purge** (*bool*) – if True, purge the HDA
- **kwd** (*dict*) – (optional) dictionary structure containing:
 - **payload: a dictionary itself containing:**
 - * **purge:** if True, purge the HDA

Note: that payload optionally can be placed in the query string of the request. This allows clients that strip the request body to still purge the dataset.

Return type dict

Returns an error object if an error occurred or a dictionary containing: * *id*: the encoded id of the history, * *deleted*: if the history was marked as deleted, * *purged*: if the history was purged

index (*self*, *trans*, *history_id*, *ids=None*, ***kwd*)

• **GET /api/histories/{history_id}/contents** return a list of HDA data for the history with the given *id*

Note: Anonymous users are allowed to get their current history contents

If *ids* is not given, *index* returns a list of *summary* objects for every HDA associated with the given *history_id*.

If *ids* is given, *index* returns a *more complete* json object for each HDA in the *ids* list.

Parameters

- **history_id** (*str*) – encoded id string of the HDA's History
- **ids** (*str*) – (optional) a comma separated list of encoded *HDA* ids
- **types** (*str*) – (optional) kinds of contents to index (currently just dataset, but dataset_collection will be added shortly).

Return type *list*

Returns dictionaries containing summary or detailed HDA information

show (*self*, *trans*, *id*, *history_id*, ***kwd*)

- **GET** /api/histories/{history_id}/contents/{id} return detailed information about an HDA within a history

Note: Anonymous users are allowed to get their current history contents

Parameters

- **ids** – the encoded id of the HDA to return
- **history_id** (*str*) – encoded id string of the HDA's History

Return type *dict*

Returns dictionary containing detailed HDA information

update (*self*, *trans*, *history_id*, *id*, *payload*, ***kwd*)

- **PUT** /api/histories/{history_id}/contents/{id} updates the values for the HDA with the given *id*

Parameters

- **history_id** (*str*) – encoded id string of the HDA's History
- **id** (*str*) – the encoded id of the history to undelete
- **payload** (*dict*) – a dictionary containing any or all the fields in `galaxy.model.HistoryDatasetAssociation.to_dict()` and/or the following:
 - **annotation**: an annotation for the HDA

Return type *dict*

Returns an error object if an error occurred or a dictionary containing any values that were different from the original and, therefore, updated

item_tags Module API operations related to tagging items.

class `galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.UsesTagsM`

create (*trans*, **args*, ***kwargs*)

delete (*trans*, **args*, ***kwargs*)

index (*trans*, **args*, ***kwargs*)

show (*trans*, **args*, ***kwargs*)

update (*trans*, **args*, ***kwargs*)


```

class galaxy.webapps.galaxy.api.item_tags.HistoryContentTagsController(app)
    Bases: galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController

    controller_name = 'history_content_tags'
    tagged_item_class = 'HistoryDatasetAssociation'
    tagged_item_id = 'history_content_id'

class galaxy.webapps.galaxy.api.item_tags.HistoryTagsController(app)
    Bases: galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController

    controller_name = 'history_tags'
    tagged_item_class = 'History'
    tagged_item_id = 'history_id'

class galaxy.webapps.galaxy.api.item_tags.WorkflowTagsController(app)
    Bases: galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController

    controller_name = 'workflow_tags'
    tagged_item_class = 'StoredWorkflow'
    tagged_item_id = 'workflow_id'

```

job_files Module API for asynchronous job running mechanisms can use to fetch or put files related to running and queued jobs.

```

class galaxy.webapps.galaxy.api.job_files.JobFilesAPIController(app)
    Bases: galaxy.web.base.controller.BaseAPIController

```

This job files controller allows remote job running mechanisms to read and modify the current state of files for queued and running jobs. It is certainly not meant to represent part of Galaxy's stable, user facing API.

Furthermore, even if a user key corresponds to the user running the job, it should not be accepted for authorization - this API allows access to low-level unfiltered files and such authorization would break Galaxy's security model for tool execution.

create (*self*, *trans*, *job_id*, *payload*, ***kwargs*)

- **POST /api/jobs/{job_id}/files** Populate an output file (formal dataset, task split part, working directory file (such as those related to metadata)). This should be a multipart post with a 'file' parameter containing the contents of the actual file to create.

Parameters

- **job_id** (*str*) – encoded id string of the job
- **payload** (*dict*) – dictionary structure containing:: 'job_key' = Key authenticating
'path' = Path to file to create.

..note: This API method is intended only for consumption by job runners, not end users.

Return type dict

Returns an okay message

index (*self*, *trans*, *job_id*, ***kwargs*)

- **GET /api/jobs/{job_id}/files** Get a file required to staging a job (proper datasets, extra inputs, task-split inputs, working directory files).

Parameters

- **job_id** (*str*) – encoded id string of the job
- **path** (*str*) – Path to file.
- **job_key** (*str*) – A key used to authenticate this request as acting on behalf of a job runner for the specified job.

..note: This API method is intended only for consumption by job runners, not end users.

Return type *binary*

Returns contents of file

jobs Module API operations on a jobs.

See also:

`galaxy.model.Jobs`

class `galaxy.webapps.galaxy.api.jobs.JobController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.UsesLibra`

create (*trans*, **args*, ***kwargs*)

See the create method in tools.py in order to submit a job.

index (*trans*, *state=None*, *tool_id=None*, *history_id=None*, *date_range_min=None*, *date_range_max=None*, *user_details=False*)

• **GET /api/jobs:** return jobs for current user

!! if user is admin and user_details is True, then return jobs for all galaxy users based on filtering - this is an extended service

Parameters **state** (*string or list*) – limit listing of jobs to those that match one of the included states. If none, all are returned.

Valid Galaxy job states include: ‘new’, ‘upload’, ‘waiting’, ‘queued’, ‘running’, ‘ok’, ‘error’, ‘paused’, ‘deleted’, ‘deleted_new’

Parameters

- **tool_id** (*string or list*) – limit listing of jobs to those that match one of the included tool_ids. If none, all are returned.
- **user_details** (*boolean*) – if true, and requestor is an admin, will return external job id and user email.
- **date_range_min** (*string ‘2014-01-01’*) – limit the listing of jobs to those updated on or after requested date
- **date_range_max** (*string ‘2014-12-31’*) – limit the listing of jobs to those updated on or before requested date
- **history_id** (*string*) – limit listing of jobs to those that match the history_id. If none, all are returned.

Return type *list*

Returns list of dictionaries containing summary job information

inputs (*trans*, **args*, ***kwargs*)

show(*trans*, *id*) * GET /api/jobs/{*job_id*}/inputs

returns input datasets created by job

Parameters *id* (*string*) – Encoded job id

Return type dictionary

Returns dictionary containing input dataset associations

outputs (*trans*, **args*, ***kwargs*)

show(*trans*, *id*) * GET /api/jobs/{*job_id*}/outputs

returns output datasets created by job

Parameters *id* (*string*) – Encoded job id

Return type dictionary

Returns dictionary containing output dataset associations

search (*trans*, *payload*)

• **POST /api/jobs/search:** return jobs for current user

Parameters *payload* (*dict*) – Dictionary containing description of requested job. This is in the same format as a request to POST /api/tools would take to initiate a job

Return type *list*

Returns list of dictionaries containing summary job information of the jobs that match the requested job run

This method is designed to scan the list of previously run jobs and find records of jobs that had the exact some input parameters and datasets. This can be used to minimize the amount of repeated work, and simply recycle the old results.

show (*trans*, *id*)

• **GET /api/jobs/{*job_id*}:** return jobs for current user

Parameters

- *id* (*string*) – Specific job id
- *full* (*boolean*) – whether to return extra information

Return type dictionary

Returns dictionary containing full description of job data

lda_datasets Module API operations on the library datasets.

class galaxy.webapps.galaxy.api.lda_datasets.**LibraryDatasetsController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*, *galaxy.web.base.controller.UsesVisual*

delete (*trans*, **args*, ***kwargs*)

delete(self, *trans*, *encoded_dataset_id*, ***kwd*): * DELETE /api/libraries/datasets/{*encoded_dataset_id*}

Marks the dataset deleted or undeleted based on the value of the undelete flag. If the flag is not present it is considered False and the item is marked deleted.

Parameters `encoded_dataset_id` (*an encoded id string*) – the encoded id of the dataset to change

Returns dict containing information about the dataset

Return type dictionary

download (*self, trans, format, **kwd*)

- **GET** /api/libraries/datasets/download/{format}

- **POST** /api/libraries/datasets/download/{format} Downloads requested datasets (identified by encoded IDs) in requested format.

example: GET localhost:8080/api/libraries/datasets/download/tbz?ld_ids%255B%255D=a0d

Note: supported format values are: 'zip', 'tgz', 'tbz', 'uncompressed'

Parameters

- **format** (*string*) – string representing requested archive format
- **ld_ids** [] (*an array*) – an array of encoded ids

Return type file

Returns either archive with the requested datasets packed inside or a single uncompressed dataset

Raises MessageException, ItemDeletionException, ItemAccessibilityException, HTTP-BadRequest, OSError, IOError, ObjectNotFound

load (*trans, *args, **kwargs*)

load(self, trans, ****kwd**): * POST /api/libraries/datasets Load dataset from the given source into the library. Source can be:

user directory - root folder specified in galaxy.ini as “\$user_library_import_dir”

example path: path/to/galaxy/\$user_library_import_dir/user@example.com/{user can browse everything here} the folder with the user login has to be created beforehand

(admin)import directory - root folder specified in galaxy ini as “\$library_import_dir”

example path: path/to/galaxy/\$library_import_dir/{admin can browse everything here}

(admin)any absolute or relative path - option allowed with “allow_library_path_paste” in galaxy.ini

Parameters

- **encoded_folder_id** (*an encoded id string*) – the encoded id of the folder to import dataset(s) to
- **source** (*str*) – source the datasets should be loaded from
- **link_data** (*bool*) – flag whether to link the dataset to data or copy it to Galaxy, defaults to copy while linking is set to True all symlinks will be resolved `_once_`
- **preserve_dirs** (*bool*) – flag whether to preserve the directory structure when importing dir if False only datasets will be imported

- **file_type** (*str*) – file type of the loaded datasets, defaults to ‘auto’ (autodetect)
- **dbkey** (*str*) – dbkey of the loaded genome, defaults to ‘?’ (unknown)

Returns dict containing information about the created upload job

Return type dictionary

show (*self*, *trans*, *id*, ***kwd*)

• **GET /api/libraries/datasets/{encoded_dataset_id}**: Displays information about the dataset identified by the encoded ID.

Parameters **id** (*an encoded id string*) – the encoded id of the dataset to query

Returns detailed dataset information from base controller

Return type dictionary

See also:

`galaxy.web.base.controller.UsesLibraryMixinItems.get_library_dataset`

show_roles (*trans*, **args*, ***kwargs*)

`show_roles(self, trans, id, **kwd)`: * GET /api/libraries/datasets/{encoded_dataset_id}/permissions

Displays information about current or available roles for a given dataset permission.

Parameters

- **encoded_dataset_id** (*an encoded id string*) – the encoded id of the dataset to query
- **scope** (*string*) – either ‘current’ or ‘available’

Return type dictionary

Returns either dict of current roles for all permission types or dict of available roles to choose from (is the same for any permission type)

show_version (*trans*, **args*, ***kwargs*)

`show_version(self, trans, encoded_dataset_id, encoded_ldda_id, **kwd)`: * GET /api/libraries/datasets/:encoded_dataset_id/versions/:encoded_ldda_id

Displays information about specific version of the library_dataset (i.e. ldda).

Parameters

- **encoded_dataset_id** (*an encoded id string*) – the encoded id of the dataset to query
- **encoded_ldda_id** (*an encoded id string*) – the encoded id of the ldda to query

Return type dictionary

Returns dict of ldda’s details

update_permissions (*trans*, **args*, ***kwargs*)

`def update(self, trans, encoded_dataset_id, **kwd)`: *POST /api/libraries/datasets/{encoded_dataset_id}/permissions

Parameters

- **encoded_dataset_id** (*an encoded id string*) – the encoded id of the dataset to update permissions of
- **action** (*string*) – (required) describes what action should be performed available actions: `make_private`, `remove_restrictions`, `set_permissions`
- **access_ids** [] (*string or list*) – list of `Role.name` defining roles that should have access permission on the dataset
- **manage_ids** [] (*string or list*) – list of `Role.name` defining roles that should have manage permission on the dataset
- **modify_ids** [] (*string or list*) – list of `Role.name` defining roles that should have modify permission on the library dataset item

Return type dictionary

Returns dict of current roles for all available permission types

Raises `RequestParameterInvalidException`, `ObjectNotFound`, `InsufficientPermissionsException`, `InternalServerError` `RequestParameterMissingException`

libraries Module API operations on a data library.

class `galaxy.webapps.galaxy.api.libraries.LibrariesController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`

create (*self, trans, payload, **kwd*)

• **POST /api/libraries:** Creates a new library. Only `name` parameter is required.

Note: Currently, only admin users can create libraries.

Parameters **payload** (*dict*) – dictionary structure containing:: `'name'`: the new library's name (required) `'description'`: the new library's description (optional) `'synopsis'`: the new library's synopsis (optional)

Returns detailed library information

Return type dict

Raises `ItemAccessibilityException`, `RequestParameterMissingException`

delete (*self, trans, id, **kwd*)

• **DELETE /api/libraries/{id}** marks the library with the given `id` as *deleted* (or removes the *deleted* mark if the *undelete* param is true)

Note: Currently, only admin users can un/delete libraries.

Parameters

- **id** (*an encoded id string*) – the encoded id of the library to un/delete
- **undelete** (*bool*) – (optional) flag specifying whether the item should be deleted or undeleted, defaults to false:

Returns detailed library information

Return type dictionary

See also:

`galaxy.model.Library.dict_element_visible_keys`

Raises ItemAccessibilityException, MalformedId, ObjectNotFound

get_permissions (*trans*, **args*, ***kwargs*)

•GET /api/libraries/{id}/permissions

Load all permissions for the given library id and return it.

Parameters

- **encoded_library_id** (*an encoded id string*) – the encoded id of the library
- **scope** (*string*) – either ‘current’ or ‘available’
- **is_library_access** (*bool*) – indicates whether the roles available for the library access are requested

Returns dictionary with all applicable permissions’ values

Return type dictionary

Raises ObjectNotFound, InsufficientPermissionsException

index (*self*, *trans*, ***kwd*)

•GET /api/libraries: Returns a list of summary data for all libraries.

Parameters **deleted** (*boolean (optional)*) – if True, show only deleted libraries, if False show only non-deleted

Returns list of dictionaries containing library information

Return type *list*

See also:

`galaxy.model.Library.dict_collection_visible_keys`

set_permissions (*trans*, **args*, ***kwargs*)

def set_permissions(self, trans, encoded_dataset_id, **kwd): *POST
/api/libraries/{encoded_library_id}/permissions

Parameters

- **encoded_library_id** (*an encoded id string*) – the encoded id of the library to set the permissions of
- **action** (*string*) – (required) describes what action should be performed available actions: remove_restrictions, set_permissions
- **access_ids** [] (*string or list*) – list of Role.id defining roles that should have access permission on the library
- **add_ids** [] (*string or list*) – list of Role.id defining roles that should have add item permission on the library
- **manage_ids** [] (*string or list*) – list of Role.id defining roles that should have manage permission on the library

- **modify_ids**[] (*string or list*) – list of Role.id defining roles that should have modify permission on the library

Return type dictionary

Returns dict of current roles for all available permission types

Raises RequestParameterInvalidException, ObjectNotFound, InsufficientPermissionsException, InternalServerError RequestParameterMissingException

set_permissions_old(*trans, library, payload, **kwd*)
* old implementation for backward compatibility *

POST /api/libraries/{encoded_library_id}/permissions Updates the library permissions.

show(*self, trans, id, deleted='False', **kwd*)

•GET /api/libraries/{encoded_id}: returns detailed information about a library

•GET /api/libraries/deleted/{encoded_id}: returns detailed information about a deleted library

Parameters

- **id** (*an encoded id string*) – the encoded id of the library
- **deleted** (*boolean*) – if True, allow information on a deleted library

Returns detailed library information

Return type dictionary

See also:

`galaxy.model.Library.dict_element_visible_keys`

Raises MalformedId, ObjectNotFound

update(*trans, *args, **kwargs*)

- PATCH /api/libraries/{encoded_id} Updates the library defined by an encoded_id with the data in the payload.

Note: Currently, only admin users can update libraries. Also the library must not be *deleted*.

param id the encoded id of the library

type id an encoded id string

param payload (required) dictionary structure containing:: 'name': new library's name, cannot be empty 'description': new library's description 'synopsis': new library's synopsis

type payload dict

returns detailed library information

rtype dict

raises ItemAccessibilityException, MalformedId, ObjectNotFound, RequestParameterInvalidException, RequestParameterMissingException

library_contents Module API operations on the contents of a data library.

```
class galaxy.webapps.galaxy.api.library_contents.LibraryContentsController(app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesLibraryMixin
    galaxy.web.base.controller.UsesLibraryMixinItems
```

create (*self*, *trans*, *library_id*, *payload*, ***kwd*)

• **POST /api/libraries/{library_id}/contents:** create a new library file or folder

To copy an HDA into a library send `create_type` of 'file' and the HDA's encoded id in `from_hda_id` (and optionally `ldda_message`).

Parameters

- **library_id** (*str*) – the encoded id of the library where to create the new item
- **payload** (*dict*) – dictionary structure containing:
 - `folder_id`: the encoded id of the parent folder of the new item
 - `create_type`: the type of item to create ('file', 'folder' or 'collection')
 - **from_hda_id**: (optional, only if `create_type` is 'file') the encoded id of an accessible HDA to copy into the library
 - `ldda_message`: (optional) the new message attribute of the LDDA created
 - **extended_metadata**: (optional) **dub-dictionary containing any extended metadata** to associate with the item
 - `upload_option`: (optional) one of 'upload_file' (default), 'upload_directory' or 'upload_paths'
 - **server_dir**: (optional, only if `upload_option` is 'upload_directory') relative path of the subdirectory of Galaxy `library_import_dir` to upload. All and only the files (i.e. no subdirectories) contained in the specified directory will be uploaded.
 - **filesystem_paths**: (optional, only if `upload_option` is 'upload_paths' and the user is an admin) file paths on the Galaxy server to upload to the library, one file per line
 - **link_data_only**: (optional, only when `upload_option` is 'upload_directory' or 'upload_paths') either 'copy_files' (default) or 'link_to_files'. Setting to 'link_to_files' symlinks instead of copying the files
 - **name**: (optional, only if `create_type` is 'folder') **name of the** folder to create
 - **description**: (optional, only if `create_type` is 'folder') **description** of the folder to create

Return type dict

Returns a dictionary containing the id, name, and 'show' url of the new item

delete (*self*, *trans*, *library_id*, *id*, ***kwd*)

• **DELETE /api/libraries/{library_id}/contents/{id}** delete the LibraryDataset with the given `id`

Parameters

- **id** (*str*) – the encoded id of the library dataset to delete
- **kwd** (*dict*) – (optional) dictionary structure containing:

– **payload: a dictionary itself containing:**

* **purge:** if True, purge the LD

Return type dict

Returns an error object if an error occurred or a dictionary containing: * **id:** the encoded id of the library dataset, * **deleted:** if the library dataset was marked as deleted, * **purged:** if the library dataset was purged

index (*self*, *trans*, *library_id*, ***kwd*)

•**GET /api/libraries/{library_id}/contents:** Returns a list of library files and folders.

Note: May be slow! Returns all content traversing recursively through all folders.

See also:

`galaxy.webapps.galaxy.api.FolderContentsController.index` for a non-recursive solution

Parameters **library_id** (*str*) – the encoded id of the library

Returns

list of dictionaries of the form: * **id:** the encoded id of the library item * **name:** the ‘library path’

or relationship of the library item to the root

- **type:** ‘file’ or ‘folder’
- **url:** the url to get detailed information on the library item

Return type *list*

Raises `MalformedId`, `InconsistentDatabase`, `RequestParamterInvalidException`, `InternalServerError`

show (*self*, *trans*, *id*, *library_id*, ***kwd*)

•**GET /api/libraries/{library_id}/contents/{id}** Returns information about library file or folder.

Parameters

- **id** (*str*) – the encoded id of the library item to return
- **library_id** (*str*) – the encoded id of the library that contains this item

Returns detailed library item information

Return type dict

See also:

`galaxy.model.LibraryDataset.to_dict()` and `galaxy.model.LibraryFolder.dict_element_v`

update (*self*, *trans*, *id*, *library_id*, *payload*, ***kwd*)

•**PUT /api/libraries/{library_id}/contents/{id}** create a `ImplicitlyConvertedDatasetAssociation`

See also:

`galaxy.model.ImplicitlyConvertedDatasetAssociation`

Parameters

- **id** (*str*) – the encoded id of the library item to return
- **library_id** (*str*) – the encoded id of the library that contains this item
- **payload** (*dict*) – dictionary structure containing:: ‘converted_dataset_id’:

Return type None**Returns** None

metrics Module API operations for for querying and recording user metrics from some client (typically a user’s browser).

class `galaxy.webapps.galaxy.api.metrics.MetricsController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`

create (*trans*, *payload*)

- **POST /api/metrics:** record any metrics sent and return some status object

Note: Anonymous users can post metrics

Parameters **payload** (*dict*) – (optional) dictionary structure containing: * metrics: a list containing dictionaries of the form:

 ** namespace: label indicating the source of the metric ** time: isoformat
 datetime when the metric was recorded ** level: an integer representing the
 metric’s log level ** args: a json string containing an array of extra data

Return type dict**Returns** status object**debugging** = None

set to true to send additional debugging info to the log

page_revisions Module API for updating Galaxy Pages

class `galaxy.webapps.galaxy.api.page_revisions.PageRevisionsController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.SharableIt`
`galaxy.model.item_attrs.UsesAnnotations`, `galaxy.web.base.controller.SharableMixin`

create (*self*, *trans*, *page_id*, *payload* ****kwd**)

- **POST /api/pages/{page_id}/revisions** Create a new revision for a page

Parameters

- **page_id** – Add revision to Page with ID=page_id
- **payload** – A dictionary containing:: ‘title’ = New title of the page ‘content’ =
New content of the page

Return type dictionary**Returns** Dictionary with ‘success’ or ‘error’ element to indicate the result of the request

index (*self*, *trans*, *page_id*, ****kwd**)

•**GET /api/pages/{page_id}/revisions** return a list of Page revisions

Parameters **page_id** – Display the revisions of Page with ID=page_id

Return type *list*

Returns dictionaries containing different revisions of the page

pages Module API for updating Galaxy Pages

class `galaxy.webapps.galaxy.api.pages.PagesController` (*app*)

Bases: `galaxy.web.base.controller.BaseAPIController`, `galaxy.web.base.controller.SharableIt`
`galaxy.model.item_attrs.UsesAnnotations`, `galaxy.web.base.controller.SharableMixin`

create (*self*, *trans*, *payload*, ***kwd*)

•**POST /api/pages** Create a page and return dictionary containing Page summary

Parameters **payload** – dictionary structure containing:: ‘slug’ = The title slug for the page URL, must be unique ‘title’ = Title of the page ‘content’ = HTML contents of the page ‘annotation’ = Annotation that will be attached to the page

Return type dict

Returns Dictionary return of the Page.to_dict call

delete (*self*, *trans*, *id*, ***kwd*)

•**DELETE /api/pages/{id}** Create a page and return dictionary containing Page summary

Parameters **id** – ID of page to be deleted

Return type dict

Returns Dictionary with ‘success’ or ‘error’ element to indicate the result of the request

index (*self*, *trans*, *deleted=False*, ***kwd*)

•**GET /api/pages** return a list of Pages viewable by the user

Parameters **deleted** – Display deleted pages

Return type *list*

Returns dictionaries containing summary or detailed Page information

show (*self*, *trans*, *id*, ***kwd*)

•**GET /api/pages/{id}** View a page summary and the content of the latest revision

Parameters **id** – ID of page to be displayed

Return type dict

Returns Dictionary return of the Page.to_dict call with the ‘content’ field populated by the most recent revision

provenance Module API operations provenance

```
class galaxy.webapps.galaxy.api.provenance.BaseProvenanceController(app)
    Bases: galaxy.web.base.controller.BaseAPIController

    create(trans, *args, **kwargs)

    delete(trans, *args, **kwargs)

    index(trans, *args, **kwargs)

    show(trans, *args, **kwargs)

class galaxy.webapps.galaxy.api.provenance.HDAProvenanceController(app)
    Bases: galaxy.webapps.galaxy.api.provenance.BaseProvenanceController

    controller_name = 'history_content_provenance'

    provenance_item_class = 'HistoryDatasetAssociation'

    provenance_item_id = 'history_content_id'

class galaxy.webapps.galaxy.api.provenance.LDDAProvenanceController(app)
    Bases: galaxy.webapps.galaxy.api.provenance.BaseProvenanceController

    controller_name = 'ldda_provenance'

    provenance_item_class = 'LibraryDatasetDatasetAssociation'

    provenance_item_id = 'library_content_id'
```

quotas Module API operations on Quota objects.

```
class galaxy.webapps.galaxy.api.quotas.QuotaAPIController(app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controllers.admin.AdminActions, galaxy.actions.admin.AdminActions, galaxy.web.base.controller.UsesQuotaMixin, galaxy.web.params.QuotaParamParser

    create(trans, *args, **kwargs)
        POST /api/quotas Creates a new quota.

    delete(trans, *args, **kwargs)
        DELETE /api/quotas/{encoded_quota_id} Deletes a quota

    index(trans, *args, **kwargs)
        GET /api/quotas GET /api/quotas/deleted Displays a collection (list) of quotas.

    show(trans, *args, **kwargs)
        GET /api/quotas/{encoded_quota_id} GET /api/quotas/deleted/{encoded_quota_id} Displays information about a quota.

    undelete(trans, *args, **kwargs)
        POST /api/quotas/deleted/{encoded_quota_id}/undelete Undeletes a quota

    update(trans, *args, **kwargs)
        PUT /api/quotas/{encoded_quota_id} Modifies a quota.
```

request_types Module API operations on RequestType objects.

```
class galaxy.webapps.galaxy.api.request_types.RequestTypeAPIController(app)
    Bases: galaxy.web.base.controller.BaseAPIController

    create(trans, *args, **kwargs)
        POST /api/request_types Creates a new request type (external_service configuration).
```

index (*trans*, *args, **kwargs)

GET /api/request_types Displays a collection (list) of request_types.

show (*trans*, *args, **kwargs)

GET /api/request_types/{encoded_request_id} Displays information about a request_type.

requests Module API operations on a sample tracking system.

class galaxy.webapps.galaxy.api.requests.**RequestsAPIController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

index (*trans*, *args, **kwargs)

GET /api/requests Displays a collection (list) of sequencing requests.

show (*trans*, *args, **kwargs)

GET /api/requests/{encoded_request_id} Displays details of a sequencing request.

update (*trans*, *args, **kwargs)

PUT /api/requests/{encoded_request_id} Updates a request state, sample state or sample dataset transfer status depending on the update_type

v = ('REQUEST', 'request_state')

roles Module API operations on Role objects.

class galaxy.webapps.galaxy.api.roles.**RoleAPIController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

create (*trans*, *args, **kwargs)

POST /api/roles Creates a new role.

index (*trans*, *args, **kwargs)

GET /api/roles Displays a collection (list) of roles.

show (*trans*, *args, **kwargs)

GET /api/roles/{encoded_role_id} Displays information about a role.

samples Module API operations for samples in the Galaxy sample tracking system.

class galaxy.webapps.galaxy.api.samples.**SamplesAPIController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*

index (*trans*, *args, **kwargs)

GET /api/requests/{encoded_request_id}/samples Displays a collection (list) of sample of a sequencing request.

k = 'SAMPLE_DATASET'

update (*trans*, *args, **kwargs)

PUT /api/samples/{encoded_sample_id} Updates a sample or objects related (mapped) to a sample.

update_type_values = ['sample_state', 'run_details', 'sample_dataset_transfer_status']

update_types = <galaxy.util.bunch.Bunch object>

v = ['sample_dataset_transfer_status']

search Module

tool_data Module

class `galaxy.webapps.galaxy.api.tool_data.ToolData` (*app*)
 Bases: `galaxy.web.base.controller.BaseAPIController`

RESTful controller for interactions with tool data

delete (*trans, *args, **kwargs*)
 DELETE /api/tool_data/{id} Removes an item from a data table

Parameters

- **id** (*str*) – the id of the data table containing the item to delete
- **kw** (*dict*) – (required) dictionary structure containing:
 - **payload: a dictionary itself containing:**
 - * values: <TAB> separated list of column contents, there must be a value for all the columns of the data table

download_field_file (*trans, *args, **kwargs*)

index (*trans, *args, **kwargs*)
 GET /api/tool_data: returns a list tool_data tables:

reload (*trans, *args, **kwargs*)
 GET /api/tool_data/{id}/reload

Reloads a tool_data table.

show (*trans, *args, **kwargs*)

show_field (*trans, *args, **kwargs*)
 GET /api/tool_data/<id>/fields/<value>

Get information about a partiular field in a tool_data table

tool_shed_repositories Module

class `galaxy.webapps.galaxy.api.tool_shed_repositories.ToolShedRepositoriesController` (*app*)
 Bases: `galaxy.web.base.controller.BaseAPIController`

RESTful controller for interactions with tool shed repositories.

exported_workflows (*trans, *args, **kwargs*)
 GET /api/tool_shed_repositories/{encoded_tool_shed_repository_id}/exported_workflows

Display a list of dictionaries containing information about this tool shed repository's exported workflows.

Parameters id – the encoded id of the ToolShedRepository object

get_latest_installable_revision (*trans, *args, **kwargs*)
 POST /api/tool_shed_repositories/get_latest_installable_revision Get the latest installable revision of a specified repository from a specified Tool Shed.

Parameters key – the current Galaxy admin user's API key

The following parameters are included in the payload. :param tool_shed_url (required): the base URL of the Tool Shed from which to retrieve the Repository revision. :param name (required): the name of the Repository :param owner (required): the owner of the Repository

import_workflow (*trans, *args, **kwargs*)
 POST /api/tool_shed_repositories/import_workflow

Import the specified exported workflow contained in the specified installed tool shed repository into Galaxy.

Parameters

- **key** – the API key of the Galaxy user with which the imported workflow will be associated.
- **id** – the encoded id of the ToolShedRepository object

The following parameters are included in the payload. :param index: the index location of the workflow tuple in the list of exported workflows stored in the metadata for the specified repository

import_workflows (*trans, *args, **kwargs*)
POST /api/tool_shed_repositories/import_workflows

Import all of the exported workflows contained in the specified installed tool shed repository into Galaxy.

Parameters

- **key** – the API key of the Galaxy user with which the imported workflows will be associated.
- **id** – the encoded id of the ToolShedRepository object

index (*trans, *args, **kwargs*)
GET /api/tool_shed_repositories Display a list of dictionaries containing information about installed tool shed repositories.

install_repository_revision (*trans, *args, **kwargs*)
POST /api/tool_shed_repositories/install_repository_revision Install a specified repository revision from a specified tool shed into Galaxy.

Parameters **key** – the current Galaxy admin user’s API key

The following parameters are included in the payload. :param tool_shed_url (required): the base URL of the Tool Shed from which to install the Repository :param name (required): the name of the Repository :param owner (required): the owner of the Repository :param changeset_revision (required): the changeset_revision of the RepositoryMetadata object associated with the Repository :param new_tool_panel_section_label (optional): label of a new section to be added to the Galaxy tool panel in which to load

tools contained in the Repository. Either this parameter must be an empty string or the tool_panel_section_id parameter must be an empty string or both must be an empty string (both cannot be used simultaneously).

Parameters

- **(optional)** (*shed_tool_conf*) – id of the Galaxy tool panel section in which to load tools contained in the Repository. If this parameter is an empty string and the above new_tool_panel_section_label parameter is an empty string, tools will be loaded outside of any sections in the tool panel. Either this parameter must be an empty string or the tool_panel_section_id parameter must be an empty string of both must be an empty string (both cannot be used simultaneously).
- **(optional)** – Set to True if you want to install repository dependencies defined for the specified repository being installed. The default setting is False.
- **(optional)** – Set to True if you want to install tool dependencies defined for the specified repository being installed. The default setting is False.
- **(optional)** – The shed-related tool panel configuration file configured in the “tool_config_file” setting in the Galaxy config file (e.g., galaxy.ini). At least one shed-related tool panel config file is required to be configured. Setting this parameter to a specific file enables you to choose where the specified repository will be

installed because the `tool_path` attribute of the `<toolbox>` from the specified file is used as the installation location (e.g., `<toolbox tool_path='../shed_tools'>`). If this parameter is not set, a shed-related tool panel configuration file will be selected automatically.

install_repository_revisions (*trans, *args, **kwargs*)

POST /api/tool_shed_repositories/install_repository_revisions Install one or more specified repository revisions from one or more specified tool sheds into Galaxy. The received parameters must be ordered lists so that positional values in `tool_shed_urls`, `names`, `owners` and `changeset_revisions` are associated.

It's questionable whether this method is needed as the above method for installing a single repository can probably cover all desired scenarios. We'll keep this one around just in case...

Parameters key – the current Galaxy admin user's API key

The following parameters are included in the payload. :param `tool_shed_urls`: the base URLs of the Tool Sheds from which to install a specified Repository :param `names`: the names of the Repositories to be installed :param `owners`: the owners of the Repositories to be installed :param `changeset_revisions`: the `changeset_revisions` of each RepositoryMetadata object associated with each Repository to be installed :param `new_tool_panel_section_label`: optional label of a new section to be added to the Galaxy tool panel in which to load

tools contained in the Repository. Either this parameter must be an empty string or the `tool_panel_section_id` parameter must be an empty string, as both cannot be used.

Parameters

- **tool_panel_section_id** – optional id of the Galaxy tool panel section in which to load tools contained in the Repository. If not set, tools will be loaded outside of any sections in the tool panel. Either this parameter must be an empty string or the `tool_panel_section_id` parameter must be an empty string, as both cannot be used.
- **(optional) (shed_tool_conf)** – Set to True if you want to install repository dependencies defined for the specified repository being installed. The default setting is False.
- **(optional)** – Set to True if you want to install tool dependencies defined for the specified repository being installed. The default setting is False.
- **(optional)** – The shed-related tool panel configuration file configured in the “`tool_config_file`” setting in the Galaxy config file (e.g., `galaxy.ini`). At least one shed-related tool panel config file is required to be configured. Setting this parameter to a specific file enables you to choose where the specified repository will be installed because the `tool_path` attribute of the `<toolbox>` from the specified file is used as the installation location (e.g., `<toolbox tool_path='../shed_tools'>`). If this parameter is not set, a shed-related tool panel configuration file will be selected automatically.

repair_repository_revision (*trans, *args, **kwargs*)

POST /api/tool_shed_repositories/repair_repository_revision Repair a specified repository revision previously installed into Galaxy.

Parameters key – the current Galaxy admin user's API key

The following parameters are included in the payload. :param `tool_shed_url` (required): the base URL of the Tool Shed from which the Repository was installed :param `name` (required): the name of the Repository :param `owner` (required): the owner of the Repository :param `changeset_revision` (required): the `changeset_revision` of the RepositoryMetadata object associated with the Repository

reset_metadata_on_installed_repositories (*trans*, **args*, ***kwargs*)

PUT /api/tool_shed_repositories/reset_metadata_on_installed_repositories

Resets all metadata on all repositories installed into Galaxy in an “orderly fashion”.

Parameters **key** – the API key of the Galaxy admin user.

show (*trans*, **args*, ***kwargs*)

GET /api/tool_shed_repositories/{encoded_tool_shed_repository_id} Display a dictionary containing information about a specified tool_shed_repository.

Parameters **id** – the encoded id of the ToolShedRepository object

galaxy.webapps.galaxy.api.tool_shed_repositories.get_message_for_no_shed_tool_config()

tools Module

users Module API operations on User objects.

class galaxy.webapps.galaxy.api.users.**UserAPIController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*, *galaxy.web.base.controller.UsesTagsMixin*, *galaxy.web.base.controller.CreatesUsersMixin*, *galaxy.web.base.controller.CreatesApiKeysMixin*

anon_user_api_value (*trans*)

Returns data for an anonymous user, truncated to only usage and quota_percent

api_key (*trans*, **args*, ***kwargs*)

POST /api/users/{encoded_user_id}/api_key Creates a new API key for specified user.

create (*trans*, **args*, ***kwargs*)

POST /api/users Creates a new Galaxy user.

delete (*trans*, **args*, ***kwargs*)

index (*trans*, **args*, ***kwargs*)

GET /api/users GET /api/users/deleted Displays a collection (list) of users.

show (*trans*, **args*, ***kwargs*)

GET /api/users/{encoded_user_id} GET /api/users/deleted/{encoded_user_id} GET /api/users/current
Displays information about a user.

undelete (*trans*, **args*, ***kwargs*)

update (*trans*, **args*, ***kwargs*)

visualizations Module Visualizations resource control over the API.

NOTE!: this is a work in progress and functionality and data structures may change often.

class galaxy.webapps.galaxy.api.visualizations.**VisualizationsController** (*app*)

Bases: *galaxy.web.base.controller.BaseAPIController*, *galaxy.web.base.controller.UsesVisualizationsMixin*, *galaxy.web.base.controller.SharableMixin*, *galaxy.model.item_attrs.UsesAnnotations*

RESTful controller for interactions with visualizations.

create (*trans*, **args*, ***kwargs*)

POST /api/visualizations creates a new visualization using the given payload

POST /api/visualizations?import_id={encoded_visualization_id} imports a copy of an existing visualization into the user’s workspace

```

index (trans, *args, **kwargs)
    GET /api/visualizations:

show (trans, *args, **kwargs)
    GET /api/visualizations/{viz_id}

update (trans, *args, **kwargs)
    PUT /api/visualizations/{encoded_visualization_id}

```

workflows Module API operations for Workflows

```

class galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController (app)
    Bases: galaxy.web.base.controller.BaseAPIController, galaxy.web.base.controller.UsesStored
    galaxy.model.item_attrs.UsesAnnotations, galaxy.web.base.controller.SharableMixin

```

```

build_module (trans, *args, **kwargs)
    POST /api/workflows/build_module Builds module details including a tool model for the workflow editor.

cancel_invocation (trans, *args, **kwargs)
    DELETE /api/workflows/{workflow_id}/invocation/{invocation_id} Cancel the specified workflow invocation.

```

Parameters

- **workflow_id** (*str*) – the workflow id (required)
- **invocation_id** (*str*) – the usage id (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

```

create (trans, *args, **kwargs)
    POST /api/workflows

```

Run or create workflows from the api.

If installed_repository_file or from_history_id is specified a new workflow will be created for this user. Otherwise, workflow_id must be specified and this API method will cause a workflow to execute.

:param installed_repository_file The path of a workflow to import. Either workflow_id, installed_repository_file or from_history_id must be specified :type installed_repository_file str

Parameters

- **workflow_id** (*str*) – An existing workflow id. Either workflow_id, installed_repository_file or from_history_id must be specified
- **parameters** (*dict*) – If workflow_id is set - see _update_step_parameters()
- **ds_map** (*dict*) – If workflow_id is set - a dictionary mapping each input step id to a dictionary with 2 keys: 'src' (which can be 'ldda', 'ld' or 'hda') and 'id' (which should be the id of a LibraryDatasetDatasetAssociation, LibraryDataset or HistoryDatasetAssociation respectively)
- **no_add_to_history** (*str*) – If workflow_id is set - if present in the payload with any value, the input datasets will not be added to the selected history
- **history** (*str*) – If workflow_id is set - optional history where to run the workflow, either the name of a new history or "hist_id=HIST_ID" where HIST_ID is the id of an existing history. If not specified, the workflow will be run a new unnamed history

- **replacement_params** (*dict*) – If workflow_id is set - an optional dictionary used when renaming datasets
- **from_history_id** (*str*) – Id of history to extract a workflow from. Either workflow_id, installed_repository_file or from_history_id must be specified
- **job_ids** (*str*) – If from_history_id is set - optional list of jobs to include when extracting a workflow from history
- **dataset_ids** (*str*) – If from_history_id is set - optional list of HDA ‘hid’s corresponding to workflow inputs when extracting a workflow from history
- **dataset_collection_ids** (*str*) – If from_history_id is set - optional list of HDCA ‘hid’s corresponding to workflow inputs when extracting a workflow from history
- **workflow_name** (*str*) – If from_history_id is set - name of the workflow to create when extracting a workflow from history

delete (*trans*, **args*, ***kwargs*)

DELETE /api/workflows/{encoded_workflow_id} Deletes a specified workflow Author: rpark
copied from galaxy.web.controllers.workflows.py (delete)

import_new_workflow_deprecated (*trans*, **args*, ***kwargs*)

POST /api/workflows/upload Importing dynamic workflows from the api. Return newly generated workflow id. Author: rpark

currently assumes payload[‘workflow’] is a json representation of a workflow to be inserted into the database

Deprecated in favor of POST /api/workflows with encoded ‘workflow’ in payload the same way.

import_shared_workflow_deprecated (*trans*, **args*, ***kwargs*)

POST /api/workflows/import Import a workflow shared by other users.

Parameters **workflow_id** (*str*) – the workflow id (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

index (*trans*, **args*, ***kwargs*)

GET /api/workflows

Displays a collection of workflows.

Parameters **show_published** (*boolean*) – if True, show also published workflows

index_invocations (*trans*, **args*, ***kwargs*)

GET /api/workflows/{ workflow_id }/invocations

Get the list of the workflow invocations

Parameters **workflow_id** (*str*) – the workflow id (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

invocation_step (*trans*, **args*, ***kwargs*)

GET /api/workflows/{ workflow_id }/invocation/{ invocation_id }/steps/{ step_id }

Parameters

- **workflow_id** (*str*) – the workflow id (required)
- **invocation_id** (*str*) – the invocation id (required)
- **step_id** (*str*) – encoded id of the WorkflowInvocationStep (required)

- **payload** – payload containing update action information for running workflow.

Raises exceptions.MessageException, exceptions.ObjectNotFound

invoke (*trans*, **args*, ***kwargs*)

POST /api/workflows/{encoded_workflow_id}/invocations

Schedule the workflow specified by *workflow_id* to run.

show (*trans*, **args*, ***kwargs*)

GET /api/workflows/{encoded_workflow_id}

Displays information needed to run a workflow from the command line.

show_invocation (*trans*, **args*, ***kwargs*)

GET /api/workflows/{workflow_id}/invocation/{invocation_id} Get detailed description of workflow invocation

Parameters

- **workflow_id** (*str*) – the workflow id (required)
- **invocation_id** (*str*) – the invocation id (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

update (*trans*, **args*, ***kwargs*)

•PUT /api/workflows/{id} updates the workflow stored with *id*

Parameters

- **id** (*str*) – the encoded id of the workflow to update
- **payload** (*dict*) – a dictionary containing any or all the * workflow the json description of the workflow as would be

produced by GET workflows/<id>/download or given to *POST workflows*

The workflow contents will be updated to target this.

Return type dict

Returns serialized version of the workflow

update_invocation_step (*trans*, **args*, ***kwargs*)

PUT /api/workflows/{workflow_id}/invocation/{invocation_id}/steps/{step_id} Update state of running workflow step invocation - still very nebulous but this would be for stuff like confirming paused steps can proceed etc....

Parameters

- **workflow_id** (*str*) – the workflow id (required)
- **invocation_id** (*str*) – the usage id (required)
- **step_id** (*str*) – encoded id of the WorkflowInvocationStep (required)

Raises exceptions.MessageException, exceptions.ObjectNotFound

workflow_dict (*trans*, **args*, ***kwargs*)

GET /api/workflows/{encoded_workflow_id}/download Returns a selected workflow as a json dictionary.

controllers Package

controllers Package Galaxy web controllers.

admin Module

```
class galaxy.webapps.galaxy.controllers.admin.AdminGalaxy (app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.web.base.controllers.admin.AdminGalaxy, galaxy.actions.admin.AdminActions, galaxy.web.base.controller.UsesQuotaMixin, galaxy.web.params.QuotaParamParser

    check_for_tool_dependencies (trans, migration_stage)

    create_quota (trans, *args, **kwargs)

    delete_operation = <galaxy.web.framework.helpers.grids.GridOperation object>

    display_applications (trans, *args, **kwargs)

    edit_quota (trans, *args, **kwargs)

    group_list_grid = <galaxy.webapps.galaxy.controllers.admin.GroupListGrid object>

    impersonate (trans, *args, **kwargs)

    manage_users_and_groups_for_quota (trans, *args, **kwargs)

    mark_quota_deleted (trans, *args, **kwargs)

    purge_operation = <galaxy.web.framework.helpers.grids.GridOperation object>

    purge_quota (trans, *args, **kwargs)

    quota_list_grid = <galaxy.webapps.galaxy.controllers.admin.QuotaListGrid object>

    quotas (trans, *args, **kwargs)

    recalculate_user_disk_usage (trans, *args, **kwargs)

    reload_display_application (trans, *args, **kwargs)

    rename_quota (trans, *args, **kwargs)

    review_tool_migration_stages (trans, *args, **kwargs)

    role_list_grid = <galaxy.webapps.galaxy.controllers.admin.RoleListGrid object>

    set_quota_default (trans, *args, **kwargs)

    tool_errors (trans, *args, **kwargs)

    tool_version_list_grid = <galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid object>

    undelelete_operation = <galaxy.web.framework.helpers.grids.GridOperation object>

    undelelete_quota (trans, *args, **kwargs)

    unset_quota_default (trans, *args, **kwargs)

    user_list_grid = <galaxy.webapps.galaxy.controllers.admin.UserListGrid object>

    view_datatypes_registry (trans, *args, **kwargs)

    view_tool_data_tables (trans, *args, **kwargs)

class galaxy.webapps.galaxy.controllers.admin.GroupListGrid
    Bases: galaxy.web.framework.helpers.grids.Grid
```

```

class NameColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grids.TextColumn
    get_value (trans, grid, group)

class GroupListGrid.RolesColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grids.GridColumn
    get_value (trans, grid, group)

class GroupListGrid.StatusColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grids.GridColumn
    get_value (trans, grid, group)

class GroupListGrid.UsersColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grids.GridColumn
    get_value (trans, grid, group)

GroupListGrid.columns = [<galaxy.webapps.galaxy.controllers.admin.NameColumn object at 0x7f369fa52f10>, <galaxy.webapps.galaxy.controllers.admin.RolesColumn object at 0x7f369fa52f10>, <galaxy.webapps.galaxy.controllers.admin.StatusColumn object at 0x7f369fa52f10>, <galaxy.webapps.galaxy.controllers.admin.UsersColumn object at 0x7f369fa52f10>]
GroupListGrid.default_sort_key = 'name'
GroupListGrid.global_actions = [<galaxy.web.framework.helpers.grids.GridAction object at 0x7f369fa52650>]
GroupListGrid.model_class
    alias of Group
GroupListGrid.num_rows_per_page = 50
GroupListGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369fa52490>, <galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369fa52490>]
GroupListGrid.preserve_state = False
GroupListGrid.standard_filters = [<galaxy.web.framework.helpers.grids.GridColumnFilter object at 0x7f369fa52490>]
GroupListGrid.template = '/admin/dataset_security/group/grid.mako'
GroupListGrid.title = 'Groups'
GroupListGrid.use_paging = True

class galaxy.webapps.galaxy.controllers.admin.QuotaListGrid
    Bases: galaxy.web.framework.helpers.grids.Grid
    class AmountColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn
        get_value (trans, grid, quota)

```

```
class QuotaListGrid.DescriptionColumn (label,          key=None,          model_class=None,
                                         method=None,  format=None,  link=None,  at-
                                         tach_popup=False,  visible=True,  nowrap=False,
                                         filterable=None,          sortable=True,          la-
                                         bel_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.TextColumn`

`get_value` (*trans*, *grid*, *quota*)

```
class QuotaListGrid.GroupsColumn (label,  key=None,  model_class=None,  method=None,
                                   format=None,  link=None,  attach_popup=False,  visi-
                                   ble=True,  nowrap=False,  filterable=None,  sortable=True,
                                   label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.GridColumn`

`get_value` (*trans*, *grid*, *quota*)

```
class QuotaListGrid.NameColumn (label,  key=None,  model_class=None,  method=None,
                                 format=None,  link=None,  attach_popup=False,  visi-
                                 ble=True,  nowrap=False,  filterable=None,  sortable=True,
                                 label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.TextColumn`

`get_value` (*trans*, *grid*, *quota*)

```
class QuotaListGrid.StatusColumn (label,  key=None,  model_class=None,  method=None,
                                   format=None,  link=None,  attach_popup=False,  visi-
                                   ble=True,  nowrap=False,  filterable=None,  sortable=True,
                                   label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.GridColumn`

`get_value` (*trans*, *grid*, *quota*)

```
class QuotaListGrid.UsersColumn (label,  key=None,  model_class=None,  method=None,
                                  format=None,  link=None,  attach_popup=False,  visi-
                                  ble=True,  nowrap=False,  filterable=None,  sortable=True,
                                  label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.GridColumn`

`get_value` (*trans*, *grid*, *quota*)

`QuotaListGrid.columns` = [`<galaxy.webapps.galaxy.controllers.admin.NameColumn object at 0x7f369fa526d0>`, `<ga`

`QuotaListGrid.default_sort_key` = `'name'`

`QuotaListGrid.global_actions` = [`<galaxy.web.framework.helpers.grids.GridAction object at 0x7f369fa52e10>`]

`QuotaListGrid.model_class`
alias of `Quota`

`QuotaListGrid.num_rows_per_page` = `50`

`QuotaListGrid.operations` = [`<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369fa52890>`, `<g`

`QuotaListGrid.preserve_state` = `False`

`QuotaListGrid.standard_filters` = [`<galaxy.web.framework.helpers.grids.GridColumnFilter object at 0x7f369fa`

`QuotaListGrid.template` = `'/admin/quota/grid.mako'`

`QuotaListGrid.title` = `'Quotas'`

`QuotaListGrid.use_paging` = `True`


```

class galaxy.webapps.galaxy.controllers.admin.RoleListGrid
    Bases: galaxy.web.framework.helpers.grids.Grid

    class DescriptionColumn(label, key=None, model_class=None, method=None, format=None,
                            link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value(trans, grid, role)

    class RoleListGrid.GroupsColumn(label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.GridColumn

        get_value(trans, grid, role)

    class RoleListGrid.NameColumn(label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value(trans, grid, role)

    class RoleListGrid.StatusColumn(label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.GridColumn

        get_value(trans, grid, role)

    class RoleListGrid.TypeColumn(label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value(trans, grid, role)

    class RoleListGrid.UsersColumn(label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.GridColumn

        get_value(trans, grid, role)

    RoleListGrid.apply_query_filter(trans, query, **kwargs)

    RoleListGrid.columns = [<galaxy.webapps.galaxy.controllers.admin.NameColumn object at 0x7f369dba1cd0>, <galaxy.webapps.galaxy.controllers.admin.RoleListGrid.GroupsColumn object at 0x7f369dba1cd0>, <galaxy.webapps.galaxy.controllers.admin.RoleListGrid.NameColumn object at 0x7f369dba1cd0>, <galaxy.webapps.galaxy.controllers.admin.RoleListGrid.StatusColumn object at 0x7f369dba1cd0>, <galaxy.webapps.galaxy.controllers.admin.RoleListGrid.TypeColumn object at 0x7f369dba1cd0>, <galaxy.webapps.galaxy.controllers.admin.RoleListGrid.UsersColumn object at 0x7f369dba1cd0>]

    RoleListGrid.default_sort_key = 'name'

    RoleListGrid.global_actions = [<galaxy.web.framework.helpers.grids.GridAction object at 0x7f369dba1890>]

    RoleListGrid.model_class
        alias of Role

    RoleListGrid.num_rows_per_page = 50

    RoleListGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dba1c10>, <galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dba1c10>]

```

```
RoleListGrid.preserve_state = False
RoleListGrid.standard_filters = [<galaxy.web.framework.helpers.grids.GridColumnFilter object at 0x7f369db...
RoleListGrid.template = '/admin/dataset_security/role/grid.mako'
RoleListGrid.title = 'Roles'
RoleListGrid.use_paging = True

class galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid
    Bases: galaxy.web.framework.helpers.grids.Grid

    class ToolIdColumn (label, key=None, model_class=None, method=None, format=None, link=None,
                        attach_popup=False, visible=True, nowrap=False, filterable=None,
                        sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value (trans, grid, tool_version)

    class ToolVersionListGrid.ToolVersionsColumn (label, key=None, model_class=None,
                                                    method=None, format=None,
                                                    link=None, attach_popup=False,
                                                    visible=True, nowrap=False, fil-
                                                    terable=None, sortable=True, la-
                                                    bel_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value (trans, grid, tool_version)

    ToolVersionListGrid.build_initial_query (trans, **kwd)

    ToolVersionListGrid.columns = [<galaxy.webapps.galaxy.controllers.admin.ToolIdColumn object at 0x7f369fa52...
    ToolVersionListGrid.default_filter = {}
    ToolVersionListGrid.default_sort_key = 'tool_id'
    ToolVersionListGrid.global_actions = []
    ToolVersionListGrid.model_class
        alias of ToolVersion
    ToolVersionListGrid.num_rows_per_page = 50
    ToolVersionListGrid.operations = []
    ToolVersionListGrid.preserve_state = False
    ToolVersionListGrid.standard_filters = []
    ToolVersionListGrid.template = '/admin/tool_version/grid.mako'
    ToolVersionListGrid.title = 'Tool versions'
    ToolVersionListGrid.use_paging = True

class galaxy.webapps.galaxy.controllers.admin.UserListGrid
    Bases: galaxy.web.framework.helpers.grids.Grid

    class ActivatedColumn (label, key=None, model_class=None, method=None, format=None,
                            link=None, attach_popup=False, visible=True, nowrap=False, filter-
                            able=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.GridColumn

        get_value (trans, grid, user)
```

```

class UserListGrid.EmailColumn(label, key=None, model_class=None, method=None,
                                format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True,
                                label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.TextColumn
    get_value(trans, grid, user)

class UserListGrid.ExternalColumn(label, key=None, model_class=None, method=None,
                                    format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None,
                                    sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.GridColumn
    get_value(trans, grid, user)

class UserListGrid.GroupsColumn(label, key=None, model_class=None, method=None,
                                  format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True,
                                  label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.GridColumn
    get_value(trans, grid, user)

class UserListGrid.LastLoginColumn(label, key=None, model_class=None, method=None,
                                      format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None,
                                      sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.GridColumn
    get_value(trans, grid, user)

class UserListGrid.RolesColumn(label, key=None, model_class=None, method=None,
                                 format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True,
                                 label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.GridColumn
    get_value(trans, grid, user)

class UserListGrid.StatusColumn(label, key=None, model_class=None, method=None,
                                  format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True,
                                  label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.GridColumn
    get_value(trans, grid, user)

class UserListGrid.TimeCreatedColumn(label, key=None, model_class=None,
                                       method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False,
                                       filterable=None, sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.GridColumn
    get_value(trans, grid, user)

class UserListGrid.UserNameColumn(label, key=None, model_class=None, method=None,
                                    format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None,
                                    sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.TextColumn

```

```
    get_value (trans, grid, user)

UserListGrid.columns = [<galaxy.webapps.galaxy.controllers.admin.EmailColumn object at 0x7f369d003a10>, <galaxy.webapps.galaxy.controllers.admin.EmailColumn object at 0x7f369d003a10>]
UserListGrid.default_sort_key = 'email'
UserListGrid.get_current_item (trans, **kwargs)
UserListGrid.global_actions = [<galaxy.web.framework.helpers.grids.GridAction object at 0x7f369dba1dd0>]
UserListGrid.model_class
    alias of User
UserListGrid.num_rows_per_page = 50
UserListGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dba1f50>, <galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dba1f50>]
UserListGrid.preserve_state = False
UserListGrid.standard_filters = [<galaxy.web.framework.helpers.grids.GridColumnFilter object at 0x7f369dba1f50>]
UserListGrid.template = '/admin/user/grid.mako'
UserListGrid.title = 'Users'
UserListGrid.use_paging = True
```

admin_toolshed Module

```
class galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed (app)
```

```
    Bases: galaxy.webapps.galaxy.controllers.admin.AdminGalaxy
```

```
    activate_repository (trans, *args, **kwargs)
```

Activate a repository that was deactivated but not uninstalled.

```
    browse_repositories (trans, *args, **kwargs)
```

```
    browse_repository (trans, *args, **kwargs)
```

```
    browse_tool_dependency (trans, *args, **kwargs)
```

```
    browse_tool_shed (trans, *args, **kwargs)
```

```
    browse_tool_sheds (trans, *args, **kwargs)
```

```
    check_for_updates (trans, *args, **kwargs)
```

Send a request to the relevant tool shed to see if there are any updates.

```
    deactivate_or_uninstall_repository (trans, *args, **kwargs)
```

Handle all changes when a tool shed repository is being deactivated or uninstalled. Notice that if the repository contents include a file named `tool_data_table_conf.xml.sample`, its entries are not removed from the defined `config.shed_tool_data_table_config`. This is because it becomes a bit complex to determine if other installed repositories include tools that require the same entry. For now we'll never delete entries from `config.shed_tool_data_table_config`, but we may choose to do so in the future if it becomes necessary.

```
    display_image_in_repository (trans, **kwd)
```

Open an image file that is contained in an installed tool shed repository or that is referenced by a URL for display. The image can be defined in either a `README.rst` file contained in the repository or the help section of a Galaxy tool config that is contained in the repository. The following image definitions are all supported. The former `$PATH_TO_IMAGES` is no longer required, and is now ignored. .. image:: https://raw.githubusercontent.com/galaxy/some_image.png .. image:: `$PATH_TO_IMAGES/some_image.png` .. image:: `/static/images/some_image.gif` .. image:: `some_image.jpg` .. image:: `/deep/some_image.png`

```
    find_tools_in_tool_shed (trans, *args, **kwargs)
```

find_workflows_in_tool_shed (*trans*, *args, **kwargs)

generate_workflow_image (*trans*, *args, **kwargs)

Return an svg image representation of a workflow dictionary created when the workflow was exported.

get_file_contents (*trans*, *args, **kwargs)

get_tool_dependencies (*trans*, *args, **kwargs)

Send a request to the appropriate tool shed to retrieve the dictionary of tool dependencies defined for the received repository name, owner and changeset revision. The received repository_id is the encoded id of the installed tool shed repository in Galaxy. We need it so that we can derive the tool shed from which it was installed.

get_updated_repository_information (*trans*, *args, **kwargs)

Send a request to the appropriate tool shed to retrieve the dictionary of information required to reinstall an updated revision of an uninstalled tool shed repository.

import_workflow (*trans*, *args, **kwargs)

Import a workflow contained in an installed tool shed repository into Galaxy.

initiate_tool_dependency_installation (*trans*, *args, **kwargs)

Install specified dependencies for repository tools. The received list of tool_dependencies are the database records for those dependencies defined in the tool_dependencies.xml file (contained in the repository) that should be installed. This allows for filtering out dependencies that have not been checked for installation on the 'Manage tool dependencies' page for an installed tool shed repository.

install_latest_repository_revision (*trans*, *args, **kwargs)

Install the latest installable revision of a repository that has been previously installed.

install_tool_dependencies_with_update (*trans*, *args, **kwargs)

Updating an installed tool shed repository where new tool dependencies but no new repository dependencies are included in the updated revision.

installed_repository_grid = <tool_shed.galaxy_install.grids.admin_toolshed_grids.InstalledRepositoryGrid object>

manage_repositories (*trans*, *args, **kwargs)

manage_repository (*trans*, *args, **kwargs)

manage_repository_tool_dependencies (*trans*, *args, **kwargs)

manage_tool_dependencies (*trans*, *args, **kwargs)

monitor_repository_installation (*trans*, *args, **kwargs)

open_folder (*trans*, *args, **kwargs)

prepare_for_install (*trans*, *args, **kwargs)

purge_repository (*trans*, *args, **kwargs)

Purge a "white ghost" repository from the database.

reinstall_repository (*trans*, *args, **kwargs)

Reinstall a tool shed repository that has been previously uninstalled, making sure to handle all repository and tool dependencies of the repository.

repair_repository (*trans*, *args, **kwargs)

Inspect the repository dependency hierarchy for a specified repository and attempt to make sure they are all properly installed as well as each repository's tool dependencies.

repair_tool_shed_repositories (*trans*, *args, **kwargs)

Repair specified tool shed repositories.

repository_installation_grid = <tool_shed.galaxy_install.grids.admin_toolshed_grids.RepositoryInstallationGrid object>

repository_installation_status_updates (*trans*, *args, **kwargs)

reselect_tool_panel_section (*trans*, *args, **kwargs)

Select or change the tool panel section to contain the tools included in the tool shed repository being reinstalled. If there are updates available for the repository in the tool shed, the tool_dependencies and repository_dependencies associated with the updated changeset revision will have been retrieved from the tool shed and passed in the received kwd. In this case, the stored tool shed repository metadata from the Galaxy database will not be used since it is outdated.

reset_metadata_on_selected_installed_repositories (*trans*, *args, **kwargs)

reset_repository_metadata (*trans*, *args, **kwargs)

Reset all metadata on a single installed tool shed repository.

reset_to_install (*trans*, *args, **kwargs)

An error occurred while cloning the repository, so reset everything necessary to enable another attempt.

set_tool_versions (*trans*, *args, **kwargs)

Get the tool_versions from the tool shed for each tool in the installed revision of a selected tool shed repository and update the metadata for the repository's revision in the Galaxy database.

tool_dependency_grid = <tool_shed.galaxy_install.grid.admin_toolshed_grid.ToolDependencyGrid object>

tool_dependency_status_updates (*trans*, *args, **kwargs)

uninstall_tool_dependencies (*trans*, *args, **kwargs)

update_to_changeset_revision (*trans*, *args, **kwargs)

Update a cloned repository to the latest revision possible.

update_tool_shed_status_for_installed_repository (*trans*, *args, **kwargs)

view_tool_metadata (*trans*, *args, **kwargs)

view_workflow (*trans*, *args, **kwargs)

Retrieve necessary information about a workflow from the database so that it can be displayed in an svg image.

async Module Upload class

class galaxy.webapps.galaxy.controllers.async.**ASync** (*app*)

Bases: *galaxy.web.base.controller.BaseUIController*

default (*trans*, *tool_id=None*, *data_id=None*, *data_secret=None*, **kwd)

Catches the tool id and redirects as needed

index (*trans*, *tool_id=None*, *data_secret=None*, **kwd)

Manages asynchronous connections

cloudlaunch Module

data_admin Module

dataset Module

class galaxy.webapps.galaxy.controllers.dataset.**DatasetInterface** (*app*)

Bases: *galaxy.web.base.controller.BaseUIController*, *galaxy.model.item_attrs.UsesAnnotation*, *galaxy.model.item_attrs.UsesItemRatings*, *galaxy.web.base.controller.UsesExtendedMetadata*

annotate_async (*trans*, *id*, *new_annotation=None*, ***kwargs*)

copy_datasets (*trans*, *source_history=None*, *source_content_ids=''*, *target_history_id=None*, *target_history_ids=''*, *new_history_name=''*, *do_copy=False*, ***kwd*)

default (*trans*, *dataset_id=None*, ***kwd*)

delete (*trans*, *dataset_id*, *filename*, *show_deleted_on_refresh=False*)

delete_async (*trans*, *dataset_id*, *filename*)

display (*trans*, *dataset_id=None*, *preview=False*, *filename=None*, *to_ext=None*, *chunk=None*, ***kwd*)

display_application (*trans*, *dataset_id=None*, *user_id=None*, *app_name=None*, *link_name=None*, *app_action=None*, *action_param=None*, *action_param_extra=None*, ***kws*)
Access to external display applications

display_at (*trans*, *dataset_id*, *filename=None*, ***kwd*)
Sets up a dataset permissions so it is viewable at an external site

display_by_username_and_slug (*trans*, *username*, *slug*, *filename=None*, *preview=True*)
Display dataset by username and slug; because datasets do not yet have slugs, the slug is the dataset's id.

edit (*trans*, *dataset_id=None*, *filename=None*, *hid=None*, ***kwd*)
Allows user to modify parameters of an HDA.

errors (*trans*, *id*)

exit_code (*trans*, *dataset_id=None*, ***kwargs*)

get_annotation_async (*trans*, *id*)

get_embed_html_async (*trans*, *id*)
Returns HTML for embedding a dataset in a page.

get_item_content_async (*trans*, *id*)
Returns item content in HTML format.

get_metadata_file (*trans*, *hda_id*, *metadata_name*)
Allows the downloading of metadata files associated with datasets (eg. bai index for bam files)

get_name_and_link_async (*trans*, **args*, ***kwargs*)
Returns dataset's name and link.

imp (*trans*, *dataset_id=None*, ***kwd*)
Import another user's dataset via a shared URL; dataset is added to user's current history.

list (*trans*, **args*, ***kwargs*)
List all available datasets

purge (*trans*, *dataset_id*, *filename*, *show_deleted_on_refresh=False*)

purge_async (*trans*, *dataset_id*, *filename*)

rate_async (*trans*, **args*, ***kwargs*)
Rate a dataset asynchronously and return updated community data.

report_error (*trans*, *id*, *email=''*, *message=''*, ***kwd*)

set_accessible_async (*trans*, **args*, ***kwargs*)
Does nothing because datasets do not have an importable/accessible attribute. This method could potentially set another attribute.

```

show_params (trans, dataset_id=None, from_noframe=None, **kwd)
    Show the parameters used for the job associated with an HDA

stderr (trans, dataset_id=None, **kwargs)

stdout (trans, dataset_id=None, **kwargs)

stored_list_grid = <galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAssociationListGrid object>

transfer_status (trans, *args, **kwargs)
    Primarily used for the S3ObjectStore - get the status of data transfer if the file is not in cache

undelelete (trans, dataset_id, filename)

undelelete_async (trans, dataset_id, filename)

unhide (trans, dataset_id, filename)

class galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAssociationListGrid
    Bases: galaxy.web.framework.helpers.grid.Grid

    class HistoryColumn (label, key=None, model_class=None, method=None, format=None,
                        link=None, attach_popup=False, visible=True, nowrap=False, filterable=None,
                        sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.GridColumn

        get_value (trans, grid, hda)

    class HistoryDatasetAssociationListGrid.StatusColumn (label,
                                                         key=None,
                                                         model_class=None,
                                                         method=None,
                                                         format=None,
                                                         link=None,
                                                         attach_popup=False,
                                                         visible=True,
                                                         nowrap=False,
                                                         filterable=None,
                                                         sortable=True,
                                                         label_id_prefix=None,
                                                         inbound=False)
        Bases: galaxy.web.framework.helpers.grid.GridColumn

        get_accepted_filters ()
            Returns a list of accepted filters for this column.

        get_value (trans, grid, hda)

HistoryDatasetAssociationListGrid.build_initial_query (trans, **kwargs)

HistoryDatasetAssociationListGrid.columns = [<galaxy.web.framework.helpers.grid.TextColumn object at

HistoryDatasetAssociationListGrid.default_filter = {'deleted': 'False', 'name': 'All', 'tags': 'All'}

HistoryDatasetAssociationListGrid.default_sort_key = 'update_time'

HistoryDatasetAssociationListGrid.model_class
    alias of HistoryDatasetAssociation

HistoryDatasetAssociationListGrid.num_rows_per_page = 50

HistoryDatasetAssociationListGrid.operations = [<galaxy.web.framework.helpers.grid.GridOperation ob

HistoryDatasetAssociationListGrid.preserve_state = False

HistoryDatasetAssociationListGrid.standard_filters = []

HistoryDatasetAssociationListGrid.template = '/dataset/grid.mako'

HistoryDatasetAssociationListGrid.title = 'Saved Datasets'

```



```
HistoryDatasetAssociationListGrid.use_async = True
```

```
HistoryDatasetAssociationListGrid.use_paging = True
```

error Module

```
class galaxy.webapps.galaxy.controllers.error.Error(app)
```

```
Bases: galaxy.web.base.controller.BaseUIController
```

```
index(trans)
```

external_service Module

```
class galaxy.webapps.galaxy.controllers.external_service.ExternalService(app)
```

```
Bases: galaxy.web.base.controller.BaseUIController, galaxy.web.base.controller.UsesFormDe
```

```
browse_external_services(trans, *args, **kwargs)
```

```
create_external_service(trans, *args, **kwargs)
```

```
delete_external_service(trans, *args, **kwargs)
```

```
edit_external_service(trans, *args, **kwargs)
```

```
edit_external_service_form_definition(trans, *args, **kwargs)
```

```
external_service_grid = <galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGrid object>
```

```
get_external_service_type(trans, external_service_type_id, ac-
tion='browse_external_services')
```

```
reload_external_service_types(trans, *args, **kwargs)
```

```
undelele_external_service(trans, *args, **kwargs)
```

```
update_external_service_form_definition(trans, *args, **kwargs)
```

```
view_external_service(trans, *args, **kwargs)
```

```
class galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGrid
```

```
Bases: galaxy.web.framework.helpers.grid.Grid
```

```
class ExternalServiceTypeColumn(label, key=None, model_class=None, method=None,
format=None, link=None, attach_popup=False, visi-
ble=True, nowrap=False, filterable=None, sortable=True,
label_id_prefix=None, inbound=False)
```

```
Bases: galaxy.web.framework.helpers.grid.TextColumn
```

```
get_value(trans, grid, external_service)
```

```
class ExternalServiceGrid.NameColumn(label, key=None, model_class=None,
method=None, format=None, link=None, at-
tach_popup=False, visible=True, nowrap=False,
filterable=None, sortable=True, la-
bel_id_prefix=None, inbound=False)
```

```
Bases: galaxy.web.framework.helpers.grid.TextColumn
```

```
get_value(trans, grid, external_service)
```

```
ExternalServiceGrid.columns = [<galaxy.webapps.galaxy.controllers.external_service.NameColumn object at 0x7
```

```
ExternalServiceGrid.default_filter = {'deleted': 'False'}
```

```
ExternalServiceGrid.default_sort_key = '-create_time'
```

```
ExternalServiceGrid.global_actions = [<galaxy.web.framework.helpers.grid.GridAction object at 0x7f36992
```

```
ExternalServiceGrid.model_class
    alias of ExternalService

ExternalServiceGrid.num_rows_per_page = 50

ExternalServiceGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dd8f...

ExternalServiceGrid.preserve_state = True

ExternalServiceGrid.template = 'admin/external_service/grid.mako'

ExternalServiceGrid.title = 'External Services'

ExternalServiceGrid.use_paging = True
```

external_services Module

```
class galaxy.webapps.galaxy.controllers.external_services.ExternalServiceController (app)
    Bases: galaxy.web.base.controller.BaseUIController

    access_action (trans, *args, **kwargs)
```

forms Module

```
class galaxy.webapps.galaxy.controllers.forms.Forms (app)
    Bases: galaxy.web.base.controller.BaseUIController

    browse_form_definitions (trans, *args, **kwargs)

    build_form_definition_field_widgets (trans, layout_grids, field_index, field, form_type)
        This method returns a list of widgets which describes a form definition field. This includes the field label,
        helptext, type, selectfield options, required/optional & layout

    create_form_definition (trans, *args, **kwargs)

    delete_form_definition (trans, *args, **kwargs)

    edit_form_definition (trans, *args, **kwargs)
        This callback method is for handling form editing. The value of response_redirect should be an URL that
        is defined by the caller. This allows for redirecting as desired when the form changes have been saved.
        For an example of how this works, see the edit_template() method in the base controller.

    empty_field = {'visible': True, 'helptext': '', 'name': '', 'default': '', 'layout': 'none', 'selectlist': [], 'required': False,

    forms_grid = <galaxy.webapps.galaxy.controllers.forms.FormsGrid object>

    get_current_form (trans, **kwd)
        This method gets all the unsaved user-entered form details and returns a dictionary containing the name,
        desc, type, layout & fields of the form

    get_saved_form (form_definition)
        This retrieves the saved form and returns a dictionary containing the name, desc, type, layout & fields of
        the form

    save_form_definition (trans, form_definition_current_id=None, **kwd)
        This method saves the current form

    show_editable_form_definition (trans, form_definition, current_form, message='', sta-
        tus='done', response_redirect=None, **kwd)
        Displays the form and any of the changes made to it in edit mode. In this method all the widgets are build
        for all name, description and all the fields of a form definition.

    undelete_form_definition (trans, *args, **kwargs)
```

```

view_latest_form_definition (trans, *args, **kwargs)
    Displays the layout of the latest version of the form definition
class galaxy.webapps.galaxy.controllers.forms.FormsGrid
    Bases: galaxy.web.framework.helpers.grid.Grid

    class DescriptionColumn (label, key=None, model_class=None, method=None, format=None,
                               link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.TextColumn

        get_value (trans, grid, form)

    class FormsGrid.NameColumn (label, key=None, model_class=None, method=None, format=None,
                                   link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.TextColumn

        get_value (trans, grid, form)

    class FormsGrid.TypeColumn (label, key=None, model_class=None, method=None, format=None,
                                   link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.TextColumn

        get_value (trans, grid, form)

FormsGrid.build_initial_query (trans, **kwargs)

FormsGrid.columns = [<galaxy.webapps.galaxy.controllers.forms.NameColumn object at 0x7f3693fb9fd0>, <galaxy.w

FormsGrid.default_filter = {'deleted': 'False'}

FormsGrid.default_sort_key = '-create_time'

FormsGrid.global_actions = [<galaxy.web.framework.helpers.grid.GridAction object at 0x7f36974b4850>]

FormsGrid.model_class
    alias of FormDefinitionCurrent

FormsGrid.num_rows_per_page = 50

FormsGrid.operations = [<galaxy.web.framework.helpers.grid.GridOperation object at 0x7f36974b4b50>, <galaxy.w

FormsGrid.preserve_state = True

FormsGrid.template = 'admin/forms/grid.mako'

FormsGrid.title = 'Forms'

FormsGrid.use_paging = True

```

history Module

```

class galaxy.webapps.galaxy.controllers.history.HistoryAllPublishedGrid
    Bases: galaxy.web.framework.helpers.grid.Grid

    class NameURLColumn (label, key=None, model_class=None, method=None, format=None,
                           link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases:
            galaxy.web.framework.helpers.grid.PublicURLColumn,
            galaxy.webapps.galaxy.controllers.history.NameColumn

    HistoryAllPublishedGrid.apply_query_filter (trans, query, **kwargs)

```

```

HistoryAllPublishedGrid.build_initial_query (trans, **kwargs)

HistoryAllPublishedGrid.columns = [<galaxy.webapps.galaxy.controllers.history.NameURLColumn object at 0x

HistoryAllPublishedGrid.default_filter = {'username': 'All', 'public_url': 'All', 'tags': 'All'}

HistoryAllPublishedGrid.default_sort_key = 'update_time'

HistoryAllPublishedGrid.model_class
    alias of History

HistoryAllPublishedGrid.num_rows_per_page = 50

HistoryAllPublishedGrid.operations = []

HistoryAllPublishedGrid.title = 'Published Histories'

HistoryAllPublishedGrid.use_async = True

HistoryAllPublishedGrid.use_paging = True
class galaxy.webapps.galaxy.controllers.history.HistoryController (app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.web.base.controller.SharableMixi
galaxy.model.item_attrs.UsesAnnotations, galaxy.model.item_attrs.UsesItemRatings,
galaxy.web.base.controller.ExportsHistoryMixin, galaxy.web.base.controller.ImportsHisto

    citations (trans)

    copy (trans, *args, **kwargs)
        Copy one or more histories

    create_new_current (trans, *args, **kwargs)

    current_history_json (trans, *args, **kwargs)

    delete_current (trans, purge=False)
        Delete just the active history – this does not require a logged in user.

    delete_hidden_datasets (trans)
        This method deletes all hidden datasets in the current history.

    display_by_username_and_slug (trans, username, slug)
        Display history based on a username and slug.

    display_structured (trans, id=None)
        Display a history as a nested structure showing the jobs and workflow invocations that created each dataset
        (if any).

    export_archive (trans, id=None, gzip=True, include_hidden=False, include_deleted=False, pre-
        view=False)
        Export a history to an archive.

    get_item (trans, id)

    get_name_and_link_async (trans, *args, **kwargs)
        Returns history's name and link.

    history_data (trans, history)

    imp (trans, id=None, confirm=False, **kwd)
        Import another user's history via a shared URL

    import_archive (trans, *args, **kwargs)
        Import a history from a file archive.

    index (trans)

```

```

list (trans, *args, **kwargs)
    List all available histories

list_as_xml (trans)
    XML history list for functional tests

list_published (trans, **kwargs)

list_shared (trans, *args, **kwargs)
    List histories shared with current user by others

name_autocomplete_data (trans, q=None, limit=None, timestamp=None)
    Return autocomplete data for history names

published_list_grid = <galaxy.webapps.galaxy.controllers.history.HistoryAllPublishedGrid object>

purge_deleted_datasets (trans)

rate_async (trans, *args, **kwargs)
    Rate a history asynchronously and return updated community data.

rename (trans, *args, **kwargs)

resume_paused_jobs (trans, current=False, ids=None)
    Resume paused jobs the active history – this does not require a logged in user.

set_accessible_async (trans, *args, **kwargs)
    Set history's importable attribute and slug.

set_as_current (trans, *args, **kwargs)

share (trans, *args, **kwargs)

share_restricted (trans, *args, **kwargs)

shared_list_grid = <galaxy.webapps.galaxy.controllers.history.SharedHistoryListGrid object>

sharing (trans, *args, **kwargs)
    Handle history sharing.

stored_list_grid = <galaxy.webapps.galaxy.controllers.history.HistoryListGrid object>

structure (trans, id=None, **kwargs)

switch_to_history (trans, *args, **kwargs)

unhide_datasets (trans, current=False, ids=None)
    Unhide the datasets in the active history – this does not require a logged in user.

view (trans, id=None, show_deleted=False, show_hidden=False, use_panels=True)
    View a history. If a history is importable, then it is viewable by any user.

view_multiple (trans, include_deleted_histories=False, order='update')

class galaxy.webapps.galaxy.controllers.history.HistoryListGrid
    Bases: galaxy.web.framework.helpers.grid.Grid

    class DatasetsByStateColumn (label, key=None, model_class=None, method=None,
                                format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True,
                                label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.GridColumn

        get_value (trans, grid, history)

```

```
class HistoryListGrid.DeletedColumn (label, key=None, model_class=None, method=None,
                                     format=None, link=None, attach_popup=False,
                                     visible=True, nowrap=False, filterable=None,
                                     sortable=True, label_id_prefix=None, in-
                                     bound=False)
    Bases: galaxy.web.framework.helpers.grids.DeletedColumn

    get_value (trans, grid, history)

    sort (trans, query, ascending, column_name=None)

class HistoryListGrid.HistoryListNameColumn (label, key=None, model_class=None,
                                              method=None, format=None, link=None,
                                              attach_popup=False, visible=True,
                                              nowrap=False, filterable=None,
                                              sortable=True, label_id_prefix=None,
                                              inbound=False)
    Bases: galaxy.webapps.galaxy.controllers.history.NameColumn

    get_link (trans, grid, history)

HistoryListGrid.apply_query_filter (trans, query, **kwargs)

HistoryListGrid.columns = [<galaxy.webapps.galaxy.controllers.history.HistoryListNameColumn object at 0x7f3690234690>,
HistoryListGrid.default_filter = {'deleted': 'False', 'sharing': 'All', 'name': 'All', 'tags': 'All'}
HistoryListGrid.default_sort_key = '-update_time'
HistoryListGrid.get_current_item (trans, **kwargs)
HistoryListGrid.info_text = 'Histories that have been deleted for more than a time period specified by the Galaxy'
HistoryListGrid.model_class
    alias of History
HistoryListGrid.num_rows_per_page = 50
HistoryListGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f3690234690>,
HistoryListGrid.preserve_state = False
HistoryListGrid.standard_filters = [<galaxy.web.framework.helpers.grids.GridColumnFilter object at 0x7f3690234690>,
HistoryListGrid.template = '/history/grid.mako'
HistoryListGrid.title = 'Saved Histories'
HistoryListGrid.use_async = True
HistoryListGrid.use_paging = True

class galaxy.webapps.galaxy.controllers.history.NameColumn (label, key=None,
                                                            model_class=None,
                                                            method=None, for-
                                                            mat=None, link=None,
                                                            attach_popup=False,
                                                            visible=True,
                                                            nowrap=False,
                                                            filterable=None,
                                                            sortable=True, la-
                                                            bel_id_prefix=None,
                                                            inbound=False)
    Bases: galaxy.web.framework.helpers.grids.TextColumn
```

```

    get_value (trans, grid, history)

class galaxy.webapps.galaxy.controllers.history.SharedHistoryListGrid
    Bases: galaxy.web.framework.helpers.grids.Grid

    class DatasetsByStateColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.GridColumn

        get_value (trans, grid, history)

    class SharedHistoryListGrid.SharedByColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.GridColumn

        get_value (trans, grid, history)

    SharedHistoryListGrid.apply_query_filter (trans, query, **kwargs)

    SharedHistoryListGrid.build_initial_query (trans, **kwargs)

    SharedHistoryListGrid.columns = [<galaxy.web.framework.helpers.grids.GridColumn object at 0x7f3690234950>]

    SharedHistoryListGrid.default_filter = {}

    SharedHistoryListGrid.default_sort_key = '-update_time'

    SharedHistoryListGrid.model_class
        alias of History

    SharedHistoryListGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f3690234950>]

    SharedHistoryListGrid.standard_filters = []

    SharedHistoryListGrid.title = 'Histories shared with you by others'

library Module

class galaxy.webapps.galaxy.controllers.library.Library (app)
    Bases: galaxy.web.base.controller.BaseUIController

    browse_libraries (trans, **kwd)

    index (trans, **kwd)

    library_list_grid = <galaxy.webapps.galaxy.controllers.library.LibraryListGrid object>

    list (trans, **kwd)

class galaxy.webapps.galaxy.controllers.library.LibraryListGrid
    Bases: galaxy.web.framework.helpers.grids.Grid

    class DescriptionColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value (trans, grid, library)

```



```
class LibraryListGrid.NameColumn(label, key=None, model_class=None, method=None,
                                format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True,
                                label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.TextColumn

    get_value(trans, grid, library)

LibraryListGrid.apply_query_filter(trans, query, **kwd)
LibraryListGrid.build_initial_query(trans, **kwargs)
LibraryListGrid.columns = [<galaxy.webapps.galaxy.controllers.library.NameColumn object at 0x7f3690eb7dd0>,
LibraryListGrid.default_filter = {'deleted': 'False', 'description': 'All', 'purged': 'False', 'name': 'All'}
LibraryListGrid.default_sort_key = 'name'
LibraryListGrid.model_class
    alias of Library

LibraryListGrid.num_rows_per_page = 50
LibraryListGrid.preserve_state = False
LibraryListGrid.standard_filters = []
LibraryListGrid.template = '/library/grid.mako'
LibraryListGrid.title = 'Data Libraries'
LibraryListGrid.use_paging = True
```

library_admin Module

```
class galaxy.webapps.galaxy.controllers.library_admin.LibraryAdmin(app)
    Bases: galaxy.web.base.controller.BaseUIController

    browse_libraries(trans, *args, **kwargs)
    create_library(trans, *args, **kwargs)
    delete_library(trans, *args, **kwargs)
    library_list_grid = <galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid object>
    purge_library(trans, *args, **kwargs)
    undelete_library(trans, *args, **kwargs)
class galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid
    Bases: galaxy.web.framework.helpers.grid.Grid

    class DescriptionColumn(label, key=None, model_class=None, method=None, format=None,
                            link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.TextColumn

        get_value(trans, grid, library)

    class LibraryListGrid.NameColumn(label, key=None, model_class=None, method=None,
                                    format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True,
                                    label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.TextColumn

        get_value(trans, grid, library)
```



```

class LibraryListGrid.StatusColumn (label, key=None, model_class=None, method=None,
                                     format=None, link=None, attach_popup=False,
                                     visible=True, nowrap=False, filterable=None,
                                     sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grids.GridColumn

    get_value (trans, grid, library)

LibraryListGrid.columns = [<galaxy.webapps.galaxy.controllers.library_admin.NameColumn object at 0x7f3690e1...
LibraryListGrid.default_filter = {'deleted': 'False', 'description': 'All', 'purged': 'False', 'name': 'All'}
LibraryListGrid.default_sort_key = 'name'
LibraryListGrid.global_actions = [<galaxy.web.framework.helpers.grids.GridAction object at 0x7f3690e341d0...
LibraryListGrid.model_class
    alias of Library

LibraryListGrid.num_rows_per_page = 50
LibraryListGrid.preserve_state = False
LibraryListGrid.standard_filters = [<galaxy.web.framework.helpers.grids.GridColumnFilter object at 0x7f36...
LibraryListGrid.template = '/admin/library/grid.mako'
LibraryListGrid.title = 'Data Libraries'
LibraryListGrid.use_paging = True

```

library_common Module

```

class galaxy.webapps.galaxy.controllers.library_common.LibraryCommon (app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.web.base.controller.UsesFormDe...
           galaxy.web.base.controller.UsesExtendedMetadataMixin,
           galaxy.web.base.controller.UsesLibraryMixinItems

    act_on_multiple_datasets (trans, cntrller, library_id=None, ldda_ids='', **kwd)

    add_history_datasets_to_library (trans, cntrller, library_id, folder_id, hda_ids='', **kwd)

    browse_library (trans, cntrller='library', **kwd)

    create_folder (trans, cntrller, parent_id, library_id, **kwd)

    delete_library_item (trans, cntrller, library_id, item_id, item_type, **kwd)

    download_dataset_from_folder (trans, cntrller, id, library_id=None, **kwd)
        Catches the dataset id and displays file contents as directed

    folder_info (trans, cntrller, id, library_id, **kwd)

    folder_permissions (trans, cntrller, id, library_id, **kwd)

    get_path_paste_uploaded_datasets (trans, cntrller, params, library_bunch, response_code,
                                     message)

    get_server_dir_uploaded_datasets (trans, cntrller, params, full_dir, import_dir_desc, li-
                                     brary_bunch, response_code, message)

    import_datasets_to_histories (trans, cntrller, library_id='', folder_id='',
                                 ldda_ids='', target_history_id='', target_history_ids='',
                                 new_history_name='', **kwd)

    ldda_edit_info (trans, cntrller, library_id, folder_id, id, **kwd)

```

```

ldda_info (trans, cntrller, library_id, folder_id, id, **kwd)
ldda_permissions (trans, cntrller, library_id, folder_id, id, **kwd)
library_dataset_info (trans, cntrller, id, library_id, **kwd)
library_dataset_permissions (trans, cntrller, id, library_id, **kwd)
library_info (trans, cntrller, **kwd)
library_item_updates (trans, *args, **kwargs)
library_permissions (trans, cntrller, **kwd)
make_library_item_public (trans, cntrller, library_id, item_type, id, **kwd)
make_library_uploaded_dataset (trans, cntrller, params, name, path, type, library_bunch,
                                in_folder=None)
manage_template_inheritance (trans, cntrller, item_type, library_id, folder_id=None,
                               ldda_id=None, **kwd)
move_library_item (trans, cntrller, item_type, item_id, source_library_id='',
                    make_target_current=True, **kwd)
undelele_library_item (trans, cntrller, library_id, item_id, item_type, **kwd)
upload_dataset (trans, cntrller, library_id, folder_id, replace_dataset=None, **kwd)
upload_library_dataset (trans, cntrller, library_id, folder_id, **kwd)
galaxy.webapps.galaxy.controllers.library_common.activatable_folders (trans,
                                                                    folder)
galaxy.webapps.galaxy.controllers.library_common.activatable_folders_and_library_datasets (trans,
                                                                    folder)
galaxy.webapps.galaxy.controllers.library_common.active_folders (trans, folder)
galaxy.webapps.galaxy.controllers.library_common.active_folders_and_library_datasets (trans,
                                                                    folder)
galaxy.webapps.galaxy.controllers.library_common.branch_deleted (folder)
galaxy.webapps.galaxy.controllers.library_common.datasets_for_lddas (trans, lddas)

    Given a list of LDDAs, return a list of Datasets for them.

galaxy.webapps.galaxy.controllers.library_common.get_comptypes (trans)
galaxy.webapps.galaxy.controllers.library_common.get_containing_library_from_library_dataset (trans,
                                                                    cn-
                                                                    tr-
                                                                    ller,
                                                                    items,
                                                                    sort_att)

galaxy.webapps.galaxy.controllers.library_common.lucene_search (trans, cntrller,
                                                                    search_term,
                                                                    search_url,
                                                                    **kwd)

    Return display of results from a full-text lucene search of data libraries.

```

`galaxy.webapps.galaxy.controllers.library_common.map_library_datasets_to_lddas` (*trans*, *lib_datasets*)

Given a list of LibraryDatasets, return a map from the LibraryDatasets to their LDDAs. If an LDDA does not exist for a LibraryDataset, then there will be no entry in the return hash.

`galaxy.webapps.galaxy.controllers.library_common.sort_by_attr` (*seq*, *attr*)

Sort the sequence of objects by object's attribute Arguments: *seq* - the list or any sequence (including immutable one) of objects to sort. *attr* - the name of attribute to sort by

`galaxy.webapps.galaxy.controllers.library_common.whoosh_search` (*trans*, *cntrlr*, *search_term*, ***kwd*)

Return display of results from a full-text whoosh search of data libraries.

mobile Module

class `galaxy.webapps.galaxy.controllers.mobile.Mobile` (*app*)

Bases: `galaxy.web.base.controller.BaseUIController`

dataset_detail (*trans*, *id*)

dataset_peek (*trans*, *id*)

history_detail (*trans*, *id*)

history_list (*trans*)

index (*trans*, ***kwargs*)

settings (*trans*, *email=None*, *password=None*)

page Module

class `galaxy.webapps.galaxy.controllers.page.HistoryDatasetAssociationSelectionGrid`

Bases: `galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid`

Grid for selecting HDAs.

apply_query_filter (*trans*, *query*, ***kwargs*)

columns = [`<galaxy.webapps.galaxy.controllers.page.NameColumn object at 0x7f368f1499d0>`, `<galaxy.web.framework.L`

model_class

alias of `HistoryDatasetAssociation`

title = 'Saved Datasets'

class `galaxy.webapps.galaxy.controllers.page.HistorySelectionGrid`

Bases: `galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid`

Grid for selecting histories.

apply_query_filter (*trans*, *query*, ***kwargs*)

columns = [`<galaxy.webapps.galaxy.controllers.page.NameColumn object at 0x7f368f006050>`, `<galaxy.web.framework.L`

model_class

alias of `History`

title = 'Saved Histories'

class `galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid`

Bases: `galaxy.web.framework.helpers.grid.Grid`

Base class for pages' item selection grids.

```
class NameColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grid.TextColumn

    get_value (trans, grid, item)

ItemSelectionGrid.apply_query_filter (trans, query, **kwargs)
ItemSelectionGrid.default_filter = {'deleted': 'False', 'sharing': 'All'}
ItemSelectionGrid.default_sort_key = 'update_time'
ItemSelectionGrid.num_rows_per_page = 10
ItemSelectionGrid.show_item_checkboxes = True
ItemSelectionGrid.template = '/page/select_items_grid.mako'
ItemSelectionGrid.use_async = True
ItemSelectionGrid.use_paging = True

class galaxy.webapps.galaxy.controllers.page.PageAllPublishedGrid
    Bases: galaxy.web.framework.helpers.grid.Grid

    apply_query_filter (trans, query, **kwargs)
    build_initial_query (trans, **kwargs)
    columns = [<galaxy.web.framework.helpers.grid.PublicURLColumn object at 0x7f368f077e90>, <galaxy.web.framework.helpers.grid.PublicURLColumn object at 0x7f368f077e90>]
    default_filter = {'username': 'All', 'title': 'All'}
    default_sort_key = 'update_time'
    model_class
        alias of Page
    title = 'Published Pages'
    use_async = True
    use_panels = True

class galaxy.webapps.galaxy.controllers.page.PageController (app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.web.base.controller.SharableMixin, galaxy.web.base.controller.UsesStoredWorkflowMixin, galaxy.web.base.controller.UsesVisualizerMixin, galaxy.model.item_attrs.UsesItemRatings

    create (trans, *args, **kwargs)
        Create a new page

    display (trans, *args, **kwargs)

    display_by_username_and_slug (trans, username, slug)
        Display page based on a username and slug.

    edit (trans, *args, **kwargs)
        Edit a page's attributes.

    edit_content (trans, *args, **kwargs)
        Render the main page editor interface.

    get_editor_iframe (trans)
        Returns the document for the page editor's iframe.
```

```

get_embed_html_async (trans, id)
    Returns HTML for embedding a workflow in a page.

get_item (trans, id)

get_name_and_link_async (trans, *args, **kwargs)
    Returns page's name and link.

get_page (trans, id, check_ownership=True, check_accessible=False)
    Get a page from the database by id.

list (trans, *args, **kwargs)
    List user's pages.

list_datasets_for_selection (trans, *args, **kwargs)
    Returns HTML that enables a user to select one or more datasets.

list_histories_for_selection (trans, *args, **kwargs)
    Returns HTML that enables a user to select one or more histories.

list_pages_for_selection (trans, *args, **kwargs)
    Returns HTML that enables a user to select one or more pages.

list_published (trans, *args, **kwargs)

list_visualizations_for_selection (trans, *args, **kwargs)
    Returns HTML that enables a user to select one or more visualizations.

list_workflows_for_selection (trans, *args, **kwargs)
    Returns HTML that enables a user to select one or more workflows.

rate_async (trans, *args, **kwargs)
    Rate a page asynchronously and return updated community data.

save (trans, *args, **kwargs)

set_accessible_async (trans, *args, **kwargs)
    Set page's importable attribute and slug.

share (trans, *args, **kwargs)
    Handle sharing with an individual user.

sharing (trans, *args, **kwargs)
    Handle page sharing.

class galaxy.webapps.galaxy.controllers.page.PageListGrid
    Bases: galaxy.web.framework.helpers.grid.Grid

    class URLColumn (label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.PublicURLColumn

        get_value (trans, grid, item)

    PageListGrid.apply_query_filter (trans, query, **kwargs)

    PageListGrid.columns = [<galaxy.web.framework.helpers.grid.TextColumn object at 0x7f368f077c50>, <galaxy.web.framework.helpers.grid.PublicURLColumn object at 0x7f368f037810>]

    PageListGrid.default_filter = {'title': 'All', 'sharing': 'All', 'tags': 'All', 'published': 'All'}

    PageListGrid.default_sort_key = '-update_time'

    PageListGrid.global_actions = [<galaxy.web.framework.helpers.grid.GridAction object at 0x7f368f037810>]

```

```
PageListGrid.model_class
    alias of Page

PageListGrid.operations = [<galaxy.web.framework.helpers.grids.DisplayByUsernameAndSlugGridOperation ob

PageListGrid.title = 'Pages'

PageListGrid.use_panels = True

class galaxy.webapps.galaxy.controllers.page.PageSelectionGrid
    Bases: galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid
    Grid for selecting pages.
    columns = [<galaxy.web.framework.helpers.grids.TextColumn object at 0x7f368f037fd0>, <galaxy.web.framework.helpe

    model_class
        alias of Page
    title = 'Saved Pages'

class galaxy.webapps.galaxy.controllers.page.VisualizationSelectionGrid
    Bases: galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid
    Grid for selecting visualizations.
    columns = [<galaxy.web.framework.helpers.grids.TextColumn object at 0x7f368f006090>, <galaxy.web.framework.helpe

    model_class
        alias of Visualization
    title = 'Saved Visualizations'

class galaxy.webapps.galaxy.controllers.page.WorkflowSelectionGrid
    Bases: galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid
    Grid for selecting workflows.
    columns = [<galaxy.webapps.galaxy.controllers.page.NameColumn object at 0x7f368f037e10>, <galaxy.web.framework.l

    model_class
        alias of StoredWorkflow
    title = 'Saved Workflows'

galaxy.webapps.galaxy.controllers.page.format_bool(b)
```

request_type Module

```
class galaxy.webapps.galaxy.controllers.request_type.RequestType(app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.web.base.controller.UsesFormDei

    browse_request_types(trans, *args, **kwargs)
    create_request_type(trans, *args, **kwargs)
    delete_request_type(trans, *args, **kwargs)
    edit_request_type(trans, *args, **kwargs)
    request_type_grid = <galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid object>
    request_type_permissions(trans, *args, **kwargs)
    undelete_request_type(trans, *args, **kwargs)
    view_editable_request_type(trans, *args, **kwargs)
```

```

view_form_definition (trans, *args, **kwargs)

view_request_type (trans, *args, **kwargs)
class galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid
    Bases: galaxy.web.framework.helpers.grids.Grid

    class DescriptionColumn (label, key=None, model_class=None, method=None, format=None,
                               link=None, attach_popup=False, visible=True, nowrap=False, filterable=None,
                               sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value (trans, grid, request_type)

    class RequestTypeGrid.ExternalServiceColumn (label, key=None, model_class=None,
                                                    method=None, format=None, link=None,
                                                    attach_popup=False, visible=True,
                                                    nowrap=False, filterable=None,
                                                    sortable=True, label_id_prefix=None,
                                                    inbound=False)
        Bases: galaxy.web.framework.helpers.grids.IntegerColumn

        get_value (trans, grid, request_type)

    class RequestTypeGrid.NameColumn (label, key=None, model_class=None, method=None,
                                         format=None, link=None, attach_popup=False, visible=True,
                                         nowrap=False, filterable=None, sortable=True,
                                         label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value (trans, grid, request_type)

    class RequestTypeGrid.RequestFormColumn (label, key=None, model_class=None,
                                                method=None, format=None, link=None,
                                                attach_popup=False, visible=True,
                                                nowrap=False, filterable=None, sortable=True,
                                                label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value (trans, grid, request_type)

    class RequestTypeGrid.SampleFormColumn (label, key=None, model_class=None,
                                                method=None, format=None, link=None,
                                                attach_popup=False, visible=True, nowrap=False,
                                                filterable=None, sortable=True, label_id_prefix=None,
                                                inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value (trans, grid, request_type)

RequestTypeGrid.columns = [<galaxy.webapps.galaxy.controllers.request_type.NameColumn object at 0x7f368f149>
RequestTypeGrid.default_filter = {'deleted': 'False'}
RequestTypeGrid.default_sort_key = '-create_time'
RequestTypeGrid.global_actions = [<galaxy.web.framework.helpers.grids.GridAction object at 0x7f36936ea110>
RequestTypeGrid.model_class
    alias of RequestType
RequestTypeGrid.num_rows_per_page = 50
RequestTypeGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369df2aa90>,

```

```
RequestTypeGrid.preserve_state = True
RequestTypeGrid.template = 'admin/request_type/grid.mako'
RequestTypeGrid.title = 'Request Types'
RequestTypeGrid.use_paging = True
```

requests Module

```
class galaxy.webapps.galaxy.controllers.requests.Requests(app)
    Bases: galaxy.web.base.controller.BaseUIController

    browse_requests(trans, **kwd)

    find_samples_index(trans, *args, **kwargs)

    index(trans, *args, **kwargs)

    request_grid = <galaxy.webapps.galaxy.controllers.requests.UserRequestsGrid object>
class galaxy.webapps.galaxy.controllers.requests.UserRequestsGrid
    Bases: galaxy.webapps.galaxy.controllers.requests_common.RequestsGrid

    apply_query_filter(trans, query, **kwd)

    operation = <galaxy.web.framework.helpers.grids.GridOperation object>

    operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dd8fad0>, <galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dd8fad0>]
```

requests_admin Module

```
class galaxy.webapps.galaxy.controllers.requests_admin.AdminRequestsGrid
    Bases: galaxy.webapps.galaxy.controllers.requests_common.RequestsGrid

    class UserColumn(label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value(trans, grid, request)

    AdminRequestsGrid.col = <galaxy.web.framework.helpers.grids.MulticolFilterColumn object>

    AdminRequestsGrid.columns = [<galaxy.webapps.galaxy.controllers.requests_common.NameColumn object at 0x7f369dd8fad0>, <galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid object at 0x7f369dd8fad0>]

    AdminRequestsGrid.global_actions = [<galaxy.web.framework.helpers.grids.GridAction object at 0x7f368dfd0000>]

    AdminRequestsGrid.operation = <galaxy.web.framework.helpers.grids.GridOperation object>

    AdminRequestsGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dd8fad0>, <galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dd8fad0>]
class galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid
    Bases: galaxy.web.framework.helpers.grids.Grid

    class ExternalServiceColumn(label, key=None, model_class=None, method=None, format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grids.TextColumn

        get_value(trans, grid, sample_dataset)
```



```

class DataTransferGrid.NameColumn(label, key=None, model_class=None, method=None,
                                   format=None, link=None, attach_popup=False,
                                   visible=True, nowrap=False, filterable=None,
                                   sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grids.TextColumn
    get_value(trans, grid, sample_dataset)

class DataTransferGrid.SizeColumn(label, key=None, model_class=None, method=None,
                                   format=None, link=None, attach_popup=False,
                                   visible=True, nowrap=False, filterable=None,
                                   sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grids.TextColumn
    get_value(trans, grid, sample_dataset)

class DataTransferGrid.StatusColumn(label, key=None, model_class=None, method=None,
                                   format=None, link=None, attach_popup=False,
                                   visible=True, nowrap=False, filterable=None,
                                   sortable=True, label_id_prefix=None, inbound=False)
    Bases: galaxy.web.framework.helpers.grids.TextColumn
    get_value(trans, grid, sample_dataset)

DataTransferGrid.apply_query_filter(trans, query, **kwd)

DataTransferGrid.columns = [<galaxy.webapps.galaxy.controllers.requests_admin.NameColumn object at 0x7f368...>]

DataTransferGrid.default_sort_key = '-create_time'

DataTransferGrid.model_class
    alias of SampleDataset

DataTransferGrid.num_rows_per_page = 50

DataTransferGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f368fdfd210>]

DataTransferGrid.preserve_state = True

DataTransferGrid.template = 'admin/requests/sample_datasets_grid.mako'

DataTransferGrid.title = 'Sample Datasets'

DataTransferGrid.use_paging = False

class galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin(app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.web.base.controller.UsesFormDe...

    browse_requests(trans, *args, **kwargs)

    datatx_grid = <galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid object>

    get_file_details(trans, *args, **kwargs)

    index(trans, *args, **kwargs)

    initiate_data_transfer(trans, *args, **kwargs)

    manage_datasets(trans, *args, **kwargs)

    open_folder(trans, *args, **kwargs)

    reject_request(trans, *args, **kwargs)

    rename_datasets(trans, *args, **kwargs)

```

```
request_grid = <galaxy.webapps.galaxy.controllers.requests_admin.AdminRequestsGrid object>
select_datasets_to_transfer (trans, *args, **kwargs)
update_sample_dataset_status (trans, cntrlr, sample_dataset_ids, new_status, error_msg=None)
galaxy.webapps.galaxy.controllers.requests_admin.build_rename_datasets_for_sample_select_f
```

requests_common Module

```
class galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon (app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.web.base.controller.UsesFormDe

    add_sample (trans, *args, **kwargs)
    add_samples (trans, *args, **kwargs)
    create_request (trans, *args, **kwargs)
    dataset_transfer_status_updates (trans, *args, **kwargs)
    delete_request (trans, *args, **kwargs)
    delete_sample (trans, *args, **kwargs)
    edit_basic_request_info (trans, *args, **kwargs)
    edit_email_settings (trans, *args, **kwargs)
        Allow for changing the email notification settings where email is sent to a list of users whenever the
        request state changes to one selected for notification.
    edit_samples (trans, *args, **kwargs)
    find_samples (trans, *args, **kwargs)
    sample_datasets_updates (trans, *args, **kwargs)
    sample_state_updates (trans, *args, **kwargs)
    submit_request (trans, *args, **kwargs)
    undelete_request (trans, *args, **kwargs)
    update_request_state (trans, *args, **kwargs)
    update_sample_state (trans, cntrlr, sample_ids, new_state, comment=None)
    view_request (trans, *args, **kwargs)
    view_request_history (trans, *args, **kwargs)
    view_sample (trans, *args, **kwargs)
    view_sample_datasets (trans, *args, **kwargs)
    view_sample_history (trans, *args, **kwargs)
class galaxy.webapps.galaxy.controllers.requests_common.RequestsGrid
    Bases: galaxy.web.framework.helpers.grid.Grid
```

```
class DescriptionColumn(label, key=None, model_class=None, method=None, format=None,
                        link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.TextColumn`

```
get_value(trans, grid, request)
```

```
class RequestsGrid.NameColumn(label, key=None, model_class=None, method=None,
                              format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.TextColumn`

```
get_value(trans, grid, request)
```

```
class RequestsGrid.SamplesColumn(label, key=None, model_class=None, method=None,
                                 format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.GridColumn`

```
get_value(trans, grid, request)
```

```
class RequestsGrid.StateColumn(label, key=None, model_class=None, method=None,
                               format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.StateColumn`

```
filter(trans, user, query, column_filter)
```

Modify query to filter request by state.

```
get_value(trans, grid, request)
```

```
class RequestsGrid.TypeColumn(label, key=None, model_class=None, method=None,
                              format=None, link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.TextColumn`

```
get_value(trans, grid, request)
```

```
RequestsGrid.columns = [<galaxy.webapps.galaxy.controllers.requests_common.NameColumn object at 0x7f369dd8
```

```
RequestsGrid.default_filter = {'deleted': 'False', 'state': 'All'}
```

```
RequestsGrid.default_sort_key = '-update_time'
```

```
RequestsGrid.model_class
```

alias of Request

```
RequestsGrid.num_rows_per_page = 50
```

```
RequestsGrid.operations = [<galaxy.web.framework.helpers.grids.GridOperation object at 0x7f369dd8fad0>]
```

```
RequestsGrid.template = 'requests/grid.mako'
```

```
RequestsGrid.title = 'Sequencing Requests'
```

```
RequestsGrid.use_paging = True
```

```
galaxy.webapps.galaxy.controllers.requests_common.invalid_id_redirect (trans,
                                                                    cntr-
                                                                    ller,
                                                                    obj_id,
                                                                    item='sequencing
                                                                    re-
                                                                    quest',
                                                                    ac-
                                                                    tion='browse_requests')
```

root Module Contains the main interface in the Universe class

class `galaxy.webapps.galaxy.controllers.root.RootController (app)`

Bases: `galaxy.web.base.controller.BaseUIController`, `galaxy.model.item_attrs.UsesAnnotation`

Controller class that maps to the url root of Galaxy (i.e. '/').

bucket_proxy (*trans*, *bucket=None*, ***kwd*)

clear_history (*trans*)

Clears the history for a user.

dataset_make_primary (*trans*, *id=None*)

Copies a dataset and makes primary.

default (*trans*, *target1=None*, *target2=None*, ***kwd*)

Called on any url that does not match a controller method.

display (*trans*, *id=None*, *hid=None*, *tofile=None*, *toext='.txt'*, *encoded_id=None*, ***kwd*)

Returns data directly into the browser.

Sets the mime-type according to the extension.

Used by the twill tool test driver - used anywhere else? Would like to drop hid argument and path if unneeded now. Likewise, would like to drop encoded_id=XXX and use assume id is encoded (likely id wouldn't be coming in encoded if this is used anywhere else though.)

display_as (*trans*, *id=None*, *display_app=None*, ***kwd*)

Returns a file in a format that can successfully be displayed in display_app.

display_child (*trans*, *parent_id=None*, *designation=None*, *tofile=None*, *toext='.txt'*)

Returns child data directly into the browser, based upon parent_id and designation.

echo (*trans*, ***kwd*)

Echos parameters (debugging).

echo_json (*trans*, **args*, ***kwargs*)

Echos parameters as JSON (debugging).

Attempts to parse values passed as boolean, float, then int. Defaults to string. Non-recursive (will not parse lists).

generate_error (*trans*, *code=500*)

Raises an exception (debugging).

generate_json_error (*trans*, **args*, ***kwargs*)

Raises an exception (debugging).

history (*trans*, *as_xml=False*, *show_deleted=None*, *show_hidden=None*, ***kwd*)

Display the current history in its own page or as xml.

history_add_to (*trans*, *history_id=None*, *file_data=None*, *name='Data Added to History'*,
info=None, *ext='txt'*, *dbkey='?'*, *copy_access_from=None*, ***kwd*)
 Adds a POSTed file to a History.

history_as_xml (*trans*, *show_deleted=None*, *show_hidden=None*)

history_delete (*trans*, *id*)
 Backward compatibility with check_galaxy script.

history_import (*trans*, *id=None*, *confirm=False*, ***kwd*)

history_new (*trans*, *name=None*)
 Create a new history with the given name and refresh the history panel.

history_options (*trans*)
 Displays a list of history related actions.

history_set_default_permissions (*trans*, *id=None*, ***kwd*)
 Sets the permissions on a history.

index (*trans*, *id=None*, *tool_id=None*, *mode=None*, *workflow_id=None*, *m_c=None*, *m_a=None*,
***kwd*)
 Called on the root url to display the main Galaxy page.

peek (*trans*, *id=None*)
 Returns a 'peek' at the data.

tool_help (*trans*, *id*)
 Return help page for tool identified by 'id' if available

tool_search (*trans*, **args*, ***kwargs*)
 Searches the tool database and returns data for any tool whose text matches the query.
 Data are returned in JSON format.

welcome (*trans*)

tag Module Tags Controller: handles tagging/untagging of entities and provides autocomplete support.

class `galaxy.webapps.galaxy.controllers.tag.TagsController` (*app*)
 Bases: `galaxy.web.base.controller.BaseUIController`, `galaxy.web.base.controller.UsesTagsMix`

add_tag_async (*trans*, **args*, ***kwargs*)
 Add tag to an item.

get_tagging_elt_async (*trans*, **args*, ***kwargs*)
 Returns HTML for editing an item's tags.

remove_tag_async (*trans*, **args*, ***kwargs*)
 Remove tag from an item.

retag_async (*trans*, **args*, ***kwargs*)
 Apply a new set of tags to an item; previous tags are deleted.

tag_autocomplete_data (*trans*, **args*, ***kwargs*)
 Get autocomplete data for an item's tags.

tool_runner Module Upload class

class `galaxy.webapps.galaxy.controllers.tool_runner.AddFrameData`

```
class galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner(app)
    Bases: galaxy.web.base.controller.BaseUIController

    biomart (trans, tool_id='biomart', **kwd)
        Catches the tool id and redirects as needed

    data_source_redirect (trans, tool_id=None)
        Redirects a user accessing a Data Source tool to its target action link. This method will subvert mix-mode
        content blocking in several browsers when accessing non-https data_source tools from an https galaxy
        server.

        Tested as working on Safari 7.0 and FireFox 26 Subverting did not work on Chrome 31

    default (trans, tool_id=None, **kwd)
        Catches the tool id and redirects as needed

    hapmapmart (trans, tool_id='hapmapmart', **kwd)
        Catches the tool id and redirects as needed

    index (trans, tool_id=None, from_noframe=None, **kwd)

    redirect (trans, redirect_url=None, **kwd)

    rerun (trans, id=None, from_noframe=None, job_id=None, **kwd)
        Given a HistoryDatasetAssociation id, find the job and that created the dataset, extract the parameters,
        and display the appropriate tool form with parameters already filled in.

    upload_async_create (trans, *args, **kwargs)
        Precreate datasets for asynchronous uploading.

    upload_async_message (trans, **kwd)
```

ucsc_proxy Module Contains the UCSC proxy

```
class galaxy.webapps.galaxy.controllers.ucsc_proxy.UCSCProxy(app)
    Bases: galaxy.web.base.controller.BaseUIController

    create_display (store)
        Creates a more meaningful display name

    index (trans, init=False, **kwd)
```

user Module Contains the user interface in the Universe class

```
class galaxy.webapps.galaxy.controllers.user.User(app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.web.base.controller.UsesFormDe
galaxy.web.base.controller.CreatesUsersMixin, galaxy.web.base.controller.CreatesApiKeys

    activate (trans, **kwd)
        Check whether token fits the user and then activate the user's account.

    api_keys (trans, *args, **kwargs)

    change_password (trans, token=None, **kwd)
        Provides a form with which one can change their password. If token is provided, don't require current
        password.

    create (trans, cntrlr='user', redirect_url='', refresh_frames=[], **kwd)

    dbkeys (trans, *args, **kwargs)
        Handle custom builds.
```

delete_address (*trans*, *args, **kwargs)

edit_address (*trans*, *args, **kwargs)

edit_info (*trans*, *cntrller*, **kwd)
Edit user information = username, email or password.

edit_toolbox_filters (*trans*, *args, **kwargs)

edit_username (*trans*, *args, **kwargs)

get_activation_token (*trans*, *email*)
Check for the activation token. Create new activation token and store it in the database if no token found.

get_most_recently_used_tool_async (*trans*, *args, **kwargs)
Returns information about the most recently used tool.

index (*trans*, *cntrller*, **kwd)

installed_len_files = None

is_outside_grace_period (*trans*, *create_time*)
Function checks whether the user is outside the config-defined grace period for inactive accounts.

log_user_action_async (*trans*, *action*, *context*, *params*)
Log a user action asynchronously. If user is not logged in, do nothing.

login (*trans*, *refresh_frames*=[], **kwd)
Handle Galaxy Log in

logout (*trans*, *logout_all*=False)

manage_addresses (*trans*, **kwd)

manage_user_info (*trans*, *cntrller*, **kwd)
Manage a user's login, password, public username, type, addresses, etc.

new_address (*trans*, *args, **kwargs)

openid_associate (*trans*, *cntrller*='user', **kwd)
Associates a user with an OpenID log in

openid_auth (*trans*, **kwd)
Handles user request to access an OpenID provider

openid_disassociate (*trans*, *args, **kwargs)
Disassociates a user with an OpenID

openid_manage (*trans*, *args, **kwargs)
Manage OpenIDs for user

openid_process (*trans*, **kwd)
Handle's response from OpenID Providers

prepare_activation_link (*trans*, *email*)
Prepare the account activation link for the user.

proceed_login (*trans*, *user*, *redirect*)
Function processes user login. It is called in case all the login requirements are valid.

resend_verification (*trans*)
Exposed function for use outside of the class. E.g. when user click on the resend link in the masthead.

resend_verification_email (*trans*, *email*, *username*)
Function resends the verification email in case user wants to log in with an inactive account or he clicks the resend link.

reset_password (*trans*, *email=None*, ***kwd*)

Reset the user's password. Send an email with token that allows a password change.

send_verification_email (*trans*, *email*, *username*)

Send the verification email containing the activation link to the user's email.

set_default_permissions (*trans*, *cntrller*, ***kwd*)

Set the user's default permissions for the new histories

set_user_pref_async (*trans*, *pref_name*, *pref_value*)

Set a user preference asynchronously. If user is not logged in, do nothing.

toolbox_filters (*trans*, **args*, ***kwargs*)

Sets the user's default filters for the toolbox. Toolbox filters are specified in galaxy.ini. The user can activate them and the choice is stored in user_preferences.

undelele_address (*trans*, **args*, ***kwargs*)

user_openid_grid = <galaxy.webapps.galaxy.controllers.user.UserOpenIDGrid object>

class galaxy.webapps.galaxy.controllers.user.**UserOpenIDGrid**

Bases: *galaxy.web.framework.helpers.grid.Grid*

build_initial_query (*trans*, ***kwd*)

columns = [<galaxy.web.framework.helpers.grid.TextColumn object at 0x7f368e904e10>, <galaxy.web.framework.help

default_filter = {'openid': 'All'}

default_sort_key = '-create_time'

model_class

alias of UserOpenID

operations = [<galaxy.web.framework.helpers.grid.GridOperation object at 0x7f368e904c10>]

template = '/user/openid_manage.mako'

title = 'OpenIDs linked to your account'

use_panels = False

visualization Module

workflow Module

reports Package

reports Package The Galaxy Reports application.

app Module

class galaxy.webapps.reports.app.**UniverseApplication** (***kwargs*)

Bases: object

Encapsulates the state of a Universe application

shutdown ()

buildapp Module

config Module Universe configuration builder.

```
class galaxy.webapps.reports.config.Configuration (**kwargs)
    Bases: object
```

```
    check ()
```

```
    get (key, default)
```

```
exception galaxy.webapps.reports.config.ConfigurationError
    Bases: exceptions.Exception
```

```
galaxy.webapps.reports.config.configure_logging (config)
    Allow some basic logging configuration to be read from the cherrpy config.
```

```
galaxy.webapps.reports.config.get_database_engine_options (kwargs)
    Allow options for the SQLAlchemy database engine to be passed by using the prefix "database_engine_option".
```

```
galaxy.webapps.reports.config.resolve_path (path, root)
    If 'path' is relative make absolute by prepending 'root'
```

Subpackages

controllers Package

controllers Package Galaxy reports controllers.

jobs Module

```
class galaxy.webapps.reports.controllers.jobs.Jobs (app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.webapps.reports.controllers.queue.QueueController
```

Class contains functions for querying data requested by user via the webapp. It exposes the functions and responds to requests with the filled .mako templates.

```
errors_per_tool (trans, **kwd)
    Queries the DB for user jobs in error. Filters out monitor jobs.
```

```
job_info (trans, **kwd)
```

```
per_month_all (trans, **kwd)
    Queries the DB for all jobs. Avoids monitor jobs.
```

```
per_month_in_error (trans, **kwd)
    Queries the DB for user jobs in error. Filters out monitor jobs.
```

```
per_tool (trans, **kwd)
```

```
per_user (trans, **kwd)
```

```
specified_date_handler (trans, **kwd)
```

```
specified_date_list_grid = <galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGrid object>
```

```
specified_month_all (trans, **kwd)
    Queries the DB for all jobs in given month, defaults to current month.
```

```
specified_month_in_error (trans, **kwd)
    Queries the DB for the user jobs in error.
```

```
test (trans, **kwd)
```

```
tool_per_month (trans, **kwd)
user_per_month (trans, **kwd)
class galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGrid
    Bases: galaxy.web.framework.helpers.grid.Grid

    class CreateTimeColumn (label, key=None, model_class=None, method=None, format=None,
                            link=None, attach_popup=False, visible=True, nowrap=False, filterable=None,
                            sortable=True, label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.DateTimeColumn

        get_value (trans, grid, job)

    class SpecifiedDateListGrid.EmailColumn (label, key=None, model_class=None,
                                              method=None, format=None, link=None,
                                              attach_popup=False, visible=True,
                                              nowrap=False, filterable=None, sortable=True,
                                              label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.GridColumn

        filter (trans, user, query, column_filter)

    class SpecifiedDateListGrid.JobIdColumn (label, key=None, model_class=None,
                                              method=None, format=None, link=None,
                                              attach_popup=False, visible=True,
                                              nowrap=False, filterable=None, sortable=True,
                                              label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.IntegerColumn

        get_value (trans, grid, job)

    class SpecifiedDateListGrid.SpecifiedDateColumn (label, key=None,
                                                      model_class=None, method=None,
                                                      format=None, link=None,
                                                      attach_popup=False, visible=True,
                                                      nowrap=False, filterable=None,
                                                      sortable=True,
                                                      label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.GridColumn

        filter (trans, user, query, column_filter)

    class SpecifiedDateListGrid.StateColumn (label, key=None, model_class=None,
                                              method=None, format=None, link=None,
                                              attach_popup=False, visible=True,
                                              nowrap=False, filterable=None, sortable=True,
                                              label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.TextColumn

        filter (trans, user, query, column_filter)

        get_value (trans, grid, job)

    class SpecifiedDateListGrid.ToolColumn (label, key=None, model_class=None,
                                             method=None, format=None, link=None,
                                             attach_popup=False, visible=True, nowrap=False,
                                             filterable=None, sortable=True,
                                             label_id_prefix=None, inbound=False)
        Bases: galaxy.web.framework.helpers.grid.TextColumn

        filter (trans, user, query, column_filter)
```

```

    get_value (trans, grid, job)

class SpecifiedDateListGrid.UserColumn (label, key=None, model_class=None,
                                         method=None, format=None, link=None, at-
                                         tach_popup=False, visible=True, nowrap=False,
                                         filterable=None, sortable=True, la-
                                         bel_id_prefix=None, inbound=False)

    Bases: galaxy.web.framework.helpers.grids.GridColumn

    get_value (trans, grid, job)

    SpecifiedDateListGrid.build_initial_query (trans, **kwd)

    SpecifiedDateListGrid.columns = [<galaxy.webapps.reports.controllers.jobs.JobIdColumn object at 0x7f368d96...

    SpecifiedDateListGrid.default_filter = {'specified_date': 'All'}

    SpecifiedDateListGrid.default_sort_key = 'id'

    SpecifiedDateListGrid.model_class
        alias of Job

    SpecifiedDateListGrid.num_rows_per_page = 50

    SpecifiedDateListGrid.preserve_state = False

    SpecifiedDateListGrid.standard_filters = []

    SpecifiedDateListGrid.template = '/webapps/reports/grid.mako'

    SpecifiedDateListGrid.title = 'Jobs'

    SpecifiedDateListGrid.use_async = False

    SpecifiedDateListGrid.use_paging = True

    galaxy.webapps.reports.controllers.jobs.get_job (trans, id)

    galaxy.webapps.reports.controllers.jobs.get_monitor_id (trans, monitor_email)
        A convenience method to obtain the monitor job id.

    galaxy.webapps.reports.controllers.jobs.sorter (default_sort_id, kwd)
        Initialize sorting variables

root Module

class galaxy.webapps.reports.controllers.root.Report (app)
    Bases: galaxy.web.base.controller.BaseUIController

    index (trans, **kwd)

sample_tracking Module

class galaxy.webapps.reports.controllers.sample_tracking.SampleTracking (app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.webapps.reports.controllers.que...

    per_month_all (trans, **kwd)

    per_user (trans, **kwd)

    specified_date_handler (trans, **kwd)

    specified_date_list_grid = <galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDateListGrid object>

    user_per_month (trans, **kwd)

```

```
class galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDateListGrid
    Bases: galaxy.web.framework.helpers.grids.Grid
```

```
class CreateTimeColumn(label, key=None, model_class=None, method=None, format=None,
                        link=None, attach_popup=False, visible=True, nowrap=False, filter-
                        able=None, sortable=True, label_id_prefix=None, inbound=False)
```

```
    Bases: galaxy.web.framework.helpers.grids.DateTimeColumn
```

```
    get_value(trans, grid, request)
```

```
class SpecifiedDateListGrid.EmailColumn(label, key=None, model_class=None,
                                         method=None, format=None, link=None,
                                         attach_popup=False, visible=True,
                                         nowrap=False, filterable=None, sortable=True,
                                         label_id_prefix=None, inbound=False)
```

```
    Bases: galaxy.web.framework.helpers.grids.GridColumn
```

```
    filter(trans, user, query, column_filter)
```

```
class SpecifiedDateListGrid.RequestNameColumn(label, key=None, model_class=None,
                                                method=None, format=None,
                                                link=None, attach_popup=False,
                                                visible=True, nowrap=False, fil-
                                                terable=None, sortable=True, la-
                                                bel_id_prefix=None, inbound=False)
```

```
    Bases: galaxy.web.framework.helpers.grids.TextColumn
```

```
    get_value(trans, grid, request)
```

```
class SpecifiedDateListGrid.SpecifiedDateColumn(label, key=None,
                                                  model_class=None, method=None,
                                                  format=None, link=None,
                                                  attach_popup=False, visi-
                                                  ble=True, nowrap=False, fil-
                                                  terable=None, sortable=True,
                                                  label_id_prefix=None, in-
                                                  bound=False)
```

```
    Bases: galaxy.web.framework.helpers.grids.GridColumn
```

```
    filter(trans, user, query, column_filter)
```

```
class SpecifiedDateListGrid.UserColumn(label, key=None, model_class=None,
                                         method=None, format=None, link=None, at-
                                         tach_popup=False, visible=True, nowrap=False,
                                         filterable=None, sortable=True, la-
                                         bel_id_prefix=None, inbound=False)
```

```
    Bases: galaxy.web.framework.helpers.grids.TextColumn
```

```
    get_value(trans, grid, request)
```

```
SpecifiedDateListGrid.build_initial_query(trans, **kwd)
```

```
SpecifiedDateListGrid.columns = [<galaxy.webapps.reports.controllers.sample_tracking.RequestNameColumn o
```

```
SpecifiedDateListGrid.default_filter = {'specified_date': 'All'}
```

```
SpecifiedDateListGrid.default_sort_key = 'name'
```

```
SpecifiedDateListGrid.model_class
    alias of Request
```

```
SpecifiedDateListGrid.num_rows_per_page = 50
```

```

SpecifiedDateListGrid.preserve_state = False
SpecifiedDateListGrid.standard_filters = []
SpecifiedDateListGrid.template = '/webapps/reports/grid.mako'
SpecifiedDateListGrid.title = 'Sequencing Requests'
SpecifiedDateListGrid.use_async = False
SpecifiedDateListGrid.use_paging = True
galaxy.webapps.reports.controllers.sample_tracking.get_request (trans, id)

```

system Module

```

class galaxy.webapps.reports.controllers.system.System (app)
    Bases: galaxy.web.base.controller.BaseUIController

    dataset_info (trans, **kwd)

    deleted_datasets (trans, **kwd)
        The number of datasets that were deleted more than the specified number of days ago, but have not yet
        been purged.

    deleted_histories (trans, **kwd)
        The number of histories that were deleted more than the specified number of days ago, but have not yet
        been purged. Also included is the number of datasets associated with the histories.

    disk_usage (trans, **kwd)

    get_disk_usage (file_path)

    index (trans, **kwd)

    userless_histories (trans, **kwd)
        The number of userless histories and associated datasets that have not been updated for the specified
        number of days.
galaxy.webapps.reports.controllers.system.nice_size (size, include_bytes=False)
    Returns a readably formatted string with the size

```

users Module

```

class galaxy.webapps.reports.controllers.users.Users (app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.webapps.reports.controllers.queue.QueueController

    last_access_date (trans, **kwd)

    registered_users (trans, **kwd)

    registered_users_per_month (trans, **kwd)

    specified_date (trans, **kwd)

    specified_month (trans, **kwd)

    user_disk_usage (trans, **kwd)

```

workflows Module

```

class galaxy.webapps.reports.controllers.workflows.SpecifiedDateListGrid
    Bases: galaxy.web.framework.helpers.grid.Grid

```

```
class CreateTimeColumn(label, key=None, model_class=None, method=None, format=None,
                       link=None, attach_popup=False, visible=True, nowrap=False, filterable=None, sortable=True, label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.DateTimeColumn`

```
get_value(trans, grid, stored_workflow)
```

```
class SpecifiedDateListGrid.EmailColumn(label, key=None, model_class=None,
                                         method=None, format=None, link=None,
                                         attach_popup=False, visible=True,
                                         nowrap=False, filterable=None, sortable=True,
                                         label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.GridColumn`

```
filter(trans, user, query, column_filter)
```

```
class SpecifiedDateListGrid.SpecifiedDateColumn(label, key=None,
                                                  model_class=None, method=None,
                                                  format=None, link=None,
                                                  attach_popup=False, visible=True,
                                                  nowrap=False, filterable=None,
                                                  sortable=True, label_id_prefix=None,
                                                  inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.GridColumn`

```
filter(trans, user, query, column_filter)
```

```
class SpecifiedDateListGrid.UserColumn(label, key=None, model_class=None,
                                        method=None, format=None, link=None,
                                        attach_popup=False, visible=True, nowrap=False,
                                        filterable=None, sortable=True, label_id_prefix=None,
                                        inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.TextColumn`

```
get_value(trans, grid, stored_workflow)
```

```
class SpecifiedDateListGrid.WorkflowNameColumn(label, key=None, model_class=None,
                                                 method=None, format=None,
                                                 link=None, attach_popup=False,
                                                 visible=True, nowrap=False,
                                                 filterable=None, sortable=True,
                                                 label_id_prefix=None, inbound=False)
```

Bases: `galaxy.web.framework.helpers.grids.TextColumn`

```
get_value(trans, grid, stored_workflow)
```

```
SpecifiedDateListGrid.build_initial_query(trans, **kwd)
```

```
SpecifiedDateListGrid.columns = [<galaxy.webapps.reports.controllers.workflows.WorkflowNameColumn object>]
```

```
SpecifiedDateListGrid.default_filter = {'specified_date': 'All'}
```

```
SpecifiedDateListGrid.default_sort_key = 'name'
```

```
SpecifiedDateListGrid.model_class
alias of StoredWorkflow
```

```
SpecifiedDateListGrid.num_rows_per_page = 50
```

```
SpecifiedDateListGrid.preserve_state = False
```

```
SpecifiedDateListGrid.standard_filters = []
```

```

    SpecifiedDateListGrid.template = '/webapps/reports/grid.mako'
    SpecifiedDateListGrid.title = 'Workflows'
    SpecifiedDateListGrid.use_async = False
    SpecifiedDateListGrid.use_paging = True
class galaxy.webapps.reports.controllers.workflows.Workflows (app)
    Bases: galaxy.web.base.controller.BaseUIController, galaxy.webapps.reports.controllers.que

    per_month_all (trans, **kwd)
    per_user (trans, **kwd)
    specified_date_handler (trans, **kwd)
    specified_date_list_grid = <galaxy.webapps.reports.controllers.workflows.SpecifiedDateListGrid object>
    user_per_month (trans, **kwd)

galaxy.webapps.reports.controllers.workflows.get_workflow (trans, id)

```

workflow Package

```

modules Module    Modules used in building workflows

exception galaxy.workflow.modules.CancelWorkflowEvaluation
    Bases: exceptions.Exception

exception galaxy.workflow.modules.DelayedWorkflowEvaluation
    Bases: exceptions.Exception

class galaxy.workflow.modules.InputDataCollectionModule (trans)
    Bases: galaxy.workflow.modules.InputModule

    collection_type = 'list'
    default_collection_type = 'list'
    default_name = 'Input Dataset Collection'
    classmethod default_state (Class)
    get_data_outputs ()
    get_runtime_inputs (filter_set=['data'])
    name = 'Input dataset collection'
    state_fields = ['name', 'collection_type']
    type = 'data_collection_input'

class galaxy.workflow.modules.InputDataModule (trans)
    Bases: galaxy.workflow.modules.InputModule

    default_name = 'Input Dataset'
    classmethod default_state (Class)
    get_data_outputs ()
    get_runtime_inputs (filter_set=['data'])
    name = 'Input dataset'

```

```
state_fields = ['name']
type = 'data_input'
class galaxy.workflow.modules.InputModule(trans)
    Bases: galaxy.workflow.modules.SimpleWorkflowModule
    execute(trans, progress, invocation, step)
    get_data_inputs()
    get_runtime_input_dicts(step_annotation)
    get_runtime_state()
    recover_mapping(step, step_invocations, progress)
exception galaxy.workflow.modules.MissingToolException
    Bases: exceptions.Exception
    WorkflowModuleInjector will raise this if the tool corresponding to the module is missing.
class galaxy.workflow.modules.PauseModule(trans)
    Bases: galaxy.workflow.modules.SimpleWorkflowModule
    Initially this module will unconditionally pause a workflow - will aim to allow conditional pausing later on.
    default_name = 'Pause for Dataset Review'
    classmethod default_state(Class)
    do_invocation_step_action(step, action)
        Update or set the workflow invocation state action - generic extension point meant to allows users to
        interact with interactive workflow modules. The action object returned from this method will be attached
        to the WorkflowInvocationStep and be available the next time the workflow scheduler visits the workflow.
    execute(trans, progress, invocation, step)
    get_data_inputs()
    get_data_outputs()
    get_runtime_input_dicts(step_annotation)
    get_runtime_inputs(**kws)
    get_runtime_state()
    name = 'Pause for dataset review'
    recover_mapping(step, step_invocations, progress)
    state_fields = ['name']
    type = 'pause'
class galaxy.workflow.modules.SimpleWorkflowModule(trans)
    Bases: galaxy.workflow.modules.WorkflowModule
    compute_runtime_state(trans, step_updates=None, source='html')
    decode_runtime_state(trans, string)
    classmethod default_state(Class)
        This method should return a dictionary describing each configuration property and its default value.
    encode_runtime_state(trans, state)
    classmethod from_dict(Class, trans, d, secure=True)
```



```

classmethod from_workflow_step (Class, trans, step)

get_config_form ()

get_state (secure=True)

classmethod new (Class, trans, tool_id=None)

normalize_runtime_state (runtime_state)

recover_runtime_state (runtime_state)
    Take secure runtime state from persisted invocation and convert it into a DefaultToolState object for use
    during workflow invocation.

recover_state (state, **kwds)
    Recover state dict from simple dictionary describing configuration state (potentially from persisted step
    state).

    Sub-classes should supply default_state method and state_fields attribute which are used to build up the
    state dict.

save_to_step (step)

update_runtime_state (trans, state, values)

update_state (incoming)

class galaxy.workflow.modules.ToolModule (trans, tool_id, tool_version=None)
    Bases: galaxy.workflow.modules.WorkflowModule

    add_dummy_datasets (connections=None)

    check_and_update_state ()

    compute_runtime_state (trans, step_updates=None, source='html')

    encode_runtime_state (trans, state)

    execute (trans, progress, invocation, step)

    classmethod from_dict (Class, trans, d, secure=True)

    classmethod from_workflow_step (Class, trans, step)

    get_config_form ()

    get_data_inputs ()

    get_data_outputs ()

    get_errors ()

    get_name ()

    get_post_job_actions (incoming=None)

    get_runtime_input_dicts (step_annotation)

    get_state (secure=True)

    get_tool_id ()

    get_tool_version ()

    get_tooltip (static_path='')

    classmethod new (Class, trans, tool_id=None)

    normalize_runtime_state (runtime_state)

```

```

recover_mapping (step, step_invocations, progress)

recover_runtime_state (runtime_state)
    Take secure runtime state from persisted invocation and convert it into a DefaultToolState object for use
    during workflow invocation.

recover_state (state, **kwds)
    Recover module configuration state property (a DefaultToolState object) using the tool's
    params_from_strings method.

save_to_step (step)

type = 'tool'

update_state (incoming)

class galaxy.workflow.modules.WorkflowModule (trans)
    Bases: object

    add_dummy_datasets (connections=None)

    check_and_update_state ()
        If the state is not in sync with the current implementation of the module, try to update. Returns a list of
        messages to be displayed

    compute_runtime_state (trans, step_updates=None, source='html')
        Determine the runtime state (potentially different from self.state which describes configuration state).
        This (again unlike self.state) is currently always a DefaultToolState object.

        If step_updates is None, this is likely for rendering the run form for instance and no runtime properties
        are available and state must be solely determined by the default runtime state described by the step.

        If step_updates are available they describe the runtime properties supplied by the workflow runner (po-
        tentially including a tool_state parameter which is the serialized default encoding state created with en-
        code_runtime_state above).

    do_invocation_step_action (step, action)
        Update or set the workflow invocation state action - generic extension point meant to allows users to
        interact with interactive workflow modules. The action object returned from this method will be attached
        to the WorkflowInvocationStep and be available the next time the workflow scheduler visits the workflow.

    encode_runtime_state (trans, state)
        Encode the default runtime state at return as a simple str for use in a hidden parameter on the workflow
        run submission form.

        This default runtime state will be combined with user supplied parameters in compute_runtime_state
        below at workflow invocation time to actually describe how each step will be executed.

    execute (trans, progress, invocation, step)
        Execute the given workflow step in the given workflow invocation. Use the supplied workflow progress
        object to track outputs, find inputs, etc...

    classmethod from_dict (Class, trans, d)
        Create a new instance of the module initialized from values in the dictionary d.

    classmethod from_workflow_step (Class, trans, step)

    get_config_form ()
        Render form that is embedded in workflow editor for modifying the step state of a node.

    get_data_inputs ()
        Get configure time data input descriptions.

    get_data_outputs ()

```

```

get_errors ()
    It seems like this is effectively just used as boolean - some places in the tool shed self.errors is set to
    boolean, other places 'unavailable', likewise in Galaxy it stores a list containing a string with an unrecog-
    nized tool id error message.

get_name ()

get_runtime_input_dicts (step_annotation)
    Get runtime inputs (inputs and parameters) as simple dictionary.

get_runtime_inputs ()
    Used internally by modules and when displaying inputs in workflow editor and run workflow templates.

    Note: The ToolModule doesn't implement this and these templates contain specialized logic for dealing
    with the tool and state directly in the case of ToolModules.

get_state ()
    Return a serializable representation of the persistable state of the step - for tools it DefaultToolState.encode
    returns a string and for simpler module types a json description is dumped out.

get_tool_id ()

get_tooltip (static_path='')

get_type ()

classmethod new (Class, trans, tool_id=None)
    Create a new instance of the module with default state

recover_mapping (step, step_invocations, progress)
    Re-populate progress object with information about connections from previously executed steps recorded
    via step_invocations.

save_to_step (step)

update_state (incoming)
    Update the current state of the module against the user supplied parameters in the dict-like object incom-
ing.

class galaxy.workflow.modules.WorkflowModuleFactory (module_types)
    Bases: object

    from_dict (trans, d, **kwargs)
        Return module initialized from the data in dictionary d.

    from_workflow_step (trans, step)
        Return module initializd from the WorkflowStep object step.

    new (trans, type, tool_id=None)
        Return module for type and (optional) tool_id intialized with new / default state.

class galaxy.workflow.modules.WorkflowModuleInjector (trans)
    Bases: object

    Injects workflow step objects from the ORM with appropriate module and module generated/influenced state.

    inject (step, step_args=None, source='html')
        Pre-condition: step is an ORM object coming from the database, if supplied step_args is the representation
        of the inputs for that step supplied via web form.

        Post-condition: The supplied step has new non-persistent attributes useful during workflow invocation.
        These include 'upgrade_messages', 'state', 'input_connections_by_name', and 'module'.

```

If `step_args` is provided from a web form this is applied to generate ‘state’ else it is just obtained from the database.

`galaxy.workflow.modules.is_tool_module_type (module_type)`

`galaxy.workflow.modules.load_module_sections (trans)`

Get abstract description of the workflow modules this Galaxy instance is configured with.

`galaxy.workflow.modules.populate_module_and_state (trans, workflow, param_map)`

Used by API but not web controller, walks through a workflow’s steps and populates transient module and state attributes on each.

1.2.3 galaxy_utils Package

Subpackages

sequence Package

fasta Module

class `galaxy_utils.sequence.fasta.fastaNamedReader (fh)`

Bases: object

close ()

get (sequence_id)

has_data ()

class `galaxy_utils.sequence.fasta.fastaReader (fh)`

Bases: object

close ()

next ()

class `galaxy_utils.sequence.fasta.fastaSequence`

Bases: object

class `galaxy_utils.sequence.fasta.fastaWriter (fh)`

Bases: object

close ()

write (fastq_read)

fastq Module

class `galaxy_utils.sequence.fastq.ReadlineCountFile (f)`

Bases: object

readline (*args, **kws)

class `galaxy_utils.sequence.fastq.fastqAggregator`

Bases: object

VALID_FORMATS = ['solexa', 'sanger', 'cssanger', 'illumina']

consume_read (fastq_read)

get_ascii_range ()

get_base_counts_for_column (column)

get_decimal_range ()

```

    get_length_counts()
    get_max_read_length()
    get_read_count()
    get_read_count_for_column(column)
    get_score_at_position_for_column(column, position)
    get_score_list_for_column(column)
    get_score_max_for_column(column)
    get_score_min_for_column(column)
    get_score_sum_for_column(column)
    get_summary_statistics_for_column(i)
    get_valid_formats(check_list=None)
class galaxy_utils.sequence.fastq.fastqCSSangerRead
    Bases: galaxy_utils.sequence.fastq.fastqSequencingRead
    apply_galaxy_conventions()
    ascii_max = 126
    ascii_min = 33
    assert_sequence_quality_lengths()
    change_adapter(new_adapter, clone=True)
    complement(clone=True)
    format = 'cssanger'
    get_sequence()
    has_adapter_base()
    insufficient_quality_length()
    quality_max = 93
    quality_min = 0
    reverse(clone=True)
    score_system = 'phred'
    sequence_space = 'color'
    valid_sequence_list = ['0', '1', '2', '3', '4', '5', '6', '.']
class galaxy_utils.sequence.fastq.fastqCombiner(format)
    Bases: object
    combine(fasta_seq, quality_seq)
class galaxy_utils.sequence.fastq.fastqFakeFastaScoreReader(format='sanger', quality_encoding=None)
    Bases: object
    close()
    get(sequence)
    has_data()

```

```
class galaxy_utils.sequence.fastq.fastqIlluminaRead
    Bases: galaxy_utils.sequence.fastq.fastqSequencingRead

    ascii_max = 126
    ascii_min = 64
    format = 'illumina'
    quality_max = 62
    quality_min = 0
    score_system = 'phred'
    sequence_space = 'base'

class galaxy_utils.sequence.fastq.fastqJoiner (format, force_quality_encoding=None)
    Bases: object

    get_paired_identifier (fastq_read)
    is_first_mate (sequence_id)
    join (read1, read2)

class galaxy_utils.sequence.fastq.fastqNamedReader (fh, format='sanger', apply_galaxy_conventions=False)
    Bases: object

    close ()
    get (sequence_identifier)
    has_data ()

class galaxy_utils.sequence.fastq.fastqReader (fh, format='sanger', apply_galaxy_conventions=False)
    Bases: object

    close ()
    next ()

class galaxy_utils.sequence.fastq.fastqSangerRead
    Bases: galaxy_utils.sequence.fastq.fastqSequencingRead

    ascii_max = 126
    ascii_min = 33
    format = 'sanger'
    quality_max = 93
    quality_min = 0
    score_system = 'phred'
    sequence_space = 'base'

class galaxy_utils.sequence.fastq.fastqSequencingRead
    Bases: galaxy_utils.sequence.sequence.SequencingRead

    apply_galaxy_conventions ()
    ascii_max = 126
    ascii_min = 33
```

```

    assert_sequence_quality_lengths()
    classmethod convert_base_to_color_space(sequence)
    classmethod convert_color_to_base_space(sequence)
    convert_read_to_format(format, force_quality_encoding=None)
    classmethod convert_score_phred_to_solexa(decimal_score_list)
    classmethod convert_score_solexa_to_phred(decimal_score_list)
    format = 'sanger'
    get_ascii_quality_scores()
    get_ascii_quality_scores_len()
        Compute ascii quality score length, without generating relatively expensive quality score array.
    classmethod get_class_by_format(format)
    get_decimal_quality_scores()
    get_sequence()
    insufficient_quality_length()
    is_ascii_encoded()
    is_valid_format()
    is_valid_sequence()
    quality_max = 93
    quality_min = 0
    classmethod restrict_scores_to_valid_range(decimal_score_list)
    reverse(clone=True)
    score_system = 'phred'
    sequence_space = 'base'
    slice(left_column_offset, right_column_offset)
    classmethod transform_scores_to_valid_range(decimal_score_list)
    classmethod transform_scores_to_valid_range_ascii(decimal_score_list)
class galaxy_utils.sequence.fastq.fastqSolexaRead
    Bases: galaxy_utils.sequence.fastq.fastqSequencingRead
    ascii_max = 126
    ascii_min = 59
    format = 'solexa'
    quality_max = 62
    quality_min = -5
    score_system = 'solexa'
    sequence_space = 'base'
class galaxy_utils.sequence.fastq.fastqSplitter
    Bases: object

```

```
    split (fastq_read)

class galaxy_utils.sequence.fastq.fastqVerboseErrorReader (fh, **kws)
    Bases: galaxy_utils.sequence.fastq.fastqReader

    MAX_PRINT_ERROR_BYTES = 1024

    next ()

class galaxy_utils.sequence.fastq.fastqWriter (fh, format=None, force_quality_encoding=None)
    Bases: object

    close ()

    write (fastq_read)

galaxy_utils.sequence.fastq.format
    alias of fastqCSSangerRead
```

sequence Module

```
class galaxy_utils.sequence.sequence.SequencingRead
    Bases: object

    append_quality (quality)

    append_sequence (sequence)

    clone ()

    color_space_converter = <galaxy_utils.sequence.transform.ColorSpaceConverter object>

    complement (clone=True)

    is_DNA ()

    reverse (clone=True)

    reverse_complement (clone=True)

    sequence_as_DNA (clone=True)

    sequence_as_RNA (clone=True)

    valid_sequence_list = 'ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz'
```

transform Module

```
class galaxy_utils.sequence.transform.ColorSpaceConverter (fake_adapter_base='G')
    Bases: object

    base = 'N'

    base_to_color_dict = {'A': {'A': '0', 'C': '1', 'T': '3', 'G': '2', 'N': '4'}, 'C': {'A': '1', 'C': '0', 'T': '2', 'G': '3', 'N': '4'}, 'T': {'A': '3', 'C': '2', 'T': '0', 'G': '1', 'N': '5'}, 'G': {'A': '2', 'C': '3', 'T': '1', 'G': '0', 'N': '6'}, 'N': {'A': '4', 'C': '4', 'T': '5', 'G': '6', 'N': '7'}}

    color_dict = {'1': 'N', '0': 'N', '3': 'N', '2': 'N', '5': 'N', '4': 'N', '6': 'N', '7': 'N'}

    color_to_base_dict = {'A': {'1': 'C', '0': 'A', '3': 'T', '2': 'G', '5': 'N', '4': 'N', '6': 'N', '7': 'N'}, 'C': {'1': 'A', '0': 'C', '3': 'G', '2': 'T', '5': 'N', '4': 'N', '6': 'N', '7': 'N'}, 'T': {'1': 'C', '0': 'A', '3': 'T', '2': 'G', '5': 'N', '4': 'N', '6': 'N', '7': 'N'}, 'G': {'1': 'A', '0': 'C', '3': 'G', '2': 'T', '5': 'N', '4': 'N', '6': 'N', '7': 'N'}, 'N': {'1': 'A', '0': 'C', '3': 'G', '2': 'T', '5': 'N', '4': 'N', '6': 'N', '7': 'N'}}

    key = '.'

    to_base_space (sequence)

    to_color_space (sequence, adapter_base=None)

    unknown_base = 'N'
```



```

    unknown_color = '.'
    value = 'N'
galaxy_utils.sequence.transform.DNA_complement(sequence)
galaxy_utils.sequence.transform.DNA_reverse_complement(sequence)
galaxy_utils.sequence.transform.RNA_complement(sequence)
galaxy_utils.sequence.transform.RNA_reverse_complement(sequence)
galaxy_utils.sequence.transform.reverse(sequence)
galaxy_utils.sequence.transform.to_DNA(sequence)
galaxy_utils.sequence.transform.to_RNA(sequence)

```

vcf Module

```

class galaxy_utils.sequence.vcf.Reader(fh)
    Bases: object

    next()
class galaxy_utils.sequence.vcf.VariantCall(vcf_line, metadata, sample_names)
    Bases: object

    classmethod get_class_by_format(format)

    header_startswith = None

    required_header_fields = None

    required_header_length = None

    version = None
class galaxy_utils.sequence.vcf.VariantCall133(vcf_line, metadata, sample_names)
    Bases: galaxy_utils.sequence.vcf.VariantCall

    header_startswith = '#CHROM\tPOS\tID\tREF\tALT\tQUAL\tFILTER\tINFO'

    required_header_fields = ['#CHROM', 'POS', 'ID', 'REF', 'ALT', 'QUAL', 'FILTER', 'INFO']

    required_header_length = 8

    version = 'VCFv3.3'
class galaxy_utils.sequence.vcf.VariantCall140(vcf_line, metadata, sample_names)
    Bases: galaxy_utils.sequence.vcf.VariantCall133

    version = 'VCFv4.0'
class galaxy_utils.sequence.vcf.VariantCall141(vcf_line, metadata, sample_names)
    Bases: galaxy_utils.sequence.vcf.VariantCall140

    version = 'VCFv4.1'
galaxy_utils.sequence.vcf.format
    alias of VariantCall141

```

1.2.4 log_tempfile Module

```

class log_tempfile.TempFile
    Bases: object

```

NamedTemporaryFile (*args, **kwargs)

mkstemp (*args, **kwargs)

1.2.5 mimeparse Module

MIME-Type Parser

This module provides basic functions for handling mime-types. It can handle matching mime-types against a list of media-ranges. See section 14.1 of the HTTP specification [RFC 2616] for a complete explanation.

<http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.1>

Contents:

- `parse_mime_type()`: Parses a mime-type into its component parts.
- `parse_media_range()`: Media-ranges are mime-types with wild-cards and a 'q' quality parameter.
- `quality()`: Determines the quality ('q') of a mime-type when compared against a list of media-ranges.
- `quality_parsed()`: Just like `quality()` except the second parameter must be pre-parsed.
- `best_match()`: Choose the mime-type with the highest quality ('q') from a list of candidates.

`mimeparse.best_match` (*supported*, *header*)

Takes a list of supported mime-types and finds the best match for all the media-ranges listed in header. The value of header must be a string that conforms to the format of the HTTP Accept: header. The value of 'supported' is a list of mime-types.

```
>>> best_match(['application/xbel+xml', 'text/xml'], 'text/*;q=0.5, */*; q=0.1')
'text/xml'
```

`mimeparse.fitness_and_quality_parsed` (*mime_type*, *parsed_ranges*)

Find the best match for a given mime-type against a list of media_ranges that have already been parsed by `parse_media_range()`. Returns a tuple of the fitness value and the value of the 'q' quality parameter of the best match, or (-1, 0) if no match was found. Just as for `quality_parsed()`, 'parsed_ranges' must be a list of parsed media ranges.

`mimeparse.parse_media_range` (*range*)

Carves up a media range and returns a tuple of the (type, subtype, params) where 'params' is a dictionary of all the parameters for the media range. For example, the media range 'application/*;q=0.5' would get parsed into:

In addition this function also guarantees that there is a value for 'q' in the params dictionary, filling it in with a proper default if necessary.

`mimeparse.parse_mime_type` (*mime_type*)

Carves up a mime-type and returns a tuple of the (type, subtype, params) where 'params' is a dictionary of all the parameters for the media range. For example, the media range 'application/xhtml;q=0.5' would get parsed into:

('application', 'xhtml', {'q', '0.5'})

`mimeparse.quality` (*mime_type*, *ranges*)

Returns the quality 'q' of a mime-type when compared against the media-ranges in ranges. For example:

```
>>> quality('text/html', 'text/*;q=0.3, text/html;q=0.7, text/html;level=1, text/html;level=2;q=0.4')
0.7
```

`mimeparse.quality_parsed(mime_type, parsed_ranges)`

Find the best match for a given mime-type against a list of `media_ranges` that have already been parsed by `parse_media_range()`. Returns the 'q' quality parameter of the best match, 0 if no match was found. This function behaves the same as `quality()` except that 'parsed_ranges' must be a list of parsed media ranges.

1.2.6 pkg_resources Module

Package resource API

A resource is a logical file contained within a package, or a logical subdirectory thereof. The package resource API expects resource names to have their path parts separated with `/`, *not* whatever the local path separator is. Do not use `os.path` operations to manipulate resource names being passed into the API.

The package resource API is designed to work with normal filesystem packages, .egg files, and unpacked .egg files. It can also work in a limited way with .zip files and with custom PEP 302 loaders that support the `get_data()` method.

`pkg_resources.require(req_str)`

`pkg_resources.get_provider(moduleOrReq)`

Return an `IResourceProvider` for the named module or requirement

`pkg_resources.get_distribution(dist)`

Return a current distribution object for a Requirement or string

`pkg_resources.load_entry_point(dist, group, name)`

Return `name` entry point of `group` for `dist` or raise `ImportError`

`pkg_resources.get_entry_map(dist, group=None)`

Return the entry point map for `group`, or the full entry map

`pkg_resources.get_entry_info(dist, group, name)`

Return the `EntryPoint` object for `group`+'`name`', or `None`

`pkg_resources.declare_namespace(packageName)`

Declare that package 'packageName' is a namespace package

`pkg_resources.find_distributions(path_item, only=False)`

Yield distributions accessible via `path_item`

`pkg_resources.get_default_cache()`

Determine the default cache location

This returns the `PYTHON_EGG_CACHE` environment variable, if set. Otherwise, on Windows, it returns a "Python-Eggs" subdirectory of the "Application Data" directory. On all other systems, it's "`~/python-eggs`".

`class pkg_resources.Environment(search_path=None, platform='linux-x86_64', python='2.7')`

Bases: `object`

Searchable snapshot of distributions on a search path

`add(dist)`

Add `dist` if we `can_add()` it and it isn't already added

`best_match(req, working_set, installer=None)`

Find distribution best matching `req` and usable on `working_set`

This calls the `find(req)` method of the `working_set` to see if a suitable distribution is already active. (This may raise `VersionConflict` if an unsuitable version of the project is already active in the specified `working_set`.) If a suitable distribution isn't active, this method returns the newest distribution in the environment that meets the Requirement in `req`. If no suitable distribution is found, and `installer`

is supplied, then the result of calling the environment's `obtain(req, installer)` method will be returned.

can_add (*dist*)

Is distribution *dist* acceptable for this environment?

The distribution must match the platform and python version requirements specified when this environment was created, or False is returned.

obtain (*requirement, installer=None*)

Obtain a distribution matching *requirement* (e.g. via download)

Obtain a distro that matches requirement (e.g. via download). In the base `Environment` class, this routine just returns `installer(requirement)`, unless *installer* is None, in which case None is returned instead. This method is a hook that allows subclasses to attempt other ways of obtaining a distribution before falling back to the *installer* argument.

remove (*dist*)

Remove *dist* from the environment

scan (*search_path=None*)

Scan *search_path* for distributions usable in this environment

Any distributions found are added to the environment. *search_path* should be a sequence of `sys.path` items. If not supplied, `sys.path` is used. Only distributions conforming to the platform/python version defined at initialization are added.

class `pkg_resources.WorkingSet` (*entries=None*)

Bases: `object`

A collection of active distributions on `sys.path` (or a similar list)

add (*dist, entry=None, insert=True*)

Add *dist* to working set, associated with *entry*

If *entry* is unspecified, it defaults to the `.location` of *dist*. On exit from this routine, *entry* is added to the end of the working set's `.entries` (if it wasn't already present).

dist is only added to the working set if it's for a project that doesn't already have a distribution in the set. If it's added, any callbacks registered with the `subscribe()` method will be called.

add_entry (*entry*)

Add a path item to `.entries`, finding any distributions on it

`find_distributions(entry, True)` is used to find distributions corresponding to the path entry, and they are added. *entry* is always appended to `.entries`, even if it is already present. (This is because `sys.path` can contain the same value more than once, and the `.entries` of the `sys.path` `WorkingSet` should always equal `sys.path`.)

find (*req*)

Find a distribution matching requirement *req*

If there is an active distribution for the requested project, this returns it as long as it meets the version requirement specified by *req*. But, if there is an active distribution for the project and it does *not* meet the *req* requirement, `VersionConflict` is raised. If there is no active distribution for the requested project, None is returned.

find_plugins (*plugin_env, full_env=None, installer=None, fallback=True*)

Find all activatable distributions in *plugin_env*

Example usage:

```
distributions, errors = working_set.find_plugins(
    Environment(plugin_dirlist)
)
map(working_set.add, distributions) # add plugins+libs to sys.path
print 'Could not load', errors      # display errors
```

The *plugin_env* should be an `Environment` instance that contains only distributions that are in the project’s “plugin directory” or directories. The *full_env*, if supplied, should be an `Environment` contains all currently-available distributions. If *full_env* is not supplied, one is created automatically from the `WorkingSet` this method is called on, which will typically mean that every directory on `sys.path` will be scanned for distributions.

installer is a standard installer callback as used by the `resolve()` method. The *fallback* flag indicates whether we should attempt to resolve older versions of a plugin if the newest version cannot be resolved.

This method returns a 2-tuple: (*distributions*, *error_info*), where *distributions* is a list of the distributions found in *plugin_env* that were loadable, along with any other distributions that are needed to resolve their dependencies. *error_info* is a dictionary mapping unloadable plugin distributions to an exception instance describing the error that occurred. Usually this will be a `DistributionNotFound` or `VersionConflict` instance.

iter_entry_points (*group*, *name=None*)

Yield entry point objects from *group* matching *name*

If *name* is `None`, yields all entry points in *group* from all distributions in the working set, otherwise only ones matching both *group* and *name* are yielded (in distribution order).

require (**requirements*)

Ensure that distributions matching *requirements* are activated

requirements must be a string or a (possibly-nested) sequence thereof, specifying the distributions and versions required. The return value is a sequence of the distributions that needed to be activated to fulfill the requirements; all relevant distributions are included, even if they were already activated in this working set.

resolve (*requirements*, *env=None*, *installer=None*)

List all distributions needed to (recursively) meet *requirements*

requirements must be a sequence of `Requirement` objects. *env*, if supplied, should be an `Environment` instance. If not supplied, it defaults to all distributions available within any entry or distribution in the working set. *installer*, if supplied, will be invoked with each requirement that cannot be met by an already-installed distribution; it should return a `Distribution` or `None`.

run_script (*requires*, *script_name*)

Locate distribution for *requires* and run *script_name* script

subscribe (*callback*)

Invoke *callback* for all distributions (including existing ones)

class `pkg_resources.ResourceManager`

Manage resource extraction and packages

cleanup_resources (*force=False*)

Delete all extracted resource files and directories, returning a list of the file and directory names that could not be successfully removed. This function does not have any concurrency protection, so it should generally only be called when the extraction path is a temporary directory exclusive to a single process. This method is not automatically called; you must call it explicitly or register it as an `atexit` function if you wish to ensure cleanup of a temporary directory used for extractions.

extraction_error ()

Give an error message for problems extracting file(s)

extraction_path = None

get_cache_path (*archive_name*, *names*=())

Return absolute location in cache for *archive_name* and *names*

The parent directory of the resulting path will be created if it does not already exist. *archive_name* should be the base filename of the enclosing egg (which may not be the name of the enclosing zipfile!), including its ".egg" extension. *names*, if provided, should be a sequence of path name parts "under" the egg's extraction location.

This method should only be called by resource providers that need to obtain an extraction location, and only for names they intend to extract, as it tracks the generated names for possible cleanup later.

postprocess (*tempname*, *filename*)

Perform any platform-specific postprocessing of *tempname*

This is where Mac header rewrites should be done; other platforms don't have anything special they should do.

Resource providers should call this method ONLY after successfully extracting a compressed resource. They must NOT call it on resources that are already in the filesystem.

tempname is the current (temporary) name of the file, and *filename* is the name it will be renamed to by the caller after this routine returns.

resource_exists (*package_or_requirement*, *resource_name*)

Does the named resource exist?

resource_filename (*package_or_requirement*, *resource_name*)

Return a true filesystem path for specified resource

resource_isdir (*package_or_requirement*, *resource_name*)

Is the named resource an existing directory?

resource_listdir (*package_or_requirement*, *resource_name*)

List the contents of the named resource directory

resource_stream (*package_or_requirement*, *resource_name*)

Return a readable file-like object for specified resource

resource_string (*package_or_requirement*, *resource_name*)

Return specified resource as a string

set_extraction_path (*path*)

Set the base path where resources will be extracted to, if needed.

If you do not call this routine before any extractions take place, the path defaults to the return value of `get_default_cache()`. (Which is based on the PYTHON_EGG_CACHE environment variable, with various platform-specific fallbacks. See that routine's documentation for more details.)

Resources are extracted to subdirectories of this path based upon information given by the `IResourceProvider`. You may set this to a temporary directory, but then you must call `cleanup_resources()` to delete the extracted files when done. There is no guarantee that `cleanup_resources()` will be able to remove all extracted files.

(Note: you may not change the extraction path for a given resource manager once resources have been extracted, unless you first call `cleanup_resources()`.)

class pkg_resources.**Distribution** (*location*=None, *metadata*=None, *project_name*=None, *version*=None, *py_version*='2.7', *platform*=None, *precedence*=3)

Bases: object

Wrap an actual or potential sys.path entry w/metadata

```

PKG_INFO = 'PKG-INFO'

activate (path=None)
    Ensure distribution is importable on path (default=sys.path)

as_requirement ()
    Return a Requirement that matches this distribution exactly

check_version_conflict ()

clone (**kw)
    Copy this distribution, substituting in any changed keyword args

egg_name ()
    Return what this distribution's standard .egg filename should be

extras

classmethod from_filename (filename, metadata=None, **kw)

classmethod from_location (location, basename, metadata=None, **kw)

get_entry_info (group, name)
    Return the EntryPoint object for group+'+'name, or None

get_entry_map (group=None)
    Return the entry point map for group, or the full entry map

has_version ()

hashcmp

insert_on (path, loc=None)
    Insert self.location in path before its nearest parent directory

key

load_entry_point (group, name)
    Return the name entry point of group or raise ImportError

parsed_version

requires (extras=())
    List of Requirements needed for this distro if extras are used

version

class pkg_resources.Requirement (project_name, specs, extras)

    static parse (s)

class pkg_resources.EntryPoint (name, module_name, attrs=(), extras=(), dist=None)
    Bases: object

    Object representing an advertised importable object

    load (require=True, env=None, installer=None)

    classmethod parse (src, dist=None)
        Parse a single entry point from string src

        Entry point syntax follows the form:

```

<pre>name = some.module:some.attr [extral,extra2]</pre>

```

        The entry name and module name are required, but the :attrs and [extras] parts are optional

```

classmethod `parse_group` (*group*, *lines*, *dist=None*)

Parse an entry point group

classmethod `parse_map` (*data*, *dist=None*)

Parse a map of entry point groups

require (*env=None*, *installer=None*)

exception `pkg_resources.ResolutionError`

Bases: `exceptions.Exception`

Abstract base for dependency resolution errors

exception `pkg_resources.VersionConflict`

Bases: `pkg_resources.ResolutionError`

An already-installed version conflicts with the requested version

exception `pkg_resources.DistributionNotFound`

Bases: `pkg_resources.ResolutionError`

A requested distribution was not found

exception `pkg_resources.UnknownExtra`

Bases: `pkg_resources.ResolutionError`

Distribution doesn't have an "extra feature" of the given name

exception `pkg_resources.ExtractionError`

Bases: `exceptions.RuntimeError`

An error occurred extracting a resource

The following attributes are available from instances of this exception:

manager The resource manager that raised this exception

cache_path The base directory for resource extraction

original_error The exception instance that caused extraction to fail

`pkg_resources.parse_requirements` (*strs*)

Yield Requirement objects for each specification in *strs*

strs must be an instance of `basestring`, or a (possibly-nested) iterable thereof.

`pkg_resources.parse_version` (*s*)

Convert a version string to a chronologically-sortable key

This is a rough cross between distutils' `StrictVersion` and `LooseVersion`; if you give it versions that would work with `StrictVersion`, then it behaves the same; otherwise it acts like a slightly-smarter `LooseVersion`. It is *possible* to create pathological version coding schemes that will fool this parser, but they should be very rare in practice.

The returned value will be a tuple of strings. Numeric portions of the version are padded to 8 digits so they will compare numerically, but without relying on how numbers compare relative to strings. Dots are dropped, but dashes are retained. Trailing zeros between alpha segments or dashes are suppressed, so that e.g. "2.4.0" is considered the same as "2.4". Alphanumeric parts are lower-cased.

The algorithm assumes that strings like "-" and any alpha string that alphabetically follows "final" represents a "patch level". So, "2.4-1" is assumed to be a branch or patch of "2.4", and therefore "2.4.1" is considered newer than "2.4-1", which in turn is newer than "2.4".

Strings like "a", "b", "c", "alpha", "beta", "candidate" and so on (that come before "final" alphabetically) are assumed to be pre-release versions, so that the version "2.4" is considered newer than "2.4a1".

Finally, to handle miscellaneous cases, the strings “pre”, “preview”, and “rc” are treated as if they were “c”, i.e. as though they were release candidates, and therefore are not as new as a version string that does not contain them, and “dev” is replaced with an ‘@’ so that it sorts lower than any other pre-release tag.

`pkg_resources.safe_name(name)`

Convert an arbitrary string to a standard distribution name

Any runs of non-alphanumeric/. characters are replaced with a single ‘-’.

`pkg_resources.safe_version(version)`

Convert an arbitrary string to a standard version string

Spaces become dots, and all other non-alphanumeric characters become dashes, with runs of multiple dashes condensed to a single dash.

`pkg_resources.get_platform()`

`pkg_resources.compatible_platforms(provided, required)`

Can code for the *provided* platform run on the *required* platform?

Returns true if either platform is `None`, or the platforms are equal.

XXX Needs compatibility checks for Linux and other unixy OSes.

`pkg_resources.yield_lines(strs)`

Yield non-empty/non-comment lines of a basestring or sequence

`pkg_resources.split_sections(s)`

Split a string or iterable thereof into (section,content) pairs

Each `section` is a stripped version of the section header (“[section]”) and each `content` is a list of stripped lines excluding blank lines and comment-only lines. If there are any such lines before the first section header, they’re returned in a first `section` of `None`.

`pkg_resources.safe_extra(extra)`

Convert an arbitrary string to a standard ‘extra’ name

Any runs of non-alphanumeric characters are replaced with a single ‘_’, and the result is always lowercased.

`pkg_resources.to_filename(name)`

Convert a project or version name to its filename-escaped form

Any ‘-’ characters are currently replaced with ‘_’.

`pkg_resources.invalid_marker(text)`

Validate text as a PEP 426 environment marker; return exception or False

`pkg_resources.evaluate_marker(text, extra=None, _ops={‘not in’: <function <lambda> at 0x7f369fe8fde8>, ‘==’: <built-in function eq>, 304: <function test at 0x7f369fe8f578>, 305: <function test at 0x7f369fe8f578>, 306: <function and_test at 0x7f369fe8fc80>, 308: <function comparison at 0x7f369fe8fd70>, ‘in’: <function <lambda> at 0x7f369fe8fe60>, ‘!=’: <built-in function ne>, 318: <function atom at 0x7f369fe8fcf8>})`

Evaluate a PEP 426 environment marker on CPython 2.4+. Return a boolean indicating the marker result in this environment. Raise `SyntaxError` if marker is invalid.

This implementation uses the ‘parser’ module, which is not implemented on Jython and has been superseded by the ‘ast’ module in Python 2.6 and later.

`pkg_resources.ensure_directory(path)`

Ensure that the parent directory of *path* exists

`pkg_resources.normalize_path(filename)`

Normalize a file/dir name for comparison purposes

class `pkg_resources.IMetadataProvider`

get_metadata (*name*)

The named metadata resource as a string

get_metadata_lines (*name*)

Yield named metadata resource as list of non-blank non-comment lines

Leading and trailing whitespace is stripped from each line, and lines with # as the first non-blank character are omitted.

has_metadata (*name*)

Does the package's distribution contain the named metadata?

metadata_isdir (*name*)

Is the named metadata a directory? (like `os.path.isdir()`)

metadata_listdir (*name*)

List of metadata names in the directory (like `os.listdir()`)

run_script (*script_name*, *namespace*)

Execute the named script in the supplied namespace dictionary

class `pkg_resources.IResourceProvider`

Bases: `pkg_resources.IMetadataProvider`

An object that provides access to package resources

get_resource_filename (*manager*, *resource_name*)

Return a true filesystem path for *resource_name*

manager must be an `IResourceManager`

get_resource_stream (*manager*, *resource_name*)

Return a readable file-like object for *resource_name*

manager must be an `IResourceManager`

get_resource_string (*manager*, *resource_name*)

Return a string containing the contents of *resource_name*

manager must be an `IResourceManager`

has_resource (*resource_name*)

Does the package contain the named resource?

resource_isdir (*resource_name*)

Is the named resource a directory? (like `os.path.isdir()`)

resource_listdir (*resource_name*)

List of resource names in the directory (like `os.listdir()`)

class `pkg_resources.FileMetadata` (*path*)

Bases: `pkg_resources.EmptyProvider`

Metadata handler for standalone PKG-INFO files

Usage:

```
metadata = FileMetadata("/path/to/PKG-INFO")
```

This provider rejects all data and metadata requests except for PKG-INFO, which is treated as existing, and will be the contents of the file at the provided location.

get_metadata (*name*)

get_metadata_lines (*name*)

has_metadata (*name*)

class pkg_resources.**PathMetadata** (*path, egg_info*)

Bases: *pkg_resources.DefaultProvider*

Metadata provider for egg directories

Usage:

```
# Development eggs:

egg_info = "/path/to/PackageName.egg-info"
base_dir = os.path.dirname(egg_info)
metadata = PathMetadata(base_dir, egg_info)
dist_name = os.path.splitext(os.path.basename(egg_info))[0]
dist = Distribution(basedir, project_name=dist_name, metadata=metadata)

# Unpacked egg directories:

egg_path = "/path/to/PackageName-ver-pyver-etc.egg"
metadata = PathMetadata(egg_path, os.path.join(egg_path, 'EGG-INFO'))
dist = Distribution.from_filename(egg_path, metadata=metadata)
```

class pkg_resources.**EggMetadata** (*importer*)

Bases: *pkg_resources.ZipProvider*

Metadata provider for .egg files

class pkg_resources.**EmptyProvider**

Bases: *pkg_resources.NullProvider*

Provider that returns nothing for all requests

module_path = None

class pkg_resources.**NullProvider** (*module*)

Try to implement resources and metadata for arbitrary PEP 302 loaders

egg_info = None

egg_name = None

get_metadata (*name*)

get_metadata_lines (*name*)

get_resource_filename (*manager, resource_name*)

get_resource_stream (*manager, resource_name*)

get_resource_string (*manager, resource_name*)

has_metadata (*name*)

has_resource (*resource_name*)

loader = None

metadata_isdir (*name*)

metadata_listdir (*name*)

resource_isdir (*resource_name*)

resource_listdir (*resource_name*)

run_script (*script_name*, *namespace*)

class `pkg_resources.EggProvider` (*module*)

Bases: `pkg_resources.NullProvider`

Provider based on a virtual filesystem

class `pkg_resources.DefaultProvider` (*module*)

Bases: `pkg_resources.EggProvider`

Provides access to package resources in the filesystem

get_resource_stream (*manager*, *resource_name*)

class `pkg_resources.ZipProvider` (*module*)

Bases: `pkg_resources.EggProvider`

Resource support for zips and eggs

eagers = None

get_resource_filename (*manager*, *resource_name*)

`pkg_resources.register_finder` (*importer_type*, *distribution_finder*)

Register *distribution_finder* to find distributions in `sys.path` items

importer_type is the type or class of a PEP 302 “Importer” (`sys.path` item handler), and *distribution_finder* is a callable that, passed a path item and the importer instance, yields `Distribution` instances found on that path item. See `pkg_resources.find_on_path` for an example.

`pkg_resources.register_namespace_handler` (*importer_type*, *namespace_handler*)

Register *namespace_handler* to declare namespace packages

importer_type is the type or class of a PEP 302 “Importer” (`sys.path` item handler), and *namespace_handler* is a callable like this:

```
def namespace_handler(importer, path_entry, moduleName, module):
    # return a path_entry to use for child packages
```

Namespace handlers are only called if the importer object has already agreed that it can handle the relevant path item, and they should only return a subpath if the module `__path__` does not already contain an equivalent subpath. For an example namespace handler, see `pkg_resources.file_ns_handler`.

`pkg_resources.register_loader_type` (*loader_type*, *provider_factory*)

Register *provider_factory* to make providers for *loader_type*

loader_type is the type or class of a PEP 302 module `__loader__`, and *provider_factory* is a function that, passed a *module* object, returns an `IResourceProvider` for that module.

`pkg_resources.fixup_namespace_packages` (*path_item*, *parent=None*)

Ensure that previously-declared namespace packages include *path_item*

`pkg_resources.get_importer` (*path_item*)

Retrieve a PEP 302 importer for the given path item

The returned importer is cached in `sys.path_importer_cache` if it was newly created by a path hook.

If there is no importer, a wrapper around the basic import machinery is returned. This wrapper is never inserted into the importer cache (None is inserted instead).

The cache (or part of it) can be cleared manually if a rescan of `sys.path_hooks` is necessary.

`pkg_resources.AvailableDistributions`
alias of *Environment*

1.2.7 psyco_full Module

Attempt to call `psyco.full`, but ignore any errors.

1.3 Releases

1.3.1 July 2015 Galaxy Release (v 15.07)

Notes

- Dates are subject to change.
- The July 2015 Galaxy release will have prolonged freeze period which includes the full GCC.

Schedule

- Planned Freeze Date: June 22, 2015
- Planned Release Date: July 13, 2015

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.2 May 2015 Galaxy Release (v 15.05)

Highlights

Authentication Plugins Galaxy now has native support for LDAP and Active Directory via a new community developed authentication plugin system.

Tool Sections Tool parameters may now be grouped into collapsable sections.

Collection Creators New widgets have been added that allow much more flexibility when creating simple dataset pair and list collections.

Github

New

```
% git clone -b master https://github.com/galaxyproject/galaxy.git
```

Update to latest stable release

```
% git checkout master && pull --ff-only origin master
```

Update to exact version

```
% git checkout v15.05
```

BitBucket

Upgrade

```
% hg pull
% hg update latest_15.05
```

See [our wiki](#) for additional details regarding the source code locations.

Release Notes

Enhancements

- Pluggable framework to custom authentication (including new LDAP/Active Directory integration). Thanks to many including Andrew Robinson, Nicola Soranzo, and David Trudgian. [Pull Request 1](#), [Pull Request 33](#), [Pull Request 51](#), [Pull Request 75](#), [Pull Request 98](#), [Pull Request 216](#)
- Implement a new `section` tag for tool parameters. [Pull Request 35](#), [Trello](#)
- New UI widgets allowing much more flexibility when creating simple dataset pair and list collections. [Pull Request 134](#), [Trello](#)
- Improved JavaScript build system for client code and libraries (now using `uglify` and featuring [Source Maps](#)). [72c876c](#), [9a7f5fc](#), [648a623](#), [22f280f](#), [Trello](#)
- Add an [External Display Application](#) for viewing GFF/GTF files with IGV. [Pull Request 70](#), [Trello](#)
- Use [TravisCI](#) and [Tox](#) for continuous integration testing. [Pull Request 40](#), [Pull Request 62](#), [Pull Request 97](#), [Pull Request 99](#), [Pull Request 123](#), [Pull Request 222](#), [Pull Request 235](#),
- Infrastructure for improved toolbox and Tool Shed searching. [Pull Request 9](#), [Pull Request 116](#), [Pull Request 142](#), [Pull Request 226](#), [c2eb74c](#), [2bf52fe](#), [ec549db](#), [Trello](#), [Trello](#)
- Enhance UI to allow renaming dataset collections. [21d1d6b](#)
- Improve highlighting of current/active content history panel. [Pull Request 126](#)
- Improvements to UI and API for histories and collections. [e36e51e](#), [1e55206](#), [0c79680](#)
- Update history dataset API to account for job re-submission. [b4cf49a](#)
- Allow recalculating user disk usage from the admin interface. [964e081](#)
- Collect significantly more metadata for BAM files. [Pull Request 107](#), [Pull Request 108](#)
- Implement `detect_errors` attribute on command of tool XML. [Pull Request 117](#)
- Allow setting `auto_format="True"` on tool output tags. [Pull Request 130](#)
- Allow testing tool outputs based on MD5 hashes. [Pull Request 125](#)
- Improved Cheetah type casting for int/float values. [Pull Request 121](#)

- Add option to pass arbitrary parameters to gem install as part of the tool shed `setup_ruby_environment` Tool Shed install action - thanks to Björn Grüning. [Pull Request 118](#)
- Add `argument` attribute to tool parameters. [Pull Request 8](#)
- Improve link and message that appears after workflows are run. [Pull Request 143](#)
- Add NCBI SRA datatype - thanks to Matt Shirley. [Pull Request 87](#)
- Stronger toolbox filtering. [Pull Request 119](#)
- Allow updating Tool Shed repositories via the API - thanks to Eric Rasche. [Pull Request 30](#)
- Expose category list in show call for Tool Shed repositories - thanks to Eric Rasche. [Pull Request 29](#)
- Add API endpoint to create Tool Shed repositories. [Pull Request 2](#)
- Do not configure Galaxy to use the test Tool Shed by default. [Pull Request 38](#)
- Add fields and improve display of Tool Shed repositories. [a24e206](#), [d6d61bc](#), [Trello](#)
- Enhance multi-selection widgets to allow key combinations `Ctrl-A` and `Ctrl-X`. [e8564d7](#), [Trello](#)
- New, consistent button for displaying citation BibTeX. [Pull Request 19](#)
- Improved `README` reflecting move to Github - thanks in part to Eric Rasche. [PR #2 \(old repo\)](#), [226e826](#), [2650d09](#), [7d5dde8](#)
- Update application to use new logo. [2748f9d](#), [Pull Request 187](#), [Pull Request 206](#)
- Update many documentation links to use https sites - thanks to Nicola Soranzo. [8254cab](#)
- Sync report options config with `galaxy.ini` - thanks to Björn Grüning. [Pull Request 12](#)
- Eliminate need to use API key to list tools via API. [cd7abe8](#)
- Restore function necessary for splitting sequence datatypes - thanks to Roberto Alonso. [Pull Request 5](#)
- Suppress filenames in SAM merge using `egrep` - thanks to Peter Cock and Roberto Alonso. [Pull Request 4](#)
- Option to sort counts in `Count1` tool (`tools/filters/uniq.xml`) - thanks to Peter Cock. [Pull Request 16](#)
- Preserve spaces in `Count1` tool (`tools/filters/uniq.xml`) - thanks to Peter Cock. [Pull Request 13](#)
- [Interactive Environments](#) improvements and fixes from multiple developers including Eric Rasche and Björn Grüning. [Pull Request 69](#), [Pull Request 73](#), [Pull Request 131](#), [Pull Request 135](#), [Pull Request 152](#), [Pull Request 197](#)
- Enable multi-part upload for exporting files with the GenomeSpace export tool. [Pull Request 74](#), [Trello](#)
- Large refactoring, expansion, and increase in test coverage for “managers”. [Pull Request 76](#)
- Improved display of headers in tool help. [157eba6](#), [Biostar](#)
- Uniform configuration of “From” field for sent emails - thanks to Nicola Soranzo. [Pull Request 23](#)
- Allow setting `job_conf.xml` params via environment variables & `galaxy.ini`. [dde2fc9](#)
- Allow a tool data table to declare that duplicate entries are not allowed. [Pull Request 245](#)
- Add verbose test error flag option in `run_tests.sh`. [62f0495](#)
- Update `.gitignore` to include `run_api_tests.html`. [b52cc98](#)
- Add experimental options to run tests in Docker. [e99adb5](#)
- Improve `run_test.sh --help` documentation to detail running specific tests. [Pull Request 86](#)
- Remove older, redundant history tests. [Pull Request 120](#), [Trello](#)

- Add test tool demonstrating citing a Github repository. [65def71](#)
- Add option to track all automated changes to the integrated tool panel. [10bb492](#)
- Make tool version explicit in all distribution tool - thanks to Peter Cock. [Pull Request 14](#).
- Relocate the external metadata setting script. [Pull Request 7](#)
- Parameterize script used to pull new builds from the UCSC Browser. [e4e5df0](#)
- Enhance jobs and workflow logging to report timings. [06346a4](#)
- Add debug message for dynamic options exceptions. [Pull Request 91](#)
- Remove demo sequencer app. [3af3bf5](#)
- Tweaks to the Pulsar's handling of async messages. [Pull Request 109](#)
- Return more specific API authentication errors. [71a64ca](#)
- Upgrade Python dependency sqlalchemy to 1.0.0. [d725aab](#), [Pull Request 129](#)
- Upgrade Python dependency amqp to 1.4.6. [Pull Request 128](#)
- Upgrade Python dependency kombu to 3.0.24. [Pull Request 128](#)
- Upgrade JavaScript dependency raven.js to 1.1.17. [bcd1701](#)

Fixes

- During the 15.05 development cycle dozens of fixes were pushed to the `release_15.03` branch of Galaxy. These are all included in 15.05 and summarized [here](#) (with special thanks to Björn Grüning and Marius van den Beek).
- Fix race condition that would occasionally prevent Galaxy from starting properly. [Pull Request 198](#), [Trello](#)
- Fix scatter plot API communications for certain proxied Galaxy instances - thanks to @yhoogstrate. [Pull Request 89](#)
- Fix bug in `collectl` job metrics plugin - thanks to Carrie Ganote. [Pull Request 231](#)
- Fix late validation of tool parameters. [Pull Request 115](#)
- Fix `fasta_to_tabular_converter.py` (for implicit conversion) - thanks to Peter Cock. [Pull Request 11](#)
- Fix to eliminate race condition by collecting extra files before declaring dataset's OK. [Pull Request 48](#)
- Fix setting current history for certain proxied Galaxy instances - thanks to @wezen. [6946e46](#).
- Fix typo in tool failure testing example - thanks to Peter Cock. [Pull Request 18](#).
- Fix Galaxy to default to using SSL for communicating with Tool Sheds. [0b037a2](#)
- Fix data source tools to open in `_top` window. [Pull Request 17](#)
- Fix to fallback to name for tool parameters without labels. [Pull Request 189](#), [Trello](#)
- Fix to remove redundant version ids in tool version selector. [Pull Request 244](#)
- Fix for downloading metadata files. [Pull Request 234](#)
- Fix for history failing to render if it contains more exotic dataset collection types. [Pull Request 196](#)
- Fixes for `BaseURLToolParameter`. [Pull Request 247](#)
- Fix to suppress pysam binary incompatibility warning when using datatypes in `binary.py`. [Pull Request 252](#)

- Fix for library UI duplication bug. [Pull Request 179](#)
- Fix for [Backbone.js](#) loading as AMD. [4e5218f](#)
- Other small Tool Shed fixes. [815f86f](#), [76e0915](#)
- Fix file closing in `lped_to_pbed_converter`. [182b67f](#)
- Fix undefined variables in Tool Shed `add_repository_entry` API script. [47e6f08](#)
- Fix user registration to respect `use_panels` when in the Galaxy app. [7ac8631](#), [Trello](#)
- Fix bug in `scramble` exception, incorrect reference to `source_path` [79d50d8](#)
- Fix error handling in `pbed_to_lped`. [7aec7a](#)
- Fix error handling in Tool Shed step handler for `chmod` action. [1454396](#)
- Fix `__safe_string_wrapper` in tool evaluation `object_wrapper`. [ab6f13e](#)
- Fixes for data types and data providers. [c1d2d1f](#), [8da70bb](#), [0b83b1e](#)
- Fixes for Tool Shed commit and mercurial handling modules. [6102edf](#), [b639bc0](#), [debea9d](#)
- Fix to clean working directory during job re-submission. [Pull Request 236](#)
- Fix bug when task splitting jobs fail. [Pull Request 214](#)
- Fix some minor typos in comment docs in `config/galaxy.ini.sample`. [Pull Request 210](#)
- Fix admin disk usage message. [Pull Request 205](#), [Trello](#)
- Fix to `sessionStorage` Model to suppress `QUOTA DOMExceptions` when Safari users are in private browsing mode. [0c94f04](#)

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.3 March 2015 Galaxy Release (v 15.03)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.4 January 2015 Galaxy Release (v 15.01)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.5 October 2014 Galaxy Release (v 14.10)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.6 August 2014 Galaxy Release (v 14.08)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.7 June 2014 Galaxy Release (v 14.06)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.8 April 2014 Galaxy Release (v 14.04)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.9 February 2014 Galaxy Release (v 14.02)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.10 November 2013 Galaxy Release (v 13.11)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.11 August 2013 Galaxy Release (v 13.08)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.12 June 2013 Galaxy Release (v 13.06)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.13 April 2013 Galaxy Release (v 13.04)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.14 February 2013 Galaxy Release (v 13.02)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.15 January 2013 Galaxy Release (v 13.01)

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

1.3.16 Galaxy Releases older than v 13.01

Please see the [Galaxy wiki](#) for announcement and release notes.

To stay up to date with Galaxy's progress watch our [screencasts](#), read our [wiki](#), and follow [@galaxyproject](#) on Twitter.

Thanks for using Galaxy!

The Galaxy Team

Indices and tables

- `genindex`
- `modindex`
- `search`

g

[galaxy](#), 42
[galaxy.actions.admin](#), 43
[galaxy.config](#), 42
[galaxy.datatypes.assembly](#), 43
[galaxy.datatypes.binary](#), 44
[galaxy.datatypes.checkers](#), 49
[galaxy.datatypes.chrominfo](#), 49
[galaxy.datatypes.converters.bed_to_gff_converter](#), 91
[galaxy.datatypes.converters.bgzip](#), 92
[galaxy.datatypes.converters.fasta_to_len](#), 92
[galaxy.datatypes.converters.fasta_to_tabular_converter](#), 92
[galaxy.datatypes.converters.fastq_to_fastq_gz](#), 92
[galaxy.datatypes.converters.fastqsolexa_to_fastq_converter](#), 92
[galaxy.datatypes.converters.fastqsolexa_to_qual_converter](#), 92
[galaxy.datatypes.converters.gff_to_bed_converter](#), 92
[galaxy.datatypes.converters.gff_to_interval_index_converter](#), 93
[galaxy.datatypes.converters.interval_to_bed_converter](#), 93
[galaxy.datatypes.converters.interval_to_bedstrict_converter](#), 93
[galaxy.datatypes.converters.interval_to_coverage](#), 93
[galaxy.datatypes.converters.interval_to_gff](#), 93
[galaxy.datatypes.converters.interval_to_interval_index_converter](#), 94
[galaxy.datatypes.converters.interval_to_tabix_converter](#), 94
[galaxy.datatypes.converters.lped_to_fped_converter](#), 94
[galaxy.datatypes.converters.lped_to_pbed_converter](#), 94
[galaxy.datatypes.converters.maf_to_fastq_converter](#), 94
[galaxy.datatypes.converters.maf_to_interval_converter](#), 94
[galaxy.datatypes.converters.pbed_ldreduced_converter](#), 95
[galaxy.datatypes.converters.pbed_to_lped_converter](#), 95
[galaxy.datatypes.converters.picard_interval_list_to_bed](#), 95
[galaxy.datatypes.converters.sam_to_bam](#), 95
[galaxy.datatypes.converters.vcf_to_interval_index_converter](#), 95
[galaxy.datatypes.converters.vcf_to_vcf_bgzip](#), 96
[galaxy.datatypes.converters.wiggle_to_array_tree_converter](#), 96
[galaxy.datatypes.converters.wiggle_to_simple_converter](#), 96
[galaxy.datatypes.coverage](#), 49
[galaxy.datatypes.data](#), 50
[galaxy.datatypes.display_applications.application](#), 96
[galaxy.datatypes.display_applications.parameters](#), 97
[galaxy.datatypes.display_applications.util](#), 98
[galaxy.datatypes.genetics](#), 54
[galaxy.datatypes.images](#), 59
[galaxy.datatypes.interval](#), 63
[galaxy.datatypes.metadata](#), 70
[galaxy.datatypes.ngsindex](#), 73
[galaxy.datatypes.qualityscore](#), 74
[galaxy.datatypes.registry](#), 75
[galaxy.datatypes.sequence](#), 76
[galaxy.datatypes.sniff](#), 82
[galaxy.datatypes.tabular](#), 85
[galaxy.datatypes.tracks](#), 90
[galaxy.datatypes.util](#), 98

galaxy.datatypes.util.gff_util, 98
galaxy.datatypes.util.image_util, 100
galaxy.datatypes.xml, 90
galaxy.eggs, 100
galaxy.eggs.dist, 101
galaxy.eggs.scramble, 102
galaxy.exceptions, 103
galaxy.external_services.actions, 106
galaxy.external_services.parameters, 107
galaxy.external_services.result_handlers, 109
galaxy.external_services.service, 108
galaxy.forms.forms, 110
galaxy.jobs, 112
galaxy.jobs.actions, 120
galaxy.jobs.actions.post, 120
galaxy.jobs.deferred, 122
galaxy.jobs.deferred.data_transfer, 123
galaxy.jobs.deferred.manual_data_transfer, 123
galaxy.jobs.deferred.pacific_biosciences, 123
galaxy.jobs.handler, 117
galaxy.jobs.manager, 119
galaxy.jobs.mapper, 119
galaxy.jobs.runners, 123
galaxy.jobs.runners.cli, 125
galaxy.jobs.runners.condor, 126
galaxy.jobs.runners.drmaa, 126
galaxy.jobs.runners.local, 127
galaxy.jobs.runners.lwr, 127
galaxy.jobs.runners.tasks, 127
galaxy.jobs.splitters.basic, 128
galaxy.jobs.splitters.multi, 128
galaxy.jobs.transfer_manager, 119
galaxy.managers, 154
galaxy.managers.api_keys, 154
galaxy.managers.base, 154
galaxy.managers.citations, 158
galaxy.managers.collections, 159
galaxy.managers.collections_util, 159
galaxy.managers.context, 159
galaxy.managers.folders, 160
galaxy.managers.hdas, 162
galaxy.managers.histories, 164
galaxy.managers.lddas, 165
galaxy.managers.libraries, 166
galaxy.managers.roles, 167
galaxy.managers.tags, 167
galaxy.managers.workflows, 168
galaxy.model, 128
galaxy.model.item_attrs, 152
galaxy.model.migrate.check, 153
galaxy.model.orm, 153
galaxy.model.orm.logging_connection_proxy, 153
galaxy.objectstore, 169
galaxy.objectstore.s3_multipart_upload, 172
galaxy.openid, 173
galaxy.openid.providers, 173
galaxy.quota, 173
galaxy.sample_tracking.data_transfer, 174
galaxy.sample_tracking.external_service_types, 175
galaxy.sample_tracking.request_types, 175
galaxy.sample_tracking.sample, 175
galaxy.security, 175
galaxy.security.validate_user_input, 181
galaxy.tags, 181
galaxy.tags.tag_handler, 181
galaxy.tools, 182
galaxy.tools.actions, 190
galaxy.tools.actions.history_imp_exp, 191
galaxy.tools.actions.metadata, 191
galaxy.tools.actions.upload, 191
galaxy.tools.actions.upload_common, 191
galaxy.tools.data, 192
galaxy.tools.deps, 195
galaxy.tools.exception_handling, 189
galaxy.tools.imp_exp, 195
galaxy.tools.imp_exp.export_history, 196
galaxy.tools.imp_exp.unpack_tar_gz_archive, 196
galaxy.tools.parameters, 196
galaxy.tools.parameters.basic, 197
galaxy.tools.parameters.dynamic_options, 208
galaxy.tools.parameters.grouping, 211
galaxy.tools.parameters.input_translation, 213
galaxy.tools.parameters.output, 214
galaxy.tools.parameters.sanitize, 217
galaxy.tools.parameters.validation, 218
galaxy.tools.search, 222
galaxy.tools.test, 189
galaxy.tools.util, 222
galaxy.tools.util.galaxyops, 225
galaxy.tools.util.maf_utilities, 222
galaxy.util, 225
galaxy.util.aliaspickler, 229
galaxy.util.backports, 237
galaxy.util.backports.importlib, 237
galaxy.util.bunch, 230
galaxy.util.debugging, 230

galaxy.util.expressions, 230
 galaxy.util.hash_util, 230
 galaxy.util.heartbeat, 231
 galaxy.util.inflection, 231
 galaxy.util.json, 233
 galaxy.util.lrucache, 234
 galaxy.util.none_like, 235
 galaxy.util.odict, 235
 galaxy.util.sanitize_html, 235
 galaxy.util.streamball, 236
 galaxy.util.template, 236
 galaxy.util.topsort, 236
 galaxy.visualization, 237
 galaxy.visualization.data_providers, 238
 galaxy.visualization.data_providers.basic, 238
 galaxy.visualization.data_providers.phylol, 239
 galaxy.visualization.data_providers.phylolbase, 239
 galaxy.visualization.data_providers.phylolnew, 240
 galaxy.visualization.data_providers.phylolnewbase, 240
 galaxy.visualization.data_providers.phylolnewbaseparser, 241
 galaxy.visualization.genome, 241
 galaxy.visualization.genomes, 237
 galaxy.visualization.tracks, 241
 galaxy.web, 241
 galaxy.web.base.controller, 246
 galaxy.web.base.controllers.admin, 251
 galaxy.web.form_builder, 241
 galaxy.web.framework, 253
 galaxy.web.framework.base, 253
 galaxy.web.framework.helpers, 257
 galaxy.web.framework.helpers.grids, 257
 galaxy.web.framework.middleware, 264
 galaxy.web.framework.middleware.profile, 264
 galaxy.web.framework.middleware.remoteuser, 265
 galaxy.web.framework.middleware.static, 265
 galaxy.web.framework.middleware.translogger, 265
 galaxy.web.framework.middleware.xforwardedfor, 265
 galaxy.web.framework.openid_manager, 256
 galaxy.web.params, 246
 galaxy.web.security, 266
 galaxy.webapps, 266
 galaxy.webapps.galaxy.api.annotations, 272
 galaxy.webapps.galaxy.api.authenticate, 273
 galaxy.webapps.galaxy.api.configuration, 273
 galaxy.webapps.galaxy.api.dataset_collections, 274
 galaxy.webapps.galaxy.api.datatypes, 274
 galaxy.webapps.galaxy.api.extended_metadata, 275
 galaxy.webapps.galaxy.api.folder_contents, 275
 galaxy.webapps.galaxy.api.folders, 276
 galaxy.webapps.galaxy.api.forms, 278
 galaxy.webapps.galaxy.api.genomes, 278
 galaxy.webapps.galaxy.api.group_roles, 278
 galaxy.webapps.galaxy.api.group_users, 279
 galaxy.webapps.galaxy.api.groups, 279
 galaxy.webapps.galaxy.api.histories, 279
 galaxy.webapps.galaxy.api.history_contents, 282
 galaxy.webapps.galaxy.api.item_tags, 284
 galaxy.webapps.galaxy.api.job_files, 285
 galaxy.webapps.galaxy.api.jobs, 286
 galaxy.webapps.galaxy.api.lda_datasets, 287
 galaxy.webapps.galaxy.api.libraries, 290
 galaxy.webapps.galaxy.api.library_contents, 293
 galaxy.webapps.galaxy.api.metrics, 295
 galaxy.webapps.galaxy.api.page_revisions, 295
 galaxy.webapps.galaxy.api.pages, 296
 galaxy.webapps.galaxy.api.provenance, 297
 galaxy.webapps.galaxy.api.quotas, 297
 galaxy.webapps.galaxy.api.request_types, 297
 galaxy.webapps.galaxy.api.requests, 298
 galaxy.webapps.galaxy.api.roles, 298
 galaxy.webapps.galaxy.api.samples, 298
 galaxy.webapps.galaxy.api.tool_data, 299
 galaxy.webapps.galaxy.api.tool_shed_repositories, 299
 galaxy.webapps.galaxy.api.users, 302
 galaxy.webapps.galaxy.api.visualizations, 302
 galaxy.webapps.galaxy.api.workflows, 303
 galaxy.webapps.galaxy.controllers, 306
 galaxy.webapps.galaxy.controllers.admin, 306
 galaxy.webapps.galaxy.controllers.admin_toolshed, 312

[galaxy.webapps.galaxy.controllers.async](#), [galaxy.webapps.reports.controllers.users](#),
[314](#) [345](#)
[galaxy.webapps.galaxy.controllers.datasets](#), [galaxy.webapps.reports.controllers.workflows](#),
[314](#) [345](#)
[galaxy.webapps.galaxy.controllers.error](#), [galaxy.workflow.modules](#), [347](#)
[317](#) [galaxy_utils.sequence.fasta](#), [352](#)
[galaxy.webapps.galaxy.controllers.external_async_vitals](#), [galaxy_utils.sequence.fastq](#), [352](#)
[317](#) [galaxy_utils.sequence.sequence](#), [356](#)
[galaxy.webapps.galaxy.controllers.external_async_vitals](#), [galaxy_utils.sequence.transform](#), [356](#)
[318](#) [galaxy_utils.sequence.vcf](#), [357](#)
[galaxy.webapps.galaxy.controllers.forms](#),
[318](#) [I](#)
[galaxy.webapps.galaxy.controllers.history_log_tempfile](#), [357](#)
[319](#)
[galaxy.webapps.galaxy.controllers.library](#), [m](#)
[323](#) [mimeparse](#), [358](#)
[galaxy.webapps.galaxy.controllers.library_admin](#),
[324](#) [p](#)
[galaxy.webapps.galaxy.controllers.library_common](#), [pkg_resources](#), [359](#)
[325](#) [psyco_full](#), [369](#)
[galaxy.webapps.galaxy.controllers.mobile](#),
[327](#)
[galaxy.webapps.galaxy.controllers.page](#),
[327](#)
[galaxy.webapps.galaxy.controllers.request_type](#),
[330](#)
[galaxy.webapps.galaxy.controllers.requests](#),
[332](#)
[galaxy.webapps.galaxy.controllers.requests_admin](#),
[332](#)
[galaxy.webapps.galaxy.controllers.requests_common](#),
[334](#)
[galaxy.webapps.galaxy.controllers.root](#),
[336](#)
[galaxy.webapps.galaxy.controllers.tag](#),
[337](#)
[galaxy.webapps.galaxy.controllers.tool_runner](#),
[337](#)
[galaxy.webapps.galaxy.controllers.ucsc_proxy](#),
[338](#)
[galaxy.webapps.galaxy.controllers.user](#),
[338](#)
[galaxy.webapps.reports](#), [340](#)
[galaxy.webapps.reports.app](#), [340](#)
[galaxy.webapps.reports.config](#), [341](#)
[galaxy.webapps.reports.controllers](#), [341](#)
[galaxy.webapps.reports.controllers.jobs](#),
[341](#)
[galaxy.webapps.reports.controllers.root](#),
[343](#)
[galaxy.webapps.reports.controllers.sample_tracking](#),
[343](#)
[galaxy.webapps.reports.controllers.system](#),
[345](#)

A

- Ab1 (class in `galaxy.datatypes.binary`), 44
- `access_action()` (`galaxy.webapps.galaxy.controllers.external_services.ExternalServiceController` module method), 318
- `act_on_multiple_datasets()` (`galaxy.webapps.galaxy.controllers.library_common.LibraryCommon` module method), 325
- Action (class in `galaxy.security`), 175
- `ACTION_NAME` (`galaxy.datatypes.display_applications.parameters.DisplayParameterWrapper` attribute), 98
- `action_name` (`galaxy.datatypes.display_applications.parameters.DisplayParameterWrapper` attribute), 98
- `ACTION_NAME` (`galaxy.datatypes.display_applications.parameters.DisplayParameterWrapper` attribute), 98
- `action_name` (`galaxy.datatypes.display_applications.parameters.DisplayParameterWrapper` attribute), 98
- `action_type` (in module `galaxy.tools.parameters.output`), 217
- ActionBox (class in `galaxy.jobs.actions.post`), 120
- ActionInputError, 103
- `actions` (`galaxy.jobs.actions.post.ActionBox` attribute), 120
- ActionSection (class in `galaxy.external_services.service`), 108
- `activatable_datasets` (`galaxy.model.History` attribute), 135
- `activatable_folders()` (in module `galaxy.webapps.galaxy.controllers.library_common`), 326
- `activatable_folders_and_library_datasets()` (in module `galaxy.webapps.galaxy.controllers.library_common`), 326
- `activatable_library_datasets` (`galaxy.model.LibraryFolder` attribute), 142
- `activate()` (`galaxy.webapps.galaxy.controllers.user.User` method), 338
- `activate()` (`pkg_resources.Distribution` method), 363
- `activate_repository()` (`galaxy.webapps.galaxy.controllers.admin_tools.AdminTools` method), 312
- `active` (`galaxy.model.WorkflowInvocation` attribute), 150
- `active_contents` (`galaxy.model.History` attribute), 135
- `active_datasets_children_and_roles` (`galaxy.model.History` attribute), 135
- `active_folders()` (in module `galaxy.tools.actions.upload_common`), 191
- `active_folders()` (in module `galaxy.webapps.galaxy.controllers.library_common`), 326
- `active_folders_and_library_datasets()` (in module `galaxy.webapps.galaxy.controllers.library_common`), 326
- `add()` (`galaxy.managers.citations.CitationCollection` method), 158
- `add()` (`galaxy.util.streamball.StreamBall` method), 236
- `add()` (`pkg_resources.Environment` method), 359
- `add()` (`pkg_resources.WorkingSet` method), 360
- `add_api_controller()` (`galaxy.web.framework.base.WebApplication` method), 255
- `add_composite_file()` (`galaxy.datatypes.data.Data` method), 50
- `add_data_table_watch()` (`galaxy.datatypes.display_applications.application` method), 96
- `add_dataset()` (`galaxy.model.History` method), 135
- `add_dataset_collection()` (`galaxy.model.History` method), 135
- `add_deserializers()` (`galaxy.managers.base.ModelDeserializer` method), 154
- `add_deserializers()` (`galaxy.managers.hdas.HDADeserializer` method), 163
- `add_deserializers()` (`galaxy.managers.histories.HistoryDeserializer` method), 164
- `add_display_app()` (`galaxy.datatypes.data.Data` method), 50
- `add_display_application()` (`galaxy.datatypes.data.Data` method), 50
- `add_dummy_datasets()` (`galaxy.workflow.modules.ToolModule` method), 349
- `add_dummy_datasets()` (`galaxy.workflow.modules.WorkflowModule` method), 350
- `add_entries()` (`galaxy.tools.data.ToolDataTable` method), 193
- `add_entry()` (`galaxy.tools.data.ToolDataTable` method),

- 193
- `add_entry()` (`pkg_resources.WorkingSet` method), 360
- `add_error()` (`galaxy.tools.ToolErrorLog` method), 188
- `add_external_service_association()` (`galaxy.model.RequestType` method), 144
- `add_folder()` (`galaxy.model.LibraryFolder` method), 142
- `add_galaxy_session()` (`galaxy.model.History` method), 135
- `add_history()` (`galaxy.model.GalaxySession` method), 134
- `add_history_datasets_to_library()` (`galaxy.webapps.galaxy.controllers.library_common.LibraryCommon` method), 325
- `add_implicit_input_collection()` (`galaxy.model.HistoryDatasetCollectionAssociation` method), 137
- `add_implicit_output_dataset_collection()` (`galaxy.model.Job` method), 138
- `add_input()` (`galaxy.model.WorkflowInvocation` method), 150
- `add_input_dataset()` (`galaxy.model.Job` method), 138
- `add_input_dataset_collection()` (`galaxy.model.Job` method), 138
- `add_input_library_dataset()` (`galaxy.model.Job` method), 138
- `add_item()` (`galaxy.external_services.service.ExternalService` method), 108
- `add_item_annotation()` (`galaxy.model.item_attrs.UsesAnnotations` method), 152
- `add_library_dataset()` (`galaxy.model.LibraryFolder` method), 142
- `add_metric()` (`galaxy.model.HasJobMetrics` method), 135
- `add_new_entries_from_config_file()` (`galaxy.tools.data.ToolDataTableManager` method), 194
- `add_option()` (`galaxy.web.form_builder.SelectField` method), 245
- `add_output_dataset()` (`galaxy.model.Job` method), 138
- `add_output_dataset_collection()` (`galaxy.model.Job` method), 138
- `add_output_library_dataset()` (`galaxy.model.Job` method), 138
- `add_parameter()` (`galaxy.model.Job` method), 138
- `add_post_job_action()` (`galaxy.model.Job` method), 138
- `add_route()` (`galaxy.web.framework.base.WebApplication` method), 255
- `add_sample()` (`galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon` method), 334
- `add_samples()` (`galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon` method), 334
- `add_serializers()` (`galaxy.managers.base.ModelSerializer` method), 157
- `add_serializers()` (`galaxy.managers.hdas.HDASerializer` method), 164
- `add_serializers()` (`galaxy.managers.histories.HistorySerializer` method), 165
- `add_species()` (`galaxy.tools.util.maf_utilities.RegionAlignment` method), 222
- `add_sreg()` (`galaxy.web.framework.openid_manager.OpenIDManager` method), 256
- `add_tag_async()` (`galaxy.webapps.galaxy.controllers.tag.TagsController` method), 337
- `add_template()` (`galaxy.web.base.controller.UsesFormDefinitionsMixin` method), 249
- `add_ui_controller()` (`galaxy.web.framework.base.WebApplication` method), 255
- `add_validation_error()` (`galaxy.model.DatasetInstance` method), 131
- `add_view()` (`galaxy.managers.base.ModelSerializer` method), 157
- `add_visualization_revision()` (`galaxy.web.base.controller.UsesVisualizationMixin` method), 250
- `addAttributesToRoot()` (`galaxy.visualization.data_providers.phyloviz.baseparser.N` method), 239
- `addChildNode()` (`galaxy.visualization.data_providers.phyloviz.baseparser.N` method), 239
- `addChildrenToJson()` (`galaxy.visualization.data_providers.phyloviz.baseparser.N` method), 239
- `AdditionalData` (class in `galaxy.webapps.galaxy.controllers.tool_runner`), 337
- `adding_to_library_dataset_files` (`galaxy.model.Sample` attribute), 145
- `AdditionalValueFilter` (class in `galaxy.tools.parameters.dynamic_options`), 208
- `addMiscToJson()` (`galaxy.visualization.data_providers.phyloviz.baseparser.N` method), 239
- `AddressField` (class in `galaxy.web.form_builder`), 241
- `addRoot()` (`galaxy.visualization.data_providers.phyloviz.baseparser.PhyloTr` method), 240
- `Admin` (class in `galaxy.web.base.controllers.admin`), 251
- `AdminActions` (class in `galaxy.actions.admin`), 43
- `AdminGalaxy` (class in `galaxy.webapps.galaxy.controllers.admin`), 306
- `AdminRequestsGrid` (class in `galaxy.webapps.galaxy.controllers.requests_admin`), 332
- `AdminRequestsGridColumn` (class in `galaxy.webapps.galaxy.controllers.requests_admin`), 332
- `AdminRequiredException`, 103
- `AdminToolshed` (class in `galaxy.webapps.galaxy.controllers.admin_toolshed`), 312
- `Affybatch` (class in `galaxy.datatypes.genetics`), 54
- `after_setting_metadata()` (`galaxy.datatypes.data.Data`

- method), 50
- AliasPickleModule (class in galaxy.util.aliaspickler), 229
- AliasUnpickler (class in galaxy.util.aliaspickler), 230
- Alignment (class in galaxy.datatypes.sequence), 76
- all_eggs (galaxy.eggs.Crate attribute), 100
- all_missing (galaxy.eggs.Crate attribute), 100
- all_names (galaxy.eggs.Crate attribute), 100
- all_roles() (galaxy.model.User method), 148
- allow_action() (galaxy.security.GalaxyRBACAgent method), 176
- allow_action() (galaxy.security.HostAgent method), 179
- allow_action_on_libitems() (galaxy.security.GalaxyRBACAgent method), 176
- allow_datatype_change (galaxy.datatypes.assembly.Velvet attribute), 44
- allow_datatype_change (galaxy.datatypes.data.Data attribute), 50
- allow_datatype_change (galaxy.datatypes.genetics.RexpBase attribute), 56
- allow_datatype_change (galaxy.datatypes.genetics.Rgenetic attribute), 57
- allow_datatype_change (galaxy.datatypes.interval.BedStrict attribute), 64
- allow_datatype_change (galaxy.datatypes.ngsindex.BowtieIndex attribute), 74
- allow_user_access() (galaxy.tools.DataManagerTool method), 182
- allow_user_access() (galaxy.tools.Tool method), 184
- allowed() (galaxy.web.framework.helpers.grids.GridOperation method), 261
- always_conditional (galaxy.eggs.GalaxyConfig attribute), 101
- Amos (class in galaxy.datatypes.assembly), 43
- amount (galaxy.model.Quota attribute), 144
- annotate_async() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 314
- annotation_assoc (galaxy.managers.hdas.HDAManager attribute), 163
- annotation_assoc (galaxy.managers.histories.HistoryManager attribute), 164
- anon_user_api_value() (galaxy.webapps.galaxy.api.users.UserAPIController method), 38, 302
- anonymous (galaxy.managers.context.ProvidesUserContext attribute), 160
- api_key() (galaxy.webapps.galaxy.api.users.UserAPIController method), 38, 302
- api_keys() (galaxy.webapps.galaxy.controllers.user.User method), 338
- api_path (galaxy.jobs.deferred.pacific_biosciences_smrt_portal.SMRTPortal attribute), 123
- api_payload_to_create_params() (in module galaxy.managers.collections_util), 159
- ApiKeyManager (class in galaxy.managers.api_keys), 154
- APIKeys (class in galaxy.model), 128
- append() (galaxy.datatypes.metadata.MetadataSpecCollection method), 72
- append_quality() (galaxy_utils.sequence.sequence.SequencingRead method), 356
- append_sequence() (galaxy_utils.sequence.sequence.SequencingRead method), 356
- apply_action() (galaxy.tools.parameters.output.FormatToolOutputAction method), 214
- apply_action() (galaxy.tools.parameters.output.MetadataToolOutputAction method), 215
- apply_action() (galaxy.tools.parameters.output.ToolOutputAction method), 215
- apply_action() (galaxy.tools.parameters.output.ToolOutputActionCondition method), 216
- apply_action() (galaxy.tools.parameters.output.ToolOutputActionCondition method), 216
- apply_action() (galaxy.tools.parameters.output.ToolOutputActionGroup method), 216
- apply_galaxy_conventions() (galaxy_utils.sequence.fastq.fastqCSSangerRead method), 353
- apply_galaxy_conventions() (galaxy_utils.sequence.fastq.fastqSequencingRead method), 354
- apply_item_tag() (galaxy.managers.tags.TagManager method), 168
- apply_item_tags() (galaxy.managers.tags.TagManager method), 168
- apply_query_filter() (galaxy.web.framework.helpers.grids.Grid method), 259
- apply_query_filter() (galaxy.webapps.galaxy.controllers.admin.RoleListGroup method), 309
- apply_query_filter() (galaxy.webapps.galaxy.controllers.history.HistoryAllIP method), 319
- apply_query_filter() (galaxy.webapps.galaxy.controllers.history.HistoryList method), 322
- apply_query_filter() (galaxy.webapps.galaxy.controllers.history.SharedHistory method), 323
- apply_query_filter() (galaxy.webapps.galaxy.controllers.library.LibraryList method), 324
- apply_query_filter() (galaxy.webapps.galaxy.controllers.page.HistoryDatabase method), 327
- apply_query_filter() (galaxy.webapps.galaxy.controllers.page.HistorySelect method), 327
- apply_query_filter() (galaxy.webapps.galaxy.controllers.page.ItemSelection method), 328
- apply_query_filter() (galaxy.webapps.galaxy.controllers.page.PageAllPublic method), 328
- apply_query_filter() (galaxy.webapps.galaxy.controllers.page.PageListGroup method), 329
- apply_query_filter() (galaxy.webapps.galaxy.controllers.requests.UserRequest method), 332

- [apply_query_filter\(\)](#) (galaxy.webapps.galaxy.controllers.requests_controller.in.DataTransformer), 333
[archive_dir](#) (galaxy.eggs.scramble.ScrambleEgg attribute), 102
[archive_download\(\)](#) (galaxy.webapps.galaxy.api.histories.HistoriesController method), 15, 279
[archive_export\(\)](#) (galaxy.webapps.galaxy.api.histories.HistoriesController method), 15, 279
[as_display_type\(\)](#) (galaxy.datatypes.data.Data method), 50
[as_display_type\(\)](#) (galaxy.model.DatasetInstance method), 131
[as_gbrowse_display_file\(\)](#) (galaxy.datatypes.tabular.Tabular method), 88
[as_requirement\(\)](#) (pkg_resources.Distribution method), 363
[as_ucsc_display_file\(\)](#) (galaxy.datatypes.genetics.GenomeGraphs method), 55
[as_ucsc_display_file\(\)](#) (galaxy.datatypes.interval.Bed method), 63
[as_ucsc_display_file\(\)](#) (galaxy.datatypes.interval.BedGraph method), 64
[as_ucsc_display_file\(\)](#) (galaxy.datatypes.interval.Interval method), 68
[as_ucsc_display_file\(\)](#) (galaxy.datatypes.tabular.Tabular method), 88
[asbool\(\)](#) (in module galaxy.util), 225
[ascii_max](#) (galaxy_utils.sequence.fastq.fastqCSSangerRead attribute), 353
[ascii_max](#) (galaxy_utils.sequence.fastq.fastqIlluminaRead attribute), 354
[ascii_max](#) (galaxy_utils.sequence.fastq.fastqSangerRead attribute), 354
[ascii_max](#) (galaxy_utils.sequence.fastq.fastqSequencingRead attribute), 354
[ascii_max](#) (galaxy_utils.sequence.fastq.fastqSolexaRead attribute), 355
[ascii_min](#) (galaxy_utils.sequence.fastq.fastqCSSangerRead attribute), 353
[ascii_min](#) (galaxy_utils.sequence.fastq.fastqIlluminaRead attribute), 354
[ascii_min](#) (galaxy_utils.sequence.fastq.fastqSangerRead attribute), 354
[ascii_min](#) (galaxy_utils.sequence.fastq.fastqSequencingRead attribute), 354
[ascii_min](#) (galaxy_utils.sequence.fastq.fastqSolexaRead attribute), 355
[assert_sequence_quality_lengths\(\)](#) (galaxy_utils.sequence.fastq.fastqCSSangerRead method), 353
[assert_sequence_quality_lengths\(\)](#) (galaxy_utils.sequence.fastq.fastqSequencingRead method), 354
[associate_action_dataset_role\(\)](#) (galaxy.security.GalaxyRBACAgent method), 176
[associate_components\(\)](#) (galaxy.security.GalaxyRBACAgent method), 176
[associate_components\(\)](#) (galaxy.security.RBACAgent method), 179
[associate_group_role\(\)](#) (galaxy.security.GalaxyRBACAgent method), 176
[associate_user_group\(\)](#) (galaxy.security.GalaxyRBACAgent method), 176
[associate_user_role\(\)](#) (galaxy.security.GalaxyRBACAgent method), 176
[ASync](#) (class in galaxy.webapps.galaxy.controllers.async), 314
[attrs_template](#) (galaxy.web.framework.helpers.grid.Grid attribute), 259
[AsyncDataSourceTool](#) (class in galaxy.tools), 182
[AsynchronousJobRunner](#) (class in galaxy.jobs.runners), 123
[AsynchronousJobState](#) (class in galaxy.jobs.runners), 124
[AttributeValueSplitterFilter](#) (class in galaxy.tools.parameters.dynamic_options), 209
[AuthenticationController](#) (class in galaxy.webapps.galaxy.api.authenticate), 8, 273
[AuthenticationFailed](#), 103
[AuthenticationRequired](#), 103
[AvailableDistributions](#) (in module pkg_resources), 369
[Axt](#) (class in galaxy.datatypes.sequence), 77
- ## B
- [BadValue](#) (class in galaxy.tools), 182
[Bam](#) (class in galaxy.datatypes.binary), 44
[Base](#) (class in galaxy.util.inflection), 231
[base](#) (galaxy.web.framework.base.Request attribute), 254
[base](#) (galaxy_utils.sequence.transform.ColorSpaceConverter attribute), 356
[base_dataprovider\(\)](#) (galaxy.datatypes.data.Data method), 50
[Base_Parser](#) (class in galaxy.visualization.data_providers.phyloviz.basepars), 239
[base_to_color_dict](#) (galaxy_utils.sequence.transform.ColorSpaceConverter attribute), 356
[BaseAnnotationsController](#) (class in galaxy.webapps.galaxy.api.annotations), 7, 272
[BaseAPIController](#) (class in galaxy.web.base.controller), 246
[BaseCitation](#) (class in galaxy.managers.citations), 158
[BaseController](#) (class in galaxy.web.base.controller), 247

BaseDataProvider (class in galaxy.visualization.data_providers.basic), 238	in 214	BooleanToolParameter (class in galaxy.tools.parameters.basic), 197	in
BaseDataToolParameter (class in galaxy.tools.parameters.basic), 197	in	BowtieBaseIndex (class in galaxy.datatypes.ngsindex), 73	
BaseExtendedMetadataController (class in galaxy.webapps.galaxy.api.extended_metadata), 10, 275	in	BowtieColorIndex (class in galaxy.datatypes.ngsindex), 73	
BaseField (class in galaxy.web.form_builder), 241		BowtieIndex (class in galaxy.datatypes.ngsindex), 74	
BaseItemTagsController (class in galaxy.webapps.galaxy.api.item_tags), 284	in 20,	branch_deleted() (in module galaxy.webapps.galaxy.controllers.library_common), 326	
BaseJobMetric (class in galaxy.model), 128		browse_external_services() (galaxy.webapps.galaxy.controllers.external_service.ExternalService method), 317	
BaseJobRunner (class in galaxy.jobs.runners), 124		browse_form_definitions() (galaxy.webapps.galaxy.controllers.forms.Forms method), 318	
BaseParamParser (class in galaxy.web.params), 246		browse_libraries() (galaxy.webapps.galaxy.controllers.library.Library method), 323	
BaseProvenanceController (class in galaxy.webapps.galaxy.api.provenance), 32, 297	in	browse_libraries() (galaxy.webapps.galaxy.controllers.library_admin.LibraryAdmin method), 324	
basestring() (galaxy.managers.base.ModelValidator method), 157		browse_library() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 325	
basestring_list() (galaxy.managers.base.ModelValidator method), 157		browse_repositories() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 312	
BaseUIController (class in galaxy.web.base.controller), 247		browse_repository() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 312	
BaseURLToolParameter (class in galaxy.tools.parameters.basic), 197	in	browse_request_types() (galaxy.webapps.galaxy.controllers.request_type.RequestType method), 330	
Bcf (class in galaxy.datatypes.binary), 45		browse_requests() (galaxy.webapps.galaxy.controllers.requests.Requests method), 332	
Bed (class in galaxy.datatypes.interval), 63		browse_requests() (galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin method), 333	
Bed12 (class in galaxy.datatypes.interval), 64		browse_tool_dependency() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 312	
Bed6 (class in galaxy.datatypes.interval), 64		browse_tool_shed() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 312	
BedGraph (class in galaxy.datatypes.interval), 64		browse_tool_sheds() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 312	
BedStrict (class in galaxy.datatypes.interval), 64		browser_url (galaxy.web.framework.base.Request attribute), 255	
before_setting_metadata() (galaxy.datatypes.data.Data method), 50		bucket_proxy() (galaxy.webapps.galaxy.controllers.root.RootController method), 336	
begin() (galaxy.model.orm.logging_connection_proxy.LoggingProxy method), 153		build() (galaxy.tools.parameters.basic.ToolParameter method), 207	
best_match() (in module mimeparse), 358		build_command_line() (galaxy.jobs.runners.BaseJobRunner method), 124	
best_match() (pkg_resources.Environment method), 359		build_dependency_manager() (in module galaxy.tools.deps), 195	
BIBTEX_UNSET (galaxy.managers.citations.DoiCitation attribute), 158		build_dependency_shell_commands() (galaxy.tools.Tool method), 184	
BibtexCitation (class in galaxy.managers.citations), 158		build_dir (galaxy.eggs.scramble.ScrambleEgg attribute), 102	
BigBed (class in galaxy.datatypes.binary), 45		build_form_definition_field_widgets()	
BigWig (class in galaxy.datatypes.binary), 45			
Binary (class in galaxy.datatypes.binary), 46			
biomart() (galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner class method), 338			
Bmp (class in galaxy.datatypes.images), 59			
bool() (galaxy.managers.base.ModelValidator method), 157			
BooleanColumn (class in galaxy.web.framework.helpers.grids), 257	in		
BooleanExternalServiceActionsGroupWhen (class in galaxy.external_services.service), 108	in		
BooleanFilter (class in galaxy.tools.parameters.output),			

(galaxy.webapps.galaxy.controllers.forms.Forms method), 107
 method), 318
 build_form_id_select_field() (galaxy.web.base.controller.UsesFormDefinitionsMixin method), 249
 build_index() (galaxy.tools.search.ToolBoxSearch method), 222
 build_initial_query() (galaxy.web.framework.helpers.grids.Grid method), 259
 build_initial_query() (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid method), 310
 build_initial_query() (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAssociationListGrid method), 316
 build_initial_query() (galaxy.webapps.galaxy.controllers.forms.FormsGrid method), 319
 build_initial_query() (galaxy.webapps.galaxy.controllers.history.Galaxy.HistoryAllPublishedGrid method), 319
 build_initial_query() (galaxy.webapps.galaxy.controllers.history.SharedHistoryListGrid method), 323
 build_initial_query() (galaxy.webapps.galaxy.controllers.library.LibraryListGrid method), 324
 build_initial_query() (galaxy.webapps.galaxy.controllers.page.PageAllPublishedGrid method), 328
 build_initial_query() (galaxy.webapps.galaxy.controllers.user.UserOpenIDGrid method), 340
 build_initial_query() (galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGrid method), 343
 build_initial_query() (galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDateListGrid method), 344
 build_initial_query() (galaxy.webapps.reports.controllers.workflows.SpecifiedDateListGrid method), 346
 build_invocations_query() (galaxy.managers.workflows.WorkflowsManager method), 169
 build_maf_index() (in module galaxy.tools.util.maf_utilities), 223
 build_maf_index_species_chromosomes() (in module galaxy.tools.util.maf_utilities), 223
 build_module() (galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController method), 39, 303
 build_object_store_from_config() (in module galaxy.objectstore), 172
 build_parameter_dict() (galaxy.datatypes.display_applications.application.DisplayApplicationLink method), 96
 build_path() (galaxy.webapps.galaxy.api.folder_contents.FolderContentsController method), 10, 275
 build_redirect_url_params() (galaxy.tools.Tool method), 184
 build_rename_datasets_for_sample_select_field() (in module galaxy.webapps.galaxy.controllers.requests.admin), 334
 build_select_field() (in module galaxy.web.form_builder), 246
 build_template() (galaxy.external_services.actions.Template method), 107
 build_url() (galaxy.datatypes.display_applications.parameters.DisplayApplicationLink method), 97
 build_workflow_from_dict() (galaxy.managers.workflows.WorkflowContentsManager method), 168
 bulk_operations (galaxy.model.Sample attribute), 145
 bunch (class in galaxy.util.bunch), 230
 by_id() (galaxy.managers.base.ModelManager method), 156
 by_ids() (galaxy.managers.base.ModelManager method), 156
 by_user() (galaxy.managers.histories.HistoryManager method), 164
 cache_job_destination() (galaxy.jobs.mapper.JobRunnerMapper method), 164
 CacheableStaticURLParser (class in galaxy.web.framework.middleware.static), 265
 cachingObjectStore (class in galaxy.objectstore), 169
 calculate_disk_usage() (galaxy.model.User method), 148
 camel_case() (galaxy.tools.Tool method), 184
 camelize() (galaxy.util.inflection.Base method), 231
 camelized() (galaxy.util.inflection.Inflector method), 232
 can_access_dataset() (galaxy.security.GalaxyRBACAgent method), 176
 can_access_dataset() (galaxy.security.RBACAgent method), 176
 can_access_library() (galaxy.security.GalaxyRBACAgent method), 176
 can_access_library() (galaxy.security.RBACAgent method), 179
 can_access_library_item() (galaxy.security.GalaxyRBACAgent method), 176
 can_access_request_type() (galaxy.security.GalaxyRBACAgent method), 176
 can_add() (pkg_resources.Environment method), 360
 can_add_item() (galaxy.managers.folders.FolderManager method), 176
 can_add_library_item() (galaxy.security.GalaxyRBACAgent method), 176
 can_add_library_item() (galaxy.security.RBACAgent method), 180
 can_convert_to() (galaxy.model.DatasetInstance method), 131
 can_current_user_add_to_library_item() (galaxy.web.base.controller.UsesLibraryMixinItems method), 249
 can_manage_dataset() (galaxy.security.GalaxyRBACAgent method), 176

[can_manage_dataset\(\)](#) (galaxy.security.RBACAgent method), 180
[can_manage_library_item\(\)](#) (galaxy.security.GalaxyRBACAgent method), 176
[can_manage_library_item\(\)](#) (galaxy.security.RBACAgent method), 180
[can_modify_library_item\(\)](#) (galaxy.security.GalaxyRBACAgent method), 176
[can_modify_library_item\(\)](#) (galaxy.security.RBACAgent method), 180
[can_split\(\)](#) (galaxy.jobs.JobWrapper method), 114
[can_split\(\)](#) (galaxy.jobs.TaskWrapper method), 117
[CANCEL](#) (galaxy.web.framework.openid_manager.OpenIDManager attribute), 256
[cancel\(\)](#) (galaxy.model.WorkflowInvocation method), 150
[cancel_invocation\(\)](#) (galaxy.managers.workflows.WorkflowsManager method), 169
[cancel_invocation\(\)](#) (galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController method), 39, 303
[CancelWorkflowEvaluation](#), 347
[CaseSensitiveConfigParser](#) (class in galaxy.eggs), 100
[center\(\)](#) (galaxy.web.base.controllers.admin.Admin method), 251
[change_adapter\(\)](#) (galaxy_utils.sequence.fastq.fastqCSSanger method), 353
[change_datatype\(\)](#) (galaxy.datatypes.registry.Registry method), 75
[change_datatype\(\)](#) (galaxy.model.DatasetInstance method), 131
[change_ownership_for_run\(\)](#) (galaxy.jobs.JobWrapper method), 114
[change_password\(\)](#) (galaxy.webapps.galaxy.controllers.user.User method), 338
[change_state\(\)](#) (galaxy.jobs.JobWrapper method), 114
[change_state\(\)](#) (galaxy.jobs.TaskWrapper method), 117
[ChangeDatatypeAction](#) (class in galaxy.jobs.actions.post), 120
[check\(\)](#) (galaxy.config.Configuration method), 42
[check\(\)](#) (galaxy.webapps.reports.config.Configuration method), 341
[check_accessible\(\)](#) (galaxy.managers.folders.FolderManager method), 160
[check_accessible\(\)](#) (galaxy.managers.libraries.LibraryManager method), 166
[check_and_reload\(\)](#) (galaxy.visualization.genomes.Genomes method), 237
[check_and_update_param_values\(\)](#) (galaxy.tools.Tool method), 184
[check_and_update_param_values_helper\(\)](#) (galaxy.tools.Tool method), 184
[check_and_update_state\(\)](#) (galaxy.workflow.modules.ToolModule method), 349
[check_and_update_state\(\)](#) (galaxy.workflow.modules.WorkflowModule method), 350
[check_binary\(\)](#) (in module galaxy.datatypes.checkers), 49
[check_bz2\(\)](#) (in module galaxy.datatypes.checkers), 49
[check_conditional\(\)](#) (galaxy.eggs.GalaxyConfig method), 101
[check_folder_contents\(\)](#) (galaxy.security.GalaxyRBACAgent method), 176
[check_for_tool_dependencies\(\)](#) (galaxy.webapps.galaxy.controllers.admin.AdminGalaxy method), 306
[check_for_updates\(\)](#) (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 306
[check_gzip\(\)](#) (in module galaxy.datatypes.checkers), 49
[check_html\(\)](#) (in module galaxy.datatypes.checkers), 49
[check_job_output_datasets_deleted\(\)](#) (galaxy.model.Job method), 138
[check_image_type\(\)](#) (in module galaxy.datatypes.checkers), 49
[check_image_type\(\)](#) (in module galaxy.datatypes.util.image_util), 100
[check_interval](#) (galaxy.jobs.deferred.data_transfer.DataTransfer attribute), 123
[check_interval](#) (galaxy.model.DeferredJob attribute), 133
[check_job\(\)](#) (galaxy.jobs.deferred.data_transfer.DataTransfer method), 123
[check_job\(\)](#) (galaxy.jobs.deferred.manual_data_transfer.ManualDataTransfer method), 123
[check_job\(\)](#) (galaxy.jobs.deferred.pacific_biosciences_smrt_portal.SMRTPortal method), 123
[check_limits\(\)](#) (galaxy.jobs.JobWrapper method), 114
[check_limits\(\)](#) (galaxy.jobs.runners.AsynchronousJobState method), 124
[check_manageable\(\)](#) (galaxy.managers.folders.FolderManager method), 161
[check_newlines\(\)](#) (in module galaxy.datatypes.sniff), 82
[check_param\(\)](#) (in module galaxy.tools.parameters), 196
[check_param_from_incoming\(\)](#) (in module galaxy.tools), 189
[check_password\(\)](#) (galaxy.model.User method), 148
[check_pid\(\)](#) (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
[check_security\(\)](#) (galaxy.managers.workflows.WorkflowsManager method), 169
[check_tool_output\(\)](#) (galaxy.jobs.JobWrapper method), 114
[check_user_can_add_to_library_item\(\)](#) (galaxy.web.base.controller.UsesLibraryMixinItems method), 249
[check_version_conflict\(\)](#) (pkg_resources.Distribution method), 363
[check_watched_item\(\)](#) (galaxy.jobs.runners.AsynchronousJobRunner method), 123

check_watched_item() (galaxy.jobs.runners.lwr.LwrJobRunner method), 241
 check_watched_items() (galaxy.jobs.runners.AsynchronousJobRunner method), 123
 check_watched_items() (galaxy.jobs.runners.cli.ShellJobRunner method), 125
 check_watched_items() (galaxy.jobs.runners.condor.CondorJobRunner method), 126
 check_watched_items() (galaxy.jobs.runners.drmaa.DRMAAJobRunner method), 126
 check_workflow_compatible() (galaxy.tools.Tool method), 184
 check_zip() (in module galaxy.datatypes.checkers), 49
 CheckboxField (class in galaxy.web.form_builder), 241
 checkComments() (galaxy.visualization.data_providers.phyloviz.nexusparser.NexusParser method), 240
 chop_block_by_region() (in module galaxy.tools.util.maf_utilities), 223
 ChromatinInteractions (class in galaxy.datatypes.interval), 64
 ChromInfo (class in galaxy.datatypes.chrominfo), 49
 chroms() (galaxy.visualization.genomes.Genomes method), 237
 chunk64_dataprovider() (galaxy.datatypes.data.Data method), 50
 chunk_dataprovider() (galaxy.datatypes.data.Data method), 50
 CHUNKABLE (galaxy.datatypes.data.Data attribute), 50
 CHUNKABLE (galaxy.datatypes.tabular.TabularData attribute), 88
 CisML (class in galaxy.datatypes.xml), 90
 CitationCollection (class in galaxy.managers.citations), 158
 citations() (galaxy.webapps.galaxy.api.histories.HistoriesController method), 15, 280
 citations() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320
 citations_for_tool() (galaxy.managers.citations.CitationsManager method), 158
 citations_for_tool_ids() (galaxy.managers.citations.CitationsManager method), 158
 CitationsManager (class in galaxy.managers.citations), 158
 class_type (in module galaxy.external_services.service), 109
 classify() (galaxy.util.inflection.Base method), 231
 classify() (galaxy.util.inflection.Inflector method), 232
 clean_base_dir() (galaxy.tools.data.TabularToolDataField method), 192
 clean_field_contents() (galaxy.web.base.controller.UsesFormController method), 249
 cleanNewickString() (galaxy.visualization.data_providers.phyloviz.nexusparser.NexusParser method), 240
 cleanTag() (galaxy.visualization.data_providers.phyloviz.phyloxmlparser.PhyloxmlParser method), 240
 cleanup() (galaxy.jobs.JobWrapper method), 114
 cleanup() (galaxy.jobs.runners.AsynchronousJobState method), 124
 cleanup() (galaxy.jobs.TaskWrapper method), 117
 cleanup_after_job() (galaxy.tools.imp_exp.JobExportHistoryArchiveWrapper method), 195
 cleanup_after_job() (galaxy.tools.imp_exp.JobImportHistoryArchiveWrapper method), 196
 cleanup_before_exit() (in module galaxy.datatypes.converters.sam_to_bam), 95
 cleanup_external_metadata() (galaxy.datatypes.metadata.JobExternalOutputMetadataWrapper method), 71
 cleanup_from_JSON_dict_filename() (galaxy.datatypes.metadata.MetadataTempFile class method), 73
 cleanup_resources() (pkg_resources.ResourceManager method), 361
 cleanup_unused_precreated_datasets() (in module galaxy.tools.actions.upload_common), 191
 clear() (galaxy.model.ImplicitlyConvertedDatasetAssociation method), 137
 clear() (galaxy.util.lrucache.LRUCache method), 235
 clear() (galaxy.util.odict.odict method), 235
 clear_associated_files() (galaxy.model.DatasetInstance method), 131
 clear_associated_files() (galaxy.model.HistoryDatasetAssociation method), 136
 clear_associated_files() (galaxy.model.LibraryDatasetDatasetAssociation method), 142
 clear_display_apps() (galaxy.datatypes.data.Data method), 50
 clear_history() (galaxy.webapps.galaxy.controllers.root.RootController method), 336
 clear_working_directory() (galaxy.jobs.JobWrapper method), 114
 clone() (galaxy_utils.sequence.sequence.SequencingRead method), 363
 clone() (pkg_resources.Distribution method), 363
 close() (galaxy.datatypes.converters.interval_to_coverage.CoverageWriter method), 93
 close() (galaxy.tools.util.maf_utilities.TempFileHandler method), 223
 close() (galaxy_utils.sequence.fasta.fastaNamedReader method), 352
 close() (galaxy_utils.sequence.fasta.fastaReader method), 352
 close() (galaxy_utils.sequence.fasta.fastaWriter method), 352
 close() (galaxy.parsers.NewickFastaFakeFastaScoreReader method), 353
 close() (galaxy.parsers.NewickFastaFakeFastaScoreReader method), 353
 close() (galaxy.parsers.fastq.fastqNamedReader method), 353

method), 354

close() (galaxy_utils.sequence.fastq.fastqReader method), 354

close() (galaxy_utils.sequence.fastq.fastqWriter method), 356

cls (in module galaxy.tools.data), 194

col (galaxy.webapps.galaxy.controllers.requests_admin.AdminRequestsGrid attribute), 332

collect_child_datasets() (galaxy.tools.Tool method), 184

collect_dynamic_collections() (galaxy.tools.Tool method), 184

collect_input_dataset_collections() (galaxy.tools.actions.DefaultToolAction method), 190

collect_input_datasets() (galaxy.tools.actions.DefaultToolAction method), 190

collect_primary_datasets() (galaxy.tools.Tool method), 184

collection_type (galaxy.tools.parameters.basic.DataCollectionToolParameter attribute), 199

collection_type (galaxy.workflow.modules.InputDataCollectionModule attribute), 347

color_dict (galaxy_utils.sequence.transform.ColorSpaceConverter attribute), 356

color_space_converter (galaxy_utils.sequence.sequence.SequencingRead attribute), 356

color_to_base_dict (galaxy_utils.sequence.transform.ColorSpaceConverter attribute), 356

ColorSpaceConverter (class in galaxy_utils.sequence.transform), 356

ColorToolParameter (class in galaxy.tools.parameters.basic), 198

column_dataprovider() (galaxy.datatypes.binary.Bam method), 44

column_dataprovider() (galaxy.datatypes.tabular.Sam method), 87

column_dataprovider() (galaxy.datatypes.tabular.TabularData method), 89

column_names (galaxy.datatypes.interval.ChromatinInteractions attribute), 64

column_names (galaxy.datatypes.interval.ENCODEPeak attribute), 65

column_names (galaxy.datatypes.interval.Gff attribute), 66

column_names (galaxy.datatypes.interval.Gff3 attribute), 66

column_names (galaxy.datatypes.interval.Gtf attribute), 67

column_names (galaxy.datatypes.tabular.Vcf attribute), 89

column_spec_to_index() (galaxy.tools.parameters.dynamic_options.DynamicOptions method), 209

ColumnDataProvider (class in galaxy.visualization.data_providers.basic), 238

ColumnListParameter (class in galaxy.tools.parameters.basic), 198

ColumnParameter (class in galaxy.datatypes.metadata), 70

ColumnReplaceFilter (class in galaxy.tools.parameters.output), 214

columns (galaxy.web.framework.helpers.grids.Grid attribute), 259

columns (galaxy.webapps.galaxy.controllers.admin.GroupListGrid attribute), 307

columns (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid attribute), 308

columns (galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute), 309

columns (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 310

columns (galaxy.webapps.galaxy.controllers.admin.UserListGrid attribute), 312

columns (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAssociation attribute), 316

columns (galaxy.webapps.galaxy.controllers.external_service.ExternalService attribute), 317

columns (galaxy.webapps.galaxy.controllers.forms.FormsGrid attribute), 319

columns (galaxy.webapps.galaxy.controllers.history.HistoryAllPublishedGrid attribute), 320

columns (galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute), 322

columns (galaxy.webapps.galaxy.controllers.history.SharedHistoryListGrid attribute), 323

columns (galaxy.webapps.galaxy.controllers.library.LibraryListGrid attribute), 324

columns (galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid attribute), 325

columns (galaxy.webapps.galaxy.controllers.page.HistoryDatasetAssociation attribute), 327

columns (galaxy.webapps.galaxy.controllers.page.HistorySelectionGrid attribute), 327

columns (galaxy.webapps.galaxy.controllers.page.PageAllPublishedGrid attribute), 328

columns (galaxy.webapps.galaxy.controllers.page.PageListGrid attribute), 329

columns (galaxy.webapps.galaxy.controllers.page.PageSelectionGrid attribute), 330

columns (galaxy.webapps.galaxy.controllers.page.VisualizationSelectionGrid attribute), 330

columns (galaxy.webapps.galaxy.controllers.page.WorkflowSelectionGrid attribute), 330

columns (galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid attribute), 330

columns (galaxy.webapps.galaxy.controllers.requests_admin.AdminRequestsGrid attribute), 332

columns (galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid attribute), 332

- attribute), 333
- columns (galaxy.webapps.galaxy.controllers.requests_common.RequestsGridlaps_region() (in module galaxy.tools.util.maf_utilities), 223
- attribute), 335
- columns (galaxy.webapps.galaxy.controllers.user.UserOpenIDGridElements_are_associated() (galaxy.security.RBACAgent method), 180
- attribute), 340
- columns (galaxy.webapps.reports.controllers.jobs.SpecifiedDataListGridFiles (galaxy.datatypes.data.Data attribute), 50
- attribute), 343
- columns (galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDataListGridFiles (galaxy.datatypes.data.Data attribute), 50
- attribute), 344
- columns (galaxy.webapps.reports.controllers.workflows.SpecifiedDataListGridFiles (galaxy.datatypes.genetics.RexpBase attribute), 57
- attribute), 346
- ColumnSetAction (class in galaxy.jobs.actions.post), 120
- ColumnStripFilter (class in galaxy.tools.parameters.output), 214
- ColumnTypesParameter (class in galaxy.datatypes.metadata), 70
- combine() (galaxy_utils.sequence.fastq.fastqCombiner method), 353
- commaify() (in module galaxy.util), 225
- commands_in_new_shell (galaxy.jobs.JobWrapper attribute), 114
- commit() (galaxy.model.orm.logging_connection_proxy.LoggingProxy outputs() (galaxy.jobs.JobWrapper method), 114
- method), 153
- CommunityRatingColumn (class in galaxy.web.framework.helpers.grids), 258
- CommunityTagManager (class in galaxy.managers.tags), 167
- CommunityTagsColumn (class in galaxy.web.framework.helpers.grids), 258
- compare_endswith() (in module galaxy.tools.parameters.output), 217
- compare_eq() (in module galaxy.tools.parameters.output), 217
- compare_gt() (in module galaxy.tools.parameters.output), 217
- compare_gte() (in module galaxy.tools.parameters.output), 217
- compare_in() (in module galaxy.tools.parameters.output), 217
- compare_lt() (in module galaxy.tools.parameters.output), 217
- compare_lte() (in module galaxy.tools.parameters.output), 217
- compare_neq() (in module galaxy.tools.parameters.output), 217
- compare_re_search() (in module galaxy.tools.parameters.output), 217
- compare_startswith() (in module galaxy.tools.parameters.output), 217
- compare_urls() (in module galaxy.util), 226
- compatible_platforms() (in module pkg_resources), 365
- complement() (galaxy_utils.sequence.fastq.fastqCSSangerRead method), 353
- complement() (galaxy_utils.sequence.sequence.SequencingRead method), 356
- compute_runtime_state() (galaxy.workflow.modules.SimpleWorkflowModule method), 348
- compute_runtime_state() (galaxy.workflow.modules.ToolModule method), 349
- compute_runtime_state() (galaxy.workflow.modules.WorkflowModule method), 350
- ComputeEnvironment (class in galaxy.jobs), 112
- cond_plural() (galaxy.util.inflection.Base method), 231
- cond_plural() (galaxy.util.inflection.Inflector method), 232
- Conditional (class in galaxy.tools.parameters.grouping), 211
- ConditionalWhen (class in galaxy.tools.parameters.grouping), 211
- CondorJobRunner (class in galaxy.jobs.runners.condor), 126
- config_directory() (galaxy.jobs.ComputeEnvironment method), 112
- config_directory() (galaxy.jobs.SimpleComputeEnvironment method), 116
- config_eggs (galaxy.eggs.Crate attribute), 100
- config_exception() (in module galaxy.jobs), 117
- config_file (galaxy.eggs.Crate attribute), 100
- config_missing (galaxy.eggs.Crate attribute), 100
- config_names (galaxy.eggs.Crate attribute), 100
- ConfigDoesNotAllowException, 103
- Configuration (class in galaxy.config), 42
- Configuration (class in galaxy.webapps.reports.config),

- 341
- ConfigurationController (class in galaxy.webapps.galaxy.api.configuration), 8, 273
- ConfigurationError, 75, 103, 341
- configure_and_load() (galaxy.tools.data.TabularToolDataTable method), 193
- configure_logging() (in module galaxy.config), 42
- configure_logging() (in module galaxy.webapps.reports.config), 341
- ConfiguresGalaxyMixin (class in galaxy.config), 42
- Conflict, 103
- consume_read() (galaxy_utils.sequence.fastq.fastqAggregator method), 352
- content (galaxy.external_services.actions.ExternalServiceResult attribute), 106
- content (galaxy.external_services.actions.ExternalServiceValueResult attribute), 106
- content (galaxy.external_services.actions.ExternalServiceWebAPIActionResult attribute), 107
- contents_iter() (galaxy.model.History method), 135
- controller_name (galaxy.webapps.galaxy.api.annotations.HistoryAnnotationController attribute), 8, 273
- controller_name (galaxy.webapps.galaxy.api.annotations.HistoryContentController attribute), 8, 273
- controller_name (galaxy.webapps.galaxy.api.annotations.WorkflowAnnotationController attribute), 8, 273
- controller_name (galaxy.webapps.galaxy.api.extended_metadata.HistoryDatasetExtendMetadataController attribute), 10, 275
- controller_name (galaxy.webapps.galaxy.api.extended_metadata.LibraryDatasetExtendMetadataController attribute), 10, 275
- controller_name (galaxy.webapps.galaxy.api.item_tags.HistoryContentTagsController attribute), 20, 285
- controller_name (galaxy.webapps.galaxy.api.item_tags.HistoryTagsController attribute), 20, 285
- controller_name (galaxy.webapps.galaxy.api.item_tags.WorkflowTagsController attribute), 20, 285
- controller_name (galaxy.webapps.galaxy.api.provenance.HDAProvenanceController attribute), 32, 297
- controller_name (galaxy.webapps.galaxy.api.provenance.LDDAProvenanceController attribute), 33, 297
- ControllerUnavailable, 247
- conversion_messages (galaxy.model.Dataset attribute), 129
- conversion_messages (galaxy.model.DatasetInstance attribute), 131
- convert_base_to_color_space() (galaxy_utils.sequence.fastq.fastqSequencingRead class method), 355
- convert_bed_coords_to_gff() (in module galaxy.datatypes.util.gff_util), 99
- convert_bytes() (in module galaxy.objectstore), 172
- convert_color_to_base_space() (galaxy_utils.sequence.fastq.fastqSequencingRead class method), 355
- convert_dataset() (galaxy.datatypes.data.Data method), 50
- convert_dataset() (galaxy.model.DatasetInstance method), 131
- convert_gff_coords_to_bed() (in module galaxy.datatypes.util.gff_util), 99
- convert_legacy_destinations() (galaxy.jobs.JobConfiguration method), 113
- convert_newlines() (in module galaxy.datatypes.sniff), 82
- convert_newlines_sep2tabs() (in module galaxy.datatypes.sniff), 83
- convert_permitted_action_strings() (galaxy.security.RBACAgent method), 180
- convert_read_to_format() (galaxy_utils.sequence.fastq.fastqSequencingRead class method), 355
- convert_score_phred_to_solexa() (galaxy_utils.sequence.fastq.fastqSequencingRead class method), 355
- convert_score_solexa_to_phred() (galaxy_utils.sequence.fastq.fastqSequencingRead class method), 355
- copy() (galaxy.managers.base.ModelManager method), 164
- copy() (galaxy.managers.collections.DatasetCollectionManager method), 129
- copy() (galaxy.model.DatasetCollection method), 129
- copy() (galaxy.model.History method), 135
- copy() (galaxy.model.HistoryDatasetAssociation method), 136
- copy() (galaxy.model.HistoryDatasetCollectionAssociation method), 137
- copy() (galaxy.model.ItemTagAssociation method), 138
- copy() (galaxy.model.LibraryDatasetDatasetAssociation method), 142
- copy() (galaxy.model.Visualization method), 149
- copy() (galaxy.model.VisualizationRevision method), 149

copy() (galaxy.tools.DefaultToolState method), 183
 copy() (galaxy.util.odict.odict method), 235
 copy() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320
 copy_build_script() (galaxy.eggs.scramble.ScrambleEgg method), 102
 copy_dataset_permissions() (galaxy.security.GalaxyRBACAgent method), 176
 copy_datasets() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315
 copy_hda_to_library_folder() (galaxy.web.base.controller.UsesLibraryMixinItems method), 249
 copy_item_annotation() (galaxy.model.item_attr.UsesAnnotation method), 152
 copy_ldda() (galaxy.managers.hdas.HDAManager method), 163
 copy_library_permissions() (galaxy.security.GalaxyRBACAgent method), 176
 copy_safe_peek (galaxy.datatypes.data.Data attribute), 50
 copy_safe_peek (galaxy.datatypes.images.Gmaji attribute), 59
 copy_safe_peek (galaxy.datatypes.images.Laji attribute), 61
 copy_tags_from() (galaxy.model.History method), 135
 copy_tags_from() (galaxy.model.StoredWorkflow method), 146
 copy_to_collection() (galaxy.model.DatasetCollectionElement method), 130
 count_data_lines() (galaxy.datatypes.data.Text method), 53
 CoverageWriter (class in galaxy.datatypes.converters.interval_to_coverage), 93
 Crate (class in galaxy.eggs), 100
 create() (galaxy.managers.base.ModelManager method), 156
 create() (galaxy.managers.collections.DatasetCollectionManager method), 159
 create() (galaxy.managers.folders.FolderManager method), 161
 create() (galaxy.managers.hdas.HDAManager method), 163
 create() (galaxy.managers.libraries.LibraryManager method), 166
 create() (galaxy.objectstore.DiskObjectStore method), 169
 create() (galaxy.objectstore.DistributedObjectStore method), 170
 create() (galaxy.objectstore.HierarchicalObjectStore method), 170
 create() (galaxy.objectstore.NestedObjectStore method), 170
 create() (galaxy.objectstore.ObjectStore method), 170
 create() (galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController method), 7, 272
 create() (galaxy.webapps.galaxy.api.dataset_collections.DatasetCollectionsController method), 9, 274
 create() (galaxy.webapps.galaxy.api.extended_metadata.BaseExtendedMetadataController method), 10, 275
 create() (galaxy.webapps.galaxy.api.folder_contents.FolderContentsController method), 10, 275
 create() (galaxy.webapps.galaxy.api.folders.FoldersController method), 11, 276
 create() (galaxy.webapps.galaxy.api.forms.FormDefinitionApiController method), 13, 278
 create() (galaxy.webapps.galaxy.api.groups.GroupApiController method), 14, 279
 create() (galaxy.webapps.galaxy.api.histories.HistoriesController method), 15, 280
 create() (galaxy.webapps.galaxy.api.history_contents.HistoryContentsController method), 17, 282
 create() (galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController method), 20, 284
 create() (galaxy.webapps.galaxy.api.job_files.JobFilesApiController method), 20, 285
 create() (galaxy.webapps.galaxy.api.jobs.JobController method), 21, 286
 create() (galaxy.webapps.galaxy.api.libraries.LibrariesController method), 25, 290
 create() (galaxy.webapps.galaxy.api.library_contents.LibraryContentsController method), 28, 293
 create() (galaxy.webapps.galaxy.api.metrics.MetricsController method), 30, 295
 create() (galaxy.webapps.galaxy.api.page_revisions.PageRevisionsController method), 31, 295
 create() (galaxy.webapps.galaxy.api.pages.PagesController method), 31, 296
 create() (galaxy.webapps.galaxy.api.provenance.BaseProvenanceController method), 32, 297
 create() (galaxy.webapps.galaxy.api.quotas.QuotaApiController method), 33, 297
 create() (galaxy.webapps.galaxy.api.request_types.RequestTypeApiController method), 33, 297
 create() (galaxy.webapps.galaxy.api.roles.RoleApiController method), 34, 298
 create() (galaxy.webapps.galaxy.api.users.UserApiController method), 38, 302
 create() (galaxy.webapps.galaxy.api.visualizations.VisualizationsController method), 38, 302
 create() (galaxy.webapps.galaxy.api.workflows.WorkflowsApiController method), 39, 303
 create() (galaxy.webapps.galaxy.controllers.page.PageController method), 328
 create() (galaxy.webapps.galaxy.controllers.user.User method), 338

create_api_key() (galaxy.managers.api_keys.ApiKeyManager method), 154
 create_api_key() (galaxy.web.base.controller.CreatesApiKeysMixin method), 247
 create_applet_tag_peek() (in module galaxy.datatypes.images), 63
 create_archive() (in module galaxy.tools.imp_exp.export_history), 196
 create_dataset_collection() (galaxy.managers.collections.DatasetCollectionManager method), 159
 create_display() (galaxy.webapps.galaxy.controllers.ucsc_protein_browser.create_ucsc_protein_browser_directory() (galaxy.jobs.JobWrapper method), 114
 create_extended_metadata() (galaxy.web.base.controller.UsesExtendedMetadataMixin method), 248
 create_external_service() (galaxy.webapps.galaxy.controllers.external_services.ExternalServiceMixin method), 317
 create_folder() (galaxy.webapps.galaxy.controllers.library_creation.LibraryCreationMixin method), 325
 create_form_definition() (galaxy.webapps.galaxy.controllers.forms.FormMixin method), 318
 create_group() (galaxy.web.base.controllers.admin.Admin method), 251
 create_item_slug() (galaxy.web.base.controller.SharableMixin method), 248
 create_job() (galaxy.jobs.deferred.data_transfer.DataTransfer method), 123
 create_job() (galaxy.jobs.deferred.manual_data_transfer.ManualDataTransfer method), 123
 create_job() (galaxy.jobs.deferred.pacific_biosciences_smrt_portal.SMRTPortal method), 123
 create_job() (in module galaxy.tools.actions.upload_common), 191
 create_library() (galaxy.webapps.galaxy.controllers.library_creation.LibraryCreationMixin method), 324
 create_new_current() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320
 create_new_user() (galaxy.web.base.controllers.admin.Admin method), 251
 create_object_in_session() (in module galaxy.objectstore), 172
 create_or_verify_database() (in module galaxy.model.migrate.check), 153
 create_paramfile() (in module galaxy.tools.actions.upload_common), 191
 create_private_user_role() (galaxy.security.GalaxyRBACAgent method), 176
 create_private_user_role() (galaxy.security.RBACAgent method), 180
 create_quota() (galaxy.webapps.galaxy.controllers.admin.AdminGalaxy method), 306
 create_request() (galaxy.webapps.galaxy.controllers.requests_common.Request method), 334
 create_request_type() (galaxy.webapps.galaxy.controllers.request_type.RequestType method), 330
 create_role() (galaxy.web.base.controllers.admin.Admin method), 251
 create_tool() (galaxy.tools.ToolBox method), 188
 create_user() (galaxy.web.base.controller.CreatesUsersMixin method), 247
 create_visualization() (galaxy.web.base.controller.UsesVisualizationMixin method), 250
 CreatedWorkflow (class in galaxy.managers.workflows), 168
 CreatesApiKeysMixin (class in galaxy.web.base.controller), 247
 CreatesExternalServiceMixin (class in galaxy.web.base.controller), 247
 creating_library(Galaxy model.DatasetInstance attribute), 131
 FastForm (class in galaxy.datatypes.sequence), 82
 css() (in module galaxy.web.framework.helpers), 257
 CSV (class in galaxy.datatypes.tabular), 85
 cur_filter_pref_name (galaxy.web.framework.helpers.grids.Grid attribute), 259
 cur_sort_key_pref_name (galaxy.web.framework.helpers.grids.Grid attribute), 259
 custom_data_transfer_plugin (in galaxy.webapps.galaxy.controllers.history.HistoryController method), 320
 custom_SMRTPortalPlugin (galaxy.model.orm.logging_connection_proxy.LoggingProxy method), 153
 cursor_execute() (galaxy.model.orm.logging_connection_proxy.TraceLogger method), 153
 CustomInterval (class in galaxy.datatypes.interval), 65
 cut_and_decode() (galaxy.managers.folders.FolderManager method), 161
 cut_the_prefix() (galaxy.managers.folders.FolderManager method), 161
 CycleError, 236
D
 Data (class in galaxy.datatypes.data), 50
 data_conversion_status() (galaxy.managers.hdas.HDAManager method), 163
 data_source_redirect() (galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner method), 338
 data_sources (galaxy.datatypes.binary.Bam attribute), 44
 data_sources (galaxy.datatypes.binary.BigBed attribute), 45
 data_sources (galaxy.datatypes.binary.BigWig attribute), 46
 data_sources (galaxy.datatypes.data.Data attribute), 50

- `data_sources` (`galaxy.datatypes.interval.Bed` attribute), 63
- `data_sources` (`galaxy.datatypes.interval.BedGraph` attribute), 64
- `data_sources` (`galaxy.datatypes.interval.ChromatinInteraction` attribute), 64
- `data_sources` (`galaxy.datatypes.interval.ENCODEPeak` attribute), 65
- `data_sources` (`galaxy.datatypes.interval.Gff` attribute), 66
- `data_sources` (`galaxy.datatypes.interval.Interval` attribute), 68
- `data_sources` (`galaxy.datatypes.interval.Wiggle` attribute), 69
- `data_sources` (`galaxy.datatypes.tabular.Pileup` attribute), 86
- `data_sources` (`galaxy.datatypes.tabular.Sam` attribute), 87
- `data_sources` (`galaxy.datatypes.tabular.Vcf` attribute), 89
- `data_transfer` (in module `galaxy.sample_tracking.data_transfer`), 174
- `data_transfer_protocol` (`galaxy.model.ExternalService` attribute), 134
- `DataCollectionToolParameter` (class in `galaxy.tools.parameters.basic`), 199
- `DataDestinationTool` (class in `galaxy.tools`), 182
- `DataManagerHistoryAssociation` (class in `galaxy.model`), 128
- `DataManagerJobAssociation` (class in `galaxy.model`), 128
- `DataManagerTool` (class in `galaxy.tools`), 182
- `DataMeta` (class in `galaxy.datatypes.data`), 52
- `DataMetaFilter` (class in `galaxy.tools.parameters.dynamic_options`), 209
- `datapvider()` (`galaxy.datatypes.data.Data` method), 50
- `datapviders` (`galaxy.datatypes.binary.Bam` attribute), 44
- `datapviders` (`galaxy.datatypes.binary.SQLite` attribute), 47
- `datapviders` (`galaxy.datatypes.data.Data` attribute), 51
- `datapviders` (`galaxy.datatypes.data.Text` attribute), 53
- `datapviders` (`galaxy.datatypes.interval.Gff` attribute), 66
- `datapviders` (`galaxy.datatypes.interval.Interval` attribute), 68
- `datapviders` (`galaxy.datatypes.interval.Wiggle` attribute), 69
- `datapviders` (`galaxy.datatypes.tabular.CSV` attribute), 85
- `datapviders` (`galaxy.datatypes.tabular.Pileup` attribute), 86
- `datapviders` (`galaxy.datatypes.tabular.Sam` attribute), 87
- `datapviders` (`galaxy.datatypes.tabular.Tabular` attribute), 88
- `datapviders` (`galaxy.datatypes.tabular.TabularData` attribute), 89
- `datapviders` (`galaxy.datatypes.tabular.Vcf` attribute), 89
- `datapviders` (`galaxy.datatypes.xml.GenericXml` attribute), 90
- `Dataset` (class in `galaxy.model`), 129
- `dataset` (`galaxy.model.DatasetCollectionElement` attribute), 130
- `dataset` (`galaxy.model.JobExternalOutputMetadata` attribute), 140
- `dataset_access_mapping()` (`galaxy.security.GalaxyRBACAgent` method), 176
- `dataset_collectors` (`galaxy.tools.ToolOutputCollection` attribute), 189
- `dataset_column_dataprovider()` (`galaxy.datatypes.tabular.Sam` method), 87
- `dataset_column_dataprovider()` (`galaxy.datatypes.tabular.TabularData` method), 89
- `dataset_content_needs_grooming()` (`galaxy.datatypes.binary.Bam` method), 44
- `dataset_content_needs_grooming()` (`galaxy.datatypes.data.Data` method), 51
- `dataset_datatype_re` (`galaxy.jobs.deferred.data_transfer.DataTransfer` attribute), 123
- `dataset_detail()` (`galaxy.webapps.galaxy.controllers.mobile.Mobile` method), 327
- `dataset_dict_dataprovider()` (`galaxy.datatypes.tabular.Sam` method), 87
- `dataset_dict_dataprovider()` (`galaxy.datatypes.tabular.TabularData` method), 89
- `dataset_elements` (`galaxy.model.DatasetCollection` attribute), 130
- `dataset_info()` (`galaxy.webapps.reports.controllers.system.System` method), 345
- `dataset_instance` (`galaxy.model.DatasetCollectionElement` attribute), 130
- `dataset_instances` (`galaxy.model.DatasetCollection` attribute), 130
- `dataset_is_private_to_user()` (`galaxy.security.GalaxyRBACAgent` method), 176
- `dataset_is_public()` (`galaxy.security.GalaxyRBACAgent` method), 176
- `dataset_is_public()` (`galaxy.security.RBACAgent` method), 180
- `dataset_is_unrestricted()` (`galaxy.security.GalaxyRBACAgent` method), 176
- `dataset_make_primary()` (`galaxy.webapps.galaxy.controllers.root.RootCont` method), 336
- `dataset_name_re` (`galaxy.jobs.deferred.data_transfer.DataTransfer` attribute), 123
- `dataset_peek()` (`galaxy.webapps.galaxy.controllers.mobile.Mobile` method), 327
- `dataset_permission_map_for_access()` (`galaxy.security.GalaxyRBACAgent` method), 177

[dataset_transfer_status_updates\(\)](#)
 (galaxy.webapps.galaxy.controllers.requests_common.RequestsCommonToolOutputActionConditionalWhen
 method), 334

[dataset_type](#) (galaxy.visualization.data_providers.phylviz.PhylovizDataProviders.galaxy.webapps.galaxy.api.datatypes),
 attribute), 239

[DatasetCollection](#) (class in galaxy.model), 129

[DatasetCollectionElement](#) (class in galaxy.model), 130

[DatasetCollectionInstance](#) (class in galaxy.model), 130

[DatasetCollectionManager](#) (class in
 galaxy.managers.collections), 159

[DatasetCollectionsController](#) (class in
 galaxy.webapps.galaxy.api.dataset_collections),
 9, 274

[DatasetInstance](#) (class in galaxy.model), 130

[DatasetInterface](#) (class in
 galaxy.webapps.galaxy.controllers.dataset),
 314

[DatasetOkValidator](#) (class in
 galaxy.tools.parameters.validation), 218

[DatasetPermissions](#) (class in galaxy.model), 133

[datasets_are_public\(\)](#) (galaxy.security.GalaxyRBACAgent
 method), 177

[datasets_for_Iddas\(\)](#) (in module
 galaxy.webapps.galaxy.controllers.library_common_library_common), 326

[DatasetTagAssociation](#) (class in galaxy.model), 133

[DatasetToValidationErrorAssociation](#) (class in
 galaxy.model), 133

[DataSourceTool](#) (class in galaxy.tools), 182

[DataToolParameter](#) (class in
 galaxy.tools.parameters.basic), 199

[DataTransfer](#) (class in
 galaxy.jobs.deferred.data_transfer), 123

[DataTransferFactory](#) (class in
 galaxy.sample_tracking.data_transfer), 174

[DataTransferGrid](#) (class in
 galaxy.webapps.galaxy.controllers.requests_admin),
 332

[DataTransferGrid.ExternalServiceColumn](#) (class in
 galaxy.webapps.galaxy.controllers.requests_admin),
 332

[DataTransferGrid.NameColumn](#) (class in
 galaxy.webapps.galaxy.controllers.requests_admin),
 332

[DataTransferGrid.SizeColumn](#) (class in
 galaxy.webapps.galaxy.controllers.requests_admin),
 333

[DataTransferGrid.StatusColumn](#) (class in
 galaxy.webapps.galaxy.controllers.requests_admin),
 333

[datatx_grid](#) (galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdminToolOutputActionConditionalWhen
 attribute), 333

[Datatype](#) (class in galaxy.web.base.controller), 247

[datatype](#) (galaxy.model.DatasetInstance attribute), 131

[DatatypeIsInstanceToolOutputActionConditionalWhen](#)
 DatatypesController (class in
 galaxy.webapps.galaxy.api.datatypes),
 274

[DateTimeColumn](#) (class in
 galaxy.web.framework.helpers.grids), 258

[db_builds](#) (galaxy.managers.context.ProvidesHistoryContext
 attribute), 160

[db_dataset_for\(\)](#) (galaxy.jobs.deferred.FakeTrans
 method), 122

[db_dataset_for\(\)](#) (galaxy.managers.context.ProvidesHistoryContext
 method), 160

[dbkey](#) (galaxy.model.DatasetInstance attribute), 131

[DBKeyParameter](#) (class in galaxy.datatypes.metadata), 70

[dbkeys\(\)](#) (galaxy.webapps.galaxy.controllers.user.User
 method), 338

[deactivate_or_uninstall_repository\(\)](#)
 (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed
 method), 312

[debugging](#) (galaxy.webapps.galaxy.api.metrics.MetricsController
 attribute), 31, 295

[declare_namespace\(\)](#) (in module pkg_resources), 359

[decode\(\)](#) (galaxy.tools.DefaultToolState method), 183

[decode_dataset_user\(\)](#) (in module
 galaxy.datatypes.display_applications.util),
 98

[decode_dbkey\(\)](#) (in module
 galaxy.visualization.genomes), 238

[decode_folder_id\(\)](#) (galaxy.managers.folders.FolderManager
 method), 161

[decode_guid\(\)](#) (galaxy.web.security.SecurityHelper
 method), 266

[decode_id\(\)](#) (galaxy.web.base.controller.BaseController
 method), 247

[decode_id\(\)](#) (galaxy.web.security.SecurityHelper
 method), 266

[decode_runtime_state\(\)](#) (galaxy.workflow.modules.SimpleWorkflowModule
 method), 348

[default\(\)](#) (galaxy.webapps.galaxy.controllers.async.ASync
 method), 314

[default\(\)](#) (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface
 method), 315

[default\(\)](#) (galaxy.webapps.galaxy.controllers.root.RootController
 method), 336

[default\(\)](#) (galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner
 method), 338

[default_collection_type](#) (galaxy.workflow.modules.InputDataCollectionModule
 attribute), 347

[default_compute_environment\(\)](#)
 (galaxy.jobs.JobWrapper method), 114

[default_deserializer\(\)](#) (galaxy.managers.base.ModelDeserializer
 method), 154

[default_exit_code_file\(\)](#) (galaxy.jobs.runners.JobState

static method), 125

default_filter (galaxy.web.framework.helpers.grids.Grid attribute), 259

default_filter (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 310

default_filter (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetGrid attribute), 316

default_filter (galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGrid attribute), 317

default_filter (galaxy.webapps.galaxy.controllers.forms.FormsGrid attribute), 319

default_filter (galaxy.webapps.galaxy.controllers.history.HistoryAllPublishedGrid attribute), 320

default_filter (galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute), 322

default_filter (galaxy.webapps.galaxy.controllers.history.SharedHistoryGrid attribute), 323

default_filter (galaxy.webapps.galaxy.controllers.library.LibraryListGrid attribute), 324

default_filter (galaxy.webapps.galaxy.controllers.library_admin.LibraryAdminGrid attribute), 325

default_filter (galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid attribute), 328

default_filter (galaxy.webapps.galaxy.controllers.page.PageAllPublishedGrid attribute), 328

default_filter (galaxy.webapps.galaxy.controllers.page.PageListGrid attribute), 329

default_filter (galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid attribute), 331

default_filter (galaxy.webapps.galaxy.controllers.requests_admin.DataToolRequestsGrid attribute), 335

default_filter (galaxy.webapps.galaxy.controllers.user.UserOpenIDGrid attribute), 340

default_filter (galaxy.webapps.reports.controllers.jobs.SpecifiedDateGrid attribute), 343

default_filter (galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDateGrid attribute), 344

default_filter (galaxy.webapps.reports.controllers.workflows.SpecifiedDateGrid attribute), 346

DEFAULT_INVALID_CHAR (galaxy.tools.parameters.sanitize.ToolParameterSanitizer attribute), 218

default_job_file() (galaxy.jobs.runners.JobState static method), 125

default_job_tool_configuration (galaxy.jobs.JobConfiguration attribute), 113

DEFAULT_MAX_OPEN_FILES (galaxy.tools.util.maf_utilities.TempFileHandler attribute), 223

default_name (galaxy.model.History attribute), 135

default_name (galaxy.workflow.modules.InputDataCollectionModule attribute), 347

default_name (galaxy.workflow.modules.InputDataModule attribute), 347

default_name (galaxy.workflow.modules.PauseModule attribute), 348

DEFAULT_NETWORKERS (galaxy.jobs.JobConfiguration attribute), 112

default_permissions (galaxy.tools.util.galaxyops), 225

default_external_service_quota (galaxy.quota.QuotaAgent attribute), 173

default_registered_quota (galaxy.quota.QuotaAgent attribute), 174

default_published_original (galaxy.managers.base.ModelSerializer method), 157

default_grid_key (galaxy.web.framework.helpers.grids.Grid attribute), 259

default_sort_key (galaxy.webapps.galaxy.controllers.admin.GroupListGrid attribute), 307

default_grid_key (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid attribute), 308

default_sort_key (galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute), 309

default_sort_key (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 310

default_sort_key (galaxy.webapps.galaxy.controllers.admin.UserListGrid attribute), 312

default_sort_key (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetGrid attribute), 316

default_sort_key (galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGrid attribute), 317

default_sort_key (galaxy.webapps.galaxy.controllers.forms.FormsGrid attribute), 319

default_sort_key (galaxy.webapps.galaxy.controllers.history.HistoryAllPublishedGrid attribute), 320

default_sort_key (galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute), 322

default_sort_key (galaxy.webapps.galaxy.controllers.history.SharedHistoryGrid attribute), 323

default_sort_key (galaxy.webapps.galaxy.controllers.library.LibraryListGrid attribute), 324

default_sort_key (galaxy.webapps.galaxy.controllers.library_admin.LibraryAdminGrid attribute), 325

default_sort_key (galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid attribute), 328

default_sort_key (galaxy.webapps.galaxy.controllers.page.PageAllPublishedGrid attribute), 328

default_sort_key (galaxy.webapps.galaxy.controllers.page.PageListGrid attribute), 329

default_sort_key (galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid attribute), 331

default_sort_key (galaxy.webapps.galaxy.controllers.requests_admin.DataToolRequestsGrid attribute), 333

default_sort_key (galaxy.webapps.galaxy.controllers.requests_common.RequestTypeGrid attribute), 335

default_sort_key (galaxy.webapps.galaxy.controllers.user.UserOpenIDGrid attribute), 340

attribute), 340

default_sort_key (galaxy.webapps.reports.controllers.jobs.SpecifiedDataListController attribute), 343

default_sort_key (galaxy.webapps.reports.controllers.sample_data.SpecifiedDataListController attribute), 344

default_sort_key (galaxy.webapps.reports.controllers.workflows.SpecifiedDataListController attribute), 346

DEFAULT_SPECS (galaxy.jobs.runners.BaseJobRunner attribute), 124

default_state() (galaxy.workflow.modules.InputDataCollectionModule class method), 347

default_state() (galaxy.workflow.modules.InputDataModule class method), 347

default_state() (galaxy.workflow.modules.PauseModule class method), 348

default_state() (galaxy.workflow.modules.SimpleWorkflowModule class method), 348

default_template (galaxy.tools.Tool attribute), 184

default_tool_action (galaxy.tools.DataManagerTool attribute), 182

default_tool_action (galaxy.tools.DataSourceTool attribute), 183

default_tool_action (galaxy.tools.Tool attribute), 184

default_unregistered_quota (galaxy.quota.QuotaAgent attribute), 174

DEFAULT_VALUE_MAP() (in module galaxy.tools.parameters.basic), 199

DefaultHistoryPermissions (class in galaxy.model), 133

DefaultJobAction (class in galaxy.jobs.actions.post), 120

DefaultJobDispatcher (class in galaxy.jobs.handler), 117

DefaultProvider (class in pkg_resources), 368

DefaultQuotaAssociation (class in galaxy.model), 133

DefaultToolAction (class in galaxy.tools.actions), 190

DefaultToolState (class in galaxy.tools), 183

DefaultUserPermissions (class in galaxy.model), 133

DefaultWebTransaction (class in galaxy.web.framework.base), 253

DeferredJob (class in galaxy.model), 133

DeferredJobQueue (class in galaxy.jobs.deferred), 122

DelayedWorkflowEvaluation, 347

delete() (galaxy.managers.collections.DatasetCollectionManager method), 159

delete() (galaxy.managers.folders.FolderManager method), 161

delete() (galaxy.managers.libraries.LibraryManager method), 166

delete() (galaxy.objectstore.DiskObjectStore method), 169

delete() (galaxy.objectstore.NestedObjectStore method), 170

delete() (galaxy.objectstore.ObjectStore method), 171

delete() (galaxy.webapps.galaxy.api.annotations.BaseAnnotationController method), 7, 272

delete() (galaxy.webapps.galaxy.api.extended_metadata.BaseExtendedMetadataController method), 10, 275

delete() (galaxy.webapps.galaxy.api.folders.FoldersController method), 11, 276

delete() (galaxy.webapps.galaxy.api.group_roles.GroupRolesAPIController method), 13, 278

delete() (galaxy.webapps.galaxy.api.group_users.GroupUsersAPIController method), 14, 279

delete() (galaxy.webapps.galaxy.api.histories.HistoriesController method), 15, 280

delete() (galaxy.webapps.galaxy.api.history_contents.HistoryContentsController method), 18, 283

delete() (galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController method), 20, 284

delete() (galaxy.webapps.galaxy.api.lda_datasets.LibraryDatasetsController method), 23, 287

delete() (galaxy.webapps.galaxy.api.libraries.LibrariesController method), 26, 290

delete() (galaxy.webapps.galaxy.api.library_contents.LibraryContentsController method), 29, 293

delete() (galaxy.webapps.galaxy.api.pages.PagesController method), 32, 296

delete() (galaxy.webapps.galaxy.api.provenance.BaseProvenanceController method), 32, 297

delete() (galaxy.webapps.galaxy.api.quotas.QuotaAPIController method), 33, 297

delete() (galaxy.webapps.galaxy.api.tool_data.ToolData method), 34, 299

delete() (galaxy.webapps.galaxy.api.users.UserAPIController method), 38, 302

delete() (galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController method), 40, 304

delete() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

delete_address() (galaxy.webapps.galaxy.controllers.user.User method), 338

delete_async() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

delete_current() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320

delete_extended_metadata() (galaxy.web.base.controller.UsesExtendedMetadataMixin method), 248

delete_external_service() (galaxy.webapps.galaxy.controllers.external_service.ExternalService method), 317

delete_external_service_associations() (galaxy.model.RequestType method), 144

delete_form_definition() (galaxy.webapps.galaxy.controllers.forms.Forms method), 318

delete_hidden_datasets() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320

delete_item_attr_annotation() (galaxy.model.item_attrs.UsesAnnotations method), 320

<code>delete_item_tags()</code> (galaxy.managers.tags.TagManager method), 168	<code>(galaxy.managers.base.ModelSerializer method), 155</code>
<code>delete_library()</code> (galaxy.webapps.galaxy.controllers.library_admin_library_admin method), 324	<code>(galaxy.managers.base.ModelSerializer method), 155</code>
<code>delete_library_item()</code> (galaxy.webapps.galaxy.controllers.library_admin_library_admin method), 325	<code>(in module galaxy.tools.actions), 191</code>
<code>delete_operation</code> (galaxy.web.base.controllers.admin.AdminDictCollectionVisibleKeys attribute), 251	<code>(galaxy.model.DatasetCollection attribute), 130</code>
<code>delete_operation</code> (galaxy.webapps.galaxy.controllers.admin.AdminDictCollectionVisibleKeys attribute), 306	<code>(dict_collection_visible_keys attribute), 130</code>
<code>delete_request()</code> (galaxy.webapps.galaxy.controllers.requests_common_requests_common method), 334	<code>(galaxy.model.DatasetCollectionElement attribute), 130</code>
<code>delete_request_type()</code> (galaxy.webapps.galaxy.controllers.requests_common_requests_common method), 330	<code>(dict_collection_visible_keys attribute), 130</code>
<code>delete_sample()</code> (galaxy.webapps.galaxy.controllers.requests_common_requests_common method), 334	<code>(galaxy.model.FormDefinition attribute), 130</code>
<code>delete_template()</code> (galaxy.web.base.controller.UsesFormDefinitionsMixin method), 249	<code>(RequestsCommon dict_collection_visible_keys (galaxy.model.Group attribute), 134</code>
<code>deleted_datasets()</code> (galaxy.webapps.reports.controllers.system.SystemDictCollectionVisibleKeys attribute), 345	<code>(dict_collection_visible_keys (galaxy.model.History attribute), 135</code>
<code>deleted_histories()</code> (galaxy.webapps.reports.controllers.system.SystemDictCollectionVisibleKeys attribute), 345	<code>(dict_collection_visible_keys (galaxy.model.ItemTagAssociation attribute), 138</code>
<code>DeleteDatasetAction</code> (class in galaxy.jobs.actions.post), 121	<code>(dict_collection_visible_keys (galaxy.model.Job attribute), 138</code>
<code>DeletedColumn</code> (class in galaxy.web.framework.helpers.grids), 258	<code>(dict_collection_visible_keys (galaxy.model.Library attribute), 141</code>
<code>DeleteIntermediatesAction</code> (class in galaxy.jobs.actions.post), 121	<code>(dict_collection_visible_keys (galaxy.model.Quota attribute), 144</code>
<code>delimiter</code> (galaxy.datatypes.tabular.CSV attribute), 85	<code>(dict_collection_visible_keys (galaxy.model.Request attribute), 144</code>
<code>demodulize()</code> (galaxy.util.inflection.Base method), 231	<code>(dict_collection_visible_keys (galaxy.model.RequestType attribute), 144</code>
<code>demodulize()</code> (galaxy.util.inflection.Inflector method), 232	<code>(dict_collection_visible_keys (galaxy.model.Role attribute), 145</code>
<code>dependency_shell_commands()</code> (galaxy.tools.deps.DependencyManager method), 195	<code>(dict_collection_visible_keys (galaxy.model.Sample attribute), 145</code>
<code>dependency_shell_commands()</code> (galaxy.tools.deps.NullDependencyManager method), 195	<code>(dict_collection_visible_keys (galaxy.model.StoredWorkflow attribute), 146</code>
<code>DependencyManager</code> (class in galaxy.tools.deps), 195	<code>(dict_collection_visible_keys (galaxy.model.User attribute), 148</code>
<code>deprecated_options</code> (galaxy.config.Configuration attribute), 42	<code>(dict_collection_visible_keys (galaxy.model.Workflow attribute), 150</code>
<code>DeprecatedMethod</code> , 103	<code>(dict_collection_visible_keys (galaxy.model.WorkflowInvocation attribute), 150</code>
<code>derive_roles_from_access()</code> (galaxy.security.GalaxyRBACAgent method), 177	<code>(dict_collection_visible_keys (galaxy.model.WorkflowInvocationStep attribute), 150</code>
<code>derive_roles_from_access()</code> (galaxy.security.RBACAgent method), 180	<code>(dict_collection_visible_keys (galaxy.model.WorkflowRequest attribute), 151</code>
<code>deserialize()</code> (galaxy.managers.base.ModelSerializer method), 154	<code>(dict_collection_visible_keys (galaxy.model.WorkflowRequestInputParameter attribute), 151</code>
<code>deserialize_basestring()</code> (galaxy.managers.base.ModelSerializer method), 155	
<code>deserialize_bool()</code> (galaxy.managers.base.ModelSerializer method), 155	
<code>deserialize_genome_build()</code>	

attribute), 151
 dict_collection_visible_keys (galaxy.model.WorkflowRequestStepState attribute), 151
 dict_collection_visible_keys (galaxy.model.WorkflowRequestToInputDatasetAssociation attribute), 151
 dict_collection_visible_keys (galaxy.model.WorkflowRequestToInputDatasetCollectionAssociation attribute), 151
 dict_collection_visible_keys (galaxy.tools.data.TabularToolDataField attribute), 192
 dict_collection_visible_keys (galaxy.tools.data.TabularToolDataTable attribute), 193
 dict_collection_visible_keys (galaxy.tools.parameters.basic.FloatToolParameter attribute), 203
 dict_collection_visible_keys (galaxy.tools.parameters.basic.IntegerToolParameter attribute), 205
 dict_collection_visible_keys (galaxy.tools.parameters.basic.ToolParameter attribute), 207
 dict_collection_visible_keys (galaxy.tools.parameters.grouping.ConditionalWorkflow attribute), 211
 dict_collection_visible_keys (galaxy.tools.parameters.grouping.Group attribute), 212
 dict_collection_visible_keys (galaxy.tools.parameters.grouping.Repeat attribute), 212
 dict_collection_visible_keys (galaxy.tools.parameters.grouping.Section attribute), 212
 dict_collection_visible_keys (galaxy.tools.Tool attribute), 184
 dict_collection_visible_keys (galaxy.tools.ToolOutput attribute), 188
 dict_dataprovider() (galaxy.datatypes.binary.Bam method), 44
 dict_dataprovider() (galaxy.datatypes.tabular.Sam method), 87
 dict_dataprovider() (galaxy.datatypes.tabular.TabularData method), 89
 dict_element_visible_keys (galaxy.model.DatasetCollection attribute), 130
 dict_element_visible_keys (galaxy.model.DatasetCollectionElement attribute), 130
 dict_element_visible_keys (galaxy.model.DefaultQuotaAssociation attribute), 133
 dict_element_visible_keys (galaxy.model.FormDefinition attribute), 134
 dict_element_visible_keys (galaxy.model.Group attribute), 135
 dict_element_visible_keys (galaxy.model.GroupQuotaAssociation attribute), 135
 dict_element_visible_keys (galaxy.model.History attribute), 135
 dict_element_visible_keys (galaxy.model.ItemTagAssociation attribute), 138
 dict_element_visible_keys (galaxy.model.Job attribute), 138
 dict_element_visible_keys (galaxy.model.Library attribute), 141
 dict_element_visible_keys (galaxy.model.LibraryFolder attribute), 142
 dict_element_visible_keys (galaxy.model.Page attribute), 143
 dict_element_visible_keys (galaxy.model.PageRevision attribute), 143
 dict_element_visible_keys (galaxy.model.Quota attribute), 144
 dict_element_visible_keys (galaxy.model.RequestType attribute), 144
 dict_element_visible_keys (galaxy.model.Role attribute), 145
 dict_element_visible_keys (galaxy.model.StoredWorkflow attribute), 146
 dict_element_visible_keys (galaxy.model.User attribute), 148
 dict_element_visible_keys (galaxy.model.UserQuotaAssociation attribute), 149
 dict_element_visible_keys (galaxy.model.Workflow attribute), 150
 dict_element_visible_keys (galaxy.model.WorkflowInvocation attribute), 150
 dict_element_visible_keys (galaxy.model.WorkflowInvocationStep attribute), 150
 dict_element_visible_keys (galaxy.model.WorkflowRequest attribute), 151
 Dictifiable (class in galaxy.model.item_attrs), 152
 dictify_dataset_collection_instance() (in module galaxy.managers.collections_util), 159
 dictify_element() (in module galaxy.managers.collections_util), 159

DictParameter (class in galaxy.datatypes.metadata), 70

disk_usage() (galaxy.webapps.reports.controllers.system.SystemController method), 345

DiskObjectStore (class in galaxy.objectstore), 169

display() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

display() (galaxy.webapps.galaxy.controllers.page.PageController method), 328

display() (galaxy.webapps.galaxy.controllers.root.RootController method), 336

display_amount (galaxy.model.Quota attribute), 144

display_application() (galaxy.webapps.galaxy.controllers.dataset.DatasetController method), 315

display_applications() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 306

display_as() (galaxy.webapps.galaxy.controllers.root.RootController method), 336

display_at() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

display_by_username_and_slug() (galaxy.web.base.controller.SharableMixin method), 248

display_by_username_and_slug() (galaxy.webapps.galaxy.controllers.dataset.DatasetController method), 315

display_by_username_and_slug() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320

display_by_username_and_slug() (galaxy.webapps.galaxy.controllers.page.PageController method), 328

display_child() (galaxy.webapps.galaxy.controllers.root.RootController method), 336

display_data() (galaxy.datatypes.binary.Binary method), 46

display_data() (galaxy.datatypes.data.Data method), 51

display_data() (galaxy.datatypes.tabular.TabularData method), 89

display_image_in_repository() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 312

display_info() (galaxy.datatypes.data.Data method), 51

display_info() (galaxy.model.DatasetInstance method), 131

display_name() (galaxy.datatypes.data.Data method), 51

display_name() (galaxy.model.DatasetCollectionInstance method), 130

display_name() (galaxy.model.DatasetInstance method), 131

display_name() (galaxy.model.LibraryDataset method), 141

display_peek() (galaxy.datatypes.binary.Ab1 method), 44

display_peek() (galaxy.datatypes.binary.Bam method), 45

display_peek() (galaxy.datatypes.binary.BigWig method), 46

display_peek() (galaxy.datatypes.binary.CompressedArchive method), 46

display_peek() (galaxy.datatypes.binary.GeminiSQLite method), 47

display_peek() (galaxy.datatypes.binary.H5 method), 47

display_peek() (galaxy.datatypes.binary.Scf method), 48

display_peek() (galaxy.datatypes.binary.Sff method), 48

display_peek() (galaxy.datatypes.binary.SQLite method), 47

display_peek() (galaxy.datatypes.binary.Sra method), 48

display_peek() (galaxy.datatypes.binary.TwoBit method), 49

display_peek() (galaxy.datatypes.data.Data method), 51

display_peek() (galaxy.datatypes.genetics.RexpBase method), 51

display_peek() (galaxy.datatypes.genetics.rgTabList method), 59

display_peek() (galaxy.datatypes.images.Gmaj method), 60

display_peek() (galaxy.datatypes.images.Laj method), 61

display_peek() (galaxy.datatypes.interval.CustomTrack method), 65

display_peek() (galaxy.datatypes.interval.Gff method), 66

display_peek() (galaxy.datatypes.interval.Interval method), 68

display_peek() (galaxy.datatypes.interval.Wiggle method), 69

display_peek() (galaxy.datatypes.ngsindex.BowtieIndex method), 74

display_peek() (galaxy.datatypes.sequence.Maf method), 80

display_peek() (galaxy.datatypes.tabular.Pileup method), 86

display_peek() (galaxy.datatypes.tabular.Sam method), 87

display_peek() (galaxy.datatypes.tabular.TabularData method), 89

display_peek() (galaxy.datatypes.tabular.Taxonomy method), 89

display_peek() (galaxy.datatypes.tabular.Vcf method), 89

display_peek() (galaxy.model.DatasetInstance method), 131

display_ready() (galaxy.datatypes.display_applications.application.PopulatedDataset method), 97

display_structured() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320

display_url() (galaxy.datatypes.display_applications.application.PopulatedDataset method), 97

displayable() (galaxy.datatypes.interval.Interval method), 68

displayable() (galaxy.datatypes.tabular.TabularData method), 89

DisplayApplication (class in

[galaxy.datatypes.display_applications.application](#) [DoiCache](#) (class in [galaxy.managers.citations](#)), 158
[96](#) [DoiCitation](#) (class in [galaxy.managers.citations](#)), 158
[DisplayApplicationDataParameter](#) (class in [download\(\)](#) ([galaxy.webapps.galaxy.api.lda_datasets.LibraryDatasetsControl](#)
[galaxy.datatypes.display_applications.parameters](#)), method), 23, 288
[97](#) [download_dataset_from_folder\(\)](#)
[DisplayApplicationLink](#) (class in [\(galaxy.webapps.galaxy.controllers.library_common.LibraryCom](#)
[galaxy.datatypes.display_applications.application](#)), method), 325
[96](#) [download_field_file\(\)](#) ([galaxy.webapps.galaxy.api.tool_data.ToolData](#)
[DisplayApplicationParameter](#) (class in method), 35, 299
[galaxy.datatypes.display_applications.parameters](#)) [DrillDownField](#) (class in [galaxy.web.form_builder](#)), 242
[97](#) [DrillDownSelectToolParameter](#) (class in
[DisplayApplicationTemplateParameter](#) (class in [galaxy.tools.parameters.basic](#)), 200
[galaxy.datatypes.display_applications.parameters](#)) [DRMAAJobRunner](#) (class in [galaxy.jobs.runners.drmaa](#)),
[97](#) 126
[DisplayByUsernameAndSlugGridOperation](#) (class in [DummyDataset](#) (class in [galaxy.tools.parameters.basic](#)),
[galaxy.web.framework.helpers.grids](#)), 259 202
[DisplayDataValueWrapper](#) (class in [dump\(\)](#) ([galaxy.util.aliaspickler.AliasPickleModule](#)
[galaxy.datatypes.display_applications.parameters](#)), method), 229
[98](#) [dumps\(\)](#) ([galaxy.util.aliaspickler.AliasPickleModule](#)
[DisplayParameterValueWrapper](#) (class in method), 229
[galaxy.datatypes.display_applications.parameters](#)) [dumps\(\)](#) (in module [galaxy.util.json](#)), 233
[98](#) [DuplicatedIdentifierException](#), 103
[dist_config_file](#) ([galaxy.eggs.dist.DistScrambleCrate](#) at-
[tribute](#)), 101 [DuplicatedSlugException](#), 104
[DistributedObjectStore](#) (class in [galaxy.objectstore](#)), 170 [dynamic_structure](#) ([galaxy.tools.ToolOutputCollection](#)
[Distribution](#) (class in [pkg_resources](#)), 362 attribute), 189
[DistributionNotFound](#), 364 [dynamic_tool_confs\(\)](#) ([galaxy.webapps.galaxy.api.configuration.Configuration](#)
[DistScrambleCrate](#) (class in [galaxy.eggs.dist](#)), 101 method), 8, 273
[DistScrambleEgg](#) (class in [galaxy.eggs.dist](#)), 102 [DynamicDisplayApplicationBuilder](#) (class in
[DNA_COMPLEMENT](#) ([galaxy.tools.util.maf_utilities.RegionAlignment](#)
[attribute](#)), 222 [DynamicOptions](#) (class in
[DNA_COMPLEMENT](#) ([galaxy.tools.util.maf_utilities.SplicedAlignment](#)
[attribute](#)), 222 [galaxy.tools.parameters.dynamic_options](#)),
209
[DNA_complement\(\)](#) (in module
[galaxy_utils.sequence.transform](#)), 357
[DNA_reverse_complement\(\)](#) (in module
[galaxy_utils.sequence.transform](#)), 357
[do_fast_split\(\)](#) ([galaxy.datatypes.sequence.Sequence](#)
[class method](#)), 81
[do_invocation_step_action\(\)](#)
[\(galaxy.workflow.modules.PauseModule](#)
[method\)](#), 348
[do_invocation_step_action\(\)](#)
[\(galaxy.workflow.modules.WorkflowModule](#)
[method\)](#), 350
[do_merge\(\)](#) (in module [galaxy.jobs.splitters.basic](#)), 128
[do_merge\(\)](#) (in module [galaxy.jobs.splitters.multi](#)), 128
[do_slow_split\(\)](#) ([galaxy.datatypes.sequence.Sequence](#)
[class method](#)), 81
[do_split\(\)](#) (in module [galaxy.jobs.splitters.basic](#)), 128
[do_split\(\)](#) (in module [galaxy.jobs.splitters.multi](#)), 128
[docstring_trim\(\)](#) (in module [galaxy.util](#)), 226
[doi\(\)](#) ([galaxy.managers.citations.DoiCitation](#) method),
159

E

[eagers](#) ([pkg_resources.ZipProvider](#) attribute), 368
[echo\(\)](#) ([galaxy.webapps.galaxy.controllers.root.RootController](#)
[method](#)), 336
[echo_json\(\)](#) ([galaxy.webapps.galaxy.controllers.root.RootController](#)
[method](#)), 336
[edam_format](#) ([galaxy.datatypes.assembly.Amos](#) at-
[tribute](#)), 43
[edam_format](#) ([galaxy.datatypes.assembly.Roadmaps](#) at-
[tribute](#)), 43
[edam_format](#) ([galaxy.datatypes.binary.Bam](#) attribute), 45
[edam_format](#) ([galaxy.datatypes.binary.Bcf](#) attribute), 45
[edam_format](#) ([galaxy.datatypes.binary.BigBed](#) attribute),
45
[edam_format](#) ([galaxy.datatypes.binary.BigWig](#) attribute),
46
[edam_format](#) ([galaxy.datatypes.binary.Binary](#) attribute),
46
[edam_format](#) ([galaxy.datatypes.binary.Scf](#) attribute), 48
[edam_format](#) ([galaxy.datatypes.binary.Sff](#) attribute), 48

- edam_format (galaxy.datatypes.binary.TwoBit attribute), 49
- edam_format (galaxy.datatypes.data.Data attribute), 51
- edam_format (galaxy.datatypes.data.Newick attribute), 53
- edam_format (galaxy.datatypes.data.Nexus attribute), 53
- edam_format (galaxy.datatypes.data.Text attribute), 53
- edam_format (galaxy.datatypes.images.Eps attribute), 59
- edam_format (galaxy.datatypes.images.Gif attribute), 59
- edam_format (galaxy.datatypes.images.Gmaj attribute), 60
- edam_format (galaxy.datatypes.images.Html attribute), 60
- edam_format (galaxy.datatypes.images.Image attribute), 60
- edam_format (galaxy.datatypes.images.Pdf attribute), 61
- edam_format (galaxy.datatypes.interval.Bed attribute), 63
- edam_format (galaxy.datatypes.interval.Gff attribute), 66
- edam_format (galaxy.datatypes.interval.Gff3 attribute), 66
- edam_format (galaxy.datatypes.interval.Gtf attribute), 67
- edam_format (galaxy.datatypes.interval.Interval attribute), 68
- edam_format (galaxy.datatypes.interval.Wiggle attribute), 69
- edam_format (galaxy.datatypes.sequence.csFasta attribute), 82
- edam_format (galaxy.datatypes.sequence.Fasta attribute), 77
- edam_format (galaxy.datatypes.sequence.Fastq attribute), 78
- edam_format (galaxy.datatypes.sequence.FastqIllumina attribute), 79
- edam_format (galaxy.datatypes.sequence.FastqSanger attribute), 79
- edam_format (galaxy.datatypes.sequence.FastqSolexa attribute), 79
- edam_format (galaxy.datatypes.sequence.Lav attribute), 79
- edam_format (galaxy.datatypes.sequence.Maf attribute), 80
- edam_format (galaxy.datatypes.sequence.RNADotPlotMatrix attribute), 80
- edam_format (galaxy.datatypes.tabular.Pileup attribute), 86
- edam_format (galaxy.datatypes.tabular.Sam attribute), 87
- edam_format (galaxy.datatypes.tabular.TabularData attribute), 89
- edam_format (galaxy.datatypes.tabular.Vcf attribute), 89
- edam_format (galaxy.datatypes.tracks.GeneTrack attribute), 90
- edam_format (galaxy.datatypes.xml.GenericXml attribute), 90
- edam_format (galaxy.datatypes.xml.Owl attribute), 91
- edam_formats (galaxy.datatypes.registry.Registry attribute), 75
- edam_formats() (galaxy.webapps.galaxy.api.datatypes.DatatypesController method), 9, 274
- edit() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315
- edit() (galaxy.webapps.galaxy.controllers.page.PageController method), 328
- edit_address() (galaxy.webapps.galaxy.controllers.user.User method), 339
- edit_basic_request_info() (galaxy.webapps.galaxy.controllers.requests_common.RequestsController method), 334
- edit_content() (galaxy.webapps.galaxy.controllers.page.PageController method), 328
- edit_email_settings() (galaxy.webapps.galaxy.controllers.requests_common.RequestsController method), 334
- edit_external_service() (galaxy.webapps.galaxy.controllers.external_service.ExternalService method), 317
- edit_external_service_form_definition() (galaxy.webapps.galaxy.controllers.external_service.ExternalService method), 317
- edit_form_definition() (galaxy.webapps.galaxy.controllers.forms.Forms method), 318
- edit_info() (galaxy.webapps.galaxy.controllers.user.User method), 339
- edit_quota() (galaxy.webapps.galaxy.controllers.admin.AdminGalaxy method), 306
- edit_request_type() (galaxy.webapps.galaxy.controllers.request_type.RequestType method), 330
- edit_samples() (galaxy.webapps.galaxy.controllers.requests_common.RequestsController method), 334
- edit_template() (galaxy.web.base.controller.UsesFormDefinitionsMixin method), 249
- edit_template_info() (galaxy.web.base.controller.UsesFormDefinitionsMixin method), 249
- edit_toolbox_filters() (galaxy.webapps.galaxy.controllers.user.User method), 339
- edit_username() (galaxy.webapps.galaxy.controllers.user.User method), 339
- editable_keys (galaxy.model.HistoryDatasetCollectionAssociation attribute), 137
- editable_keys (galaxy.model.LibraryDatasetCollectionAssociation attribute), 141
- effective_output_name (galaxy.tools.ToolOutputCollectionPart attribute), 189
- Egg (class in galaxy.eggs), 101
- egg_info (pkg_resources.NullProvider attribute), 367
- egg_name (pkg_resources.NullProvider attribute), 367
- egg_name() (pkg_resources.Distribution method), 363
- EggMetadata (class in pkg_resources), 367
- EggNotFetchable, 101
- EggProvider (class in pkg_resources), 368
- Eigenstratgeno (class in galaxy.datatypes.genetics), 54

- Eigenstratpca (class in galaxy.datatypes.genetics), 54
- Eland (class in galaxy.datatypes.tabular), 85
- ElandMulti (class in galaxy.datatypes.tabular), 86
- element_is_set() (galaxy.datatypes.metadata.MetadataCollection method), 71
- element_object (galaxy.model.DatasetCollectionElement attribute), 130
- element_type (galaxy.model.DatasetCollectionElement attribute), 130
- ELEMENTS_UNINITIALIZED (galaxy.managers.collections.DatasetCollectionManager attribute), 159
- EmailAction (class in galaxy.jobs.actions.post), 121
- empty (galaxy.model.History attribute), 135
- empty() (galaxy.objectstore.DiskObjectStore method), 169
- empty() (galaxy.objectstore.NestedObjectStore method), 170
- empty() (galaxy.objectstore.ObjectStore method), 171
- empty_field (galaxy.webapps.galaxy.controllers.forms.Forms attribute), 318
- EmptyProvider (class in pkg_resources), 367
- EmptyTextfieldValidator (class in galaxy.tools.parameters.validation), 218
- encode() (galaxy.tools.DefaultToolState method), 183
- encode_all_ids() (galaxy.web.base.controller.BaseController method), 247
- encode_all_ids() (galaxy.web.security.SecurityHelper method), 266
- encode_dataset_user() (in module galaxy.datatypes.display_applications.util), 98
- encode_dict_ids() (galaxy.web.security.SecurityHelper method), 266
- encode_guid() (galaxy.web.security.SecurityHelper method), 266
- encode_id() (galaxy.web.security.SecurityHelper method), 266
- encode_runtime_state() (galaxy.workflow.modules.SimpleWorkflowModule method), 348
- encode_runtime_state() (galaxy.workflow.modules.ToolModule method), 349
- encode_runtime_state() (galaxy.workflow.modules.WorkflowModule method), 350
- ENCODEPeak (class in galaxy.datatypes.interval), 65
- end (galaxy.tools.util.maf_utilities.SplicedAlignment attribute), 222
- engine (galaxy.model.Dataset attribute), 129
- English (class in galaxy.util.inflection), 232
- ensure_directory() (in module pkg_resources), 365
- ensure_tempdir() (galaxy.config.Configuration method), 42
- EntryPoint (class in pkg_resources), 363
- Environment (class in pkg_resources), 359
- Eps (class in galaxy.datatypes.images), 59
- equals() (galaxy.managers.citations.BaseCitation method), 158
- err_code (galaxy.exceptions.ActionInputError attribute), 103
- err_code (galaxy.exceptions.AdminRequiredException attribute), 103
- err_code (galaxy.exceptions.AuthenticationFailed attribute), 103
- err_code (galaxy.exceptions.AuthenticationRequired attribute), 103
- err_code (galaxy.exceptions.ConfigDoesNotAllowException attribute), 103
- err_code (galaxy.exceptions.ConfigurationError attribute), 103
- err_code (galaxy.exceptions.Conflict attribute), 103
- err_code (galaxy.exceptions.DeprecatedMethod attribute), 103
- err_code (galaxy.exceptions.DuplicatedIdentifierException attribute), 104
- err_code (galaxy.exceptions.DuplicatedSlugException attribute), 104
- err_code (galaxy.exceptions.InconsistentDatabase attribute), 104
- err_code (galaxy.exceptions.InsufficientPermissionsException attribute), 104
- err_code (galaxy.exceptions.InternalServerError attribute), 104
- err_code (galaxy.exceptions.ItemAccessibilityException attribute), 104
- err_code (galaxy.exceptions.ItemOwnershipException attribute), 104
- err_code (galaxy.exceptions.MalformedId attribute), 104
- err_code (galaxy.exceptions.MessageException attribute), 105
- err_code (galaxy.exceptions.NotImplemented attribute), 105
- err_code (galaxy.exceptions.ObjectAttributeInvalidException attribute), 105
- err_code (galaxy.exceptions.ObjectAttributeMissingException attribute), 105
- err_code (galaxy.exceptions.ObjectNotFound attribute), 105
- err_code (galaxy.exceptions.RequestParameterInvalidException attribute), 105
- err_code (galaxy.exceptions.RequestParameterMissingException attribute), 105
- err_code (galaxy.exceptions.ToolMetaParameterException attribute), 106
- err_code (galaxy.exceptions.UnknownContentsType attribute), 106
- Error (class in galaxy.webapps.galaxy.controllers.error), 317
- error() (galaxy.web.framework.middleware.remoteuser.RemoteUser

method), 265

error_if_uploading() (galaxy.managers.hdas.HDAManager method), 163

errors() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

errors_per_tool() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341

Eset (class in galaxy.datatypes.genetics), 55

estimate_file_lines() (galaxy.datatypes.data.Text method), 53

evaluate_marker() (in module pkg_resources), 365

Event (class in galaxy.model), 133

exec_after_process() (galaxy.tools.DataManagerTool method), 182

exec_after_process() (galaxy.tools.SetMetadataTool method), 183

exec_after_process() (galaxy.tools.Tool method), 184

exec_before_job() (galaxy.tools.DataSourceTool method), 183

exec_before_job() (galaxy.tools.OutputParameterJSONTool method), 183

exec_before_job() (galaxy.tools.Tool method), 184

execute() (galaxy.jobs.actions.post.ActionBox class method), 120

execute() (galaxy.jobs.actions.post.ChangeDatatypeAction class method), 120

execute() (galaxy.jobs.actions.post.ColumnSetAction class method), 120

execute() (galaxy.jobs.actions.post.DefaultJobAction class method), 120

execute() (galaxy.jobs.actions.post.DeleteDatasetAction class method), 121

execute() (galaxy.jobs.actions.post.DeleteIntermediatesAction class method), 121

execute() (galaxy.jobs.actions.post.EmailAction class method), 121

execute() (galaxy.jobs.actions.post.HideDatasetAction class method), 121

execute() (galaxy.jobs.actions.post.RenameDatasetAction class method), 121

execute() (galaxy.jobs.actions.post.SetMetadataAction class method), 122

execute() (galaxy.jobs.actions.post.TagDatasetAction class method), 122

execute() (galaxy.tools.actions.DefaultToolAction method), 190

execute() (galaxy.tools.actions.history_imp_exp.ExportHistoryToolAction method), 191

execute() (galaxy.tools.actions.history_imp_exp.ImportHistoryToolAction method), 191

execute() (galaxy.tools.actions.metadata.SetMetadataToolAction method), 191

execute() (galaxy.tools.actions.ToolAction method), 190

execute() (galaxy.tools.actions.upload.UploadToolAction method), 191

execute() (galaxy.tools.Tool method), 184

execute() (galaxy.workflow.modules.InputModule method), 348

execute() (galaxy.workflow.modules.PauseModule method), 348

execute() (galaxy.workflow.modules.ToolModule method), 349

execute() (galaxy.workflow.modules.WorkflowModule method), 350

execute_via_app() (galaxy.tools.actions.metadata.SetMetadataToolAction method), 191

ExecutionTimer (class in galaxy.util), 225

exists() (galaxy.objectstore.DiskObjectStore method), 169

exists() (galaxy.objectstore.HierarchicalObjectStore method), 170

exists() (galaxy.objectstore.NestedObjectStore method), 170

exists() (galaxy.objectstore.ObjectStore method), 171

exit_code() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

exmeta_item_id (galaxy.webapps.galaxy.api.extended_metadata.HistoryDataset attribute), 10, 275

exmeta_item_id (galaxy.webapps.galaxy.api.extended_metadata.LibraryDataset attribute), 10, 275

expand_here_template() (in module galaxy.tools.data), 195

expand_user_properties() (galaxy.model.User static method), 148

export_archive() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320

export_name (galaxy.model.JobExportHistoryArchive attribute), 140

exported_workflows() (galaxy.webapps.galaxy.api.tool_shed_repositories.ToolShedRepositories method), 35, 299

ExportHistoryTool (class in galaxy.tools), 183

ExportHistoryToolAction (class in galaxy.tools.actions.history_imp_exp), 191

ExportsHistoryMixin (class in galaxy.web.base.controller), 248

exposed (galaxy.web.framework.helpers.grids.Grid attribute), 259

ExpressionContext (class in galaxy.util.expressions), 230

ExpressionValidator (class in galaxy.tools.parameters.validation), 218

export_tool_action() (galaxy.managers.context.ProvidesAppContext method), 160

export_tool_action() (galaxy.model.DatasetInstance attribute), 131

extend_data_with() (galaxy.tools.data.TabularToolDataTable method), 193

extend_validation_errors() (galaxy.model.DatasetInstance method), 131

ExtendedMetadata (class in galaxy.model), 133
 ExtendedMetadataIndex (class in galaxy.model), 133
 external_metadata_set_successfully() (galaxy.datatypes.metadata.JobExternalOutputMetadataWrapper method), 71
 external_runjob() (galaxy.jobs.runners.drmaa.DRMAAJobRunner method), 126
 external_service_grid (galaxy.webapps.galaxy.controllers.external_service attribute), 317
 external_services (galaxy.model.RequestType attribute), 145
 ExternalService (class in galaxy.model), 133
 ExternalService (class in galaxy.webapps.galaxy.controllers.external_service), 317
 ExternalServiceAction (class in galaxy.external_services.actions), 106
 ExternalServiceActionJQueryGridResultHandler (class in galaxy.external_services.result_handlers.basic), 109
 ExternalServiceActionJSONResultHandler (class in galaxy.external_services.result_handlers.basic), 110
 ExternalServiceActionResultHandler (class in galaxy.external_services.result_handlers.basic), 110
 ExternalServiceActionsConditional (class in galaxy.external_services.service), 108
 ExternalServiceActionsGroup (class in galaxy.external_services.service), 108
 ExternalServiceActionsGroupWhen (class in galaxy.external_services.service), 108
 ExternalServiceActionURLRedirectResultHandler (class in galaxy.external_services.result_handlers.basic), 110
 ExternalServiceController (class in galaxy.webapps.galaxy.controllers.external_service), 318
 ExternalServiceGrid (class in galaxy.webapps.galaxy.controllers.external_service), 317
 ExternalServiceGrid.ExternalServiceTypeColumn (class in galaxy.webapps.galaxy.controllers.external_service), 317
 ExternalServiceGrid.NameColumn (class in galaxy.webapps.galaxy.controllers.external_service), 317
 ExternalServiceParameter (class in galaxy.external_services.parameters), 107
 ExternalServiceResult (class in galaxy.external_services.actions), 106
 ExternalServiceTemplateAction (class in galaxy.external_services.actions), 106
 ExternalServiceTemplateParameter (class in galaxy.external_services.parameters), 107
 ExternalServiceType (class in galaxy.sample_tracking.external_service_types), 175
 ExternalServiceTypeNotFoundException, 175
 ExternalServiceTypesCollection (class in galaxy.sample_tracking.external_service_types), 175
 ExternalServiceValueResult (class in galaxy.external_services.actions), 106
 ExternalServiceWebAction (class in galaxy.external_services.actions), 107
 ExternalServiceWebAPIAction (class in galaxy.external_services.actions), 106
 ExternalServiceWebAPIAction.ExternalServiceWebAPIActionRequest (class in galaxy.external_services.actions), 106
 ExternalServiceWebAPIActionResult (class in galaxy.external_services.actions), 107
 extra_files_path (galaxy.model.Dataset attribute), 129
 extra_files_path (galaxy.model.DatasetInstance attribute), 131
 extract_value() (galaxy.tools.test.ParamContext method), 189
 extraction_error() (pkg_resources.ResourceManager method), 361
 extraction_path (pkg_resources.ResourceManager attribute), 362
 ExtractionError, 364
 extras (pkg_resources.Distribution attribute), 363
 ez_setup (galaxy.eggs.scramble.ScrambleEgg attribute), 102
 ez_setup_url (galaxy.eggs.scramble.ScrambleEgg attribute), 102
F
 fail() (galaxy.jobs.JobWrapper method), 114
 fail() (galaxy.jobs.TaskWrapper method), 117
 fail() (galaxy.model.WorkflowInvocation method), 150
 fail() (in module galaxy.tools.util.galaxyops), 225
 fail_job() (galaxy.jobs.runners.AsynchronousJobRunner method), 124
 fail_job() (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
 FAILURE (galaxy.web.framework.openid_manager.OpenIDManager attribute), 256
 FakeTrans (class in galaxy.jobs.deferred), 122
 Fasta (class in galaxy.datatypes.sequence), 77
 fastaNamedReader (class in galaxy_utils.sequence.fasta), 352
 fastaReader (class in galaxy_utils.sequence.fasta), 352
 fastaSequence (class in galaxy_utils.sequence.fasta), 352
 fastaWriter (class in galaxy_utils.sequence.fasta), 352
 Fastq (class in galaxy.datatypes.sequence), 78

fastqAggregator (class in galaxy_utils.sequence.fastq), 352
 fastqCombiner (class in galaxy_utils.sequence.fastq), 353
 FastqCSSanger (class in galaxy.datatypes.sequence), 79
 fastqCSSangerRead (class in galaxy_utils.sequence.fastq), 353
 fastqFakeFastaScoreReader (class in galaxy_utils.sequence.fastq), 353
 FastqIllumina (class in galaxy.datatypes.sequence), 79
 fastqIlluminaRead (class in galaxy_utils.sequence.fastq), 354
 fastqJoiner (class in galaxy_utils.sequence.fastq), 354
 fastqNamedReader (class in galaxy_utils.sequence.fastq), 354
 fastqReader (class in galaxy_utils.sequence.fastq), 354
 FastqSanger (class in galaxy.datatypes.sequence), 79
 fastqSangerRead (class in galaxy_utils.sequence.fastq), 354
 fastqSequencingRead (class in galaxy_utils.sequence.fastq), 354
 FastqSolexa (class in galaxy.datatypes.sequence), 79
 fastqSolexaRead (class in galaxy_utils.sequence.fastq), 355
 fastqSplitter (class in galaxy_utils.sequence.fastq), 355
 fastqVerboseErrorReader (class in galaxy_utils.sequence.fastq), 356
 fastqWriter (class in galaxy_utils.sequence.fastq), 356
 FeatureLocationIndex (class in galaxy.datatypes.tabular), 86
 fetch() (galaxy.eggs.Egg method), 101
 fetch_one() (galaxy.eggs.scramble.ScrambleEgg method), 102
 fetch_source() (galaxy.eggs.scramble.ScrambleEgg method), 102
 field (in module galaxy.forms.forms), 112
 field_as_html() (galaxy.model.FormDefinition method), 134
 field_param_values_ok() (galaxy.web.base.controller.UsesFormDefinitionsMixin method), 249
 fields() (galaxy.web.form_builder.AddressField static method), 241
 FieldStorage (class in galaxy.web.framework.base), 253
 file_ext (galaxy.datatypes.assembly.Amos attribute), 43
 file_ext (galaxy.datatypes.assembly.Velvet attribute), 44
 file_ext (galaxy.datatypes.binary.Ab1 attribute), 44
 file_ext (galaxy.datatypes.binary.Bam attribute), 45
 file_ext (galaxy.datatypes.binary.Bcf attribute), 45
 file_ext (galaxy.datatypes.binary.CompressedArchive attribute), 46
 file_ext (galaxy.datatypes.binary.GeminiSQLite attribute), 47
 file_ext (galaxy.datatypes.binary.GenericAsn1Binary attribute), 47
 file_ext (galaxy.datatypes.binary.H5 attribute), 47
 file_ext (galaxy.datatypes.binary.Idat attribute), 47
 file_ext (galaxy.datatypes.binary.RData attribute), 47
 file_ext (galaxy.datatypes.binary.Scf attribute), 48
 file_ext (galaxy.datatypes.binary.Sff attribute), 48
 file_ext (galaxy.datatypes.binary.SQLite attribute), 47
 file_ext (galaxy.datatypes.binary.Sra attribute), 48
 file_ext (galaxy.datatypes.binary.TwoBit attribute), 49
 file_ext (galaxy.datatypes.binary.Xlsx attribute), 49
 file_ext (galaxy.datatypes.chrominfo.ChromInfo attribute), 49
 file_ext (galaxy.datatypes.coverage.LastzCoverage attribute), 49
 file_ext (galaxy.datatypes.data.GenericAsn1 attribute), 52
 file_ext (galaxy.datatypes.data.Newick attribute), 53
 file_ext (galaxy.datatypes.data.Nexus attribute), 53
 file_ext (galaxy.datatypes.data.Text attribute), 53
 file_ext (galaxy.datatypes.genetics.Affybatch attribute), 54
 file_ext (galaxy.datatypes.genetics.Eigenstratgeno attribute), 54
 file_ext (galaxy.datatypes.genetics.Eigenstratpca attribute), 55
 file_ext (galaxy.datatypes.genetics.Eset attribute), 55
 file_ext (galaxy.datatypes.genetics.Fped attribute), 55
 file_ext (galaxy.datatypes.genetics.Fphe attribute), 55
 file_ext (galaxy.datatypes.genetics.GenomeGraphs attribute), 55
 file_ext (galaxy.datatypes.genetics.IdIndep attribute), 58
 file_ext (galaxy.datatypes.genetics.Lped attribute), 56
 file_ext (galaxy.datatypes.genetics.MAlist attribute), 56
 file_ext (galaxy.datatypes.genetics.Pbed attribute), 56
 file_ext (galaxy.datatypes.genetics.Phe attribute), 56
 file_ext (galaxy.datatypes.genetics.Phenotype attribute), 56
 file_ext (galaxy.datatypes.genetics.Pphe attribute), 56
 file_ext (galaxy.datatypes.genetics.RexpBase attribute), 57
 file_ext (galaxy.datatypes.genetics.Rgenetics attribute), 58
 file_ext (galaxy.datatypes.genetics.rgFeatureList attribute), 58
 file_ext (galaxy.datatypes.genetics.rgSampleList attribute), 59
 file_ext (galaxy.datatypes.genetics.rgTabList attribute), 59
 file_ext (galaxy.datatypes.genetics.SNPMatrix attribute), 58
 file_ext (galaxy.datatypes.genetics.Snptest attribute), 58
 file_ext (galaxy.datatypes.images.Bmp attribute), 59
 file_ext (galaxy.datatypes.images.Eps attribute), 59
 file_ext (galaxy.datatypes.images.Gif attribute), 59
 file_ext (galaxy.datatypes.images.Gmaj attribute), 60
 file_ext (galaxy.datatypes.images.Html attribute), 60
 file_ext (galaxy.datatypes.images.Im attribute), 60

- `file_ext` (galaxy.datatypes.images.Jpg attribute), 61
- `file_ext` (galaxy.datatypes.images.Laj attribute), 61
- `file_ext` (galaxy.datatypes.images.Pbm attribute), 61
- `file_ext` (galaxy.datatypes.images.Pcd attribute), 61
- `file_ext` (galaxy.datatypes.images.Pcx attribute), 61
- `file_ext` (galaxy.datatypes.images.Pdf attribute), 61
- `file_ext` (galaxy.datatypes.images.Pgm attribute), 62
- `file_ext` (galaxy.datatypes.images.Png attribute), 62
- `file_ext` (galaxy.datatypes.images.Ppm attribute), 62
- `file_ext` (galaxy.datatypes.images.Psd attribute), 62
- `file_ext` (galaxy.datatypes.images.Rast attribute), 62
- `file_ext` (galaxy.datatypes.images.Rgb attribute), 62
- `file_ext` (galaxy.datatypes.images.Tiff attribute), 62
- `file_ext` (galaxy.datatypes.images.Xbm attribute), 63
- `file_ext` (galaxy.datatypes.images.Xpm attribute), 63
- `file_ext` (galaxy.datatypes.interval.Bed attribute), 63
- `file_ext` (galaxy.datatypes.interval.Bed12 attribute), 64
- `file_ext` (galaxy.datatypes.interval.Bed6 attribute), 64
- `file_ext` (galaxy.datatypes.interval.BedGraph attribute), 64
- `file_ext` (galaxy.datatypes.interval.BedStrict attribute), 64
- `file_ext` (galaxy.datatypes.interval.ChromatinInteractions attribute), 65
- `file_ext` (galaxy.datatypes.interval.CustomTrack attribute), 65
- `file_ext` (galaxy.datatypes.interval.ENCODEPeak attribute), 65
- `file_ext` (galaxy.datatypes.interval.Gff attribute), 66
- `file_ext` (galaxy.datatypes.interval.Gff3 attribute), 66
- `file_ext` (galaxy.datatypes.interval.Gtf attribute), 67
- `file_ext` (galaxy.datatypes.interval.Interval attribute), 68
- `file_ext` (galaxy.datatypes.interval.Wiggle attribute), 69
- `file_ext` (galaxy.datatypes.ngsindex.BowtieBaseIndex attribute), 73
- `file_ext` (galaxy.datatypes.ngsindex.BowtieColorIndex attribute), 74
- `file_ext` (galaxy.datatypes.ngsindex.BowtieIndex attribute), 74
- `file_ext` (galaxy.datatypes.qualityscore.QualityScore attribute), 74
- `file_ext` (galaxy.datatypes.qualityscore.QualityScore454 attribute), 74
- `file_ext` (galaxy.datatypes.qualityscore.QualityScoreIllumina attribute), 75
- `file_ext` (galaxy.datatypes.qualityscore.QualityScoreSolexa attribute), 75
- `file_ext` (galaxy.datatypes.qualityscore.QualityScoreSOLiD attribute), 75
- `file_ext` (galaxy.datatypes.sequence.Axt attribute), 77
- `file_ext` (galaxy.datatypes.sequence.csFasta attribute), 82
- `file_ext` (galaxy.datatypes.sequence.Fasta attribute), 77
- `file_ext` (galaxy.datatypes.sequence.Fastq attribute), 78
- `file_ext` (galaxy.datatypes.sequence.FastqCSSanger attribute), 79
- `file_ext` (galaxy.datatypes.sequence.FastqIllumina attribute), 79
- `file_ext` (galaxy.datatypes.sequence.FastqSanger attribute), 79
- `file_ext` (galaxy.datatypes.sequence.FastqSolexa attribute), 79
- `file_ext` (galaxy.datatypes.sequence.Lav attribute), 79
- `file_ext` (galaxy.datatypes.sequence.Maf attribute), 80
- `file_ext` (galaxy.datatypes.sequence.MafCustomTrack attribute), 80
- `file_ext` (galaxy.datatypes.sequence.RNADotPlotMatrix attribute), 81
- `file_ext` (galaxy.datatypes.sequence.SequenceSplitLocations attribute), 82
- `file_ext` (galaxy.datatypes.tabular.CSV attribute), 85
- `file_ext` (galaxy.datatypes.tabular.Eland attribute), 85
- `file_ext` (galaxy.datatypes.tabular.ElandMulti attribute), 86
- `file_ext` (galaxy.datatypes.tabular.FeatureLocationIndex attribute), 86
- `file_ext` (galaxy.datatypes.tabular.Pileup attribute), 86
- `file_ext` (galaxy.datatypes.tabular.Sam attribute), 87
- `file_ext` (galaxy.datatypes.tabular.Vcf attribute), 89
- `file_ext` (galaxy.datatypes.tracks.GeneTrack attribute), 90
- `file_ext` (galaxy.datatypes.xml.CisML attribute), 90
- `file_ext` (galaxy.datatypes.xml.GenericXml attribute), 90
- `file_ext` (galaxy.datatypes.xml.MEMEXml attribute), 91
- `file_ext` (galaxy.datatypes.xml.Owl attribute), 91
- `file_ext` (galaxy.datatypes.xml.Phyloxml attribute), 91
- `file_iter()` (in module galaxy.util), 226
- `file_name` (galaxy.datatypes.metadata.MetadataTempFile attribute), 73
- `file_name` (galaxy.model.Dataset attribute), 129
- `file_name` (galaxy.model.DatasetInstance attribute), 131
- `file_name` (galaxy.model.MetadataFile attribute), 143
- `file_path` (galaxy.model.Dataset attribute), 129
- `file_reader()` (in module galaxy.util), 226
- `file_ready()` (galaxy.objectstore.NestedObjectStore method), 170
- `file_ready()` (galaxy.objectstore.ObjectStore method), 171
- `FileField` (class in galaxy.web.form_builder), 243
- `FileMetadata` (class in pkg_resources), 366
- `FileParameter` (class in galaxy.datatypes.metadata), 70
- `FileToolParameter` (class in galaxy.tools.parameters.basic), 202
- `fill_in_new_state()` (galaxy.tools.Tool method), 185
- `fill_region_alignment()` (in module galaxy.tools.util.maf_utilities), 223
- `fill_template()` (in module galaxy.util.template), 236
- `Filter` (class in galaxy.tools.parameters.dynamic_options), 210
- `filter()` (galaxy.web.framework.helpers.grids.CommunityTagsColumn method), 258

[find_tools_in_tool_shed\(\)](#) (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 312
[find_workflows_in_tool_shed\(\)](#) (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 312
[finish\(\)](#) (galaxy.jobs.JobWrapper method), 115
[finish\(\)](#) (galaxy.jobs.TaskWrapper method), 117
[finish_job\(\)](#) (galaxy.jobs.runners.AsynchronousJobRunner method), 124
[finish_job\(\)](#) (galaxy.jobs.runners.cli.ShellJobRunner method), 125
[finish_job\(\)](#) (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
[finished](#) (galaxy.model.Job attribute), 138
[first_dataset_instance\(\)](#) (galaxy.model.DatasetCollectionElement method), 130
[fitness_and_quality_parsed\(\)](#) (in module mimeparse), 358
[fixup_namespace_packages\(\)](#) (in module pkg_resources), 368
[flatten\(\)](#) (galaxy.util.Params method), 225
[flatten\(\)](#) (in module galaxy.web.framework.base), 256
[FloatToolParameter](#) (class in galaxy.tools.parameters.basic), 202
[flush\(\)](#) (galaxy.tools.util.maf_utilities.RegionAlignment method), 222
[flush\(\)](#) (galaxy.tools.util.maf_utilities.TempFileHandler method), 223
[fn_filter_parsers](#) (galaxy.managers.base.ModelFilterParser attribute), 155
[folder_info\(\)](#) (galaxy.webapps.galaxy.controllers.library_common.LibraryCommonController method), 325
[folder_is_public\(\)](#) (galaxy.security.GalaxyRBACAgent method), 177
[folder_is_public\(\)](#) (galaxy.security.RBACAgent method), 180
[folder_is_unrestricted\(\)](#) (galaxy.security.GalaxyRBACAgent method), 177
[folder_permissions\(\)](#) (galaxy.webapps.galaxy.controllers.library_common.LibraryCommonController method), 325
[FolderContentsController](#) (class in galaxy.webapps.galaxy.api.folder_contents), 10, 275
[FolderManager](#) (class in galaxy.managers.folders), 160
[FoldersController](#) (class in galaxy.webapps.galaxy.api.folders), 11, 276
[for_state\(\)](#) (galaxy.tools.test.ParamContext method), 189
[for_state\(\)](#) (galaxy.tools.test.RootParamContext method), 190
[force_bed_field_count\(\)](#) (in module galaxy.datatypes.converters.interval_to_bedstrict_conversion), 93
[force_symlink\(\)](#) (in module galaxy.util), 226
[foreign_key_name](#) (galaxy.managers.base.ModelManager attribute), 156
[foreign_key_name](#) (galaxy.managers.hdas.HDAManager attribute), 163
[foreign_key_name](#) (galaxy.managers.histories.HistoryManager attribute), 164
[foreign_key_name](#) (galaxy.managers.roles.RoleManager attribute), 167
[foreignKey\(\)](#) (galaxy.util.inflection.Base method), 231
[foreignKey\(\)](#) (galaxy.util.inflection.Inflector method), 232
[format](#) (galaxy.web.framework.middleware.translogger.TransLogger attribute), 265
[format](#) (galaxy_utils.sequence.fastq.fastqCSSangerRead attribute), 353
[format](#) (galaxy_utils.sequence.fastq.fastqIlluminaRead attribute), 354
[format](#) (galaxy_utils.sequence.fastq.fastqSangerRead attribute), 354
[format](#) (galaxy_utils.sequence.fastq.fastqSequencingRead attribute), 355
[format](#) (galaxy_utils.sequence.fastq.fastqSolexaRead attribute), 355
[format](#) (in module galaxy_utils.sequence.fastq), 356
[format](#) (in module galaxy_utils.sequence.vcf), 357
[format_bool\(\)](#) (in module galaxy.webapps.galaxy.controllers.page), 330
[formats](#) (galaxy.datatypes.display_applications.parameters.DisplayApplication attribute), 97
[FormatToolOutputAction](#) (class in galaxy.tools.parameters.output), 214
[FormDefinition](#) (class in galaxy.model), 134
[FormDefinitionAddressFieldFactory](#) (class in galaxy.forms.forms), 110
[FormDefinitionApiController](#) (class in galaxy.webapps.galaxy.api.forms), 13, 278
[FormDefinitionCurrent](#) (class in galaxy.model), 134
[FormDefinitionFactory](#) (class in galaxy.forms.forms), 110
[FormDefinitionFieldFactory](#) (class in galaxy.forms.forms), 110
[FormDefinitionHistoryFieldFactory](#) (class in galaxy.forms.forms), 111
[FormDefinitionPasswordFieldFactory](#) (class in galaxy.forms.forms), 111
[FormDefinitionSelectFieldFactory](#) (class in galaxy.forms.forms), 111
[FormDefinitionTextFieldFactory](#) (class in galaxy.forms.forms), 111
[FormDefinitionWorkflowFieldFactory](#) (class in galaxy.forms.forms), 111
[FormDefinitionWorkflowMappingFieldFactory](#) (class in galaxy.forms.forms), 112
[Forms](#) (class in galaxy.webapps.galaxy.controllers.forms), 318

forms_grid (galaxy.webapps.galaxy.controllers.forms.Formsfrom_elem() (galaxy.forms.forms.FormDefinitionFieldFactory attribute), 318 method), 111
 FormsGrid (class in galaxy.webapps.galaxy.controllers.forms)from_elem() (galaxy.forms.forms.FormDefinitionHistoryFieldFactory method), 111
 FormsGrid.DescriptionColumn (class in galaxy.webapps.galaxy.controllers.forms), from_elem() (galaxy.forms.forms.FormDefinitionPasswordFieldFactory method), 111
 FormsGrid.NameColumn (class in galaxy.webapps.galaxy.controllers.forms), from_elem() (galaxy.forms.forms.FormDefinitionSelectFieldFactory method), 111
 FormsGrid.TypeColumn (class in galaxy.webapps.galaxy.controllers.forms), from_elem() (galaxy.forms.forms.FormDefinitionTextFieldFactory method), 111
 FormsGrid.TypeColumn (class in galaxy.webapps.galaxy.controllers.forms), from_elem() (galaxy.forms.forms.FormDefinitionWorkflowFieldFactory method), 111
 FormsGrid.TypeColumn (class in galaxy.webapps.galaxy.controllers.forms), from_elem() (galaxy.forms.forms.FormDefinitionWorkflowMappingFieldFactory method), 111
 FormValues (class in galaxy.model), 134
 Fped (class in galaxy.datatypes.genetics), 55 from_elem() (galaxy.openid.providers.OpenIDProvider class method), 173
 Fphe (class in galaxy.datatypes.genetics), 55
 from_dict() (galaxy.visualization.genomes.GenomeRegion static method), 237 from_elem() (galaxy.openid.providers.OpenIDProviders class method), 173
 from_dict() (galaxy.workflow.modules.SimpleWorkflowModule class method), 348 from_elem() (galaxy.sample_tracking.request_types.RequestTypeFactory method), 175
 from_dict() (galaxy.workflow.modules.ToolModule class method), 349 from_elem() (galaxy.sample_tracking.sample.SampleStateFactory method), 175
 from_dict() (galaxy.workflow.modules.WorkflowModule class method), 350 from_elem() (galaxy.tools.data.ToolDataTable class method), 193
 from_dict() (galaxy.workflow.modules.WorkflowModuleFactory class method), 351 from_elem() (galaxy.tools.parameters.output.ToolOutputAction class method), 215
 from_elem() (galaxy.datatypes.display_applications.application_from_display_application tools.parameters.output.ToolOutputActionConditional class method), 96 class method), 216
 from_elem() (galaxy.datatypes.display_applications.application_from_display_application tools.parameters.output.ToolOutputActionOption class method), 96 class method), 216
 from_elem() (galaxy.datatypes.display_applications.parameter_from_display_application tools.parameters.output.ToolOutputActionOptionFilter class method), 97 class method), 216
 from_elem() (galaxy.external_services.actions.ExternalServiceAction from_action() (galaxy.tools.parameters.dynamic_options.Filter class method), 106 class method), 210
 from_elem() (galaxy.external_services.parameters.ExternalServiceParameter from_action() (galaxy.tools.parameters.input_translation.ToolInputTranslator class method), 107 class method), 214
 from_elem() (galaxy.external_services.result_handlers.basic_from_action() (galaxy.tools.parameters.input_translation.ToolInputTranslator class method), 110 class method), 218
 from_elem() (galaxy.external_services.result_handlers.basic_from_action() (galaxy.tools.parameters.input_translation.ToolInputTranslator class method), 110 class method), 218
 from_elem() (galaxy.external_services.service.BooleanExternalServiceActionGroupWhen parameters.validation.EmptyTextfieldValidator class method), 108 class method), 218
 from_elem() (galaxy.external_services.service.ExternalServiceActionGroupWhen parameters.validation.ExpressionValidator class method), 108 class method), 219
 from_elem() (galaxy.external_services.service.ExternalServiceActionGroupWhen parameters.validation.InRangeValidator class method), 108 class method), 219
 from_elem() (galaxy.external_services.service.ItemIsInstanceOfExternalServiceActionGroupWhen parameters.validation.LengthValidator class method), 109 class method), 220
 from_elem() (galaxy.external_services.service.ValueExternalServiceActionGroupWhen parameters.validation.MetadataInDataTableColumnValidator class method), 109 class method), 220
 from_elem() (galaxy.forms.forms.FormDefinitionAddressFieldFactory from_factory() (galaxy.tools.parameters.validation.MetadataInFileColumnValidator class method), 110 class method), 220
 from_elem() (galaxy.forms.forms.FormDefinitionFactory from_element() (galaxy.tools.parameters.validation.MetadataValidator class method), 110 class method), 221

[from_element\(\) \(galaxy.tools.parameters.validation.NoOptionsValidation class method\), 221](#)
[from_element\(\) \(galaxy.tools.parameters.validation.RegexValidation class method\), 221](#)
[from_element\(\) \(galaxy.tools.parameters.validation.UnspecifiedValidation class method\), 221](#)
[from_element\(\) \(galaxy.tools.parameters.validation.Validation class method\), 221](#)
[from_external_value\(\) \(galaxy.datatypes.metadata.FileParameter method\), 70](#)
[from_external_value\(\) \(galaxy.datatypes.metadata.MetadataParameter method\), 72](#)
[from_file\(\) \(galaxy.datatypes.display_applications.application_display_output.ActionOption \(class in galaxy.tools.parameters.output\), 214](#)
[from_file\(\) \(galaxy.openid.providers.OpenIDProvider class method\), 173](#)
[from_file\(\) \(galaxy.openid.providers.OpenIDProviders class method\), 173](#)
[from_filename\(\) \(pkg_resources.Distribution class method\), 363](#)
[from_html\(\) \(galaxy.tools.parameters.basic.BaseURLToolParameter method\), 197](#)
[from_html\(\) \(galaxy.tools.parameters.basic.BooleanToolParameter method\), 197](#)
[from_html\(\) \(galaxy.tools.parameters.basic.ColumnListParameter method\), 198](#)
[from_html\(\) \(galaxy.tools.parameters.basic.DataCollectionToolParameter method\), 199](#)
[from_html\(\) \(galaxy.tools.parameters.basic.DataToolParameter method\), 199](#)
[from_html\(\) \(galaxy.tools.parameters.basic.DrillDownSelectToolParameter method\), 201](#)
[from_html\(\) \(galaxy.tools.parameters.basic.FileToolParameter method\), 202](#)
[from_html\(\) \(galaxy.tools.parameters.basic.FloatToolParameter method\), 203](#)
[from_html\(\) \(galaxy.tools.parameters.basic.FTPFileToolParameter method\), 202](#)
[from_html\(\) \(galaxy.tools.parameters.basic.IntegerToolParameter method\), 205](#)
[from_html\(\) \(galaxy.tools.parameters.basic.LibraryDatasetToolParameter method\), 205](#)
[from_html\(\) \(galaxy.tools.parameters.basic.SelectToolParameter method\), 206](#)
[from_html\(\) \(galaxy.tools.parameters.basic.ToolParameter method\), 207](#)
[from_JSON\(\) \(galaxy.datatypes.metadata.MetadataTempFile class method\), 73](#)
[from_json\(\) \(galaxy.tools.parameters.basic.BooleanToolParameter method\), 197](#)
[from_json\(\) \(galaxy.tools.parameters.basic.ToolParameter method\), 207](#)
[from_JSON_dict\(\) \(galaxy.datatypes.metadata.MetadataCollection method\), 71](#)
[from_validation\(\) \(pkg_resources.Distribution class method\), 363](#)
[from_toolstr\(\) \(galaxy.visualization.genomes.GenomeRegion static method\), 237](#)
[from_workflow_step\(\) \(galaxy.workflow.modules.SimpleWorkflowModule class method\), 348](#)
[from_workflow_step\(\) \(galaxy.workflow.modules.ToolModule class method\), 349](#)
[from_workflow_step\(\) \(galaxy.workflow.modules.WorkflowModule class method\), 350](#)
[from_workflow_step\(\) \(galaxy.workflow.modules.WorkflowModuleFactory method\), 351](#)
[FromDisplayApplicationOutputActionOption \(class in galaxy.tools.parameters.output\), 214](#)
[FromFileToolOutputActionOption \(class in galaxy.tools.parameters.output\), 214](#)
[FromParamToolOutputActionOption \(class in galaxy.tools.parameters.output\), 214](#)
[FtpDataTransferFactory \(class in galaxy.sample_tracking.data_transfer\), 174](#)
[FTPFileField \(class in galaxy.web.form_builder\), 243](#)
[FTPFileToolParameter \(class in galaxy.tools.parameters.basic\), 202](#)
[full_delete\(\) \(galaxy.model.Dataset method\), 129](#)
[funcstd_string\(\) \(in module galaxy.web.framework.middleware.profile\), 264](#)

G

[galaxy \(module\), 42](#)
[galaxy-admin \(module\), 43](#)
[galaxy.config \(module\), 42](#)
[galaxy.datatypes.assembly \(module\), 43](#)
[galaxy.datatypes.binary \(module\), 44](#)
[galaxy.datatypes.checkers \(module\), 49](#)
[galaxy.datatypes.chrominfo \(module\), 49](#)
[galaxy.datatypes.converters.bed_to_gff_converter \(module\), 91](#)
[galaxy.datatypes.converters.bgzip \(module\), 92](#)
[galaxy.datatypes.converters.fasta_to_len \(module\), 92](#)
[galaxy.datatypes.converters.fasta_to_tabular_converter \(module\), 92](#)
[galaxy.datatypes.converters.fastq_to_fqtc \(module\), 92](#)
[galaxy.datatypes.converters.fastqsolexa_to_fasta_converter \(module\), 92](#)
[galaxy.datatypes.converters.fastqsolexa_to_qual_converter \(module\), 92](#)
[galaxy.datatypes.converters.gff_to_bed_converter \(module\), 92](#)
[galaxy.datatypes.converters.gff_to_interval_index_converter \(module\), 93](#)
[galaxy.datatypes.converters.interval_to_bed_converter \(module\), 93](#)

galaxy.datatypes.converters.interval_to_bedstrict_converter (module), 93
galaxy.datatypes.converters.interval_to_coverage (module), 93
galaxy.datatypes.converters.interval_to_fli (module), 93
galaxy.datatypes.converters.interval_to_interval_index_converter (module), 94
galaxy.datatypes.converters.interval_to_tabix_converter (module), 94
galaxy.datatypes.converters.lped_to_fped_converter (module), 94
galaxy.datatypes.converters.lped_to_pbed_converter (module), 94
galaxy.datatypes.converters.maf_to_fasta_converter (module), 94
galaxy.datatypes.converters.maf_to_interval_converter (module), 94
galaxy.datatypes.converters.pbed_ldreduced_converter (module), 95
galaxy.datatypes.converters.pbed_to_lped_converter (module), 95
galaxy.datatypes.converters.picard_interval_list_to_bed6_converter (module), 95
galaxy.datatypes.converters.sam_to_bam (module), 95
galaxy.datatypes.converters.vcf_to_interval_index_converter (module), 95
galaxy.datatypes.converters.vcf_to_vcf_bgzip (module), 96
galaxy.datatypes.converters.wiggle_to_array_tree_converter (module), 96
galaxy.datatypes.converters.wiggle_to_simple_converter (module), 96
galaxy.datatypes.coverage (module), 49
galaxy.datatypes.data (module), 50
galaxy.datatypes.display_applications.application (module), 96
galaxy.datatypes.display_applications.parameters (module), 97
galaxy.datatypes.display_applications.util (module), 98
galaxy.datatypes.genetics (module), 54
galaxy.datatypes.images (module), 59
galaxy.datatypes.interval (module), 63
galaxy.datatypes.metadata (module), 70
galaxy.datatypes.ngsindex (module), 73
galaxy.datatypes.qualityscore (module), 74
galaxy.datatypes.registry (module), 75
galaxy.datatypes.sequence (module), 76
galaxy.datatypes.sniff (module), 82
galaxy.datatypes.tabular (module), 85
galaxy.datatypes.tracks (module), 90
galaxy.datatypes.util (module), 98
galaxy.datatypes.util.gff_util (module), 98
galaxy.datatypes.util.image_util (module), 100
galaxy.datatypes.xml (module), 90
galaxy.eggs (module), 100
galaxy.eggs.dist (module), 101
galaxy.eggs.scramble (module), 102
galaxy.exceptions (module), 103
galaxy.external_services.actions (module), 106
galaxy.external_services.parameters (module), 107
galaxy.external_services.result_handlers.basic (module), 109
galaxy.external_services.service (module), 108
galaxy.forms.forms (module), 110
galaxy.jobs (module), 112
galaxy.jobs.actions (module), 120
galaxy.jobs.actions.post (module), 120
galaxy.jobs.deferred (module), 122
galaxy.jobs.deferred.data_transfer (module), 123
galaxy.jobs.deferred.manual_data_transfer (module), 123
galaxy.jobs.deferred.pacific_biosciences_smrt_portal (module), 123
galaxy.jobs.handler (module), 117
galaxy.jobs.manager (module), 119
galaxy.jobs.mapper (module), 119
galaxy.jobs.runners (module), 123
galaxy.jobs.runners.cli (module), 125
galaxy.jobs.runners.condor (module), 126
galaxy.jobs.runners.drmaa (module), 126
galaxy.jobs.runners.local (module), 127
galaxy.jobs.runners.lwr (module), 127
galaxy.jobs.runners.tasks (module), 127
galaxy.jobs.splitters.basic (module), 128
galaxy.jobs.splitters.multi (module), 128
galaxy.jobs.transfer_manager (module), 119
galaxy.managers (module), 154
galaxy.managers.api_keys (module), 154
galaxy.managers.base (module), 154
galaxy.managers.citations (module), 158
galaxy.managers.collections (module), 159
galaxy.managers.collections_util (module), 159
galaxy.managers.context (module), 159
galaxy.managers.folders (module), 160
galaxy.managers.hdas (module), 162
galaxy.managers.histories (module), 164
galaxy.managers.lddas (module), 165
galaxy.managers.libraries (module), 166
galaxy.managers.roles (module), 167
galaxy.managers.tags (module), 167
galaxy.managers.workflows (module), 168
galaxy.model (module), 128
galaxy.model.item_attrs (module), 152
galaxy.model.migrate.check (module), 153
galaxy.model.orm (module), 153
galaxy.model.orm.logging_connection_proxy (module), 153
galaxy.objectstore (module), 169
galaxy.objectstore.s3_multipart_upload (module), 172

[galaxy.openid \(module\), 173](#)
[galaxy.openid.providers \(module\), 173](#)
[galaxy.quota \(module\), 173](#)
[galaxy.sample_tracking.data_transfer \(module\), 174](#)
[galaxy.sample_tracking.external_service_types \(module\), 175](#)
[galaxy.sample_tracking.request_types \(module\), 175](#)
[galaxy.sample_tracking.sample \(module\), 175](#)
[galaxy.security \(module\), 175](#)
[galaxy.security.validate_user_input \(module\), 181](#)
[galaxy.tags \(module\), 181](#)
[galaxy.tags.tag_handler \(module\), 181](#)
[galaxy.tools \(module\), 182](#)
[galaxy.tools.actions \(module\), 190](#)
[galaxy.tools.actions.history_imp_exp \(module\), 191](#)
[galaxy.tools.actions.metadata \(module\), 191](#)
[galaxy.tools.actions.upload \(module\), 191](#)
[galaxy.tools.actions.upload_common \(module\), 191](#)
[galaxy.tools.data \(module\), 192](#)
[galaxy.tools.deps \(module\), 195](#)
[galaxy.tools.exception_handling \(module\), 189](#)
[galaxy.tools.imp_exp \(module\), 195](#)
[galaxy.tools.imp_exp.export_history \(module\), 196](#)
[galaxy.tools.imp_exp.unpack_tar_gz_archive \(module\), 196](#)
[galaxy.tools.parameters \(module\), 196](#)
[galaxy.tools.parameters.basic \(module\), 197](#)
[galaxy.tools.parameters.dynamic_options \(module\), 208](#)
[galaxy.tools.parameters.grouping \(module\), 211](#)
[galaxy.tools.parameters.input_translation \(module\), 213](#)
[galaxy.tools.parameters.output \(module\), 214](#)
[galaxy.tools.parameters.sanitize \(module\), 217](#)
[galaxy.tools.parameters.validation \(module\), 218](#)
[galaxy.tools.search \(module\), 222](#)
[galaxy.tools.test \(module\), 189](#)
[galaxy.tools.util \(module\), 222](#)
[galaxy.tools.util.galaxyops \(module\), 225](#)
[galaxy.tools.util.maf_utilities \(module\), 222](#)
[galaxy.util \(module\), 225](#)
[galaxy.util.aliaspickler \(module\), 229](#)
[galaxy.util.backports \(module\), 237](#)
[galaxy.util.backports.importlib \(module\), 237](#)
[galaxy.util.bunch \(module\), 230](#)
[galaxy.util.debugging \(module\), 230](#)
[galaxy.util.expressions \(module\), 230](#)
[galaxy.util.hash_util \(module\), 230](#)
[galaxy.util.heartbeat \(module\), 231](#)
[galaxy.util.inflection \(module\), 231](#)
[galaxy.util.json \(module\), 233](#)
[galaxy.util.lrucache \(module\), 234](#)
[galaxy.util.none_like \(module\), 235](#)
[galaxy.util.odict \(module\), 235](#)
[galaxy.util.sanitize_html \(module\), 235](#)
[galaxy.util.streamball \(module\), 236](#)
[galaxy.util.template \(module\), 236](#)
[galaxy.util.topsort \(module\), 236](#)
[galaxy.visualization \(module\), 237](#)
[galaxy.visualization.data_providers \(module\), 238](#)
[galaxy.visualization.data_providers.basic \(module\), 238](#)
[galaxy.visualization.data_providers.phyloviz \(module\), 239](#)
[galaxy.visualization.data_providers.phyloviz.baseparser \(module\), 239](#)
[galaxy.visualization.data_providers.phyloviz.newickparser \(module\), 240](#)
[galaxy.visualization.data_providers.phyloviz.nexusparser \(module\), 240](#)
[galaxy.visualization.data_providers.phyloviz.phyloxmlparser \(module\), 241](#)
[galaxy.visualization.genome \(module\), 241](#)
[galaxy.visualization.genomes \(module\), 237](#)
[galaxy.visualization.tracks \(module\), 241](#)
[galaxy.web \(module\), 241](#)
[galaxy.web.base.controller \(module\), 246](#)
[galaxy.web.base.controllers.admin \(module\), 251](#)
[galaxy.web.form_builder \(module\), 241](#)
[galaxy.web.framework \(module\), 253](#)
[galaxy.web.framework.base \(module\), 253](#)
[galaxy.web.framework.helpers \(module\), 257](#)
[galaxy.web.framework.helpers.grid \(module\), 257](#)
[galaxy.web.framework.middleware \(module\), 264](#)
[galaxy.web.framework.middleware.profile \(module\), 264](#)
[galaxy.web.framework.middleware.remoteuser \(module\), 265](#)
[galaxy.web.framework.middleware.static \(module\), 265](#)
[galaxy.web.framework.middleware.translogger \(module\), 265](#)
[galaxy.web.framework.middleware.xforwardedhost \(module\), 265](#)
[galaxy.web.framework.openid_manager \(module\), 256](#)
[galaxy.web.params \(module\), 246](#)
[galaxy.web.security \(module\), 266](#)
[galaxy.webapps \(module\), 266](#)
[galaxy.webapps.galaxy.api.annotations \(module\), 7, 272](#)
[galaxy.webapps.galaxy.api.authenticate \(module\), 8, 273](#)
[galaxy.webapps.galaxy.api.configuration \(module\), 8, 273](#)
[galaxy.webapps.galaxy.api.dataset_collections \(module\), 9, 274](#)
[galaxy.webapps.galaxy.api.datatypes \(module\), 9, 274](#)
[galaxy.webapps.galaxy.api.extended_metadata \(module\), 10, 275](#)
[galaxy.webapps.galaxy.api.folder_contents \(module\), 10, 275](#)
[galaxy.webapps.galaxy.api.folders \(module\), 11, 276](#)
[galaxy.webapps.galaxy.api.forms \(module\), 13, 278](#)
[galaxy.webapps.galaxy.api.genomes \(module\), 13, 278](#)
[galaxy.webapps.galaxy.api.group_roles \(module\), 13, 278](#)

- galaxy.webapps.galaxy.api.group_users (module), 14, 279
- galaxy.webapps.galaxy.api.groups (module), 14, 279
- galaxy.webapps.galaxy.api.histories (module), 14, 279
- galaxy.webapps.galaxy.api.history_contents (module), 17, 282
- galaxy.webapps.galaxy.api.item_tags (module), 20, 284
- galaxy.webapps.galaxy.api.job_files (module), 20, 285
- galaxy.webapps.galaxy.api.jobs (module), 21, 286
- galaxy.webapps.galaxy.api.lda_datasets (module), 23, 287
- galaxy.webapps.galaxy.api.libraries (module), 25, 290
- galaxy.webapps.galaxy.api.library_contents (module), 28, 293
- galaxy.webapps.galaxy.api.metrics (module), 30, 295
- galaxy.webapps.galaxy.api.page_revisions (module), 31, 295
- galaxy.webapps.galaxy.api.pages (module), 31, 296
- galaxy.webapps.galaxy.api.provenance (module), 32, 297
- galaxy.webapps.galaxy.api.quotas (module), 33, 297
- galaxy.webapps.galaxy.api.request_types (module), 33, 297
- galaxy.webapps.galaxy.api.requests (module), 33, 298
- galaxy.webapps.galaxy.api.roles (module), 34, 298
- galaxy.webapps.galaxy.api.samples (module), 34, 298
- galaxy.webapps.galaxy.api.tool_data (module), 34, 299
- galaxy.webapps.galaxy.api.tool_shed_repositories (module), 35, 299
- galaxy.webapps.galaxy.api.users (module), 38, 302
- galaxy.webapps.galaxy.api.visualizations (module), 38, 302
- galaxy.webapps.galaxy.api.workflows (module), 39, 303
- galaxy.webapps.galaxy.controllers (module), 306
- galaxy.webapps.galaxy.controllers.admin (module), 306
- galaxy.webapps.galaxy.controllers.admin_toolshed (module), 312
- galaxy.webapps.galaxy.controllers.async (module), 314
- galaxy.webapps.galaxy.controllers.dataset (module), 314
- galaxy.webapps.galaxy.controllers.error (module), 317
- galaxy.webapps.galaxy.controllers.external_service (module), 317
- galaxy.webapps.galaxy.controllers.external_services (module), 318
- galaxy.webapps.galaxy.controllers.forms (module), 318
- galaxy.webapps.galaxy.controllers.history (module), 319
- galaxy.webapps.galaxy.controllers.library (module), 323
- galaxy.webapps.galaxy.controllers.library_admin (module), 324
- galaxy.webapps.galaxy.controllers.library_common (module), 325
- galaxy.webapps.galaxy.controllers.mobile (module), 327
- galaxy.webapps.galaxy.controllers.page (module), 327
- galaxy.webapps.galaxy.controllers.request_type (module), 330
- galaxy.webapps.galaxy.controllers.requests (module), 332
- galaxy.webapps.galaxy.controllers.requests_admin (module), 332
- galaxy.webapps.galaxy.controllers.requests_common (module), 334
- galaxy.webapps.galaxy.controllers.root (module), 336
- galaxy.webapps.galaxy.controllers.tag (module), 337
- galaxy.webapps.galaxy.controllers.tool_runner (module), 337
- galaxy.webapps.galaxy.controllers.ucsc_proxy (module), 338
- galaxy.webapps.galaxy.controllers.user (module), 338
- galaxy.webapps.reports (module), 340
- galaxy.webapps.reports.app (module), 340
- galaxy.webapps.reports.config (module), 341
- galaxy.webapps.reports.controllers (module), 341
- galaxy.webapps.reports.controllers.jobs (module), 341
- galaxy.webapps.reports.controllers.root (module), 343
- galaxy.webapps.reports.controllers.sample_tracking (module), 343
- galaxy.webapps.reports.controllers.system (module), 345
- galaxy.webapps.reports.controllers.users (module), 345
- galaxy.webapps.reports.controllers.workflows (module), 345
- galaxy.workflow.modules (module), 347
- galaxy_directory() (in module galaxy.util), 226
- galaxy_lib_dir (galaxy.jobs.JobWrapper attribute), 115
- galaxy_system_pwent (galaxy.jobs.JobWrapper attribute), 115
- galaxy_utils.sequence.fasta (module), 352
- galaxy_utils.sequence.fastq (module), 352
- galaxy_utils.sequence.sequence (module), 356
- galaxy_utils.sequence.transform (module), 356
- galaxy_utils.sequence.vcf (module), 357
- GalaxyConfig (class in galaxy.eggs), 101
- GalaxyRBACAgent (class in galaxy.security), 175
- GalaxySession (class in galaxy.model), 134
- GalaxySessionToHistoryAssociation (class in galaxy.model), 134
- GalaxyTagManager (class in galaxy.managers.tags), 167
- gbrowse_links() (galaxy.datatypes.interval.Gff method), 66
- gbrowse_links() (galaxy.datatypes.interval.Wiggle method), 69
- GeminiSQLite (class in galaxy.datatypes.binary), 46
- generate_auto_primary_file() (galaxy.datatypes.data.Data method), 51
- generate_error() (galaxy.webapps.galaxy.controllers.root.RootController method), 336
- generate_json_error() (galaxy.webapps.galaxy.controllers.root.RootController method), 336
- generate_primary_file() (galaxy.datatypes.assembly.Velvet method), 44

[generate_primary_file\(\) \(galaxy.datatypes.genetics.RexpBase method\), 57](#)
[generate_primary_file\(\) \(galaxy.datatypes.genetics.Rgenetics method\), 58](#)
[generate_primary_file\(\) \(galaxy.datatypes.ngsindex.BowtieIndex method\), 74](#)
[generate_workflow_image\(\) \(galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method\), 313](#)
[generateJsonableDict\(\) \(galaxy.visualization.data_providers.phyloviz.bastphaser/PhyloTree method\), 240](#)
[GenericAsn1 \(class in galaxy.datatypes.data\), 52](#)
[GenericAsn1Binary \(class in galaxy.datatypes.binary\), 47](#)
[GenericXml \(class in galaxy.datatypes.xml\), 90](#)
[GeneTrack \(class in galaxy.datatypes.tracks\), 90](#)
[Genome \(class in galaxy.visualization.genomes\), 237](#)
[genome_build\(\) \(galaxy.managers.base.ModelValidator method\), 157](#)
[GenomeBuildParameter \(class in galaxy.tools.parameters.basic\), 203](#)
[GenomeGraphs \(class in galaxy.datatypes.genetics\), 55](#)
[GenomeIndexTool \(class in galaxy.tools\), 183](#)
[GenomeIndexToolData \(class in galaxy.model\), 134](#)
[GenomeRegion \(class in galaxy.visualization.genomes\), 237](#)
[Genomes \(class in galaxy.visualization.genomes\), 237](#)
[GenomesController \(class in galaxy.webapps.galaxy.api.genomes\), 13, 278](#)
[genomic_region_dataprovider\(\) \(galaxy.datatypes.binary.Bam method\), 45](#)
[genomic_region_dataprovider\(\) \(galaxy.datatypes.interval.Gff method\), 66](#)
[genomic_region_dataprovider\(\) \(galaxy.datatypes.interval.Interval method\), 68](#)
[genomic_region_dataprovider\(\) \(galaxy.datatypes.tabular.Pileup method\), 86](#)
[genomic_region_dataprovider\(\) \(galaxy.datatypes.tabular.Sam method\), 87](#)
[genomic_region_dataprovider\(\) \(galaxy.datatypes.tabular.Vcf method\), 89](#)
[genomic_region_dict_dataprovider\(\) \(galaxy.datatypes.binary.Bam method\), 45](#)
[genomic_region_dict_dataprovider\(\) \(galaxy.datatypes.interval.Gff method\), 66](#)
[genomic_region_dict_dataprovider\(\) \(galaxy.datatypes.interval.Interval method\), 68](#)
[genomic_region_dict_dataprovider\(\) \(galaxy.datatypes.tabular.Pileup method\), 86](#)
[genomic_region_dict_dataprovider\(\) \(galaxy.datatypes.tabular.Sam method\), 87](#)
[genomic_region_dict_dataprovider\(\) \(galaxy.datatypes.tabular.Vcf method\), 90](#)
[GenomicRegionAlignment \(class in galaxy.tools.util.maf_utilities\), 222](#)
[get\(\) \(galaxy.config.Configuration method\), 42](#)
[get\(\) \(galaxy.datatypes.metadata.MetadataCollection method\), 71](#)
[get\(\) \(galaxy.datatypes.metadata.MetadataElementSpec method\), 71](#)
[get\(\) \(galaxy.managers.folders.FolderManager method\), 162](#)
[get\(\) \(galaxy.managers.lddas.LDDAManager method\), 165](#)
[get\(\) \(galaxy.managers.libraries.LibraryManager method\), 166](#)
[get\(\) \(galaxy.managers.roles.RoleManager method\), 167](#)
[get\(\) \(galaxy.openid.providers.OpenIDProviders method\), 173](#)
[get\(\) \(galaxy.tools.data.ToolDataTableManager method\), 194](#)
[get\(\) \(galaxy.util.bunch.Bunch method\), 230](#)
[get\(\) \(galaxy.util.Params method\), 225](#)
[get\(\) \(galaxy.webapps.reports.config.Configuration method\), 341](#)
[get\(\) \(galaxy_utils.sequence.fasta.fastaNamedReader method\), 352](#)
[get\(\) \(galaxy_utils.sequence.fastq.fastqFakeFastaScoreReader method\), 353](#)
[get\(\) \(galaxy_utils.sequence.fastq.fastqNamedReader method\), 354](#)
[get_accepted_filters\(\) \(galaxy.web.framework.helpers.grids.DeletedColumn method\), 259](#)
[get_accepted_filters\(\) \(galaxy.web.framework.helpers.grids.GridColumn method\), 260](#)
[get_accepted_filters\(\) \(galaxy.web.framework.helpers.grids.SharingStatusC method\), 263](#)
[get_accepted_filters\(\) \(galaxy.web.framework.helpers.grids.StateColumn method\), 263](#)
[get_accepted_filters\(\) \(galaxy.webapps.galaxy.controllers.dataset.HistoryDa method\), 316](#)
[get_access_roles\(\) \(galaxy.managers.libraries.LibraryManager method\), 166](#)
[get_access_roles\(\) \(galaxy.model.Dataset method\), 129](#)
[get_access_roles\(\) \(galaxy.model.HistoryDatasetAssociation method\), 136](#)
[get_access_roles\(\) \(galaxy.model.Library method\), 141](#)
[get_access_roles\(\) \(galaxy.model.LibraryDatasetDatasetAssociation method\), 142](#)
[get_accessible_libraries\(\) \(galaxy.security.GalaxyRBACAgent method\), 177](#)
[get_accessible_libraries\(\) \(galaxy.security.RBACAgent method\), 180](#)

get_accessible_request_types() (galaxy.security.GalaxyRBACAgent method), 177
 get_accessible_request_types() (galaxy.security.RBACAgent method), 180
 get_action() (galaxy.security.RBACAgent method), 180
 get_action_access_link() (galaxy.external_services.actions.ExternalServiceWebAction method), 106
 get_action_access_link() (galaxy.external_services.actions.ExternalServiceWebAction method), 107
 get_action_access_link() (galaxy.external_services.actions.PopulateExternalServiceActions method), 107
 get_action_by_name() (galaxy.external_services.service.PopulateExternalService method), 109
 get_actions() (galaxy.security.RBACAgent method), 180
 get_actions_for_items() (galaxy.security.GalaxyRBACAgent method), 177
 get_activation_token() (galaxy.webapps.galaxy.controllers.user.User method), 339
 get_active_folders() (galaxy.model.Library method), 141
 get_add_list() (galaxy.jobs.actions.post.ActionBox class method), 120
 get_add_roles() (galaxy.managers.libraries.LibraryManager method), 166
 get_all_forms() (galaxy.web.base.controller.UsesFormDefinitionsMixin method), 249
 get_all_forms_by_type() (galaxy.web.base.controller.UsesFormDefinitionsMixin method), 249
 get_all_roles() (galaxy.security.GalaxyRBACAgent method), 177
 get_all_roles() (galaxy.security.RBACAgent method), 180
 get_amount() (galaxy.model.Quota method), 144
 get_annotation_async() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315
 get_api_key() (galaxy.webapps.galaxy.api.authenticate.AuthenticationController method), 8, 273
 get_ascii_quality_scores() (galaxy_utils.sequence.fastq.fastqSequencingRead method), 355
 get_ascii_quality_scores_len() (galaxy_utils.sequence.fastq.fastqSequencingRead method), 355
 get_ascii_range() (galaxy_utils.sequence.fastq.fastqAggregator method), 352
 get_attributes_from_fasta_header() (in module galaxy.tools.util.maf_utilities), 223
 get_available_tracks() (galaxy.datatypes.registry.Registry method), 75
 get_ave_item_rating_data() (galaxy.model.item_attrs.UsesItemRatings method), 152
 get_base_counts_for_column() (galaxy_utils.sequence.fastq.fastqAggregator method), 352
 get_base_dir() (galaxy.tools.data.TabularToolDataField method), 192
 get_base_path() (galaxy.tools.data.TabularToolDataField method), 192
 get_bibtex() (galaxy.managers.citations.DoiCache method), 158
 get_bool() (galaxy.config.Configuration method), 42
 get_bulk() (galaxy.visualization.genomes.Genomes method), 237
 get_bulk_path() (ServiceActions method), 362
 get_headers() (in module galaxy.util), 226
 get_check_interval() (galaxy.model.DeferredJob method), 133
 get_child_by_designation() (galaxy.model.DatasetInstance method), 131
 get_chopped_blocks_for_region() (in module galaxy.tools.util.maf_utilities), 223
 get_chopped_blocks_with_index_offset_for_region() (in module galaxy.tools.util.maf_utilities), 223
 get_chunk() (galaxy.datatypes.tabular.TabularData method), 89
 get_class() (galaxy.web.base.controller.BaseController method), 147
 get_class() (in module galaxy.managers.base), 158
 get_class_by_format() (galaxy_utils.sequence.fastq.fastqSequencingRead class method), 355
 get_class_by_format() (galaxy_utils.sequence.vcf.VariantCall class method), 357
 get_cli_plugins() (galaxy.jobs.runners.cli.ShellJobRunner method), 127
 get_client() (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
 get_client_from_state() (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
 get_client_from_wrapper() (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
 get_column_list() (galaxy.tools.parameters.basic.ColumnListParameter method), 198
 get_column_name_list() (galaxy.tools.data.TabularToolDataTable method), 193
 get_command_line() (galaxy.jobs.JobWrapper method), 115
 get_command_line() (galaxy.jobs.TaskWrapper method), 117
 get_command_line() (galaxy.model.Job method), 138
 get_command_line() (galaxy.model.Task method), 146
 get_community_tags() (galaxy.managers.tags.TagManager method), 168
 get_component_associations()

(galaxy.security.GalaxyRBACAgent method), 177
 get_component_associations() (galaxy.security.RBACAgent method), 180
 get_components_by_src() (in module galaxy.tools.util.maf_utilities), 223
 get_components_by_src_start() (in module galaxy.tools.util.maf_utilities), 223
 get_composite_dataset_name() (galaxy.tools.parameters.grouping.UploadDataset method), 212
 get_composite_extensions() (galaxy.datatypes.registry.Registry method), 75
 get_composite_files() (galaxy.datatypes.data.Data method), 51
 get_comptypes() (in module galaxy.webapps.galaxy.controllers.library_common), 326
 get_config_dict() (galaxy.webapps.galaxy.api.configuration.ConfigurationController method), 8, 273
 get_config_form() (galaxy.jobs.actions.post.ChangeDatatypeAction class method), 120
 get_config_form() (galaxy.jobs.actions.post.ColumnSetAction class method), 120
 get_config_form() (galaxy.jobs.actions.post.DefaultJobAction class method), 120
 get_config_form() (galaxy.jobs.actions.post.DeleteDatasetAction class method), 121
 get_config_form() (galaxy.jobs.actions.post.DeleteIntermediatesAction class method), 121
 get_config_form() (galaxy.jobs.actions.post.EmailAction class method), 121
 get_config_form() (galaxy.jobs.actions.post.HideDatasetAction class method), 121
 get_config_form() (galaxy.jobs.actions.post.RenameDatasetAction class method), 121
 get_config_form() (galaxy.jobs.actions.post.SetMetadataAction class method), 122
 get_config_form() (galaxy.jobs.actions.post.TagDatasetAction class method), 122
 get_config_form() (galaxy.workflow.modules.SimpleWorkflowModule method), 349
 get_config_form() (galaxy.workflow.modules.ToolModule method), 349
 get_config_form() (galaxy.workflow.modules.WorkflowModule method), 350
 get_consumer() (galaxy.web.framework.openid_manager.OpenIDManager method), 256
 get_containing_library_from_library_dataset() (in module galaxy.webapps.galaxy.controllers.library_common), 326
 get_content_type() (galaxy.web.framework.base.Response method), 255
 get_converted_dataset() (galaxy.model.DatasetInstance method), 131
 get_converted_dataset_deps() (galaxy.model.DatasetInstance method), 131
 get_converted_files_by_type() (galaxy.model.DatasetInstance method), 131
 get_converter_by_target_type() (galaxy.datatypes.registry.Registry method), 75
 get_converter_types() (galaxy.datatypes.data.Data method), 51
 get_converter_types() (galaxy.model.DatasetInstance method), 131
 get_converters_by_datatype() (galaxy.datatypes.registry.Registry method), 75
 get_current() (galaxy.managers.histories.HistoryManager method), 164
 get_current_case() (galaxy.tools.parameters.grouping.ConditionalActionController method), 164
 get_current_cases() (galaxy.external_services.service.ExternalServiceAction method), 108
 get_current_form() (galaxy.webapps.galaxy.controllers.forms.Forms method), 318
 get_current_item() (galaxy.web.framework.helpers.grid.Grid method), 259
 get_current_item() (galaxy.webapps.galaxy.controllers.admin.UserListGrid method), 312
 get_current_item() (galaxy.webapps.galaxy.controllers.history.HistoryListGroup method), 322
 get_current_roles() (galaxy.managers.folders.FolderManager method), 162
 get_current_roles() (galaxy.managers.libraries.LibraryManager method), 166
 get_current_thread_object_dict() (in module galaxy.util.heartbeat), 231
 get_current_user_roles() (galaxy.jobs.deferred.FakeTrans method), 122
 get_current_user_roles() (galaxy.managers.context.ProvidesUserContext method), 160
 get_data() (galaxy.objectstore.DiskObjectStore method), 69
 get_data() (galaxy.objectstore.NestedObjectStore method), 170
 get_data() (galaxy.objectstore.ObjectStore method), 171
 get_data() (galaxy.visualization.data_providers.basic.BaseDataProvider method), 238
 get_data() (galaxy.visualization.data_providers.basic.ColumnDataProvider method), 238
 get_data() (galaxy.visualization.data_providers.phyloviz.PhylovizDataProvider method), 239
 get_data_inputs() (galaxy.workflow.modules.InputModule method), 348
 get_data_inputs() (galaxy.workflow.modules.PauseModule method), 348

[get_data_inputs\(\) \(galaxy.workflow.modules.ToolModule method\), 349](#)
[get_data_inputs\(\) \(galaxy.workflow.modules.WorkflowModule method\), 350](#)
[get_data_outputs\(\) \(galaxy.workflow.modules.InputDataCollectionModule method\), 347](#)
[get_data_outputs\(\) \(galaxy.workflow.modules.InputDataModule method\), 347](#)
[get_data_outputs\(\) \(galaxy.workflow.modules.PauseModule method\), 348](#)
[get_data_outputs\(\) \(galaxy.workflow.modules.ToolModule method\), 349](#)
[get_data_outputs\(\) \(galaxy.workflow.modules.WorkflowModule method\), 350](#)
[get_database_engine_options\(\) \(in module galaxy.config\), 42](#)
[get_database_engine_options\(\) \(in module galaxy.webapps.reports.config\), 341](#)
[get_dataset_collection\(\) \(galaxy.managers.collections.DatasetCollectionManager method\), 159](#)
[get_dataset_collection_instance\(\) \(galaxy.managers.collections.DatasetCollectionManager method\), 159](#)
[get_dataset_filename\(\) \(in module galaxy.tools.imp_exp.export_history\), 196](#)
[get_dataset_finish_context\(\) \(galaxy.jobs.JobWrapper method\), 115](#)
[get_dataset_finish_context\(\) \(galaxy.jobs.TaskWrapper method\), 117](#)
[get_dataset_metadata_key\(\) \(galaxy.datatypes.metadata.JobExternalOutputMetadataWrapper method\), 71](#)
[get_dataset_state\(\) \(galaxy.model.DatasetInstance method\), 131](#)
[get_datasources\(\) \(galaxy.model.DatasetInstance method\), 131](#)
[get_datatype\(\) \(galaxy.tools.parameters.grouping.UploadDataset method\), 212](#)
[get_datatype_by_extension\(\) \(galaxy.datatypes.registry.Registry method\), 75](#)
[get_datatype_class_by_name\(\) \(galaxy.datatypes.registry.Registry method\), 76](#)
[get_datatype_ext\(\) \(galaxy.tools.parameters.grouping.UploadDataset method\), 212](#)
[get_dbkey\(\) \(galaxy.model.DatasetInstance method\), 132](#)
[get_dbkeys\(\) \(galaxy.visualization.genomes.Genomes method\), 237](#)
[get_decimal_quality_scores\(\) \(galaxy_utils.sequence.fastq.fastqSequencingRead method\), 355](#)
[get_decimal_range\(\) \(galaxy_utils.sequence.fastq.fastqAggregator method\), 352](#)
[get_default_cache\(\) \(in module pkg_resources\), 359](#)
[get_default_history_by_trans\(\) \(galaxy.tools.DataManagerTool method\), 182](#)
[get_default_history_by_trans\(\) \(galaxy.tools.Tool method\), 185](#)
[get_dependencies\(\) \(galaxy.tools.parameters.basic.ColumnListParameter method\), 198](#)
[get_dependencies\(\) \(galaxy.tools.parameters.basic.DataToolParameter method\), 199](#)
[get_dependencies\(\) \(galaxy.tools.parameters.basic.DrillDownSelectToolParameter method\), 201](#)
[get_dependencies\(\) \(galaxy.tools.parameters.basic.SelectToolParameter method\), 206](#)
[get_dependencies\(\) \(galaxy.tools.parameters.basic.ToolParameter method\), 207](#)
[get_dependency_name\(\) \(galaxy.tools.parameters.dynamic_options.DataManagerTool method\), 209](#)
[get_dependency_name\(\) \(galaxy.tools.parameters.dynamic_options.Filter method\), 210](#)
[get_dependency_name\(\) \(galaxy.tools.parameters.dynamic_options.Parameter method\), 210](#)
[get_dependency_name\(\) \(galaxy.tools.parameters.dynamic_options.UniqueParameter method\), 211](#)
[get_dependency_names\(\) \(galaxy.tools.parameters.dynamic_options.DynamicOptions method\), 209](#)
[get_destination\(\) \(galaxy.jobs.JobConfiguration method\), 113](#)
[get_destinations\(\) \(galaxy.jobs.JobConfiguration method\), 113](#)
[get_disabled_str\(\) \(galaxy.web.form_builder.BaseField method\), 241](#)
[get_disk_size\(\) \(galaxy.model.History method\), 135](#)
[get_disk_size_bytes \(galaxy.model.History attribute\), 135](#)
[get_disk_usage\(\) \(galaxy.model.GalaxySession method\), 134](#)
[get_disk_usage\(\) \(galaxy.model.User method\), 148](#)
[get_disk_usage\(\) \(galaxy.webapps.reports.controllers.system.System method\), 345](#)
[get_display_application\(\) \(galaxy.datatypes.data.Data method\), 51](#)
[get_display_applications\(\) \(galaxy.model.DatasetInstance method\), 132](#)
[get_display_applications_by_dataset\(\) \(galaxy.datatypes.data.Data method\), 51](#)
[get_display_label\(\) \(galaxy.datatypes.data.Data method\), 51](#)
[get_display_links\(\) \(galaxy.datatypes.data.Data method\), 51](#)
[get_display_name\(\) \(galaxy.model.HasName method\), 135](#)
[get_display_sites\(\) \(galaxy.datatypes.registry.Registry method\), 76](#)
[get_display_text\(\) \(galaxy.web.form_builder.HistoryField method\), 132](#)

method), 244

get_display_text() (galaxy.web.form_builder.LibraryField method), 244

get_display_text() (galaxy.web.form_builder.WorkflowMappingField method), 246

get_display_types() (galaxy.datatypes.data.Data method), 51

get_display_url() (galaxy.datatypes.display_applications.application_display_application method), 96

get_distribution() (in module pkg_resources), 359

get_editor_iframe() (galaxy.webapps.galaxy.controllers.page.PageController method), 328

get_elements() (galaxy.util.topsort.CycleError method), 236

get_embed_html_async() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

get_embed_html_async() (galaxy.webapps.galaxy.controllers.page.PageController method), 328

get_empty_field_by_name() (galaxy.tools.data.ToolDataTable method), 194

get_entries() (galaxy.tools.data.TabularToolDataTable method), 193

get_entry() (galaxy.tools.data.TabularToolDataTable method), 193

get_entry_info() (in module pkg_resources), 359

get_entry_info() (pkg_resources.Distribution method), 363

get_entry_map() (in module pkg_resources), 359

get_entry_map() (pkg_resources.Distribution method), 363

get_env() (in module galaxy.eggs), 101

get_env_setup_clause() (galaxy.jobs.JobWrapper method), 115

get_errors() (galaxy.workflow.modules.ToolModule method), 349

get_errors() (galaxy.workflow.modules.WorkflowModule method), 350

get_estimated_display_viewport() (galaxy.datatypes.interval.BedGraph method), 64

get_estimated_display_viewport() (galaxy.datatypes.interval.CustomTrack method), 65

get_estimated_display_viewport() (galaxy.datatypes.interval.Gff method), 66

get_estimated_display_viewport() (galaxy.datatypes.interval.Interval method), 68

get_estimated_display_viewport() (galaxy.datatypes.interval.Wiggle method), 69

get_exit_code() (galaxy.jobs.TaskWrapper method), 117

get_external_output_metadata() (galaxy.model.Job method), 138

get_external_output_metadata() (galaxy.model.Task method), 146

get_external_service() (galaxy.model.RequestType method), 145

get_external_service() (galaxy.model.ExternalService method), 134

get_external_service_type() (galaxy.webapps.galaxy.controllers.external_service.ExternalService method), 317

get_external_services_for_manual_data_transfer() (galaxy.model.RequestType method), 145

get_externally_referenced_paths() (galaxy.tools.Tool class method), 185

get_extra_files_path() (galaxy.model.Dataset method), 129

get_fasta_header() (in module galaxy.tools.util.maf_utilities), 223

get_field() (galaxy.tools.data.TabularToolDataTable method), 193

get_field_by_name_for_value() (galaxy.tools.parameters.dynamic_options.DynamicOptions method), 209

get_fields() (galaxy.tools.data.TabularToolDataTable method), 193

get_fields() (galaxy.tools.parameters.dynamic_options.DynamicOptions method), 209

get_fields_by_value() (galaxy.tools.parameters.dynamic_options.DynamicOptions method), 209

get_file_base_name() (galaxy.tools.parameters.grouping.UploadDataset method), 213

get_file_contents() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 313

get_file_details() (galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin method), 333

get_file_name() (galaxy.model.Dataset method), 129

get_file_name() (galaxy.model.DatasetInstance method), 132

get_file_peek() (galaxy.datatypes.genetics.RexpBase method), 57

get_file_peek() (in module galaxy.datatypes.data), 54

get_file_size() (in module galaxy.util), 226

get_file_type() (galaxy.tools.parameters.grouping.UploadDataset method), 213

get_filename() (galaxy.objectstore.DiskObjectStore method), 170

get_filename() (galaxy.objectstore.NestedObjectStore method), 170

get_filename() (galaxy.objectstore.ObjectStore method), 172

get_filename_for_source()

- (`galaxy.tools.data.TabularToolDataTable` method), 193
- `get_files()` (`galaxy.tools.data.TabularToolDataField` method), 192
- `get_filesize_map()` (`galaxy.tools.data.TabularToolDataField` method), 192
- `get_filter()` (`galaxy.web.framework.helpers.grids.CommunityTagsColumn` method), 258
- `get_filter()` (`galaxy.web.framework.helpers.grids.IndividualTagsColumn` method), 261
- `get_filter()` (`galaxy.web.framework.helpers.grids.TextColumn` method), 264
- `get_fingerprint()` (`galaxy.tools.data.TabularToolDataField` method), 192
- `get_folder_dict()` (`galaxy.managers.folders.FolderManager` method), 162
- `get_form_template()` (in module `galaxy.jobs.actions.post`), 122
- `get_form_values()` (`galaxy.web.base.controller.UsesFormDefinitionsMixin` method), 249
- `get_forms()` (`galaxy.jobs.actions.post.ActionBox` class method), 120
- `get_func_list()` (in module `galaxy.web.framework.middleware.profile`), 264
- `get_galaxy_session()` (`galaxy.jobs.deferred.FakeTrans` method), 122
- `get_group()` (`galaxy.web.base.controller.BaseController` method), 247
- `get_group()` (in module `galaxy.web.base.controllers.admin`), 252
- `get_handler()` (`galaxy.jobs.JobConfiguration` method), 113
- `get_handler()` (`galaxy.model.Job` method), 138
- `get_hda()` (`galaxy.web.base.controller.UsesVisualizationMixin` method), 250
- `get_hda_or_ldda()` (`galaxy.web.base.controller.UsesVisualizationMixin` method), 250
- `get_headers()` (in module `galaxy.datatypes.sniff`), 83
- `get_history_datasets()` (`galaxy.tools.imp_exp.JobExportHistoryArchiveByMapper` method), 195
- `get_hook()` (`galaxy.tools.Tool` method), 185
- `get_html()` (`galaxy.datatypes.metadata.ColumnParameter` method), 70
- `get_html()` (`galaxy.datatypes.metadata.DBKeyParameter` method), 70
- `get_html()` (`galaxy.datatypes.metadata.FileParameter` method), 70
- `get_html()` (`galaxy.datatypes.metadata.MetadataParameter` method), 72
- `get_html()` (`galaxy.datatypes.metadata.PythonObjectParameter` method), 73
- `get_html()` (`galaxy.datatypes.metadata.RangeParameter` method), 73
- `get_html()` (`galaxy.datatypes.metadata.SelectParameter` method), 73
- `get_html()` (`galaxy.model.UserAddress` method), 149
- `get_html()` (`galaxy.tools.parameters.basic.DrillDownSelectToolParameter` method), 201
- `get_html()` (`galaxy.tools.parameters.basic.ToolParameter` method), 208
- `get_html()` (`galaxy.web.form_builder.AddressField` method), 241
- `get_html()` (`galaxy.web.form_builder.BaseField` method), 241
- `get_html()` (`galaxy.web.form_builder.CheckboxField` method), 242
- `get_html()` (`galaxy.web.form_builder.DrillDownField` method), 243
- `get_html()` (`galaxy.web.form_builder.FileField` method), 243
- `get_html()` (`galaxy.web.form_builder.FTPFileField` method), 243
- `get_html()` (`galaxy.web.form_builder.HiddenField` method), 244
- `get_html()` (`galaxy.web.form_builder.HistoryField` method), 244
- `get_html()` (`galaxy.web.form_builder.LibraryField` method), 244
- `get_html()` (`galaxy.web.form_builder.PasswordField` method), 244
- `get_html()` (`galaxy.web.form_builder.SelectField` method), 245
- `get_html()` (`galaxy.web.form_builder.SwitchingSelectField` method), 245
- `get_html()` (`galaxy.web.form_builder.TextArea` method), 245
- `get_html()` (`galaxy.web.form_builder.TextField` method), 245
- `get_html()` (`galaxy.web.form_builder.WorkflowField` method), 246
- `get_html()` (`galaxy.web.form_builder.WorkflowMappingField` method), 246
- `get_html_by_mapper()` (`galaxy.datatypes.metadata.MetadataCollection` method), 71
- `get_html_checkboxes()` (`galaxy.web.form_builder.SelectField` method), 245
- `get_html_default()` (`galaxy.web.form_builder.SelectField` method), 245
- `get_html_field()` (`galaxy.datatypes.metadata.ColumnParameter` method), 70
- `get_html_field()` (`galaxy.datatypes.metadata.DBKeyParameter` method), 70
- `get_html_field()` (`galaxy.datatypes.metadata.FileParameter` method), 70
- `get_html_field()` (`galaxy.datatypes.metadata.MetadataParameter` method), 72
- `get_html_field()` (`galaxy.datatypes.metadata.PythonObjectParameter` method), 73

method), 73

get_html_field() (galaxy.datatypes.metadata.RangeParameter method), 73

get_html_field() (galaxy.datatypes.metadata.SelectParameter method), 73

get_html_field() (galaxy.tools.parameters.basic.BaseURLToolParameter method), 197

get_html_field() (galaxy.tools.parameters.basic.BooleanToolParameter method), 197

get_html_field() (galaxy.tools.parameters.basic.ColorToolParameter method), 198

get_html_field() (galaxy.tools.parameters.basic.DataCollectionToolParameter method), 199

get_html_field() (galaxy.tools.parameters.basic.DataToolParameter method), 199

get_html_field() (galaxy.tools.parameters.basic.DrillDownSelectToolParameter method), 201

get_html_field() (galaxy.tools.parameters.basic.FileToolParameter method), 202

get_html_field() (galaxy.tools.parameters.basic.FloatToolParameter method), 203

get_html_field() (galaxy.tools.parameters.basic.FTPFileToolParameter method), 202

get_html_field() (galaxy.tools.parameters.basic.HiddenDataToolParameter method), 204

get_html_field() (galaxy.tools.parameters.basic.HiddenToolParameter method), 204

get_html_field() (galaxy.tools.parameters.basic.IntegerToolParameter method), 205

get_html_field() (galaxy.tools.parameters.basic.LibraryDatasetToolParameter method), 205

get_html_field() (galaxy.tools.parameters.basic.SelectToolParameter method), 207

get_html_field() (galaxy.tools.parameters.basic.TextToolParameter method), 207

get_html_field() (galaxy.tools.parameters.basic.ToolParameter method), 208

get_html_radio() (galaxy.web.form_builder.SelectField method), 245

get_id() (galaxy.model.Job method), 138

get_id() (galaxy.model.Task method), 147

get_id() (in module galaxy.webapps.galaxy.api.genomes), 13, 278

get_id_col_in_item_tag_assoc_table() (galaxy.managers.tags.TagManager method), 168

get_id_tag() (galaxy.jobs.JobWrapper method), 115

get_id_tag() (galaxy.jobs.TaskWrapper method), 117

get_id_tag() (galaxy.model.Job method), 138

get_id_tag() (galaxy.model.Task method), 147

get_ids() (galaxy.web.framework.helpers.grids.Grid method), 259

get_image_ext() (in module galaxy.datatypes.util.image_util), 100

get_imported() (galaxy.model.Job method), 138

get_importer() (in module pkg_resources), 368

get_incoming_value() (in module galaxy.tools), 189

get_index() (galaxy.tools.test.RootParamContext method), 190

get_info() (galaxy.model.Job method), 138

get_info() (galaxy.model.LibraryDataset method), 141

get_info() (galaxy.model.Task method), 147

get_info_association() (galaxy.model.Library method), 141

get_info_association() (galaxy.model.LibraryDatasetDatasetAssociation method), 142

get_info_association() (galaxy.model.LibraryFolder method), 142

get_initial_values() (galaxy.datatypes.display_applications.application.Display method), 96

get_initial_value() (galaxy.tools.parameters.basic.BaseURLToolParameter method), 197

get_initial_value() (galaxy.tools.parameters.basic.BooleanToolParameter method), 197

get_initial_value() (galaxy.tools.parameters.basic.ColorToolParameter method), 198

get_initial_value() (galaxy.tools.parameters.basic.ColumnListParameter method), 198

get_initial_value() (galaxy.tools.parameters.basic.DataToolParameter method), 199

get_initial_value() (galaxy.tools.parameters.basic.DrillDownSelectToolParameter method), 201

get_initial_value() (galaxy.tools.parameters.basic.FileToolParameter method), 202

get_initial_value() (galaxy.tools.parameters.basic.FloatToolParameter method), 203

get_initial_value() (galaxy.tools.parameters.basic.FTPFileToolParameter method), 202

get_initial_value() (galaxy.tools.parameters.basic.HiddenDataToolParameter method), 204

get_initial_value() (galaxy.tools.parameters.basic.HiddenToolParameter method), 204

get_initial_value() (galaxy.tools.parameters.basic.IntegerToolParameter method), 205

get_initial_value() (galaxy.tools.parameters.basic.LibraryDatasetToolParameter method), 205

get_initial_value() (galaxy.tools.parameters.basic.SelectToolParameter method), 207

get_initial_value() (galaxy.tools.parameters.basic.TextToolParameter method), 207

get_initial_value() (galaxy.tools.parameters.basic.ToolParameter method), 208

get_initial_value() (galaxy.tools.parameters.grouping.Conditional method), 211

get_initial_value() (galaxy.tools.parameters.grouping.Group method), 212

get_initial_value() (galaxy.tools.parameters.grouping.Repeat method), 212

[get_initial_value\(\)](#) (galaxy.tools.parameters.grouping.Section method), 212
[get_initial_value\(\)](#) (galaxy.tools.parameters.grouping.UploadDataset method), 213
[get_initial_value_from_history_prevent_repeats\(\)](#) (galaxy.tools.parameters.basic.DataToolParameter method), 199
[get_initial_value_from_history_prevent_repeats\(\)](#) (galaxy.tools.parameters.basic.ToolParameter method), 208
[get_input_dataset_fnames\(\)](#) (galaxy.jobs.JobWrapper method), 115
[get_input_datasets\(\)](#) (galaxy.model.Job method), 138
[get_input_files\(\)](#) (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
[get_input_fnames\(\)](#) (galaxy.jobs.JobWrapper method), 115
[get_input_library_datasets\(\)](#) (galaxy.model.Job method), 139
[get_input_paths\(\)](#) (galaxy.jobs.JobWrapper method), 115
[get_interesting_stack_frame\(\)](#) (galaxy.util.heartbeat.Heartbeat method), 231
[get_invocation\(\)](#) (galaxy.managers.workflows.WorkflowsManager method), 169
[get_invocation_step\(\)](#) (galaxy.managers.workflows.WorkflowsManager method), 169
[get_item\(\)](#) (galaxy.web.base.controller.SharableMixin method), 248
[get_item\(\)](#) (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320
[get_item\(\)](#) (galaxy.webapps.galaxy.controllers.page.PageController method), 329
[get_item_actions\(\)](#) (galaxy.security.GalaxyRBACAgent method), 177
[get_item_actions\(\)](#) (galaxy.security.RBACAgent method), 180
[get_item_and_stuff\(\)](#) (galaxy.web.base.controller.UsesFormDefinitionMixin method), 249
[get_item_annotation_obj\(\)](#) (galaxy.model.item_attrs.UsesAnnotations method), 152
[get_item_annotation_str\(\)](#) (galaxy.model.item_attrs.UsesAnnotations method), 152
[get_item_content_async\(\)](#) (galaxy.web.base.controller.SharableMixin method), 248
[get_item_content_async\(\)](#) (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315
[get_item_extended_metadata_obj\(\)](#) (galaxy.web.base.controller.UsesExtendedMetadataMixin method), 248
[get_iterator\(\)](#) (galaxy.visualization.data_providers.basic.BaseDataProvider method), 238
[get_job\(\)](#) (galaxy.jobs.JobWrapper method), 115
[get_job\(\)](#) (galaxy.jobs.TaskWrapper method), 117
[get_job\(\)](#) (galaxy.model.Job method), 139
[get_job\(\)](#) (galaxy.model.Task method), 147
[get_job\(\)](#) (in module galaxy.webapps.reports.controllers.jobs), 343
[get_job_destination\(\)](#) (galaxy.jobs.mapper.JobRunnerMapper method), 119
[get_job_destination\(\)](#) (galaxy.tools.Tool method), 185
[get_job_file\(\)](#) (galaxy.jobs.runners.BaseJobRunner method), 124
[get_job_handler\(\)](#) (galaxy.tools.Tool method), 185
[get_job_runner\(\)](#) (galaxy.jobs.JobWrapper method), 115
[get_job_runner_external_id\(\)](#) (galaxy.model.Job method), 139
[get_job_runner_external_id\(\)](#) (galaxy.model.Task method), 147
[get_job_runner_name\(\)](#) (galaxy.model.Job method), 139
[get_job_runner_name\(\)](#) (galaxy.model.Task method), 147
[get_job_runner_plugins\(\)](#) (galaxy.jobs.JobConfiguration method), 113
[get_job_runner_url\(\)](#) (galaxy.jobs.JobWrapper method), 115
[get_jobtool_configurations\(\)](#) (galaxy.jobs.JobConfiguration method), 113
[get_label\(\)](#) (galaxy.tools.parameters.basic.HiddenToolParameter method), 204
[get_label\(\)](#) (galaxy.tools.parameters.basic.ToolParameter method), 208
[get_latest_check\(\)](#) (galaxy.model.DeferredJob method), 133
[get_latest_installable_revision\(\)](#) (galaxy.webapps.galaxy.api.tool_shed_repositories.ToolShedRepository method), 35, 299
[get_legacy_sites_by_build\(\)](#) (galaxy.datatypes.registry.Registry method), 76
[get_legal_values\(\)](#) (galaxy.tools.parameters.basic.ColumnListParameter method), 198
[get_legal_values\(\)](#) (galaxy.tools.parameters.basic.DrillDownSelectToolParameter method), 202
[get_legal_values\(\)](#) (galaxy.tools.parameters.basic.GenomeBuildParameter method), 204
[get_legal_values\(\)](#) (galaxy.tools.parameters.basic.SelectToolParameter method), 207
[get_legitimate_roles\(\)](#) (galaxy.security.GalaxyRBACAgent method), 177
[get_legitimate_roles\(\)](#) (galaxy.security.RBACAgent method), 180
[get_length_counts\(\)](#) (galaxy_utils.sequence.fastq.fastqAggregator method), 352
[get_library\(\)](#) (galaxy.web.base.controller.UsesLibraryMixin method), 249

[get_library_dataset\(\)](#) (galaxy.web.base.controller.UsesLibraryMixin method), 249
[get_library_dataset_dataset_association\(\)](#) (galaxy.web.base.controller.UsesLibraryMixin method), 249
[get_library_dict\(\)](#) (galaxy.managers.libraries.LibraryManager method), 166
[get_library_folder\(\)](#) (galaxy.web.base.controller.UsesLibraryMixin method), 249
[get_link\(\)](#) (galaxy.datatypes.display_applications.application_display.Application method), 96
[get_link\(\)](#) (galaxy.web.framework.helpers.grids.GridColumn method), 260
[get_link\(\)](#) (galaxy.web.framework.helpers.grids.PublicURLColumn method), 262
[get_link\(\)](#) (galaxy.web.framework.helpers.grids.SharingStatusColumn method), 263
[get_link\(\)](#) (galaxy.webapps.galaxy.controllers.history.HistoryListGrid.HistoryListGridNameColumn method), 322
[get_manage_permissions_roles\(\)](#) (galaxy.model.Dataset method), 129
[get_manage_permissions_roles\(\)](#) (galaxy.model.LibraryDatasetDatasetAssociation method), 142
[get_manage_roles\(\)](#) (galaxy.managers.libraries.LibraryManager method), 166
[get_mapping_by_name\(\)](#) (galaxy.tools.parameters.sanitize.ToolParameterSanitizer class method), 218
[get_max_optional_metadata_filesize\(\)](#) (galaxy.datatypes.data.Data method), 51
[get_max_read_length\(\)](#) (galaxy_utils.sequence.fastq.fastqAggregate method), 353
[get_message_for_no_shed_tool_config\(\)](#) (in module galaxy.webapps.galaxy.api.tool_shed_repositories), 38, 302
[get_metadata\(\)](#) (galaxy.model.DatasetInstance method), 132
[get_metadata\(\)](#) (pkg_resources.FileMetadata method), 367
[get_metadata\(\)](#) (pkg_resources.IMetadataProvider method), 366
[get_metadata\(\)](#) (pkg_resources.NullProvider method), 367
[get_metadata_dataset\(\)](#) (galaxy.model.DatasetInstance method), 132
[get_metadata_file\(\)](#) (galaxy.webapps.galaxy.controllers.dataset.DatasetMetadata method), 315
[get_metadata_lines\(\)](#) (pkg_resources.FileMetadata method), 367
[get_metadata_lines\(\)](#) (pkg_resources.IMetadataProvider method), 366
[get_metadata_lines\(\)](#) (pkg_resources.NullProvider method), 367
[get_mimetype\(\)](#) (galaxy.datatypes.binary.Binary method), 46
[get_mime\(\)](#) (galaxy.datatypes.data.Data method), 51
[get_mime\(\)](#) (galaxy.datatypes.data.Text method), 53
[get_mime\(\)](#) (galaxy.datatypes.genetics.GenomeGraphs method), 55
[get_mime\(\)](#) (galaxy.datatypes.genetics.RexpBase method), 57
[get_mime\(\)](#) (galaxy.datatypes.genetics.Rgenetics method), 58
[get_mime\(\)](#) (galaxy.datatypes.genetics.rgTabList method), 59
[get_mime\(\)](#) (galaxy.datatypes.images.Gmajor method), 60
[get_mime\(\)](#) (galaxy.datatypes.images.Html method), 60
[get_mime\(\)](#) (galaxy.model.DatasetInstance method), 132
[get_mimetype_by_extension\(\)](#) (galaxy.datatypes.registry.Registry method), 76
[get_modify_roles\(\)](#) (galaxy.managers.libraries.LibraryManager method), 166
[get_monitor_id\(\)](#) (in module galaxy.webapps.reports.controllers.jobs), 343
[get_most_recently_used_tool_async\(\)](#) (galaxy.webapps.galaxy.controllers.user.User method), 339
[get_mutable_output_fnames\(\)](#) (galaxy.jobs.JobWrapper method), 115
[get_name\(\)](#) (galaxy.model.LibraryDataset method), 141
[get_name\(\)](#) (galaxy.workflow.modules.ToolModule method), 349
[get_name\(\)](#) (galaxy.workflow.modules.WorkflowModule method), 351
[get_name_and_link_async\(\)](#) (galaxy.web.base.controller.SharableMixin method), 248
[get_name_and_link_async\(\)](#) (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315
[get_name_and_link_async\(\)](#) (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320
[get_name_and_link_async\(\)](#) (galaxy.webapps.galaxy.controllers.page.PageController method), 329
[get_named_fields_list\(\)](#) (galaxy.tools.data.TabularToolDataTable method), 193
[get_native_spec\(\)](#) (galaxy.jobs.runners.drmaa.DRMAAJobRunner method), 126
[get_new_guid\(\)](#) (galaxy.web.security.SecurityHelper method), 266
[get_new_track_config\(\)](#) (galaxy.web.base.controller.UsesVisualizationMixin method), 250
[get_object\(\)](#) (galaxy.web.base.controller.BaseAPIController method), 246
[get_object\(\)](#) (galaxy.web.base.controller.BaseController method), 246

- method), 247
- get_object() (galaxy.web.base.controller.BaseUIController method), 247
- get_object() (in module galaxy.managers.base), 158
- get_object_url() (galaxy.objectstore.DiskObjectStore method), 170
- get_object_url() (galaxy.objectstore.NestedObjectStore method), 170
- get_object_url() (galaxy.objectstore.ObjectStore method), 172
- get_open_tempfile() (galaxy.tools.util.maf_utilities.TempFileHandler method), 223
- get_options() (galaxy.tools.parameters.basic.ColumnListParameter method), 198
- get_options() (galaxy.tools.parameters.basic.DrillDownSelectToolParameter method), 202
- get_options() (galaxy.tools.parameters.basic.GenomeBuildParameter method), 204
- get_options() (galaxy.tools.parameters.basic.SelectToolParameter method), 207
- get_options() (galaxy.tools.parameters.dynamic_options.DynamicOptions method), 210
- get_or_create_api_key() (galaxy.managers.api_keys.ApiKeyManager method), 154
- get_oriented_chopped_blocks_for_region() (in module galaxy.tools.util.maf_utilities), 223
- get_oriented_chopped_blocks_with_index_offset_for_region() (in module galaxy.tools.util.maf_utilities), 223
- get_output_datasets() (galaxy.model.Job method), 139
- get_output_destination() (galaxy.jobs.JobWrapper method), 115
- get_output_destination() (galaxy.jobs.TaskWrapper method), 117
- get_output_file_id() (galaxy.jobs.JobWrapper method), 115
- get_output_file_id() (galaxy.jobs.TaskWrapper method), 117
- get_output_filenames_by_dataset() (galaxy.datatypes.metadata.JobExternalOutputMetadataWrapper method), 71
- get_output_files() (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
- get_output_fnames() (galaxy.jobs.JobWrapper method), 115
- get_output_hdas_and_fnames() (galaxy.jobs.JobWrapper method), 115
- get_output_library_datasets() (galaxy.model.Job method), 139
- get_output_name() (galaxy.tools.actions.DefaultToolAction method), 190
- get_output_sizes() (galaxy.jobs.JobWrapper method), 115
- get_page() (galaxy.webapps.galaxy.controllers.page.PageController method), 329
- get_paired_identifier() (galaxy_utils.sequence.fastq.fastqJoiner method), 354
- get_pairlist() (galaxy.util.topsort.CycleError method), 236
- get_panel_section() (galaxy.tools.Tool method), 185
- get_parallelism() (galaxy.jobs.JobWrapper method), 115
- get_param() (galaxy.tools.Tool method), 185
- get_param_dict() (galaxy.jobs.JobWrapper method), 115
- get_param_dict() (galaxy.jobs.TaskWrapper method), 117
- get_param_filename() (galaxy.model.Job method), 139
- get_param_html_map() (galaxy.tools.Tool method), 185
- get_param_name_by_url() (galaxy.datatypes.display_applications.application.PopulatedDisplay method), 97
- get_param_value() (galaxy.datatypes.display_applications.application.PopulatedDisplay method), 97
- get_param_values() (galaxy.model.Job method), 139
- get_param_values() (galaxy.model.Task method), 147
- get_parameters() (galaxy.model.Job method), 139
- get_permissions() (galaxy.model.Task method), 147
- get_params() (galaxy.model.Job method), 139
- get_params() (galaxy.web.params.BaseParamParser method), 246
- get_parent() (galaxy.datatypes.metadata.MetadataCollection method), 71
- get_partial() (galaxy.util.topsort.CycleError method), 236
- get_path_paste_uploaded_datasets() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 325
- get_peek() (galaxy.datatypes.genetics.RexpBase method), 57
- get_percent() (galaxy.quota.NoQuotaAgent method), 173
- get_percent() (galaxy.quota.QuotaAgent method), 174
- get_permissions() (galaxy.security.GalaxyRBACAgent method), 177
- get_permissions() (galaxy.security.RBACAgent method), 180
- get_permissions() (galaxy.webapps.galaxy.api.folders.FoldersController method), 12, 277
- get_permissions() (galaxy.webapps.galaxy.api.libraries.LibrariesController method), 26, 291
- get_permitted_actions() (in module galaxy.security), 181
- get_permitted_libraries() (galaxy.security.GalaxyRBACAgent method), 177
- get_permitted_libraries() (galaxy.security.RBACAgent method), 180
- get_phecols() (galaxy.datatypes.genetics.RexpBase method), 57
- get_pheno() (galaxy.datatypes.genetics.RexpBase method), 57
- get_platform() (in module pkg_resources), 365
- get_platforms() (galaxy.eggs.dist.DistScrambleCrate

method), 101

get_post_job_actions() (galaxy.model.Job method), 139

get_post_job_actions() (galaxy.workflow.modules.ToolModule method), 349

get_precreated_dataset() (in module galaxy.tools.actions.upload_common), 192

get_precreated_datasets() (in module galaxy.tools.actions.upload_common), 192

get_pred_counts() (galaxy.util.topsort.CycleError method), 236

get_preds() (galaxy.util.topsort.CycleError method), 236

get_prepare_input_files_cmd() (galaxy.model.Task method), 147

get_prepare_steps() (galaxy.datatypes.display_applications.application_display_applications.NullProvider method), 97

get_private_user_role() (galaxy.security.GalaxyRBACAgent method), 178

get_private_user_role() (galaxy.security.RBACAgent method), 180

get_provider() (in module pkg_resources), 359

get_published_visualizations() (galaxy.web.base.controller.UsesVisualizationMixin method), 250

get_quota() (galaxy.quota.NoQuotaAgent method), 173

get_quota() (galaxy.quota.QuotaAgent method), 174

get_quota() (galaxy.web.base.controller.UsesQuotaMixin method), 249

get_quota() (in module galaxy.web.base.controllers.admin), 252

get_quota_params() (galaxy.web.params.QuotaParamParser method), 246

get_random_bytes() (in module galaxy.web.security), 266

get_raw_data() (galaxy.datatypes.data.Data method), 51

get_raw_data() (galaxy.model.DatasetInstance method), 132

get_read_count() (galaxy_utils.sequence.fastq.fastqAggregator method), 353

get_read_count_for_column() (galaxy_utils.sequence.fastq.fastqAggregator method), 353

get_ref() (galaxy.external_services.service.ExternalServiceActionsGroup method), 108

get_ref() (galaxy.tools.parameters.output.ToolOutputActionConditionalMethod method), 216

get_region_alignment() (in module galaxy.tools.util.maf_utilities), 224

get_reports() (galaxy.util.debugging.SimpleProfiler method), 230

get_request() (in module galaxy.webapps.reports.controllers.sample_tracking), 345

get_required_encype() (galaxy.tools.parameters.basic.FileToolParameter method), 202

get_required_encype() (galaxy.tools.parameters.basic.ToolParameter method), 208

get_resource_filename() (pkg_resources.IResourceProvider method), 366

get_resource_filename() (pkg_resources.NullProvider method), 367

get_resource_filename() (pkg_resources.ZipProvider method), 368

get_resource_group() (galaxy.jobs.JobToolConfiguration method), 114

get_resource_stream() (pkg_resources.DefaultProvider method), 368

get_resource_stream() (pkg_resources.IResourceProvider method), 366

get_resource_stream() (pkg_resources.NullProvider method), 367

get_resource_string() (pkg_resources.IResourceProvider method), 366

get_resource_string() (pkg_resources.NullProvider method), 367

get_role() (galaxy.web.base.controller.BaseController method), 247

get_role() (in module galaxy.web.base.controllers.admin), 252

get_roles_for_action() (galaxy.security.GalaxyRBACAgent method), 178

get_runtime_input_dicts() (galaxy.workflow.modules.InputModule method), 348

get_runtime_input_dicts() (galaxy.workflow.modules.PauseModule method), 348

get_runtime_input_dicts() (galaxy.workflow.modules.ToolModule method), 349

get_runtime_input_dicts() (galaxy.workflow.modules.WorkflowModule method), 351

get_runtime_inputs() (galaxy.workflow.modules.InputDataCollectionModule method), 347

get_runtime_inputs() (galaxy.workflow.modules.InputDataModule method), 347

get_runtime_inputs() (galaxy.workflow.modules.PauseModule method), 348

get_runtime_inputs() (galaxy.workflow.modules.WorkflowModule method), 351

get_runtime_state() (galaxy.workflow.modules.InputModule method), 348

get_runtime_state() (galaxy.workflow.modules.PauseModule method), 348

get_sample() (galaxy.model.Request method), 144

get_saved_form() (galaxy.webapps.galaxy.controllers.forms.Forms method), 318

get_score_at_position_for_column()

method), 353

get_score_list_for_column() (galaxy_utils.sequence.fastq.fastqAggregator method), 353

get_score_max_for_column() (galaxy_utils.sequence.fastq.fastqAggregator method), 353

get_score_min_for_column() (galaxy_utils.sequence.fastq.fastqAggregator method), 353

get_score_sum_for_column() (galaxy_utils.sequence.fastq.fastqAggregator method), 353

get_selected() (galaxy.web.form_builder.SelectField method), 245

get_sequence() (galaxy.tools.util.maf_utilities.RegionAlignment method), 222

get_sequence() (galaxy.tools.util.maf_utilities.SplicedAlignment method), 222

get_sequence() (galaxy_utils.sequence.fastq.fastqCSSangerReads method), 353

get_sequence() (galaxy_utils.sequence.fastq.fastqSequencingReads method), 355

get_sequence_reverse_complement() (galaxy.tools.util.maf_utilities.RegionAlignment method), 222

get_sequence_reverse_complement() (galaxy.tools.util.maf_utilities.SplicedAlignment method), 222

get_sequences_per_file() (galaxy.datatypes.sequence.Sequence static method), 81

get_server_dir_uploaded_datasets() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommonTools method), 325

get_session() (galaxy.web.framework.openid_manager.OpenIDManager method), 256

get_session_id() (galaxy.jobs.JobWrapper method), 115

get_session_id() (galaxy.jobs.TaskWrapper method), 117

get_session_id() (galaxy.model.Job method), 139

get_session_id() (galaxy.model.Task method), 147

get_sharing_roles() (galaxy.security.GalaxyRBACAgent method), 178

get_short_str() (galaxy.jobs.actions.post.ActionBox class method), 120

get_short_str() (galaxy.jobs.actions.post.ChangeDatatypeAction class method), 120

get_short_str() (galaxy.jobs.actions.post.ColumnSetAction class method), 120

get_short_str() (galaxy.jobs.actions.post.DefaultJobAction class method), 120

get_short_str() (galaxy.jobs.actions.post.DeleteDatasetAction class method), 121

get_short_str() (galaxy.jobs.actions.post.DeleteIntermediatesAction class method), 121

get_short_str() (galaxy.jobs.actions.post.EmailAction class method), 121

get_short_str() (galaxy.jobs.actions.post.HideDatasetAction class method), 121

get_short_str() (galaxy.jobs.actions.post.RenameDatasetAction class method), 121

get_short_str() (galaxy.jobs.actions.post.TagDatasetAction class method), 122

get_showable_folders() (galaxy.security.GalaxyRBACAgent method), 178

get_single_filter() (galaxy.web.framework.helpers.grids.BooleanColumn method), 257

get_single_filter() (galaxy.web.framework.helpers.grids.IntegerColumn method), 261

get_single_filter() (galaxy.web.framework.helpers.grids.OwnerAnnotation method), 262

get_single_filter() (galaxy.web.framework.helpers.grids.TextColumn method), 264

get_size() (galaxy.model.Dataset method), 129

get_size() (galaxy.model.DatasetInstance method), 132

get_reported_accessible_library_items() (in module galaxy.webapps.galaxy.controllers.library_common), 326

get_species_in_block() (in module galaxy.tools.util.maf_utilities), 224

get_species_in_maf() (in module galaxy.tools.util.maf_utilities), 224

get_species_names() (galaxy.tools.util.maf_utilities.RegionAlignment method), 222

get_species_names() (galaxy.tools.util.maf_utilities.SplicedAlignment method), 222

get_spliced_region_alignment() (in module galaxy.tools.util.maf_utilities), 224

get_split_commands_sequential() (galaxy.datatypes.sequence.Sequence static method), 81

get_split_commands_with_toc() (galaxy.datatypes.sequence.Sequence static method), 81

get_sreg() (galaxy.web.framework.openid_manager.OpenIDManager method), 256

get_starts_ends_fields_from_gene_bed() (in module galaxy.tools.util.maf_utilities), 224

get_state() (galaxy.jobs.JobWrapper method), 115

get_state() (galaxy.jobs.TaskWrapper method), 117

get_state() (galaxy.jobs.transfer_manager.TransferManager method), 119

get_state() (galaxy.model.Job method), 139

get_state() (galaxy.model.Task method), 147

get_state() (galaxy.workflow.modules.SimpleWorkflowModule method), 349

get_state() (galaxy.workflow.modules.ToolModule method), 349

- [get_state\(\)](#) (galaxy.workflow.modules.WorkflowModule method), 351
[get_static_param_values\(\)](#) (galaxy.tools.Tool method), 185
[get_stderr\(\)](#) (galaxy.model.Task method), 147
[get_stdout\(\)](#) (galaxy.model.Task method), 147
[get_store_usage_percent\(\)](#) (galaxy.objectstore.DiskObjectStore method), 170
[get_store_usage_percent\(\)](#) (galaxy.objectstore.ObjectStore method), 172
[get_stored_workflow\(\)](#) (galaxy.web.base.controller.UsesStoredWorkflowMixin method), 250
[get_stored_workflow_steps\(\)](#) (galaxy.web.base.controller.UsesStoredWorkflowMixin method), 250
[get_succs\(\)](#) (galaxy.util.topsort.CycleError method), 236
[get_suite\(\)](#) (in module galaxy.tools.parameters.validation), 221
[get_suite\(\)](#) (in module galaxy.web.form_builder), 246
[get_summary_statistics_for_column\(\)](#) (galaxy_utils.sequence.fastq.fastqAggregator method), 353
[get_tables\(\)](#) (galaxy.tools.data.ToolDataTableManager method), 194
[get_tag_assoc_class\(\)](#) (galaxy.managers.tags.TagManager method), 168
[get_tag_by_id\(\)](#) (galaxy.managers.tags.TagManager method), 168
[get_tag_by_name\(\)](#) (galaxy.managers.tags.TagManager method), 168
[get_tag_handler\(\)](#) (galaxy.web.base.controller.UsesTagsMixin method), 250
[get_tagging_elt_async\(\)](#) (galaxy.webapps.galaxy.controllers.tag.TagsController method), 337
[get_tags_str\(\)](#) (galaxy.managers.tags.TagManager method), 168
[get_task\(\)](#) (galaxy.jobs.TaskWrapper method), 117
[get_task_runner_external_id\(\)](#) (galaxy.model.Task method), 147
[get_task_runner_name\(\)](#) (galaxy.model.Task method), 147
[get_tasks\(\)](#) (galaxy.model.Job method), 139
[get_template_widgets\(\)](#) (galaxy.model.Library method), 141
[get_template_widgets\(\)](#) (galaxy.model.LibraryDatasetDatasetAssociation method), 142
[get_template_widgets\(\)](#) (galaxy.model.LibraryFolder method), 143
[get_template_widgets\(\)](#) (galaxy.model.RequestType method), 145
[get_template_widgets\(\)](#) (galaxy.model.Sample method), 145
[get_test_fname\(\)](#) (in module galaxy.datatypes.data), 54
[get_test_fname\(\)](#) (in module galaxy.datatypes.sniff), 83
[get_tld\(\)](#) (galaxy.eggs.scramble.ScrambleEgg method), 102
[get_tool_def\(\)](#) (galaxy.web.base.controller.UsesVisualizationMixin method), 250
[get_tool_dependencies\(\)](#) (galaxy.webapps.galaxy.controllers.admin_toolshe method), 313
[get_tool_id\(\)](#) (galaxy.model.Job method), 139
[get_tool_id\(\)](#) (galaxy.workflow.modules.ToolModule method), 349
[get_tool_id\(\)](#) (galaxy.workflow.modules.WorkflowModule method), 351
[get_tool_provided_job_metadata\(\)](#) (galaxy.jobs.JobWrapper method), 115
[get_tool_provided_job_metadata\(\)](#) (galaxy.jobs.TaskWrapper method), 117
[get_tool_resource_parameters\(\)](#) (galaxy.jobs.JobConfiguration method), 113
[get_tool_tags\(\)](#) (galaxy.managers.tags.TagManager method), 168
[get_tool_version\(\)](#) (galaxy.model.Job method), 139
[get_tool_version\(\)](#) (galaxy.workflow.modules.ToolModule method), 349
[get_toolbox\(\)](#) (galaxy.managers.context.ProvidesAppContext method), 160
[get_toolbox\(\)](#) (galaxy.web.base.controller.BaseController method), 247
[get_tooltip\(\)](#) (galaxy.workflow.modules.ToolModule method), 349
[get_tooltip\(\)](#) (galaxy.workflow.modules.WorkflowModule method), 351
[get_total_job_count_per_destination\(\)](#) (galaxy.jobs.handler.JobHandlerQueue method), 118
[get_total_size\(\)](#) (galaxy.model.Dataset method), 129
[get_total_size\(\)](#) (galaxy.model.DatasetInstance method), 132
[get_track_resolution\(\)](#) (galaxy.datatypes.coverage.LastzCoverage method), 49
[get_track_resolution\(\)](#) (galaxy.datatypes.interval.Interval method), 68
[get_track_resolution\(\)](#) (galaxy.datatypes.interval.Wiggle method), 69
[get_track_window\(\)](#) (galaxy.datatypes.coverage.LastzCoverage method), 49
[get_track_window\(\)](#) (galaxy.datatypes.interval.Interval method), 68
[get_track_window\(\)](#) (galaxy.datatypes.interval.Wiggle method), 69
[get_type\(\)](#) (galaxy.workflow.modules.WorkflowModule method), 351
[get_untransferred_dataset_size\(\)](#) (galaxy.model.Sample method), 145

[get_updated_repository_information\(\)](#) (galaxy.webapps.galaxy.controllers.admin_toolshed.get_admin_toolshed method), 313
[get_upload_metadata_params\(\)](#) (galaxy.datatypes.registry.Registry method), 76
[get_uploaded_datasets\(\)](#) (galaxy.tools.parameters.grouping.UploadData method), 213
[get_uploaded_datasets\(\)](#) (in module galaxy.tools.actions.upload_common), 192
[get_url_args\(\)](#) (galaxy.web.framework.helpers.grids.DisplayByUserAndSlugGridOperation method), 259
[get_url_args\(\)](#) (galaxy.web.framework.helpers.grids.GridColumnFilter method), 260
[get_url_args\(\)](#) (galaxy.web.framework.helpers.grids.GridOperation method), 261
[get_usage\(\)](#) (galaxy.quota.NoQuotaAgent method), 173
[get_user\(\)](#) (galaxy.model.Job method), 139
[get_user\(\)](#) (galaxy.web.base.controller.BaseController method), 247
[get_user\(\)](#) (in module galaxy.web.base.controllers.admin), 252
[get_user_by_username\(\)](#) (in module galaxy.web.base.controllers.admin), 253
[get_user_id\(\)](#) (galaxy.model.Job method), 139
[get_user_item_rating\(\)](#) (galaxy.model.item_attrs.UsesItemRatings method), 152
[get_user_job_count\(\)](#) (galaxy.jobs.handler.JobHandlerQueue method), 118
[get_user_job_count_per_destination\(\)](#) (galaxy.jobs.handler.JobHandlerQueue method), 118
[get_user_quotas\(\)](#) (galaxy.quota.NoQuotaAgent method), 173
[get_user_quotas\(\)](#) (galaxy.quota.QuotaAgent method), 174
[get_user_tags_used\(\)](#) (galaxy.web.base.controller.UsesTagsMixin method), 250
[get_valid_by_name\(\)](#) (galaxy.tools.parameters.sanitize.ToolParameterSanitizer class method), 218
[get_valid_formats\(\)](#) (galaxy_utils.sequence.fastq.fastqAggregator method), 353
[get_valid_roles\(\)](#) (galaxy.security.GalaxyRBACAgent method), 178
[get_value\(\)](#) (galaxy.datatypes.display_applications.parameters.get_display_application_parameters method), 97
[get_value\(\)](#) (galaxy.datatypes.display_applications.parameters.get_display_application_parameters method), 97
[get_value\(\)](#) (galaxy.datatypes.display_applications.parameters.get_display_application_parameters method), 97
[get_value\(\)](#) (galaxy.external_services.parameters.ExternalServiceParameter method), 107
[get_value\(\)](#) (galaxy.external_services.parameters.ExternalServiceTemplateParameter method), 107
[get_value\(\)](#) (galaxy.tools.parameters.output.FromDataTableOutputActionOption method), 214
[get_value\(\)](#) (galaxy.tools.parameters.output.FromFileToolOutputActionOption method), 214
[get_value\(\)](#) (galaxy.tools.parameters.output.FromParamToolOutputActionOption method), 215
[get_value\(\)](#) (galaxy.tools.parameters.output.NullToolOutputActionOption method), 215
[get_value\(\)](#) (galaxy.tools.parameters.output.ToolOutputActionOption method), 216
[get_value\(\)](#) (galaxy.web.framework.helpers.grids.CommunityRatingColumn method), 258
[get_value\(\)](#) (galaxy.web.framework.helpers.grids.CommunityTagsColumn method), 258
[get_value\(\)](#) (galaxy.web.framework.helpers.grids.GridColumn method), 260
[get_value\(\)](#) (galaxy.web.framework.helpers.grids.IndividualTagsColumn method), 261
[get_value\(\)](#) (galaxy.web.framework.helpers.grids.OwnerAnnotationColumn method), 262
[get_value\(\)](#) (galaxy.web.framework.helpers.grids.OwnerColumn method), 262
[get_value\(\)](#) (galaxy.web.framework.helpers.grids.SharingStatusColumn method), 263
[get_value\(\)](#) (galaxy.web.framework.helpers.grids.StateColumn method), 264
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.GroupListGrid.Name method), 307
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.GroupListGrid.Roles method), 307
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.GroupListGrid.Status method), 307
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.GroupListGrid.Users method), 307
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid.Amount method), 307
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid.Description method), 308
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid.Group method), 308
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid.Name method), 308
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid.Status method), 308
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid.Users method), 308
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.RoleListGrid.Description method), 309
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.RoleListGrid.Groups method), 309
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.RoleListGrid.Name method), 309
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.RoleListGrid.Status method), 309
[get_value\(\)](#) (galaxy.webapps.galaxy.controllers.admin.RoleListGrid.Type method), 309

method), 309

get_value() (galaxy.webapps.galaxy.controllers.admin.RoleListGrid.URLCol), 324

method), 309

get_value() (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid.ToolIdCol), 324

method), 310

get_value() (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid.ToolNameCol), 325

method), 310

get_value() (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid.ToolWebappsCol), 328

method), 310

get_value() (galaxy.webapps.galaxy.controllers.admin.UserListGrid.ActiveCol), 329

method), 310

get_value() (galaxy.webapps.galaxy.controllers.admin.UserListGrid.EmailCol), 331

method), 311

get_value() (galaxy.webapps.galaxy.controllers.admin.UserListGrid.FullNameCol), 331

method), 311

get_value() (galaxy.webapps.galaxy.controllers.admin.UserListGrid.GroupCol), 331

method), 311

get_value() (galaxy.webapps.galaxy.controllers.admin.UserListGrid.LoginCol), 331

method), 311

get_value() (galaxy.webapps.galaxy.controllers.admin.UserListGrid.RolesCol), 331

method), 311

get_value() (galaxy.webapps.galaxy.controllers.admin.UserListGrid.StatusCol), 332

method), 311

get_value() (galaxy.webapps.galaxy.controllers.admin.UserListGrid.FindingCol), 332

method), 311

get_value() (galaxy.webapps.galaxy.controllers.admin.UserListGrid.SetNameCol), 333

method), 316

get_value() (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetGrid.HistoryCol), 333

method), 316

get_value() (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetGrid.DatasetCol), 333

method), 317

get_value() (galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGrid.ExternalServiceCol), 335

method), 317

get_value() (galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGrid.NameCol), 335

method), 319

get_value() (galaxy.webapps.galaxy.controllers.forms.FormsGrid.DescriptionCol), 335

method), 319

get_value() (galaxy.webapps.galaxy.controllers.forms.FormsGrid.NameCol), 335

method), 319

get_value() (galaxy.webapps.galaxy.controllers.forms.FormsGrid.TypeCol), 335

method), 321

get_value() (galaxy.webapps.galaxy.controllers.history.HistoryListGrid.DatasetsByStepsCol), 342

method), 322

get_value() (galaxy.webapps.galaxy.controllers.history.HistoryListGrid.DatasetCol), 342

method), 322

get_value() (galaxy.webapps.galaxy.controllers.history.NameCol), 342

method), 323

get_value() (galaxy.webapps.galaxy.controllers.history.ShareHistoryListGrid.DatasetsByStepsCol), 342

method), 323

get_value() (galaxy.webapps.galaxy.controllers.history.ShareHistoryListGrid.DatasetCol), 343

method), 323

get_value() (galaxy.webapps.galaxy.controllers.library.LibraryListGrid.DescriptionCol), 344

method), 324

get_value() (galaxy.webapps.galaxy.controllers.library.LibraryListGrid.NameCol), 344

method), 324

get_value() (galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid.LibraryCol), 344

- method), 344
- get_value() (galaxy.webapps.reports.controllers.workflows.SpecifiedDatasetGridOverlay method), 346
- get_value() (galaxy.webapps.reports.controllers.workflows.SpecifiedDatasetGridOverlay method), 346
- get_value() (galaxy.webapps.reports.controllers.workflows.SpecifiedDatasetGridOverlay method), 346
- get_value() (galaxy.webapps.reports.controllers.workflows.SpecifiedDatasetGridOverlay method), 346
- get_version_fields() (galaxy.tools.data.TabularToolDataTable method), 193
- get_version_string_path() (galaxy.jobs.JobWrapper method), 115
- get_visualization() (galaxy.web.base.controller.UsesVisualizationMixin method), 250
- get_visualization_config() (galaxy.web.base.controller.UsesVisualizationMixin method), 250
- get_visualization_dict() (galaxy.web.base.controller.UsesVisualizationMixin method), 250
- get_visualization_revision_dict() (galaxy.web.base.controller.UsesVisualizationMixin method), 251
- get_visualization_summary_dict() (galaxy.web.base.controller.UsesVisualizationMixin method), 251
- get_visualizations() (galaxy.datatypes.data.Data method), 51
- get_visualizations() (galaxy.datatypes.data.Newick method), 53
- get_visualizations() (galaxy.datatypes.data.Nexus method), 53
- get_visualizations() (galaxy.datatypes.xml.Phyloxml method), 91
- get_visualizations() (galaxy.model.DatasetInstance method), 132
- get_visualizations_by_user() (galaxy.web.base.controller.UsesVisualizationMixin method), 251
- get_visualizations_shared_with_user() (galaxy.web.base.controller.UsesVisualizationMixin method), 251
- get_web_api_action() (galaxy.external_services.actions.ExternalServiceWebAPIAction method), 107
- get_widgets() (galaxy.model.FormDefinition method), 134
- get_work_dir_outputs() (galaxy.jobs.runners.BaseJobRunner method), 124
- get_workflow() (in module galaxy.webapps.reports.controllers.workflows), 347
- get_working_directory() (galaxy.model.Task method), 147
- getMissval() (in module galaxy.datatypes.converters.lped_to_pbed_converter), 94
- Gff (class in galaxy.datatypes.interval), 65
- GffFieldListGridOverlay (class in galaxy.datatypes.interval), 66
- gff_attributes_to_str() (in module galaxy.datatypes.util), 99
- GFFFeature (class in galaxy.datatypes.util.gff_util), 98
- GFFFieldListGridOverlay (class in galaxy.datatypes.util.gff_util), 99
- GFFIntervalToBEDReaderWrapper (class in galaxy.datatypes.util.gff_util), 99
- GFFReaderWrapper (class in galaxy.datatypes.util.gff_util), 99
- Gif (class in galaxy.datatypes.images), 59
- global_actions (galaxy.web.framework.helpers.grids.Grid attribute), 259
- global_actions (galaxy.webapps.galaxy.controllers.admin.GroupListGrid attribute), 307
- global_actions (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid attribute), 308
- global_actions (galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute), 309
- global_actions (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 310
- global_actions (galaxy.webapps.galaxy.controllers.admin.UserListGrid attribute), 312
- global_actions (galaxy.webapps.galaxy.controllers.external_service.ExternalService attribute), 317
- global_actions (galaxy.webapps.galaxy.controllers.forms.FormsGrid attribute), 319
- global_actions (galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid attribute), 325
- global_actions (galaxy.webapps.galaxy.controllers.page.PageListGrid attribute), 329
- global_actions (galaxy.webapps.galaxy.controllers.request_type.RequestType attribute), 331
- global_actions (galaxy.webapps.galaxy.controllers.requests_admin.AdminRequests attribute), 332
- Gmaji (class in galaxy.datatypes.images), 59
- Grid (class in galaxy.web.framework.helpers.grids), 259
- grid_fields() (galaxy.model.FormDefinition method), 134
- GridAction (class in galaxy.web.framework.helpers.grids), 260
- GridColumnFilter (class in galaxy.web.framework.helpers.grids), 260
- GridOperation (class in galaxy.web.framework.helpers.grids), 260
- groom_dataset_content() (galaxy.datatypes.binary.Bam method), 45
- groom_dataset_content() (galaxy.datatypes.data.Data method), 51
- Group (class in galaxy.model), 134
- Group (class in galaxy.tools.parameters.grouping), 212
- group_assoc (galaxy.managers.roles.RoleManager attribute), 167

group_list_grid (galaxy.web.base.controllers.admin.Admin attribute), 251
 group_list_grid (galaxy.webapps.galaxy.controllers.admin.Admin attribute), 306
 group_title() (galaxy.tools.parameters.grouping.UploadDataset method), 213
 GroupApiController (class in galaxy.webapps.galaxy.api.groups), 14, 279
 GroupListGrid (class in galaxy.webapps.galaxy.controllers.admin), 306
 GroupListGrid.NameColumn (class in galaxy.webapps.galaxy.controllers.admin), 306
 GroupListGrid.RolesColumn (class in galaxy.webapps.galaxy.controllers.admin), 307
 GroupListGrid.StatusColumn (class in galaxy.webapps.galaxy.controllers.admin), 307
 GroupListGrid.UsersColumn (class in galaxy.webapps.galaxy.controllers.admin), 307
 GroupQuotaAssociation (class in galaxy.model), 135
 GroupRoleAssociation (class in galaxy.model), 135
 GroupRolesApiController (class in galaxy.webapps.galaxy.api.group_roles), 13, 278
 groups() (galaxy.web.base.controllers.admin.Admin method), 251
 GroupUsersApiController (class in galaxy.webapps.galaxy.api.group_users), 14, 279
 Gtf (class in galaxy.datatypes.interval), 67
 guess_derived_permissions_for_datasets() (galaxy.security.GalaxyRBACAgent method), 178
 guess_derived_permissions_for_datasets() (galaxy.security.RBACAgent method), 180
 guess_ext() (in module galaxy.datatypes.sniff), 83
 guess_galaxy_port() (galaxy.config.Configuration method), 42
 guess_type() (galaxy.datatypes.tabular.CSV method), 85
H
 H5 (class in galaxy.datatypes.binary), 47
 handle_action() (galaxy.external_services.actions.ExternalServiceAction method), 106
 handle_compressed_file() (in module galaxy.datatypes.sniff), 84
 handle_controller_exception() (galaxy.web.framework.base.WebApplication method), 256
 handle_datatypes_changed() (galaxy.tools.ToolBox method), 188
 handle_galaxy_index_file() (galaxy.tools.data.TabularToolDataTable method), 193
 handle_incoming() (galaxy.jobs.actions.post.ActionBox class method), 120
 handle_input() (galaxy.tools.Tool method), 185
 handle_interrupted() (galaxy.tools.Tool method), 185
 handle_job_failure_exception() (galaxy.tools.Tool method), 186
 handle_library_params() (in module galaxy.tools.actions.upload_common), 192
 handle_operation() (galaxy.web.framework.helpers.grids.Grid method), 259
 handle_population_failed() (galaxy.model.DatasetCollection method), 130
 handle_request() (galaxy.web.framework.base.WebApplication method), 256
 handle_result() (galaxy.external_services.result_handlers.basic.ExternalServiceResultHandler method), 109
 handle_result() (galaxy.external_services.result_handlers.basic.ExternalServiceResultHandler method), 110
 handle_result() (galaxy.external_services.result_handlers.basic.ExternalServiceResultHandler method), 110
 handle_result() (galaxy.external_services.result_handlers.basic.ExternalServiceResultHandler method), 110
 handle_results() (galaxy.external_services.actions.PopulatedExternalServiceAction method), 107
 handle_single_execution() (galaxy.tools.Tool method), 186
 handle_stop() (galaxy.jobs.runners.AsynchronousJobRunner method), 124
 handle_unvalidated_param_values() (galaxy.tools.Tool method), 186
 handle_unvalidated_param_values_helper() (galaxy.tools.Tool method), 186
 handle_uploaded_dataset_file() (in module galaxy.datatypes.sniff), 84
 handler_class (in module galaxy.external_services.result_handlers.basic), 110
 hapmapmart() (galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner method), 338
 has_accessible_folders() (galaxy.security.GalaxyRBACAgent method), 178
 has_accessible_library_datasets() (galaxy.security.GalaxyRBACAgent method), 178
 has_action() (galaxy.external_services.service.ActionSection method), 108
 has_adapter_base() (galaxy_utils.sequence.fastq.fastqCSSangerRead method), 353

[has_been_resubmitted\(\)](#) (galaxy.managers.hdas.HDAManager method), 163
[has_data\(\)](#) (galaxy.model.Dataset method), 129
[has_data\(\)](#) (galaxy.model.DatasetInstance method), 132
[has_data\(\)](#) (galaxy.visualization.data_providers.basic.BaseDataProvider method), 238
[has_data\(\)](#) (galaxy_utils.sequence.fasta.fastaNamedReader method), 352
[has_data\(\)](#) (galaxy_utils.sequence.fastq.fastqFakeFastaScoreReader method), 353
[has_data\(\)](#) (galaxy_utils.sequence.fastq.fastqNamedReader method), 354
[has_dataprovider\(\)](#) (galaxy.datatypes.data.Data method), 51
[has_doi\(\)](#) (galaxy.managers.citations.BaseCitation method), 158
[has_doi\(\)](#) (galaxy.managers.citations.DoiCitation method), 159
[has_input_for_step\(\)](#) (galaxy.model.WorkflowInvocation method), 150
[has_limits\(\)](#) (galaxy.jobs.JobWrapper method), 115
[has_manage_permissions_roles\(\)](#) (galaxy.model.Dataset method), 129
[has_manage_permissions_roles\(\)](#) (galaxy.model.LibraryDatasetDatasetAssociation method), 142
[has_metadata\(\)](#) (pkg_resources.FileMetadata method), 367
[has_metadata\(\)](#) (pkg_resources.IMetadataProvider method), 366
[has_metadata\(\)](#) (pkg_resources.NullProvider method), 367
[has_outputs_defined\(\)](#) (galaxy.model.Workflow method), 150
[has_post_authentication_actions\(\)](#) (galaxy.openid.providers.OpenIDProvider method), 173
[has_reference_data\(\)](#) (galaxy.visualization.genomes.Genomes method), 237
[has_resolution](#) (galaxy.datatypes.data.Data attribute), 52
[has_resource\(\)](#) (pkg_resources.IResourceProvider method), 366
[has_resource\(\)](#) (pkg_resources.NullProvider method), 367
[has_version\(\)](#) (pkg_resources.Distribution method), 363
[hashcmp](#) (pkg_resources.Distribution attribute), 363
[HasJobMetrics](#) (class in galaxy.model), 135
[HasName](#) (class in galaxy.model), 135
[HDADeserializer](#) (class in galaxy.managers.hdas), 162
[HDAFilterParser](#) (class in galaxy.managers.hdas), 163
[HDAManager](#) (class in galaxy.managers.hdas), 163
[HDAProvenanceController](#) (class in galaxy.webapps.galaxy.api.provenance), 32, 297
[HDASerializer](#) (class in galaxy.managers.hdas), 163
[header_dataprovider\(\)](#) (galaxy.datatypes.binary.Bam method), 45
[header_dataprovider\(\)](#) (galaxy.datatypes.tabular.Sam method), 87
[header_startswith](#) (galaxy_utils.sequence.vcf.VariantCall attribute), 357
[header_startswith](#) (galaxy_utils.sequence.vcf.VariantCall33 attribute), 357
[Heartbeat](#) (class in galaxy.util.heartbeat), 231
[help](#) (galaxy.tools.Tool attribute), 186
[help_by_page](#) (galaxy.tools.Tool attribute), 186
[HiddenDataToolParameter](#) (class in galaxy.tools.parameters.basic), 204
[HiddenField](#) (class in galaxy.web.form_builder), 243
[HiddenToolParameter](#) (class in galaxy.tools.parameters.basic), 204
[HideDatasetAction](#) (class in galaxy.jobs.actions.post), 121
[HierarchicalObjectStore](#) (class in galaxy.objectstore), 170
[HistoriesController](#) (class in galaxy.webapps.galaxy.api.histories), 14, 279
[History](#) (class in galaxy.model), 135
[history\(\)](#) (galaxy.webapps.galaxy.controllers.root.RootController method), 336
[history_add_to\(\)](#) (galaxy.webapps.galaxy.controllers.root.RootController method), 336
[history_as_xml\(\)](#) (galaxy.webapps.galaxy.controllers.root.RootController method), 337
[history_content_type](#) (galaxy.model.HistoryDatasetAssociation attribute), 136
[history_content_type](#) (galaxy.model.HistoryDatasetCollectionAssociation attribute), 137
[history_data\(\)](#) (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320
[history_dataset_collections\(\)](#) (galaxy.managers.collections.DatasetCollectionManager method), 159
[history_delete\(\)](#) (galaxy.webapps.galaxy.controllers.root.RootController method), 337
[history_detail\(\)](#) (galaxy.webapps.galaxy.controllers.mobile.Mobile method), 327
[history_get_default_permissions\(\)](#) (galaxy.security.GalaxyRBACAgent method), 178
[history_import\(\)](#) (galaxy.webapps.galaxy.controllers.root.RootController method), 337
[history_list\(\)](#) (galaxy.webapps.galaxy.controllers.mobile.Mobile method), 327
[history_new\(\)](#) (galaxy.webapps.galaxy.controllers.root.RootController method), 337
[history_options\(\)](#) (galaxy.webapps.galaxy.controllers.root.RootController method), 337

[history_set_default_permissions\(\)](#)
 (galaxy.security.GalaxyRBACAgent method), [178](#)
[history_set_default_permissions\(\)](#)
 (galaxy.security.RBACAgent method), [180](#)
[history_set_default_permissions\(\)](#)
 (galaxy.webapps.galaxy.controllers.root.RootController method), [337](#)
[HistoryAllPublishedGrid](#) (class in galaxy.webapps.galaxy.controllers.history), [319](#)
[HistoryAllPublishedGrid.NameURLColumn](#) (class in galaxy.webapps.galaxy.controllers.history), [319](#)
[HistoryAnnotationAssociation](#) (class in galaxy.model), [136](#)
[HistoryAnnotationsController](#) (class in galaxy.webapps.galaxy.api.annotations), [273](#)
[HistoryContentAnnotationsController](#) (class in galaxy.webapps.galaxy.api.annotations), [273](#)
[HistoryContentsController](#) (class in galaxy.webapps.galaxy.api.history_contents), [17](#), [282](#)
[HistoryContentTagsController](#) (class in galaxy.webapps.galaxy.api.item_tags), [284](#)
[HistoryController](#) (class in galaxy.webapps.galaxy.controllers.history), [320](#)
[HistoryDatasetAssociation](#) (class in galaxy.model), [136](#)
[HistoryDatasetAssociationAnnotationAssociation](#) (class in galaxy.model), [136](#)
[HistoryDatasetAssociationDisplayAtAuthorization](#) (class in galaxy.model), [136](#)
[HistoryDatasetAssociationListGrid](#) (class in galaxy.webapps.galaxy.controllers.dataset), [316](#)
[HistoryDatasetAssociationListGrid.HistoryColumn](#) (class in galaxy.webapps.galaxy.controllers.dataset), [316](#)
[HistoryDatasetAssociationListGrid.StatusColumn](#) (class in galaxy.webapps.galaxy.controllers.dataset), [316](#)
[HistoryDatasetAssociationRatingAssociation](#) (class in galaxy.model), [136](#)
[HistoryDatasetAssociationSelectionGrid](#) (class in galaxy.webapps.galaxy.controllers.page), [327](#)
[HistoryDatasetAssociationSubset](#) (class in galaxy.model), [136](#)
[HistoryDatasetAssociationTagAssociation](#) (class in galaxy.model), [136](#)
[HistoryDatasetCollectionAnnotationAssociation](#) (class in galaxy.model), [136](#)
[HistoryDatasetCollectionAssociation](#) (class in galaxy.model), [137](#)
[HistoryDatasetCollectionRatingAssociation](#) (class in galaxy.model), [137](#)
[HistoryDatasetCollectionTagAssociation](#) (class in galaxy.model), [137](#)
[HistoryDatasetExtendMetadataController](#) (class in galaxy.webapps.galaxy.api.extended_metadata), [10](#), [275](#)
[HistoryDeserializer](#) (class in galaxy.managers.histories), [164](#)
[HistoryField](#) (class in galaxy.web.form_builder), [244](#)
[HistoryFilters](#) (class in galaxy.managers.histories), [164](#)
[HistoryListGrid](#) (class in galaxy.webapps.galaxy.controllers.history), [321](#)
[HistoryListGrid.DatasetsByStateColumn](#) (class in galaxy.webapps.galaxy.controllers.history), [321](#)
[HistoryListGrid.DeletedColumn](#) (class in galaxy.webapps.galaxy.controllers.history), [321](#)
[HistoryListGrid.HistoryListNameColumn](#) (class in galaxy.webapps.galaxy.controllers.history), [322](#)
[HistoryManager](#) (class in galaxy.managers.histories), [164](#)
[HistoryRatingAssociation](#) (class in galaxy.model), [137](#)
[HistorySelectionGrid](#) (class in galaxy.webapps.galaxy.controllers.page), [327](#)
[HistorySerializer](#) (class in galaxy.managers.histories), [165](#)
[HistoryTagAssociation](#) (class in galaxy.model), [137](#)
[HistoryTagsController](#) (class in galaxy.webapps.galaxy.api.item_tags), [285](#)
[HistoryUserShareAssociation](#) (class in galaxy.model), [137](#)
[hmac_new\(\)](#) (in module galaxy.util.hash_util), [230](#)
[HostAgent](#) (class in galaxy.security), [179](#)
[Html](#) (class in galaxy.datatypes.images), [60](#)
[html_table](#) (galaxy.datatypes.genetics.RexpBase attribute), [57](#)
[http_error_default\(\)](#) (galaxy.eggs.URLRetriever method), [101](#)
[HttpDataTransferFactory](#) (class in galaxy.sample_tracking.data_transfer), [174](#)
[humanize\(\)](#) (galaxy.util.inflection.Base method), [231](#)
[humanize\(\)](#) (galaxy.util.inflection.Inflector method), [232](#)
[id_seq_qual_dataprovider\(\)](#)
 (galaxy.datatypes.binary.Bam method), [45](#)

- `id_seq_qual_dataprovider()`
(`galaxy.datatypes.tabular.Sam` method), 87
- `Idat` (class in `galaxy.datatypes.binary`), 47
- `iff()` (in module `galaxy.web.framework.helpers`), 257
- `Im` (class in `galaxy.datatypes.images`), 60
- `Image` (class in `galaxy.datatypes.images`), 60
- `image_type()` (in module `galaxy.datatypes.util.image_util`), 100
- `IMetadataProvider` (class in `pkg_resources`), 366
- `immediate_actions` (`galaxy.jobs.actions.post.ActionBox` attribute), 120
- `imp()` (`galaxy.webapps.galaxy.controllers.dataset.DatasetInterface` method), 315
- `imp()` (`galaxy.webapps.galaxy.controllers.history.HistoryController` method), 320
- `impersonate()` (`galaxy.webapps.galaxy.controllers.admin.AdminGalaxy` method), 306
- `ImplicitlyConvertedDatasetAssociation` (class in `galaxy.model`), 137
- `ImplicitlyCreatedDatasetCollectionInput` (class in `galaxy.model`), 137
- `import_archive()` (`galaxy.webapps.galaxy.controllers.history.HistoryController` method), 320
- `import_datasets_to_histories()`
(`galaxy.webapps.galaxy.controllers.library_common_library_common` method), 325
- `import_module()` (in module `galaxy.util.backports.importlib`), 237
- `import_new_workflow_deprecated()`
(`galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController` method), 40, 304
- `import_shared_workflow_deprecated()`
(`galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController` method), 40, 304
- `import_visualization()` (`galaxy.web.base.controller.UsesVisualizationMixin` method), 251
- `import_workflow()` (`galaxy.webapps.galaxy.api.tool_shed_repository_tool_shed_repository` method), 35, 299
- `import_workflow()` (`galaxy.webapps.galaxy.controllers.admin_tool_shed_repository_tool_shed_repository` method), 313
- `import_workflows()` (`galaxy.webapps.galaxy.api.tool_shed_repository_tool_shed_repository` method), 36, 300
- `ImportHistoryTool` (class in `galaxy.tools`), 183
- `ImportHistoryToolAction` (class in `galaxy.tools.actions.history_imp_exp`), 191
- `ImportsHistoryMixin` (class in `galaxy.web.base.controller`), 248
- `in_directory()` (in module `galaxy.util`), 226
- `in_ready_state()` (`galaxy.model.Dataset` method), 129
- `InappropriateDatasetContentError`, 82
- `InconsistentDatabase`, 104
- `increase_running_job_count()`
(`galaxy.jobs.handler.JobHandlerQueue` method), 118
- `index()` (`galaxy.web.base.controllers.admin.Admin` method), 251
- `index()` (`galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController` method), 7, 272
- `index()` (`galaxy.webapps.galaxy.api.configuration.ConfigurationController` method), 9, 273
- `index()` (`galaxy.webapps.galaxy.api.dataset_collections.DatasetCollectionsController` method), 9, 274
- `index()` (`galaxy.webapps.galaxy.api.datatypes.DatatypesController` method), 9, 274
- `index()` (`galaxy.webapps.galaxy.api.extended_metadata.BaseExtendedMetadataController` method), 10, 275
- `index()` (`galaxy.webapps.galaxy.api.folder_contents.FolderContentsController` method), 11, 275
- `index()` (`galaxy.webapps.galaxy.api.folders.FoldersController` method), 12, 277
- `index()` (`galaxy.webapps.galaxy.api.forms.FormDefinitionAPIController` method), 13, 278
- `index()` (`galaxy.webapps.galaxy.api.genomes.GenomesController` method), 13, 278
- `index()` (`galaxy.webapps.galaxy.api.group_roles.GroupRolesAPIController` method), 14, 278
- `index()` (`galaxy.webapps.galaxy.api.group_users.GroupUsersAPIController` method), 14, 279
- `index()` (`galaxy.webapps.galaxy.api.groups.GroupAPIController` method), 14, 279
- `index()` (`galaxy.webapps.galaxy.api.histories.HistoriesController` method), 16, 280
- `index()` (`galaxy.webapps.galaxy.api.history_contents.HistoryContentsController` method), 19, 283
- `index()` (`galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController` method), 20, 284
- `index()` (`galaxy.webapps.galaxy.api.job_files.JobFilesAPIController` method), 21, 285
- `index()` (`galaxy.webapps.galaxy.api.jobs.JobController` method), 21, 286
- `index()` (`galaxy.webapps.galaxy.api.libraries.LibrariesController` method), 26, 291
- `index()` (`galaxy.webapps.galaxy.api.library_contents.LibraryContentsController` method), 29, 294
- `index()` (`galaxy.webapps.galaxy.api.page_revisions.PageRevisionsController` method), 31, 295
- `index()` (`galaxy.webapps.galaxy.api.pages.PagesController` method), 32, 296
- `index()` (`galaxy.webapps.galaxy.api.provenance.BaseProvenanceController` method), 32, 297
- `index()` (`galaxy.webapps.galaxy.api.quotas.QuotaAPIController` method), 33, 297
- `index()` (`galaxy.webapps.galaxy.api.request_types.RequestTypeAPIController` method), 33, 298
- `index()` (`galaxy.webapps.galaxy.api.requests.RequestsAPIController` method), 33, 298
- `index()` (`galaxy.webapps.galaxy.api.roles.RoleAPIController` method), 34, 298

[index\(\) \(galaxy.webapps.galaxy.api.samples.SamplesAPIController method\), 34, 298](#)
[index\(\) \(galaxy.webapps.galaxy.api.tool_data.ToolData method\), 35, 299](#)
[index\(\) \(galaxy.webapps.galaxy.api.tool_shed_repositories.ToolShedRepositoriesController method\), 36, 300](#)
[index\(\) \(galaxy.webapps.galaxy.api.users.UserAPIController method\), 38, 302](#)
[index\(\) \(galaxy.webapps.galaxy.api.visualizations.VisualizationController method\), 38, 302](#)
[index\(\) \(galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController method\), 40, 304](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.async.ASync method\), 314](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.error.Error method\), 317](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.history.HistoryController method\), 320](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.library.Library method\), 323](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.mobile.Mobile method\), 327](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.requests.Requests method\), 332](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin method\), 333](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.root.RootController method\), 337](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner method\), 338](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.ucsc_proxy.UCSCProxy method\), 338](#)
[index\(\) \(galaxy.webapps.galaxy.controllers.user.User method\), 339](#)
[index\(\) \(galaxy.webapps.reports.controllers.root.Report method\), 343](#)
[index\(\) \(galaxy.webapps.reports.controllers.system.System method\), 345](#)
[index_invocations\(\) \(galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController method\), 40, 304](#)
[IndividualTagsColumn \(class in galaxy.web.framework.helpers.grids\), 261](#)
[Inflector \(class in galaxy.util.inflection\), 232](#)
[info \(galaxy.model.LibraryDataset attribute\), 141](#)
[info_text \(galaxy.web.framework.helpers.grids.Grid attribute\), 259](#)
[info_text \(galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute\), 322](#)
[inheritable \(galaxy.model.LibraryDatasetDatasetInfoAssociation attribute\), 142](#)
[init_meta\(\) \(galaxy.datatypes.binary.Bam method\), 45](#)
[init_meta\(\) \(galaxy.datatypes.binary.SQLite method\), 48](#)
[init_meta\(\) \(galaxy.datatypes.data.Data method\), 52](#)
[init_meta\(\) \(galaxy.datatypes.data.Newick method\), 53](#)
[init_meta\(\) \(galaxy.datatypes.data.Nexus method\), 53](#)
[init_meta\(\) \(galaxy.datatypes.genetics.RexpBase method\), 57](#)
[init_meta\(\) \(galaxy.datatypes.interval.Interval method\), 80](#)
[init_meta\(\) \(galaxy.datatypes.sequence.Maf method\), 80](#)
[init_meta\(\) \(galaxy.datatypes.tabular.Pileup method\), 86](#)
[init_meta\(\) \(galaxy.model.DatasetInstance method\), 132](#)
[init_meta\(\) \(galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin method\), 333](#)
[init_meta\(\) \(galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method\), 313](#)
[inject\(\) \(galaxy.workflow.modules.WorkflowModuleInjector method\), 351](#)
[inprogress_dataset_files \(galaxy.model.Sample attribute\), 145](#)
[input_paths\(\) \(galaxy.jobs.ComputeEnvironment method\), 112](#)
[input_paths\(\) \(galaxy.jobs.SharedComputeEnvironment method\), 116](#)
[InputDataCollectionModule \(class in galaxy.workflow.modules\), 347](#)
[InputDataModule \(class in galaxy.workflow.modules\), 347](#)
[InputModule \(class in galaxy.workflow.modules\), 348](#)
[inputs\(\) \(galaxy.webapps.galaxy.api.jobs.JobController method\), 22, 286](#)
[InputRangeValidator \(class in galaxy.tools.parameters.validation\), 219](#)
[insert_on\(\) \(pkg_resources.Distribution method\), 363](#)
[InsertColumnToolOutputActionOptionFilter \(class in galaxy.tools.parameters.output\), 215](#)
[install_latest_repository_revision\(\) \(galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method\), 313](#)
[install_model \(galaxy.managers.context.ProvidesAppContext method\), 313](#)
[install_repository_revision\(\) \(galaxy.webapps.galaxy.api.tool_shed_repositories.ToolShedRepositoriesController method\), 36, 300](#)
[install_repository_revisions\(\) \(galaxy.webapps.galaxy.api.tool_shed_repositories.ToolShedRepositoriesController method\), 36, 301](#)
[install_tool_dependencies_with_update\(\) \(galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method\), 313](#)
[installed_len_files \(galaxy.webapps.galaxy.controllers.user.User attribute\), 339](#)
[installed_repository_grid \(galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed attribute\), 313](#)
[installed_tool_dependencies \(galaxy.tools.Tool attribute\), 313](#)

186

insufficient_quality_length()
(galaxy_utils.sequence.fastq.fastqCSSangerRead method), 353

insufficient_quality_length()
(galaxy_utils.sequence.fastq.fastqSequencingReads_case() method), 355

InsufficientPermissionsException, 104

int() (galaxy.managers.base.ModelValidator method), 157

int_range() (galaxy.managers.base.ModelValidator method), 157

IntegerColumn (class in galaxy.web.framework.helpers.grids), 261

IntegerToolParameter (class in galaxy.tools.parameters.basic), 204

integrated_datatypes_configs
(galaxy.datatypes.registry.Registry attribute), 76

InternalServerError, 104

InterruptedUpload, 183

Interval (class in galaxy.datatypes.interval), 68

interval_dataprovider() (galaxy.datatypes.interval.Gff method), 66

interval_dataprovider() (galaxy.datatypes.interval.Interval method), 68

interval_dict_dataprovider()
(galaxy.datatypes.interval.Gff method), 66

interval_dict_dataprovider()
(galaxy.datatypes.interval.Interval method), 68

invalid_id_redirect() (in module galaxy.webapps.galaxy.controllers.requests_common), 335

invalid_marker() (in module pkg_resources), 365

invalidate_external_metadata()
(galaxy.datatypes.metadata.JobExternalOutputMetadataWrapper method), 71

invalidate_external_metadata() (galaxy.jobs.JobWrapper method), 115

invocation_step() (galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController method), 40, 304

invoke() (galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController method), 41, 305

IResourceProvider (class in pkg_resources), 366

is_accessible() (galaxy.managers.hdas.HDAManager method), 163

is_admin_user() (galaxy.config.Configuration method), 42

is_ascii_encoded() (galaxy_utils.sequence.fastq.fastqSequencingRead method), 355

is_binary (galaxy.datatypes.data.Data attribute), 52

is_binary (galaxy.datatypes.genetics.RexpBase attribute), 57

is_binary (galaxy.datatypes.ngsindex.BowtieIndex attribute), 74

is_binary() (in module galaxy.util), 226

is_bz2() (in module galaxy.datatypes.checkers), 49

is_case() (galaxy.external_services.service.BooleanExternalServiceActions method), 108

is_case() (galaxy.external_services.service.ExternalServiceActionsGroupW method), 108

is_case() (galaxy.external_services.service.ItemIsInstanceExternalServiceA method), 109

is_case() (galaxy.external_services.service.ValueExternalServiceActionsGro method), 109

is_case() (galaxy.tools.parameters.output.DatatypeIsInstanceToolOutputAct method), 214

is_case() (galaxy.tools.parameters.output.ToolOutputActionConditionalWh method), 216

is_case() (galaxy.tools.parameters.output.ValueToolOutputActionCondition method), 217

is_check_time (galaxy.model.DeferredJob attribute), 133

is_checked() (galaxy.web.form_builder.CheckboxField static method), 242

is_collection (galaxy.model.DatasetCollectionElement attribute), 130

is_column_based() (in module galaxy.datatypes.sniff), 84

is_complete (galaxy.model.Request attribute), 144

is_current_version() (galaxy.tools.data.ToolDataTable method), 194

is_DNA() (galaxy_utils.sequence.sequence.SequencingRead method), 356

is_ext_unsniffable() (galaxy.datatypes.binary.Binary static method), 46

is_first_mate() (galaxy_utils.sequence.fastq.fastqJoiner method), 354

is_float() (galaxy.datatypes.tabular.CSV method), 85

is_gzip() (in module galaxy.datatypes.checkers), 49

is_handler() (galaxy.jobs.JobConfiguration method), 114

is_hash_util() (in module galaxy.util.hash_util), 230

is_id() (galaxy.jobs.JobConfiguration method), 114

is_int() (galaxy.datatypes.tabular.CSV method), 85

is_job_resource_conditional
(galaxy.tools.parameters.grouping.Conditional attribute), 211

is_known_value() (galaxy.datatypes.metadata.MetadataTempFile class method), 73

is_multi_byte() (galaxy.model.Dataset method), 129

is_multi_byte() (galaxy.model.DatasetInstance method), 132

is_multi_byte() (in module galaxy.util), 226

is_named_collection_part_name()
(galaxy.tools.ToolOutputCollectionPart static method), 189

is_new (galaxy.model.Request attribute), 144

is_outside_grace_period()
(galaxy.webapps.galaxy.controllers.user.User method), 339

- is_owner() (galaxy.managers.hdas.HDAManager method), 163
- is_owner() (galaxy.managers.histories.HistoryManager method), 164
- is_pending (galaxy.model.DatasetInstance attribute), 132
- is_preparing() (galaxy.datatypes.display_applications.parameters.DisplayApplicationParameters method), 97
- is_preparing() (galaxy.datatypes.display_applications.parameters.DisplayApplicationParameters method), 97
- is_public() (galaxy.managers.libraries.LibraryManager method), 166
- is_rejected (galaxy.model.Request attribute), 144
- is_sniffable_binary() (galaxy.datatypes.binary.Binary static method), 46
- is_submitted (galaxy.model.Request attribute), 144
- is_tag() (galaxy.jobs.JobConfiguration method), 114
- is_tool_module_type() (in module galaxy.workflow.modules), 352
- is_true() (in module galaxy.web.framework.helpers), 257
- is_unsubmitted (galaxy.model.Request attribute), 144
- is_uuid() (in module galaxy.util), 226
- is_valid_format() (galaxy_utils.sequence.fastq.fastqSequencingRead method), 355
- is_valid_sequence() (galaxy_utils.sequence.fastq.fastqSequencingRead method), 355
- item_has_tag() (galaxy.managers.tags.TagManager method), 168
- item_permission_map_for_add() (galaxy.security.GalaxyRBACAgent method), 178
- item_permission_map_for_manage() (galaxy.security.GalaxyRBACAgent method), 178
- item_permission_map_for_modify() (galaxy.security.GalaxyRBACAgent method), 178
- ItemAccessibilityException, 104
- ItemDeletionException, 104
- ItemIsInstanceExternalServiceActionsGroupWhen (class in galaxy.external_services.service), 108
- ItemOwnershipException, 104
- ItemRatingAssociation (class in galaxy.model), 138
- items() (galaxy.datatypes.metadata.MetadataCollection method), 71
- items() (galaxy.util.bunch.Bunch method), 230
- items() (galaxy.util.odict.odict method), 235
- ItemSelectionGrid (class in galaxy.webapps.galaxy.controllers.page), 327
- ItemSelectionGrid.NameColumn (class in galaxy.webapps.galaxy.controllers.page), 327
- ItemTagAssociation (class in galaxy.model), 138
- ItemTagAssocInfo (class in galaxy.managers.tags), 167
- iter() (galaxy.datatypes.metadata.MetadataSpecCollection method), 72
- iter_blocks_split_by_species() (in module galaxy.tools.util.maf_utilities), 224
- iter_blocks_split_by_src() (in module galaxy.tools.util.maf_utilities), 224
- iter_components_by_src() (in module galaxy.tools.util.maf_utilities), 224
- iter_components_by_src_start() (in module galaxy.tools.util.maf_utilities), 224
- iter_entry_points() (pkg_resources.WorkingSet method), 361
- iter_fasta_alignment() (in module galaxy.tools.util.maf_utilities), 224
- iterate_file() (in module galaxy.web.framework.base), 256
- iteritems() (galaxy.util.odict.odict method), 235
- iterkeys() (galaxy.util.odict.odict method), 235
- itervalues() (galaxy.util.odict.odict method), 235
- ## J
- Job (class in galaxy.model), 138
- job_destination (galaxy.jobs.JobWrapper attribute), 115
- job_enqueue() (galaxy.tools.SetMetadataTool method), 183
- job_failed() (galaxy.tools.Tool method), 186
- job_info() (galaxy.web.base.controllers.admin.Admin method), 251
- job_info() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
- job_pair_for_id() (galaxy.jobs.handler.JobHandlerQueue method), 118
- job_states (galaxy.jobs.deferred.DeferredJobQueue attribute), 122
- job_wrapper() (galaxy.jobs.handler.JobHandlerQueue method), 118
- JobConfiguration (class in galaxy.jobs), 112
- JobController (class in galaxy.webapps.galaxy.api.jobs), 21, 286
- JobDestination (class in galaxy.jobs), 114
- JobExportHistoryArchive (class in galaxy.model), 140
- JobExportHistoryArchiveWrapper (class in galaxy.tools.imp_exp), 195
- JobExternalOutputMetadata (class in galaxy.model), 140
- JobExternalOutputMetadataWrapper (class in galaxy.datatypes.metadata), 71
- JobFilesAPIController (class in galaxy.webapps.galaxy.api.job_files), 20, 285
- JobHandler (class in galaxy.jobs.handler), 118
- JobHandlerQueue (class in galaxy.jobs.handler), 118
- JobHandlerStopQueue (class in galaxy.jobs.handler), 118
- JobImportHistoryArchive (class in galaxy.model), 140
- JobImportHistoryArchiveWrapper (class in galaxy.tools.imp_exp), 196

JobManager (class in galaxy.jobs.manager), 119
 JobMappingException, 119
 JobMetricNumeric (class in galaxy.model), 140
 JobMetricText (class in galaxy.model), 140
 JobNotReadyException, 119
 JobParameter (class in galaxy.model), 140
 JobRunnerMapper (class in galaxy.jobs.mapper), 119
 Jobs (class in galaxy.webapps.reports.controllers.jobs), 341
 jobs() (galaxy.web.base.controllers.admin.Admin method), 252
 JobState (class in galaxy.jobs.runners), 125
 JobStateHistory (class in galaxy.model), 140
 JobToImplicitOutputDatasetCollectionAssociation (class in galaxy.model), 140
 JobToInputDatasetAssociation (class in galaxy.model), 140
 JobToInputDatasetCollectionAssociation (class in galaxy.model), 140
 JobToInputLibraryDatasetAssociation (class in galaxy.model), 140
 JobToolConfiguration (class in galaxy.jobs), 114
 JobToOutputDatasetAssociation (class in galaxy.model), 140
 JobToOutputDatasetCollectionAssociation (class in galaxy.model), 141
 JobToOutputLibraryDatasetAssociation (class in galaxy.model), 141
 JobWrapper (class in galaxy.jobs), 114
 join() (galaxy_utils.sequence.fastq.fastqJoiner method), 354
 Jpg (class in galaxy.datatypes.images), 61
 js() (in module galaxy.web.framework.helpers), 257
 js_helper() (in module galaxy.web.framework.helpers), 257
 json_fix() (in module galaxy.tools), 189
 json_fix() (in module galaxy.util.json), 234
 jsonrpc_request() (in module galaxy.util.json), 234
 jsonrpc_response() (in module galaxy.util.json), 234

K

k (galaxy.webapps.galaxy.api.samples.SamplesAPIController attribute), 34, 298
 key (galaxy_utils.sequence.transform.ColorSpaceConverter attribute), 356
 key (pkg_resources.Distribution attribute), 363
 keys() (galaxy.util.bunch.Bunch method), 230
 keys() (galaxy.util.odict.odict method), 235
 known_outputs() (galaxy.tools.ToolOutputCollection method), 189

L

label (galaxy.tools.parameters.grouping.Conditional attribute), 211

label() (galaxy.tools.parameters.grouping.Repeat method), 212
 label() (galaxy.tools.parameters.grouping.Section method), 212
 Laj (class in galaxy.datatypes.images), 61
 last_access_date() (galaxy.webapps.reports.controllers.users.Users method), 345
 last_check (galaxy.model.DeferredJob attribute), 133
 last_comment (galaxy.model.Request attribute), 144
 LastzCoverage (class in galaxy.datatypes.coverage), 49
 latest_event (galaxy.model.Request attribute), 144
 latest_event (galaxy.model.Sample attribute), 145
 latest_export (galaxy.model.History attribute), 135
 LateValidationError, 219
 Lav (class in galaxy.datatypes.sequence), 79
 lazy_property (in module galaxy.web.framework.base), 256
 LazyProperty (class in galaxy.web.framework.base), 254
 ldda_edit_info() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 325
 ldda_info() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 325
 ldda_permissions() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 326
 LDDAManager (class in galaxy.managers.lddas), 165
 LDDAProvenanceController (class in galaxy.webapps.galaxy.api.provenance), 32, 297
 ldIndep (class in galaxy.datatypes.genetics), 58
 legal_values (galaxy.tools.parameters.basic.BooleanToolParameter attribute), 197
 legend (galaxy.web.framework.helpers.grids.Grid attribute), 260
 LengthValidator (class in galaxy.tools.parameters.validation), 219
 LibrariesController (class in galaxy.webapps.galaxy.api.libraries), 25, 290
 Library (class in galaxy.model), 141
 Library (class in galaxy.webapps.galaxy.controllers.library), 323
 library_dataset_info() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 326
 library_dataset_permissions() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 326
 library_info() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 326
 library_is_public() (galaxy.security.GalaxyRBACAgent method), 178
 library_is_public() (galaxy.security.RBACAgent method), 180
 library_is_unrestricted() (galaxy.security.GalaxyRBACAgent method), 178

[library_item_updates\(\)](#) (galaxy.webapps.galaxy.controllers.library_admin.LibraryAdmin method), 326
[library_list_grid](#) (galaxy.webapps.galaxy.controllers.library.Library attribute), 323
[library_list_grid](#) (galaxy.webapps.galaxy.controllers.library_admin.LibraryAdmin attribute), 324
[library_path](#) (galaxy.model.LibraryFolder attribute), 143
[library_permissions\(\)](#) (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 326
[LibraryAdmin](#) (class in galaxy.webapps.galaxy.controllers.library_admin), 324
[LibraryCommon](#) (class in galaxy.webapps.galaxy.controllers.library_common), 325
[LibraryContentsController](#) (class in galaxy.webapps.galaxy.api.library_contents), 28, 293
[LibraryDataset](#) (class in galaxy.model), 141
[LibraryDatasetCollectionAnnotationAssociation](#) (class in galaxy.model), 141
[LibraryDatasetCollectionAssociation](#) (class in galaxy.model), 141
[LibraryDatasetCollectionRatingAssociation](#) (class in galaxy.model), 141
[LibraryDatasetCollectionTagAssociation](#) (class in galaxy.model), 142
[LibraryDatasetDatasetAssociation](#) (class in galaxy.model), 142
[LibraryDatasetDatasetAssociationPermissions](#) (class in galaxy.model), 142
[LibraryDatasetDatasetInfoAssociation](#) (class in galaxy.model), 142
[LibraryDatasetExtendMetadataController](#) (class in galaxy.webapps.galaxy.api.extended_metadata), 10, 275
[LibraryDatasetPermissions](#) (class in galaxy.model), 142
[LibraryDatasetsController](#) (class in galaxy.webapps.galaxy.api.lda_datasets), 23, 287
[LibraryDatasetToolParameter](#) (class in galaxy.tools.parameters.basic), 205
[LibraryField](#) (class in galaxy.web.form_builder), 244
[LibraryFolder](#) (class in galaxy.model), 142
[LibraryFolderInfoAssociation](#) (class in galaxy.model), 143
[LibraryFolderPermissions](#) (class in galaxy.model), 143
[LibraryInfoAssociation](#) (class in galaxy.model), 143
[LibraryListGrid](#) (class in galaxy.webapps.galaxy.controllers.library), 323
[LibraryListGrid](#) (class in galaxy.webapps.galaxy.controllers.library_admin), 324
[LibraryListGrid.DescriptionColumn](#) (class in galaxy.webapps.galaxy.controllers.library_admin), 324
[LibraryListGrid.NameColumn](#) (class in galaxy.webapps.galaxy.controllers.library_admin), 324
[LibraryListGrid.StatusColumn](#) (class in galaxy.webapps.galaxy.controllers.library_admin), 324
[LibraryManager](#) (class in galaxy.managers.libraries), 166
[LibraryPermissions](#) (class in galaxy.model), 143
[line_class](#) (galaxy.datatypes.data.Text attribute), 53
[line_class](#) (galaxy.datatypes.interval.Interval attribute), 68
[line_class](#) (galaxy.datatypes.tabular.Pileup attribute), 86
[line_dataprovider\(\)](#) (galaxy.datatypes.binary.Bam method), 45
[line_dataprovider\(\)](#) (galaxy.datatypes.data.Text method), 54
[line_dataprovider\(\)](#) (galaxy.datatypes.tabular.Sam method), 87
[line_enumerator\(\)](#) (in galaxy.tools.util.maf_utilities), 224
[LineCount](#) (class in galaxy.datatypes.data), 53
[lines\(\)](#) (galaxy.datatypes.util.gff_util.GFFFeature method), 99
[list\(\)](#) (galaxy.managers.base.ModelManager method), 156
[list\(\)](#) (galaxy.managers.libraries.LibraryManager method), 166
[list\(\)](#) (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315
[list\(\)](#) (galaxy.webapps.galaxy.controllers.history.HistoryController method), 320
[list\(\)](#) (galaxy.webapps.galaxy.controllers.library.Library method), 323
[list\(\)](#) (galaxy.webapps.galaxy.controllers.page.PageController method), 329
[list_as_xml\(\)](#) (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321
[list_datasets_for_selection\(\)](#) (galaxy.webapps.galaxy.controllers.page.PageController method), 329
[list_histories_for_selection\(\)](#) (galaxy.webapps.galaxy.controllers.page.PageController method), 329
[list_pages_for_selection\(\)](#) (galaxy.webapps.galaxy.controllers.page.PageController method), 329

- method), 329
 - list_published() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321
 - list_published() (galaxy.webapps.galaxy.controllers.page.PageController method), 329
 - list_shared() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321
 - list_visualizations_for_selection() (galaxy.webapps.galaxy.controllers.page.PageController method), 329
 - list_workflows_for_selection() (galaxy.webapps.galaxy.controllers.page.PageController method), 329
 - listify() (in module galaxy.util), 226
 - ListParameter (class in galaxy.datatypes.metadata), 71
 - load() (galaxy.util.aliaspickler.AliasPickleModule method), 229
 - load() (galaxy.webapps.galaxy.api.lda_datasets.LibraryDatasetsController method), 24, 288
 - load() (pkg_resources.EntryPoint method), 363
 - load_all() (galaxy.sample_tracking.external_service_types.ExternalServiceTypesCollection method), 175
 - load_build_sites() (galaxy.datatypes.registry.Registry method), 76
 - load_data_transfer_settings() (galaxy.model.ExternalService method), 134
 - load_datatype_converters() (galaxy.datatypes.registry.Registry method), 76
 - load_datatype_sniffers() (galaxy.datatypes.registry.Registry method), 76
 - load_datatypes() (galaxy.datatypes.registry.Registry method), 76
 - load_display_applications() (galaxy.datatypes.registry.Registry method), 76
 - load_egg_for_url() (in module galaxy.model.orm), 153
 - load_entry_point() (in module pkg_resources), 359
 - load_entry_point() (pkg_resources.Distribution method), 363
 - load_external_metadata_tool() (galaxy.datatypes.registry.Registry method), 76
 - load_external_service_type() (galaxy.sample_tracking.external_service_types.ExternalServiceTypesCollection method), 175
 - load_from_config_file() (galaxy.tools.data.ToolDataTableManager method), 194
 - load_history_imp_exp_tools() (in module galaxy.tools.imp_exp), 196
 - load_module_sections() (in module galaxy.workflow.modules), 352
 - load_sub_elems() (galaxy.external_services.service.ExternalServiceActionsGroup method), 108
 - loader (pkg_resources.NullProvider attribute), 367
 - loads() (galaxy.util.aliaspickler.AliasPickleModule method), 230
 - load_extra_dir() (in module galaxy.util.json), 234
 - local_extra_dirs() (in module galaxy.objectstore), 172
 - LocalJobRunner (class in galaxy.jobs.runners.local), 127
 - log_action() (galaxy.managers.context.ProvidesAppContext method), 160
 - log_event() (galaxy.jobs.deferred.FakeTrans method), 122
 - log_event() (galaxy.managers.context.ProvidesAppContext method), 160
 - log_tempfile (module), 357
 - login_user_action_async() (galaxy.webapps.galaxy.controllers.user.User method), 339
 - LoggingProxy (class in galaxy.model.orm.logging_connection_proxy), 153
 - login() (galaxy.webapps.galaxy.controllers.user.User method), 339
 - logout() (galaxy.webapps.galaxy.controllers.user.User method), 339
 - LRUCache (class in galaxy.util.lrucache), 234
 - lucene_search() (in module galaxy.webapps.galaxy.controllers.library_common), 326
 - LwrJobRunner (class in galaxy.jobs.runners.lwr), 127
- ## M
- Maf (class in galaxy.datatypes.sequence), 80
 - maf_index_by_uid() (in module galaxy.tools.util.maf_utilities), 224
 - MafCustomTrack (class in galaxy.datatypes.sequence), 80
 - main() (in module galaxy.datatypes.converters.bgzip), 92
 - main() (in module galaxy.datatypes.converters.fastq_to_fqtc), 92
 - main() (in module galaxy.datatypes.converters.gff_to_interval_index_converter), 93
 - main() (in module galaxy.datatypes.converters.interval_to_coverage), 93
 - main() (in module galaxy.datatypes.converters.interval_to_fli), 93
 - main() (in module galaxy.datatypes.converters.interval_to_interval_index_converter), 94
 - main() (in module galaxy.datatypes.converters.interval_to_tabix_converter), 94
 - main() (in module galaxy.datatypes.converters.lped_to_fped_converter), 94
 - main() (in module galaxy.datatypes.converters.lped_to_pbed_converter), 94
 - main() (in module galaxy.datatypes.converters.pbed_to_lped_converter), 95
 - main() (in module galaxy.datatypes.converters.pbed_to_lped_converter), 95

[main\(\)](#) (in module `galaxy.datatypes.converters.vcf_to_interval`), 95
[main\(\)](#) (in module `galaxy.datatypes.converters.vcf_to_vcf_bgzip`), 96
[main\(\)](#) (in module `galaxy.datatypes.converters.wiggle_to_array_tree`), 96
[main\(\)](#) (in module `galaxy.datatypes.converters.wiggle_to_simple_converter`), 96
[makeLDreduced\(\)](#) (in module `galaxy.datatypes.converters.pbbed_ldreduced_converter`), 196
[make_body_iterable\(\)](#) (`galaxy.web.framework.base.WebApplication` method), 256
[make_copy\(\)](#) (`galaxy.datatypes.metadata.FileParameter` method), 70
[make_copy\(\)](#) (`galaxy.datatypes.metadata.MetadataParameter` method), 72
[make_dataset_public\(\)](#) (`galaxy.security.GalaxyRBACAgent` method), 178
[make_dataset_public\(\)](#) (`galaxy.security.RBACAgent` method), 180
[make_dict_copy\(\)](#) (`galaxy.datatypes.metadata.MetadataCollection` method), 71
[make_file\(\)](#) (`galaxy.web.framework.base.FieldStorage` method), 254
[make_filter\(\)](#) (in module `galaxy.web.framework.middleware.translogger`), 265
[make_folder_public\(\)](#) (`galaxy.security.GalaxyRBACAgent` method), 178
[make_folder_public\(\)](#) (`galaxy.security.RBACAgent` method), 180
[make_html_peek_header\(\)](#) (`galaxy.datatypes.tabular.TabularData` method), 89
[make_html_peek_rows\(\)](#) (`galaxy.datatypes.tabular.TabularData` method), 89
[make_html_table\(\)](#) (`galaxy.datatypes.genetics.GenomeGraphs` method), 55
[make_html_table\(\)](#) (`galaxy.datatypes.genetics.RexpBase` method), 57
[make_html_table\(\)](#) (`galaxy.datatypes.sequence.Maf` method), 80
[make_html_table\(\)](#) (`galaxy.datatypes.tabular.Eland` method), 85
[make_html_table\(\)](#) (`galaxy.datatypes.tabular.TabularData` method), 89
[make_library_item_public\(\)](#) (`galaxy.webapps.galaxy.controllers.library_common.LibraryCommon` method), 326
[make_library_public\(\)](#) (`galaxy.security.GalaxyRBACAgent` method), 178
[make_library_public\(\)](#) (`galaxy.security.RBACAgent` method), 180
[make_library_public_dataset\(\)](#) (`galaxy.webapps.galaxy.controllers.library_common.LibraryCommon` method), 326
[make_public\(\)](#) (`galaxy.managers.libraries.LibraryManager` method), 167
[make_static\(\)](#) (in module `galaxy.web.framework.middleware.static`), 265
[makeLDreduced\(\)](#) (in module `galaxy.datatypes.converters.pbbed_ldreduced_converter`), 196
[makeNode\(\)](#) (`galaxy.visualization.data_providers.phyloviz.baseparser.Phylo` method), 240
[MalformedId](#), 104
[MAlist](#) (class in `galaxy.datatypes.genetics`), 56
[manage_addresses\(\)](#) (`galaxy.webapps.galaxy.controllers.user.User` method), 339
[manage_datasets\(\)](#) (`galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin` method), 333
[manage_repositories\(\)](#) (`galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed` method), 313
[manage_repository\(\)](#) (`galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed` method), 313
[manage_repository_tool_dependencies\(\)](#) (`galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed` method), 313
[manage_roles_and_groups_for_user\(\)](#) (`galaxy.web.base.controllers.admin.Admin` method), 252
[manage_template_inheritance\(\)](#) (`galaxy.webapps.galaxy.controllers.library_common.LibraryCommon` method), 326
[manage_tool_dependencies\(\)](#) (`galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed` method), 313
[manage_user_info\(\)](#) (`galaxy.webapps.galaxy.controllers.user.User` method), 339
[manage_users_and_groups_for_quota\(\)](#) (`galaxy.webapps.galaxy.controllers.admin.AdminGalaxy` method), 306
[manage_users_and_groups_for_role\(\)](#) (`galaxy.web.base.controllers.admin.Admin` method), 252
[manage_users_and_roles_for_group\(\)](#) (`galaxy.web.base.controllers.admin.Admin` method), 252
[ManualDataTransferPlugin](#) (class in `galaxy.jobs.deferred.manual_data_transfer`), 266
[map_library_datasets_to_lddas\(\)](#) (in module `galaxy.webapps.galaxy.controllers.library_common`), 326
[map_wrap\(\)](#) (in module `galaxy.objectstore.s3_multipart_upload`),

- 172
- mapping() (galaxy.webapps.galaxy.api.datatypes.DatatypesController method), 9, 274
- MAPPING_PRESET (galaxy.tools.parameters.sanitize.ToolParameter attribute), 218
- mark_as_failed() (galaxy.jobs.runners.AsynchronousJobRunner method), 124
- mark_as_finished() (galaxy.jobs.runners.AsynchronousJobRunner method), 124
- mark_as_populated() (galaxy.model.DatasetCollection method), 130
- mark_as_queued() (galaxy.jobs.runners.BaseJobRunner method), 124
- mark_as_resubmitted() (galaxy.jobs.JobWrapper method), 116
- mark_as_resubmitted() (galaxy.jobs.runners.BaseJobRunner method), 124
- mark_deleted() (galaxy.model.Dataset method), 129
- mark_deleted() (galaxy.model.DatasetInstance method), 132
- mark_deleted() (galaxy.model.Job method), 139
- mark_group_deleted() (galaxy.web.base.controllers.admin.AdminController method), 252
- mark_quota_deleted() (galaxy.webapps.galaxy.controllers.admin.AdminController method), 306
- mark_role_deleted() (galaxy.web.base.controllers.admin.AdminController method), 252
- mark_undeleted() (galaxy.model.DatasetInstance method), 132
- mark_unhidden() (galaxy.model.DatasetInstance method), 132
- mark_user_deleted() (galaxy.web.base.controllers.admin.AdminController method), 252
- marshal() (galaxy.datatypes.metadata.FileParameter class method), 70
- marshal() (galaxy.datatypes.metadata.MetadataParameter class method), 72
- marshal() (galaxy.datatypes.metadata.PythonObjectParameter class method), 73
- marshal() (galaxy.datatypes.metadata.RangeParameter class method), 73
- marshal() (galaxy.datatypes.metadata.SelectParameter class method), 73
- mask_password_from_url() (in module galaxy.util), 226
- match_collections() (galaxy.managers.collections.DatasetCollectionManager method), 159
- match_collections() (galaxy.tools.parameters.basic.DataCollectionToolParameter method), 199
- match_collections() (galaxy.tools.parameters.basic.DataToolParameter method), 199
- match_datasets() (galaxy.tools.parameters.basic.DataToolParameter method), 199
- match_multirun_collections() (galaxy.tools.parameters.basic.DataCollectionToolParameter method), 199
- match_many() (galaxy.datatypes.data.Data method), 52
- MAX_LINES_RETURNED
- SanitizerVisualization.data_providers.basic.ColumnDataProvider attribute), 238
- max_optional_metadata_filesize (galaxy.datatypes.data.Data attribute), 52
- MAX_PRINT_ERROR_BYTES (galaxy_utils.sequence.fastq.fastqVerboseErrorReader attribute), 356
- MAX_SEQUENCE_SIZE (galaxy.tools.util.maf_utilities.RegionAlignment attribute), 222
- md5() (in module galaxy.web.framework.helpers), 257
- MEMEXml (class in galaxy.datatypes.xml), 91
- merge() (galaxy.datatypes.binary.Bam static method), 45
- merge() (galaxy.datatypes.data.Data static method), 52
- merge() (galaxy.datatypes.tabular.Sam static method), 87
- merge() (galaxy.datatypes.xml.GenericXml static method), 90
- merge_sorted_iterables() (in module galaxy.util), 226
- merge_tool_data_table() (galaxy.tools.data.TabularToolDataTable method), 193
- merge_tool_data_table() (galaxy.tools.data.ToolDataTable method), 194
- MessageException, 105
- metadata (galaxy.model.DatasetInstance attribute), 132
- metadata_isdir() (pkg_resources.IMetadataProvider method), 366
- metadata_isdir() (pkg_resources.NullProvider method), 367
- metadata_listdir() (pkg_resources.IMetadataProvider method), 366
- metadata_listdir() (pkg_resources.NullProvider method), 367
- metadata_spec (galaxy.datatypes.assembly.Amos attribute), 43
- metadata_spec (galaxy.datatypes.assembly.Roadmaps attribute), 43
- metadata_spec (galaxy.datatypes.assembly.Sequences attribute), 44
- metadata_spec (galaxy.datatypes.assembly.Velvet attribute), 44
- metadata_spec (galaxy.datatypes.binary.Ab1 attribute), 45
- metadata_spec (galaxy.datatypes.binary.Bam attribute), 45
- metadata_spec (galaxy.datatypes.binary.Bcf attribute), 45
- metadata_spec (galaxy.datatypes.binary.BigBed attribute), 45
- metadata_spec (galaxy.datatypes.binary.BigWig attribute), 46
- metadata_spec (galaxy.datatypes.binary.Binary attribute), 46

`metadata_spec` (galaxy.datatypes.binary.CompressedArchive attribute), 46
`metadata_spec` (galaxy.datatypes.binary.GeminiSQLite attribute), 47
`metadata_spec` (galaxy.datatypes.binary.GenericAsn1Binary attribute), 47
`metadata_spec` (galaxy.datatypes.binary.H5 attribute), 47
`metadata_spec` (galaxy.datatypes.binary.Idat attribute), 47
`metadata_spec` (galaxy.datatypes.binary.RData attribute), 47
`metadata_spec` (galaxy.datatypes.binary.Scf attribute), 48
`metadata_spec` (galaxy.datatypes.binary.Sff attribute), 48
`metadata_spec` (galaxy.datatypes.binary.SQLite attribute), 48
`metadata_spec` (galaxy.datatypes.binary.Sra attribute), 48
`metadata_spec` (galaxy.datatypes.binary.TwoBit attribute), 49
`metadata_spec` (galaxy.datatypes.binary.Xlsx attribute), 49
`metadata_spec` (galaxy.datatypes.chrominfo.ChromInfo attribute), 49
`metadata_spec` (galaxy.datatypes.coverage.LastzCoverage attribute), 49
`metadata_spec` (galaxy.datatypes.data.Data attribute), 52
`metadata_spec` (galaxy.datatypes.data.GenericAsn1 attribute), 53
`metadata_spec` (galaxy.datatypes.data.LineCount attribute), 53
`metadata_spec` (galaxy.datatypes.data.Newick attribute), 53
`metadata_spec` (galaxy.datatypes.data.Nexus attribute), 53
`metadata_spec` (galaxy.datatypes.data.Text attribute), 54
`metadata_spec` (galaxy.datatypes.genetics.Affybatch attribute), 54
`metadata_spec` (galaxy.datatypes.genetics.Eigenstratgeno attribute), 54
`metadata_spec` (galaxy.datatypes.genetics.Eigenstratpca attribute), 55
`metadata_spec` (galaxy.datatypes.genetics.Eset attribute), 55
`metadata_spec` (galaxy.datatypes.genetics.Fped attribute), 55
`metadata_spec` (galaxy.datatypes.genetics.Fphe attribute), 55
`metadata_spec` (galaxy.datatypes.genetics.GenomeGraphs attribute), 55
`metadata_spec` (galaxy.datatypes.genetics.ldIndep attribute), 58
`metadata_spec` (galaxy.datatypes.genetics.Lped attribute), 56
`metadata_spec` (galaxy.datatypes.genetics.MAlist attribute), 56
`metadata_spec` (galaxy.datatypes.genetics.Pbed attribute), 56
`metadata_spec` (galaxy.datatypes.genetics.Phe attribute), 56
`metadata_spec` (galaxy.datatypes.genetics.Phe attribute), 56
`metadata_spec` (galaxy.datatypes.genetics.Phen attribute), 56
`metadata_spec` (galaxy.datatypes.genetics.Pphe attribute), 56
`metadata_spec` (galaxy.datatypes.genetics.RexpBase attribute), 57
`metadata_spec` (galaxy.datatypes.genetics.Rgenetics attribute), 58
`metadata_spec` (galaxy.datatypes.genetics.rgFeatureList attribute), 58
`metadata_spec` (galaxy.datatypes.genetics.rgSampleList attribute), 59
`metadata_spec` (galaxy.datatypes.genetics.rgTabList attribute), 59
`metadata_spec` (galaxy.datatypes.genetics.SNPMMatrix attribute), 58
`metadata_spec` (galaxy.datatypes.genetics.Snptest attribute), 58
`metadata_spec` (galaxy.datatypes.images.Bmp attribute), 59
`metadata_spec` (galaxy.datatypes.images.Eps attribute), 59
`metadata_spec` (galaxy.datatypes.images.Gif attribute), 59
`metadata_spec` (galaxy.datatypes.images.Gmaj attribute), 60
`metadata_spec` (galaxy.datatypes.images.Html attribute), 60
`metadata_spec` (galaxy.datatypes.images.Im attribute), 60
`metadata_spec` (galaxy.datatypes.images.Image attribute), 60
`metadata_spec` (galaxy.datatypes.images.Jpg attribute), 61
`metadata_spec` (galaxy.datatypes.images.Laj attribute), 61
`metadata_spec` (galaxy.datatypes.images.Pbm attribute), 61
`metadata_spec` (galaxy.datatypes.images.Pcd attribute), 61
`metadata_spec` (galaxy.datatypes.images.Pcx attribute), 61
`metadata_spec` (galaxy.datatypes.images.Pdf attribute), 61
`metadata_spec` (galaxy.datatypes.images.Pgm attribute), 62
`metadata_spec` (galaxy.datatypes.images.Png attribute), 62
`metadata_spec` (galaxy.datatypes.images.Ppm attribute), 62
`metadata_spec` (galaxy.datatypes.images.Psd attribute), 62
`metadata_spec` (galaxy.datatypes.images.Rast attribute), 62

metadata_spec (galaxy.datatypes.images.Rgb attribute), 62	metadata_spec (galaxy.datatypes.sequence.csFasta attribute), 82
metadata_spec (galaxy.datatypes.images.Tiff attribute), 62	metadata_spec (galaxy.datatypes.sequence.Fasta attribute), 77
metadata_spec (galaxy.datatypes.images.Xbm attribute), 63	metadata_spec (galaxy.datatypes.sequence.Fastq attribute), 78
metadata_spec (galaxy.datatypes.images.Xpm attribute), 63	metadata_spec (galaxy.datatypes.sequence.FastqCSSanger attribute), 79
metadata_spec (galaxy.datatypes.interval.Bed attribute), 63	metadata_spec (galaxy.datatypes.sequence.FastqIllumina attribute), 79
metadata_spec (galaxy.datatypes.interval.Bed12 attribute), 64	metadata_spec (galaxy.datatypes.sequence.FastqSanger attribute), 79
metadata_spec (galaxy.datatypes.interval.Bed6 attribute), 64	metadata_spec (galaxy.datatypes.sequence.FastqSolexa attribute), 79
metadata_spec (galaxy.datatypes.interval.BedGraph attribute), 64	metadata_spec (galaxy.datatypes.sequence.Lav attribute), 79
metadata_spec (galaxy.datatypes.interval.BedStrict attribute), 64	metadata_spec (galaxy.datatypes.sequence.Maf attribute), 80
metadata_spec (galaxy.datatypes.interval.ChromatinInteractions attribute), 65	metadata_spec (galaxy.datatypes.sequence.MafCustomTrack attribute), 80
metadata_spec (galaxy.datatypes.interval.CustomTrack attribute), 65	metadata_spec (galaxy.datatypes.sequence.RNADotPlotMatrix attribute), 81
metadata_spec (galaxy.datatypes.interval.ENCODEPeak attribute), 65	metadata_spec (galaxy.datatypes.sequence.Sequence attribute), 81
metadata_spec (galaxy.datatypes.interval.Gff attribute), 66	metadata_spec (galaxy.datatypes.sequence.SequenceSplitLocations attribute), 82
metadata_spec (galaxy.datatypes.interval.Gff3 attribute), 67	metadata_spec (galaxy.datatypes.tabular.CSV attribute), 85
metadata_spec (galaxy.datatypes.interval.Gtf attribute), 67	metadata_spec (galaxy.datatypes.tabular.Eland attribute), 86
metadata_spec (galaxy.datatypes.interval.Interval attribute), 68	metadata_spec (galaxy.datatypes.tabular.ElandMulti attribute), 86
metadata_spec (galaxy.datatypes.interval.Wiggle attribute), 69	metadata_spec (galaxy.datatypes.tabular.FeatureLocationIndex attribute), 86
metadata_spec (galaxy.datatypes.ngsindex.BowtieBaseIndex attribute), 73	metadata_spec (galaxy.datatypes.tabular.Pileup attribute), 86
metadata_spec (galaxy.datatypes.ngsindex.BowtieColorIndex attribute), 74	metadata_spec (galaxy.datatypes.tabular.Sam attribute), 87
metadata_spec (galaxy.datatypes.ngsindex.BowtieIndex attribute), 74	metadata_spec (galaxy.datatypes.tabular.Tabular attribute), 88
metadata_spec (galaxy.datatypes.qualityscore.QualityScore attribute), 74	metadata_spec (galaxy.datatypes.tabular.TabularData attribute), 89
metadata_spec (galaxy.datatypes.qualityscore.QualityScore454 attribute), 74	metadata_spec (galaxy.datatypes.tabular.Taxonomy attribute), 89
metadata_spec (galaxy.datatypes.qualityscore.QualityScoreIllumina attribute), 75	metadata_spec (galaxy.datatypes.tabular.Vcf attribute), 90
metadata_spec (galaxy.datatypes.qualityscore.QualityScoreSolexa attribute), 75	metadata_spec (galaxy.datatypes.tracks.GeneTrack attribute), 90
metadata_spec (galaxy.datatypes.qualityscore.QualityScoreSolid attribute), 75	metadata_spec (galaxy.datatypes.xml.CisML attribute), 90
metadata_spec (galaxy.datatypes.sequence.Alignment attribute), 77	metadata_spec (galaxy.datatypes.xml.GenericXml attribute), 90
metadata_spec (galaxy.datatypes.sequence.Axt attribute), 77	metadata_spec (galaxy.datatypes.xml.MEMEXml attribute), 91

[metadata_spec \(galaxy.datatypes.xml.Owl attribute\), 91](#)
[metadata_spec \(galaxy.datatypes.xml.Phyloxml attribute\), 91](#)
[MetadataCollection \(class in galaxy.datatypes.metadata\), 71](#)
[MetadataElement \(in module galaxy.datatypes.metadata\), 71](#)
[MetadataElementSpec \(class in galaxy.datatypes.metadata\), 71](#)
[MetadataFile \(class in galaxy.model\), 143](#)
[MetadataInDataTableColumnValidator \(class in galaxy.tools.parameters.validation\), 220](#)
[MetadataInFileColumnValidator \(class in galaxy.tools.parameters.validation\), 220](#)
[MetadataParameter \(class in galaxy.datatypes.metadata\), 72](#)
[MetadataSpecCollection \(class in galaxy.datatypes.metadata\), 72](#)
[MetadataTempFile \(class in galaxy.datatypes.metadata\), 72](#)
[MetadataToolOutputAction \(class in galaxy.tools.parameters.output\), 215](#)
[MetadataValidator \(class in galaxy.tools.parameters.validation\), 221](#)
[MetadataValueFilter \(class in galaxy.tools.parameters.output\), 215](#)
[metrics \(galaxy.model.HasJobMetrics attribute\), 135](#)
[MetricsController \(class in galaxy.webapps.galaxy.api.metrics\), 30, 295](#)
[migrate_to_current_version\(\) \(in module galaxy.model.migrate.check\), 153](#)
[mime_type\(\) \(galaxy.datatypes.display_applications.parameters.DisplayDataValueWrapper method\), 98](#)
[mime_type\(\) \(galaxy.datatypes.display_applications.parameters.DisplayParameterValueWrapper method\), 98](#)
[mimeparse \(module\), 358](#)
[missing_meta\(\) \(galaxy.datatypes.data.Data method\), 52](#)
[missing_meta\(\) \(galaxy.model.DatasetInstance method\), 132](#)
[missing_meta\(\) \(galaxy.util.none_like.NoneDataset method\), 235](#)
[missing_tools \(galaxy.managers.workflows.CreatedWorkflow attribute\), 168](#)
[MissingToolException, 348](#)
[MissingToolsException \(class in galaxy.managers.workflows\), 168](#)
[mkstemp\(\) \(log_tempfile.TempFile method\), 358](#)
[mkstemp_in\(\) \(in module galaxy.util\), 227](#)
[Mobile \(class in galaxy.webapps.galaxy.controllers.mobile\), 327](#)
[model \(galaxy.managers.context.ProvidesAppContext attribute\), 160](#)
[model_class \(galaxy.managers.base.ModelFilterParser attribute\), 155](#)
[model_class \(galaxy.managers.base.ModelManager attribute\), 156](#)
[model_class \(galaxy.managers.hdas.HDAFilterParser attribute\), 163](#)
[model_class \(galaxy.managers.hdas.HDAManager attribute\), 163](#)
[model_class \(galaxy.managers.histories.HistoryFilters attribute\), 164](#)
[model_class \(galaxy.managers.histories.HistoryManager attribute\), 164](#)
[model_class \(galaxy.managers.roles.RoleManager attribute\), 167](#)
[model_class \(galaxy.web.framework.helpers.grids.Grid attribute\), 260](#)
[model_class \(galaxy.webapps.galaxy.controllers.admin.GroupListGrid attribute\), 307](#)
[model_class \(galaxy.webapps.galaxy.controllers.admin.QuotaListGrid attribute\), 308](#)
[model_class \(galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute\), 309](#)
[model_class \(galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute\), 310](#)
[model_class \(galaxy.webapps.galaxy.controllers.admin.UserListGrid attribute\), 312](#)
[model_class \(galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAssociation attribute\), 316](#)
[model_class \(galaxy.webapps.galaxy.controllers.external_service.ExternalService attribute\), 317](#)
[model_class \(galaxy.webapps.galaxy.controllers.forms.FormsGrid attribute\), 319](#)
[model_class \(galaxy.webapps.galaxy.controllers.history.HistoryAllPublished attribute\), 320](#)
[model_class \(galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute\), 322](#)
[model_class \(galaxy.webapps.galaxy.controllers.history.SharedHistoryListGrid attribute\), 323](#)
[model_class \(galaxy.webapps.galaxy.controllers.library.LibraryListGrid attribute\), 324](#)
[model_class \(galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid attribute\), 325](#)
[model_class \(galaxy.webapps.galaxy.controllers.page.HistoryDatasetAssociation attribute\), 327](#)
[model_class \(galaxy.webapps.galaxy.controllers.page.HistorySelectionGrid attribute\), 327](#)
[model_class \(galaxy.webapps.galaxy.controllers.page.PageAllPublishedGrid attribute\), 328](#)
[model_class \(galaxy.webapps.galaxy.controllers.page.PageListGrid attribute\), 329](#)
[model_class \(galaxy.webapps.galaxy.controllers.page.PageSelectionGrid attribute\), 330](#)
[model_class \(galaxy.webapps.galaxy.controllers.page.VisualizationSelectionGrid attribute\), 330](#)
[model_class \(galaxy.webapps.galaxy.controllers.page.WorkflowSelectionGrid attribute\), 330](#)

attribute), 330
 model_class (galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid attribute), 331
 model_class (galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid attribute), 333
 model_class (galaxy.webapps.galaxy.controllers.requests_common.MultipleSplittersGrid attribute), 335
 model_class (galaxy.webapps.galaxy.controllers.user.UserOpenIDGrid attribute), 340
 model_class (galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGrid attribute), 343
 model_class (galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDateListGrid attribute), 344
 model_class (galaxy.webapps.reports.controllers.workflows.SpecifiedDateListGrid attribute), 346
 model_manager_class (galaxy.managers.base.ModelSerializer attribute), 155
 model_manager_class (galaxy.managers.hdas.HDADeserializer attribute), 163
 model_manager_class (galaxy.managers.histories.HistoryDeserializer attribute), 164
 ModelDeserializer (class in galaxy.managers.base), 154
 ModelDeserializingError, 155
 ModelFilterParser (class in galaxy.managers.base), 155
 ModelManager (class in galaxy.managers.base), 156
 ModelSerializer (class in galaxy.managers.base), 156
 ModelSerializingError, 157
 ModelValidator (class in galaxy.managers.base), 157
 module_path (pkg_resources.EmptyProvider attribute), 367
 modularize() (galaxy.util.inflection.Base method), 231
 modularize() (galaxy.util.inflection.Inflector method), 233
 monitor() (galaxy.jobs.handler.JobHandlerStopQueue method), 118
 monitor() (galaxy.jobs.runners.AsynchronousJobRunner method), 124
 monitor_job() (galaxy.jobs.runners.AsynchronousJobRunner method), 124
 monitor_repository_installation()
 (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 313
 monitor_step() (galaxy.jobs.handler.JobHandlerStopQueue method), 118
 most_recent() (galaxy.managers.histories.HistoryManager method), 165
 move_library_item() (galaxy.webapps.galaxy.controllers.library_common.LibraryCommon method), 326
 move_merge() (in module galaxy.util), 227
 mp_from_ids() (in module galaxy.objectstore.s3_multipart_upload), 172
 MulticolFilterColumn (class in galaxy.web.framework.helpers.grids), 261
 multimap() (in module galaxy.objectstore.s3_multipart_upload), 172
 multipart_upload() (in module galaxy.objectstore.s3_multipart_upload), 172
 MultipleSplittersGrid (class in galaxy.tools.parameters.dynamic_options), 210
 MultipleSplitterFilter (class in galaxy.tools.parameters.output), 215
 name (galaxy.jobs.actions.post.ChangeDatatypeAction attribute), 120
 name (galaxy.jobs.actions.post.ColumnSetAction attribute), 120
 name (galaxy.jobs.actions.post.DefaultJobAction attribute), 121
 name (galaxy.jobs.actions.post.DeleteDatasetAction attribute), 121
 name (galaxy.jobs.actions.post.DeleteIntermediatesAction attribute), 121
 name (galaxy.jobs.actions.post.EmailAction attribute), 121
 name (galaxy.jobs.actions.post.HideDatasetAction attribute), 121
 name (galaxy.jobs.actions.post.RenameDatasetAction attribute), 121
 name (galaxy.jobs.actions.post.SetMetadataAction attribute), 122
 name (galaxy.jobs.actions.post.TagDatasetAction attribute), 122
 name (galaxy.model.LibraryDataset attribute), 141
 name (galaxy.workflow.modules.InputDataCollectionModule attribute), 347
 name (galaxy.workflow.modules.InputDataModule attribute), 347
 name (galaxy.workflow.modules.PauseModule attribute), 348
 name() (galaxy.datatypes.util.gff_util.GFFFeature method), 99
 name_autocomplete_data()
 (galaxy.web.base.controllers.admin.Admin method), 252
 name_autocomplete_data()
 (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321
 NameColumn (class in galaxy.webapps.galaxy.controllers.history), 322
 NamedTemporaryFile() (log_tempfile.TempFile method), 357
 NestedObjectStore (class in galaxy.objectstore), 170
 NEVER_SANITIZE (galaxy.util.Params attribute), 225

new() (galaxy.forms.forms.FormDefinitionAddressFieldFactory method), 189
 new() (galaxy.forms.forms.FormDefinitionFactory method), 110
 new() (galaxy.forms.forms.FormDefinitionFieldFactory method), 111
 new() (galaxy.forms.forms.FormDefinitionHistoryFieldFactory method), 111
 new() (galaxy.forms.forms.FormDefinitionPasswordFieldFactory method), 111
 new() (galaxy.forms.forms.FormDefinitionSelectFieldFactory method), 111
 new() (galaxy.forms.forms.FormDefinitionTextFieldFactory method), 111
 new() (galaxy.forms.forms.FormDefinitionWorkflowFieldFactory method), 111
 new() (galaxy.forms.forms.FormDefinitionWorkflowMappingFieldFactory method), 112
 new() (galaxy.jobs.transfer_manager.TransferManager method), 119
 new() (galaxy.sample_tracking.request_types.RequestTypeFactory method), 175
 new() (galaxy.sample_tracking.sample.SampleStateFactory method), 175
 new() (galaxy.workflow.modules.SimpleWorkflowModule class method), 349
 new() (galaxy.workflow.modules.ToolModule class method), 349
 new() (galaxy.workflow.modules.WorkflowModule class method), 351
 new() (galaxy.workflow.modules.WorkflowModuleFactory method), 351
 new_address() (galaxy.webapps.galaxy.controllers.user.User method), 339
 new_file() (galaxy.datatypes.metadata.FileParameter method), 70
 new_file_path() (galaxy.jobs.ComputeEnvironment method), 112
 new_file_path() (galaxy.jobs.SharedComputeEnvironment method), 116
 new_provider_from_identifier() (galaxy.openid.providers.OpenIDProviders method), 173
 new_secure_hash() (in module galaxy.util.hash_util), 230
 new_state() (galaxy.tools.Tool method), 186
 new_upload() (in module galaxy.tools.actions.upload_common), 192
 Newick (class in galaxy.datatypes.data), 53
 Newick_Parser (class in galaxy.visualization.data_providers.phylviz.newick_parser), 240
 next() (galaxy.datatypes.util.gff_util.GFFReaderWrapper method), 99
 next() (galaxy.tools.exception_handling.UCSCOutWrapper method), 189
 next() (galaxy_utils.sequence.fasta.fastaReader method), 352
 next() (galaxy_utils.sequence.fastq.fastqReader method), 354
 next() (galaxy_utils.sequence.fastq.fastqVerboseErrorReader method), 356
 next() (galaxy_utils.sequence.vcf.Reader method), 357
 Nexus (class in galaxy.datatypes.data), 53
 Nexus_Parser (class in galaxy.visualization.data_providers.phylviz.nexusparser), 240
 nice_size() (in module galaxy.util), 227
 nice_size() (in module galaxy.webapps.reports.controllers.system), 345
 no_disk_usage (galaxy.model.User attribute), 148
 NO_PROVIDER_ID (galaxy.openid.providers.OpenIDProviders attribute), 173
 NoConverterException, 143
 NoIndex (class in galaxy.visualization.data_providers.phylviz.baseparser), 239
 NON_DATA_CONNECTION (galaxy.model.WorkflowStepConnection attribute), 151
 non_data_connection (galaxy.model.WorkflowStepConnection attribute), 151
 non_ready_states (galaxy.model.Dataset attribute), 129
 NoneDataset (class in galaxy.util.none_like), 235
 NoopHandler (class in galaxy.jobs.manager), 119
 NoopQueue (class in galaxy.jobs), 116
 NoOptionsValidator (class in galaxy.tools.parameters.validation), 221
 NoQuotaAgent (class in galaxy.quota), 173
 normalize_path() (in module pkg_resources), 365
 normalize_runtime_state() (galaxy.workflow.modules.SimpleWorkflowModule method), 349
 normalize_runtime_state() (galaxy.workflow.modules.ToolModule method), 349
 not_implemented() (galaxy.web.base.controller.BaseAPIController method), 247
 NotImplemented, 105
 nottest() (in module galaxy.tools.test), 190
 nullable_basestring() (galaxy.managers.base.ModelValidator method), 157
 NullDependencyManager (class in galaxy.tools.deps), 195
 NullProvider (class in pkg_resources), 367
 NullToolOutputActionOption (class in galaxy.tools.parameters.output), 215
 num_page_links (galaxy.web.framework.helpers.grid.Grid attribute), 260

O

- num_rows_per_page (galaxy.web.framework.helpers.grids.GridToDisplay() (galaxy.security.GalaxyRBACAgent attribute), 260
- num_rows_per_page (galaxy.webapps.galaxy.controllers.admin.GroupListGrid() (in module galaxy.tools.actions), attribute), 307
- num_rows_per_page (galaxy.webapps.galaxy.controllers.admin.QuotaListGridmanagers.base.ModelManager method), attribute), 308
- num_rows_per_page (galaxy.webapps.galaxy.controllers.admin.RoleListGridgalaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), attribute), 309
- num_rows_per_page (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGalaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin method), attribute), 310
- num_rows_per_page (galaxy.webapps.galaxy.controllers.admin.UserListGridmaf_index() (in module galaxy.tools.util.maf_utilities), attribute), 312
- num_rows_per_page (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAssociationListGridgalaxy.controllers.user.User method), attribute), 316
- num_rows_per_page (galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGalaxy.controllers.user.User method), attribute), 318
- num_rows_per_page (galaxy.webapps.galaxy.controllers.forms.FormsGridAssociate() (galaxy.webapps.galaxy.controllers.user.User method), attribute), 319
- num_rows_per_page (galaxy.webapps.galaxy.controllers.history.HistoryAllPublishedGridGalaxy.controllers.user.User method), attribute), 320
- num_rows_per_page (galaxy.webapps.galaxy.controllers.history.HistoryListGridgalaxy.webapps.galaxy.controllers.user.User method), attribute), 322
- num_rows_per_page (galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid (class in galaxy.web.framework.openid_manager), attribute), 324
- num_rows_per_page (galaxy.webapps.galaxy.controllers.library_admin.OpenIDProvider class in galaxy.openid.providers), attribute), 325
- num_rows_per_page (galaxy.webapps.galaxy.controllers.page.PageListGridoperation (galaxy.webapps.galaxy.controllers.requests.UserRequestsGrid attribute), 328
- num_rows_per_page (galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid operation (galaxy.webapps.galaxy.controllers.requests_admin.AdminRequest attribute), 331
- num_rows_per_page (galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid operations (galaxy.web.framework.helpers.grids.Grid attribute), 333
- num_rows_per_page (galaxy.webapps.galaxy.controllers.requests_contributed.RequestsGrid operations (galaxy.webapps.galaxy.controllers.admin.GroupListGrid attribute), 335
- num_rows_per_page (galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGridoperations (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid attribute), 343
- num_rows_per_page (galaxy.webapps.reports.controllers.sample_tracking.SampleTrackingDateListGridoperations (galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute), 344
- num_rows_per_page (galaxy.webapps.reports.controllers.workflows.SharedHistoryListGridoperations (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 346
- object_store (galaxy.model.Dataset attribute), 129
- object_to_string() (in module galaxy.util), 227
- ObjectAttributeInvalidException, 105
- ObjectAttributeMissingException, 105
- ObjectInvalid, 105
- ObjectNotFound, 105
- ObjectStore (class in galaxy.objectstore), 170
- ObjectStorePopulator (class in galaxy.tools.actions), 190
- obtain() (pkg_resources.Environment method), 360
- odict (class in galaxy.util.odict), 235
- oidlog() (in module galaxy.web.framework.openid_manager), 256

- attribute), 323
 - operations (galaxy.webapps.galaxy.controllers.page.PageListGrid attribute), 330
 - operations (galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid controller (class in galaxy.webapps.galaxy.api.page_revisions), attribute), 331
 - operations (galaxy.webapps.galaxy.controllers.requests.UserRequestsGrid controller (class in galaxy.webapps.galaxy.api.page_revisions), attribute), 332
 - operations (galaxy.webapps.galaxy.controllers.requests_admin.AdminRequestsGrid controller (class in galaxy.webapps.galaxy.api.pages), 31, 296 attribute), 332
 - operations (galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid controller (class in galaxy.webapps.galaxy.controllers.page), attribute), 333
 - operations (galaxy.webapps.galaxy.controllers.requests_coming.RequestsGrid controller (class in galaxy.model), 143 attribute), 335
 - operations (galaxy.webapps.galaxy.controllers.user.UserOpenPageGrid controller (class in galaxy.model), 143 attribute), 340
 - option_type (in module galaxy.tools.parameters.output), 217
 - optionxform() (galaxy.eggs.CaseSensitiveConfigParser method), 100
 - ordinalize() (galaxy.util.inflection.Base method), 231
 - ordinalize() (galaxy.util.inflection.Inflector method), 233
 - orient_block_by_region() (in module galaxy.tools.util.maf_utilities), 224
 - orm_filter_parsers (galaxy.managers.base.ModelFilterParser attribute), 155
 - output_paths() (galaxy.jobs.ComputeEnvironment method), 112
 - output_paths() (galaxy.jobs.SharedComputeEnvironment method), 116
 - OutputParameterJSONTool (class in galaxy.tools), 183
 - outputs() (galaxy.webapps.galaxy.api.jobs.JobController method), 22, 287
 - Owl (class in galaxy.datatypes.xml), 91
 - OwnerAnnotationColumn (class in galaxy.web.framework.helpers.grids), 262
 - OwnerColumn (class in galaxy.web.framework.helpers.grids), 262
- ## P
- package_tool() (galaxy.web.base.controllers.admin.Admin method), 252
 - Page (class in galaxy.model), 143
 - PageAllPublishedGrid (class in galaxy.webapps.galaxy.controllers.page), 328
 - PageAnnotationAssociation (class in galaxy.model), 143
 - PageController (class in galaxy.webapps.galaxy.controllers.page), 328
 - PageListGrid (class in galaxy.webapps.galaxy.controllers.page), 329
 - PageListGrid.URLColumn (class in galaxy.webapps.galaxy.controllers.page), 329
 - PageRatingAssociation (class in galaxy.model), 143
 - PageRevision (class in galaxy.model), 143
 - PageRequestTypeGrid controller (class in galaxy.webapps.galaxy.api.page_revisions), 31, 296
 - PageSelectionGrid (class in galaxy.webapps.galaxy.controllers.page), 330
 - PageUserShareAssociation (class in galaxy.model), 143
 - ParamContextInfo (class in galaxy.jobs), 116
 - param_names() (galaxy.tools.test.ParamContext method), 189
 - param_names() (galaxy.tools.test.RootParamContext method), 190
 - ParamContext (class in galaxy.tools.test), 189
 - Params (class in galaxy.util), 225
 - params_from_strings() (galaxy.tools.Tool method), 186
 - params_from_strings() (in module galaxy.tools.parameters), 196
 - params_to_incoming() (in module galaxy.tools.parameters), 196
 - params_to_strings() (galaxy.tools.Tool method), 186
 - params_to_strings() (in module galaxy.tools.parameters), 197
 - params_with_missing_data_table_entry (galaxy.tools.Tool attribute), 186
 - params_with_missing_index_file (galaxy.tools.Tool attribute), 186
 - ParamsWithSpecs (class in galaxy.util), 225
 - ParamValueFilter (class in galaxy.tools.parameters.dynamic_options), 210
 - ParamValueToolOutputActionOptionFilter (class in galaxy.tools.parameters.output), 215
 - parent (galaxy.datatypes.metadata.MetadataCollection attribute), 71
 - parent_library (galaxy.model.LibraryFolder attribute), 143
 - parse() (galaxy.eggs.Crate method), 100
 - parse() (galaxy.eggs.dist.DistScrambleCrate method), 101
 - parse() (galaxy.eggs.scramble.ScrambleCrate method), 102
 - parse() (galaxy.sample_tracking.data_transfer.DataTransferFactory method), 174
 - parse() (galaxy.sample_tracking.data_transfer.FtpDataTransferFactory method), 174
 - parse() (galaxy.sample_tracking.data_transfer.HttpDataTransferFactory method), 174
 - parse() (galaxy.sample_tracking.data_transfer.ScpDataTransferFactory method), 174

method), 174

parse() (galaxy.sample_tracking.external_service_types.ExternalServiceType method), 175

parse() (galaxy.tools.SetParamAction static method), 184

parse() (galaxy.tools.Tool method), 186

parse() (galaxy.tools.TracksterConfig static method), 189

parse() (pkg_resources.EntryPoint class method), 363

parse() (pkg_resources.Requirement static method), 363

parse_bool() (galaxy.managers.base.ModelFilterParser method), 155

parse_cast_attribute() (in module galaxy.tools.parameters.output), 217

parse_citation() (galaxy.managers.citations.CitationsManager method), 158

parse_citation() (in module galaxy.managers.citations), 159

parse_cols_arg() (in module galaxy.tools.util.galaxyops), 225

parse_column_definitions() (galaxy.tools.parameters.dynamic_options.DynamicOptions method), 210

parse_column_spec() (galaxy.tools.data.TabularToolDataTable method), 193

parse_compare_type() (in module galaxy.tools.parameters.output), 217

parse_data_transfer_settings() (galaxy.sample_tracking.external_service_types.ExternalServiceType method), 175

parse_destination_params() (galaxy.jobs.runners.BaseJobRunner method), 124

parse_destination_params() (galaxy.jobs.runners.cli.ShellJobRunner method), 125

parse_egg_section() (galaxy.eggs.Crate method), 100

parse_egg_section() (galaxy.eggs.dist.DistScrambleCrate method), 101

parse_egg_section() (galaxy.eggs.scramble.ScrambleCrate method), 102

parse_file_fields() (galaxy.tools.data.TabularToolDataTable method), 193

parse_file_fields() (galaxy.tools.parameters.dynamic_options.DynamicOptions method), 210

parse_filter() (galaxy.managers.base.ModelFilterParser method), 155

parse_filter_params() (galaxy.web.base.controller.BaseController method), 247

parse_filters() (galaxy.managers.base.ModelFilterParser method), 155

parse_gff_attributes() (in module galaxy.datatypes.util.gff_util), 100

parse_group() (pkg_resources.EntryPoint class method), 363

parse_help() (galaxy.tools.Tool method), 186

parse_id_list() (galaxy.managers.base.ModelFilterParser method), 155

parse_input_elem() (galaxy.tools.Tool method), 186

parse_input_page() (galaxy.tools.Tool method), 186

parse_inputs() (galaxy.tools.DataSourceTool method), 183

parse_inputs() (galaxy.tools.Tool method), 186

parse_limit_offset() (galaxy.web.base.controller.BaseController method), 247

parse_map() (pkg_resources.EntryPoint class method), 364

parse_media_range() (in module mimeparse), 358

parse_mime_type() (in module mimeparse), 358

parse_name() (galaxy.tools.parameters.basic.ToolParameter class method), 208

parse_outputs() (galaxy.tools.Tool method), 187

parse_param_elem() (galaxy.tools.Tool method), 187

parse_redirect_url() (galaxy.tools.Tool method), 187

parse_requirements() (in module pkg_resources), 364

parse_row() (galaxy.datatypes.util.gff_util.GFFIntervalToBEDReaderWrapper method), 99

parse_row() (galaxy.datatypes.util.gff_util.GFFReaderWrapper method), 99

parse_run_details() (galaxy.sample_tracking.external_service_types.ExternalServiceType method), 175

parse_run_details_results() (galaxy.sample_tracking.external_service_types.ExternalServiceType method), 175

parse_species_option() (in module galaxy.tools.util.maf_utilities), 224

parse_stdio() (galaxy.tools.Tool method), 187

parse_tags() (galaxy.managers.tags.TagManager method), 168

parse_tests() (in module galaxy.tools.test), 190

parse_version() (in module pkg_resources), 364

parse_xml() (in module galaxy.util), 227

parse_xml_string() (in module galaxy.util), 227

parsed_version (pkg_resources.Distribution attribute), 363

parseData() (galaxy.visualization.data_providers.phyloviz.newickparser.NewickParser method), 240

parseFile() (galaxy.visualization.data_providers.phyloviz.baseparser.BaseParser method), 239

parseFile() (galaxy.visualization.data_providers.phyloviz.newickparser.NewickParser method), 240

parseFile() (galaxy.visualization.data_providers.phyloviz.nexusparser.NexusParser method), 240

parseFile() (galaxy.visualization.data_providers.phyloviz.phyloxmlparser.PhyloxmlParser method), 241

parseNexus() (galaxy.visualization.data_providers.phyloviz.nexusparser.NexusParser method), 240

parseNode() (galaxy.visualization.data_providers.phyloviz.newickparser.NewickParser method), 240

parseNode() (galaxy.visualization.data_providers.phyloviz.phyloxmlparser.PhyloxmlParser method), 241

- method), 241
- pass_through_operations
 - (galaxy.web.framework.helpers.grids.Grid attribute), 260
- PasswordField (class in galaxy.web.form_builder), 244
- PasswordResetToken (class in galaxy.model), 143
- path (galaxy.eggs.dist.DistScrambleEgg attribute), 102
- path (galaxy.eggs.Egg attribute), 101
- path (galaxy.web.framework.base.Request attribute), 255
- PathMetadata (class in pkg_resources), 367
- pause() (galaxy.jobs.JobWrapper method), 116
- PauseModule (class in galaxy.workflow.modules), 348
- Pbed (class in galaxy.datatypes.genetics), 56
- Pbm (class in galaxy.datatypes.images), 61
- Pcd (class in galaxy.datatypes.images), 61
- Pcx (class in galaxy.datatypes.images), 61
- Pdf (class in galaxy.datatypes.images), 61
- peek() (galaxy.webapps.galaxy.controllers.root.RootController method), 337
- peek_size (galaxy.datatypes.tabular.CSV attribute), 85
- per_month_all() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
- per_month_all() (galaxy.webapps.reports.controllers.sample_tracking.SampleTracking method), 343
- per_month_all() (galaxy.webapps.reports.controllers.workflows.Workflows method), 347
- per_month_in_error() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
- per_tool() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
- per_user() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
- per_user() (galaxy.webapps.reports.controllers.sample_tracking.SampleTracking method), 343
- per_user() (galaxy.webapps.reports.controllers.workflows.Workflows method), 347
- perform_action() (galaxy.external_services.actions.ExternalServiceAction method), 106
- perform_action() (galaxy.external_services.actions.ExternalServiceTemplateAction method), 106
- perform_action() (galaxy.external_services.actions.ExternalServiceWebAPIAction method), 107
- perform_action() (galaxy.external_services.actions.PopulatedExternalServiceAction method), 107
- perform_action_by_name()
 - (galaxy.external_services.service.PopulatedExternalService method), 109
- permitted_actions (galaxy.model.Dataset attribute), 129
- permitted_actions (galaxy.model.DatasetInstance attribute), 132
- permitted_actions (galaxy.model.Library attribute), 141
- permitted_actions (galaxy.model.RequestType attribute), 145
- permitted_actions (galaxy.security.RBACAgent attribute), 180
- persist_session() (galaxy.web.framework.openid_manager.OpenIDManager method), 256
- persist_uploads()
 - (in module galaxy.tools.actions.upload_common), 192
- Pgm (class in galaxy.datatypes.images), 61
- Phe (class in galaxy.datatypes.genetics), 56
- Pheno (class in galaxy.datatypes.genetics), 56
- PhyloTree (class in galaxy.visualization.data_providers.phyloviz.baseparser), 239
- PhylovizDataProvider
 - (class in galaxy.visualization.data_providers.phyloviz), 239
- Phyloxml (class in galaxy.datatypes.xml), 91
- Phyloxml_Parser
 - (class in galaxy.visualization.data_providers.phyloviz.phyloxmlparser), 241
- pick_a_cycle() (galaxy.util.topsort.CycleError method), 236
- Pileup (class in galaxy.datatypes.tabular), 86
- PKG_INFO (pkg_resources.Distribution attribute), 362
- pkg_resources (module), 359
- pluralize() (galaxy.util.inflection.Inflector method), 232
- pluralize() (galaxy.util.inflection.Inflector method), 233
- Png (class in galaxy.datatypes.images), 62
- poll_active_workflow_ids()
 - (galaxy.model.WorkflowInvocation static method), 150
- popitem() (galaxy.util.odict.odict method), 235
- populate() (galaxy.external_services.service.ExternalServiceActionsGroup method), 108
- populate() (galaxy.external_services.service.PopulatedExternalService method), 109
- populate_action() (galaxy.external_services.actions.ExternalServiceAction method), 106
- populate_actions()
 - (galaxy.model.ExternalService method), 134
- populate_external_services()
 - (galaxy.model.Sample method), 106
- populate_module_and_state()
 - (in module galaxy.workflow.modules), 352
- populate_state() (galaxy.tools.Tool method), 187
- populate_state_info() (galaxy.tools.Tool method), 187
- populate_widgets_from_kwd()
 - (galaxy.web.base.controller.UsesFormDefinitionsMixin method), 249
- populated (galaxy.model.DatasetCollection attribute), 130
- populated_states (galaxy.model.DatasetCollection attribute), 130
- PopulatedDisplayApplicationLink
 - (class in galaxy.datatypes.display_applications.application), 96

PopulatedExternalService (class in attribute), 324
 galaxy.external_services.service), 109
 PopulatedExternalServiceAction (class in attribute), 325
 galaxy.external_services.actions), 107
 post_authentication() (galaxy.openid.providers.OpenIDProvider attribute), 331
 method), 173
 preserve_state (galaxy.webapps.galaxy.controllers.requests_admin.DataTransfer attribute), 333
 PostJobAction (class in galaxy.model), 143
 PostJobActionAssociation (class in galaxy.model), 143
 postprocess() (pkg_resources.ResourceManager method), 362
 preserve_state (galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGrid attribute), 343
 preserve_state (galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDate attribute), 344
 preserve_state (galaxy.webapps.reports.controllers.workflows.SpecifiedDate attribute), 344
 Pphe (class in galaxy.datatypes.genetics), 56
 Ppm (class in galaxy.datatypes.images), 62
 prepare() (galaxy.datatypes.display_applications.parameters.DisplayApplicationDataParameter method), 97
 prepare() (galaxy.datatypes.display_applications.parameters.DisplayApplicationParameter method), 97
 prepare() (galaxy.jobs.JobWrapper method), 116
 prepare() (galaxy.jobs.TaskWrapper method), 117
 prepare_actions() (galaxy.external_services.service.ExternalServiceActionsGroup method), 108
 prepare_activation_link()
 (galaxy.webapps.galaxy.controllers.user.User attribute), 339
 prepare_display() (galaxy.datatypes.display_applications.application_display.DisplayApplicationHeartbeat attribute), 231
 method), 97
 prepare_for_install() (galaxy.webapps.galaxy.controllers.admin_tool_kit.GalaxyAdminToolKit attribute), 145
 method), 313
 privately_share_dataset()
 (galaxy.security.GalaxyRBACAgent method), 178
 prepare_job() (galaxy.jobs.runners.BaseJobRunner method), 124
 preparing (galaxy.model.JobExportHistoryArchive attribute), 140
 preparing_display() (galaxy.datatypes.display_applications.application_display.DisplayApplicationStatement class method), 97
 preserve_state (galaxy.web.framework.helpers.grids.Grid attribute), 260
 preserve_state (galaxy.webapps.galaxy.controllers.admin.GroupsGrid attribute), 307
 preserve_state (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid attribute), 308
 preserve_state (galaxy.webapps.galaxy.controllers.admin.RolesGrid attribute), 309
 preserve_state (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 310
 preserve_state (galaxy.webapps.galaxy.controllers.admin.UserListGrid attribute), 312
 preserve_state (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAssociationDistGrid attribute), 316
 preserve_state (galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGrid attribute), 318
 preserve_state (galaxy.webapps.galaxy.controllers.forms.FormsGrid attribute), 319
 preserve_state (galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute), 322
 preserve_state (galaxy.webapps.galaxy.controllers.library.LibraryListGrid attribute), 324

ProvidesHistoryContext (class in galaxy.managers.context), 160

ProvidesUserContext (class in galaxy.managers.context), 160

pruneLD() (in module galaxy.datatypes.converters.pbed_ldreduced_converter), 95

Psd (class in galaxy.datatypes.images), 62

pstats_as_html() (in module galaxy.web.framework.middleware.profile), 264

psyco_full (module), 369

public_actions (galaxy.jobs.actions.post.ActionBox attribute), 120

PublicURLColumn (class in galaxy.web.framework.helpers.grids), 262

published_list_grid (galaxy.webapps.galaxy.controllers.history.HistoryController attribute), 321

purge() (galaxy.managers.hdas.HDAManager method), 163

purge() (galaxy.managers.histories.HistoryManager method), 165

purge() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

purge_async() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

purge_deleted_datasets() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321

purge_group() (galaxy.web.base.controllers.admin.Admin method), 252

purge_library() (galaxy.webapps.galaxy.controllers.library_admin.LibraryAdmin method), 324

purge_operation (galaxy.web.base.controllers.admin.Admin attribute), 252

purge_operation (galaxy.webapps.galaxy.controllers.admin.Admin attribute), 306

purge_quota() (galaxy.webapps.galaxy.controllers.admin.Admin method), 306

purge_repository() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 313

purge_role() (galaxy.web.base.controllers.admin.Admin method), 252

purge_user() (galaxy.web.base.controllers.admin.Admin method), 252

put() (galaxy.jobs.handler.DefaultJobDispatcher method), 117

put() (galaxy.jobs.handler.JobHandlerQueue method), 118

put() (galaxy.jobs.handler.JobHandlerStopQueue method), 118

put() (galaxy.jobs.NoopQueue method), 116

put() (galaxy.jobs.runners.BaseJobRunner method), 125

put_stop() (galaxy.jobs.NoopQueue method), 116

PythonObjectParameter (class in galaxy.datatypes.metadata), 73

Q

qp (galaxy.datatypes.display_applications.parameters.DisplayDataValueWrapper attribute), 98

qp (galaxy.datatypes.display_applications.parameters.DisplayParameterValue attribute), 98

quality() (in module mimeparse), 358

quality_max (galaxy_utils.sequence.fastq.fastqCSSangerRead attribute), 353

quality_max (galaxy_utils.sequence.fastq.fastqIlluminaRead attribute), 354

quality_max (galaxy_utils.sequence.fastq.fastqSangerRead attribute), 354

quality_max (galaxy_utils.sequence.fastq.fastqSequencingRead attribute), 355

quality_max (galaxy_utils.sequence.fastq.fastqSolexaRead attribute), 355

quality_min (galaxy_utils.sequence.fastq.fastqCSSangerRead attribute), 353

quality_min (galaxy_utils.sequence.fastq.fastqIlluminaRead attribute), 354

quality_min (galaxy_utils.sequence.fastq.fastqSangerRead attribute), 354

quality_min (galaxy_utils.sequence.fastq.fastqSequencingRead attribute), 355

quality_min (galaxy_utils.sequence.fastq.fastqSolexaRead attribute), 355

quality_parsed() (in module mimeparse), 358

QualityScore (class in galaxy.datatypes.qualityscore), 74

QualityScoreIllumina (class in galaxy.datatypes.qualityscore), 74

QualityScoreSolexa (class in galaxy.datatypes.qualityscore), 75

QualityScoreSOLID (class in galaxy.datatypes.qualityscore), 75

query() (galaxy.managers.base.ModelManager method), 156

query_associated() (galaxy.managers.base.ModelManager method), 156

queue_history_export() (galaxy.web.base.controller.ExportsHistoryMixin method), 248

queue_history_import() (galaxy.web.base.controller.ImportsHistoryMixin method), 248

queue_job() (galaxy.jobs.runners.BaseJobRunner method), 125

queue_job() (galaxy.jobs.runners.cli.ShellJobRunner method), 125

queue_job() (galaxy.jobs.runners.condor.CondorJobRunner method), 126

[queue_job\(\) \(galaxy.jobs.runners.drmaa.DRMAAJobRunner method\), 126](#)
[queue_job\(\) \(galaxy.jobs.runners.local.LocalJobRunner method\), 127](#)
[queue_job\(\) \(galaxy.jobs.runners.lwr.LwrJobRunner method\), 127](#)
[queue_job\(\) \(galaxy.jobs.runners.tasks.TaskedJobRunner method\), 127](#)
[queued_dataset_files \(galaxy.model.Sample attribute\), 145](#)
[Quota \(class in galaxy.model\), 144](#)
[quota_amount\(\) \(galaxy.model.HistoryDatasetAssociation method\), 136](#)
[quota_list_grid \(galaxy.web.base.controllers.admin.Admin attribute\), 252](#)
[quota_list_grid \(galaxy.webapps.galaxy.controllers.admin.AdminGalaxy attribute\), 306](#)
[QuotaAgent \(class in galaxy.quota\), 174](#)
[QuotaAPIController \(class in galaxy.webapps.galaxy.api.quotas\), 33, 297](#)
[QuotaListGrid \(class in galaxy.webapps.galaxy.controllers.admin\), 307](#)
[QuotaListGrid.AmountColumn \(class in galaxy.webapps.galaxy.controllers.admin\), 307](#)
[QuotaListGrid.DescriptionColumn \(class in galaxy.webapps.galaxy.controllers.admin\), 307](#)
[QuotaListGrid.GroupsColumn \(class in galaxy.webapps.galaxy.controllers.admin\), 308](#)
[QuotaListGrid.NameColumn \(class in galaxy.webapps.galaxy.controllers.admin\), 308](#)
[QuotaListGrid.StatusColumn \(class in galaxy.webapps.galaxy.controllers.admin\), 308](#)
[QuotaListGrid.UsersColumn \(class in galaxy.webapps.galaxy.controllers.admin\), 308](#)
[QuotaParamParser \(class in galaxy.web.params\), 246](#)
[quotas\(\) \(galaxy.webapps.galaxy.controllers.admin.AdminGalaxy method\), 306](#)

R

[RangeParameter \(class in galaxy.datatypes.metadata\), 73](#)
[Rast \(class in galaxy.datatypes.images\), 62](#)
[rate_async\(\) \(galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method\), 315](#)
[rate_async\(\) \(galaxy.webapps.galaxy.controllers.history.HistoryController method\), 321](#)
[rate_async\(\) \(galaxy.webapps.galaxy.controllers.page.PageController method\), 329](#)
[rate_async\(\) \(galaxy.jobs.runners.drmaa.DRMAAJobRunner method\), 152](#)
[rating_assoc \(galaxy.managers.histories.HistoryManager attribute\), 165](#)
[raw_param_dict\(\) \(galaxy.model.Job method\), 139](#)
[RBACAgent \(class in galaxy.security\), 179](#)
[RData \(class in galaxy.datatypes.binary\), 47](#)
[read_build_sites\(\) \(in module galaxy.util\), 227](#)
[read_dbnames\(\) \(in module galaxy.util\), 227](#)
[read_lines\(\) \(galaxy.web.framework.base.FieldStorage method\), 254](#)
[read_unordered_gtf\(\) \(in module galaxy.datatypes.util.gff_util\), 100](#)
[Reader \(class in galaxy_utils.sequence.vcf\), 357](#)
[readline\(\) \(galaxy.tools.exception_handling.UCSCOutWrapper method\), 189](#)
[readline\(\) \(galaxy_utils.sequence.fastq.ReadlineCountFile method\), 352](#)
[ReadlineCountFile \(class in galaxy_utils.sequence.fastq\), 352](#)
[ready \(galaxy.model.JobExportHistoryArchive attribute\), 140](#)
[ready\(\) \(galaxy.datatypes.display_applications.parameters.DisplayApplication method\), 97](#)
[ready\(\) \(galaxy.datatypes.display_applications.parameters.DisplayApplication method\), 97](#)
[ready_name_for_url\(\) \(in module galaxy.util\), 227](#)
[ready_states \(galaxy.model.Dataset attribute\), 129](#)
[recalculate_user_disk_usage\(\) \(galaxy.webapps.galaxy.controllers.admin.AdminGalaxy method\), 306](#)
[reclaim_ownership\(\) \(galaxy.jobs.JobWrapper method\), 116](#)
[recover\(\) \(galaxy.jobs.handler.DefaultJobDispatcher method\), 117](#)
[recover\(\) \(galaxy.jobs.runners.BaseJobRunner method\), 125](#)
[recover\(\) \(galaxy.jobs.runners.cli.ShellJobRunner method\), 125](#)
[recover\(\) \(galaxy.jobs.runners.condor.CondorJobRunner method\), 126](#)
[recover\(\) \(galaxy.jobs.runners.drmaa.DRMAAJobRunner method\), 126](#)
[recover\(\) \(galaxy.jobs.runners.local.LocalJobRunner method\), 127](#)
[recover\(\) \(galaxy.jobs.runners.lwr.LwrJobRunner method\), 127](#)
[recover\(\) \(galaxy.jobs.runners.tasks.TaskedJobRunner method\), 127](#)
[recover_mapping\(\) \(galaxy.workflow.modules.InputModule method\), 348](#)
[recover_mapping\(\) \(galaxy.workflow.modules.PauseModule method\), 348](#)
[recover_mapping\(\) \(galaxy.workflow.modules.ToolModule method\), 348](#)

method), 349

recover_mapping() (galaxy.workflow.modules.WorkflowModule method), 351

recover_runtime_state() (galaxy.workflow.modules.SimpleWorkflowModule method), 349

recover_runtime_state() (galaxy.workflow.modules.ToolModule method), 350

recover_state() (galaxy.workflow.modules.SimpleWorkflowModule method), 349

recover_state() (galaxy.workflow.modules.ToolModule method), 350

recursively_stringify_dictionary_keys() (in module galaxy.util), 227

RecursiveNone (class in galaxy.util.none_like), 235

redirect() (galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner method), 338

reduce_block_by_primary_genome() (in module galaxy.tools.util.maf_utilities), 224

reference() (galaxy.visualization.genomes.Genomes method), 238

regenerate_primary_file() (galaxy.datatypes.assembly.Velvet method), 44

regenerate_primary_file() (galaxy.datatypes.genetics.RexpBase method), 57

regenerate_primary_file() (galaxy.datatypes.genetics.Rgenetics method), 58

regenerate_primary_file() (galaxy.datatypes.ngsindex.BowtieIndex method), 74

regex_line_dataprovider() (galaxy.datatypes.binary.Bam method), 45

regex_line_dataprovider() (galaxy.datatypes.data.Text method), 54

regex_line_dataprovider() (galaxy.datatypes.tabular.Sam method), 87

RegexValidator (class in galaxy.tools.parameters.validation), 221

RegionAlignment (class in galaxy.tools.util.maf_utilities), 222

register_cleanup_file_attribute() (galaxy.jobs.runners.AsynchronousJobState method), 124

register_finder() (in module pkg_resources), 368

register_loader_type() (in module pkg_resources), 368

register_namespace_handler() (in module pkg_resources), 368

register_sniffable_binary_format() (galaxy.datatypes.binary.Binary static method), 46

register_unsniffable_binary_ext() (galaxy.datatypes.binary.Binary static method), 46

registered_users() (galaxy.webapps.reports.controllers.users.Users method), 345

registered_users_per_month() (galaxy.webapps.reports.controllers.users.Users method), 345

Registry (class in galaxy.datatypes.registry), 75

reindex_tool_search() (galaxy.config.ConfiguresGalaxyMixin method), 42

reinstall_repository() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 313

reject_request() (galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin method), 333

relativize_symlinks() (in module galaxy.util), 227

reload() (galaxy.datatypes.display_applications.application.DisplayApplication method), 96

reload() (galaxy.sample_tracking.external_service_types.ExternalServiceTypes method), 175

reload() (galaxy.webapps.galaxy.api.tool_data.ToolData method), 35, 299

reload_display_application() (galaxy.webapps.galaxy.controllers.admin.AdminGalaxy method), 306

reload_display_applications() (galaxy.datatypes.registry.Registry method), 76

reload_external_service_types() (galaxy.webapps.galaxy.controllers.external_service.ExternalService method), 317

reload_from_files() (galaxy.tools.data.ToolDataTable method), 194

reload_genomes() (galaxy.visualization.genomes.Genomes method), 238

reload_tables() (galaxy.tools.data.ToolDataTableManager method), 194

reload_tool() (galaxy.web.base.controllers.admin.Admin method), 252

remote_host (galaxy.web.framework.base.Request attribute), 255

remote_hostname (galaxy.web.framework.base.Request attribute), 255

remote_port (galaxy.web.framework.base.Request attribute), 255

RemoteUser (class in galaxy.web.framework.middleware.remoteuser), 265

remove() (pkg_resources.Environment method), 360

remove_display_app() (galaxy.datatypes.data.Data method), 52

remove_doppelgangers() (galaxy.eggs.Egg method), 101

remove_entry() (galaxy.tools.data.ToolDataTable method), 194

remove_file_or_path() (in module galaxy.eggs), 101

remove_item_tag() (galaxy.managers.tags.TagManager method), 168

remove_tag_async() (galaxy.webapps.galaxy.controllers.tag.TagsController method), 337

remove_temp_index_file() (in module request_grid (galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin), 333
 galaxy.tools.util.maf_utilities), 224
 RemoveValueFilter (class in request_type_grid (galaxy.webapps.galaxy.controllers.request_type.RequestType), 330
 galaxy.tools.parameters.dynamic_options), 210
 request_type_permissions()
 rename() (galaxy.webapps.galaxy.controllers.history.HistoryController(galaxy.webapps.galaxy.controllers.request_type.RequestType method), 321
 method), 330
 rename_dataset_options (galaxy.model.RequestType attribute), 145
 rename_datasets() (galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdmin(galaxy.model), 144
 method), 333
 RequestInvalidException, 105
 RequestParameterInvalidException, 105
 RequestParameterMissingException, 105
 rename_group() (galaxy.web.base.controllers.admin.AdminRequestParameterMissingException, 105
 method), 252
 Requests (class in galaxy.webapps.galaxy.controllers.requests), 332
 rename_quota() (galaxy.webapps.galaxy.controllers.admin.AdminGalaxyRequestsAdmin (class in
 method), 306
 galaxy.webapps.galaxy.controllers.requests_admin), 333
 rename_role() (galaxy.web.base.controllers.admin.AdminRequestsAdminController (class in
 method), 252
 galaxy.webapps.galaxy.api.requests), 33,
 RenameDatasetAction (class in galaxy.jobs.actions.post), 121
 298
 repair_methods() (galaxy.datatypes.data.Data method), 52
 RequestsCommon (class in
 galaxy.webapps.galaxy.controllers.requests_common), 334
 repair_methods() (galaxy.datatypes.interval.Interval method), 68
 RequestsGrid (class in
 galaxy.webapps.galaxy.controllers.requests_common), 334
 repair_methods() (galaxy.datatypes.tabular.Pileup method), 86
 AdminToolshed
 repair_repository() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed
 method), 313
 RequestsGrid.DescriptionColumn (class in
 galaxy.webapps.galaxy.controllers.requests_common), 334
 repair_repository_revision()
 (galaxy.webapps.galaxy.api.tool_shed_repositories.ToolShedRepositoriesController
 method), 37, 301
 RequestsGrid.NameColumn (class in
 galaxy.webapps.galaxy.controllers.requests_common), 335
 repair_tool_shed_repositories()
 (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed
 method), 313
 RequestsGrid.SamplesColumn (class in
 galaxy.webapps.galaxy.controllers.requests_common), 335
 Repeat (class in galaxy.tools.parameters.grouping), 212
 Report (class in galaxy.webapps.reports.controllers.root), 343
 RequestsGrid.StateColumn (class in
 galaxy.webapps.galaxy.controllers.requests_common), 335
 report() (galaxy.util.debugging.SimpleProfiler method), 230
 RequestsGrid.TypeColumn (class in
 galaxy.webapps.galaxy.controllers.requests_common), 335
 report_error() (galaxy.webapps.galaxy.controllers.dataset.DatasetController
 method), 315
 REQUEST_FORMAT (galaxy.util.debugging.SimpleProfiler
 attribute), 230
 RequestType (class in galaxy.model), 144
 repository_installation_grid
 (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed
 attribute), 313
 RequestType (class in
 galaxy.webapps.galaxy.controllers.request_type), 330
 repository_installation_status_updates()
 (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed
 method), 313
 RequestTypeApiController (class in
 galaxy.webapps.galaxy.api.request_types), 33, 297
 repository_list_grid (galaxy.web.base.controllers.admin.AdminRequestTypeExternalServiceAssociation (class in
 attribute), 252
 galaxy.model), 145
 Request (class in galaxy.model), 144
 RequestTypeFactory (class in
 galaxy.sample_tracking.request_types), 175
 Request (class in galaxy.web.framework.base), 254
 RequestTypeGrid (class in
 galaxy.webapps.galaxy.controllers.request_type), 332

331
 RequestTypeGrid.DescriptionColumn (class in galaxy.webapps.galaxy.controllers.request_type), 331
 RequestTypeGrid.ExternalServiceColumn (class in galaxy.webapps.galaxy.controllers.request_type), 331
 RequestTypeGrid.NameColumn (class in galaxy.webapps.galaxy.controllers.request_type), 331
 RequestTypeGrid.RequestFormColumn (class in galaxy.webapps.galaxy.controllers.request_type), 331
 RequestTypeGrid.SampleFormColumn (class in galaxy.webapps.galaxy.controllers.request_type), 331
 RequestTypePermissions (class in galaxy.model), 145
 RequestTypeRunAssociation (class in galaxy.model), 145
 require() (galaxy.eggs.Egg method), 101
 require() (in module galaxy.eggs), 101
 require() (in module pkg_resources), 359
 require() (pkg_resources.EntryPoint method), 364
 require() (pkg_resources.WorkingSet method), 361
 require_file() (in module galaxy.tools.test), 190
 required_header_fields (galaxy_utils.sequence.vcf.VariantCall attribute), 357
 required_header_fields (galaxy_utils.sequence.vcf.VariantCall33 attribute), 357
 required_header_length (galaxy_utils.sequence.vcf.VariantCall attribute), 357
 required_header_length (galaxy_utils.sequence.vcf.VariantCall33 attribute), 357
 Requirement (class in pkg_resources), 363
 requires() (pkg_resources.Distribution method), 363
 requires_setting_metadata (galaxy.jobs.JobWrapper attribute), 116
 requires_setting_metadata (galaxy.tools.SetMetadataTool attribute), 184
 requires_setting_metadata (galaxy.tools.Tool attribute), 187
 requires_user_input (galaxy.external_services.parameters.ExternalServiceParameter attribute), 107
 rerun() (galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner method), 338
 reselect_tool_panel_section() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 314
 resend_verification() (galaxy.webapps.galaxy.controllers.user.User method), 339
 resend_verification_email() (galaxy.webapps.galaxy.controllers.user.User method), 339
 reset_metadata_on_installed_repositories() (galaxy.webapps.galaxy.api.tool_shed_repositories.RepositoryController method), 37, 301
 reset_metadata_on_selected_installed_repositories() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 314
 reset_password() (galaxy.webapps.galaxy.controllers.user.User method), 339
 reset_repository_metadata() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 314
 reset_to_install() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 314
 reset_user_password() (galaxy.web.base.controllers.admin.Admin method), 252
 ResolutionError, 364
 resolve() (galaxy.eggs.Crate method), 101
 resolve() (galaxy.eggs.Egg method), 101
 resolve() (pkg_resources.WorkingSet method), 361
 resolve_path() (galaxy.config.Configuration method), 42
 resolve_path() (in module galaxy.config), 42
 resolve_path() (in module galaxy.webapps.reports.config), 341
 resource_exists() (pkg_resources.ResourceManager method), 362
 resource_filename() (pkg_resources.ResourceManager method), 362
 resource_isdir() (pkg_resources.IResourceProvider method), 366
 resource_isdir() (pkg_resources.NullProvider method), 368
 resource_isdir() (pkg_resources.ResourceManager method), 362
 resource_listdir() (pkg_resources.IResourceProvider method), 366
 resource_listdir() (pkg_resources.NullProvider method), 368
 resource_listdir() (pkg_resources.ResourceManager method), 362
 resource_stream() (pkg_resources.ResourceManager method), 362
 resource_string() (pkg_resources.ResourceManager method), 362
 ResourceManager (class in pkg_resources), 361
 Response (class in galaxy.web.framework.base), 255
 restore_param() (galaxy.tools.parameters.sanitize.ToolParameterSanitizer method), 218
 restore_param() (galaxy.tools.parameters.sanitize.ToolParameterSanitizer method), 218
 restore_text() (in module galaxy.util), 228
 restrict_scores_to_valid_range() (galaxy_utils.sequence.fastq.fastqSequencingRead class method), 355
 resume_paused_jobs() (galaxy.model.History method), 135
 ResubmitJobsController (class in galaxy.webapps.galaxy.controllers.history.HistoryController), 135

- method), 321
- retag_async() (galaxy.webapps.galaxy.controllers.tag.TagsController method), 337
- reverse() (galaxy.util.odict.odict method), 235
- reverse() (galaxy_utils.sequence.fastq.fastqCSSangerRead method), 353
- reverse() (galaxy_utils.sequence.fastq.fastqSequencingRead method), 355
- reverse() (galaxy_utils.sequence.sequence.SequencingRead method), 356
- reverse() (in module galaxy_utils.sequence.transform), 357
- reverse_complement() (galaxy_utils.sequence.sequence.SequencingRead method), 356
- ReverseSortColumn (class in galaxy.web.framework.helpers.grids), 262
- review_tool_migration_stages() (galaxy.webapps.galaxy.controllers.admin.AdminController method), 306
- RexpBase (class in galaxy.datatypes.genetics), 56
- Rgb (class in galaxy.datatypes.images), 62
- rgConv() (in module galaxy.datatypes.converters.lped_to_fastq_converter), 94
- rgConv() (in module galaxy.datatypes.converters.lped_to_pbed_converter), 94
- rgConv() (in module galaxy.datatypes.converters.pbed_to_lped_converter), 95
- Rgenetics (class in galaxy.datatypes.genetics), 57
- rgFeatureList (class in galaxy.datatypes.genetics), 58
- rgSampleList (class in galaxy.datatypes.genetics), 58
- rgTabList (class in galaxy.datatypes.genetics), 59
- RNA_complement() (in module galaxy_utils.sequence.transform), 357
- RNA_reverse_complement() (in module galaxy_utils.sequence.transform), 357
- RNADotPlotMatrix (class in galaxy.datatypes.sequence), 80
- Roadmaps (class in galaxy.datatypes.assembly), 43
- Role (class in galaxy.model), 145
- role_list_grid (galaxy.web.base.controllers.admin.AdminController attribute), 252
- role_list_grid (galaxy.webapps.galaxy.controllers.admin.AdminController attribute), 306
- RoleApiController (class in galaxy.webapps.galaxy.api.roles), 34, 298
- RoleListGrid (class in galaxy.webapps.galaxy.controllers.admin), 308
- RoleListGrid.DescriptionColumn (class in galaxy.webapps.galaxy.controllers.admin), 309
- RoleListGrid.GroupsColumn (class in galaxy.webapps.galaxy.controllers.admin), 309
- RoleListGrid.NameColumn (class in galaxy.webapps.galaxy.controllers.admin), 309
- RoleListGrid.StatusColumn (class in galaxy.webapps.galaxy.controllers.admin), 309
- RoleListGrid.TypeColumn (class in galaxy.webapps.galaxy.controllers.admin), 309
- RoleListGrid.UsersColumn (class in galaxy.webapps.galaxy.controllers.admin), 309
- RoleManager (class in galaxy.managers.roles), 167
- roles() (galaxy.web.base.controllers.admin.AdminController method), 252
- rollback() (galaxy.model.orm.logging_connection_proxy.LoggingProxy method), 153
- RollbackContext (in module galaxy.web.base.controller), 248
- RootController (class in galaxy.webapps.galaxy.controllers.root), 336
- RootParentContext (class in galaxy.tools.test), 190
- roundify() (in module galaxy.util), 228
- roundify() (in module galaxy.util), 228
- Run (class in galaxy.model), 145
- run() (galaxy.jobs.transfer_manager.TransferManager method), 119
- run() (galaxy.util.heartbeat.Heartbeat method), 231
- run_details (galaxy.model.RequestType attribute), 145
- run_details (galaxy.model.Sample attribute), 145
- run_job() (galaxy.jobs.deferred.data_transfer.DataTransfer method), 123
- run_next() (galaxy.jobs.runners.BaseJobRunner method), 125
- run_scramble_script() (galaxy.eggs.dist.DistScrambleEgg method), 102
- run_scramble_script() (galaxy.eggs.scramble.ScrambleEgg method), 102
- run_script() (pkg_resources.IMetadataProvider method), 366
- run_script() (pkg_resources.NullProvider method), 368
- run_script() (pkg_resources.WorkingSet method), 361
- runner_name (galaxy.jobs.runners.cli.ShellJobRunner attribute), 125
- runner_name (galaxy.jobs.runners.condor.CondorJobRunner attribute), 126
- runner_name (galaxy.jobs.runners.drmaa.DRMAAJobRunner attribute), 126
- runner_name (galaxy.jobs.runners.local.LocalJobRunner attribute), 127
- runner_name (galaxy.jobs.runners.lwr.LwrJobRunner attribute), 127
- runner_name (galaxy.jobs.runners.tasks.TaskedJobRunner attribute), 128

- runner_states (galaxy.jobs.runners.JobState attribute), 125
- RunnerParams (class in galaxy.jobs.runners), 125
- running (galaxy.jobs.runners.AsynchronousJobState attribute), 124
- RuntimeException, 152
- RuntimeValue (class in galaxy.tools.parameters.basic), 205
- ## S
- sa_session (galaxy.managers.context.ProvidesAppContext attribute), 160
- sa_session (galaxy.security.GalaxyRBACAgent attribute), 178
- sa_session (galaxy.security.HostAgent attribute), 179
- sa_session (galaxy.tools.Tool attribute), 187
- safe_dumps() (in module galaxy.util.json), 234
- safe_extra() (in module pkg_resources), 365
- safe_name() (in module pkg_resources), 365
- safe_str_cmp() (in module galaxy.util), 228
- safe_version() (in module pkg_resources), 365
- Sam (class in galaxy.datatypes.tabular), 87
- Sample (class in galaxy.model), 145
- sample_datasets_updates() (galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon method), 334
- sample_state_updates() (galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon method), 334
- SampleDataset (class in galaxy.model), 146
- SampleEvent (class in galaxy.model), 146
- SampleRunAssociation (class in galaxy.model), 146
- samples_have_common_state (galaxy.model.Request attribute), 144
- samples_with_bar_code (galaxy.model.Request attribute), 144
- samples_without_library_destinations (galaxy.model.Request attribute), 144
- SamplesApiController (class in galaxy.webapps.galaxy.api.samples), 34, 298
- SampleState (class in galaxy.model), 146
- SampleStateFactory (class in galaxy.sample_tracking.sample), 175
- SampleTracking (class in galaxy.webapps.reports.controllers.sample_tracking), 343
- samtools_dataprovider() (galaxy.datatypes.binary.Bam method), 45
- sanitize_for_filename() (in module galaxy.util), 228
- sanitize_html() (in module galaxy.util.sanitize_html), 235
- sanitize_lists_to_string() (in module galaxy.util), 228
- sanitize_param() (galaxy.tools.parameters.sanitize.ToolParameterSanitizer method), 218
- sanitize_param() (in module galaxy.util), 228
- sanitize_text() (galaxy.tools.parameters.sanitize.ToolParameterSanitizer method), 218
- sanitize_text() (in module galaxy.util), 228
- save() (galaxy.webapps.galaxy.controllers.page.PageController method), 329
- save_form_definition() (galaxy.webapps.galaxy.controllers.forms.Forms method), 318
- save_to_step() (galaxy.workflow.modules.SimpleWorkflowModule method), 349
- save_to_step() (galaxy.workflow.modules.ToolModule method), 350
- save_to_step() (galaxy.workflow.modules.WorkflowModule method), 351
- save_visualization() (galaxy.web.base.controller.UsesVisualizationMixin method), 251
- save_widget_field() (galaxy.web.base.controller.UsesFormDefinitionsMixin method), 249
- scan() (pkg_resources.Environment method), 360
- Scf (class in galaxy.datatypes.binary), 48
- score_system (galaxy_utils.sequence.fastq.fastqCSSangerRead attribute), 353
- score_system (galaxy_utils.sequence.fastq.fastqIlluminaRead attribute), 354
- score_system (galaxy_utils.sequence.fastq.fastqSangerRead attribute), 354
- score_system (galaxy_utils.sequence.fastq.fastqSequencingRead attribute), 355
- score_system (galaxy_utils.sequence.fastq.fastqSolexaRead attribute), 355
- ScpDataTransferFactory (class in galaxy.sample_tracking.data_transfer), 174
- scramble() (galaxy.eggs.scramble.ScrambleCrate method), 102
- scramble() (galaxy.eggs.scramble.ScrambleEgg method), 102
- scramble_dir (galaxy.eggs.scramble.ScrambleEgg attribute), 102
- ScrambleCrate (class in galaxy.eggs.scramble), 102
- ScrambleEgg (class in galaxy.eggs.scramble), 102
- ScrambleFailure, 102
- script_dir (galaxy.eggs.scramble.ScrambleEgg attribute), 102
- search() (galaxy.tools.search.ToolBoxSearch method), 222
- search() (galaxy.webapps.galaxy.api.jobs.JobController method), 22, 287
- Section (class in galaxy.tools.parameters.grouping), 212
- secure() (galaxy.managers.folders.FolderManager method), 162
- secure() (galaxy.managers.libraries.LibraryManager method), 167
- security_check() (galaxy.web.base.controller.SharableItemSecurityMixin method), 248
- security_check() (in module galaxy.managers.base), 158

SecurityHelper (class in galaxy.web.security), 266
 select_datasets_to_transfer() (galaxy.webapps.galaxy.controllers.requests_admin.RequestAdminManagers.hdas.HDASerializer method), 334
 SelectField (class in galaxy.web.form_builder), 244
 SelectParameter (class in galaxy.datatypes.metadata), 73
 SelectToolParameter (class in galaxy.tools.parameters.basic), 205
 send_email_notification() (galaxy.model.Request method), 144
 send_file() (in module galaxy.web.framework.base), 256
 send_mail() (in module galaxy.util), 228
 send_redirect() (galaxy.web.framework.base.Response method), 255
 send_verification_email() (galaxy.webapps.galaxy.controllers.user.User method), 340
 sentry_dsn_public (galaxy.config.Configuration attribute), 42
 sep() (galaxy.jobs.ComputeEnvironment method), 112
 sep() (galaxy.jobs.SimpleComputeEnvironment method), 116
 sep2tabs() (in module galaxy.datatypes.sniff), 85
 Sequence (class in galaxy.datatypes.sequence), 81
 sequence_as_DNA() (galaxy_utils.sequence.sequence.Sequence object), 356
 sequence_as_RNA() (galaxy_utils.sequence.sequence.Sequence object), 356
 sequence_space (galaxy_utils.sequence.fastq.fastqCSSangerRead attribute), 353
 sequence_space (galaxy_utils.sequence.fastq.fastqIlluminaRead attribute), 354
 sequence_space (galaxy_utils.sequence.fastq.fastqSangerRead attribute), 354
 sequence_space (galaxy_utils.sequence.fastq.fastqSequencingRead attribute), 355
 sequence_space (galaxy_utils.sequence.fastq.fastqSolexaRead attribute), 355
 Sequences (class in galaxy.datatypes.assembly), 44
 SequenceSplitLocations (class in galaxy.datatypes.sequence), 82
 SequencingRead (class in galaxy_utils.sequence.sequence), 356
 serialize() (galaxy.managers.base.ModelSerializer method), 157
 serialize_contents() (galaxy.managers.histories.HistorySerializer method), 165
 serialize_date() (galaxy.managers.base.ModelSerializer method), 157
 serialize_display_apps() (galaxy.managers.hdas.HDASerializer method), 164
 serialize_history_state() (galaxy.managers.histories.HistorySerializer method), 165
 serialize_id() (galaxy.managers.base.ModelSerializer method), 157
 serialize_old_display_applications() (galaxy.managers.hdas.HDASerializer method), 164
 serialize_state_counts() (galaxy.managers.histories.HistorySerializer method), 165
 serialize_state_ids() (galaxy.managers.histories.HistorySerializer method), 165
 serialize_to_view() (galaxy.managers.base.ModelSerializer method), 157
 serialize_type_id() (galaxy.managers.hdas.HDASerializer method), 164
 serialize_urls() (galaxy.managers.hdas.HDASerializer method), 164
 serialize_visualization_links() (galaxy.managers.hdas.HDASerializer method), 164
 serve_ready_history_export() (galaxy.web.base.controller.ExportsHistoryMixin method), 248
 session (galaxy.web.framework.base.DefaultWebTransaction attribute), 253
 session() (galaxy.managers.base.ModelManager method), 156
 setting_black() (galaxy.tools.data.ToolDataTableManager method), 194
 setting_black_async() (galaxy.webapps.galaxy.controllers.dataset.DatasetIn method), 315
 setting_black_accessible_async() (galaxy.webapps.galaxy.controllers.history.HistoryC method), 321
 setting_black_accessible_async() (galaxy.webapps.galaxy.controllers.page.PageContro method), 329
 set_all_dataset_permissions() (galaxy.security.GalaxyRBACAgent method), 178
 set_all_dataset_permissions() (galaxy.security.RBACAgent method), 180
 set_all_library_permissions() (galaxy.security.GalaxyRBACAgent method), 179
 set_all_library_permissions() (galaxy.security.RBACAgent method), 180
 set_amount() (galaxy.model.Quota method), 144
 set_as_current() (galaxy.webapps.galaxy.controllers.history.HistoryControll method), 321
 set_attribute_metadata() (galaxy.datatypes.interval.Gff method), 66
 set_basic_defaults() (in module galaxy.jobs.splitters.basic), 128
 set_check_interval() (galaxy.model.DeferredJob method), 133
 set_checked() (galaxy.web.form_builder.CheckboxField method), 242
 set_collection_elements()

- (`galaxy.managers.collections.DatasetCollectionManager` method), 159
- `set_command_line()` (`galaxy.model.Job` method), 139
- `set_command_line()` (`galaxy.model.Task` method), 147
- `set_content_type()` (`galaxy.web.framework.base.Response` method), 255
- `set_current()` (`galaxy.managers.histories.HistoryManager` method), 165
- `set_current_by_id()` (`galaxy.managers.histories.HistoryManager` method), 165
- `set_dataset_permission()` (`galaxy.security.GalaxyRBACAgent` method), 179
- `set_dataset_permission()` (`galaxy.security.RBACAgent` method), 180
- `set_dataset_permissions()` (`galaxy.security.HostAgent` method), 179
- `set_dataset_state()` (`galaxy.model.DatasetInstance` method), 132
- `set_datatypes_registry()` (in module `galaxy.model`), 151
- `set_dbkey()` (`galaxy.model.DatasetInstance` method), 132
- `set_default_permissions()` (`galaxy.webapps.galaxy.controllers.user.User` method), 340
- `set_default_quota()` (`galaxy.quota.QuotaAgent` method), 174
- `set_default_values()` (`galaxy.datatypes.registry.Registry` method), 76
- `set_defaults()` (`galaxy.jobs.runners.JobState` method), 125
- `set_dir()` (`galaxy.eggs.dist.DistScrambleEgg` method), 102
- `set_dir()` (`galaxy.eggs.Egg` method), 101
- `set_disk_usage()` (`galaxy.model.GalaxySession` method), 134
- `set_disk_usage()` (`galaxy.model.User` method), 148
- `set_distribution()` (`galaxy.eggs.Egg` method), 101
- `set_entity_group_associations()` (`galaxy.security.GalaxyRBACAgent` method), 179
- `set_entity_quota_associations()` (`galaxy.quota.QuotaAgent` method), 174
- `set_entity_role_associations()` (`galaxy.security.GalaxyRBACAgent` method), 179
- `set_entity_user_associations()` (`galaxy.security.GalaxyRBACAgent` method), 179
- `set_extra_files_path()` (`galaxy.model.Dataset` method), 129
- `set_extraction_path()` (`pkg_resources.ResourceManager` method), 362
- `set_file_name()` (`galaxy.model.Dataset` method), 129
- `set_file_name()` (`galaxy.model.DatasetInstance` method), 132
- `set_final_state()` (`galaxy.model.Job` method), 139
- `set_from_dict()` (`galaxy.model.DatasetCollection` method), 130
- `set_from_dict()` (`galaxy.model.DatasetCollectionInstance` method), 130
- `set_handler()` (`galaxy.model.Job` method), 139
- `set_id()` (`galaxy.model.Task` method), 147
- `set_imported()` (`galaxy.model.Job` method), 139
- `set_info()` (`galaxy.model.Job` method), 139
- `set_info()` (`galaxy.model.LibraryDataset` method), 141
- `set_info()` (`galaxy.model.Task` method), 147
- `set_input_datasets()` (`galaxy.model.Job` method), 139
- `set_input_library_datasets()` (`galaxy.model.Job` method), 139
- `set_item()` (`galaxy.model.HistoryDatasetAssociationRatingAssociation` method), 136
- `set_item()` (`galaxy.model.HistoryDatasetCollectionRatingAssociation` method), 137
- `set_item()` (`galaxy.model.HistoryRatingAssociation` method), 137
- `set_item()` (`galaxy.model.ItemRatingAssociation` method), 138
- `set_item()` (`galaxy.model.LibraryDatasetCollectionRatingAssociation` method), 142
- `set_item()` (`galaxy.model.PageRatingAssociation` method), 143
- `set_item()` (`galaxy.model.StoredWorkflowRatingAssociation` method), 146
- `set_item()` (`galaxy.model.VisualizationRatingAssociation` method), 149
- `set_item_extended_metadata_obj()` (`galaxy.web.base.controller.UsesExtendedMetadataMixin` method), 248
- `set_job()` (`galaxy.model.Task` method), 147
- `set_job_destination()` (`galaxy.jobs.JobWrapper` method), 116
- `set_job_runner_external_id()` (`galaxy.model.Task` method), 147
- `set_job_runner_external_pid()` (`galaxy.datatypes.metadata.JobExternalOutputMetadataWrapper` method), 71
- `set_last_check()` (`galaxy.model.DeferredJob` method), 133
- `set_library_dataset_dataset_association()` (`galaxy.model.LibraryDataset` method), 141
- `set_library_item_permission()` (`galaxy.security.GalaxyRBACAgent` method), 179
- `set_library_item_permission()` (`galaxy.security.RBACAgent` method), 180
- `set_max_optional_metadata_filesize()` (`galaxy.datatypes.data.Data` method), 52
- `set_meta()` (`galaxy.datatypes.assembly.Velvet` method), 44
- `set_meta()` (`galaxy.datatypes.binary.Bam` method), 45

- `set_meta()` (galaxy.datatypes.binary.Bcf method), 45
- `set_meta()` (galaxy.datatypes.binary.GeminiSQLite method), 47
- `set_meta()` (galaxy.datatypes.binary.SQLite method), 48
- `set_meta()` (galaxy.datatypes.data.Data method), 52
- `set_meta()` (galaxy.datatypes.data.Text method), 54
- `set_meta()` (galaxy.datatypes.genetics.GenomeGraphs method), 55
- `set_meta()` (galaxy.datatypes.genetics.RexpBase method), 57
- `set_meta()` (galaxy.datatypes.genetics.Rgenetics method), 58
- `set_meta()` (galaxy.datatypes.interval.Bed method), 63
- `set_meta()` (galaxy.datatypes.interval.BedStrict method), 64
- `set_meta()` (galaxy.datatypes.interval.CustomTrack method), 65
- `set_meta()` (galaxy.datatypes.interval.Gff method), 66
- `set_meta()` (galaxy.datatypes.interval.Gff3 method), 67
- `set_meta()` (galaxy.datatypes.interval.Interval method), 68
- `set_meta()` (galaxy.datatypes.interval.Wiggle method), 69
- `set_meta()` (galaxy.datatypes.qualityscore.QualityScoreSOLiD method), 75
- `set_meta()` (galaxy.datatypes.sequence.csFasta method), 82
- `set_meta()` (galaxy.datatypes.sequence.Fastq method), 78
- `set_meta()` (galaxy.datatypes.sequence.Maf method), 80
- `set_meta()` (galaxy.datatypes.sequence.MafCustomTrack method), 80
- `set_meta()` (galaxy.datatypes.sequence.Sequence method), 81
- `set_meta()` (galaxy.datatypes.tabular.CSV method), 85
- `set_meta()` (galaxy.datatypes.tabular.Eland method), 86
- `set_meta()` (galaxy.datatypes.tabular.Sam method), 87
- `set_meta()` (galaxy.datatypes.tabular.Tabular method), 88
- `set_meta()` (galaxy.datatypes.tabular.Vcf method), 90
- `set_meta()` (galaxy.model.DatasetInstance method), 132
- `set_metadata()` (galaxy.model.DatasetInstance method), 132
- `set_name()` (galaxy.model.LibraryDataset method), 141
- `set_non_data_connection()` (galaxy.model.WorkflowStepConnection method), 151
- `set_object_store_id()` (galaxy.tools.actions.ObjectStorePopulator method), 190
- `set_output_datasets()` (galaxy.model.Job method), 139
- `set_output_library_datasets()` (galaxy.model.Job method), 139
- `set_param_filename()` (galaxy.model.Job method), 139
- `set_parameters()` (galaxy.model.Job method), 139
- `set_parameters()` (galaxy.model.Task method), 147
- `set_params()` (galaxy.model.Job method), 139
- `set_parent()` (galaxy.datatypes.metadata.MetadataCollection method), 71
- `set_password_cleartext()` (galaxy.model.User method), 148
- `set_peek()` (galaxy.datatypes.binary.Abl method), 44
- `set_peek()` (galaxy.datatypes.binary.Bam method), 45
- `set_peek()` (galaxy.datatypes.binary.BigWig method), 46
- `set_peek()` (galaxy.datatypes.binary.Binary method), 46
- `set_peek()` (galaxy.datatypes.binary.CompressedArchive method), 46
- `set_peek()` (galaxy.datatypes.binary.GeminiSQLite method), 47
- `set_peek()` (galaxy.datatypes.binary.H5 method), 47
- `set_peek()` (galaxy.datatypes.binary.Scf method), 48
- `set_peek()` (galaxy.datatypes.binary.Sff method), 48
- `set_peek()` (galaxy.datatypes.binary.SQLite method), 48
- `set_peek()` (galaxy.datatypes.binary.Sra method), 48
- `set_peek()` (galaxy.datatypes.binary.TwoBit method), 49
- `set_peek()` (galaxy.datatypes.data.Data method), 52
- `set_peek()` (galaxy.datatypes.data.Text method), 54
- `set_peek()` (galaxy.datatypes.genetics.RexpBase method), 57
- `set_peek()` (galaxy.datatypes.genetics.SNPMatrix method), 58
- `set_peek()` (galaxy.datatypes.images.Gmaj method), 60
- `set_peek()` (galaxy.datatypes.images.Html method), 60
- `set_peek()` (galaxy.datatypes.images.Image method), 60
- `set_peek()` (galaxy.datatypes.images.Laj method), 61
- `set_peek()` (galaxy.datatypes.ngsindex.BowtieIndex method), 74
- `set_peek()` (galaxy.datatypes.sequence.Maf method), 80
- `set_peek()` (galaxy.datatypes.sequence.RNADotPlotMatrix method), 81
- `set_peek()` (galaxy.datatypes.sequence.Sequence method), 81
- `set_peek()` (galaxy.datatypes.sequence.SequenceSplitLocations method), 82
- `set_peek()` (galaxy.datatypes.tabular.TabularData method), 89
- `set_peek()` (galaxy.datatypes.xml.CisML method), 90
- `set_peek()` (galaxy.datatypes.xml.GenericXml method), 90
- `set_peek()` (galaxy.datatypes.xml.MEMEXml method), 91
- `set_peek()` (galaxy.datatypes.xml.Owl method), 91
- `set_peek()` (galaxy.datatypes.xml.Phyloxml method), 91
- `set_peek()` (galaxy.model.DatasetInstance method), 132
- `set_permission_roles()` (galaxy.managers.libraries.LibraryManager method), 167
- `set_permissions()` (galaxy.webapps.galaxy.api.folders.FoldersController method), 12, 277
- `set_permissions()` (galaxy.webapps.galaxy.api.libraries.LibrariesController method), 27, 291
- `set_permissions_old()` (galaxy.webapps.galaxy.api.libraries.LibrariesController method), 27, 292
- `set_position()` (galaxy.tools.util.maf_utilities.RegionAlignment

method), 222

set_post_job_actions() (galaxy.model.Job method), 139

set_prepare_input_files_cmd() (galaxy.model.Task method), 147

set_public_username() (galaxy.web.base.controller.SharableMixin method), 248

set_quota_default() (galaxy.webapps.galaxy.controllers.admin.AdminController method), 306

set_range() (galaxy.tools.util.maf_utilities.RegionAlignment method), 222

set_raw_data() (galaxy.datatypes.data.Data method), 52

set_raw_data() (galaxy.datatypes.data.Text method), 54

set_raw_data() (galaxy.model.DatasetInstance method), 132

set_request_type_permissions() (galaxy.security.GalaxyRBACAgent method), 179

set_runner() (galaxy.jobs.JobWrapper method), 116

set_runner() (galaxy.jobs.TaskWrapper method), 117

set_runner_external_id() (galaxy.model.Job method), 139

set_runner_name() (galaxy.model.Job method), 139

set_session_id() (galaxy.model.Job method), 140

set_size() (galaxy.model.Dataset method), 129

set_size() (galaxy.model.DatasetInstance method), 132

set_size() (galaxy.web.form_builder.PasswordField method), 244

set_size() (galaxy.web.form_builder.TextArea method), 245

set_size() (galaxy.web.form_builder.TextField method), 246

set_slug_async() (galaxy.web.base.controller.SharableMixin method), 248

set_state() (galaxy.model.Job method), 140

set_state() (galaxy.model.Task method), 147

set_stderr() (galaxy.model.Task method), 147

set_stdout() (galaxy.model.Task method), 147

set_tags_from_list() (galaxy.managers.tags.TagManager method), 168

set_tags_from_list() (galaxy.web.base.controller.UsesTagsMixin method), 250

set_task_runner_external_id() (galaxy.model.Task method), 147

set_task_runner_name() (galaxy.model.Task method), 147

set_tool_id() (galaxy.model.Job method), 140

set_tool_version() (galaxy.model.Job method), 140

set_tool_versions() (galaxy.webapps.galaxy.controllers.admin.AdminController method), 314

set_total_size() (galaxy.model.Dataset method), 129

set_total_size() (galaxy.model.DatasetInstance method), 132

set_transaction_factory() (galaxy.web.framework.base.WebApplication method), 256

set_user_id() (galaxy.model.Job method), 140

set_user_pref_async() (galaxy.webapps.galaxy.controllers.user.User method), 340

set_working_directory() (galaxy.model.Task method), 147

setDefault() (galaxy.util.odict.odict method), 235

SetMetadataAction (class in galaxy.jobs.actions.post), 122

SetMetadataTool (class in galaxy.tools), 183

SetMetadataToolAction (class in galaxy.tools.actions.metadata), 191

SetParamAction (class in galaxy.tools), 184

settings() (galaxy.webapps.galaxy.controllers.mobile.Mobile method), 327

setup_external_metadata() (galaxy.datatypes.metadata.JobExternalOutputMetadataWrapper method), 71

setup_external_metadata() (galaxy.jobs.JobWrapper method), 116

setup_external_metadata() (galaxy.jobs.TaskWrapper method), 117

setup_job() (galaxy.tools.imp_exp.JobExportHistoryArchiveWrapper method), 196

SETUP_NEEDED (galaxy.web.framework.openid_manager.OpenIDManager attribute), 256

Sff (class in galaxy.datatypes.binary), 48

SharableItemSecurityMixin (class in galaxy.web.base.controller), 248

SharableMixin (class in galaxy.web.base.controller), 248

share() (galaxy.web.base.controller.SharableMixin method), 248

share() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321

share() (galaxy.webapps.galaxy.controllers.page.PageController method), 329

share_restricted() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321

shared_list_grid (galaxy.webapps.galaxy.controllers.history.HistoryController attribute), 321

SharedComputeEnvironment (class in galaxy.jobs), 116

SharedHistoryListGrid (class in galaxy.webapps.galaxy.controllers.history), 323

SharedHistoryListGrid.DatasetsByStateColumn (class in galaxy.webapps.galaxy.controllers.history), 323

SharedHistoryListGrid.SharedByColumn (class in galaxy.webapps.galaxy.controllers.history), 323

sharing() (galaxy.web.base.controller.SharableMixin method), 248

sharing() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321

sharing() (galaxy.webapps.galaxy.controllers.page.PageController

method), 329

SharingStatusColumn (class in galaxy.web.framework.helpers.grids), 263

ShellJobRunner (class in galaxy.jobs.runners.cli), 125

show() (galaxy.webapps.galaxy.api.dataset_collections.DatasetCollectionsApiController method), 9, 274

show() (galaxy.webapps.galaxy.api.folder_contents.FolderContentsApiController method), 11, 276

show() (galaxy.webapps.galaxy.api.folders.FoldersApiController method), 13, 277

show() (galaxy.webapps.galaxy.api.forms.FormDefinitionApiController method), 13, 278

show() (galaxy.webapps.galaxy.api.genomes.GenomesApiController method), 13, 278

show() (galaxy.webapps.galaxy.api.group_roles.GroupRolesApiController method), 14, 278

show() (galaxy.webapps.galaxy.api.group_users.GroupUsersApiController method), 14, 279

show() (galaxy.webapps.galaxy.api.groups.GroupApiController method), 14, 279

show() (galaxy.webapps.galaxy.api.histories.HistoriesApiController method), 16, 281

show() (galaxy.webapps.galaxy.api.history_contents.HistoryContentsApiController method), 19, 284

show() (galaxy.webapps.galaxy.api.item_tags.BaseItemTagsApiController method), 20, 284

show() (galaxy.webapps.galaxy.api.jobs.JobApiController method), 23, 287

show() (galaxy.webapps.galaxy.api.lda_datasets.LibraryDatasetsApiController method), 24, 289

show() (galaxy.webapps.galaxy.api.libraries.LibrariesApiController method), 27, 292

show() (galaxy.webapps.galaxy.api.library_contents.LibraryContentsApiController method), 30, 294

show() (galaxy.webapps.galaxy.api.pages.PagesApiController method), 32, 296

show() (galaxy.webapps.galaxy.api.provenance.BaseProvenanceApiController method), 32, 297

show() (galaxy.webapps.galaxy.api.quotas.QuotaApiController method), 33, 297

show() (galaxy.webapps.galaxy.api.request_types.RequestTypesApiController method), 33, 298

show() (galaxy.webapps.galaxy.api.requests.RequestsApiController method), 34, 298

show() (galaxy.webapps.galaxy.api.roles.RoleApiController method), 34, 298

show() (galaxy.webapps.galaxy.api.tool_data.ToolDataApiController method), 35, 299

show() (galaxy.webapps.galaxy.api.tool_shed_repositories.ToolShedRepositoriesApiController method), 38, 302

show() (galaxy.webapps.galaxy.api.users.UserApiController method), 38, 302

show() (galaxy.webapps.galaxy.api.visualizations.VisualizationsApiController method), 39, 303

show() (galaxy.webapps.galaxy.api.workflows.WorkflowsApiController method), 41, 305

show_editable_form_definition() (galaxy.webapps.galaxy.controllers.forms.FormsController method), 35, 299

show_field() (galaxy.webapps.galaxy.api.tool_data.ToolDataApiController method), 41, 305

show_invocation() (galaxy.webapps.galaxy.api.workflows.WorkflowsApiController method), 41, 305

show_item_checkboxes (galaxy.web.framework.helpers.grids.Grid attribute), 260

show_item_checkboxes (galaxy.webapps.galaxy.controllers.page.ItemSelector attribute), 328

show_library_item() (galaxy.security.GalaxyRBACAgent method), 179

show_params() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 315

show_roles() (galaxy.webapps.galaxy.api.lda_datasets.LibraryDatasetsApiController method), 24, 289

show_version() (galaxy.webapps.galaxy.api.lda_datasets.LibraryDatasetsApiController method), 25, 289

shrink_stream_by_size() (in module galaxy.util), 228

shrink_stream_by_size() (in module galaxy.util), 229

shutdown() (galaxy.jobs.deferred.DeferredJobQueue method), 122

shutdown() (galaxy.jobs.handler.DefaultJobDispatcher method), 117

shutdown() (galaxy.jobs.handler.JobHandler method), 118

shutdown() (galaxy.jobs.handler.JobHandlerQueue method), 118

shutdown() (galaxy.jobs.handler.JobHandlerStopQueue method), 118

shutdown() (galaxy.jobs.manager.JobManager method), 119

shutdown() (galaxy.jobs.manager.NoopHandler method), 116

shutdown() (galaxy.jobs.NoopQueue method), 116

shutdown() (galaxy.jobs.runners.AsynchronousJobRunner method), 124

shutdown() (galaxy.jobs.runners.BaseJobRunner method), 125

shutdown() (galaxy.jobs.runners.lwr.LwrJobRunner method), 127

shutdown() (galaxy.jobs.transfer_manager.TransferManager method), 119

shutdown() (galaxy.objectstore.DistributedObjectStore method), 170

shutdown() (galaxy.objectstore.NestedObjectStore method), 170

shutdown() (galaxy.objectstore.ObjectStore method), 172

shutdown() (galaxy.util.heartbeat.Heartbeat method), 231

shutdown() (galaxy.webapps.reports.app.UniverseApplication method), 340

- SimpleComputeEnvironment (class in galaxy.jobs), 116
- SimpleProfiler (class in galaxy.util.debugging), 230
- SimpleWorkflowModule (class in galaxy.workflow.modules), 348
- SINGLE_CHAR_ABBR (galaxy.managers.histories.HistorySerializer attribute), 165
- singularize() (galaxy.util.inflection.English method), 232
- singularize() (galaxy.util.inflection.Inflector method), 233
- sites (galaxy.security.HostAgent attribute), 179
- size() (galaxy.objectstore.DiskObjectStore method), 170
- size() (galaxy.objectstore.NestedObjectStore method), 170
- size() (galaxy.objectstore.ObjectStore method), 172
- size_to_bytes() (in module galaxy.util), 229
- skip() (galaxy.managers.base.ModelSerializer method), 157
- SkipAttribute, 158
- skipped() (in module galaxy.tools.util.galaxyops), 225
- sleep() (galaxy.jobs.deferred.Sleeper method), 122
- sleep() (galaxy.jobs.transfer_manager.Sleeper method), 119
- Sleeper (class in galaxy.jobs.deferred), 122
- Sleeper (class in galaxy.jobs.transfer_manager), 119
- slice() (galaxy_utils.sequence.fastq.fastqSequencingRead method), 355
- smart_str() (in module galaxy.util), 229
- SMRTPortalPlugin (class in galaxy.jobs.deferred.pacific_biosciences_smrt_portal), 123
- sniff() (galaxy.datatypes.assembly.Amos method), 43
- sniff() (galaxy.datatypes.assembly.Roadmaps method), 43
- sniff() (galaxy.datatypes.assembly.Sequences method), 44
- sniff() (galaxy.datatypes.binary.Bam method), 45
- sniff() (galaxy.datatypes.binary.Bcf method), 45
- sniff() (galaxy.datatypes.binary.BigWig method), 46
- sniff() (galaxy.datatypes.binary.GeminiSQLite method), 47
- sniff() (galaxy.datatypes.binary.Idat method), 47
- sniff() (galaxy.datatypes.binary.RData method), 47
- sniff() (galaxy.datatypes.binary.Sff method), 48
- sniff() (galaxy.datatypes.binary.SQLite method), 48
- sniff() (galaxy.datatypes.binary.Sra method), 48
- sniff() (galaxy.datatypes.binary.TwoBit method), 49
- sniff() (galaxy.datatypes.binary.Xlsx method), 49
- sniff() (galaxy.datatypes.data.Newick method), 53
- sniff() (galaxy.datatypes.data.Nexus method), 53
- sniff() (galaxy.datatypes.genetics.GenomeGraphs method), 55
- sniff() (galaxy.datatypes.genetics.rgSampleList method), 59
- sniff() (galaxy.datatypes.genetics.SNPMatrix method), 58
- sniff() (galaxy.datatypes.images.Bmp method), 59
- sniff() (galaxy.datatypes.images.Eps method), 59
- sniff() (galaxy.datatypes.images.Gif method), 59
- sniff() (galaxy.datatypes.images.Gmaj method), 60
- sniff() (galaxy.datatypes.images.Html method), 60
- sniff() (galaxy.datatypes.images.Im method), 60
- sniff() (galaxy.datatypes.images.Image method), 60
- sniff() (galaxy.datatypes.images.Jpg method), 61
- sniff() (galaxy.datatypes.images.Pbm method), 61
- sniff() (galaxy.datatypes.images.Pcd method), 61
- sniff() (galaxy.datatypes.images.Pcx method), 61
- sniff() (galaxy.datatypes.images.Pdf method), 61
- sniff() (galaxy.datatypes.images.Pgm method), 62
- sniff() (galaxy.datatypes.images.Png method), 62
- sniff() (galaxy.datatypes.images.Ppm method), 62
- sniff() (galaxy.datatypes.images.Psd method), 62
- sniff() (galaxy.datatypes.images.Rast method), 62
- sniff() (galaxy.datatypes.images.Rgb method), 62
- sniff() (galaxy.datatypes.images.Tiff method), 62
- sniff() (galaxy.datatypes.images.Xbm method), 63
- sniff() (galaxy.datatypes.images.Xpm method), 63
- sniff() (galaxy.datatypes.interval.Bed method), 63
- sniff() (galaxy.datatypes.interval.BedStrict method), 64
- sniff() (galaxy.datatypes.interval.ChromatinInteractions method), 65
- sniff() (galaxy.datatypes.interval.CustomTrack method), 65
- sniff() (galaxy.datatypes.interval.ENCODERPeak method), 65
- sniff() (galaxy.datatypes.interval.Gff method), 66
- sniff() (galaxy.datatypes.interval.Gff3 method), 67
- sniff() (galaxy.datatypes.interval.Gtf method), 67
- sniff() (galaxy.datatypes.interval.Interval method), 68
- sniff() (galaxy.datatypes.interval.Wiggle method), 69
- sniff() (galaxy.datatypes.ngsindex.BowtieIndex method), 74
- sniff() (galaxy.datatypes.qualityscore.QualityScore454 method), 74
- sniff() (galaxy.datatypes.qualityscore.QualityScoreSOLiD method), 75
- sniff() (galaxy.datatypes.sequence.Axt method), 77
- sniff() (galaxy.datatypes.sequence.csFasta method), 82
- sniff() (galaxy.datatypes.sequence.Fasta method), 77
- sniff() (galaxy.datatypes.sequence.Fastq method), 78
- sniff() (galaxy.datatypes.sequence.Lav method), 79
- sniff() (galaxy.datatypes.sequence.Maf method), 80
- sniff() (galaxy.datatypes.sequence.RNADotPlotMatrix method), 81
- sniff() (galaxy.datatypes.sequence.SequenceSplitLocations method), 82
- sniff() (galaxy.datatypes.tabular.CSV method), 85
- sniff() (galaxy.datatypes.tabular.Eland method), 86
- sniff() (galaxy.datatypes.tabular.ElandMulti method), 86
- sniff() (galaxy.datatypes.tabular.Pileup method), 86
- sniff() (galaxy.datatypes.tabular.Sam method), 87
- sniff() (galaxy.datatypes.tabular.Vcf method), 90

sniff() (galaxy.datatypes.xml.CisML method), 90
 sniff() (galaxy.datatypes.xml.GenericXml method), 90
 sniff() (galaxy.datatypes.xml.MEMEXml method), 91
 sniff() (galaxy.datatypes.xml.Owl method), 91
 sniff() (galaxy.datatypes.xml.Phyloxml method), 91
 sniffable_binary_formats (galaxy.datatypes.binary.Binary attribute), 46
 sniffers() (galaxy.webapps.galaxy.api.datatypes.DatatypesController method), 9, 274
 SNPMatrix (class in galaxy.datatypes.genetics), 58
 SnpTest (class in galaxy.datatypes.genetics), 58
 sort() (galaxy.web.framework.helpers.grids.BooleanColumns method), 257
 sort() (galaxy.web.framework.helpers.grids.CommunityRatingGrid method), 258
 sort() (galaxy.web.framework.helpers.grids.DateTimeColumn method), 258
 sort() (galaxy.web.framework.helpers.grids.GridColumn method), 260
 sort() (galaxy.web.framework.helpers.grids.IntegerColumn method), 261
 sort() (galaxy.web.framework.helpers.grids.OwnerColumn method), 262
 sort() (galaxy.web.framework.helpers.grids.ReverseSortColumn method), 263
 sort() (galaxy.web.framework.helpers.grids.TextColumn method), 264
 sort() (galaxy.webapps.galaxy.controllers.history.HistoryList method), 322
 sort_block_components_by_block() (in module galaxy.tools.util.maf_utilities), 224
 sort_by_attr() (galaxy.security.GalaxyRBACAgent method), 179
 sort_by_attr() (in module galaxy.web.base.controller), 251
 sort_by_attr() (in module galaxy.webapps.galaxy.controllers.library_common), 327
 SortByColumnFilter (class in galaxy.tools.parameters.dynamic_options), 211
 sorter() (in module galaxy.webapps.reports.controllers.jobs), 343
 source_dataset_chain (galaxy.model.DatasetInstance attribute), 133
 source_library_dataset (galaxy.model.DatasetInstance attribute), 133
 spec (galaxy.datatypes.metadata.MetadataCollection attribute), 71
 specified_date() (galaxy.webapps.reports.controllers.users.Users method), 345
 specified_date_handler() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
 specified_date_handler() (galaxy.webapps.reports.controllers.sample_tracking method), 343
 specified_date_handler() (galaxy.webapps.reports.controllers.workflows.Workflows method), 347
 specified_date_list_grid (galaxy.webapps.reports.controllers.jobs.Jobs attribute), 341
 specified_date_list_grid (galaxy.webapps.reports.controllers.sample_tracking method), 343
 specified_date_list_grid (galaxy.webapps.reports.controllers.workflows.Workflows attribute), 347
 specified_month() (galaxy.webapps.reports.controllers.users.Users method), 345
 specified_month_all() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
 specified_month_in_error() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
 SpecifiedDateListGrid (class in galaxy.webapps.reports.controllers.jobs), 342
 SpecifiedDateListGrid (class in galaxy.webapps.reports.controllers.sample_tracking), 344
 SpecifiedDateListGrid (class in galaxy.webapps.reports.controllers.workflows), 345
 SpecifiedDateListGrid.CreateTimeColumn (class in galaxy.webapps.reports.controllers.jobs), 342
 SpecifiedDateListGrid.CreateTimeColumn (class in galaxy.webapps.reports.controllers.sample_tracking), 344
 SpecifiedDateListGrid.CreateTimeColumn (class in galaxy.webapps.reports.controllers.workflows), 345
 SpecifiedDateListGrid.EmailColumn (class in galaxy.webapps.reports.controllers.jobs), 342
 SpecifiedDateListGrid.EmailColumn (class in galaxy.webapps.reports.controllers.sample_tracking), 344
 SpecifiedDateListGrid.EmailColumn (class in galaxy.webapps.reports.controllers.workflows), 346
 SpecifiedDateListGrid.JobIdColumn (class in galaxy.webapps.reports.controllers.jobs), 342
 SpecifiedDateListGrid.RequestNameColumn (class in galaxy.webapps.reports.controllers.sample_tracking), 344
 SpecifiedDateListGrid.SpecifiedDateColumn (class in galaxy.webapps.reports.controllers.jobs), 342
 SpecifiedDateListGrid.SpecifiedDateColumn (class in galaxy.webapps.reports.controllers.sample_tracking), 344
 SpecifiedDateListGrid.SpecifiedDateColumn (class in galaxy.webapps.reports.controllers.sample_tracking), 344
 SpecifiedDateListGrid.SpecifiedDateColumn (class in galaxy.webapps.reports.controllers.sample_tracking), 344

- galaxy.webapps.reports.controllers.workflows), 346
- SpecifiedDateListGrid.StateColumn (class in galaxy.webapps.reports.controllers.jobs), 342
- SpecifiedDateListGrid.ToolColumn (class in galaxy.webapps.reports.controllers.jobs), 342
- SpecifiedDateListGrid.UserColumn (class in galaxy.webapps.reports.controllers.jobs), 343
- SpecifiedDateListGrid.UserColumn (class in galaxy.webapps.reports.controllers.sample_tracking), 344
- SpecifiedDateListGrid.UserColumn (class in galaxy.webapps.reports.controllers.workflows), 346
- SpecifiedDateListGrid.WorkflowNameColumn (class in galaxy.webapps.reports.controllers.workflows), 346
- SplicedAlignment (class in galaxy.tools.util.maf_utilities), 222
- split() (galaxy.datatypes.data.Text class method), 54
- split() (galaxy.datatypes.sequence.Alignment method), 77
- split() (galaxy.datatypes.sequence.Fasta class method), 78
- split() (galaxy.datatypes.sequence.Fastq class method), 79
- split() (galaxy.datatypes.sequence.Sequence method), 81
- split() (galaxy_utils.sequence.fastq.fastqSplitter method), 355
- split_output_name() (galaxy.tools.ToolOutputCollectionPart static method), 189
- split_sections() (in module pkg_resources), 365
- splitLinebyWhitespaces() (galaxy.visualization.data_providers.phylviz.nextstar.galaxyutils.DatasetCollection attribute), 240
- SQLite (class in galaxy.datatypes.binary), 47
- sqlite_datadictprovider() (galaxy.datatypes.binary.SQLite method), 48
- sqlite_dataprovider() (galaxy.datatypes.binary.SQLite method), 48
- sqlite_datatableprovider() (galaxy.datatypes.binary.SQLite method), 48
- Sra (class in galaxy.datatypes.binary), 48
- src_merge() (in module galaxy.tools.util.maf_utilities), 224
- src_split() (in module galaxy.tools.util.maf_utilities), 224
- stack_trace_string() (in module galaxy.util.debugging), 230
- standard_filters (galaxy.web.framework.helpers.grids.Grid attribute), 260
- standard_filters (galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute), 307
- standard_filters (galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute), 308
- standard_filters (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 310
- standard_filters (galaxy.webapps.galaxy.controllers.admin.UserListGrid attribute), 312
- standard_filters (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAttribute attribute), 316
- standard_filters (galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute), 322
- standard_filters (galaxy.webapps.galaxy.controllers.history.SharedHistoryListGrid attribute), 323
- standard_filters (galaxy.webapps.galaxy.controllers.library.LibraryListGrid attribute), 324
- standard_filters (galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid attribute), 325
- standard_filters (galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGrid attribute), 343
- standard_filters (galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDateListGrid attribute), 345
- standard_filters (galaxy.webapps.reports.controllers.workflows.SpecifiedDateListGrid attribute), 346
- start (galaxy.tools.util.maf_utilities.SplicedAlignment attribute), 222
- start() (galaxy.jobs.handler.JobHandler method), 118
- start() (galaxy.jobs.handler.JobHandlerQueue method), 118
- start() (galaxy.jobs.manager.JobManager method), 119
- start() (galaxy.jobs.manager.NoopHandler method), 119
- start() (galaxy.util.debugging.SimpleProfiler method), 230
- state (galaxy.model.DatasetCollection attribute), 130
- state (galaxy.model.DatasetCollectionInstance attribute), 130
- state (galaxy.model.DatasetInstance attribute), 133
- state (galaxy.model.Request attribute), 144
- state (galaxy.model.Sample attribute), 145
- state_fields (galaxy.workflow.modules.InputDataCollectionModule attribute), 347
- state_fields (galaxy.workflow.modules.InputDataModule attribute), 347
- state_fields (galaxy.workflow.modules.PauseModule attribute), 348
- StateColumn (class in galaxy.web.framework.helpers.grids), 263
- Statement (class in galaxy.datatypes.metadata), 73
- states (galaxy.model.Dataset attribute), 129
- states (galaxy.model.DatasetInstance attribute), 133
- states (galaxy.model.DeferredJob attribute), 133
- states (galaxy.model.Job attribute), 140
- states (galaxy.model.Request attribute), 144
- states (galaxy.model.Task attribute), 147
- states (galaxy.model.TransferJob attribute), 148

states (galaxy.model.WorkflowInvocation attribute), 150
 StaticValueFilter (class in galaxy.tools.parameters.dynamic_options), 211
 status_code (galaxy.exceptions.ActionInputError attribute), 103
 status_code (galaxy.exceptions.AdminRequiredException attribute), 103
 status_code (galaxy.exceptions.AuthenticationFailed attribute), 103
 status_code (galaxy.exceptions.AuthenticationRequired attribute), 103
 status_code (galaxy.exceptions.ConfigDoesNotAllowException attribute), 103
 status_code (galaxy.exceptions.ConfigurationError attribute), 103
 status_code (galaxy.exceptions.Conflict attribute), 103
 status_code (galaxy.exceptions.DeprecatedMethod attribute), 103
 status_code (galaxy.exceptions.DuplicatedIdentifierException attribute), 104
 status_code (galaxy.exceptions.DuplicatedSlugException attribute), 104
 status_code (galaxy.exceptions.InconsistentDatabase attribute), 104
 status_code (galaxy.exceptions.InsufficientPermissionsException attribute), 104
 status_code (galaxy.exceptions.InternalServerError attribute), 104
 status_code (galaxy.exceptions.ItemAccessibilityException attribute), 104
 status_code (galaxy.exceptions.ItemOwnershipException attribute), 104
 status_code (galaxy.exceptions.MalformedId attribute), 104
 status_code (galaxy.exceptions.MessageException attribute), 105
 status_code (galaxy.exceptions.NotImplemented attribute), 105
 status_code (galaxy.exceptions.ObjectAttributeInvalidException attribute), 105
 status_code (galaxy.exceptions.ObjectAttributeMissingException attribute), 105
 status_code (galaxy.exceptions.ObjectNotFound attribute), 105
 status_code (galaxy.exceptions.RequestParameterInvalidException attribute), 105
 status_code (galaxy.exceptions.RequestParameterMissingException attribute), 105
 status_code (galaxy.exceptions.ToolMetaParameterException attribute), 106
 status_code (galaxy.exceptions.UnknownContentsType attribute), 106
 stderr() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 316
 stdout() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 316
 step_invocations_by_step_id() (galaxy.model.WorkflowInvocation method), 150
 step_invocations_for_step_id() (galaxy.model.WorkflowInvocation method), 150
 step_states_by_step_id() (galaxy.model.WorkflowInvocation method), 150
 stop() (galaxy.jobs.handler.DefaultJobDispatcher method), 118
 stop_err() (in module galaxy.datatypes.converters.fastqsolexa_to_fasta_converter), 92
 stop_err() (in module galaxy.datatypes.converters.fastqsolexa_to_qual_converter), 92
 stop_err() (in module galaxy.datatypes.converters.interval_to_bed_converter), 93
 stop_err() (in module galaxy.datatypes.converters.interval_to_bedstrict_converter), 93
 stop_err() (in module galaxy.datatypes.converters.wiggle_to_simple_converter), 96
 stop_job() (galaxy.jobs.runners.BaseJobRunner method), 125
 stop_job() (galaxy.jobs.runners.cli.ShellJobRunner method), 125
 stop_job() (galaxy.jobs.runners.condor.CondorJobRunner method), 126
 stop_job() (galaxy.jobs.runners.drmaa.DRMAAJobRunner method), 126
 stop_job() (galaxy.jobs.runners.local.LocalJobRunner method), 127
 stop_job() (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
 stop_job() (galaxy.jobs.runners.tasks.TaskedJobRunner method), 128
 STOP_SIGNAL (galaxy.jobs.handler.JobHandlerQueue attribute), 118
 STOP_SIGNAL (galaxy.jobs.handler.JobHandlerStopQueue attribute), 118
 stop_jobtemplate() (galaxy.jobs.runners.drmaa.DRMAAJobRunner method), 126
 stored_list_grid (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface attribute), 316
 stored_list_grid (galaxy.webapps.galaxy.controllers.history.HistoryController attribute), 321
 stop_workflow (galaxy.managers.workflows.CreatedWorkflow attribute), 168
 StoredWorkflow (class in galaxy.model), 146
 StoredWorkflowAnnotationAssociation (class in galaxy.model), 146
 StoredWorkflowMenuEntry (class in galaxy.model), 146
 StoredWorkflowRatingAssociation (class in galaxy.model), 146

- galaxy.model), 146
- StoredWorkflowTagAssociation (class in galaxy.model), 146
- StoredWorkflowUserShareAssociation (class in galaxy.model), 146
- stream() (galaxy.util.streamball.StreamBall method), 236
- stream() (galaxy.util.streamball.ZipBall method), 236
- stream_to_file() (in module galaxy.datatypes.sniff), 85
- stream_to_open_named_file() (in module galaxy.datatypes.sniff), 85
- StreamBall (class in galaxy.util.streamball), 236
- string_as_bool() (in module galaxy.eggs), 101
- string_as_bool() (in module galaxy.util), 229
- string_as_bool_or_none() (in module galaxy.util), 229
- string_replace() (galaxy.util.inflection.Base method), 231
- string_standard_ops() (galaxy.managers.base.ModelFilterParser method), 156
- string_to_object() (in module galaxy.util), 229
- StringFunctionFilter (class in galaxy.tools.parameters.output), 215
- stringify_dictionary_keys() (in module galaxy.util), 229
- stripwd() (in module galaxy.model.orm.logging_connection_proxy), 153
- structure() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321
- submit_request() (galaxy.webapps.galaxy.controllers.requests_common.controller.request method), 334
- subscribe() (pkg_resources.WorkingSet method), 361
- SUCCESS (galaxy.web.framework.openid_manager.OpenIDManager attribute), 256
- supported_display_apps (galaxy.datatypes.data.Data attribute), 52
- supported_field_types (galaxy.model.FormDefinition attribute), 134
- supported_field_types (galaxy.model.Sample attribute), 145
- switch_to_history() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321
- SwitchingSelectField (class in galaxy.web.form_builder), 245
- synchronized() (in module galaxy.util), 229
- System (class in galaxy.webapps.reports.controllers.system), 345
- T**
- tableize() (galaxy.util.inflection.Base method), 232
- tableize() (galaxy.util.inflection.Inflector method), 233
- Tabular (class in galaxy.datatypes.tabular), 88
- TabularData (class in galaxy.datatypes.tabular), 88
- TabularToolDataField (class in galaxy.tools.data), 192
- TabularToolDataTable (class in galaxy.tools.data), 192
- Tag (class in galaxy.model), 146
- tag (galaxy.tools.parameters.output.BooleanFilter attribute), 214
- tag (galaxy.tools.parameters.output.ColumnReplaceFilter attribute), 214
- tag (galaxy.tools.parameters.output.ColumnStripFilter attribute), 214
- tag (galaxy.tools.parameters.output.DatatypeIsInstanceToolOutputActionConditionalFilter attribute), 214
- tag (galaxy.tools.parameters.output.FormatToolOutputAction attribute), 214
- tag (galaxy.tools.parameters.output.FromDataTableOutputActionOption attribute), 214
- tag (galaxy.tools.parameters.output.FromFileToolOutputActionOption attribute), 214
- tag (galaxy.tools.parameters.output.FromParamToolOutputActionOption attribute), 215
- tag (galaxy.tools.parameters.output.InsertColumnToolOutputActionOption attribute), 215
- tag (galaxy.tools.parameters.output.MetadataToolOutputAction attribute), 215
- tag (galaxy.tools.parameters.output.MetadataValueFilter attribute), 215
- tag (galaxy.tools.parameters.output.MultipleSplitterFilter attribute), 215
- tag (galaxy.tools.parameters.output.NullToolOutputActionOption attribute), 215
- tag (galaxy.tools.parameters.output.ParamValueToolOutputActionOptionFilter attribute), 215
- tag (galaxy.tools.parameters.output.StringFunctionFilter attribute), 215
- tag (galaxy.tools.parameters.output.ToolOutputAction attribute), 215
- tag (galaxy.tools.parameters.output.ToolOutputActionConditional attribute), 216
- tag (galaxy.tools.parameters.output.ToolOutputActionConditionalWhen attribute), 216
- tag (galaxy.tools.parameters.output.ToolOutputActionGroup attribute), 216
- tag (galaxy.tools.parameters.output.ToolOutputActionOption attribute), 216
- tag (galaxy.tools.parameters.output.ToolOutputActionOptionFilter attribute), 216
- tag (galaxy.tools.parameters.output.ValueToolOutputActionConditionalWhen attribute), 217
- tag_assoc (galaxy.managers.hdas.HDAManager attribute), 163
- tag_assoc (galaxy.managers.histories.HistoryManager attribute), 165
- tag_autocomplete_data() (galaxy.webapps.galaxy.controllers.tag.TagsController method), 337
- TagDatasetAction (class in galaxy.jobs.actions.post), 122
- tagged_item_class (galaxy.webapps.galaxy.api.item_tags.HistoryContentTagsController attribute), 20, 285
- tagged_item_class (galaxy.webapps.galaxy.api.item_tags.HistoryTagsController attribute), 20, 285
- tagged_item_class (galaxy.webapps.galaxy.api.item_tags.WorkflowTagsController attribute), 20, 285

attribute), 20, 285
 tagged_item_id (galaxy.webapps.galaxy.api.annotations.HistoryListGrid attribute), 8, 273
 tagged_item_id (galaxy.webapps.galaxy.api.annotations.HistoryListGrid attribute), 8, 273
 tagged_item_id (galaxy.webapps.galaxy.api.annotations.WorkflowListGrid attribute), 8, 273
 tagged_item_id (galaxy.webapps.galaxy.api.item_tags.HistoryListGrid attribute), 20, 285
 tagged_item_id (galaxy.webapps.galaxy.api.item_tags.HistoryListGrid attribute), 20, 285
 tagged_item_id (galaxy.webapps.galaxy.api.item_tags.WorkflowListGrid attribute), 20, 285
 TagManager (class in galaxy.managers.tags), 167
 TagsController (class in galaxy.webapps.galaxy.controllers.tag), 337
 Task (class in galaxy.model), 146
 TaskedJobRunner (class in galaxy.jobs.runners.tasks), 127
 TaskMetricNumeric (class in galaxy.model), 148
 TaskMetricText (class in galaxy.model), 148
 TaskWrapper (class in galaxy.jobs), 117
 Taxonomy (class in galaxy.datatypes.tabular), 89
 TempFile (class in log_tempfile), 357
 TempFileHandler (class in galaxy.tools.util.maf_utilities), 223
 Template (class in galaxy.external_services.actions), 107
 template (galaxy.web.framework.helpers.grid.Grid attribute), 260
 template (galaxy.webapps.galaxy.controllers.admin.GroupListGrid attribute), 307
 template (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid attribute), 308
 template (galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute), 310
 template (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 310
 template (galaxy.webapps.galaxy.controllers.admin.UserListGrid attribute), 312
 template (galaxy.webapps.galaxy.controllers.dataset.HistoryListGrid attribute), 316
 template (galaxy.webapps.galaxy.controllers.external_service.FileTransferGrid attribute), 318
 template (galaxy.webapps.galaxy.controllers.forms.FormsGrid attribute), 319
 template (galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute), 322
 template (galaxy.webapps.galaxy.controllers.library.LibraryListGrid attribute), 324
 template (galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid attribute), 325
 template (galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid attribute), 328
 template (galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid attribute), 332
 template (galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid attribute), 333
 template (galaxy.webapps.galaxy.controllers.requests_common.RequestsGrid attribute), 335
 template (galaxy.webapps.galaxy.controllers.user.UserOpenIDGrid attribute), 340
 templates (in module galaxy.web.framework.helpers), 257
 templates_dict() (galaxy.model.LibraryDatasetDatasetAssociation method), 142
 templates_json() (galaxy.model.LibraryDatasetDatasetAssociation method), 142
 terminal_states (galaxy.model.TransferJob attribute), 148
 test() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
 test_data() (galaxy.tools.test.ToolTestBuilder method), 190
 test_data_iter() (in module galaxy.tools.test), 190
 tests (galaxy.tools.Tool attribute), 187
 Text (class in galaxy.datatypes.data), 53
 text_data() (galaxy.managers.hdas.HDAManager method), 163
 TextArea (class in galaxy.web.form_builder), 245
 TextColumn (class in galaxy.web.framework.helpers.grid.Grid), 264
 TextField (class in galaxy.web.form_builder), 245
 TextToolParameter (class in galaxy.tools.parameters.basic), 207
 time_ago() (in module galaxy.web.framework.helpers), 257
 timenow() (in module galaxy.datatypes.converters.lped_to_fped_converter), 94
 timenow() (in module galaxy.datatypes.converters.lped_to_pbed_converter), 94
 timenow() (in module galaxy.datatypes.converters.pbed_ldreduced_converter), 95
 time_type (in module

galaxy.datatypes.converters.pbmed_to_lped_converter (galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDateListGrid attribute), 345
 title (galaxy.web.framework.helpers.grids.Grid attribute), 260
 title (galaxy.webapps.galaxy.controllers.admin.GroupListGrid attribute), 307
 title (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid attribute), 308
 title (galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute), 310
 title (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 310
 title (galaxy.webapps.galaxy.controllers.admin.UserListGrid attribute), 312
 title (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAssociationGrid attribute), 316
 title (galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGrid attribute), 318
 title (galaxy.webapps.galaxy.controllers.forms.FormsGrid attribute), 319
 title (galaxy.webapps.galaxy.controllers.history.HistoryAllPublicationsGrid attribute), 320
 title (galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute), 322
 title (galaxy.webapps.galaxy.controllers.history.SharedHistoryListGrid attribute), 323
 title (galaxy.webapps.galaxy.controllers.library.LibraryListGrid attribute), 324
 title (galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid attribute), 325
 title (galaxy.webapps.galaxy.controllers.page.HistoryDatasetAssociationSelectionGrid attribute), 327
 title (galaxy.webapps.galaxy.controllers.page.HistorySelectionGrid attribute), 327
 title (galaxy.webapps.galaxy.controllers.page.PageAllPublicationsGrid attribute), 328
 title (galaxy.webapps.galaxy.controllers.page.PageListGrid attribute), 330
 title (galaxy.webapps.galaxy.controllers.page.PageSelectionGrid attribute), 330
 title (galaxy.webapps.galaxy.controllers.page.VisualizationSelectionGrid attribute), 330
 title (galaxy.webapps.galaxy.controllers.page.WorkflowSelectionGrid attribute), 330
 title (galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid attribute), 332
 title (galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid attribute), 333
 title (galaxy.webapps.galaxy.controllers.requests_common.RequestsGrid attribute), 335
 title (galaxy.webapps.galaxy.controllers.user.UserOpenIDGrid attribute), 340
 title (galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGrid attribute), 343
 title (galaxy.webapps.reports.controllers.workflows.SpecifiedDateListGrid attribute), 347
 title_by_index() (galaxy.tools.parameters.grouping.UploadDataset method), 213
 title_plural (galaxy.tools.parameters.grouping.Repeat attribute), 212
 title_plural (galaxy.tools.parameters.grouping.Section attribute), 212
 title_plural (galaxy.tools.parameters.grouping.UploadDataset attribute), 213
 titleize() (galaxy.util.inflection.Base method), 232
 titleize() (galaxy.util.inflection.Inflector method), 233
 tmp_association_galaxy_datatypes.metadata.MetadataTempFile attribute), 73
 transform_color_space() (galaxy_utils.sequence.transform.ColorSpaceConverter method), 356
 to_bibtex() (galaxy.managers.citations.BibtexCitation method), 158
 to_html() (galaxy.managers.citations.DoiCitation method), 159
 to_color_space() (galaxy_utils.sequence.transform.ColorSpaceConverter method), 356
 to_dict() (galaxy.managers.citations.BaseCitation method), 158
 to_dict() (galaxy.model.History method), 135
 to_dict() (galaxy.model.HistoryDatasetAssociation method), 136
 to_dict() (galaxy.model.HistoryDatasetCollectionAssociation method), 136
 to_dict() (galaxy.model.item_attrs.Dictifiable method), 152
 to_dict() (galaxy.model.Job method), 140
 to_dict() (galaxy.model.Library method), 141
 to_dict() (galaxy.model.LibraryDataset method), 141
 to_dict() (galaxy.model.LibraryDatasetCollectionAssociation method), 141
 to_dict() (galaxy.model.LibraryDatasetDatasetAssociation method), 142
 to_dict() (galaxy.model.LibraryFolder method), 143
 to_dict() (galaxy.model.Page method), 143
 to_dict() (galaxy.model.PageRevision method), 143
 to_dict() (galaxy.model.StoredWorkflow method), 146
 to_dict() (galaxy.model.Workflow method), 150
 to_dict() (galaxy.model.WorkflowInvocation method), 150
 to_dict() (galaxy.model.WorkflowInvocationStep method), 150
 to_dict() (galaxy.model.WorkflowRequest method), 151
 to_dict() (galaxy.tools.data.TabularToolDataField method), 192
 to_dict() (galaxy.tools.data.TabularToolDataTable method), 193

[to_dict\(\)](#) (galaxy.tools.parameters.basic.BaseURLToolParameter method), 197
[to_dict\(\)](#) (galaxy.tools.parameters.basic.BooleanToolParameter method), 197
[to_dict\(\)](#) (galaxy.tools.parameters.basic.ColumnListParameter method), 198
[to_dict\(\)](#) (galaxy.tools.parameters.basic.DataCollectionToolParameter method), 199
[to_dict\(\)](#) (galaxy.tools.parameters.basic.DataToolParameter method), 199
[to_dict\(\)](#) (galaxy.tools.parameters.basic.DrillDownSelectToolParameter method), 202
[to_dict\(\)](#) (galaxy.tools.parameters.basic.FTPFileToolParameter method), 202
[to_dict\(\)](#) (galaxy.tools.parameters.basic.GenomeBuildParameter method), 204
[to_dict\(\)](#) (galaxy.tools.parameters.basic.LibraryDatasetToolParameter method), 205
[to_dict\(\)](#) (galaxy.tools.parameters.basic.SelectToolParameter method), 207
[to_dict\(\)](#) (galaxy.tools.parameters.basic.TextToolParameter method), 207
[to_dict\(\)](#) (galaxy.tools.parameters.basic.ToolParameter method), 208
[to_dict\(\)](#) (galaxy.tools.parameters.grouping.Conditional method), 211
[to_dict\(\)](#) (galaxy.tools.parameters.grouping.ConditionalWhen method), 211
[to_dict\(\)](#) (galaxy.tools.parameters.grouping.Group method), 212
[to_dict\(\)](#) (galaxy.tools.parameters.grouping.Repeat method), 212
[to_dict\(\)](#) (galaxy.tools.parameters.grouping.Section method), 212
[to_dict\(\)](#) (galaxy.tools.Tool method), 187
[to_dict\(\)](#) (galaxy.tools.ToolOutput method), 188
[to_dict\(\)](#) (galaxy.visualization.genomes.Genome method), 237
[to_dict\(\)](#) (galaxy.web.form_builder.SelectField method), 245
[to_DNA\(\)](#) (in module galaxy_utils.sequence.transform), 357
[to_external_value\(\)](#) (galaxy.datatypes.metadata.FileParameter method), 70
[to_external_value\(\)](#) (galaxy.datatypes.metadata.MetadataParameter method), 72
[to_filename\(\)](#) (in module pkg_resources), 365
[to_history_dataset_association\(\)](#) (galaxy.model.LibraryDatasetDatasetAssociation method), 142
[to_html_value\(\)](#) (galaxy.tools.parameters.basic.BooleanToolParameter method), 198
[to_html_value\(\)](#) (galaxy.tools.parameters.basic.SelectToolParameter method), 207
[to_html_value\(\)](#) (galaxy.tools.parameters.basic.TextToolParameter method), 207
[to_html_value\(\)](#) (galaxy.tools.parameters.basic.ToolParameter method), 208
[to_JSON\(\)](#) (galaxy.datatypes.metadata.MetadataTempFile method), 73
[to_JSON_dict\(\)](#) (galaxy.datatypes.metadata.MetadataCollection method), 71
[to_library_dataset_dataset_association\(\)](#) (galaxy.model.HistoryDatasetAssociation method), 136
[to_param_dict_string\(\)](#) (galaxy.tools.parameters.basic.BooleanToolParameter method), 198
[to_param_dict_string\(\)](#) (galaxy.tools.parameters.basic.DataToolParameter method), 199
[to_param_dict_string\(\)](#) (galaxy.tools.parameters.basic.DrillDownSelectToolParameter method), 202
[to_param_dict_string\(\)](#) (galaxy.tools.parameters.basic.FTPFileToolParameter method), 202
[to_param_dict_string\(\)](#) (galaxy.tools.parameters.basic.LibraryDatasetToolParameter method), 205
[to_param_dict_string\(\)](#) (galaxy.tools.parameters.basic.SelectToolParameter method), 207
[to_param_dict_string\(\)](#) (galaxy.tools.parameters.basic.ToolParameter method), 208
[to_python\(\)](#) (galaxy.tools.parameters.basic.BooleanToolParameter method), 198
[to_python\(\)](#) (galaxy.tools.parameters.basic.DataCollectionToolParameter method), 199
[to_python\(\)](#) (galaxy.tools.parameters.basic.DataToolParameter method), 199
[to_python\(\)](#) (galaxy.tools.parameters.basic.FileToolParameter method), 202
[to_python\(\)](#) (galaxy.tools.parameters.basic.FloatToolParameter method), 203
[to_python\(\)](#) (galaxy.tools.parameters.basic.FTPFileToolParameter method), 202
[to_python\(\)](#) (galaxy.tools.parameters.basic.IntegerToolParameter method), 205
[to_python\(\)](#) (galaxy.tools.parameters.basic.LibraryDatasetToolParameter method), 205
[to_python\(\)](#) (galaxy.tools.parameters.basic.ToolParameter method), 208
[to_RNA\(\)](#) (in module galaxy_utils.sequence.transform), 357
[to_safe_string\(\)](#) (galaxy.datatypes.metadata.DictParameter method), 70
[to_safe_string\(\)](#) (galaxy.datatypes.metadata.FileParameter method), 70
[to_safe_string\(\)](#) (galaxy.datatypes.metadata.MetadataParameter method), 72
[to_string\(\)](#) (galaxy.datatypes.metadata.ColumnTypesParameter method), 70

to_string() (galaxy.datatypes.metadata.DictParameter method), 70
 to_string() (galaxy.datatypes.metadata.FileParameter method), 70
 to_string() (galaxy.datatypes.metadata.ListParameter method), 71
 to_string() (galaxy.datatypes.metadata.MetadataParameter method), 72
 to_string() (galaxy.datatypes.metadata.PythonObjectParameter method), 73
 to_string() (galaxy.datatypes.metadata.SelectParameter method), 73
 to_string() (galaxy.tools.parameters.basic.DataCollectionToolParameter method), 199
 to_string() (galaxy.tools.parameters.basic.DataToolParameter method), 199
 to_string() (galaxy.tools.parameters.basic.FileToolParameter method), 202
 to_string() (galaxy.tools.parameters.basic.FTPFileToolParameter method), 202
 to_string() (galaxy.tools.parameters.basic.LibraryDatasetToolParameter method), 205
 to_string() (galaxy.tools.parameters.basic.TextToolParameter method), 207
 to_string() (galaxy.tools.parameters.basic.ToolParameter method), 208
 to_unicode() (in module galaxy.web.framework.helpers), 257
 to_xml_file() (galaxy.datatypes.registry.Registry method), 76
 to_xml_file() (galaxy.tools.data.ToolDataTableManager method), 194
 toJson() (galaxy.visualization.data_providers.phylviz.baseparser.BaseParser method), 239
 toJson() (galaxy.visualization.data_providers.phylviz.baseparser.BaseParser method), 239
 Tool (class in galaxy.tools), 184
 tool (galaxy.tools.parameters.output.ToolOutputAction attribute), 215
 tool (galaxy.tools.parameters.output.ToolOutputActionConditional attribute), 216
 tool (galaxy.tools.parameters.output.ToolOutputActionGroup attribute), 216
 tool (galaxy.tools.parameters.output.ToolOutputActionOptional attribute), 216
 tool (galaxy.tools.parameters.output.ToolOutputActionOptional attribute), 216
 tool_class (in module galaxy.tools), 189
 tool_dependency_grid (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed attribute), 314
 tool_dependency_status_updates() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 314
 tool_directory() (galaxy.jobs.ComputeEnvironment method), 112
 tool_directory() (galaxy.jobs.SharedComputeEnvironment method), 116
 tool_errors() (galaxy.webapps.galaxy.controllers.admin.AdminGalaxy method), 306
 tool_fail() (in module galaxy.tools.util.maf_utilities), 224
 tool_help() (galaxy.webapps.galaxy.controllers.root.RootController method), 337
 tool_lineages() (galaxy.webapps.galaxy.api.configuration.ConfigurationController method), 9, 274
 tool_per_month() (galaxy.webapps.reports.controllers.jobs.Jobs method), 341
 tool_search() (galaxy.webapps.galaxy.controllers.root.RootController method), 337
 tool_shed_repository (galaxy.tools.Tool attribute), 187
 tool_type (galaxy.tools.AsyncDataSourceTool attribute), 182
 tool_type (galaxy.tools.DataDestinationTool attribute), 182
 tool_type (galaxy.tools.DataManagerTool attribute), 182
 tool_type (galaxy.tools.DataSourceTool attribute), 183
 tool_type (galaxy.tools.ExportHistoryTool attribute), 183
 tool_type (galaxy.tools.GenomeIndexTool attribute), 183
 tool_type (galaxy.tools.ImportHistoryTool attribute), 183
 tool_type (galaxy.tools.OutputParameterJSONTool attribute), 183
 tool_type (galaxy.tools.SetMetadataTool attribute), 184
 tool_type (galaxy.tools.Tool attribute), 187
 tool_version (galaxy.tools.Tool attribute), 187
 tool_version_list_grid (galaxy.web.base.controllers.admin.Admin attribute), 252
 tool_version_list_grid (galaxy.webapps.galaxy.controllers.admin.AdminGalaxy attribute), 306
 tool_versions (galaxy.tools.Tool attribute), 187
 tool_versions() (galaxy.web.base.controllers.admin.Admin attribute), 252
 ToolAction (class in galaxy.tools.actions), 190
 ToolBox (class in galaxy.tools), 188
 toolbox_filters() (galaxy.webapps.galaxy.controllers.user.User method), 340
 ToolBoxSearch (class in galaxy.tools.search), 222
 ToolData (class in galaxy.webapps.galaxy.api.tool_data), 34, 299
 ToolDataTable (class in galaxy.tools.data), 193
 ToolDataTableManager (class in galaxy.tools.data), 194
 ToolErrorLog (class in galaxy.tools), 188
 ToolInputTranslator (class in galaxy.tools.parameters.input_translation), 314
 ToolMetaParameterException, 106
 ToolModule (class in galaxy.workflow.modules), 349
 ToolNotFound (class in galaxy.tools), 188
 ToolOutput (class in galaxy.tools), 188
 ToolOutputAction (class in galaxy.tools), 188

- galaxy.tools.parameters.output), 215
- ToolOutputActionConditional (class in galaxy.tools.parameters.output), 216
- ToolOutputActionConditionalWhen (class in galaxy.tools.parameters.output), 216
- ToolOutputActionGroup (class in galaxy.tools.parameters.output), 216
- ToolOutputActionOption (class in galaxy.tools.parameters.output), 216
- ToolOutputActionOptionFilter (class in galaxy.tools.parameters.output), 216
- ToolOutputBase (class in galaxy.tools), 188
- ToolOutputCollection (class in galaxy.tools), 188
- ToolOutputCollectionPart (class in galaxy.tools), 189
- ToolOutputCollectionStructure (class in galaxy.tools), 189
- ToolParameter (class in galaxy.tools.parameters.basic), 207
- ToolParameterSanitizer (class in galaxy.tools.parameters.sanitize), 217
- ToolRunner (class in galaxy.webapps.galaxy.controllers.tool_runner), 337
- tools_by_id (galaxy.tools.ToolBox attribute), 188
- ToolShedRepositoriesController (class in galaxy.webapps.galaxy.api.tool_shed_repositories), 35, 299
- ToolTagAssociation (class in galaxy.model), 148
- ToolTestBuilder (class in galaxy.tools.test), 190
- ToolVersionListGrid (class in galaxy.webapps.galaxy.controllers.admin), 310
- ToolVersionListGrid.ToolIdColumn (class in galaxy.webapps.galaxy.controllers.admin), 310
- ToolVersionListGrid.ToolVersionsColumn (class in galaxy.webapps.galaxy.controllers.admin), 310
- topsort() (in module galaxy.util.topsort), 236
- topsort_levels() (in module galaxy.util.topsort), 236
- total_disk_usage (galaxy.model.GalaxySession attribute), 134
- total_disk_usage (galaxy.model.User attribute), 148
- trace() (galaxy.web.framework.base.WebApplication method), 256
- TraceLoggerProxy (class in galaxy.model.orm.logging_connection_proxy), 153
- track_type (galaxy.datatypes.binary.Bam attribute), 45
- track_type (galaxy.datatypes.binary.BigWig attribute), 46
- track_type (galaxy.datatypes.data.Data attribute), 52
- track_type (galaxy.datatypes.interval.Bed attribute), 64
- track_type (galaxy.datatypes.interval.BedGraph attribute), 64
- track_type (galaxy.datatypes.interval.ChromatinInteraction attribute), 65
- track_type (galaxy.datatypes.interval.Gff attribute), 66
- in track_type (galaxy.datatypes.interval.Gff3 attribute), 67
- track_type (galaxy.datatypes.interval.Gtf attribute), 68
- in track_type (galaxy.datatypes.interval.Interval attribute), 69
- in track_type (galaxy.datatypes.interval.Wiggle attribute), 70
- in track_type (galaxy.datatypes.tabular.Sam attribute), 88
- track_type (galaxy.datatypes.tabular.Vcf attribute), 90
- in TracksterConfig (class in galaxy.tools), 189
- transfer_error_dataset_files (galaxy.model.Sample attribute), 146
- transfer_part() (in module galaxy.objectstore.s3_multipart_upload), 173
- transfer_status (galaxy.model.SampleDataset attribute), 146
- transfer_status() (galaxy.webapps.galaxy.controllers.dataset.DatasetInterface method), 316
- TransferJob (class in galaxy.model), 148
- TransferManager (class in galaxy.jobs.transfer_manager), 119
- transferred_dataset_files (galaxy.model.Sample attribute), 146
- transferring_dataset_files (galaxy.model.Sample attribute), 146
- transform_publicname() (in module galaxy.security.validate_user_input), 181
- in transform_scores_to_valid_range() (galaxy_utils.sequence.fastq.fastqSequencingRead class method), 355
- transform_scores_to_valid_range_ascii() (galaxy_utils.sequence.fastq.fastqSequencingRead class method), 355
- translate() (galaxy.tools.parameters.input_translation.ToolInputTranslator method), 214
- TransLogger (class in galaxy.web.framework.middleware.translogger), 265
- throw (galaxy.web.form_builder.FTPFileField attribute), 243
- truncate() (in module galaxy.web.framework.helpers), 257
- TwoBit (class in galaxy.datatypes.binary), 48
- type (galaxy.datatypes.display_applications.parameters.DisplayApplication attribute), 97
- type (galaxy.datatypes.display_applications.parameters.DisplayApplication attribute), 97
- type (galaxy.datatypes.display_applications.parameters.DisplayApplication attribute), 97
- type (galaxy.external_services.actions.ExternalServiceAction attribute), 106
- type (galaxy.external_services.actions.ExternalServiceTemplateAction attribute), 106

- type (galaxy.external_services.actions.ExternalServiceWebAPIAttribute attribute), 107
- type (galaxy.external_services.actions.ExternalServiceWebAPIAttribute attribute), 107
- type (galaxy.external_services.parameters.ExternalServiceParameters attribute), 107
- type (galaxy.external_services.parameters.ExternalServiceParameters attribute), 107
- type (galaxy.external_services.result_handlers.basic.ExternalServiceActionQueryGridBasedHandlerModule attribute), 109
- type (galaxy.external_services.result_handlers.basic.ExternalServiceActionJSONResultHandlerModule attribute), 110
- type (galaxy.external_services.result_handlers.basic.ExternalServiceActionJSONResultHandlerModule attribute), 110
- type (galaxy.external_services.result_handlers.basic.ExternalServiceActionQueryGridBasedHandlerModule attribute), 110
- type (galaxy.external_services.service.BooleanExternalServiceActionsGroupWhen attribute), 108
- type (galaxy.external_services.service.ExternalServiceActionsGroupWhen attribute), 108
- type (galaxy.external_services.service.ExternalServiceActionsGroupWhen attribute), 108
- type (galaxy.external_services.service.ItemIsInstanceExternalServiceActionsGroupWhen attribute), 109
- type (galaxy.external_services.service.ValueExternalServiceActionsGroupWhen attribute), 109
- type (galaxy.forms.forms.FormDefinitionAddressFieldFactory attribute), 110
- type (galaxy.forms.forms.FormDefinitionFieldFactory attribute), 111
- type (galaxy.forms.forms.FormDefinitionHistoryFieldFactory attribute), 111
- type (galaxy.forms.forms.FormDefinitionPasswordFieldFactory attribute), 111
- type (galaxy.forms.forms.FormDefinitionSelectFieldFactory attribute), 111
- type (galaxy.forms.forms.FormDefinitionTextFieldFactory attribute), 111
- type (galaxy.forms.forms.FormDefinitionWorkflowFieldFactory attribute), 112
- type (galaxy.forms.forms.FormDefinitionWorkflowMappingFieldFactory attribute), 112
- type (galaxy.sample_tracking.data_transfer.DataTransferFactory attribute), 174
- type (galaxy.sample_tracking.data_transfer.FtpDataTransferFactory attribute), 174
- type (galaxy.sample_tracking.data_transfer.HttpDataTransferFactory attribute), 174
- type (galaxy.sample_tracking.data_transfer.ScpDataTransferFactory attribute), 174
- type (galaxy.tools.parameters.grouping.Conditional attribute), 211
- type (galaxy.tools.parameters.grouping.Repeat attribute), 212
- type (galaxy.tools.parameters.grouping.Section attribute), 212
- type (galaxy.tools.parameters.grouping.UploadDataset attribute), 213
- type (galaxy.workflow.modules.InputDataCollectionModule attribute), 347
- type (galaxy.workflow.modules.InputDataModule attribute), 348
- type (galaxy.workflow.modules.InputDataModule attribute), 348
- type (galaxy.workflow.modules.InputDataModule attribute), 350
- type (galaxy.workflow.modules.InputDataModule attribute), 350
- type (galaxy.workflow.modules.InputDataModule attribute), 158
- type (galaxy.workflow.modules.InputDataModule attribute), 193
- type (galaxy.workflow.modules.InputDataModule attribute), 133
- type (galaxy.workflow.modules.InputDataModule attribute), 134
- types (galaxy.model.Role attribute), 145
- type (galaxy.model.WorkflowRequestInputParameter attribute), 151
- type (galaxy.model.WorkflowRequestInputParameter attribute), 151
- type (galaxy.model.WorkflowRequestInputParameter attribute), 148
- ucsc_links() (galaxy.datatypes.genetics.GenomeGraphs method), 55
- ucsc_links() (galaxy.datatypes.interval.CustomTrack method), 65
- ucsc_links() (galaxy.datatypes.interval.Gff method), 66
- ucsc_links() (galaxy.datatypes.interval.Interval method), 69
- ucsc_links() (galaxy.datatypes.interval.Wiggle method), 70
- UCSCLimitException, 189
- UCSCOutWrapper (class in galaxy.tools.exception_handling), 189
- UCSCProxy (class in galaxy.webapps.galaxy.controllers.ucsc_proxy), 338
- umask_fix_perms() (in module galaxy.util), 229
- unaccent() (galaxy.util.inflection.Base method), 232
- unaccent() (galaxy.util.inflection.Inflector method), 233
- undeletable() (galaxy.model.DatasetInstance method), 133
- undelete() (galaxy.webapps.galaxy.api.annotations.BaseAnnotationsController method), 8, 273
- undelete() (galaxy.webapps.galaxy.api.extended_metadata.BaseExtendedMetadataController method), 10, 275
- undelete() (galaxy.webapps.galaxy.api.histories.HistoriesController method), 17, 281
- undelete() (galaxy.webapps.galaxy.api.quotas.QuotaAPIController method), 33, 297
- undelete() (galaxy.webapps.galaxy.api.users.UserAPIController method), 38, 302

update() (galaxy.webapps.galaxy.api.folder_contents.FolderContentsController method), 11, 276
 update() (galaxy.webapps.galaxy.api.folders.FoldersController method), 13, 278
 update() (galaxy.webapps.galaxy.api.group_roles.GroupRolesAPIController method), 14, 278
 update() (galaxy.webapps.galaxy.api.group_users.GroupUsersAPIController method), 14, 279
 update() (galaxy.webapps.galaxy.api.groups.GroupAPIController method), 14, 279
 update() (galaxy.webapps.galaxy.api.histories.HistoriesController method), 17, 282
 update() (galaxy.webapps.galaxy.api.history_contents.HistoryContentsController method), 19, 284
 update() (galaxy.webapps.galaxy.api.item_tags.BaseItemTagsController method), 20, 284
 update() (galaxy.webapps.galaxy.api.libraries.LibrariesController method), 28, 292
 update() (galaxy.webapps.galaxy.api.library_contents.LibraryContentsController method), 30, 294
 update() (galaxy.webapps.galaxy.api.quotas.QuotaAPIController method), 33, 297
 update() (galaxy.webapps.galaxy.api.requests.RequestsAPIController method), 34, 298
 update() (galaxy.webapps.galaxy.api.samples.SamplesAPIController method), 34, 298
 update() (galaxy.webapps.galaxy.api.users.UserAPIController method), 38, 302
 update() (galaxy.webapps.galaxy.api.visualizations.VisualizationsController method), 39, 303
 update() (galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController method), 41, 305
 update_external_service_form_definition()
 (galaxy.webapps.galaxy.controllers.external_services.ExternalServiceController method), 317
 update_from_file() (galaxy.objectstore.DiskObjectStore method), 170
 update_from_file() (galaxy.objectstore.NestedObjectStore method), 170
 update_from_file() (galaxy.objectstore.ObjectStore method), 172
 update_invocation_step()
 (galaxy.managers.workflows.WorkflowsManager method), 169
 update_invocation_step()
 (galaxy.webapps.galaxy.api.workflows.WorkflowsAPIController method), 41, 305
 update_permissions() (galaxy.webapps.galaxy.api.lda_datasets.LdaDatasetsController method), 25, 289
 update_request_state() (galaxy.webapps.galaxy.controllers.requests.RequestsController method), 334
 update_runtime_state() (galaxy.workflow.modules.SimpleWorkflowModule method), 349
 update_sample_dataset_status()
 (galaxy.webapps.galaxy.controllers.requests_admin.RequestsAdminController method), 334
 (galaxy.webapps.galaxy.controllers.requests_common.RequestsCommonController method), 334
 (galaxy.tools.Tool method), 187
 (galaxy.workflow.modules.SimpleWorkflowModule method), 349
 (galaxy.workflow.modules.ToolModule method), 350
 (galaxy.workflow.modules.WorkflowModule method), 351
 update_to_changeset_revision()
 (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshedController method), 314
 update_shed_status_for_installed_repository()
 (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshedController method), 314
 update_type_values (galaxy.webapps.galaxy.api.samples.SamplesAPIController attribute), 34, 298
 update_types (galaxy.webapps.galaxy.api.samples.SamplesAPIController attribute), 34, 298
 update_workflow_from_dict()
 (galaxy.managers.workflows.WorkflowContentsManager method), 168
 upload_async_create() (galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner method), 338
 upload_async_message()
 (galaxy.webapps.galaxy.controllers.tool_runner.ToolRunner method), 338
 upload_dataset()
 (galaxy.webapps.galaxy.controllers.library_common.LibraryCommonController method), 326
 upload_library_dataset()
 (galaxy.webapps.galaxy.controllers.library_common.LibraryCommonController method), 326
 upload_library_dataset()
 (galaxy.model.LibraryDataset attribute), 141
 UploadDataset (class in galaxy.tools.parameters.grouping), 212
 UploadToolAction (class in galaxy.tools.actions.upload), 191
 url (galaxy.datatypes.display_applications.parameters.DisplayParameterValue attribute), 98
 url_for() (galaxy.managers.base.ModelSerializer static method), 157
 url_to_destination() (galaxy.jobs.handler.DefaultJobDispatcher method), 118
 url_to_destination() (galaxy.jobs.runners.BaseJobRunner method), 125
 url_to_destination() (galaxy.jobs.runners.cli.ShellJobRunner method), 125
 url_to_destination() (galaxy.jobs.runners.drmaa.DRMAAJobRunner method), 126
 url_to_destination() (galaxy.jobs.runners.lwr.LwrJobRunner method), 127
 url_to_file() (in module

- galaxy.tools.imp_exp.unpack_tar_gz_archive), 196
- urlize() (galaxy.util.inflection.Base method), 232
- urlize() (galaxy.util.inflection.Inflector method), 233
- URLRetriever (class in galaxy.eggs), 101
- use_async (galaxy.web.framework.helpers.grids.Grid attribute), 260
- use_async (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetListGrid attribute), 316
- use_async (galaxy.webapps.galaxy.controllers.history.HistoryAllPublishedGrid attribute), 320
- use_async (galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute), 322
- use_async (galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid attribute), 328
- use_async (galaxy.webapps.galaxy.controllers.page.PageAllPublishedGrid attribute), 328
- use_async (galaxy.webapps.galaxy.controllers.page.PageListGrid attribute), 330
- use_async (galaxy.webapps.galaxy.controllers.user.UserOpenIDGrid attribute), 340
- use_async (galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGrid attribute), 343
- use_async (galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDateListGrid attribute), 345
- use_async (galaxy.webapps.reports.controllers.workflows.SpecifiedDateListGrid attribute), 347
- use_hide_message (galaxy.web.framework.helpers.grids.Grid attribute), 260
- use_paging (galaxy.web.framework.helpers.grids.Grid attribute), 260
- use_paging (galaxy.webapps.galaxy.controllers.admin.GroupListGrid attribute), 307
- use_paging (galaxy.webapps.galaxy.controllers.admin.QuotaListGrid attribute), 308
- use_paging (galaxy.webapps.galaxy.controllers.admin.RoleListGrid attribute), 310
- use_paging (galaxy.webapps.galaxy.controllers.admin.ToolVersionListGrid attribute), 310
- use_paging (galaxy.webapps.galaxy.controllers.admin.UserListGrid attribute), 312
- use_paging (galaxy.webapps.galaxy.controllers.dataset.HistoryDatasetAssociationListGrid attribute), 317
- use_paging (galaxy.webapps.galaxy.controllers.external_service.ExternalServiceGrid attribute), 318
- use_paging (galaxy.webapps.galaxy.controllers.forms.FormsGrid attribute), 319
- use_paging (galaxy.webapps.galaxy.controllers.history.HistoryAllPublishedGrid attribute), 320
- use_paging (galaxy.webapps.galaxy.controllers.history.HistoryListGrid method), 343
- use_paging (galaxy.webapps.galaxy.controllers.history.HistoryListGrid attribute), 322
- use_paging (galaxy.webapps.galaxy.controllers.library.LibraryListGrid method), 347
- use_paging (galaxy.webapps.galaxy.controllers.library.LibraryListGrid attribute), 324
- use_paging (galaxy.webapps.galaxy.controllers.library_admin.LibraryListGrid attribute), 325
- use_paging (galaxy.webapps.galaxy.controllers.page.ItemSelectionGrid attribute), 328
- use_paging (galaxy.webapps.galaxy.controllers.request_type.RequestTypeGrid attribute), 332
- use_paging (galaxy.webapps.galaxy.controllers.requests_admin.DataTransferGrid attribute), 333
- use_paging (galaxy.webapps.galaxy.controllers.requests_common.RequestsGrid attribute), 335
- use_paging (galaxy.webapps.reports.controllers.jobs.SpecifiedDateListGrid attribute), 343
- use_paging (galaxy.webapps.reports.controllers.sample_tracking.SpecifiedDateListGrid attribute), 345
- use_paging (galaxy.webapps.reports.controllers.workflows.SpecifiedDateListGrid attribute), 347
- use_paging (galaxy.webapps.galaxy.controllers.page.PageAllPublishedGrid attribute), 328
- use_paging (galaxy.webapps.galaxy.controllers.page.PageListGrid attribute), 330
- use_paging (galaxy.webapps.galaxy.controllers.user.UserOpenIDGrid attribute), 340
- use_paging (galaxy.model.User attribute), 148
- User (class in galaxy.model), 148
- UserSpecifiedDateListGrid (class in galaxy.webapps.galaxy.controllers.user), 338
- UserSpecifiedDateListGridWrapper (class in galaxy.model), 116
- user_assoc (galaxy.managers.roles.RoleManager attribute), 167
- user_can_do_run_as() (galaxy.managers.context.ProvidesUserContext method), 160
- user_can_purge (galaxy.model.Dataset attribute), 129
- user_list_usage() (galaxy.webapps.reports.controllers.users.Users method), 345
- user_list_dir (galaxy.managers.context.ProvidesUserContext attribute), 160
- user_list_default_permissions() (galaxy.security.GalaxyRBACAgent method), 179
- user_is_admin() (galaxy.managers.context.ProvidesUserContext method), 160
- user_list_grid (galaxy.web.base.controllers.admin.Admin method), 160
- user_list_grid (galaxy.webapps.galaxy.controllers.admin.AdminGalaxy method), 160
- user_list_grid (galaxy.webapps.galaxy.controllers.admin.AdminGalaxy attribute), 340
- user_openid_grid (galaxy.webapps.galaxy.controllers.user.User attribute), 340
- user_per_month() (galaxy.webapps.reports.controllers.jobs.Jobs method), 342
- user_per_month() (galaxy.webapps.reports.controllers.sample_tracking.SampleTracking method), 342
- user_per_month() (galaxy.webapps.reports.controllers.workflows.Workflow method), 347
- user_set_default_permissions() (galaxy.security.GalaxyRBACAgent method), 179
- user_set_default_permissions() (galaxy.security.RBACAgent method), 180
- user_type_grid (galaxy.managers.histories.HistoryManager attribute), 332

- attribute), 165
- user_system_pwent (galaxy.jobs.JobWrapper attribute), 116
- user_template_environment() (galaxy.model.User static method), 148
- UserAction (class in galaxy.model), 149
- UserAddress (class in galaxy.model), 149
- UserApiController (class in galaxy.webapps.galaxy.api.users), 38, 302
- UserGroupAssociation (class in galaxy.model), 149
- userless_histories() (galaxy.webapps.reports.controllers.system.SystemController method), 345
- UserListGrid (class in galaxy.webapps.galaxy.controllers.admin), 310
- UserListGrid.ActivatedColumn (class in galaxy.webapps.galaxy.controllers.admin), 310
- UserListGrid.EmailColumn (class in galaxy.webapps.galaxy.controllers.admin), 310
- UserListGrid.ExternalColumn (class in galaxy.webapps.galaxy.controllers.admin), 311
- UserListGrid.GroupsColumn (class in galaxy.webapps.galaxy.controllers.admin), 311
- UserListGrid.LastLoginColumn (class in galaxy.webapps.galaxy.controllers.admin), 311
- UserListGrid.RolesColumn (class in galaxy.webapps.galaxy.controllers.admin), 311
- UserListGrid.StatusColumn (class in galaxy.webapps.galaxy.controllers.admin), 311
- UserListGrid.TimeCreatedColumn (class in galaxy.webapps.galaxy.controllers.admin), 311
- UserListGrid.UserNameColumn (class in galaxy.webapps.galaxy.controllers.admin), 311
- UserOpenID (class in galaxy.model), 149
- UserOpenIDGrid (class in galaxy.webapps.galaxy.controllers.user), 340
- UserPreference (class in galaxy.model), 149
- UserQuotaAssociation (class in galaxy.model), 149
- UserRequestsGrid (class in galaxy.webapps.galaxy.controllers.requests), 332
- UserRoleAssociation (class in galaxy.model), 149
- Users (class in galaxy.webapps.reports.controllers.users), 345
- users() (galaxy.web.base.controllers.admin.Admin method), 252
- uses_tool_shed_dependencies() (galaxy.tools.deps.DependencyManager method), 195
- uses_tool_shed_dependencies() (galaxy.tools.deps.NullDependencyManager method), 195
- UsesAnnotations (class in galaxy.model.item_attrs), 152
- UsesExtendedMetadataMixin (class in galaxy.web.base.controller), 248
- UsesFormDefinitionsMixin (class in galaxy.web.base.controller), 249
- UsesItemRatings (class in galaxy.model.item_attrs), 152
- UsesLibraryMixin (class in galaxy.web.base.controller), 249
- UsesLibraryMixinItems (class in galaxy.web.base.controller), 249
- UsesQuotaMixin (class in galaxy.web.base.controller), 249
- UsesStoredWorkflowMixin (class in galaxy.web.base.controller), 249
- UsesTagsMixin (class in galaxy.web.base.controller), 250
- UsesVisualizationMixin (class in galaxy.web.base.controller), 250
- ## V
- v (galaxy.webapps.galaxy.api.requests.RequestsApiController attribute), 34, 298
- v (galaxy.webapps.galaxy.api.samples.SamplesApiController attribute), 34, 298
- VALID_FORMATS (galaxy_utils.sequence.fastq.fastqAggregator attribute), 352
- valid_gff3_phase (galaxy.datatypes.interval.Gff3 attribute), 67
- valid_gff3_strand (galaxy.datatypes.interval.Gff3 attribute), 67
- valid_operations (galaxy.model.Quota attribute), 144
- VALID_PRESET (galaxy.tools.parameters.sanitize.ToolParameterSanitizer attribute), 218
- valid_sequence_list (galaxy_utils.sequence.fastq.fastqCSSangerRead attribute), 353
- valid_sequence_list (galaxy_utils.sequence.sequence.SequencingRead attribute), 356
- validate() (galaxy.datatypes.data.Data method), 52
- validate() (galaxy.datatypes.genetics.GenomeGraphs method), 56
- validate() (galaxy.datatypes.interval.Interval method), 69
- validate() (galaxy.datatypes.metadata.MetadataParameter method), 72
- validate() (galaxy.model.DatasetCollection method), 130
- validate() (galaxy.tools.parameters.basic.DataCollectionToolParameter method), 199

validate() (galaxy.tools.parameters.basic.DataToolParameter.value_from_basic() (galaxy.tools.parameters.grouping.Group method), 199
 validate() (galaxy.tools.parameters.basic.ToolParameter.value_from_basic() (galaxy.tools.parameters.grouping.Repeat method), 208
 validate() (galaxy.tools.parameters.validation.DatasetOkValidator.value_from_basic() (galaxy.tools.parameters.grouping.Section method), 218
 validate() (galaxy.tools.parameters.validation.EmptyTextFieldValidator.value_from_basic() (galaxy.tools.parameters.grouping.UploadDataset method), 218
 validate() (galaxy.tools.parameters.validation.ExpressionValidator.value_to_basic() (galaxy.tools.parameters.basic.SelectToolParameter method), 219
 validate() (galaxy.tools.parameters.validation.InRangeValidator.value_to_basic() (galaxy.tools.parameters.basic.ToolParameter method), 219
 validate() (galaxy.tools.parameters.validation.LengthValidator.value_to_basic() (galaxy.tools.parameters.grouping.Conditional method), 220
 validate() (galaxy.tools.parameters.validation.MetadataInDataTableValidator.value_to_basic() (galaxy.tools.parameters.grouping.Group method), 220
 validate() (galaxy.tools.parameters.validation.MetadataInFileCollectionValidator.value_to_basic() (galaxy.tools.parameters.grouping.Repeat method), 220
 validate() (galaxy.tools.parameters.validation.MetadataValidator.value_to_basic() (galaxy.tools.parameters.grouping.Section method), 221
 validate() (galaxy.tools.parameters.validation.NoOptionsValidator.value_to_basic() (galaxy.tools.parameters.grouping.UploadDataset method), 221
 validate() (galaxy.tools.parameters.validation.RegexValidator.value_to_display_text() (galaxy.tools.parameters.basic.DataCollectionTool method), 221
 validate() (galaxy.tools.parameters.validation.UnspecifiedBuilderValidator.value_to_display_text() (galaxy.tools.parameters.basic.DataToolParameter method), 221
 validate() (galaxy.tools.parameters.validation.Validator.value_to_display_text() (galaxy.tools.parameters.basic.DrillDownSelectTool method), 221
 validate_email() (in module galaxy.security.validate_user_input), 181
 validate_in_users_and_groups() (galaxy.web.base.controller.BaseApiController method), 247
 validate_input_element_identifiers() (in module galaxy.managers.collections_util), 159
 validate_jsonrpc_request() (in module galaxy.util.json), 234
 validate_jsonrpc_response() (in module galaxy.util.json), 234
 validate_password() (in module galaxy.security.validate_user_input), 181
 validate_publicname() (in module galaxy.security.validate_user_input), 181
 ValidationError (class in galaxy.model), 149
 Validator (class in galaxy.tools.parameters.validation), 221
 value (galaxy_utils.sequence.transform.ColorSpaceConverter.verbose_name (galaxy.jobs.actions.post.ChangeDatatypeAction attribute), 357
 value_from_basic() (galaxy.tools.parameters.basic.SelectToolParameter method), 207
 value_from_basic() (galaxy.tools.parameters.basic.ToolParameter method), 208
 value_from_basic() (galaxy.tools.parameters.grouping.Conditional method), 211
 value_to_display_text() (galaxy.tools.parameters.grouping.Group method), 212
 value_to_display_text() (galaxy.tools.parameters.grouping.Repeat method), 212
 value_to_display_text() (galaxy.tools.parameters.grouping.Section method), 212
 value_to_display_text() (galaxy.tools.parameters.grouping.UploadDataset method), 213
 value_to_basic() (galaxy.tools.parameters.basic.SelectToolParameter method), 207
 value_to_basic() (galaxy.tools.parameters.basic.ToolParameter method), 208
 value_to_basic() (galaxy.tools.parameters.grouping.Conditional method), 211
 value_to_basic() (galaxy.tools.parameters.grouping.Group method), 212
 value_to_basic() (galaxy.tools.parameters.grouping.Repeat method), 212
 value_to_basic() (galaxy.tools.parameters.grouping.Section method), 212
 value_to_basic() (galaxy.tools.parameters.grouping.UploadDataset method), 213
 value_to_display_text() (galaxy.tools.parameters.basic.DataCollectionTool method), 199
 value_to_display_text() (galaxy.tools.parameters.basic.DataToolParameter method), 199
 value_to_display_text() (galaxy.tools.parameters.basic.DrillDownSelectTool method), 202
 value_to_display_text() (galaxy.tools.parameters.basic.SelectToolParameter method), 207
 value_to_display_text() (galaxy.tools.parameters.basic.ToolParameter method), 208
 ValueExternalServiceActionsGroupWhen (class in galaxy.external_services.service), 109
 values() (galaxy.util.bunch.Bunch method), 230
 values() (galaxy.util.odict.odict method), 235
 ValueToolOutputActionConditionalWhen (class in galaxy.tools.parameters.output), 216
 variablize() (galaxy.util.inflection.Base method), 232
 variablize() (galaxy.util.inflection.Inflector method), 233
 VariantCall (class in galaxy_utils.sequence.vcf), 357
 VariantCall33 (class in galaxy_utils.sequence.vcf), 357
 VariantCall40 (class in galaxy_utils.sequence.vcf), 357
 VariantCall41 (class in galaxy_utils.sequence.vcf), 357
 Vcf (class in galaxy.datatypes.tabular), 89
 Velvet (class in galaxy.datatypes.assembly), 44
 verbose_name (galaxy.jobs.actions.post.ChangeDatatypeAction attribute), 120
 verbose_name (galaxy.jobs.actions.post.ColumnSetAction attribute), 120
 verbose_name (galaxy.jobs.actions.post.DefaultJobAction attribute), 121
 verbose_name (galaxy.jobs.actions.post.DeleteDatasetAction attribute), 121

verbose_name (galaxy.jobs.actions.post.DeleteIntermediatesAction attribute), 121
 verbose_name (galaxy.jobs.actions.post.EmailAction attribute), 121
 verbose_name (galaxy.jobs.actions.post.HideDatasetAction attribute), 121
 verbose_name (galaxy.jobs.actions.post.RenameDatasetAction attribute), 121
 verbose_name (galaxy.jobs.actions.post.TagDatasetAction attribute), 122
 version (galaxy_utils.sequence.vcf.VariantCall attribute), 357
 version (galaxy_utils.sequence.vcf.VariantCall33 attribute), 357
 version (galaxy_utils.sequence.vcf.VariantCall40 attribute), 357
 version (galaxy_utils.sequence.vcf.VariantCall41 attribute), 357
 version (pkg_resources.Distribution attribute), 363
 version() (galaxy.webapps.galaxy.api.configuration.ConfigurationController method), 9, 274
 version_conflict() (galaxy.eggs.Egg method), 101
 version_path() (galaxy.jobs.ComputeEnvironment method), 112
 version_path() (galaxy.jobs.SharedComputeEnvironment method), 116
 VersionConflict, 364
 view() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321
 view_datatypes_registry() (galaxy.webapps.galaxy.controllers.admin.AdminController method), 306
 view_editable_request_type() (galaxy.webapps.galaxy.controllers.request_type.RequestType method), 330
 view_external_service() (galaxy.webapps.galaxy.controllers.external_service.ExternalService method), 317
 view_form_definition() (galaxy.webapps.galaxy.controllers.request_type.RequestType method), 330
 view_latest_form_definition() (galaxy.webapps.galaxy.controllers.forms.Forms method), 318
 view_multiple() (galaxy.webapps.galaxy.controllers.history.HistoryController method), 321
 view_request() (galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon method), 334
 view_request_history() (galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon method), 334
 view_request_type() (galaxy.webapps.galaxy.controllers.request_type.RequestType method), 331
 view_sample() (galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon method), 334
 view_sample_datasets() (galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon method), 334
 view_sample_history() (galaxy.webapps.galaxy.controllers.requests_common.RequestsCommon method), 334
 view_tool_data_tables() (galaxy.webapps.galaxy.controllers.admin.AdminController method), 306
 view_tool_metadata() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 314
 view_workflow() (galaxy.webapps.galaxy.controllers.admin_toolshed.AdminToolshed method), 314
 visible (galaxy.tools.parameters.basic.FTPFileToolParameter attribute), 202
 visible (galaxy.tools.parameters.basic.ToolParameter attribute), 208
 visible (galaxy.tools.parameters.grouping.Group attribute), 212
 visit_input_values() (in module galaxy.tools.parameters), 197
 visit_inputs() (galaxy.tools.parameters.grouping.Conditional method), 211
 visit_inputs() (galaxy.tools.parameters.grouping.Repeat method), 212
 visit_inputs() (galaxy.tools.parameters.grouping.Section method), 212
 visit_inputs() (galaxy.tools.parameters.grouping.UploadDataset method), 213
 visit_inputs() (galaxy.tools.Tool method), 187
 Visualization (class in galaxy.model), 149
 VisualizationAnnotationAssociation (class in galaxy.model), 149
 VisualizationRatingAssociation (class in galaxy.model), 149
 VisualizationRevision (class in galaxy.model), 149
 VisualizationsController (class in galaxy.webapps.galaxy.api.visualizations), 302
 VisualizationSelectionGrid (class in galaxy.webapps.galaxy.controllers.page), 330
 VisualizationRequestAssociation (class in galaxy.model), 150
 VisualizationUserShareAssociation (class in galaxy.model), 150
 viz_types (galaxy.web.base.controller.UsesVisualizationMixin attribute), 251
 W
 warning_for_elements (galaxy.model.DatasetCollection attribute), 130
 wake() (galaxy.jobs.transfer_manager.Sleeper method), 122
 warn() (in module galaxy.tools.util.galaxyops), 225
 WebApplication (class in galaxy.web.framework.base), 255
 welcome() (galaxy.webapps.galaxy.controllers.root.RootController method), 337

whoosh_search() (in module galaxy.model), 151
 galaxy.webapps.galaxy.controllers.library_common_workflow_step_connection (class in galaxy.model), 151
 327 WorkflowStepTagAssociation (class in galaxy.model), 151
 widget_fields_have_contents() (galaxy.web.base.controller.UsesFormDefinitionsWorkflowTagsController (class in galaxy.webapps.galaxy.api.item_tags), 20, method), 249 285
 Wiggle (class in galaxy.datatypes.interval), 69
 wiggle_dataprovider() (galaxy.datatypes.interval.Wiggle working_directory() (galaxy.jobs.ComputeEnvironment method), 70 method), 112
 wiggle_dict_dataprovider() (galaxy.datatypes.interval.Wiggle method), 116
 70 WorkingSet (class in pkg_resources), 360
 Workflow (class in galaxy.model), 150
 workflow_dict() (galaxy.webapps.galaxy.api.workflows.WorkflowRequestTagAssociation (class in galaxy.model), 150 method), 41, 305
 workflow_to_dict() (galaxy.managers.workflows.WorkflowContentsManager (class in galaxy.datatypes.metadata.FileParameter method), 168 method), 70
 WorkflowAnnotationsController (class in galaxy.webapps.galaxy.api.annotations), 8, 273
 WorkflowContentsManager (class in galaxy.managers.workflows), 168
 WorkflowField (class in galaxy.web.form_builder), 246
 WorkflowInvocation (class in galaxy.model), 150
 WorkflowInvocationStep (class in galaxy.model), 150
 WorkflowMappingField (class in galaxy.web.form_builder), 246
 WorkflowModule (class in galaxy.workflow.modules), 350
 WorkflowModuleFactory (class in galaxy.workflow.modules), 351
 WorkflowModuleInjector (class in galaxy.workflow.modules), 351
 WorkflowOutput (class in galaxy.model), 150
 WorkflowRequest (class in galaxy.model), 151
 WorkflowRequestInputParameter (class in galaxy.model), 151
 WorkflowRequestStepState (class in galaxy.model), 151
 WorkflowRequestToInputDatasetAssociation (class in galaxy.model), 151
 WorkflowRequestToInputDatasetCollectionAssociation (class in galaxy.model), 151
 Workflows (class in galaxy.webapps.reports.controllers.workflows), 347
 WorkflowsApiController (class in galaxy.webapps.galaxy.api.workflows), 39, 303
 WorkflowSelectionGrid (class in galaxy.webapps.galaxy.controllers.page), 330
 WorkflowsManager (class in galaxy.managers.workflows), 169
 WorkflowStep (class in galaxy.model), 151
 WorkflowStepAnnotationAssociation (class in galaxy.model), 151
 WorkflowStepConnection (class in galaxy.model), 151
 WorkflowStepTagAssociation (class in galaxy.model), 151
 WorkflowTagsController (class in galaxy.webapps.galaxy.api.item_tags), 20, 285
 working_directory() (galaxy.jobs.ComputeEnvironment method), 112
 working_directory() (galaxy.jobs.SharedComputeEnvironment method), 116
 WorkingSet (class in pkg_resources), 360
 WorkRequestTagAssociation (class in galaxy.model), 150
 wrap() (galaxy.datatypes.metadata.FileParameter method), 70
 wrap() (galaxy.datatypes.metadata.MetadataElementSpec method), 72
 wrap() (galaxy.datatypes.metadata.MetadataParameter method), 72
 wrap() (galaxy.datatypes.metadata.SelectParameter method), 73
 writable_files (galaxy.datatypes.data.Data attribute), 52
 write() (galaxy.datatypes.converters.interval_to_coverage.CoverageWriter method), 93
 write() (galaxy_utils.sequence.fasta.fastaWriter method), 352
 write() (galaxy_utils.sequence.fastq.fastqWriter method), 356
 write_data_to_file() (galaxy.visualization.data_providers.basic.BaseDataProvider method), 238
 write_from_stream() (galaxy.datatypes.data.Data method), 52
 write_from_stream() (galaxy.datatypes.data.Text method), 54
 write_from_stream() (galaxy.model.DatasetInstance method), 133
 write_log() (galaxy.web.framework.middleware.translogger.TransLogger method), 265
 write_split_files() (galaxy.datatypes.sequence.Sequence class method), 82
 wsgi_headeritems() (galaxy.web.framework.base.Response method), 255
 wsgi_status() (galaxy.web.framework.base.Response method), 255
 WSGIEnvironmentProperty (class in galaxy.web.framework.base), 255
 X
 Xbm (class in galaxy.datatypes.images), 63
 XForwardedHostMiddleware (class in galaxy.web.framework.middleware.xforwardedhost), 265
 Xlsx (class in galaxy.datatypes.binary), 49

`xml_dataprovider()` (`galaxy.datatypes.xml.GenericXml` method), 90
`xml_element_compare()` (in module `galaxy.util`), 229
`xml_element_list_compare()` (in module `galaxy.util`), 229
`xml_element_to_dict()` (in module `galaxy.util`), 229
`xml_string` (`galaxy.tools.data.TabularToolDataTable` attribute), 193
`xml_text()` (in module `galaxy.util`), 229
`xml_to_string()` (in module `galaxy.util`), 229
`Xpm` (class in `galaxy.datatypes.images`), 63

Y

`yield_lines()` (in module `pkg_resources`), 365

Z

`ZipBall` (class in `galaxy.util.streamball`), 236
`ZipProvider` (class in `pkg_resources`), 368